



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

Medium

Water

State

*Liquid***Operating data**☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	80.0	46.0	✗ 0.0	°C
p1	✗ 99.0	8.0	0.0	kgf/cm ² (g)
○ p2	✗ 98.0	7.0		kgf/cm ² (g)
● Δp	1.0	1.0	✗ 0.0	kgf/cm ²
Cv	261.82	263.7	✗	GPM(US)
○ qm	221,570.0	224,760.0		kg/h
● qv	227.0	227.0	✗ 0.0	m ³ /h
LpAe	35.2	46.9		dB(A)
	<i>Non-critical</i>	<i>Non-critical</i>		

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
ρ1	976.09	990.13	✗ 0.0	kg/m ³
ρ2	976.09	990.13		kg/m ³
● η1	0.35691	0.58577	✗ 0.0	mPa s
○ v1	0.36565	0.59161		mm ² /s
pv1	0.47414	0.10099	✗	bar(a)
tv1	309.59	174.68	99.974	°C
cF1	1,573.5	1,539.2	0.0	m/s

Pipe downstream of valve

Size class downstream of valve

NPS2

6"

Schedule downstream

SCH2

STD



Calculation Sheet

Valve configuration

Valve type	<i>Straight globe valve</i>
Trim type	<i>Contoured plug</i>
Flow direction	<i>FTC</i>
Valve performance class	<i>Multi stage valve</i>
Protection	<i>Non-hardened</i>
Low-noise design	<i>n.a.</i>

Valve data

Basic characteristic		<i>Linear</i>	
☐ Lift stopper			
Selected valve size	NPS	<i>6"</i>	
Pressure class	class ☐	<i>class 150</i>	
Maximum operating pressure	p,max ☐	<i>21.0</i>	bar(a)
Valve modifier (Cv/Cv100 = 0.75)	FL ²	<i>0.907</i>	-
Valve modifier (Cv/Cv100 = 0.75)	Kc	<i>0.863</i>	-
Cavitation modifier (Cv/Cv100 = 0.75)	xFz	<i>0.475</i>	-
Valve style modifier (Cv/Cv100 = 1)	Fd	<i>0.41</i>	-

Load-dependent values

	Maximum flow	Mean flow	Minimum flow	
u2	<i>3.4567</i>	<i>3.4567</i>		m/s
LpAe	<i>35.2</i>	<i>46.9</i>		dB(A)
Ri	<i>0.0</i>	<i>0.0</i>		-

Noise calculation

Calculation standard (noise, liquid)	<i>IEC 60534-8-4 (2015)</i>
--------------------------------------	-----------------------------

Noise prediction data

Low-noise design		<i>n.a.</i>	
Sound velocity	cF1	<i>1,573.5</i>	m/s
Pressure level	LA1	<i>145.0</i>	dB
Sound pressure level	Lpi	<i>145.0</i>	dB
Transmission loss	TL	<i>-93.6</i>	dB





Calculation Sheet

Noise prediction data (continued)

Sound power level (A-weighted)	LwAe	53.2	dB(A)
Sound pressure level of valve (A-weighted)	LpAe	35.2	dB(A)

Comments:

Reliability index - Ri

Recommended solution: Standard valve

Reliability index - Ri,op2

Recommended solution: Standard valve

Legend

✖ Errors

