



Calculation Sheet

Calculation header

Identifier

*New calculation (1)***Medium selection and state**

Medium

Fuel Gas

State

Gaseous

Gas

Gas, dry (Standard conditions)

Standard conditions

*0°C, 1013.25 mbar***Operating data**☐ Safety-related application

	Maximum flow	Mean flow	Minimum flow	
t1	<i>20.0</i>	<i>20.0</i>		°C
p1	<i>0.75</i>	<i>0.6</i>		kgf/cm ² (g)

Fluid operating data

	Maximum flow	Mean flow	Minimum flow	
○ η1	<i>0.01088</i>	<i>0.01088</i>	<i>0.0</i>	mPa s
cF1	<i>524.56</i>	<i>524.56</i>	<i>506.35</i>	m/s
κ	<i>1.3456</i>	<i>1.346</i>	<i>0.0</i>	-

Pipe downstream of valve

Size class downstream of valve	NPS2	<i>2"</i>
Schedule downstream	SCH2	<i>STD</i>

Valve configuration

Valve type	<i>Straight globe valve</i>
Trim type	<i>Cage trim</i>
Flow direction	<i>FTO</i>
Valve performance class	<i>Heavy duty valve</i>
Protection	<i>Hardened seat/plug</i>
Low-noise design	<i>n.a.</i>



Calculation Sheet

Valve data

Basic characteristic

Equal percentage

Nominal flow coefficient

Cv100

30.0

GPM(US)

☐ Lift stopper

Selected valve size

NPS

2"

Pressure class

class

class 600

Maximum operating pressure

p,max

105.0

bar(a)

Valve modifier (Cv/Cv100 = 0.75)

FL²*0.838*

-

Valve modifier (Cv/Cv100 = 0.75)

xT

0.72

-

Valve style modifier (Cv/Cv100 = 1)

Fd

0.41

-

Load-dependent values**Noise calculation**

Calculation standard (noise, gas)

*IEC 60534-8-3 (2010)***Noise prediction data**

Low-noise design

n.a.