

ADO.NET Connected Architecture

Q1. What are the objects used to execute SQL queries or Stored Procedures against the data Source?

Ans: Command Object and Connection Object

Q2. After Execution of a query where will the result stored?

Ans: DataReader Object

Q3. What is the method that we use to retrieve the rows from the table?

Ans: DataReader.read()

Q4. What is the purpose of connection in connected architecture?

Ans: Connection class used to establish the connection between front end and back end.

Explanation: In Connection Oriented Data Access Architecture the application makes a connection to the Data Source and then interact with it through SQL requests using the same connection. In these cases the application stays connected to the database system even when it is not using any Database Operations.

Q5. What is the flow of connection in connected architecture?

Ans: Open Connection

Execute Command

Process Data in Reader

Close Reader

Close Connection

Explanation: In connection-oriented architecture the Database gets connected to the front end then the command passes the query to the server from back end and on the server the result which has been generated. The result which has been generated will be read by DataReader.

Q6. What are the classes that contains ADO.NET?

Ans:

Connection

Command

DataReader

DataAdapter

DataSet

Q7. What is DataSet Object?

A) It is set to be collection of data with a tabular column representation.

Q8. What is Connection Oriented Data Access Architecture? What are the disadvantages?

EXPLANATION:

In Connection Oriented Data Access Architecture the application makes a connection to the Data Source and then interact with it through SQL requests using the same connection. In these cases the application stays connected to the database system even when it is not using any Database Operations.

ADO.Net solves this problem by introduces a new component called Dataset. The DataSet is the central component in the ADO.NET Disconnected Data Access Architecture. A DataSet is an in-memory data store that can hold multiple tables at the same time. DataSets only hold data and do not interact with a Data Source. One of the key characteristics of the DataSet is that it has no knowledge of the underlying Data Source that might have been used to populate it.

```
DataSet ds = new DataSet();
```

In Connection Oriented Data Access, when you read data from a database by using a DataReader object, an open connection must be maintained between your application and the Data Source. Unlike the DataReader, the DataSet is not connected directly to a Data Source through a Connection object when you populate it. It is the DataAdapter that manages connections between Data Source and Dataset by fill the data from Data Source to the Dataset and giving a disconnected behavior to the Dataset. The DataAdapter acts as a bridge between the Connected and Disconnected Objects.

```
SqlDataAdapter adapter = new SqlDataAdapter("sql", "connection");
```

```
DataSet ds = new DataSet();
```

```
adapter.Fill(ds, "Src Table");
```

By keeping connections open for only a minimum period of time, ADO .NET conserves system resources and provides maximum security for databases and also has less impact on system performance.

Q 9. DATAREADER IN CONNECTED ARCHITECTURE

EXPLANATION: You can use the ADO.NET DataReader to retrieve a read-only, forward-only stream of data from a database. Results are returned as the query executes, and are stored in the network buffer on the client until you request them using the Read method of the DataReader. Using the DataReader can increase application performance both by retrieving data as soon as it is available, and (by default) storing only one row at a time in memory, reducing system overhead.

Q10. What are Stored Procedures?

Ans. A stored procedure is a reusable sub routine stored in a database. A stored procedure can be called by simply passing the stored procedure name followed by parameter arguments as an SQL statement. But you can use the Parameters collection of the ADO.NET Command object which enables you to more explicitly define stored procedure parameters as well as to access output parameters and return values. To call a stored procedure, set the **CommandType** of the Command object to **StoredProcedure**.

Q11. How to execute Stored Procedures?

Ans. A Stored Procedure written in SQL server can be called and executed through ADO.NET

The SQL command object is used to execute Stored Procedures

```
Example: sql Command cmd = new SqlCommand("Query_Stud",con);  
cmd.CommandType = CommandType.StoredProcedure;
```

Q12. What are the various SQL Command constructors used in a connected Architecture?

Ans.- There are 4 types of SQL Command Constructors used .They are as follows :

- a. SqlCommand()
- b. SqlCommand(String CommandText)
- c. SqlCommand(String CommandText,SqlConnection con)
- d. SqlCommand(String CommandText, SqlConnection con,SqlTransaction trans)

SqlCommand() creates a new SqlCommand with no properties set and no associated connection.

SqlCommand(String CommandText) creates a new SqlCommand with the CommandText property set but no associated connection.

SqlCommand(String CommandText,SqlConnection con) creates a new SqlCommand with the CommandText property set and the specified SqlConnection as the Connection property.

SqlCommand(String CommandText, SqlConnection con,SqlTransaction trans) creates a new SqlCommand with the CommandText property set, the specified SqlConnection as the Connection property and SQLTransaction to for the command to execute in.

Q13. What are the functions of the command classes OracleCommand and SqlCommand?

Ans. The command classes (OracleCommand and SqlCommand) are used to execute commands on a data source across a connection. Once a connection is established, a command can be used to execute a SQL statement or stored procedure. The SqlCommand represents a TransactSQL statement or stored procedure to execute against a SQL Server database. The SqlCommand class is part of the System.Data.SqlClient namespace. When an instance of SqlCommand is created, the read/write properties are set to their initial values.

Q14. What is a DataReader object?

The DataReader object helps in retrieving the data from a database in a forward-only, read-only mode. The base class for all the DataReader objects is the DbDataReader class.The DataReader object is returned as a result of calling the ExecuteReader() method of the Command object. The DataReader object enables faster retrieval of data from databases and enhances the performance of .NET applications by providing rapid data access speed. However, it is less preferred as compared to the DataAdapter object because the DataReader object needs an Open connection till it completes reading all the rows of the specified table.

Q15. What is the use of the Connection object?

The Connection object is used to connect your application to a specific data source by providing the required authentication information in connection string. The connection object is used according to the type of the data source. For example, the OleDbConnection object is used with an OLE-DB provider and the SqlConnection object is used with an MS SQL Server.

Disconnected Data Architecture

1.What is SQL Data Adapter?

The SqlDataAdapter uses the Fill method, which changes the data in the DataSet to match the data in the data source, and the Update method, which changes the data in the data source to match the data in the DataSet, using the appropriate Transact-

SQL statements against the data source. SqlDataAdapter fills a DataSet , it creates the necessary tables and columns for the returned data if they do not already exist.

2. What does the Update and Fill method of Data Adapter do?

The DataAdapter's Fill and Update method automatically opens the connection, executes, and closes the connection

3. What is Data Set?

The DataSet is a memory-resident representation of data that provides consistent relational programming model regardless of the source of the data it contains. A DataSet represents a complete set of data including the tables that contain columns, rows and constrain the data, as well as the relationships between the tables. It is disconnected from the data source.

4. What are the various members exposed by Data Set?

DataSetName - Gets or sets the name of the current DataSet

EnforceConstraints – Gets or sets a value indicating whether constraint rules are followed when attempting any update operation

HasErrors – Indicates whether there are errors in any of the rows in any of the tables of this DataSet

Relations – Retrieves the collection of relations that link tables and allow navigation from parent tables to child tables

Tables - Retrieves the collection of tables contained in the DataSet.

AcceptChanges() – Commits all the changes made to this DataSet since it was loaded or the last time AcceptChanges was called

Clear()- clears the DataSet of any data by removing all rows in all tables.

GetChanges()- Retrieves a copy of the DataSet containing all changes made to it since it was last loaded, or since AcceptChanges was called.

HasChanges()- Retrieves a value indicating whether the DataSet has changes, including new, deleted, or modified rows

RejectChanges()- Rolls back all the changes made to the DataSet since it was created, or since the last time DataSet.AcceptChanges was called

Merge() – Merges this DataSet with a specified DataSet.

Reset()- Resets the DataSet to its original state. Subclasses should override Reset to restore a DataSet to its original state.

5. When do we use Data Set?

DataSet can be used in the application whenever discrete table of results is being navigated and also if the application manipulates data from different sources like a relational database or XML file. Additionally, caching the data using the DataSet improves performance for tasks such as Sorting, Filtering.

6. What is Typed DataSet?

It is a collection of classes that inherit from DataSet, DataTable and DataRow Classes with additional properties, methods and events based on DataSet Schema. It allows developer to work with values, access parent and child records, and helps us find rows and handle null column values.

7. What is Untyped DataSet?

It doesn't have corresponding built-in-schema. It has tables, columns and so on which are exposed as collection.

DataSet's structure can be exported after creating tables and elements manually.

8. When do you use DataSet?

DataSet can be used in the application whenever discrete table of results is being navigated and also if the application manipulates data from different sources like a relational database or XML file.

Additionally, caching the data using the DataSet improves performance for tasks such as Sorting, Filtering.

To include type checking at design time use Typed DataSet. Apart from this in .Net environment statement completion is also supported when you work with Typed DataSet.

9. Method to refresh Data in DataSet? How?

DataAdapter.Fill method. This method matches new rows based on primary keys and applies corresponding changes from the server, if a Primary Key is defined for the DataTable.

If the Primary Key is not defined, then leads to duplicate rows.

10. Members of Data Table?

*ChildRelations

*Columns

- *Constraints
- *DataSet
- *ParentRelations
- *PrimaryKey
- *Rows
- *Tablename
- *NewRow()
- *Select().

11. Features of DataColumn?

- *Type of Data to store
- *Length of the column
- *Whether the data can be modified
- *Whether the data is unique
- *Can accept null values
- *Automated values
- *Values calculated based on the expressions.

12. Purpose of the DataRow?

It maintains RowState property that is used by ADO.NET to track the changes that have been made to a DataRow and allows to identify the rows which are modified.

13. What is RowState?

It is a property to track changes that have been made to DataRow while it is disconnected to be updated back to the data source. It has two versions :

- a) Original version - contains values that are loaded into the row.
- b) Current version - it contains values that are modified.

14. What is foreignKey constraint?

It enforces rules how update and deletes to related tables are propagated and they follow:

- *Cascade - Deletes or updates related rows
- *SetNull - Set values in related rows to DBNull
- *SetDefault - Set values in related rows to the default value.
- *None - Take no action on related rows.

15. What is the difference between data reader and data set?

DATA READER:

1. Used in a connected architecture
2. Provides better performance
3. DataReader object has read-only access
4. DataReader object supports a single table based on a single SQL query of one database.
5. A DataReader object is bound to a single control.
6. A DataReader object has faster access to data.
7. A DataReader object must be manually coded.
8. We can't create a relation in a data reader.
9. Whereas a DataReader doesn't support data reader communicates with the command object.
10. DataReader cannot modify data.

DATASET

1. Used in a disconnected architecture.
2. Provides lower performance.
3. A DataSet object has read/write access.
4. A DataSet object supports multiple tables from various databases.
5. A DataSet object is bound to multiple controls.

- 6. A DataSet object has slower access to data.
- 7. A DataSet object is supported by Visual Studio tools.
- 8. We can create relations in a dataset.
- 9. A Dataset supports integration with XML Dataset communicates with the Data Adapter only.
- 10. A DataSet can modify data.

16. Disadvantages of disconnected architecture?

- a.Data is not always uptodate.
- b.Change conflicts can occur and must be changed.

17. What is a command object?

The command object is one of the basic components of ADO .NET.

The Command Object uses the connection object to execute SQL queries.

The queries can be in the form of Inline text, Stored Procedures or direct Table access.

An important feature of Command object is that it can be used to execute queries and Stored Procedures with Parameters.

If a select query is issued, the result set it returns is usually stored in either a DataSet or a DataReader object.

Connection **Read/Write** The SqlConnection object that is used by the command object to execute SQL queries or Stored Procedure.

CommandTextRead/Write Represents the T-SQL Statement or the name of the Stored Procedure.

CommandType **Read/Write** This property indicates how the CommandText property should be interpreted. The possible values are:

- 1. Text (T-SQL Statement)
- 2. StoredProcedure (Stored Procedure Name)
- 3. TableDirect.

18. What is DataAdapter?

Answer: A DataAdapter bridges the gap between the disconnected DataTable objects and the physical data source.

The SqlDataAdapter is capable of executing a SELECT, DELETE and UPDATE statement on a data source as well as extracting

input from the result set into a DataTable object.

The SqlDataAdapter class provides a method called Fill() to copy the result set into the DataTable.

19. What are the properties of data adapter?

SelectCommand	This command executed to fill in a Data Table with the result set.
InsertCommand	Executed to insert a new row to the SQL database.
UpdateCommand	Executed to update an existing record on the SQL database.
DeleteCommand	Executed to delete an existing record on the SQL database.

20. Describe the Disconnected Architecture of Ado.net's Data Access Model?

ADO.NET maintains a disconnected database access model, which means, the application never remains connected constantly to the data source.

Any changes and operations done on the data are saved in a local copy (dataset) that acts as a data source.

Whenever, the connection to the server is re-established, these changes are sent back to the server,

in which these changes are saved in the actual database or data source.

LINQ & EF

1. What is LINQ , when it was introduced and what are the advantages of LINQ?

LINQ Stands for Language Integrated Query.

It was introduced from .NET framework 3.5 and continued as a part of .Net framework 4.0 and 4.5.

- Integrate Better with programming languages
- Improves productivity through intellisense in Visual studio
- Interact with data as objects.
- By creating a common querying language in LINQ, the developer is free from having to master independent data programmability technologies (for example: Xpath, Xquery, T/SQL). Instead, LINQ offers the developer a consistent way to query data.

2.Explain the layer of LINQ Architecture.

1. The top most layer consist of language extension which show all the languages which can use LINQ including C# , VB and other language which are the part of .Net Framework
2. The second layer consist of .NET LINQ
3. The third layer consist of LINQ Enabled Data source which specifies different data source on which LINQ can be used. LINQ can be use with Objects, SQL, Dataset and XML.

3. What are different flavors of LINQ?

LINQ to Objects

LINQ to ADO.NET

LINQ to XML

4.What is PLINQ?

Parallel LINQ (PLINQ) is a parallel implementation of the LINQ pattern. The primary difference is that PLINQ attempts to make full use of all the processors on the system. It does this by partitioning the data source into segments, and then executing the query on each segment on separate worker threads in parallel on multiple processors. In many cases, parallel execution means that the query runs significantly faster. Through parallel execution, PLINQ can achieve significant performance improvements over legacy code for certain kinds of queries, often just by adding the (AsParallel) query operation to the data source.

5. In which Namespaces API for different flavours of LINQ is defined?

Components	namespaces
LINQ to Objects	System.Linq namespaces inside System.Core.dll
LINQ to ADO.NET	System.Data.Linq namespace
LINQ to XML	System.XML.Linq namespace

6. What are the basic action required for LINQ query operations ?

All LINQ Query consists of three distinct actions

1. Obtain the data source
2. Create the query
3. Execute the query

7. write the syntax of a Basic LINQ Query.

from <range variable> in <collection>

<filter, joining, grouping, aggregate operators etc><Lambda expression>

<select or groupBy operator><formulate the result>

Every LINQ query begins with a from clause ends with a select query or group. In

between can be use filtering , joining , grouping etc on the data.

8. What are the basic query operator in LINQ?

Filtering Operators

Sorting Operators

projection Operators

Aggregation

Concatenation operator

Grouping Operators

Conversions

9. What does filtering operator do explain with example.

It filter a sequence based on a predicate function Suppose that you have to list the names and cities of customers from Italy. To filter a set of items, you can use the Where operator, which is also called a “restriction operator” because it restricts a set of items.

10. What are projection operator and what is difference between them?

Select Operator

- The Select operator performs a projection over a sequence.
- When the object returned by Select is enumerated, it enumerates the source sequence. Subsequently, it yields the results of evaluating the select or function for each element.

The first argument of the selector function represents the element to process.

The second argument, if present, represents the zero-based index of the element within the source sequence.

SelectMany Operator

The SelectMany operator performs a projection over a sequence. This operator is similar to Select because it allows us to define the elements that have to be picked up from a sequence. The difference is in the return type.

With the `IEnumerable<S>` type returned by the selector parameter of SelectMany, it is possible to concatenate many projection operations together. This can be done either on different sequences or starting from the result of a previous query.

11. What are sorting operators and describe them

OrderBy and OrderByDescending

The OrderBy sort the data in ascending order and OrderByDescending operator inverts the ordering.

ThenBy and ThenByDescending

OrderBy allows us to specify only one ordering key. Hence we have to use either ThenBy or ThenByDescending to concatenate ordering-key values.

Reverse

This method simply returns a new sequence with elements in a reverse ordering of the source sequence. REVERSE simply reverses the items in the collection.

12. What does group by operator do?

The GroupBy operator groups elements of a sequence based on a given selector function.

13. What is concatenation operator do and write the syntax

This operator concatenates two sequences. The resulting `IEnumerable<T>` type is the concatenation of the first and second sequences specified as a parameter.

number and morenumbers are two different sequences

```
var query=numbers.Concat(morenumbers);
```

14.What are set operators and describe them

Distinct:

- This operator is similar to the DISTINCT keyword used in SQL. It eliminates the duplicates from a sequence.
- When the code processes the query, it enumerates the element of the sequence, and stores into an IEnumerable<T> type. It is done for each element that has not been previously stored.
- The Distinct operator selects unique values from the sequence.

Except:

- This Operator Produces the set difference of two sequences by using the default equality comparer to compare values.

Intersect:

- This operator returns a sequence made by common elements of two different sequences.
- The Intersect Method is used to retrieve common elements in two sequences

Union:

- This operator returns a new sequence formed by uniting the two different sequences.

15.What are Types of Conversion operator and explain them.

- This operator produces a new IEnumerable<T> type composed of only the element of the specified type

OfType:

- The OfType Searches for the specified type T in the Sequence

ToArray:

- This operator returns an array composed of the elements of the source sequence.