

Deep Learning Project 1

Dutt Salveen Singh, Patryk Prusak

March 26, 2024

Warsaw University of Technology

Table of contents

1. Introduction

2. Experiments

3. Results

Introduction

Problem

Test and compare different network architectures (preferably CNN) with different hyperparameters and data augmentation techniques on a CINIC-10 dataset[1].

Architectures

- MobileNetv3
- EfficientNet

Hyperparameters

- For the hyper-parameters related to the training process we chose batch size, learning rate, and number of epochs
- For the hyper-parameters related to Regularization we decided to use L2 Regularization (Weight Decay) and Dropout Rate

Data Augmentation


- Basic augmentation: rotation, flipping, zoom, brightness change
- Advanced augmentation: random erasing

Experiments


Procedure

1. Choose a starting parameter X (such as batch size) and answer the following question: given a set of basic (commonly seen in literature) parameter values (such as a hyperparameter or data augmentation technique) excluding parameter X , what value for X results in best accuracy?
2. Choose the best-found value for parameter X and replace the parameter's basic initial value, then choose a different parameter X and start from 1.


EfficientNet




EfficientNet




EfficientNet




EfficientNet




EfficientNet




EfficientNet




MobileNet




MobileNet




MobileNet




MobileNet




MobileNet






Results


EfficientNet




EfficientNet




EfficientNet




MobileNet



MobileNet



MobileNet



Thank You

References



Cinic-10 dataset.