

//cyclic code

```
clc;
clear all;
close all;
n=input('Enter the value of n: ');
k=input('Enter the value of k: ');
m=n-k;
G=cyclpoly(n,k,'max')
poly2sym(G)
d1=[1 0 0 0];
poly2sym(d1)
c1=poly2sym(d1)*poly2sym(G)
d2=[0 1 0 0];
poly2sym(d2)
c2=poly2sym(d2)*poly2sym(G)
d3=[0 0 1 0];
poly2sym(d3)
c3=poly2sym(d3)*poly2sym(G)
d4=[0 0 0 1];
poly2sym(d4)
c4=poly2sym(d4)*poly2sym(G)
s=[c1;c2;c3;c4]
d=[d1;d2;d3;d4]
c=d*s
parmat=hammgen(m)
trt=syndtable(parmat)

recd=[0 1 0 1 0 0 0]
syndrome=rem(recd*parmat',2)
syndrome_de=bi2de(syndrome,'left-msb')
disp([syndrome,'left-msb'])
disp(['Syndrome=',num2str(syndrome_de), '(decimal) ',num2str(syndrome_de),'(binary)'])
Error=trt(1+syndrome_de,:)
corrctedcode= rem(Error+recd,2)
recd=[1 1 0 1 1 0 1]
syndrome=rem(recd*parmat',2)
syndrome_de=bi2de(syndrome,'left-msb');
disp(['Syndrome=',num2str(syndrome_de), '(decimal)', num2str(syndrome_de),'(binary)'])
Error=trt(1+syndrome_de,:)
correctedcode=rem(Error+recd,2)
```

//linear block code

```
clc;
clear all;
k=input('Enter the length of msg word:');
n=input('Enter the length of codeword:');
p=input('Enter the parity matrix:');
G=[eye(k);p];m=input('Enter the length of msg word:');

H=[eye(n-k) p']
dtable=syndtable(H)
R=input('Enter the received code word');
%S=R*H'
S_B=rem(R*H',2)
S_D=bi2de(S_B, 'left-msb')
if(S_D==0)
    disp('The recieved codeword is valid:')
else
    disp('The corrected codeword is invalid:')
E=dtable(S_D+1, :)
%CC=R+E
disp('The corrected codeword is: ')
cc=rem(R+E, 2)
msg=cc(1:k)
end
```

//mary psk mpsk

```
clc;
clear all;
M=input('Number_Symbols=');
x=0:M-1;
N=1;
OFF=0;
z=pskmod(x,M);
figure(1)
scatterplot(z,N,OFF,"r+");
N=1;
OFF=0;
y=qammod(x,M);
figure(2)
scatterplot(y,N,OFF,"bo");
```

// bpsk receiver

```
clc;
close all;
data_bits=10000;
b=(randn(1,data_bits) > 5);
s=2*b-1;
SNRdB=0:9;
for(k=1:length(SNRdB))
y=s+awgn(s,SNRdB(k));
error=0;
for(c=1:1:data_bits)
if (y(c)>0&& s(c)==-1) || (y(c)<0&&s(c)==1)
error=error+1;
end
end
BER(k)=error/data_bits;
end
figure(1);
semilogy(SNRdB, BER, 'r', 'Linewidth', 2);
grid on;
hold on;
SNR=10.^(SNRdB/10);
BER_thBPSK=(1/2)*erfc(sqrt(SNR));
semilogy(SNRdB,BER_thBPSK,'k', 'linewidth', 2);
BER_thQPSK=erfc(sqrt(SNR));
semilogy (SNRdB, BER_thQPSK, 'b', 'LineWidth',2);
legend('PR-SNR','BPSK','QPSK')
```

```
//random process
```

```
m = 0;
sd = 1;
x = -6:0.1:6;
y = normpdf(x, m, sd);
figure(1)
subplot(2, 3, 1);
plot(x, y);
axis([-6 6 0 0.5]);
title('CASE-1, mean=0, sd=1');
xlabel('x values --->');
ylabel('pdf --->');
grid on;

m = -1;
sd = 1;
x = -6:0.1:6;
y = normpdf(x, m, sd);
figure(1)
subplot(2, 3, 2);
plot(x, y);
axis([-6 6 0 0.5]);
title('CASE-2, mean=-1, sd=1');
xlabel('x values --->');
ylabel('pdf --->');
grid on;
```

```
m = 1;
sd = 1;
x = -6:0.1:6;
y = normpdf(x, m, sd);
figure(1)
subplot(2, 3, 3);
plot(x, y);
axis([-6 6 0 0.5]);
title('CASE-3, mean=1, sd=1');
xlabel('x values --->');
ylabel('pdf --->');
grid on;
```