

# Bibliography

Objectif Nux. App inventor : Premire application - orientation du smartphone, april 2012. URL <http://objnux.1s.fr/index.php?post/2012/04/29/App-Inventor-%3A-Premier-programme>. Accessed: 20.04.17.



---

WORKSHOP 7 :

# Embedded Systems Engineering IoT Applications Prototyping

Team B: SmartCart  
Date: 21st April 2017  
Lecturer: Dionysios Satikidis, MSc

---

Team members:

Project leader:	1644604	Timo Acquistapace
Developer:	1644612	Wojciech Lesnianski
Data-Analyst:	1644609	Markus Just
Documentation-Manager:	1644625	Simon Schneider

Deadline 24<sup>th</sup> April, 2017

---

# Contents

<b>1</b>	<b>Smart Cart - A smarter Way of Shopping</b>	<b>1</b>
1.1	Introduction . . . . .	2
1.1.1	Initial Idea of Smart Cart . . . . .	2
1.1.2	Change of Scope and final Idea of Smart Cart . . . . .	2
1.2	System Analysis . . . . .	3
1.2.1	Use Cases . . . . .	3
1.2.2	Relations between the captured Gestures and the used Sensors . . . . .	4
1.2.3	Application Context . . . . .	4
1.2.4	Finite State Machine . . . . .	5
1.3	Mathematical Basics of Gesture Recognition . . . . .	6
1.3.1	Terminology of the possible Rotations . . . . .	6
1.3.2	Acceleration depending on Pitch . . . . .	7
1.3.3	Acceleration depending on Roll . . . . .	8
1.3.4	Acceleration depending on Azimuth . . . . .	9
1.3.5	Final Equations for the Acceleration Values . . . . .	9
1.4	Recognition of Gestures . . . . .	12

## List of Abbreviations

## **Abstract**

Das vorliegende Dokument beschreibt das Produkt SmartCart des Teams IoT-Designers. Das Ziel der Anwendung ist es einen smarter Way of Shopping zu ermöglichen. Die Anwendung offers the possibility of easily marking items as added to the cart and the navigating through a list via gestures, um den User beim Einkauf zu unterstützen und entlasten. Therefore, the recognition of gestures is done via the built-in acceleration sensor.

# Chapter 1

## Smart Cart - A smarter Way of Shopping

In the following sections, the idea and implementation of SmartCart – an Android application that will simplify your shopping experience – will be exposed. The application was created in the course of the workshop “IoT Applications Prototyping” by the team IoT-Designers:

Timo  
Acquistapace




Wojciech  
Lesnianski



Markus  
Just



Simon  
Schneider



Project Leader

Developer

Data Analyst

Documentation  
Manager

## 1.1 Introduction

Since the idea of SmartCart evolved during the workshop, this section firstly introduces the initial product idea of SmartCart and the change of scope that project went through. Later on, the architecture and the system's context as well as the used state machine and its evolution are described. The following sections focus on the recognition of gestures. For this purpose, the mathematical basics that are necessary to recognize gestures are derived and the gestures that are used to control the system are introduced.

### 1.1.1 Initial Idea of SmartCart

The first concept of SmartCart was to offer its user the possibility to add items to a shopping list and to get this shopping list ordered automatically as the user enters a supermarket. The entered grocery is determined with the help of the Microsoft Here API. Based on the knowledge of the accessed shop and the ordering of its departments, the items that were previously added to the shopping list, should be ordered.

### 1.1.2 Change of Scope and final Idea of SmartCart

Even though the initial idea of SmartCart would have been a very helpful application to the user, it is strongly based on the collaboration with the operators of the supported supermarkets. This is especially true for the data acquisition regarding the offered products and the available departments of a supermarket. Therefore, the initial scope of the application was changed towards an application that is less dependent on master data.

The revised concept of SmartCart focusses more on the interaction of the user and the application. It omits the features of recognising a shop that is entered and ordering the list of shopping items according to the recognised shop. Instead, the application should offer the possibility of easily marking an item as added to the cart and of navigating through the list via gestures. The recognition of gestures is done via the built-in sensors for acceleration and the gyroscope.




Figure 1.2.1: Overview of the System's Use Cases

Even the initial idea was discarded during the workshop for the mentioned reasons, the focus that is now put on the user interaction might nevertheless support the initial idea.

## 1.2 System Analysis

The upfront steps that were taken to create a shared understanding and to examine possible solutions in building the application are shortly presented in the current section.

### 1.2.1 Use Cases

SmartCart in its final scope addresses two main use cases: the use case of creating a shopping list and adding items to it as well as the process of going shopping itself (see 1.2.1). The use case “Go shopping” implements the main user interaction that consists of switching the next item to buy and of marking an item of the shopping list as ‘added to cart’. This interaction takes place via gestures made by the user with its smartphone that are detected by the SmartCart application.




Figure 1.2.2: Data Model of the User Gestures to recognize

### 1.2.2 Relations between the captured Gestures and the used Sensors

Figure 1.3.1 shows a model of how the smartphone, the sensors and the gestures that should be recognized are related to each other. The acceleration sensor provides information about the smartphone's speed-up along its coordinate axes. In the most cases, these axes are not aligned with the standard x-y-z axes because of the smartphone's orientation. Since the orientation affects the measured acceleration values, it has to be taken into account when recognizing the user's gestures.

### 1.2.3 Application Context

The context of the application can be retrieved from figure 1.2.3. The inputs are the values of the accelerometer  $a_x$ ,  $a_y$  and  $a_z$  as well as the angles *azimuth*, *pitch* and *roll* that determine the smartphone's orientation. The current state and any other information of the application are visualized on the smartphone's display.




Figure 1.2.3: Context of the Application to develop




Figure 1.2.4: First Finite State Machine

## 1.2.4 Finite State Machine

hier war noch nicht sicher welche gesten berhaupt verwendet werden und bla bla bla (vllt einfach ner murks state machine machen weil die vom dio der letzte rotz ist und absolut flasch)

### First State Machine

auf jedenfall zuerst diese kackendreck state machin richtig falsch machen aber dennoch wenigstens halbwegs sinnvoll

### Evolutioned State Machine

auch diese self bergnge erklren... also alles darf passieren uznd er bleibt in diesem state




Figure 1.2.5: Evolutioned Finite State Machine

## 1.3 Mathematical Basics of Gesture Recognition

The recognition of gestures is based on measured acceleration values. These values depend, as it was already depicted in section 1.2.2, on the orientation of the smartphone. The mathematical relation of the measured acceleration values and the smartphone's orientation will be derived in this chapter. At first, the impact the smartphone being rotated along one of its axes is investigated in isolation. Afterwards, the results are combined and the final equation for each of the acceleration values is set up.

### 1.3.1 Terminology of the possible Rotations

There exist three different possible rotations that are measured by the gyroscope sensor:




Figure 1.3.1: Possibilities of rotating a Smartphone, see Objectif Nux [2012]

- **Pitch**

The angle of a rotation around the x-axis is called pitch. In the following equations,  $\alpha$  will be used to describe the value of pitch that is retrieved from the gyroscope.

- **Roll**

The angle of a rotation around the y-axis is called roll. In the following equations,  $\beta$  will be used to describe the value of roll that is retrieved from the gyroscope.

- **Azimuth**

The angle of a rotation around the z-axis is called azimuth. In the following equations,  $\gamma$  will be used to describe the value of azimuth that is retrieved from the gyroscope.

### 1.3.2 Acceleration depending on Pitch

The current section investigates the effect of a rotation around the smartphone's x-axis on the measured acceleration values. Figures 1.3.2 and 1.3.3 show how accelerations in the direction of x and of z respectively might be decomposed into the different acceleration vectors that are parallel to the

smartphone's axes. The magnitudes of these vectors are measured by the smartphone's acceleration sensor.




Figure 1.3.2:  $a_y$  depending on Pitch






Figure 1.3.3:  $a_z$  depending on Pitch

### 1.3.3 Acceleration depending on Roll

A rotation around a certain axis affects the measured acceleration values of the axes that are parallel to axis of rotation. Therefore, if the smartphone is rotated around its  $y$ -axis, the accelerations in the direction of  $x$  and  $z$  have to be investigated. The composition of the acceleration vectors can be retrieved from the figures 1.3.4 and 1.3.5.


 Figure 1.3.4:  $a_x$  depending on Roll

 Figure 1.3.5:  $a_z$  depending on Roll

### 1.3.4 Acceleration depending on Azimuth


The last rotation that is examined is the one around the \$z\$-axis. This rotation affects the measured acceleration values in the direction of \$x\$ and \$y\$. The vector-decomposition is depicted in the figures 1.3.6 and 1.3.7.

### 1.3.5 Final Equations for the Acceleration Values

After the acceleration values have been examined depending on each rotation value in isolation, the results are combined together in this section.

#### Final Equation: X-Acceleration


As it has been shown in the equations (1.6) and (1.10), the acceleration in the direction of \$x\$ depends on the values of roll and azimuth. Combining these two equations leads to the following equation:



$$a_{y,handy} = \tan(\gamma) \cdot a_{x,handy} \quad (1.9)$$

$$a_x = \frac{a_{x,handy}}{\cos(\gamma)} \quad (1.10)$$

Figure 1.3.6:  $a_x$  depending on Azimuth



$$a_{x,handy} = \tan(\gamma) \cdot a_{y,handy} \quad (1.11)$$

$$a_y = \frac{a_{y,handy}}{\cos(\gamma)} \quad (1.12)$$

Figure 1.3.7:  $a_y$  depending on Azimuth

$$a_x = \frac{a_{x,handy}}{\cos(\beta) \cdot \cos(\gamma)} \quad (1.13)$$

The measured value of  $a_{x,handy}$  is affected in two cases:

- if the handy is accelerated in the direction of z and the value of pitch is not equal to 0
- if the handy is accelerated in the direction of y and the value of azimuth is not equal to 0

These affectations are defined by the equations (1.7) and (1.11). Taking these

equations into account leads to the following, final equation:

$$a_x = \frac{a_{x,handy} \cdot (1 - \tan(\beta) \cdot a_{z,handy} - \tan(\gamma) \cdot a_{y,handy})}{\cos(\beta) \cdot \cos(\gamma)} \quad (1.14)$$

### Final Equation: Y-Acceleration

The equations (1.2) and (1.12) show the dependency of an acceleration in the direction of y depending on the values of pitch and azimuth. If these equations are put together, the result is given by:

$$a_y = \frac{a_{y,handy}}{\cos(\alpha) \cdot \cos(\gamma)} \quad (1.15)$$

The measured value of  $a_{y,handy}$  is affected in two cases:

- if the handy is accelerated in the direction of z and the value of pitch is not equal to 0
- if the handy is accelerated in the direction of x and the value of azimuth is not equal to 0

Therefore, the equations (1.3) and (1.9) have to be included in the calculations. This leads to the following, final equation:

$$a_y = \frac{a_{y,handy} \cdot (1 - \tan(\alpha) \cdot a_{z,handy} - \tan(\gamma) \cdot a_{x,handy})}{\cos(\alpha) \cdot \cos(\gamma)} \quad (1.16)$$

### Final Equation: Z-Acceleration

The basic equation for the acceleration in the direction of z is retrieved by assembling the equations (1.4) and (1.8) that define the accelerations dependency on the values of roll and pitch respectively.

$$a_z = \frac{a_{z,handy}}{\cos(\alpha) \cdot \cos(\beta)} \quad (1.17)$$

The measured value of  $a_{z,handy}$  is affected in two cases:


- if the handy is accelerated in the direction of y and the value of pitch is not equal to 0

- if the handy is accelerated in the direction of x and the value of roll is not equal to 0

If these cases (see equations (1.1) and (1.5)) are considered the final is given by:

$$a_z = \frac{a_{z,\text{handy}} \cdot (1 - \tan(\alpha) \cdot a_{y,\text{handy}} - \tan(\beta) \cdot a_{x,\text{handy}})}{\cos(\alpha) \cdot \cos(\beta)} \quad (1.18)$$

## 1.4 Recognition of Gestures



(a) Add Item to Cart



(b) Switch Item

Figure 1.4.1: Gestures to Recognize

## **List of Tables**

# List of Figures

1.2.1 Overview of the System's Use Cases . . . . .	3
1.2.2 Data Model of the User Gestures to recognize . . . . .	4
1.2.3 Context of the Application to develop . . . . .	5
1.2.4 First Finite State Machine . . . . .	5
1.2.5 Evolutioned Finite State Machine . . . . .	6
1.3.1 Possibilities of rotating a Smartphone, see Objectif Nux [2012]	7
1.3.2 $a_y$ depending on Pitch . . . . .	8
1.3.3 $a_z$ depending on Pitch . . . . .	8
1.3.4 $a_x$ depending on Roll . . . . .	9
1.3.5 $a_z$ depending on Roll . . . . .	9
1.3.6 $a_x$ depending on Azimuth . . . . .	10
1.3.7 $a_y$ depending on Azimuth . . . . .	10
1.4.1 Gestures to Recognize . . . . .	12

# Bibliography

Objectif Nux. App inventor : Premire application - orientation du smartphone, april 2012. URL <http://objnux.1s.fr/index.php?post/2012/04/29/App-Inventor-%3A-Premier-programme>. Accessed: 20.04.17.