Technical Supplement to ProbeFlow: Complete Conditions, Evidence and Conditional-Control Diagnostics

Finite theory, strong-comparator development and a posthoc finite-law diagnosis

Contents

Integrated evidence guide and source-local conventions 2
Technical supplement: navigation and evidence boundaries 2
S1. Common information model, states and complete grammars 3
S2. Exact finite certification, envelopes and planning proofs 6
S3. Strong fixed baselines, joint worlds and common randomized coverage 21
S4. Sharp acceptance bounds and paid-information fusion 46
S5. Conditional transfer, exact projections and sensitivity 59
S6. MHEALTH: complete methods, controls and participant outcomes 68
S7. WISDM custody, windows, descriptors and shared predictor results 106
S8. Participant-excluded risk construction and matched fitted acquisition 128
S9. HGB intervention, failed fusion and calibrated terminal mixtures 148
S10. Observable-history acquisition: every primary control and path 173
S11. Nominal coverage optimization: full expected outcomes and costs 182
S12. Known-person robust coverage: all radii, people and certificates 194
S13. Reproducibility, measured resources and preserved failures 205
S13. Source-section concordance 212
S14. Reference identity and exact inspection scope 224
S15. Conditional history control: full method, proof, outcomes and limits 237
S16. Posthoc same-class diagnosis and separately corrected exact bounds 246
References 251

Integrated evidence guide and source-local conventions

S1-S14 preserve every section and native payload of the prior complete technical supplement. S15 adds the full conditional-controller source evidence; any separately admitted posthoc diagnosis is namespaced independently. Historical words such as final or current inside a retained construction describe that source contract, not a new population result.

The article integrates these constructions by question, method, result and limitation. Every original source-local reference is resolved by its namespace and concordance. Actual sibling-PDF page links are rebuilt from the present documents, not copied from the earlier17/239page layout.

The primary method review is needs_evidence. Numerical checking and read-budget compliance are different checks; the final review-scope statement records both, without an accepted/full-pass claim.

Technical supplement: navigation and evidence boundaries

This standalone supplement accompanies ProbeFlow: Exact Acquisition, Strong Comparators, and the Limits of Useful-Coverage Transport. It is a topic-based technical reconstruction, not a concatenation of prior papers or PDFs. One bibliography and one navigation scheme cover every admitted construction. The original scientific inputs are retained byte-for-byte in the accompanying source manifest; no scientific actor is executed in building these documents.

The article gives the unified estimands, methods, results and interpretation. This supplement retains full declared conditions, proof steps, exact and numerical witnesses, complete policy and participant tables, diagnostic failures, costs and reproducibility limits. Historical theorem/lemma names inside a construction are local. Stable S-numbered headings and links provide global references.

Navigation rule. New global sections are the S-numbered headings and clickable section links. Any remaining unlinked section/figure/table/algorithm name inside a retained technical derivation is an original source-local label, not a new global number. The printed source concordance in Supplement S13 resolves every original source section to its new section and actual page. Tokens such as T5 or C5 may instead identify empirical data units; their local definition takes priority.

Read Supplement S1–Supplement S5 for theory, Supplement S6 for MHEALTH, Supplement S7–Supplement S12 for WISDM and Supplement S13–Supplement S14 for provenance and inspected literature. For the common empirical definitions see Article §3; for the final known-person result and interpretation see Article §15.

S1. Common information model, states and complete grammars

The supplement uses the article's C/E/K/J convention. The detailed retained constructions also use local historical symbols, defined at their point of use: in particular A may mean an accuracy or abstention indicator, and C may name a calibration partition. Such local notation does not change the common performance definitions. Each subsection states its construction scope before giving definitions, proofs or numerical evidence.

S1.1. Finite model / MHEALTH: Information, actions and objectives

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$J_P(\pi) = E_P\left[\text{error} + \left(\frac{2}{5}\right)\text{abstain} + \lambda N\right]$$

The normal finite model has no initial observation. N counts every paid attempt, including failed attempts.

$$V_K = \min_{q\in\Delta(\Pi_K)} \max_{v\in\{0,1\}} \sum_i q_i L_{iv}, \quad K \in \{F, A\}$$

Absolute robust objective over the two-law convex hull. F denotes fixed orders with adaptive stopping; A additionally permits adaptive query choice.

$$\gamma = \max_{q\in\Delta(\Pi_A)} \min_{v\in\{0,1\}} \left[b_v - \sum_i q_i L_{iv}\right]$$

The reference endpoint vector b is fixed first. Candidate and reference are evaluated at the same endpoint v.

$$R(S) = \max_{z:\Omega_{S,z}\neq\varnothing} [U(S,z) - L(S,z)]$$

The separate fixed-subset objective is a worst conditional interval width, not sequential prediction loss.




Figure S1: Information rights during planning, execution and evaluation. The three lanes separate declared laws, paid public histories and post-decision truth. The dotted line marks a cooperative information boundary; operating-system isolation was not evaluated.

S1.2. Finite model / MHEALTH: Fair policy classes and execution

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.




Figure S2: Episode execution with a family-specific stopping rule, shared support and budget admission, attempted-query cost and common terminal scoring. Forced subsets continue while incomplete and supported. The cached experiment contains normal responses; conditional-model failed attempts remain paid.

S1.3. Finite model / MHEALTH: Scope, notation, and evidence units

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

This Supplement is an audit trail for the scientific argument, not a chronological account of task execution. Supplement S1.4 through Supplement S2.9 develop the finite model, grammar, LP certificates, same-law comparison, and all-cost proof. S9 contains every designed-regime result and witness summary. S10-S12 delimit the older interval-width problem. S13-S19 give cached-state rules, all policy tables, paired counts, arithmetic, and complexity qualifications. S20-S22 preserve incomplete studies, source custody, reading limits, and falsifiable follow-up requirements.

An endpoint index v is a law index; a query index a is an action; a policy index i identifies one original tree. None ranks scientific quality. The primal distribution q chooses policies before an episode; the dual weight t mixes the two laws only in a certificate. The reference vector b_v must not be confused with maximum query depth. Error and abstention are mutually exclusive terminal indicators. Quote counts are attempted logical acquisitions. Counts, expectations, participant-macro rates, pooled window rates, and path visits are reported with their respective denominators.

Exact model expectations, exposed cached-development outcomes, and execution receipts are separate evidence families. This derivative checks saved arithmetic and renders figures without replaying a producer, oracle, experiment, model call, or historical test.

S1.4. Finite model / MHEALTH: Atoms, observations, and loss components

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The eight atoms are 000, 001, 010, 011, 100, 101, 110, and 111, in coordinate order C,B0,B1. P0 assigns probability 1/4 to the first four and zero to the rest; P1 reverses those assignments. A convex mixture gives mass t/4 to each C=0 atom and (1-t)/4 to each C=1 atom. Every mass is nonnegative and the total is one. Varying the route probability preserves independent fair bits and the target's fair marginal. Those assumptions define the example; they were not learned from the development participants.

The response functions reveal exactly one coordinate: query 0 returns C, query 1 returns B0, and query 2 returns B1. Routed target Y uses the selected bit, static target uses B0, and known-route sets both endpoint laws to C=0. In the erased condition, the response function returns F for every query without changing the

target's uncertainty. Acquiring an uninformative response is still an attempted action. No response, failure flag, endpoint number, or target may be previewed before its permitted point in the public history.

For terminal 0 or 1, error is one exactly when prediction differs from Y. For terminal A, abstention is one and error is zero. Consequently the reported unconditional error can fall merely because predictions become abstentions. The total loss adds error, 2/5 times abstention, and λ times the attempt count. This is not error conditional on prediction. At zero cost, numerically equal losses can correspond to different attempt counts, so the component triple is retained even if a solver only needs the total-loss vector for one cost.

S1.5. Finite model / MHEALTH: Public histories and complete policy grammar

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A normal public history contains the ordered attempted queries and their revealed responses. Remaining depth and unused queries are derived from it. A seed may be internal state, but its distribution must be independent of the latent atom and true law. A normal query requires two response branches; an erased query requires exactly its singleton F branch. Repeated queries, depth beyond two, missing normal branches, and invalid terminal symbols are rejected. The evaluator's ability to inspect a full atom cannot be used as an actor feature.

The adaptive grammar always includes three terminals. If depth remains, it chooses any unused query and assigns a legal subtree to each response. The fixed grammar instead chooses only the next element of a preselected order, with the same suffix for every response. Termination may differ across branches. An exhausted order cannot switch to another query even if some budget remains. A fixed order therefore has adaptive stopping, but not adaptive query identity. A forced subset with mandatory supported continuation is a different family again.

Any randomized behavior policy on the finite history space can be represented by sampling all its potential random choices in advance. The resulting seed defines a deterministic tree; its distribution gives the same expected loss. This argument relies on seed independence. A seed correlated with C is additional information, not harmless randomization. Similarly, observing C and then choosing between two otherwise fixed orders is an adaptive policy. This distinction is what permits the classes to differ by one well-defined right.

History sufficiency depends on static values. Time, failure history, cache state, or deadlines may require a richer state and new matched rights; set-encoding invariance does not prove that extension.

S1.6. Finite model / MHEALTH: Grammar counts and retained raw rows

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

With one step left and two unused normal queries, the adaptive menu has three immediate terminals plus two queries with nine terminal response maps each, hence 21 elements. At the root, the three initial queries each combine two independent menus of size 21. Adding the three immediate terminals gives 3+3 times 21 squared, or 1,326 trees. Distinct root queries or subtree combinations are structurally distinct. This is a combinatorial count, not a desired output count used to truncate generated trees.

For one fixed pair, each first response permits three terminals or the second query with nine terminal maps, a menu of 12. The two pair orders sharing the same first query overlap in exactly the nine maps that terminate after either first response. Their union has 2 times 12 squared minus 9, or 279 elements with that root query. Three root queries and three immediate terminals give 840. Empty and single-query orders are already represented; adding their counts again would duplicate trees. The saved checker verified validity and structural uniqueness before using the total count to infer completeness.

In the erased grammar the last-step adaptive menu is 3+2 times 3, or 9, and the root count is 3+3 times 9, or 30. A fixed pair has six possible continuations after its singleton response; the two choices of second query overlap in three terminals, again giving nine per root and 30 overall. Because no query reveals distinguishing information, the two syntactic classes coincide in this special regime.

Equal loss vectors are not identical policies. At λ zero an otherwise unnecessary query can leave total loss unchanged; at positive cost it can change it. The raw rows therefore preserve the original tree and endpoint error, abstention, and attempts. Duplicate-vector and dominance removal is scoped to solving one matrix. Original indices remain available and every final dual inequality is checked against every raw row, including rows omitted from candidate search.

S2. Exact finite certification, envelopes and planning proofs

This chapter proves finite grammar, minimax, reference-relative and known-law statements. Declared rational worlds are mathematical inputs. Enumeration and independent arithmetic checks establish those finite claims; they do not estimate a population law or create independent application samples. The separate interval-width problem retains its own objective and conditions.

S2.1. Finite model / MHEALTH: Exact same-law certification

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Algorithm S1. Certify a common-law improvement
Require: Complete legal fixed and adaptive grammars with common atoms, observation, failure, terminal, and attempt-cost rights. A nonempty exact rational loss matrix with precisely two law columns.
Ensure: Fixed reference, adaptive mixture, endpoint vectors, probabilities, and primal/dual witnesses. Same-law paired gamma or an explicit invalid, exhausted, failed, or unknown result.

1 Validate every tree and fixed-order prefix; verify fixed-class inclusion.
2 Evaluate error, abstention, and attempted queries on the same endpoint atoms.
3 Retain raw rows; reduce only duplicate and dominated rows for candidate search.
4 Compare pure rows and valid two-row equalizing mixtures; search valid dual intersections.
5 Require exact primal feasibility, all-original-row dual inequalities, and equal rational values.
6 Freeze the selected fixed endpoint vector b; subtract its column values from adaptive rows and certify the contrast separately.
7 Report gamma as the negative contrast value; preserve gamma=0 as no_gain.
8 Link the original tree indices and every failure or incomplete denominator to the witnesses.

$$\min_{q,z} z: \quad \sum_i q_i L_{i0} \le z, \quad \sum_i q_i L_{i1} \le z, \quad \sum_i q_i = 1, \quad q_i \ge 0$$

Epigraph primal LP for a two-column loss matrix. The contrast matrix may contain negative entries.

$$\max_{0\le t\le 1} \min_i [tL_{i0} + (1-t)L_{i1}]$$

Dual law weight t supplies a lower bound from every original policy row; exact equality with a feasible primal supplies a certificate.

S2.2. Finite model / MHEALTH: Cost envelope and no-gain boundaries

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$V_F = \min\left(\frac{2}{5}, \frac{1}{4}+\lambda, \frac{1}{5}+3\frac{\lambda}{2}\right), \quad V_A = \min\left(\frac{2}{5}, 2\lambda\right)$$

Exact envelopes under independent fair bits, two distinct query attempts, abstention cost 2/5, and nonnegative λ.

$$\gamma = \frac{1}{5} - \frac{\lambda}{2}, \quad 0 \le \lambda \le \frac{1}{10}$$

The low-cost reference mixes C-first fixed orders.

$$\gamma = \frac{1}{4} - \lambda, \quad \frac{1}{10} \le \lambda \le \frac{3}{20}$$

The middle reference mixes single-bit policies.

$$\gamma = \frac{2}{5} - 2\lambda, \quad \frac{3}{20} \le \lambda \le \frac{1}{5}$$

The reference abstains in the third interval; γ is zero for λ at or above 1/5.




Figure S3: Exact routed-model cost envelope. (a) Optimal worst-law losses for the full fixed and adaptive classes. (b) Their same-law gain against the symmetric fixed reference, reaching zero at λ=1/5. These are analytical finite-model values in logical loss units.

S2.3. Finite model / MHEALTH: Objective-matched myopic controls

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Algorithm S2. Complete shared-alpha myopic family and matched certificate

Require: Frozen T endpoint laws P5/P6 and seven-mask predictor; legal observed histories, raw support 30/both groups, two additional distinct queries. Error 1, abstention 2/5, every quote 1/20 including the initial quote; canonical zero-raw-mass and action ties; the original frozen reference b.

Ensure: Every complete 38-state action signature in the declared M_alpha family, legal forest witnesses, exact T endpoint vectors and the point/open-atom ledger. Separately matched minimax-M/A and directly paired-M/A primal/dual certificates; no_gain, strict finite gain, or an explicit incomplete/failure status.

1. Form each history's occupancy and STOP-error endpoint masses using its original group denominator. Fix one design alpha for the whole episode.
2. Score STOP by error mass and abstention by (2/5) times occupancy. Score a legal query by occupancy/20 plus the sum of its children's minimum STOP/abstention masses; do not include a second acquisition in this score.
3. Split at every child-terminal equality. Within each valid affine cell, include every exact action-score intersection; unite the cuts over all histories and include alpha=0 and alpha=1.
4. Evaluate every cut itself and one representative of every open interval at all 38 histories. Use A at zero total raw T; otherwise apply STOP, A, then ascending-query tie order, even when alpha-weighted mass is zero.
5. Deduplicate only identical complete signatures. Roll out with the same alpha and remaining rights after each actual observation. Retain point-only and off-path decisions.
6. Compare with the complete A grammar and F's common global order. For each class, form affine endpoint rows in the separate adversarial theta; shift each row by the same frozen b only for the paired game.
7. Maximize each exact lower envelope over theta; recover one or two feasible complete forests and rational ex ante weights. Require both primal endpoint bounds, every original-row dual inequality and zero primal/dual gap.
8. Freeze all T selectors, original reference identity and weights before C scoring and the first new DEV read. Preserve zero planning increments as no_gain and negative paired-M values without clipping.

$$t_\alpha(h,j,z) = \min\left(e_\alpha(h,j,z), \left(\frac{2}{5}\right) m_\alpha(h,j,z)\right)$$

The one-step child terminal cost chooses STOP or abstention, with no further purchase.

$$Q_\alpha(h,j) = \left(\frac{1}{20}\right) m_\alpha(h) + \sum_{z\in\{0,1\}} t_\alpha(h,j,z)$$

One-step query score in unnormalized masses. The same α is retained when the actor later replans.

$$R_M = R_A = \frac{123}{440}, \quad \Gamma_b(M) = \Gamma_b(A) = \frac{2091}{205940}$$

Matched primary values. Both full-A increments are exactly zero.

Table S1: Cumulative exposed DEV macro J under the same error/abstention/quote loss. Different selectors and forced-purchase definitions remain explicit; this is not an independent-final performance table.

Policy	Selection / forced rights	Exact DEV J	Display
Historical committed token 2	T mean, forced token 2	28743/114380	0.251294
New forced two-additional order	T mean, supported global order 3 then 2	182801/686280	0.266365
Historical fixed 2 / new Tmean F	T mean, optional continuation	134663/457520	0.294332
Tmean A = Tmean M	T mean, shared loss	1364/4515	0.302104
paired A = paired M	Direct paired to original b	316099513/ 1009517880	0.313119
robust A = robust M	Absolute minimax	145279/457520	0.317536
Original robust reference b	Historical full-F minimax	115999/343140	0.338052




Figure S4: Complete shared-α one-step family and matched objectives. Sixteen exact cuts and31 point/open atoms give11 complete38-state signatures. Both minimax and paired planning increments are zero when M and A optimize the same declared objective.

S2.4. Finite model / MHEALTH: Conditional known-law planning regimes

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$V_M(\theta) - V_A(\theta) = \max\left(0, \frac{615\theta - 538}{6160}\right)$$

Post hoc known-θ Bayes risk on frozen empirical T rows, not a new primary experiment or population bound.

Table S2: Ordering of lower known-θ empirical Bayes loss. Equalities at both rational boundaries are exact.

Known θ	Class relation
[0,79/145)	V M=V A<V F
[79/145,538/615]	V M=V A=V F
(538/615,1]	V A=V F<V M




Figure S5: Post hoc known-θ risk envelopes and excess risk over A. The exact class ordering is M=A<F, then M=A=F, then A=F<M, with rational boundaries 79/145 and538/615. The strict M gap reaches1/80; its adaptive witness is also fixed-order feasible.

S2.5. Finite model / MHEALTH: Finite verification and the nine designed regimes

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

All nine cases of the preserved two-law study were planned, started, and completed. There were no failed, exhausted, unknown, or unstarted cases in that study. Four routed conditions have positive paired gains: 1/5 at zero cost, 7/40 at cost 1/20, 1/8 at cost 1/8, and 1/15 at cost 1/6. The routed boundary and expensive cases, erased observations, a static target, and a known route give five no_gain outcomes. Supplement Figure S6 displays every regime in the same scale and retains the five zeros. Four of nine is a description of selected model conditions, not the probability that adaptation benefits an application.




Figure S6: All nine author-designed regimes, with four positive exact gains and five no-gain outcomes. Zero-valued rows remain visible. The rows are selected model conditions, not independent application samples or a success-rate estimate.

S2.6. Finite model / MHEALTH: Primal existence, two-row candidates, and dual witnesses

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The finite primal minimizes the maximum of two affine functions over a probability simplex. Its objective is continuous and the simplex compact, so a finite optimum exists for a nonempty finite matrix. The epigraph variable has no nonnegativity restriction because reference-relative contrast losses may be negative. An empty matrix is an invalid input rather than an opportunity to invent an infinite or zero certificate. Rational entries permit exact construction and checking without a floating-point tolerance.

To see the support bound, consider an optimal extreme solution with s positive probabilities and a value variable. Probability normalization and at most two active endpoint constraints impose at most three independent equalities on s+1 variables. If s is at least three, a nonzero perturbation preserves those equalities. A sufficiently small perturbation in both directions preserves positive probabilities and any slack endpoint constraint, so the solution is not extreme. At least one optimum can thus be chosen with at most two positive rows. This does not restrict all optima; a distribution over many duplicate optimal rows can also be optimal.

For two rows a and b, mixing with weight α produces two affine endpoint losses. Their maximum is convex and piecewise linear on the unit interval. A minimum occurs at an interval endpoint or at their crossing. The saved α formula equalizes endpoint losses; a zero denominator is handled separately, and only weights in the unit interval are legal. Combining this fact with the support theorem makes pure rows and valid pair crossings sufficient. The stable tie-break selects one reproducible representative without assigning it statistical meaning.

The dual lower envelope is the minimum of all policy-loss lines as a function of t. It is concave and piecewise linear on the unit interval, so a maximum can be chosen at an endpoint or a valid line intersection. A feasible q with both endpoint values at most v and a feasible t with every original row's weighted loss at least v sandwich the optimum exactly. This certificate uses weak duality and does not require trust in the solver's candidate traversal. A stored witness is checked for row validity, probability normalization, atom-derived losses, all inequalities, and exact equality.

$$\alpha = \frac{b_1 - b_0}{(a_0 - a_1) - (b_0 - b_1)}$$

Valid two-row primal crossing; the entire denominator is parenthesized and zero is treated separately.

$$t = \frac{b_1 - a_1}{(a_0 - a_1) - (b_0 - b_1)}$$

Dual crossing of two policy-loss lines. Exactly two law columns are assumed.

S2.7. Finite model / MHEALTH: Same-law improvement and the minimax-gap counterexample

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

After choosing the fixed minimax reference, retain its actual endpoint vector b. For each adaptive row subtract b_v from the corresponding endpoint loss. The minimax value of this contrast matrix is the negative guaranteed gain. A negative contrast means improvement. Since the fixed mixture belongs to the adaptive class, a zero contrast is feasible, so optimal γ cannot be negative under this inclusion and an exact solver. The operational no_gain rule still keeps the reference when γ is zero.

For any law on the declared segment, expected contrast is an affine combination of endpoint contrasts. If one fixed adaptive mixture improves both endpoints by at least γ, that same mixture improves every law on the segment by at least γ. This order of quantifiers matters: one candidate is chosen and then tested against all laws. Solving a different candidate for every law and reporting the best pointwise values does not establish the same uniform statement. Nor does exact optimization prove the true application law lies on the segment.

Take a fixed reference f=(0,1) and add a candidate a=(1/2,1/2) to the adaptive class. With candidate weight α, absolute endpoint losses are $\alpha/2$ and 1-$\alpha/2$. The adaptive minimax value is 1/2 at α=1, compared with fixed value 1. But the endpoint improvement vector relative to f is (-$\alpha/2$,$\alpha/2$). Its minimum is -$\alpha/2$, maximized at α=0 with guaranteed gain zero. An absolute minimax reduction of 1/2 therefore supplies no positive reference-relative guarantee.

The counterexample does not rely on data noise or a misspecified law. It is a consequence of subtracting worst values attained at different endpoints. A scalar reference value discards precisely the vector information needed for the paired comparison. In the routed-bit model the selected symmetric reference has equal endpoint losses, making γ equal to its common value minus the adaptive minimax value. This special equality motivates a convenient plot, but the implementation still builds and certifies the contrast matrix independently.

S2.8. Finite model / MHEALTH: Deriving all fixed-order and adaptive envelopes

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Under the symmetric routed law, no observation leaves a fair target, so abstention costs 2/5 and beats prediction error 1/2. Observing C alone does not change this terminal choice. Observing Bj=v makes Y=v with probability 3/4: half the mass follows route j and is known, while the other half uses an independent fair bit. The optimal terminal prediction therefore has error 1/4. This posterior risk is the same for v=0 and v=1.

After observing both bits, equal bits determine Y, while unequal bits leave a fair route and favor abstention. The average terminal cost is therefore 1/5. Observing Bj and C gives the same average: the matching half is known and the nonmatching half favors abstention. Identical average values here do not mean identical information structures. Both calculations use the common abstention right; prohibiting abstention for the fixed reference would invalidate the comparison.

The empty order and a C-only order have value 2/5 after allowing immediate STOP. A Bj-only order has the minimum of 2/5 and λ+1/4. For C then Bj, pay the first query; on a matching route choose between a second paid query and abstention, and on a nonmatching route abstain. For Bj then C or the other bit, compare immediate posterior prediction error 1/4 with a second query followed by average terminal risk 1/5. These cases cover all ten orders, including observation-dependent stopping. Mixing before the episode cannot improve the minimum expected loss under this one symmetric law, so it is also a lower bound for randomized fixed policies.

The nonconstant fixed candidates reduce to 1/4+λ and 1/5+3lambda/2, together with abstention 2/5. A symmetric mixture of single-bit policies attains the former at both endpoints. A symmetric mixture of C-first preselected-bit policies attains the latter with error zero, abstention one half, and mean query count three halves. For costs where a construction is no longer competitive, immediate abstention supplies the minimum. These matching upper bounds establish the exact robust fixed envelope independently of enumerating 840 rows.

For an adaptive C-first root, the remaining choice is to buy the relevant bit or abstain, giving λ plus the minimum of λ and 2/5. A bit-first root has the same second-step alternatives already examined. Comparing all root terminals and query choices yields the Bayes lower envelope min(2/5,2lambda). Reading C then the matching bit, or abstaining immediately, attains it equally at both endpoints. This completes the adaptive proof. A deterministic adaptive tree suffices for this construction, but arbitrary two-law matrices may still require randomized adaptive mixtures.

$$V_{C\to B_j} = \min\left(\frac{2}{5}, \lambda + \frac{1}{5} + \left(\frac{1}{2}\right)\min\left(\lambda, \frac{2}{5}\right)\right)$$

C-first fixed order includes root abstention and abstention on the mismatched route.

$$V_{B_j\to C} = V_{B_j\to B_{1-j}} = \min\left(\frac{2}{5}, \lambda + \min\left(\frac{1}{4}, \lambda + \frac{1}{5}\right)\right)$$

Bit-first fixed orders compare immediate prediction against a second paid query.

S2.9. Finite model / MHEALTH: Breakpoints, degenerate regimes, and rejection rules

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The fixed C-first mixture and single-bit mixture meet at λ=1/10. The single-bit mixture and immediate abstention meet at 3/20. Adaptive exact acquisition and abstention meet at 1/5. Subtracting the active fixed and adaptive branches gives the three γ pieces in the main paper. At 1/10 both adjacent expressions equal 3/20; at 3/20 both equal 1/10; at 1/5 the final expression reaches zero. These exact checks preserve boundary ties and make the curve continuous.

Erased responses never change the target posterior. Deleting an uninformative nonnegative-cost query and taking the same terminal cannot increase loss, so immediate abstention supplies matching lower and upper bounds of 2/5. In static and known-route conditions, reading B0 gives perfect prediction at cost λ and no other information can improve the unobserved fair-bit terminal. Both classes therefore achieve min(λ,2/5). This is an author-defined complete-failure model, not a measurement of partially informative failures, device availability, or a provider failure rate.

Input and completion failures are distinct from no_gain. The retained contract rejects an empty or non-two-column matrix, floating-point loss input, invalid probabilities, repeated queries, depth violations, missing branches, cap overflow, excessive fraction size, and primal/dual mismatch. No output is silently rounded,

truncated, or filled with a theoretical prediction after an execution failure. Candidate exhaustion is not evidence that the reference is optimal. An unstarted condition stays unstarted, and an unknown termination stays unknown until supported lifecycle evidence resolves it.

When extending the method, the two-law dimension is a real boundary. The support-at-most-two proof does not establish a generic two-policy representation for three or more law vertices, identified sets, or side-constrained policies. Likewise, a proof assuming true-law inclusion cannot be applied to an estimated catalog without an independent structural and statistical argument. Those extensions are substantive work rather than configuration changes to the current solver.

S2.10. Finite model / MHEALTH: Every designed-regime result and witness summary

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The following three tables preserve the frozen model results, component triples, and original support indices. Pure-fixed values are shown next to randomized-fixed values to reveal the effect of strengthening the comparator. Paired lower and upper bounds agree exactly in every completed case. A gain row is a strict total-objective improvement under its declared law set and selected reference. A no_gain row is a completed negative result. Neither label describes application accuracy or a population success rate.

At λ zero, the selected reference may include a zero-weight support entry or a behavior that makes an unneeded free query. Such representation choices do not alter its distribution or value, but original policy indices and component triples are preserved. This is why the free-cost reference has the stored query count shown in the component table rather than being rewritten as a different equivalent tree. Reconstructing a prettier witness would weaken the link to the saved original rows.

Each normal case has 840 fixed and 1,326 adaptive trees evaluated on four atoms per endpoint, producing 17,328 tree-atom rollouts. Eight normal cases and one erased case with 480 rollouts total 139,104. The denominator measures exact computation on the declared finite laws. It is unrelated to the 524 cached windows, their two participant groups, or any statistical sample size. The present derivative copies stored results and checks arithmetic without running the historical producer or tree interpreter.

Table S3: S1. All nine designed regimes: exact losses and paired bounds.

Regime; λ	Pure fixed	Randomized fixed	Adaptive	Paired lower / upper	Decision
routed free; 0	1/5	1/5	0	1/5 / 1/5	gain
routed cheap; 1/20	3/10	11/40	1/10	7/40 / 7/40	gain
routed middle; 1/8	2/5	3/8	1/4	1/8 / 1/8	gain
routed late; 1/6	2/5	2/5	1/3	1/15 / 1/15	gain
routed boundary; 1/5	2/5	2/5	2/5	0 / 0	no gain
routed expensive; 1/4	2/5	2/5	2/5	0 / 0	no gain
erased; 1/20	2/5	2/5	2/5	0 / 0	no gain
static; 1/20	1/20	1/20	1/20	0 / 0	no gain
known route; 1/20	1/20	1/20	1/20	0 / 0	no gain

Table S4: S2. Stored endpoint components (unconditional error; abstention; attempted queries).

Regime	Reference P0	Reference P1	Candidate P0	Candidate P1
routed free	0; 1/2; 2	0; 1/2; 2	0; 0; 2	0; 0; 2
routed cheap	0; 1/2; 3/2	0; 1/2; 3/2	0; 0; 2	0; 0; 2
routed middle	1/4; 0; 1	1/4; 0; 1	0; 0; 2	0; 0; 2
routed late	0; 1; 0	0; 1; 0	0; 0; 2	0; 0; 2
routed boundary	0; 1; 0	0; 1; 0	0; 1; 0	0; 1; 0
routed expensive	0; 1; 0	0; 1; 0	0; 1; 0	0; 1; 0
erased	0; 1; 0	0; 1; 0	0; 1; 0	0; 1; 0
static	0; 0; 1	0; 0; 1	0; 0; 1	0; 0; 1
known route	0; 0; 1	0; 0; 1	0; 0; 1	0; 0; 1

Table S5: S3. Stored support indices:exact probabilities and dual weights. Zero weights are preserved.

Regime	Reference support	Reference t	Adaptive support	Adaptive t	Paired t
routed free	80:0; 487:1	1/2	100:1	1	1
routed cheap	80:1/2; 58:1/2	1/2	100:1	9/10	9/10
routed middle	283:1/2; 562:1/2	1/2	100:1	3/4	3/4
routed late	2:1	8/15	100:1	2/3	2/3
routed boundary	2:1	3/5	2:1	3/5	3/5

Regime	Reference support	Reference t	Adaptive support	Adaptive t	Paired t
routed expensive	2:1	7/10	2:1	7/10	7/10
erased	2:1	1	2:1	1	1
static	283:1	1	445:1	1	1
known route	283:1	1	445:1	1	1

S2.11. Finite model / MHEALTH: Separate fixed-subset interval-width problem

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The older fixed-subset problem concerns a sharp loss contrast over original compatible worlds. For participant j and coordinate i, a marks an already requested coordinate and u is binary error. Requested-coordinate errors share one cap across all participants, rather than a separate cap per person. Known STOP errors retain their declared values. Route and static availability vectors each satisfy their own unit-box and participant-sum constraints. Separate constraints are not an empirical statistical independence claim about sensor failures.

The coordinate losses below define the original route-minus-static contrast. First average coordinates within each participant, then average participants equally. Minimize and maximize that contrast in the same original world to obtain sharp endpoints. Independently optimizing route loss and static loss and subtracting their extrema would not yield the same sharp contrast. The analogy with a same-law paired objective is methodological; the optimization variables and target quantities are different.

A query reports a closed bin constraining a static availability coordinate relative to its threshold. At an exact threshold both labels can be feasible. An impossible observation leaves an empty compatible-world set and is represented as no endpoint, rather than endpoint zero. Substituting zero would turn an impossible event into a spuriously narrow interval. A design S is chosen before observations, subject to cost, and R(S) maximizes its residual sharp width over feasible observations. The canonical exact representative minimizes width, then cost, then integer mask.

This objective does not train a predictor, choose the next measurement adaptively, or directly optimize the sequential J used in the main paper. The true application risk can worsen with an added feature under a fixed predictor, and acquisition cost can increase even when compatible-world width decreases. A bridge from lower R to lower J would need a separate theorem. The current work supplies no such theorem and does not pool their result tables as common performance evidence.

$$\ell_{\mathrm{route},ji} = \big(1 - a_{ji} r_{ji}\big) u_{ji} + c\big(1 + a_{ji}\big) + k a_{ji} \big(1 - r_{ji}\big)$$

Original route coordinate loss; c=1/20, k is nonnegative, and the requested-error cap is global.

$$\ell_{\mathrm{static},ji} = \big(1 - v_{ji}\big) u_{ji} + 2c + k\big(1 - v_{ji}\big)$$

Original static coordinate loss under its separate availability constraints.

S2.12. Finite model / MHEALTH: Bound directions, frontier coverage, and strong DP

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

An outer node with required set I and undecided set U represents designs between I and M=I union U. A verified feasible complete observation of M projects to a feasible observation of any represented S. Adding observations only shrinks the compatible-world set. Its width at M is therefore no larger than the width at S, which is no larger than R(S). This makes the M width a lower bound for outer minimization, even when M is too costly to return as a feasible design. It is a relaxation witness, not an incumbent.

The direction reverses inside the observation maximization. A partial history h has a world set containing every completion z, so its interval contains the completed interval and its width is an upper bound on a descendant width. With one maximum witness required, an internal prefix can be pruned on equality with an already completed incumbent. If every tied maximum witness is required, equality pruning is not generally safe. These output contracts have different work and cannot be exchanged while retaining an all-ties completeness claim.

The outer solver retains a feasible incumbent and a frontier covering every unresolved design. The minimum of the incumbent upper bound and all frontier lower bounds is a global lower bound. Their gap bounds absolute residual-width regret. When the frontier is empty, the lower bound equals the incumbent. A resource stop that loses the active node loses coverage and cannot report a certificate without restoring it. For exact lexicographic output, zero scalar risk gap is insufficient if a cheaper or smaller-mask tied design remains unresolved.

The strong comparator is memoized value-only subset DP with the same endpoint kernel, caches, warm start, and one-witness output. Its state is the subset, with remaining cost determined by the subset price. It compares the current width-cost-mask tuple with every affordable extension, memoizing multiple orders reaching the same subset. Positive prices and increasing masks permit stopping once a common global seed floor is reached. This comparator removes avoidable permutation and all-tie-output work from the claimed branch-and-bound gain. General subset and subset-observation counts still grow exponentially.

$$W(M, z_M) \le W(S, z_S) \le R(S), \quad I \subseteq S \subseteq M$$

An M observation supplies an outer-minimization lower bound for every I subset S subset M.

$$L(h) \le L(z) \le U(z) \le U(h)$$

A partial history supplies an inner-maximization upper bound, the opposite direction.

$$L_F = \min\Big(\mathrm{UB}, \min_{n \in F} \mathrm{LB}(n)\Big) \le R^* \le \mathrm{UB}$$

A valid frontier covers all unresolved designs. An empty frontier sets its lower bound to UB.

S2.13. Finite model / MHEALTH: Seven engineering conditions and complementarity

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The preserved comparison has four arms: original all-ties output, strong memoized value-only DP, exact one-winner branch-and-bound, and epsilon branch-and-bound. The table below retains the seven exact DP-versus-branch-and-bound conditions. They return the same exact interval-width objective; exact objective improvements are zero. Only two of seven conditions reduce both median CPU and maximum traced Python allocation. A larger speed difference against original all-ties output includes the cost of a different output contract and is not the principal comparison.

The measured scope includes validation, the declared seed construction, warm start, endpoint and bound work, caches, search, and raw-event writing. Common imports, final receipt serialization, and independent oracle work are separate. CPU is a median, while traced allocation is a maximum. Three cold cyclic-order repetitions expose some order sensitivity but are not independent scientific data. Physical disk traffic, energy, whole-host peak memory, and user latency were not measured. Counters with the same name across different arms may count different events, so only matching primitive definitions justify direct count comparisons.

The complementarity witness has equal width 3/8 at masks 4, 5, and 6, but width 1/4 at mask 7. A single addition can show no gain while a combination helps. Thus a zero one-step reduction does not justify permanently discarding a query, and adaptive-submodular diminishing returns has not been established. A greedy warm start is merely a feasible incumbent whose width is exactly evaluated. This counterexample does not refute adaptive-submodular theorems; it prevents transferring their conclusion without their assumptions.

For the Q4 example, original all-ties median CPU is 6.96875 seconds, strong DP is 0.71875, and exact branch-and-bound is 0.28125. Their traced maxima are respectively 231943, 334535, and 141338 bytes. Even the output-heavy original arm is not always the memory maximum. The engineering result is conditional on the implementation, primitives, and output contract. It does not establish a generic scalability theorem or improve the prediction objective of the later acquisition problem.

Table S6: S4. Preserved exact interval-width engineering comparison; CPU medians and traced Python maxima.

Condition	CPU seconds DP / B&B	Python bytes DP / B&B	Exact R
Equality ties	0.015625 / 0.015625	16224 / 16842	0
Impossible bins	0.015625 / 0.03125	25126 / 27007	11/30
Zero cap / prices	0.0625 / 0.078125	46670 / 72149	41/120
Complementarity	0.25 / 0.21875	73531 / 59281	1/4
Shared-cap ties	0.203125 / 0.25	85789 / 137717	3/5
Four pairs Q2	0.125 / 0.125	66535 / 80798	51/128
Four pairs Q4	0.71875 / 0.28125	334535 / 141338	21/64

S2.14. Finite model / MHEALTH: Completed finite-catalog identification context

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The W61 study is a different completed author/reviewer result from the failed historical W60 attempt. It restricts compatibility to retained catalog vertices and their convex hull, rather than constructing the full inverse image of an arbitrary latent logging model. A point-law advantage is identified only when compatible

laws agree on it; a fixed-reference same-law guarantee instead directly optimizes worst compatible-law contrast.

In the anchor-zero-upper case, compatible laws have point gains 1/6 and 0, so the point gain is not identified. A separate minimax-value difference is 1/6, while direct paired Γ is zero. This is an explicit warning against using two unrelated optimized values as a uniform benefit certificate. The labelled singleton case identifies its point gain, and the acquisition-failure case has no gain.

The completed catalog review checks 13,116 policy-loss entries and primal/dual/Bellman evidence, with algorithm, architecture and baseline evidence but partial complexity, evaluation and related-work coverage. It is exact finite-model evidence. No new application, full latent-law inverse, finite-sample inclusion guarantee, complete physical-cost accounting or external reproduction follows.

Table S7: Completed W61 catalog cases, kept separate from empirical cache results and from the failed W60 pipeline.

Case	Compatible point gains	Point gain identified?	Direct paired Γ
partial positive	7/40; 0	No	7/40
anchor zero upper	1/6; 0	No	0
labelled separation	1/6	Yes, within singleton	1/6
acquisition failure	0; 0	Yes, within catalog	0

S2.15. Finite model / MHEALTH: One shared law and the exact Bellman construction

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Let P5 and P6 be the empirical laws assigning mass 1/n_g to each T row of group g. One unknown θ in[0,1] selects P_theta=θ P5+(1-θ)P6 for the whole episode. For an observed history h define m_g(h)=n_g(h)/ n_g and e_g(h)=number of cached-predictor errors at h divided by n_g. These are unnormalized endpoint masses. The STOP vector is(e5,e6); abstention is(2m5/5,2m6/5). Every vector v represents the affine loss θ *v5+(1-θ)*v6.

For a query q, add(m5/20,m6/20) to the sum of the two child lower envelopes evaluated at the same θ, then minimize across legal actions. Initial-root contributions are summed and initial cost(1/20,1/20) is added once. For F this entire root sum is computed for each global order before minimizing over orders. The group prior is never reset to1/2 after observing a history, and the adversary never maximizes independently at a node or branch.

Exact Fraction arithmetic partitions θ only at intrinsic intersections of candidate affine pieces. The resulting critical points are optimizer outputs, not a regularization or DEV tuning grid. Both global A and global F envelopes contain four pieces in this run. Each piece retains its feasible global forest witness, and the local certificates retain the tree witness for every interval.

Algorithm S3. Shared-Theta Exact Robust Bellman with a Frozen Full-Static Reference

Require: Pinned seven-mask predictor cache and T endpoint laws P5/P6; no C/DEV optimization inputs. Common support, two extra distinct queries, terminal STOP/A and losses1,2/5,1/20. Ten exante global prefix orders and deterministic tie rules.

Ensure: Full A/F rational lower envelopes with feasible tree/forest witnesses. Minimax A/F primal mixtures and dual theta; frozen full-F endpoint reference b. Direct paired-A mixture, uniform empirical endpoint improvement Gamma, and once-read expected C/DEV metrics.

1. Compute globally normalized per-group state/error masses n_g(h)/n_g and e_g(h)/n_g from T only.
2. Make STOP and abstention affine endpoint vectors; return canonical A at zero total T mass.
3. For every legal query, merge child piecewise envelopes at the SAME theta and add query cost times state mass; take exact lower envelopes with deterministic ties.
4. Sum both initial roots and initial quote. For F, perform this sum separately for each global order, then minimize across orders.
5. Maximize each concave envelope over its exact breakpoints. Recover at most two active GLOBAL forest witnesses and verify both primal endpoint inequalities.
6. Freeze the selected minimax-F endpoint b. Maximize V_A(theta)-theta*b5-(1-theta)*b6 directly, recover its primal mixture, and set Gamma to minus that value.
7. Require reference feasibility and Gamma>=0. Verify actual source-witness endpoint rollouts and the predeclared Tmean1361/6160 control; save/hash all T solutions and ties.
8. Only after that freeze, score C diagnostically and read DEV once. Report exact expectations over exante mixture draws without inventing integer randomized episodes.

9 In separate code enumerate all legal root programs, all adaptive global forests and each fixed global-order product. Check all-row dual bounds, all witnesses, local/global envelopes and every saved metric.

S2.16. Finite model / MHEALTH: Finite-class optimality and the paired certificate

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For fixed θ, a subtree contributes its unnormalized loss on rows consistent with its history. Children partition those rows, so additivity and finite backward induction prove that the Bellman lower envelope equals the minimum affine value over every legal contingent subtree. The same argument after the two-root sum proves the global A envelope. For each F order it proves that order's complete terminal grammar; minimizing after the sum proves the correct global-order class.

Let L_C be the finite set of endpoint loss vectors for class C. Allowing independent exante policy mixtures gives its convex hull. For any mixture, max_theta θ*J5+(1-θ)*J6=max(J5,J6). The finite zero-sum minimax identity therefore equates min over policy mixtures of their maximum endpoint loss to max_theta min_{v in L_C} θ*v5+(1-θ)*v6. A supporting line at the maximizing θ supplies active global witnesses. A supporting face in two endpoint dimensions is a line segment, so at most two witnesses suffice. The implementation additionally verifies nonnegative weights summing to1 and both endpoint inequalities exactly.

A policy selected by re-evaluating a kink or boundary with an arbitrary tie can have an unacceptable opposite endpoint. Recovery keeps the one-sided active affine-piece forests and admits a single forest only after its actual maximum endpoint equals the dual value. Otherwise it mixes opposite-slope active forests. In the actual A/F minimax games $\theta^\star$=0, and the chosen deterministic witnesses pass both endpoint inequalities. The paired game has an interior kink and uses two global witnesses.

Freeze b=(3/14,45/154), the deterministically selected full-F minimax reference endpoint. The paired game is min_pi max_g[J_g(pi)-b_g]. Its dual is max_theta[$V_A(\theta)$-θ*b5-(1-θ)*b6]. The A class can imitate each F forest and any exante mixture, so the zero-improvement reference is feasible and Γ cannot be negative. A negative result would block the claim rather than be repaired by replay. This run yields $\theta^\star$=162/1471, value=-2091/205940, and Γ=2091/205940.

The paired primal draws Tmean-A with probability421/1471 and the new robust-A forest with probability1050/1471. Its endpoint losses are42039/205940 and 638949/2265340. Subtracting b gives exactly(-Γ,-Γ). In contrast, the independent minimax-value difference is39/3080. That different number is preserved only as a diagnostic and is not substituted for the paired guarantee. The guarantee concerns the two empirical T laws and all their shared global mixtures, not unseen participants, each window or physical sensing.

S2.17. Finite model / MHEALTH: Exact grammar and no cross-root fixed-order adaptation

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A full binary-token depth-two root grammar with three first queries has2+3*(2+2*2^2)^2=302 trees before support pruning. Two roots give at most302^2=91,204 adaptive forests. For one length-two fixed order a root has2+(2+2^2)^2=38 possibilities; six directed pairs contribute6*38^2, three singletons contribute3*6^2, and empty order contributes2^2, totaling8,776 order-tagged forests before support pruning. Distinct terminal STOP and A choices are retained, including committed continuation choices. Zero-total-T states are canonically A and do not introduce favorable unseen-state choices.

The actual order-tagged F rows are formed by Cartesian products of root catalogs computed under the SAME order. An order minimizing separately at each root would be a larger information-adaptive class. The pre-seal counterexample uses two orders whose root losses are(0,1/2) and(1/2,0): the correct global order costs1/2, whereas illegally selecting after the initial root would cost0. This is not the strong F reference used here.

S2.18. Finite model / MHEALTH: Global-law and paired-objective counterexamples

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For a fixed forest with root contribution vectors(2/5,0) and(0,2/5), a single global adversary gives maximum total2/5. Maximizing independently per root gives4/5. The synthetic test demonstrates the different mathematical object obtained by rectangularizing the uncertainty. Bellman here always conditions and sums at one shared θ.

A second synthetic class has reference b=(1/5,2/5) and an adaptive candidate(3/10,3/10). Its separate minimax values differ by 1/10, but its direct paired Γ is0 because the reference itself is in A and the alternative

cannot improve group 5 uniformly. This counterexample guards against reporting a difference of unrelated worst cases as a paired guarantee.

Zero-mass, raw-child29 support, exact STOP/A ties, mask15, duplicate queries, third extra queries, nonbinary results, future-token leases, missing freeze, failure classes and read/write/time/rational guards are also tested. Final 39 tests pass before raw data access. One development negative test initially exposed a boundary-only subroutine accepting an infeasible affine line; explicit endpoint-vector membership was added before seal. The failed test and cause are retained in TESTS.json. There were no scientific main/oracle failures or retries.

S2.19. Finite model / MHEALTH: Exact law and state sufficiency

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For group g, every observed history contributes its raw count divided by the original group T denominator. Its STOP mass is the corresponding frozen-prediction error count divided by that denominator. Alpha combines those endpoint masses once globally. No inference step reintroduces a 1/2 local group prior.

The history records positions and token values only. Predictions are selected from the frozen cache at the acquired mask; policy construction does not use DEV labels. Per-window labels are used only for empirical training errors and later diagnostics. Raw support controls query rights and never becomes a population support guarantee.

The new derivation fixes the α/θ notation explicitly: α selects a canonical episode-wide one-step policy, whereas θ evaluates or adversarially weights endpoint losses after the complete policy class has been built. Raw support is assessed independently of α. The initial quote contributes (1/20,1/20) to every complete forest and is not repeatedly charged at each local subtree.

S2.20. Finite model / MHEALTH: Parametric completeness proof

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

At any state, STOP and A are affine in α. Each legal query is an affine quote cost plus two minima of affine child-terminal lines. Child terminal equalities split[0,1] into finitely many closed-boundary/open cells on which each query score is affine. Within such a cell, the ordering of two distinct scores can change only at their exact rational equality; coincident lines preserve the canonical tie order throughout.

The union of every local equality, child kink and α endpoint partitions the global domain. On each remaining open cell, every state action is constant. Evaluating all rational cuts separately includes point-only signatures created by exact tie order. This proves completeness of the specified M family. Supplementary quarter-point oracle checks are diagnostics and do not replace the analytic argument.

The main construction uses terminal-kink affine cells. The oracle instead enumerates all child STOP/A halfspace combinations, intersects their validity intervals, then enumerates every score-expression equality within overlapping domains. Their exact local cut sets and global signatures must agree.

The union cuts are 0, 162/1471, 276/1915, 174/955, 102/355, 13/35, 79/145, 69/124, 156/277, 204/347, 56/89, 195/283, 342/485, 87/109, 339/350 and 1. Sixteen exact points and fifteen open intervals give 31 atoms. Eleven distinct complete signatures survive. These are α construction cuts, not the six-interval θ comparison partition below. A point-only canonical action cannot be discarded merely because an adjacent interval has the same scalar optimized value.

S2.21. Finite model / MHEALTH: Grammar completeness and M inclusion

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

At each nonempty history, enumerate STOP and A plus every legal query and the Cartesian product of all complete child programs. Zero-totalT contributes only canonical A. The depth bound terminates recursion after two additional queries. By structural induction this lists all legal root programs; taking their Cartesian product lists all fullA forests.

For fullF, repeat the same recursion with the next position restricted to a single predeclared order. For each of ten orders, multiply both roots before taking the union. This prevents using the initial token or hidden group to choose an order. The oracle also directly rolls every root program through all compatible source windows.

Every M forest uses only observed history, permitted actions and the same remaining budget. Its root programs occur in the complete A list. Thus conv(M) is a subset of conv(A), so robustA cannot be worse than robustM and direct pairedA Γ cannot be below pairedM. Frozen b need not belong to M, so pairedM Γ may be negative.

There are 78 root-0 programs and 62 root-1 programs; their Cartesian product gives 4,836 adaptive forests. The ten F orders have 4,36,36,36,196,196,196,84,196,84 order-tagged forests, totaling 1,064. Order tags and structural duplicates do not create new participants or independent trials. The same original b forest, [[3,A,S], [3,S,S]], is used for every T/C/DEV comparison. The different-author review establishes b is not a member of M. The primary M optimization is not augmented with b to manufacture safety, and any negative Gamma_M would be retained.

S2.22. Finite model / MHEALTH: Direct paired objective and exact saddle certificate

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For a class X with endpoint rows v, minimize max(v5-b5,v6-b6) over independent exante mixtures. The dual is max over θ in[0,1] of min_v θ(v5-b5)+(1-θ)(v6-b6). This directly subtracts the same affine reference before maximization. Subtracting two independently optimized robust values generally answers a different question.

The lower envelope is concave and piecewise affine. A maximum occurs at an endpoint or a breakpoint, with a possible flat maximizer interval. We choose the smallest maximizing θ. Active rows satisfy exact all-row lower bounds. One feasible active deterministic row or a rational mixture of two active rows with opposite endpoint-excess slopes supplies primal endpoint upper bounds. Equality of primal and dual values proves the finite LP optimum.

The negative of that optimum is Γ. Ties and zero incremental values are no_gain. The certificate is about exact rational empirical losses; it contains no confidence interval, population extrapolation, novelty certification or model-performance claim.

The deterministic robust M/A witness is [[2,[1,S,A],S],[3,S,S]], with endpoints (377/1680,123/440), dual θ=0 and value 123/440. The paired M/A witness uses this forest at weight 1050/1471 and [[2,S,S],[3,S,S]] at weight 421/1471. Its endpoints are (42039/205940,638949/2265340), dual θ=162/1471 and dual value -2091/205940. Exact subtraction from b gives equal reductions 2091/205940. The respective all-row checks use 11 M rows and 4,836 A rows; the identical optimized scalar does not replace either check.

S2.23. Finite model / MHEALTH: Known-theta Bayes-risk algebra, six-piece static comparison and proof

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For a known empirical mixture P_theta=θ P5+(1-θ)P6, define $V_X(\theta)$=min_{v in X} θ*v5+(1-θ)*v6. Deterministic rows suffice for this fixed-θ linear minimum even though ex ante mixtures remain available. This $V_X(\theta)$ function differs from R_X=max_theta $V_X(\theta)$, and the directly paired objective is -max_theta[$V_X(\theta)$-θ *b5-(1-θ)*b6]. Neither maximization permits branchwise reselection of a group law.

Take the union of all frozen A/F/M envelope cuts in [0,1]: 0, 162/1471, 28/215, 13/35, 79/145, 538/615, 1. The six intervals in the table retain the actual active endpoint vectors in every class. At a shared endpoint the adjacent vectors can tie; the vectors need not be identical. F-minus-A is retained explicitly. It is positive before 79/145 and zero thereafter; M-minus-A is zero through 538/615 and positive afterwards. Both comparison boundaries are exact ties.

Proof on one interval [l,u]: the listed row is an actual feasible forest. For every same-class row w, the difference L_theta(w)-L_theta(v) is affine. If it is nonnegative at l and u, then its value at θ=(1-t)l+t u equals the corresponding convex combination of the endpoint differences and is nonnegative throughout. The stored algebra records 70,932 all-row endpoint inequalities: 6 intervals times 2 endpoints times (4,836+1,064+11) rows. Coverage of the full [0,1] union plus these inequalities proves the lower envelopes, including their boundaries. The separate different-author numerical review reconstructed the grammar and confirmed all six rows and the three regimes. The original algebra file's earlier pending-review sentence is a historical derivation-time statement, not a remaining claim that review39 did not occur.

On the final interval the M row is (37/280,967/3080) and the A/F row is (67/560,309/770). Their group-5 difference is 1/80; their group-6 difference is -269/3080. Hence M-minus-A equals θ/80-(1-θ)*269/3080=(615 θ-538)/6160. It crosses zero at 538/615. Before that crossing the previously listed M and A minima coincide, proving the clipped formula max(0,(615 θ-538)/6160). At θ=1 the gap is 1/80 exactly, not a newly measured sensor effect.

The first F-minus-A piece, 39/3080-(421/18480)θ, remains positive through its endpoint 162/1471. F then changes at 28/215 and 13/35; its last positive piece is 79/3080-(29/616)θ, whose zero is 79/145. The intervening second piece is 3/770+(5/88)θ and the third is (1-θ)/77. These pieces are compatible at every cut. The table therefore proves the three regimes without assuming F and M are nested: [0,79/145) has M=A<F; [79/145,538/615] has all tie; (538/615,1] has A=F<M.

A feasible final-interval forest is [[3,S,[2,S,S]],S], with a common order 3 then 2 and optional STOP. Both initial roots obey that order, so it is also F-feasible. The (43/280,116/385) witness queries token 2 in both roots; the (37/280,967/3080) witness queries 2 in root0 and STOPs in root1; b queries 3 in both roots. The two other A-active rows are the mean and robust M/A forests already given in M4 and M9. These actual witnesses prevent a numerical lower-envelope claim from being mistaken for an unattainable bound.

This is post hoc exact algebra on already frozen derived endpoint rows, after completion of the primary experiment. It is not a preregistered hypothesis, new training, raw-data experiment, new C/DEV score or new independent final. Equality of two optimized robust values does not establish full-hull equality; the strict final interval is a direct counterexample to such an inference. Completeness and the conditional proof remain restricted to the declared finite empirical law, canonical M family, support and cost contract.

Algorithm S4. Read a known-theta empirical class regime

Require: Frozen derived M/A/F endpoint rows, exact class membership and forest witnesses; a declared known empirical group weight theta in [0,1]. All envelope breakpoints, with endpoint convention V_X(theta)=min_v theta*v5+(1-theta)*v6.

Ensure: A feasible minimum row in each class, its exact Bayes risk, the three-class ordering and a stated scope of applicability. An explicit distinction between post hoc fixed-law algebra, the already completed robust games and any unrun application decision.

1. Take the union of frozen class-envelope cuts within [0,1]; do not refit predictors or choose theta from DEV outcomes.
2. For each resulting interval, retain actual feasible active endpoint rows and show their affine losses are no larger than every same-class row at both interval ends.
3. Use affinity to extend each inequality to the interval interior, checking exact ties at each shared boundary.
4. Subtract the active class lines to obtain M-minus-A and F-minus-A pieces; merge intervals only when the claimed ordering remains valid.
5. At a requested theta, return the witnessed class comparison with the common support, information and cost contract. Check whether a purported A advantage also beats full F.
6. Keep optimized minimax/direct-paired results separate. If the target law, physical costs, support or independent performance are unknown, retain the result as an empirical conditional calculation rather than activate a system.

$$V_M(\theta) - V_A(\theta) = \max\left(0, \frac{615\theta - 538}{6160}\right)$$

Exact post hoc finite empirical Bayes-risk relation; the last-interval A forest is also in F.

Table S8: Six exact affine intervals. Endpoints are group-5/group-6 losses; expression is valid on the entire listed closed interval with exact boundary ties.

Theta interval	A row	F row	M row	F minus A	M minus A
0 to 162/1471	377/1680, 123/440	3/14, 45/154	377/1680, 123/440	-421/18480 θ + 39/3080	0 θ + 0
162/1471 to 28/215	43/280, 111/385	3/14, 45/154	43/280, 111/385	5/88 θ + 3/770	0 θ + 0
28/215 to 13/35	43/280, 111/385	43/280, 116/385	43/280, 111/385	-1/77 θ + 1/77	0 θ + 0
13/35 to 79/145	43/280, 111/385	37/280, 967/3080	43/280, 111/385	-29/616 θ + 79/3080	0 θ + 0
79/145 to 538/615	37/280, 967/3080	37/280, 967/3080	37/280, 967/3080	0 θ + 0	0 θ + 0
538/615 to 1	67/560, 309/770	67/560, 309/770	37/280, 967/3080	0 θ + 0	123/1232 θ + -269/3080

Table S9: Concrete feasible A forest for every endpoint row used above. S is STOP and A is abstain; the explicit F witnesses and common orders are stated in the adjoining proof.

Endpoint row	Feasible forest	Scope
377/1680, 123/440	[[2,[1,"S","A"],"S"],[3,"S","S"]]	A; F membership as specified in text
3/14, 45/154	[[3,"A","S"],[3,"S","S"]]	A; F membership as specified in text
43/280, 111/385	[[2,"S","S"],[3,"S","S"]]	A; F membership as specified in text
43/280, 116/385	[[2,"S","S"],[2,"S","S"]]	A; F membership as specified in text
37/280, 967/3080	[[2,"S","S"],"S"]	A; F membership as specified in text

Endpoint row	Feasible forest	Scope
67/560, 309/770	[[3,"S",[2,"S","S"]],"S"]	A; F membership as specified in text

S2.24. Finite model / MHEALTH: How to use the conditional result and when to stop

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

First declare the question. For an unknown shared T-group mixture, use the already certified minimax or directly paired objective and its full ex ante policy mixture. Both matched planning increments are zero. For a separately justified known empirical mixture, use $V_X(\theta)$ and the complete F/M/A regime table. A θ supplied by a real application would need its own justification; the current frozen T hull is not a verified population ambiguity set.

At execution, read only the observed token positions/values and frozen table. Test raw support at the parent and every positive-T child before a purchase. If acquisition is unsupported, retain STOP and abstention; a zero-total-raw-T history canonically abstains. Otherwise STOP uses the frozen predictor at the current mask, and A costs 2/5 without claiming a correct prediction. The remaining rights permit at most two additional distinct tokens and never mask15. These rules are common across M, A, full F and forced-order fallback.

For $\theta<79/145$, both M and A attain a smaller known-law loss than F, so deeper planning has no additional value over M there. In the all-tie interval use the equality honestly; an optimization tie is not an improvement. For $\theta>538/615$, deeper lookahead can beat this M family, but the same minimum is available from F's order 3 then 2. The strongest static witness must therefore accompany any suggested use of A. None of these choices is an authorization to deploy or replace a current system.

Stop a broader performance claim when the target law is unsupported, no unexposed final block exists, a cost or failure denominator is missing, a comparator's rights differ, or the completed result ties its matched objective. Preserve failed, exhausted, unknown and unstarted cells rather than converting them into a successful mean. A future prospective benchmark should predeclare one practically meaningful paired participant-level endpoint, coverage/harm constraints and attempted-purchase cost including failures and delay, then compare faithful strong static and modern controls before evaluating new labels.

The bounded literature review is separate evidence. Its eight targeted records and two failed direct opens do not certify exhaustive priority, full theorem equivalence or external reproducibility. NM-PPG and BRiG-AFA abstract overlap motivates a deeper comparator/proof review. It does not allow importing authors' external scores into RF tables. A general characterization of equality or separation between canonical M and deeper planning remains a proposed theoretical direction; the present empirical three-regime calculation is not such a general theorem.

S3. Strong fixed baselines, joint worlds and common randomized coverage

The common actor cannot observe a world index or an unbought response. Static and adaptive comparators receive the same independent root coin, stopping, terminal and coverage rights. The constructions below distinguish a fixed reference, a world-specific best-fixed envelope and one common feasible policy. All theorem numbers inside a retained derivation are local to that derivation.

S3.1. Best-fixed benchmark: Common-law comparison and information authority

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

Write J_P(pi) for expected error plus abstention and attempted-query cost under one joint law P. Let F be the complete fixed-order class and A the class that additionally chooses a query identity after observing the free history. Both classes may stop, predict either binary label, abstain, and randomize before an episode. For a frozen reference b, the reference-safe set is {pi: sup_P[J_P(pi)-J_P(b)]<=0}. The best-fixed-safe set is {pi: sup_P[J_P(pi)-min_(f in F)J_P(f)]<=0}. The latter equals the intersection of the former sets over every f in F, with the same P on both sides. It can be empty even though every reference-safe set separately contains its own reference.

The law-specific minimum is an evaluation oracle, not a deployable baseline selector with free knowledge of P. A TRAIN-selected baseline is another legitimate comparator, but its selection uses only the declared TRAIN/TUNE evidence. Reading unbought target features, target labels, future failures or a hidden law identifier to choose the baseline grants extra information. Any acquisition made to learn which baseline to use must be paid and given to all methods on equal terms. The theorem concerns a frozen single-episode rule, with no earlier target-label observations or interepisode learning.

Here the only permitted pre-episode evidence has the same distribution under P_0 and P_1: it is a fixed declared contract plus freeR,with no target-label sample,unbought feature values or endpoint-informative training sample. This is the actual observational-equivalence condition for the model. Merely naming an uncertainty set would not establish partial identification; informative labeled training data or paid calibration can shrink the set and changes this result.

Algorithm S5. Certify the requested comparator before deploying an acquisition policy
Require: A common joint-law uncertainty set, finite complete policy grammars, terminal/observation permissions and paid-attempt costs. A comparator request: one frozen reference, a TRAIN-selected baseline, or every fixed policy; uniform estimation-error bounds if losses are estimated.
Ensure: A policy and a common-law contrast certificate with the precise comparator scope, or infeasible/unknown/invalid. All policies, witnesses, costs, failed constraints and uncertainty assumptions; no silent abstention fallback.

1. Freeze the allowed histories, predictor, costs, fixed-order stopping rights, query budget and baseline-selection information.
2. Construct every policy's loss from the same joint law; retain duplicate policy identities in raw output.
3. For a selected reference subtract its same-law loss vector. For best-fixed safety impose a contrast constraint for every fixed policy and every possible law.
4. If inputs are estimated, use a jointly valid law/confidence set or add the simultaneous contrast-error margin before selecting the candidate.
5. Solve the declared robust contrast problem; check every original row against a dual lower witness and the returned mixture against every constraint.
6. Return infeasible if the best-fixed minimax regret is positive. Retain a selected reference only for the weaker selected-reference contract; abstain only if its full cost and any coverage restriction meet the requested contract.
7. Keep external data/algorithm reproduction and general novelty pending until their separate acceptance conditions are met.

S3.2. Best-fixed benchmark: A paid perfect observation and the exact feasibility boundary

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

Choose 0<a<1/2, 0<q<=1/2 and c>=0. There are two possible laws P_z, z in {0,1}. A free route R is fair. Independently, Y equals z with probability 1-a, and an independent bit U is fair. Set X_R=Y and X_(1-R)=U. Only R is initially visible. One query reveals one X_j and costs c; a wrong prediction costs1 and abstention costsq. Fixed policies precommit j before seeing R but may stop on either R branch and may map a queried bit to any terminal. Adaptive policies may choose j after R. All have query budget1. The

identification set is conv{P_0,P_1}; the permitted free observations have exactly the same distribution under both endpoint laws.

Theorem 1. Put s=min(a,q). The strongest fixed minimax loss is V_F=(min(c,q)+q)/2. The adaptive minimax loss is V_A=min(c,q). At each endpoint, the best fixed loss is v_F=(min(c,s)+s)/2. Consequently the minimum worst-law regret against all fixed policies is R*=min(c,q)-(min(c,s)+s)/2. Its feasible set is nonempty if and only if c<=a or q<=a. This statement allows all ex ante randomization, not just pure policies. Full proof, including the two boundary equalities, appears in Supplement S3.7 through Supplement S3.9.

In the region a<c<q, routing-based acquisition strictly improves the strongest fixed minimax reference by (q-c)/2, but R*=c-a>0. Thus even perfect information about the current label cannot make the stronger comparator requirement feasible once its price exceeds the oracle static error. Conversely, c<a permits a genuine all-fixed-safe acquisition, and q<=a makes abstention an admissible common fallback. Abstention at a larger q is not such a fallback. A separate positive-coverage requirement can remove the all-abstain witness and changes the feasible set.

The query budget is1. This example isolates observation-dependent query identity and comparator-relative safety; it provides no evidence of nonmyopic or multistep planning superiority. A greedy rule with the same correct model can choose the matching query as well.

$$V_F = \frac{\min(c, q) + q}{2}, \quad V_A = \min(c, q)$$

Complete fixed/adaptive minimax values in the routed one-query model; all costs are normalized mathematical losses.

$$s = \min(a, q), \quad v_F = \frac{\min(c, s) + s}{2}, \quad R^\star = V_A - v_F$$

The endpoint best-fixed oracle is symmetric. R* may be negative when adaptive acquisition uniformly beats every fixed policy.

$$V_{\mathcal{F}} = \frac{\min(c, q) + q}{2}, \quad V_{\mathcal{A}} = \min(c, q)$$

Strongest fixed minimax and adaptive minimax losses for this single-query construction.

$$s = \min(a, q), \quad v^\star_{\mathcal{F}} = \frac{\min(c, s) + s}{2}$$

The best fixed loss at either endpoint law. This law-wise oracle is an evaluation comparator, not information supplied to the deployed policy.

$$R^\star = \min(c, q) - \frac{\min(c, s) + s}{2}$$

Minimum worst-case regret against every fixed policy. Safety is feasible exactly when c ≤ a or q ≤ a in the declared domain and without an added coverage restriction.

S3.3. Best-fixed benchmark: Exact counterexample and computational evidence

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

At a=1/10,c=1/5,q=2/5, constant prediction0 has losses (1/10,9/10), constant1 has (9/10,1/10), and full abstention has (2/5,2/5). A fixed policy that queries0 at R=0 and abstains at R=1 has losses (3/10,3/10). It is a strongest fixed minimax reference, not an intentionally weak baseline. The adaptive rule queries X_R and predicts that bit, giving (1/5,1/5). Its same-law reference improvement is (1/10,1/10), while its best-static regret is (1/10,1/10). No alternative adaptive mixture can reduce the worst regret below1/10.

Fresh standard-library code explicitly enumerates 12 branch actions for each precommitted index and hence 2*12^2=288 fixed policies, and 21 branch actions and hence21^2=441 adaptive policies. It evaluates the eight positive atoms of each endpoint exactly, solves the two-column mixture problem, and verifies the θ =1/2 dual inequality for every original row. All ten independent hand/negative-control tests and all nine locked boundary cases pass. Raw row identities, endpoint fractions, witness mixtures, per-case formulas and actual commands are retained. These counts are finite arithmetic checks, not independent data samples or a benchmark success rate.

S3.4. Best-fixed benchmark: Robust constraints after baseline selection and estimation

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

For finite law vertices P_j and fixed baselines f, let D_(i,j,f)=J_(P_j)(a_i)-J_(P_j)(f). Best-fixed certification requires sum_i w_i D_(i,j,f)<=0 for every(j,f), w in the simplex. The optimum r*=min_w max_(j,f)sum_i w_i D_(i,j,f) has the standard minimax dual max_lambda min_i sum_(j,f)lambda_(j,f)D_(i,j,f). A positive dual lower witness separates the entire candidate simplex from the feasible set; adding a selected-reference fallback cannot defeat that witness. This is ordinary finite-game duality, not a new LP principle. The routed theorem supplies an explicit complete-policy instance with both strict selected-reference improvement and positive all-fixed regret.

Suppose a data-dependent common joint-law set U_hat covers P* with probability at least1-δ and the computed contrasts are exact on U_hat. Any data-dependent choice satisfying all baseline constraints on U_hat is then safe against min_f J_(P*)(f) on that event. No extra post-selection assumption is needed when that single coverage event is uniform over the permitted policies, baselines and shared predictor. A confidence interval for one prespecified baseline alone does not supply this event after a larger menu is searched.

For a finite matrix with simultaneous |L_hat-L|<=epsilon on all candidate and baseline entries, the true contrast is at most the estimated contrast plus2epsilon, since a convex mixture of candidate errors has magnitude at mostepsilon. Therefore an estimated all-fixed maximum<=-2epsilon suffices. The exact all-fixed optimum changes by at most2epsilon under that entrywise error bound. This result is only conditional on a valid simultaneous event; it does not derive a distribution-shift radius from unlabelled observations. Direct paired-difference bounds can be tighter because they retain shared-predictor cancellations.

S3.5. Best-fixed benchmark: Computed boundary of comparator safety

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.




Figure S7: Exact results for the constructed two-law model with a=0.1 and abstention cost q=0.4. Markers are predeclared computed cases; connecting lines guide the eye. The comparator changes the safety conclusion. These are theoretical examples, not measurements on sensor data.

S3.6. Best-fixed benchmark: Full model, rights and trusted assumptions

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

Each P_z has eight atoms indexed by(r,y,u). Their probabilities are (1-a)/4 ify=z and a/4 otherwise; X_r=y and X_(1-r)=u. For everyz, P_z(R=r)=1/2. The model itself, the absence of a hidden free channel, the stable query semantics and the cost ledger are assumptions. The only initially acquired data are R. The common law applies to all policy losses in a contrast and throughout each episode. Averaging endpoint laws for a dual argument does not permit changing the endpoint after observing a branch.

A terminal is0,1 orA. A query branch consists of a query index and any of the3^2 terminal maps of its returned bit. A fixed rule choosesj beforeR; eachR branch may independently choose one of3 immediate terminals or9 query maps, hence288 identities including duplicates. An adaptive branch additionally chooses between

both indices, hence3+2*9=21 actions and441 identities. Zero-query policies, all-abstain rules, acquired-bit-dependent abstention, stopping atR, and ex ante randomization are included for both classes. Acquisition is charged even when followed by abstention.

This fixed-order definition permits observation-dependent stopping but forbids a free post-R change of the first query identity. If a purported fixed comparator may skip any earlier coordinate for free based onR and then buy a later coordinate, it can imitate this routed adaptive policy; the class distinction and formulas must then be recomputed. Likewise, interepisode learning ofz, a different shared predictor, additional budgets, hidden target metadata or physical query failures define different problems.

S3.7. Best-fixed benchmark: Proof of the law-specific best fixed value

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

Fix endpointz and one precommitted queryj. On eitherR branch, stopping with labelz has errora, stopping with1-z has error1-a>a, and abstaining costsq. The best immediate terminal therefore has losss=min(a,q). AtR=j, querying revealsY without error; since no terminal has negative loss and predicting the returned bit gives terminal loss0, the best query has total lossc. The branch optimum is min(c,s). AtR!=j, the only purchasable bitU is independent ofY, so it cannot improve on the best immediate terminal: any deterministic map ofU is a mixture of immediate terminals in expected loss and additionally paysc. The branch optimum remains s. Each branch has mass1/2, givingv_F=(min(c,s)+s)/2.

This lower bound applies to every deterministic fixed policy, including branch-dependent stopping and bit-dependent abstention, and is attained by querying only the matching branch ifc<s and taking an optimal immediate terminal otherwise. Both choices ofj have the same value. A mixture cannot improve a scalar law-specific minimum because its loss is a convex combination. This proves the claimed oracle value for the complete fixed class, not only for the two constant-prediction baselines.

$$V_{\mathcal{F}} = \frac{\min(c, q) + q}{2}, \quad V_{\mathcal{A}} = \min(c, q)$$

Strongest fixed minimax and adaptive minimax losses for this single-query construction.

$$s = \min(a, q), \quad v^{\star}_{\mathcal{F}} = \frac{\min(c, s) + s}{2}$$

The best fixed loss at either endpoint law. This law-wise oracle is an evaluation comparator, not information supplied to the deployed policy.

$$R^{\star} = \min(c, q) - \frac{\min(c, s) + s}{2}$$

Minimum worst-case regret against every fixed policy. Safety is feasible exactly when c ≤ a or q ≤ a in the declared domain and without an added coverage restriction.

S3.8. Best-fixed benchmark: Proof of both minimax values, including every mixture

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

Use the common dual law P_bar=(P_0+P_1)/2. Under this lawY is fair and independent ofR, andU is independent ofY. Before querying, the best immediate terminal costsq becauseq<=1/2. AtR=j, a fixed indexj may obtainY perfectly at costc, so the branch Bayes loss ismin(c,q). AtR!=j, querying onlyU cannot reduce Bayes error; abstention achievesq and any useless query adds nonnegativec. Thus every fixed deterministic policy has P_bar loss at least(min(c,q)+q)/2. The average of its two endpoint losses equals its P_bar loss, so its worst endpoint loss is at least that quantity. The same lower bound holds for every ex ante mixture by linearity.

For attainment, choose any fixedj; query and predictX_j onR=j ifc<q, and abstain onR!=j. Ifc>=q, abstain on both branches. This fixed rule has equal losses(min(c,q)+q)/2 at both endpoints. Lower and upper bounds agree, proving V_F.

For adaptive policies, P_bar again yields a branch lower boundmin(c,q): one can either abstain atq or payc to revealY through the matching coordinate. A mismatched query cannot do better, and every prediction without a query has expected error1/2. No mixture can evade this lower bound. QueryX_R and predict it whenever c<q, otherwise abstain. This rule has lossmin(c,q) under each endpoint law. Therefore V_A=min(c,q).

S3.9. Best-fixed benchmark: Proof of all-fixed regret and the if-and-only-if boundary

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

For any pi, g(P)=J_P(pi)-min_f J_P(f)=max_f[J_P(pi)-J_P(f)] is convex inP because every contrast is linear in the sameP. On conv{P_0,P_1}, its supremum is therefore the maximum of its endpoint values. At either endpoint the fixed oracle value is the samev_F fromS1. Hence min_pi sup_P g(P)=min_pi max_z J_(P_z)(pi)-v_F=V_A-v_F, proving R*=min(c,q)-(min(c,s)+s)/2.

Ifq<=a, thens=q. Ifc<q, R*=(c-q)/2<0; ifc>=q, R*=0 and abstaining is a common best-fixed policy. Ifa<q, thens=a. Forc<=a, R*=(c-a)/2<=0; forc>a, R*=min(c,q)-a>0 becausebothc andq exceeda. These cases cover the entire declared domain and show nonempty feasibility exactly whenc<=a orq<=a. Atc=a<q there is equality, not a strict gain; atq=a andc>=q the abstain witness has equality. No additional mixing or randomized choice changes these conclusions.

In particular, ifa<c<q, the fixed minimax witness inS2 has value(c+q)/2 and the routed witness has valuec, for a strict same-law reference gain(q-c)/2. But every adaptive policy has worst all-fixed regret at leastc-a>0. At least one endpoint must harm a law-specific best-fixed rule. Here the routed minimax witness harms both. A selected-reference-safe algorithm may therefore be mathematically correct and still fail the stronger best-static request.

S3.10. Best-fixed benchmark: Hand-reproducible primary-case table

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

All entries below usea=1/10,c=1/5,q=2/5; tuples list(P_0,P_1) losses. Constant0:(1/10,9/10). Constant1: (9/10,1/10). Abstain:(2/5,2/5). Fixed query0 atR=0 then predict the observed bit, abstain atR=1: (3/10,3/10). Fixed query0 atR=0 then predict the bit, predict0 atR=1:(3/20,11/20). Query0 at both routes and predict that bit:(9/20,9/20). Adaptive queryR and predict the bit:(1/5,1/5).

For example the fixed query/abstain value is(1/2)(1/5)+(1/2)(2/5)=3/10. The fixed query/predict0 value underP_0 is(1/2)(1/5)+(1/2)(1/10)=3/20; underP_1 it is(1/2)(1/5)+(1/2)(9/10)=11/20. In the always-query0 policy, half the queries revealY and half reveal an independent fair bit, so total loss isc+(1/2)(1/2)=9/20. These are exact expected losses of constructed laws, not measured errors on people.

S3.11. Best-fixed benchmark: Nine predeclared cases and full raw evidence

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

The case list ininputs.json was fixed before execution. For(a,c,q), the tuple below is(V_F,V_A,v_F,R*). (1/10,0,2/5):(1/5,0,1/20,-1/20). (1/10,1/20,2/5):(9/40,1/20,3/40,-1/40). (1/10,1/10,2/5):(1/4,1/10,1/10,0). (1/10,1/5,2/5):(3/10,1/5,1/10,1/10). (1/10,2/5,2/5):(2/5,2/5,1/10,3/10). (1/10,3/5,2/5):(2/5,2/5,1/10,3/10). (2/5,3/5,1/5):(1/5,1/5,1/5,0). (1/5,3/5,1/5):(1/5,1/5,1/5,0). (1/4,1/5,1/2):(7/20,1/5,9/40,-1/40).

raw_results.json contains every primary fixed/adaptive policy identity and both exact fractions, plus the minimax witnesses, formula values, dual row counts/slacks and all boundary outcomes. EXECUTION.json retains original commands, exits, stdout/stderr and the failed broad exposure query. The theorem is proved analytically for the parameter domain; these nine examples corroborate the implementation rather than prove a continuum by sampling. The primary case is also present in the nine-case table by design and is not counted as a new independent experiment.

S3.12. Best-fixed benchmark: Solver correctness and complexity

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

ForN risk rows with two law columns, a minimax mixture has a pure or two-row optimum. The epigraph LP minimizesv with sum_i w_i=1,w_i>=0 and two risk inequalities. An extreme optimum withs positive weights hass+1 active variables and at most normalization plus two independent risk constraints, hences<=2. The code tests all pure rows and every valid pair weight making its two endpoint risks equal, and retains exact duplicate identities in the raw file. Pairs with zero denominator or an intersection outside[0,1] supply no interior candidate. Every candidate is feasible for the simplex.

An exact dual weighttheta=1/2 is available fromS2. The code independently evaluates all288/441 original row means and checks their slack against the analytic lower values. A returned feasible mixture attaining that dual value certifies the finite optimum; rows omitted only as exact risk duplicates during pair search remain

in the dual check. Best-fixed regret subtracts the per-endpoint oracle vector and repeats the same solve. The explicit primary check also maximizes the contrast over all288 fixed rows at each endpoint.

ForH free histories,Q query choices,K response values andT terminals under one-query budget, the branch action count isT+Q*T^K and deterministic adaptive policy count isN=(T+Q*T^K)^H; the fixed count here isQ*(T+T^K)^H. Atom evaluation takesO(N*W*S), withW law vertices andS atoms. The two-world candidate search takesO(N^2) rational arithmetic operations andO(N) stored risk rows apart from raw policy descriptors. GeneralW or added constraints require a general robust LP; the two-row claim does not extend automatically. Fraction bit length and exponential grammar growth are real costs, not hidden constants of a scalable application. Measured process wall/CPU cover this local calculation only; native authoring, whole host and physical I/O costs are unknown.

S3.13. Best-fixed benchmark: Proof of the simultaneous estimation statements

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

LetE={P* in U_hat}. OnE, every certified inequality sup_(P in U_hat)[J_P(pi_hat)-J_P(f)]<=0 impliesJ_(P*)(pi_hat)<=J_(P*)(f). Intersecting over everyf yields safety against the best fixed policy atP*. The argument holds even whenpi_hat and the selected comparator were chosen using the same data becauseE controls one common law and every allowed choice, not a single pointwise contrast chosen before seeing data. SincePr(E)>=1-δ, the conclusion has that probability. If a learned predictor is used, either the event covers its induced joint losses uniformly or an independent fitting/calibration construction must justify the conditional event.

On a simultaneous finite-matrix event, |sum_i w_i(Lhat_ij-L_ij)|<=sum_i w_i epsilon=epsilon for every probability vectorw. Also|Lhat_fj-L_fj|<=epsilon, so each estimated candidate-minus-baseline contrast differs from truth by at most2epsilon. Takingmax over(j,f) preserves the error bound, and takingmin overw preserves it again. ThusR_true(w)<=R_hat(w)+2epsilon and|r*_true-r*_hat|<=2epsilon. A negative estimated contrast without the margin is insufficient: Lhat_candidate=.19,Lhat_baseline=.22 appear safe, but true values.21,.20 within epsilon=.02 reverse the ordering. The+2epsilon check rejects this example.

Baseline selection error has to be separated from the all-fixed oracle. If TRAIN selectsb_hat with J_(P*)(b_hat)-min_f J_(P*)(f)<=η, then reference safetyJ(pi)<=J(b_hat) gives at mosteta oracle regret, not zero. A claimed zero-oracle-regret guarantee needs a negative reference margin at leasteta or the direct all-baseline constraints. Without a valideta bound, the selection step remains an information/estimation gap. No distribution-free argument from unlabelledR alone identifies the endpoint in this model.

S3.14. Best-fixed benchmark: Concrete external execution contract and its remaining gates

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

The contract file preserves the design frozen before the theory calculation. WISDM's proposed51 eligible people split25TRAIN/8TUNE/8CALIBRATION/10FINAL, and WESAD's15 split7/2/2/4. Subject IDs are ordered by SHA256 of the fixed string prefix and dataset/ID; only a separate custodian may establish eligible unexposed identities. A different count requires a new pre-value-access contract. Windows are nonoverlapping5seconds, with all windows for one person kept together. WESAD's very small final split cannot support the planned competitive claim. Official metadata counts alone do not establish complete usable sensor alignment or eligibility.

The primary objective is subject-macro wrong_nonabstaining_fraction+(2/5)*abstention_fraction+(1/20)*attempted_query_count. WISDM has at most3of4 block queries and41 fixed order prefixes including no query; WESAD has at most1of2 device queries and3 prefixes. Every order may stop on observed history and abstain, while changing a fixed order after seeing observations is disallowed. One shared per-mask predictor gives identical predictions for the same episode/history. The separate full-system SEFA/L2M rows may use their own predictors but cannot attribute their predictor advantage to query selection.

Before any execution, the next Task must freeze the exact32 stop/gain configurations rather than interpret 'at most32 prelisted' as permission to tune adaptively. A concrete proposed grid is early-stop confidence{0,.5,.6,.7,.8,.9,.95,1} crossed with estimated one-step J-gain{0,.01,.025,.05}, with terminal predict iff max_probability>=.6 and otherwise abstain. Any method-specific score transformation must be fixed onTRAIN/TUNE and labeled as an adaptation; published SEFA latent scores are not already J-gains. This grid is a proposed next-execution binding, not a claim that published implementations or a32-configuration benchmark were run here.

Use the same TRAIN/TUNE/CALIBRATION access, seeds6101/6102/6103 and at most32 configurations per method, no FINAL tuning, fixed L2=1 masked logistic predictor with max_iter1000 for the primary acquisition comparison, and all predictor/MC calls and training resources logged. Paper-faithful official baseline code, its configuration, any pretrained checkpoint/data rights, multiclass support and installed environment compatibility must be reviewed and hashed first. No cloned repository, trained checkpoint or reproduced external result is claimed by this author.

All passive replay query charges are simulated, not sensor energy or provider fees. Time alignment and observed missing blocks must be counted separately from seeded simulated attempt failures{0,.1,.3} and delays{0,1,2}windows. Attempts still consume budget and charge1/20. Future availability is not visible before an attempt. Report subject-macro objective, conditional error and its accepted denominator, coverage, per-subject harm, unsuccessful attempts, unsupported histories, p50/p95 replay wall time, process memory, model bytes and training CPU/wall. Zero accepted count gives null conditional error.

For independent subject-level differences in[-M,M],M=1+budget/20, a simultaneous one-sided Hoeffding upper bound forK fixed comparisons is mean_diff+2*M*sqrt(log(K/.05)/(2*n)). It targets the subject population only under independent, suitably representative subject sampling. At n=10,K=3,budget3 the added margin exceeds1, so this conservative gate can be uninformative; it is an honest no-go outcome, not an instruction to discard the strongest controls. A subject bootstrap with10000 resamples andseed6101 is descriptive. Seeds and windows do not multiplyn.

A competitive claim requires pre-governed FINAL eligibility, all final people completed, a negative corrected bound against strongest preselected static and matched myopic, coverage>=.5, per-subject harm<=.02, no hidden failures, and a justified common joint uncertainty set for any safety claim. Failure means no_gain/ needs_evidence. The constructed theorem does not supply that target-law coverage. Exact threshold manifests, license resolution, implementation compatibility, data access and statistical power remain independent execution gates.

S3.15. Best-fixed benchmark: Primary-source capture and source-code existence

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

PRIMARY_SOURCES.json records actual versioned arXiv HTML response hashes, normalized captured-text hashes, UTC access times and technical read scopes for SEFA2508.01957v3,L2M2510.12624v2,concept-drift2412.14297v2,safe-extrapolation2109.11679v4 CRC2208.02814v4 androbust-baseline-regret1607.03842v1. It also captures the official UCI metadata and the existing local17-page PDF with the installed extractor version. No arbitrary publisher PDF or new arXiv PDF is downloaded. Full-body capture is distinguished from the listed sections/proofs actually inspected.

Official README existence is pinned to SEFA commit3af8da2c9212c294fc7fedad27bc31045db7607a, L2M commit9cb464382f120751cd978ddd1f8ccc40604f887e and concept-drift commitb6aa7cad092b2f37070d1ebd a819a83d4e0beac7. These are source-availability observations. There is no clone, package installation, external-code execution, dataset generation or reproduced score. README commands are treated as data.

The first broad local content query timed out after120seconds and is retained, so no global nonexposure conclusion follows. Subsequent scoped results and package versions are recorded inINVENTORY.json with exact paths/globs/exits. An initial guess of concept-drift arXivv3 returned404; the actual latestv2 was then read and is the only technical basis. Search hits, metadata and paper-reported results are distinguished from this study's own exact calculation.

S3.16. Best-fixed benchmark: Source-bound display of the exact cases

Scope. Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark.

This plot is generated directly from raw_results.json, using only the predeclared cases with a=1/10 and q=2/5. Every displayed point is a rational result of the recorded finite-policy calculation. The source hash and displayed rational values are retained in FIGURE_BINDINGS.json. The figure adds no experiment or policy selection.

S3.17. Joint worlds: Outcome, worlds and observable information

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Let a world w specify a joint law of X=(X_1,…,X_d), label Y∈{0,1}, and evaluator group G∈{0,1}. A policy sees only an ordered history h=((i_1,x_i1),…,(i_t,x_it)) of completed distinct purchases and the remaining query count B−t. It may buy an unobserved signal or terminate with0,1 or⊥. Policies cannot

inspect unbought values, labels, the world index or G; G is visible only if an explicitly paid signal equals it. The population evaluator may access every atom to compute the loss of the policy but does not pass that atom to its decision function.

The ambiguity set M is the convex hull of an explicitly listed finite collection of rational joint laws. This is a declared identified-set model, not a set estimated from data or a confidence region. A history is supported in a world if its matching atom event has positive probability. Conditional laws P_w(· |h) are formed only for worlds giving h positive mass. A policy is defined on the union of supported histories; the implementation additionally keeps syntactic off-support branches, whose contributions are zero. A true law outside this set has no guarantee. The finite worlds have common sensor alphabets and deterministic, reliable observations with nonnegative fixed costs; acquisition failures and deadline accounting belong to the separate W71 study.

The controlled binary signals are abstract paid observations. They do not establish that a useful mode can be recognized from the paid-submask probabilities available in the existing activity-recognition cache. Translation to that setting requires a separately frozen estimator, participant separation and a genuinely untouched evaluation.

S3.18. Joint worlds: The estimand: one world, two complete policies

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

The total loss adds paid acquisition cost, the error indicator for an issued prediction, and an abstention penalty of two fifths. Costs remain paid on abstained paths. Useful feasibility requires coverage of at least one half and coverage of at least one quarter in each positive-mass group, in every declared world. The separate unconstrained regime includes all-abstain, with loss 0.4 and zero coverage. No randomization is supplied to a feasible policy.

For complete policies pi and b, identify D_w=J_w(pi)−J_w(b) and the interval [min_w D_w,max_w D_w]. The comparison uses the same joint law, including its dependence between future observations and labels. It is an expectation difference; paired atoms are useful bookkeeping, but its expectation depends only on the two policy risks under the same distribution. It is not a causal claim about two physically observed sensor trajectories.

Proposition1. If the actual evaluation law belongs to M and pi,b are fixed before evaluation and obey the observable input contract, max_w D_w<=−epsilon implies J_true(pi)<=J_true(b)−epsilon. For the convex hull of the finite vertices, endpoints occur at vertices because D is linear in the world. Conversely, a strictly positive vertex difference disproves a uniform noninferiority guarantee over that set. The statement is necessary and sufficient for the declared set, not evidence that a fitted set contains the population. If inclusion is established with probability1−α by another valid procedure, the implication holds on that inclusion event; this study estimates neither α nor an inclusion probability.

$$L_\pi = \sum_i c_i \mathbf{1}\{\pi \ \text{ buys } \ i\} + \mathbf{1}\{\text{wrong prediction}\} + \frac{2}{5}\mathbf{1}\{\text{abstain}\}$$

The indicator terms are evaluated on the same full atom; the deployed tree only sees purchased observations.

$$J_w(\pi) = E_w + \text{purchase cost}_w + \frac{2}{5}(1 - C_w)$$

Here E denotes wrong issued predictions divided by all cases, and C denotes coverage.

$$D_w(\pi, b) = J_w(\pi) - J_w(b), \quad D \in \left[\min_w D_w, \max_w D_w\right]$$

Both complete policies are evaluated under the same joint world.

S3.19. Joint worlds: Strong static comparison and the certificate

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Let B_F be every complete fixed-order policy in F(M). A fixed order is a permutation of the available signals, but the policy may stop after any observed prefix, choose any terminal label or abstain, and use all already bought values. Thus B_F contains every fixed subset with every terminal decision map. A fixed subset itself always buys its declared subset and then terminates; its terminal map is equally unrestricted. All methods share costs, query budget, terminal actions and observable values. The oracle that sees Y and obtains loss0 is listed separately and is not a deployable baseline.

Define the signed static-envelope excess as the largest same-world difference between the candidate and the best member of the common jointly feasible fixed-order class. It can be negative because the adaptive class is larger; conventional regret against a class containing the candidate cannot be negative. An excess at most

minus epsilon is equivalent to beating every feasible static policy in every declared world by at least epsilon. A single fixed reference can be audited by its own largest same-world difference. Comparator feasibility is defined jointly for the same set, rather than separately within each world.

Minimizing R_B is an ex-ante decision criterion, not an unconditional safety promise. When its optimum is positive, no member of this deterministic class dominates the complete static envelope; the reported optimizer receives no certificate. Minimax absolute J and minimax signed excess can select different policies. In the enlarged unconstrained case, the latter selects a one-signal policy with losses(0.33,0.48,0.33); all-abstain has(0.40,0.40,0.40). The chosen policy has the smaller maximum excess to the varying static envelope, but the larger worst absolute loss. A deployment rule must therefore specify its reference and refusal condition before applying the word safe.

$$R_{\mathcal{B}}(\pi) = \max_{w}\left[J_w(\pi) - \min_{b\in\mathcal{B}_F} J_w(b)\right]$$

The comparator family contains complete fixed orders with observation-dependent stopping and terminal decisions.

$$R_{\mathcal{B}}(\pi) = \max_{w,b\in\mathcal{B}_F} [J_w(\pi) - J_w(b)]$$

The second maximum abbreviates a world and a comparator from the common family. A negative value is a conditional certificate; a positive value is not.

S3.20. Joint worlds: Acquisition conditions and limits of local reasoning

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Proposition2. Suppose pi0 stops at supported histories H0 forming a disjoint terminal partition and pi replaces only those terminal choices with observable subtrees T_h. For each world, define Delta_w(h)=the conditional loss of the old terminal decision minus the conditional future acquisition-plus-terminal loss of T_h, excluding already sunk costs. Then J_w(pi0)−J_w(pi)=Σ_h P_w(h)Delta_w(h), where zero-support terms are0. Thus min_w Σ_h P_w(h)Delta_w(h)>0 is the exact uniform improvement condition for that modification. Positivity of each Delta in each supported world is a sufficient condition, not a necessary one. Uniform Delta>=epsilon on a single changed history gives only epsilon min_w P_w(h); a world in which the history never occurs prevents that argument from proving a strict global gain.

A complete known-world condition is available in the noiseless context construction. Let the paid mode cost u, each of two channels cost v, and abstention cost γ=2/5. The mode is fair; one channel equals Y, the other is independent noise, with their roles determined by the paid mode. Buying the mode and then its useful channel gives full-coverage J=u+v with budget 2. The minimum over all unconstrained complete fixed orders is V_F=min{2/5, u+[min(v,2/5)+2/5]/2, v+min(1/4,u+1/5,v+1/5)}. Therefore u+v<V_F suffices to beat even unconstrained fixed orders and hence all useful feasible fixed orders. For u=1/50,v=2/25, V_F=13/50 and u+v=1/10, a proved gap of at least4/25; the exact useful-floor comparator is31/100, giving21/100. The formula and its case proof apply to this defined family, not arbitrary acquired probabilities.

XOR explains why nonmyopia alone does not establish adaptation value: either single fair bit leaves Y uncertain, while buying both bits resolves it. A one-step rule stops, but the complete fixed subset also buys both and matches the multistep loss. In the hidden-mode construction, channel roles remain unidentifiable even after the constant paid context. With costs2/25 per channel, no contingent acquisition can improve on the one-channel J=33/100; the proof in the supplement and the exact enumeration agree.

$$J_w(\pi_0) - J_w(\pi) = \sum_{h\in\mathcal{H}_0} P_w(h)\Delta_w(h)$$

The changed histories form a disjoint terminal partition; zero-support terms contribute zero and sunk costs cancel.

$$V_F = \min\left\{\frac{2}{5}, u + \frac{\min\left(v, \frac{2}{5}\right) + \frac{2}{5}}{2}, v + \min\left(\frac{1}{4}, u + \frac{1}{5}, v + \frac{1}{5}\right)\right\}$$

For the defined noiseless observed-mode construction at budget two, u+v below V_F is sufficient for strict adaptive improvement over every unconstrained fixed order. It is not a generic acquisition theorem.

S3.21. Joint worlds: Computation and architecture

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

The solver carries world-indexed unconditional sums of errors, accepted mass, purchase count/cost, group acceptance and each sensor purchase mass. Query branches add these vectors and the paid action cost;

no maximization is performed until a complete root policy is scored. The conditional-world set is never independently rectangularized. A policy is stored as terminal[0,label] or query[1,index,left,right], so every decision is a function of bought values. Labels are used when constructing expected losses from known mathematical worlds and for evaluation only; the resulting tree never receives labels at runtime.

The implementation uses Python standard-library integers and Fraction only. World masses are rescaled to their least common denominator D, and loss costs to CD; optimization compares integer numerators over D×CD without floating ties. An independent atom-traversal scorer recomputes every retained selected/control tree. Full paths report purchases followed by prediction or abstention, while paired transition cells retain corrected errors, introduced errors and moves to/from abstention. Integer mass denominator D is a probability weight scale, never the number of independent observations. No fitting, external model request, private array, global skill change or operational scheduling occurs.

Algorithm S6. exact ex-ante world-vector policy enumeration

Require: Finite rational joint-world vertices P_w(X,Y,G), bought-signal alphabets, query budget B, nonnegative purchase costs and terminal actions0/1/abstain. Global C>=1/2 and group-conditional C>=1/4 constraints in every world, or the separately labeled unconstrained regime. Complete feasible fixed-order comparator class including observation-dependent early stopping and terminal choices.

Ensure: An observable deterministic committed policy minimizing signed static-envelope excess, with a complete world-specific loss/coverage/cost vector and a strict/non-strict/absent certificate. Strong fixed-subset/order controls, two explicit myopic controls, all-abstain, separately marked label oracle, full purchase-path and prediction-transition masses.

1. Freeze source, exact worlds, costs, ties, baselines, resource caps and claim scope before solving. Check user-enabled control and source hashes.
2. Recursively enumerate every terminal or unbought-signal query and every pair of continuation trees. Cache proper subtrees; stream the root. Carry unconditional mass separately for each original world. Never replace the world vector with a local worst-case scalar.
3. In pass1, test global/group coverage for every world and obtain each world's minimum loss over jointly feasible complete fixed-order controls. Also enumerate fixed-subset controls.
4. In pass2, minimize max_w[J_w(pi)-min_b J_w(b)] with the frozen tie order. Report the same criterion for strong static policies; do not replace it with minimax absolute loss.
5. Recompute each retained policy by an independent atom-by-atom tree traversal, including paid costs on abstained cases. Calculate paired differences inside each world and all coverage/purchase denominators.
6. Return a strict all-world improvement certificate only when the signed excess is negative and the policy is feasible. Otherwise retain no_gain or no_certificate; do not label the selected minimax-regret policy safe.
7. Evaluate the already selected nominal policy in the prespecified excluded world without retuning. Preserve every prespecified case and all false scientific expectations.

S3.22. Joint worlds: Prospective evaluation and finite complexity

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Source, exact scenario atoms, costs, tie order, baselines, resource bounds and claim scope were hashed before any controlled optimization. The design-only source check counted policies; a syntax error was corrected before that freeze.13 scenarios jointly cover XOR complementarity and high cost, observed context at budgets0–3, hidden mode, two-world ambiguity and its enlargement, and context cost multipliers1/2,1,2,4,8. The nominal context optimizer is then evaluated once in the prespecified excluded inverted world without new selection. Every case is retained. No train/test terminology or confidence interval is appropriate for these known finite populations.

For binary signals and T=3 terminal actions, N(d,0)=N(0,b)=T and N(d,b)=T+dN(d−1,b−1)^2 counts syntactic trees. Counts are291 for d=2,B=2,1,326 for d=3,B=2 and254,046 for d=3,B=3. Across the 13 scenarios there are265,269 root trees, visited in two passes for530,538 root visits. Proper subtree collections contain at most291 trees per history in this study; the root is streamed. No dominance pruning is used, so coverage and ties cannot be removed by a risk-only filter.

Let A be the total finite support size across all W worlds, H the number of cached histories and Q the largest cached proper-subtree collection. With precomputed history masses, producing/scoring one node record costs O(W(d+6)); comparing a root record also costs O(W(d+6)). A conservative bound is O(H A d + N(d,B)W(d+6)) arithmetic operations per pass, plus proper-subtree generation, which is bounded by the same full-tree expansion scale for fixed d,B. Cached vector storage is O(HQW(d+6)), plus shared tree

references and O(B) streaming stack; bit lengths depend on rational denominators and costs. The general algorithm is exponential/superexponential in the depth-dependent tree count, not a scalable AFA learner. The measured study CPU2.859375s and wall3.1396514s cover the solver process, not authoring, primary-source reading, host cost or physical sensing. Cooperative CPU90s/wall180s checks are not OS isolation.

$$N(d,0) = N(0,b) = 3, \quad N(d,b) = 3 + dN(d-1,b-1)^2$$

This recurrence counts syntactic binary-query trees with three terminal choices; no policy pruning is used.

S3.23. Joint worlds: Exact controlled results and coverage

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

The table reports useful feasible policies and worst vertex J for each selected family; multiworld vectors and paired comparisons are provided separately. A row's maximum losses alone must not be subtracted to claim dominance. R_B is candidate minus the best complete feasible static order within each world. A negative value certifies a set-conditional improvement for that constructed population. Zero is no_gain. Positive is no_certificate, even if the selected policy happens to be static.

At context budget 2 the adaptive path buys the mode with probability1 and each useful channel with probability1/2: expected query count2, cost1/10, C=1, E=0, both group coverages1. The useful fixed-order control costs3/50 with expected count3/2 but incurs E=1/4, giving J=31/100. The best fixed-subset control has C=3/4, group coverages(1,1/2), E=1/8 and cost1/10, giving13/40. Comparing only full-coverage fixed subsets would therefore weaken the baseline. With budget 3 the strong fixed order uses early stopping to reach J=7/50 rather than the full three-signal subset9/50; adaptation still saves1/25.

The selective myopic context policy at budget 2 has J=3/10,C=1/2 but group coverage(0,1), so it is infeasible for the useful regime. The full-coverage myopic policy is feasible and gives33/100. At budget 3 the selective myopic rule reaches7/50 and remains worse than the adaptive1/10. These policies are reported with their actual constraints, rather than being discarded or promoted to a feasible win. In high-cost XOR and the eightfold context-cost case, useful optimal policies predict without acquisition at J=1/2; unconstrained all-abstain wins at2/5. At fourfold context costs, useful adaptive J=2/5 ties all-abstain but has full coverage, so strict J<2/5 is false.

Table S10: Complete useful-domain controlled comparison. Exact probability laws; worst-world values are descriptive aggregates, not paired differences.

Scenario	Budget	Trees	Adaptive max J	Fixed subset max J	Fixed order max J	Adaptive min C	Signed R B
xor low	2	291	1/10	1/10	1/10	1	0
xor high	2	291	1/2	1/2	1/2	1	0
context b0	0	3	1/2	1/2	1/2	1	0
context b1	1	30	33/100	33/100	33/100	1	0
context b2	2	1326	1/10	13/40	31/100	1	-21/100
context b3	3	254046	1/10	9/50	7/50	1	-1/25
hidden mode	2	1326	33/100	33/100	33/100	1	0
ambiguity paired	2	1326	2/5	19/40	23/50	1	-3/50
ambiguity enlarged	2	1326	12/25	12/25	12/25	1	1/50
context cost 1 2	2	1326	1/20	11/40	27/100	1	-11/50
context cost 2	2	1326	1/5	41/100	37/100	1	-17/100
context cost 4	2	1326	2/5	1/2	49/100	1	-9/100
context cost 8	2	1326	1/2	1/2	1/2	1	0




Figure S8: Exact outputs from the frozen controlled study. Left: useful-domain adaptation and the strongest fixed order as costs change; all-abstain is outside that useful feasible set. Right: retain the world index for candidate and control. Lines connect prespecified settings or worlds; they do not represent confidence intervals.

S3.24. Joint worlds: Ambiguity, incompatible extrema and true-world exclusion

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

For proper mappings with useful-channel error q=0 or3/10, the same full-coverage adaptive tree has J=(1/10,2/5). The useful static envelope and the selected strong fixed order coincide at(31/100,23/50). The paired advantage is(21/100,3/50), so the guaranteed margin is3/50. Separately taking min baseline and max candidate yields31/100−2/5=−9/100: this is a safe but conservative lower bound and fails to certify an improvement that the paired calculation certifies. Subtracting max candidate and max baseline happens to yield−3/50 here, but that operation is not a general certificate.

A separate exact counterexample makes max-minus-max unsafe: in two worlds P(Y=1)=(1/10,9/10), pi always predicts0, whereas b buys a constant sensor costing1/10 and then predicts1. Their losses are pi=(1/10,9/10), b=(1,1/5). max J_pi−max J_b=−1/10 appears favorable, yet the paired worst excess is7/10. Conversely, a genuine ambiguity superset or rectangular hull supplies an upper bound on a fixed policy's worst loss; calling that conservatism an unsafe lower bound would reverse the inequality.

Adding the inverted mapping changes no unlabelled joint law of the three sensors: each observed bit vector remains equally probable. Its label dependence does change. In the useful enlarged set, the optimum signed excess is+1/50, and the selected adaptive and static policies coincide on buying one channel, with losses(33/100,12/25,33/100). The nominal adaptive tree is no longer certified. If that tree is instead retained while the true inverted mapping is omitted from M, its evaluated loss becomes3/5, E=1/2,C=1,cost1/10, which is1/5 worse than all-abstain. This is an explicit assumption-failure example, not evidence for real-world safety.

S3.25. Joint worlds: Time consistency and primary-method comparisons

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Ex-ante enumeration commits to the whole tree. Prior-by-prior conditioning of a nonrectangular M can rationally recommend a different continuation under a conditional worst-case objective. With two equally probable observed branches and conditional P(Y=1) vectors(3/5,0) or(0,3/5), committing to predict0 in both branches has worst loss3/10. All nine terminal plans show it is the ex-ante optimum. After either branch is observed, the conditional worst prediction error is3/5, so a freshly optimized conditional minimax rule abstains at2/5; following those recommendations raises the ex-ante loss to2/5. The rectangular hull admits both bad branches simultaneously and gives the fixed prediction policy an upper bound3/5. It is conservative, rather than an unsafe underestimate. No Bellman consistency theorem is invoked. A single known world with additive expected loss and no coupled global constraints admits ordinary finite-horizon recursion; robust scalar recursion requires an appropriate stable rectangular set and a matching objective, which are not proved for this study's set or global coverage constraints.

Li and Oliva's primary arXiv2010.02433v2 Sections1–2.1 formulate bought subsets/values as the AFA state and balance prediction loss with acquisition cost. Their GSMRL learns feature conditionals and uses model-based information to guide reinforcement learning. This study instead knows a finite set of complete joint laws and exhausts policies; it reproduces neither their learned method nor their reported performance.

Valancius, Lennon and Oliva's primary arXiv2302.13960v1 Sections3.1–3.2 distinguish a retrospective label/unbought-feature oracle from an acquisition-conditioned oracle using conditional expectations. Their specified oracle searches feature subsets and samples an acquisition from a chosen subset. Our solver exhausts contingent trees and compares them with complete fixed orders under joint-world ambiguity. The distinction does not establish a novel AFA principle: observability, joint acquisition and nongreedy decisions are prior work.

Iyengar's2005 publisher abstract explicitly conditions robust dynamic-programming extensions on rectangularity. We inspected that abstract and metadata, not the full proof. Our elementary counterexample explains why we keep world vectors, and does not constitute a reproduction or refutation of that theorem. Manski's arXiv2204.11318v2 abstract distinguishes identification and statistical decision performance and discusses potential benefits of randomized choices. We inspected the versioned abstract/metadata only. Our deterministic convex-world exercise neither estimates a statistical identified set nor settles the randomized optimum. Source bytes or serialized tool-visible publisher text, retrieval times, versions, read scope and failures are bound in PRIMARY_EVIDENCE108.json.

S3.26. Joint worlds: Proof of joint-world comparison and comparator envelope

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

Fix any realized training/selection information so pi and b are measurable deterministic functions of bought histories. For each full atom, run both trees on the same declared sensor vector and label, subtract their total losses, then integrate. Linear expectation gives D_w. If w_true∈M, D_true is one of the admissible differences, so D_true<=sup_M D; epsilon dominance follows immediately. For M=conv{P_1,…,P_W}, D(P)=Σ_w lambda_w D(P_w), hence extrema occur at listed vertices. The interval is sharp for the declared set because each extremizing listed law is permitted. This is a mathematical identified range, not a statistical coverage assertion.

A jointly feasible static family is finite in this study. For fixed pi, J_w(pi)−min_b J_w(b)=max_b[J_w(pi)−J_w(b)], so maximizing over w and b proves the stated equivalence. Over a convex hull the maximum of that family of linear differences again occurs at a vertex. Robust group coverage is also vertex-checkable: P_w(predict,G=g)−(1/4)P_w(G=g)>=0 is linear, with P_w(G=g)>0 here. Macro C>=1/2 is linear. Thus vertexwise feasibility and certificate calculations extend to this declared hull even though the label posterior at an intermediate history is nonlinear in mixture weights.

For a fixed comparator and fixed policies, enlarging M can only increase the upper loss-difference bound and decrease the lower advantage bound. The same monotonicity holds for a fixed comparator family. If the family is redefined as B_F(M), enlargement may remove infeasible comparators, so monotonicity of the envelope value is not automatic. In these controlled enlargements, every world has the same observed group/sensor law and therefore exactly the same coverage feasibility set; the changed result comes from label dependence, not a hidden change in coverage membership.

$$P_w(\text{predict}, G = g) - \frac{1}{4} P_w(G = g) \geq 0$$

With positive group mass, the conditional coverage floor is equivalent to this linear joint-mass inequality. It can be checked at the declared convex-hull vertices.

S3.27. Joint worlds: Proof of replacement criterion and explicit context condition

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

The old and new policies have identical purchased prefixes before each modified terminal h. Their costs and loss contributions outside the disjoint terminal events cancel. On each positive-support h, conditional expectation of their remaining loss difference is Delta_w(h). The law of total expectation gives the exact sum in Proposition2. A min of sums need not equal a sum of independent minima; requiring every local contribution positive is sufficient but can be unnecessarily strict. Multiplication by the history mass is essential. For a zero-probability branch, any conditional choice is irrelevant to that world's ex-ante risk.

For the context condition, examine all possible first purchases; symmetry exchanges channels A and B. No purchase has minimum terminal loss2/5. If the mode is first, its useful group may either abstain at2/5 or buy the useful channel at cost v and predict perfectly. Its other group has no useful channel left within that fixed order/budget, so it abstains at2/5; buying its irrelevant channel cannot improve that terminal minimum. This yields u+[min(v,2/5)+2/5]/2. Stopping before or after the first purchase is already included.

If channel A is first, its marginal posterior accuracy is3/4 regardless of the observed bit; stopping has minimum loss1/4. Buying the mode next resolves the label in half the group cases and leaves it fair in the rest, so the optimal terminal loss averages1/5 and total continuation is u+1/5. Buying channel B next gives equal

channel bits with probability1/2, where the label is known, and different bits with probability1/2, where it is fair, again giving terminal average1/5 and continuation v+1/5. Values are symmetric for either first-bit value, so observation-dependent early stopping cannot lower the minimum by mixing those identical continuation choices. Add the first cost v and minimize to obtain the third term. These cases exhaust all complete fixed orders at budget 2, proving V_F. The adaptive mode→useful-channel tree uses two queries and has cost u+v and zero error. Its coverage is1 in both groups, so strict u+v<V_F proves the stated sufficient advantage under either regime. At equality strict certification fails; the full cost sweep is retained rather than extrapolating this sufficient condition beyond its assumptions.

$$\min_{w} \sum_{h \in \mathcal{H}_0} P_w(h) \Delta_w(h) > 0$$

This is the exact uniform improvement condition for the specified policy modification. A sum of separately optimized local bounds is a different quantity.

S3.28. Joint worlds: XOR and indistinguishable-mode proofs

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

For fair independent XOR bits, either one bit alone leaves the label fair. A one-step full-coverage policy sees no error reduction and pays a positive cost, so it stops with error1/2; the selective one-step rule abstains at2/5. Buying both bits determines Y and costs1/10 in the low-cost case. A fixed subset can buy both as well, so this mechanism alone cannot separate adaptation from the strongest static comparator. In the high-cost case the pair costs3/5; stopping/abstaining is preferable, exactly as the enumeration records.

For the hidden mode, sensor0 is constant and cannot change any posterior. Buying either A or B gives posterior accuracy3/4 regardless of its bit. Buying the remaining signal makes equal bits (probability1/2) perfectly informative and different bits uninformative, so the optimal selective terminal loss is1/5. From the first-signal state its expected loss reduction is1/4−1/5=1/20, below the remaining signal cost2/25. The alternatives have total losses: no acquisition/abstain2/5; one signal/full prediction2/25+1/4=33/100; both signals/optimal selective terminal4/25+1/5=9/25. Conditional branches of the first bit have identical values, so adaptive stopping cannot improve this minimum. The constant context adds cost without information. This proves no adaptive gain for this fixture, not a general theorem that hidden modes preclude all adaptive improvements.

S3.29. Joint worlds: Nonrectangular updating and safe versus unsafe bounds

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

For any two real-valued losses over M, min J_b−max J_pi <= min(J_b−J_pi), so the independent min-minus-max advantage is always a safe lower bound. By contrast, max J_pi−max J_b need not upper-bound max(J_pi−J_b); the constant-sensor counterexample attains−1/10 versus+7/10. Rectangularizing means enlarging M only when the original laws really are contained in that hull. For a fixed policy and the same loss, sup over a superset cannot be smaller. It can be loose and change the optimal policy. An arbitrary approximation that deletes feasible laws or changes comparator coupling is not necessarily conservative.

In the two-branch time-consistency example, predict0 in both branches has losses3/10 in both original worlds. Predict1 has error at least2/5 at the risky branch and1 at the other in some world, while predicting0 in one branch and abstaining in the other has worst loss(3/5+2/5)/2=1/2. All-abstain gives2/5, and plans using prediction1 cannot improve on all-predict0. The9-plan exact check records the unique ex-ante optimum. After observing a branch, each of the original worlds still has positive probability for that branch, and its conditional Y=1 probability can be0 or3/5. The conditional worst loss for predict0 is3/5, for predict1 is1, and for abstain is2/5. Replanning therefore changes the continuation. The rectangular hull admits the joint choice(3/5,3/5), raising the fixed predict0 upper bound to3/5. The computation preserves ex-ante commitment rather than silently replacing it with that different problem.

Guarantees for a completed continuation subtree require a declared updating and commitment convention. A fresh conditional world set can be retained as posterior vertices with original coupling, but greedily optimizing scalar conditional worst losses discards that coupling. Global group/coverage constraints also couple choices across histories even under a known world. This study neither proves a robust Bellman theorem for its objective nor permits a run-time replanner to inherit the commitment certificate without rechecking the whole policy.

$$\min_{w} J_w(b) - \max_{w} J_w(\pi) \le \min_{w} [J_w(b) - J_w(\pi)]$$

The independent min-minus-max expression is a conservative lower bound on advantage. Subtracting two independent maxima is not a valid substitute.

S3.30. Joint worlds: Enumeration, reproducibility and exact denominators

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

The recurrence counts three terminal actions plus d choices of first signal, each with an independently chosen pair of continuation trees. Each continuation has one fewer available signal and one fewer query. This proves completeness by induction on budget: every admissible finite deterministic tree is either terminal or has exactly such a first query and children. Fixed-order membership is an intersection of permutation bitsets; a query at depth t restricts membership to orders whose t-th element equals that signal, and both child continuations must match. Fixed-subset membership requires that every syntactic leaf has the same purchased mask. Keeping off-support branches can duplicate behavior but cannot exclude a supported behavior or improve the optimum. No policy is pruned.

Each world law is stored as explicit (x,y,group,probability) atoms. D is the least common denominator of their probabilities, so integer atom masses sum to D in each world; they are not observations. CD is the least common denominator of costs and2/5. A score vector uses unconditional matching-history masses; adding children and the parent purchase mass computes exactly the integrated cost/error/coverage without dividing by a possibly zero history probability. Every root loss numerator is E_count×CD+cost_numerator+(2/5)CD(D−C_count). Feasibility tests use2C_count>=D and4group_C_count>=group_mass_count. Standard integer comparisons settle ties exactly; floating point appears only in SVG coordinates and resource seconds.

The result retains the tree, exact J/E/C/conditional-error/group coverage, expected purchase count/cost, each sensor purchase probability, and each purchase-path/terminal mass for every chosen candidate and baseline. Candidate-versus-static prediction transitions have all nonzero correct/wrong/abstain cells and sum to1 in each world. The label oracle is a separate information-expanded lower reference. Two myopic rules use the uniform mixture over the frozen world vertices and strict one-step improvement; this nominal prior is part of their definition, not a robust guarantee. Relabeling/duplicating vertices could change that myopic prior, so it must not be inferred from the convex set alone.

The script research108.py is frozen before controlled execution by DESIGN_FREEZE108.json. CONTROLLED_RESULTS108.json and CHECKS108.json preserve the original measurements and scientific expectations. A separate authoring script produces this document and vector figure from those outputs, and validates source hashes, numerical tables, path sums and artifact bounds. The primary papers compare concepts and scope, not performance: GSM2021 and ACO2024 have versioned method HTML; IYENGAR2005 is limited to publisher abstract/metadata via serialized web-tool text after direct403; MANSKI2024 is limited to versioned abstract/metadata after v1 HTML404. Four source records are used, zero source words are quoted, and copyrighted full HTML/tool text stays local under _private_primary_HTML excluded from public artifacts/Git.

S3.31. Joint worlds: Scope, prior evidence and unresolved research

Scope. Deterministic complete-policy joint-world partial-identification theory and controlled finite cases.

This author read the frozen public99/101 decomposition/review,102 source3 summaries and105 method/next-contract reviews. Existing raw arrays, caches and FINAL were not opened or hashed. The exposedDEV fixed-coverage error diagnostic and zero selected fusion gain motivate the question, not a new benchmark result. The study has no data-derived estimator, confidence procedure, fit calls, model API calls or failure/deadline implementation. Experimental authoring model identity is not inferred from a requested routing label.

The complete deterministic search solves exactly this small declared problem. It does not solve a randomized policy problem: randomization can improve minimax criteria and may help meet coverage constraints. It also does not prove true-world inclusion, identify a mode in paid probability vectors, estimate learned value functions, demonstrate untouched-participant performance, measure physical sensor cost, or reproduce external AFA methods. Each of these remains a separate acceptance condition. Independence of a later review is organizational evidence, never certification of scientific truth. Source/contract/results are immutable after handoff; Root owns official Task completion, integration and independent review.

S3.32. Randomized strong-static theory: Worlds, bought histories and one retained random seed

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

A world specifies a rational joint law of binary purchased signals X, label Y and evaluator group G. The world set is the convex hull of a finite listed family. A policy observes only an ordered history of distinct bought

indices and their values, together with the remaining query budget. It may predict 0, predict 1 or abstain, or buy another signal. Labels, the world index, evaluator group and unbought values are unavailable to the policy; in the context construction a paid signal deliberately equals the mode/group, so group information becomes available only after that purchase.

Let T contain all deterministic trees obeying this observable contract. Draw one tree index I from q before a decision unit and independently of its full atom and world; retain that tree for the entire acquisition trajectory. Thus the same q is evaluated in every world. A new independent draw per unit implements the population mixture in repeated decisions. Drawing one tree once for an entire deployment instead gives only an expectation over deployments; its realized group coverage need not satisfy the mixture constraints. Neither convention grants an exact finite-cohort quota.

The per-world coefficients include unconditional wrong-prediction probability E, coverage C, expected acquisition count K, paid cost and joint group-prediction masses. Costs on trajectories ending in abstention remain charged. Conditional selective error is E/C when C is positive. Evaluation may inspect complete atoms, but that information is never supplied to a runtime decision tree.

$$J_w(q) = \sum_i q_i J_{wi} = E_w(q) + K_w^{\mathrm{cost}(q)} + \left(\frac{2}{5}\right)(1 - C_w(q))$$

The error term counts only wrong accepted predictions; K with the cost superscript denotes paid acquisition cost, not query count.

$$q_i \geq 0 \quad \sum_i q_i = 1$$

One common probability vector applies to every world. Sampling and retaining its index is part of the policy.

S3.33. Randomized strong-static theory: Coverage after convexification

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

For each world impose C at least kappa and, for every positive-mass group g, conditional coverage at least rho_g. Use the joint-mass form rather than treating conditional ratios as affine. Collect the resulting coefficients into A and bounds into h, so Aq at least h defines one polytope F_T. If a group has zero mass in a world, its joint-mass inequality is vacuous. All constructed cases have positive group masses.

Theorem 1, exact common-mixture representation. For a finite horizon, finite bought alphabets and the stated observable input rights, the attainable population performance vectors of all randomized history policies with independent internal randomness equal the convex hull of the deterministic-tree vectors. Consequently F_T and the linear loss coefficients exactly represent this finite randomized problem. Sampling all internal random choices in advance fixes a deterministic continuation at every possible history; collecting equal trees gives q. Conversely, sampling a tree from q realizes its weighted performance vector. This argument preserves the same randomness law across worlds and does not justify independent world-specific plans.

Theorem 2, feasibility and filtering. Constant prediction without purchases satisfies every coverage floor in[0,1] in every world, deterministically. Therefore a deterministic-infeasible but randomized-feasible example is impossible under this contract. Nevertheless, mixing only individually feasible trees can be strictly suboptimal: in the no-information balanced-label case every individually feasible deterministic policy predicts with loss 1/2, while a half-predict, half-abstain mixture meets C=1/2 and has loss 9/20. Global feasibility must be imposed after convexification.

$$\sum_i q_i C_{wi} \geq \kappa$$

Global coverage is required separately in every listed world.

$$\sum_i q_i P_w(\text{predict under tree } i, G = g) \geq \rho_g P_w(G = g)$$

The positive-group coverage condition uses unconditional joint mass on the left and a fixed world-specific group mass on the right.

S3.34. Randomized strong-static theory: An equally randomized strong static benchmark

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

A deterministic fixed-order policy buys along a prefix of one fixed permutation, but may stop on any observed prefix and use arbitrary terminal prediction or abstention maps. This class includes complete fixed subsets

and their terminal maps. Its mixtures may draw an order and a corresponding complete stopping tree ex ante. Let F_B be all such mixtures satisfying the same coverage constraints in every world. No candidate or comparator receives extra labels, extra observations, a different cost or a different coverage exemption.

For each world w, define b_w as the minimum J_w among F_B. Different w can have different minimizing mixtures. These are hindsight reference values, not an implementable policy that learns w. Their role is deliberately strong: a negative maximum candidate excess means the candidate beats every feasible static mixture in every admissible world. The candidate q itself must be common across all worlds. We also optimize one common static mixture against the very same b vector, and separately report candidate-minus-that-fixed-mixture differences inside each world.

Theorem 3, certificate meaning. If the true law belongs to the declared convex hull, coverage is feasible and R(q) is at most minus epsilon, then q has expected loss at least epsilon lower than every member of F_B under that true law. The statement conditions on all selection information that fixed q and the world set. It is a set-conditional statement, not evidence that the set contains the population. Signed excess may be negative because the adaptive class is larger; it is not conventional nonnegative regret against a class containing the candidate.

$$b_w = \min_{\lambda \in F_B} J_w(\lambda)$$

Each minimizing λ is a common policy satisfying coverage in every world; only the objective world changes.

$$R(q) = \max_{w}(J_w(q) - b_w) = \max_{w, \lambda \in F_B} (J_w(q) - J_w(\lambda))$$

This is a same-world static-envelope comparison. Independent maxima of candidate and comparator losses cannot replace it.

S3.35. Randomized strong-static theory: Epigraph program, dual certificate and algorithm

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

With one column per deterministic tree, solve the displayed epigraph program. The benchmark LPs are solved first over the complete fixed-order columns, enforcing every world's coverage constraints. The common static and fixed-subset excess programs use those same benchmark values. The finite exactness claim concerns this full tree library and declared world hull; restricting a library or approximating its coefficients changes the claim.

A feasible dual certificate consists of nonnegative weights α over world excess constraints, nonnegative coverage multipliers mu, and a free η satisfying the displayed column inequalities. For any primal feasible q, r, multiplication and summation give the dual objective as a lower bound on r. A feasible rational primal point with equal objective therefore proves optimality without relying on floating solver tolerances. In 43 executed programs, rationalized SciPy solutions pass exact Fraction tests for every primal row, every dual column, equality, sign and objective gap. The supplement gives the proof and reconstruction details.

Algorithm S7. common observable mixtures with exact rational certificates

Require: Frozen rational joint-world vertices, paid costs, query budget and observable terminal/query actions. Global and group coverage floors and complete deterministic adaptive/fixed-order/fixed-subset classes.

Ensure: One exactly certified common adaptive mixture; one equally randomized common static mixture; per-world jointly feasible static envelope optima. World-specific J/E/C/K/cost/group values, same-world differences, prediction transitions, all negative cases and inclusion failure.

1. Seal source, scenarios, resources, rights and claim criteria before optimization; check the user stop gate.
2. Enumerate every observable deterministic tree. Carry each world's unconditional score vector through branches without local worst-case pruning. Retain fixed-order and fixed-subset membership.
3. Construct one coverage polytope after convexification. Do not discard individually coverage-infeasible component trees.
4. Solve each benchmark-world objective over the same jointly feasible static-mixture polytope; these minima define b.
5. Solve common adaptive, common static and fixed-subset epigraph programs against the same b. Any primary optimum with an exact certificate is admissible; report its actual support and do not claim a unique tie solution.
6. Convert primal and dual coefficients to rational numbers, verify every row/column and require zero duality gap. Preserve any failed scientific expectation.
7. Report fixed-reference same-world differences and group coverages separately from the stronger hindsight envelope. Evaluate the frozen nominal policy once in the excluded world without retuning.

$$\min_{q,r} r \quad \text{subject to} \quad Aq \geq h \quad \sum_i q_i = 1 \quad q \geq 0$$

Coverage and the simplex constrain the common tree mixture.

$$\sum_i J_{wi} q_i - r \leq b_w \quad \text{for every world } w$$

A single epigraph value bounds the same-world excess at every vertex.

$$\alpha_w \geq 0 \quad \sum_w \alpha_w = 1 \quad \mu_k \geq 0$$

These are dual world and coverage weights.

$$\eta \leq \sum_w \alpha_w J_{wi} - \sum_k \mu_k A_{ki} \quad \text{for every tree } i$$

Checking all columns proves the dual lower bound, including trees excluded by any floating optimizer presolve.

$$r \geq \eta + \sum_k \mu_k h_k - \sum_w \alpha_w b_w$$

Equality with a feasible primal objective is an exact finite optimum certificate.

S3.36. Randomized strong-static theory: Prospective controlled cases and computation

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

The source, ten explicit scenarios, resources, coverage floors, comparator definition and decision criteria were sealed before solving. Cases comprise no information, an unobserved group with unequal floors, observed mode with three coverage regimes, paired ambiguity, enlarged ambiguity, hidden mode, high cost and XOR. All are exact finite mathematical laws, not synthetic independent samples. The additional true-world-exclusion check changes only the evaluation law of the frozen nominal policy.

The complete enumeration retains 9,579 syntactic root trees across the ten cases:3 each in two no-signal cases,1,326 each in seven three-signal budget-two cases, and 291 in the two-signal XOR case. Every three-signal class contains 840 fixed-order trees and 516 fixed-subset trees. Duplicate off-support behavior remains; no risk-only pruning occurs. Installed SciPy 1.16.1 and NumPy 2.3.2 solve 43 LPs, after which standard-library rational arithmetic validates all certificates. An independent tiny oracle enumerates all six candidate active bases of an explicit three-action LP and obtains the four feasible vertices and optimum 9/20.

The measured solver process used CPU 1.015625 seconds and wall 0.998652 seconds. Those values exclude source retrieval, authoring and publication rendering. CPU 120 seconds/wall 180 seconds are cooperative phase bounds, not operating-system isolation. No model/API invocation, private array access or added dependency occurred. Complete enumeration is exponential in the policy-tree count and is not a scalable learner.

S3.37. Randomized strong-static theory: The randomized baseline materially narrows the apparent advantage

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

For the observed mode at the default floors, adaptive purchase of the mode and then its relevant channel gives J=1/10, E=0, C=1, K=2 and paid cost 1/10. The strongest deterministic jointly feasible fixed order had J=31/100 in 108 and is reproduced here. A common mixture of two early-stopping fixed orders gives J=13/50, E=0, C=1/2, K=3/2 and paid cost 3/50. The selected weights are 3/4 and 1/4, producing group coverages 3/4 and 1/4. Either component alone violates one group floor; their mixture is jointly feasible. The strict adaptive advantage is therefore 4/25, rather than 21/100.

When each group floor rises to 3/4, the randomized static optimum is 57/200 and the adaptive gap is 37/200. Full coverage forces the static optimum back to 31/100 and recovers the deterministic 21/100 gap. These three controlled constraints show why a baseline's acceptance entitlement is part of the estimand. Fixed subsets remain weaker: their selected randomized default loss is 3/10, compared with 13/50 for fixed orders with early stopping. A comparison to fixed subsets alone would overstate the evidence for adaptation.

Under paired noiseless/noisy worlds, the adaptive losses are(1/10,2/5), while one common static mixture attains the benchmark vector(13/50,41/100). The same-world guaranteed advantage is the smaller coordinate gain,1/100. The prior deterministic comparator gave 6/100. The stronger randomized baseline removes five

sixths of that previous certificate, while leaving a strict finite-set improvement. At the noisy world the adaptive loss equals all-abstain 2/5, so strict improvement over all-abstain is false there.

Table S11: Complete retained cases. Vectors list the declared worlds in contract order. Both common optimizers use the identical randomized fixed-order envelope b. Outcome refers to a strict adaptive envelope certificate, not a new empirical result.

Case	Adaptive J vector	Static envelope b	Adaptive R	Common static R	Outcome
no information	9/20	9/20	0	0	no gain
hidden group coordination	19/40	19/40	0	0	no gain
observed mode	1/10	13/50	-4/25	0	gain
observed mode group three quarters	1/10	57/200	-37/200	0	gain
observed mode full coverage	1/10	31/100	-21/100	0	gain
paired ambiguity	1/10, 2/5	13/50, 41/100	-1/100	0	gain
enlarged ambiguity	33/100, 12/25, 33/100	13/50, 41/100, 13/50	7/100	7/100	no gain
hidden mode	33/100	33/100	0	0	no gain
high cost	9/20	9/20	0	0	no gain
xor static tie	1/10	1/10	0	0	no gain

Table S12: Coverage and error of the actual common policies. Equal coverage constraints do not imply equal realized coverage. Vectors use the same world order as the preceding table; the full-coverage case gives a matched-coverage comparison.

Case	Adaptive C	Common static C	Adaptive E	Common static E
no information	1/2	1/2	1/4	1/4
hidden group coordination	3/4	3/4	3/8	3/8
observed mode	1	1/2	0	0
observed mode group three quarters	1	3/4	0	1/8
observed mode full coverage	1	1	0	1/4
paired ambiguity	1, 1	1/2, 1/2	0, 3/10	0, 3/20
enlarged ambiguity	1, 1, 1	1, 1, 1	1/4, 2/5, 1/4	1/4, 2/5, 1/4
hidden mode	1	1	1/4	1/4
high cost	1/2	1/2	1/4	1/4
xor static tie	1	1	0	0




Figure S9: Executed exact comparisons. A: individually feasible deterministic static controls, globally feasible static mixtures and adaptive mixtures; each bar reports its coverage C as well as loss J. B: adaptive and common-static excess to the identical randomized envelope. Negative R is the strict set-conditional certificate; zero/positive outcomes are retained.

S3.38. Randomized strong-static theory: What randomization cannot fix

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

With no information, mixing prediction and abstention lowers J from 1/2 to 9/20 at C=1/2, but adaptive and static classes coincide. With the hidden group and floors(1/4,3/4), every observable common mixture must have the same coverage in both groups; it predicts with probability 3/4 and has J=19/40. An illegal policy that conditions its terminal label and acceptance on unobserved G could instead achieve J=1/5. This is an information advantage, not a valid coverage optimizer.

Adding the inverted mapping world preserves the observed signal/group law and hence the coverage polytope, yet removes adaptive gain. Both adaptive and common-static excess optima are 7/100. The selected one-channel policy has losses(33/100,12/25,33/100), C=1 and is itself static. This is simultaneously a no_gain adaptive comparison and a positive-excess failure to dominate the hindsight static envelope. It does not become safe because it minimizes that excess. The separate frozen nominal policy has J=3/5 in the excluded inverted world, worse than all-abstain 2/5 by 1/5.

Hidden mode and XOR produce no adaptive advantage against randomized strong static controls. High acquisition cost yields the same no-information 9/20 mixture: randomization improves constrained loss over deterministic 1/2 without creating any acquisition value. These retained negatives prevent the claim that adding a random seed generally creates an adaptive benefit.




Figure S10: Left: exact no-information linear mixture frontier, with C=1/2 and J=9/20. Right: the same frozen nominal policy evaluated without retuning in an included and an excluded world. The all-abstain loss2/5 is a separate reference outside the coverage-feasible class.

S3.39. Randomized strong-static theory: Why independent occupancy LPs and local Bellman shortcuts fail

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

Consider two worlds with no observations, full coverage and opposite constant labels. A separate LP in each world predicts that world's label and reports loss 0. No common observable policy can realize both choices. A common half-zero, half-one coin has worst loss 1/2, which is optimal because the two world errors sum to 1. Independent world occupancies have implicitly supplied the hidden world index. A valid compact occupancy formulation would need nonanticipativity or realization constraints that enforce a common observable policy; separate flow constraints are insufficient.

Coverage also couples observed histories even in a single known world. With two equally likely terminal histories, a global coverage floor 1/2 can be satisfied by predicting only at a perfectly informative first history and abstaining at the fair-label second history, giving J=1/5. Unconstrained local minimization can

abstain everywhere when both histories are uninformative, violating the floor. Conversely, replacing the global condition with coverage 1/2 at every history is unnecessarily restrictive in the informative/fair example and raises the optimum to 9/40. Lagrange multipliers may coordinate histories when solved globally, but an arbitrary local rule inherits neither feasibility nor the finite common-mixture certificate.

S3.40. Randomized strong-static theory: Exact policy convexification and its assumptions

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

Let H be the finite set of all syntactically possible bought histories up to budget B. A deterministic policy chooses a terminal action or an unbought-signal query at every reachable history, with a continuation for each bought value. Inductively it is either terminal or a query node with deterministic children. This is exactly the class enumerated by the recurrence below. Repeated signal purchases are disallowed, all observations are reliable, and paid costs are nonnegative fixed constants.

For a randomized observable policy, take all independent internal random draws that could be used during a decision and sample them before observing the atom. Fixing their joint seed makes every continuation deterministic. If a later draw depends on previous actions or internal random values, fix the entire seed stream and execute that deterministic rule recursively on every history; the induced complete tree is still deterministic. There are finitely many resulting trees, so their probabilities define q. The seed distribution is independent of the world and atom, hence one q works simultaneously for every world. This gives the inclusion of all randomized performance vectors in the convex hull. Drawing a deterministic tree according to any q proves the reverse inclusion.

A behavioral rule with new randomness at each history is covered only when those draws are internal and independent of the unavailable world/label/group. Correlated randomness across histories within a decision is allowed through the retained seed. A draw made after reading a hidden full atom is excluded, even if its marginal q happens to match in one world. The fixed-order mixture class is more specific: each sampled tree has one common order through its branches. Randomly selecting a different next order based on observed values can be adaptive and need not be a fixed-order mixture.

$$N(d,0) = 3 \quad N(0,B) = 3$$

The three terminal actions are predict0, predict1 and abstain.

$$N(d,B) = 3 + dN(d-1,B-1)^2$$

A binary query chooses one of d remaining signals and any pair of continuation trees. This recurrence counts syntax, including off-support duplicate behavior.

S3.41. Randomized strong-static theory: Coverage, convex hulls and why feasibility rescue is impossible

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

For positive group mass, divide the joint-mass inequality by P_w(G=g) to obtain the conditional floor. At a zero-mass group the inequality is 0>=0; no undefined conditional quantity is evaluated. Each global or group joint-mass residual is linear in a world law and in q. If all vertex residuals are nonnegative, every convex combination residual is nonnegative. Thus all-world feasibility over the declared convex hull is exactly equivalent to the listed vertex tests. Conditional group-coverage ratios themselves need not be affine in mixture weights.

For any nonnegative query budget, the no-query policy predict 0 has C_w=1 and P_w(predict, G=g)=P_w(G=g). It satisfies all floors between 0 and 1, regardless of labels or ambiguity. Hence no deterministic-infeasible/randomized-feasible example exists here. A positive-group floor exceeding 1 or a global floor exceeding 1 is impossible for every randomized policy too, since prediction indicators are bounded by 1. Feasibility-rescue examples in other constrained-control settings rely on additional upper-risk/cost/action restrictions absent from this contract.

The feasible mixtures of all trees need not equal the convex hull of individually feasible trees. With no observations and balanced labels, the three trees have(C, J)=(1,1/2),(1,1/2),(0,2/5). Under C>=1/2, the last tree alone is infeasible, but either half-prediction/half-abstention mixture is feasible at(1/2,9/20). The convex hull of only the individually feasible trees has C=1 and J=1/2 everywhere. This proves strict containment and identifies a concrete baseline error to avoid.

For the hidden-group example G=Y with equal group mass and no observations, a common policy predicts with one common probability p, regardless of group. The stronger group floor 3/4 implies p>=3/4. Any label

mixture has unconditional error p/2, so J=2/5+p/10 and the optimum is 19/40. If unobserved G is illegally revealed, the policy can predict the correct group label with probabilities 1/4 and 3/4, meet global C=1/2 and obtain J=1/5. The lower value demonstrates the effect of unavailable information, not an alternative feasible solution.

$$J(p) = \frac{p}{2} + \left(\frac{2}{5}\right)(1-p) = \frac{2}{5} + \frac{p}{10}$$

With no signal and balanced labels, all prediction coins have error probability one half conditional on predicting.

$$\min_{p \geq \frac{1}{2}} J(p) = \frac{9}{20} \quad \min_{p \geq \frac{3}{4}} J(p) = \frac{19}{40}$$

These are exact one-dimensional optima for the ordinary and hidden-group examples, respectively.

S3.42. Randomized strong-static theory: Benchmark quantifiers and the same-world theorem

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

Write F_B for the static-mixture polytope jointly feasible over the original finite vertices. It is nonempty by constant prediction and compact as a closed subset of a finite simplex. For each w its minimum b_w is attained. Algebra gives J_w(q)-b_w=max_lambda[J_w(q)-J_w(λ)]. Maximizing over worlds yields the stated equivalence. Therefore R(q)<=-epsilon bounds every pair of a listed world and a feasible static mixture. No single λ need attain all b_w simultaneously.

For a convex-combination law P=sum_w theta_w P_w, choose any common comparator λ. The difference J_P(q)-J_P(λ) equals sum_w theta_w[J_w(q)-J_w(λ)], at most R(q). The same mixture q and λ are coverage-feasible at P by the affine residual argument. Taking the supremum over λ proves the certificate for every law in the hull. Alternatively, the objective J_P(q)-min_lambda J_P(λ) is a maximum of linear functions of P, and its supremum over a finite hull equals its maximum at a vertex. This establishes exact vertex reduction without treating conditional posteriors as independent.

A common static optimizer minimizes max_w(J_w(λ)-b_w) over F_B. Its value is nonnegative: each coordinate is nonnegative because b_w is the minimum over exactly that set. The value can be positive because no single λ simultaneously attains the envelope vector. The enlarged case attains 7/100. Comparing an adaptive optimizer with this one fixed common static optimizer answers a weaker, deployable-reference question, so we report its worldwise differences separately. In that enlarged case they are all zero even though both envelope excesses are positive.

For fixed q and a fixed comparator set, enlarging the world set can only enlarge the supremum of pairwise differences. If the comparator feasibility set is itself redefined after enlargement, it may shrink, so general monotonicity of the recomputed optimum is not automatic. The paired/enlarged constructions here share identical X, G laws, so their coverage polytopes and comparator membership do not change; the loss of certificate is driven by additional label dependence. Excluding the true world voids the implication entirely, as the frozen-policy 3/5 case shows.

$$J_P(q) - J_P(\lambda) = \sum_w \theta_w (J_w(q) - J_w(\lambda)) \leq R(q)$$

The same pair of complete policies is compared at each vertex before averaging.

$$R_B^{\text{static}} = \min_{\lambda \in F_B} \max_w (J_w(\lambda) - b_w) \geq 0$$

A common static policy is compared with a hindsight envelope; the envelope need not be jointly attainable.

S3.43. Randomized strong-static theory: Dual lower bound and exact optimality audit

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

Define the epigraph Lagrangian as r plus α times(Jq-b-r), plus mu times(h-Aq), plus η times(1-sum q). Taking the infimum over free r requires sum α=1. Taking the infimum over q>=0 requires every coefficient sum α J minus sum mu A minus η to be nonnegative. The remaining constant is η+mu h-α b. These conditions produce a dual lower bound on every primal feasible objective. Equality at an explicit feasible rational primal/dual pair is a complete optimality proof for that finite LP.

SciPy uses A_ub x<=b_ub, equality Ex=d and nonnegative q with free r. Its inequality duals y are nonpositive. For coverage rows A_ub=-A, set mu=-y; for excess rows set α=-y; the simplex equality dual is η. The checker converts each reported float to a Fraction with denominator bounded by 10,000,000. It never accepts mere closeness: it verifies exact equality of the simplex and objectives, nonnegative primal slacks, nonpositive inequality duals, and every reduced cost. The free r column must have exactly zero reduced cost. A reconstruction failure would reject the result rather than truncate or repair it.

For a per-world static benchmark LP the objective coefficients are J_wi and there is no free r column. The same rational checker verifies its lower bound and zero gap. Every original column is passed to the checker, including those eliminated internally by floating presolve. Certificates record all dual coefficients, the constraint names, column/row counts and exact objectives. Sparse primal supports store canonical enumeration indices, trees and weights. An independent reviewer can rebuild the coefficient matrix from frozen source and explicit world atoms; the column-inventory hash binds that reconstruction.

This audit proves numerical optimality relative to the supplied coefficient matrix. The correctness of observability, tree completeness and atom scoring remains a separate implementation/proof obligation. Reusing the previously reviewed 108 vector scorer is not an independent reimplementation. The tiny no-information oracle is independent of SciPy and of that scorer: it explicitly enumerates all pairs of active inequalities, uses Fraction Gaussian elimination, tests feasibility and minimizes the resulting four vertex objectives. Distinct independent review remains pending at author freeze.

$$L = r + \sum_w \alpha_w \left(\sum_i J_{wi} q_i - b_w - r \right) + \sum_k \mu_k \left(h_k - \sum_i A_{ki} q_i \right) + \eta \left(1 - \sum_i q_i \right)$$

Each multiplier sign corresponds to a nonpositive residual for the minimization problem.

$$c_j - \sum_l \left(A_{\mathrm{ub}}\right)_{lj} y_l - \sum_l E_{lj} z_l \geq 0$$

This reduced cost is checked for each nonnegative column; it must equal zero for a free column.

S3.44. Randomized strong-static theory: Exact context calculations and stronger comparator effects

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

The noiseless context has independent fair G, Y, N. Signal 0 is G and costs u=1/50. Depending on G, channel A or B equals Y and the other equals N; each costs v=2/25. The query budget is 2. The adaptive policy pays u+v=1/10 and predicts perfectly. A fixed order that buys G then A can predict only on its useful group and abstain on the other, with E=0, C=1/2, K=3/2, cost=u+v/2=3/50 and J=13/50. Its group coverages are(1,0); the analogous G-then-B tree has(0,1).

Choose the first tree with probability θ and the second with probability 1-θ. Their group coverages are(θ,1-θ), while C, J and cost remain 1/2,13/50 and 3/50. Every θ in[1/4,3/4] satisfies the default group floors. The returned optimizer chooses θ=1/4. The single-world dual certificate has η=13/50, all coverage multipliers zero, and one excess multiplier 1; it certifies that every fixed-order column has unconstrained J at least 13/50. Hence this feasible mixture is globally optimal, not merely a handpicked upper bound.

With full coverage, no abstaining mixture component may have positive abstention probability on a supported atom. The best static policy then has J=31/100. With group floors 3/4 the exact static-mixture minimum is 57/200. Both values follow from the full rational certificates. A fixed-subset mixture must buy its fixed subset even on paths that will abstain; its default loss is 3/10, above the fixed-order 13/50 because early stopping avoids an irrelevant paid channel. All compared costs include abstained cases.

For the noisy world, the relevant signal has flip probability 3/10. The adaptive policy pays 1/10 and has unconditional error 3/10, giving 2/5. The half-coverage static mixture pays 3/50, has error 3/20 and abstains on half the population, giving 41/100. Thus the paired same-world advantages are 4/25 and 1/100. At the noisy world, half the static refusals become predictions: mass 7/20 becomes correct and 3/20 becomes wrong, matching the transition table and explaining why increased coverage is not a free accuracy gain.

In the inverted noiseless world, the frozen nominal adaptive tree buys the now-irrelevant channel. Its bought channel is independent of Y, so error 1/2 plus cost 1/10 gives 3/5 at full coverage. The exclusion check regenerates the same canonical tree indices and verifies tree equality before scoring. It performs no optimization under the excluded law.

S3.45. Randomized strong-static theory: Global coordination and occupancy counterexamples

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

In the no-observation full-coverage two-world example, let p be the probability of predicting 1. World 0 has Y=0 surely and loss p; world 1 has Y=1 surely and loss 1-p. Their maximum is at least 1/2, attained at p=1/2. Separate world LPs choose p=0 and p=1 and report 0, but no common q satisfies both choices. A flow model indexed by world that lacks common action/realization constraints permits this illegal stitching. Hidden-group conditioning fails for the same informational reason in S2.

For the two equally likely observed histories, first suppose both have fair labels and free terminal actions. Independent unconstrained local minimization chooses abstention because 2/5<1/2 and produces C=0, violating the global floor 1/2. To show that a per-history floor is also a different problem, change the first history to a perfectly known label and leave the second fair. Global optimization predicts at the first and abstains at the second, C=1/2, J=1/5. Enforcing local coverage 1/2 at each history makes the fair branch use at least a half-prediction coin. Its conditional loss is 9/20, and the population optimum becomes 9/40.

These examples do not disprove all occupancy or dynamic formulations. A correct formulation can retain global resources, a common observable realization plan and the declared coupling between worlds. A known-world constrained problem can use globally optimized Lagrange multipliers. The invalid shortcut is to optimize independent local or world-specific scalars and declare the resulting pieces a common feasible policy without a realization proof. This study supplies a complete finite-tree formulation and certificates, not a new general occupancy theorem.

S3.46. Randomized strong-static theory: Finite complexity, approximation and reproducibility

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

The exact run enumerates 9,579 root trees. For d=3, B=2, N=1,326; fixed-order membership is determined by a common permutation bitset across all query branches, and fixed-subset membership by a common purchased mask at every terminal leaf. Off-support syntactic branches may duplicate behavior but do not remove a supported behavior. Each complete tree carries world-indexed unconditional E, C, K, cost, group and purchase probabilities, as in the reviewed 108 recursion. Selected mixtures require no new signal fitting.

For W worlds, G group constraints and N tree columns, the coverage matrix has W(1+G) rows. A regret LP adds W excess rows and one free epigraph column. Dense coefficient storage is O(NW(1+G)) rational entries, plus tree records and cached subtree vectors. Benchmark construction solves W LPs over the fixed-order columns, then adaptive, fixed-order and fixed-subset excess programs add three solves per case. Exact auditing checks all entries needed for primal slacks and dual columns. Rational bit complexity depends on input and reconstructed denominators; no polynomial-in-depth or large-scale throughput claim is made.

Restricting the adaptive library while retaining the full comparator library cannot improve its optimum R and may lose a real certificate; restricting comparators can lower the envelope's strength and make apparent gains larger. Approximating costs or probabilities without bounds can reverse both feasibility and a small 1/100 margin. A valid approximation would need explicit uniform coefficient-error or primal/dual residual bounds and a conservative coverage slack. None is estimated here. Sampling a finite subset of worlds also needs an inclusion argument before a population guarantee.

The frozen execution has zero model calls, zero private-row reads and zero new dependencies. Primary acquisition reads official HTML/metadata only; no arbitrary PDF is downloaded. Full publisher HTML and web-tool payloads remain in the excluded private folder, while public evidence records URLs, dates, scopes, status and hashes. Metadata verification does not reproduce a learned AFA baseline or validate its reported performance. The author's distinct result and source hashes are stable at handoff; Root performs official settlement and commissions independent review.

S3.47. Randomized strong-static theory: Six method-area judgments and remaining research

Scope. Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope.

Algorithm: exists for the finite contract, with exact common-mixture epigraph LPs and all-column rational certificates; scalable discovery of policy columns remains open. Architecture: exists as an observable tree

simulator separated from the full-atom evaluator, with one retained per-unit random draw; no production sensing deployment or finite-cohort quota is implemented. Complexity: exists as explicit tree counts, LP dimensions and measured solver scope; no large-scale or asymptotic efficiency claim is made.

Evaluation: partial, because ten exact constructed laws and a frozen exclusion check establish only mathematical finite-case behavior; statistical inclusion and untouched-participant transport are unexecuted. Baselines: partial, with complete equally randomized fixed orders and subsets and a fixed common-reference comparison, while modern trained AFA systems are not reproduced. Related work: partial, with five scoped primary works and preserved access limitations; no exhaustive novelty assessment or full external proof audit is claimed.

A useful empirical successor must separate missing conditional information, approximation error and transport. Every fitting stage and coverage multiplier needs participant exclusion, and a fresh cohort cannot be created by renaming an exposed split. A data-derived ambiguity set needs a defensible inclusion event. The 1/100 paired margin also calls for tight approximation/error control rather than a coarse token refinement. These requirements are future gates, not scientific outcomes of the present finite exact study.

S4. Sharp acceptance bounds and paid-information fusion

Accuracy/coverage bounds are oracle coupling statements unless acceptance recognizability is separately supplied. Expert-label selection and probability fusion have different correctness-union ceilings. The proofs retain all equality, lattice, transport and paid-information assumptions and all negative witnesses.

S4.1. Acceptance bounds: Population, loss and terminal rights

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Let p index participants, w_p>0 with sum w_p=1, and choose an example uniformly inside each participant. Within p, a fixed predictor h has correctness indicator K, accuracy a_p=E_p[K], and acceptance probability g in [0,1]. Define coverage c_p=E_p[g], accepted error mass e_p=E_p[g(1-K)], C=sum w_p c_p and E=sum w_p e_p. Standard selective risk is E/C for C>0, while the objective here uses E itself. E/C is undefined at C=0.

A fixed paid set M is acquired on every example. Its virtual cost kappa(M) is unconditional, including examples later rejected. The objective is J=kappa+E+γ(1-C), with 0<γ<1 for the main theorem; the implementation also accepts the boundary values 0 and 1. Required coverage is C>=q and every c_p>=r_p. The all-abstain reference has J_ref=γ and C=0, so it is a loss threshold outside the useful-coverage feasible set, not a feasible constrained competitor.

A single terminal predictor is a smaller rights set than all predictors h_s for s contained in M. If multiple terminal predictors may be chosen, their union-of-correctness mass u_p=P_p(exists allowed s: h_s(X_s)=Y) supplies a label-informed relaxation. It does not supply a way to know which s is correct at deployment.

S4.2. Acceptance bounds: Sharp error and participant-floor bounds

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Theorem 1. For one fixed predictor of exact accuracy A and exact coverage C, max(0,C-A)<=E<=min(C,1-A). Both endpoints are attainable in an unrestricted correctness/selection coupling. For N equally weighted examples with k correct and m accepted, the attainable errors are the integers from max(0,m-k) to min(m,N-k), divided by N. Randomized acceptance gives every intermediate value without integer restrictions.

Theorem 2. Put Abar=sum w_p a_p, R=sum w_p r_p, D=sum w_p(r_p-a_p)_+, and H=sum w_p(r_p+a_p-1)_+. At exact C in [R,1], the sharp randomized participantwise error interval is [max(D,C-Abar), min(C-H,1-Abar)]. A pooled-window accuracy cannot replace Abar when the loss is participant-macro. Even Abar alone loses information: D and H can be positive under heterogeneous participant accuracies.

At C=0, both error endpoints are zero when feasible; at C=1 both equal 1-Abar. Exact finite deterministic populations additionally obey each participant acceptance lattice. The continuous interval is a valid relaxation for deterministic policies; it is not a claim that every fractional point is attainable without randomization.




Figure S11: Exact synthetic theorem witness, separate from development data. Two participants have a=(1,0), weights (1/2,1/2), floors (1/4,1/4). Thus D=H=1/8, and the feasible exact-coverage domain is [1/4,1]. The plot displays the stated sharp interval, not measured model performance.

S4.3. Acceptance bounds: The fixed-action oracle envelope and exclusion rule

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Theorem 3. Among arbitrary label-informed randomized selectors satisfying the floors and C>=q, the exact lower objective is L=kappa+γ(1-Abar)+(1-γ)max(D,q-Abar). Its attaining coverage is C*=max(Abar+D,q), which is always at least R and at most 1. For one participant without an additional floor, C*=max(A,q) and L=kappa+γ(1-A)+(1-γ)(q-A)_+.

If L>=J_ref, no deployable selector inside that fixed action and terminal-rights class can strictly improve on J_ref, because deployable selectors are a subset of this oracle relaxation. If L>J_ref all are strictly worse; at equality the certificate excludes strict improvement only. L<J_ref is insufficient information and is never evidence of safety or achievable gain.

The same formula with valid per-person upper accuracy bounds remains a lower certificate because the oracle optimum is nonincreasing in each correctness mass. Exact development accuracies certify only the fixed finite development population. They do not become population accuracy bounds without additional sampling, uncertainty and selection-control assumptions. A target selective-risk ρ at exact C is impossible if max(D,C-Abar)>ρ C; this remains a necessary condition only.

S4.4. Acceptance bounds: Certificate procedure and cost

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

The procedure implements the theorem with rational arithmetic and rejects float estimates as exact inputs. It keeps the family of terminal rights explicit. For P participants and K allowed terminal predictors it takes O(PK) rational operations to bound unknown unions, followed by O(P) operations and storage for the envelope and witness. Rational bit complexity depends on input numerator and denominator lengths; these are arithmetic-operation bounds, not unit-cost guarantees for arbitrary-precision integers.

The tool is a decision-rule study. It reads declared aggregate inputs, computes an oracle lower bound, and returns either a justified exclusion or insufficient information. It neither fits a predictor nor runs a deployable confidence or acquisition policy.

Algorithm S8. one-sided participantwise fixed-paid-action certificate

Require: A declared population; positive rational participant weights w summing to 1; per-person floors r; macro coverage floor q; gamma in [0,1]; constant unconditional paid cost kappa; reference J_ref. For single-predictor rights: exact per-person accuracies or valid upper bounds. For multiple terminal predictors: exact correctness unions or simultaneous valid per-person marginal upper bounds and the precise allowed-rights set.
Ensure: Exact rational lower_J and rules_out_strict_improvement, with explicit scope and oracle witness for exact correctness mass. Return insufficient_information when the lower bound is below J_ref; never return a positive deployment/safety guarantee. Reject malformed probabilities, weights, cost or infeasible exact coverage.

1 Validate inputs and rights. Each paid action must have a declared fixed cost charged on every example, including abstentions; do not substitute an adaptive expected cost.
2 For a single predictor use a_p. For exact union rights use u_p. With only marginal upper bounds use u_p^+=min(1,sum_s a_ps^+); optionally retain max_s a_ps as a lower union endpoint only when accuracies are exact.
3 Compute Abar=sum_p w_p a_p and D=sum_p w_p max(0,r_p-a_p). The effective coverage requirement is max(q,sum_p w_p r_p).
4 Set lower_J=kappa+gamma(1-Abar)+(1-gamma)max(D,q-Abar). For exact C>=sum_p w_p r_p use lower_E=max(D,C-Abar).
5 For exact a_p, start c_p=max(a_p,r_p), then distribute max(0,q-sum_p w_p c_p) over remaining capacities 1-c_p. Accept all correct mass before any additional wrong mass. This is a label-informed oracle witness.
6 If lower_J>=J_ref, no policy within these declared fixed-paid rights can strictly improve that objective on this population. Equality only rules out strict gain. Otherwise return insufficient_information; a joint-label union and a deployable selector are still different objects.

S4.5. Acceptance bounds: Paid-submask union: identifiable limits and deployment gap

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Theorem 4. From exact marginal accuracies a_ps alone, max_s a_ps<=u_p<=min(1,sum_s a_ps). The endpoints are sharp over otherwise unrestricted correctness-event couplings. Using the union upper endpoint in Theorem 3 gives the sharp optimistic oracle objective over those couplings; using the lower endpoint gives the pessimistic oracle objective. The resulting objective interval is about label-informed oracles, not a deployable-policy risk interval.

Witness: two predictors each have accuracy 1/4 on four examples. Nested correct sets give u=1/4, while disjoint correct sets give u=1/2. With kappa=1/10, γ=2/5, q=1/2 and r=1/4, their best label-oracle objectives are 11/20 and 3/10. Thus the same marginals can either rule out or leave open strict improvement over 2/5. The actual fixed classifiers may impose extra prediction/label compatibility constraints; arbitrary event recoupling is not an assertion that these are valid alternative conditional worlds for a supplied model.

Deployment gap: let all observed information be constant, Y be an independent fair bit, and h_0=0, h_1=1. Each accuracy is 1/2 and the correctness union is 1. A label-informed oracle is perfect; every label-free choice and acceptance randomization still has E=C/2. The union supplies an optimistic lower bound, not an implementable selector.

S4.6. Acceptance bounds: Fixed-full failure does not imply adaptive failure

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Consider independent fair bits Z,Y,B, with Z visible for free. If Z=0 the two paid channels are (Y,B), and if Z=1 they are (B,Y). Each channel costs 3/10, and every participant has this same distribution. Acquiring both channels on every example has cost 3/5 and perfect accuracy, so its oracle J is at least 3/5, above the all-abstain threshold 2/5.

A deployable adaptive policy observes Z and buys exactly its relevant channel, predicts Y without error, covers every person completely, and has J=3/10. It uses no labels at decision time. A single unconditional channel has accuracy at most 3/4; its unrestricted oracle lower envelope is 2/5, so even it cannot strictly beat the threshold. The explicit eight-atom conditional world is enumerated in EXACT_CHECKS.json. These are synthetic virtual costs, not physical sensor measurements.

S4.7. Acceptance bounds: Already exposed development aggregates

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Table S13: Descriptive fixed-fullmask certificates and unknown paid-rights oracle intervals; J_ref=0.4. The interval columns are oracle objectives over unrestricted marginal couplings, not deployable outcomes.

Partition	Macro accuracy	Single h7 lower J	Excludes strict gain	Paid rights oracle J interval	Union identified
TUNE	0.307566791	0.542433209	True	[0.150000000, 0.484025312]	False
CAL	0.333898285	0.516101715	True	[0.150000000, 0.482666662]	False

S4.8. Acceptance bounds: Four-cell proof and equality conditions

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Write t=E[gK]. The four nonnegative masses are accepted/correct t, accepted/wrong C-t, rejected/correct A-t, and rejected/wrong 1-A-C+t. They sum to one and require max(0,A+C-1)<=t<=min(A,C). Substituting E=C-t gives Theorem 1. Conversely, every t in that interval defines a valid probability table, proving sharpness over unrestricted event couplings.

For the lower endpoint: if C<=A, accept only correct mass; if C>A, accept all correct mass and C-A wrong mass. For the upper endpoint: if C<=1-A, accept only wrong mass; otherwise accept every wrong example and the unavoidable C-(1-A) correct mass. With N examples, k correct and m accepted, choosing x accepted correct gives integer x from max(0,k+m-N) to min(k,m), so every stated integer error is constructible. Randomizing acceptance on one boundary example or mixing selectors supplies fractional coverage. None of these constructions describes how an unlabelled production policy identifies correctness.

S4.9. Acceptance bounds: Participant-floor proof at exact coverage

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Necessity: in each participant e_p>=r_p-a_p whenever r_p>a_p, so E>=D. Also accepted correct mass cannot exceed Abar, giving E>=C-Abar. For the upper bound, participant floors force at least (r_p-(1-a_p))_+=(r_p+a_p-1)_+ correct mass, hence E<=C-H; all wrong mass is at most 1-Abar. The feasible exact-coverage domain is C>=R=sum w_p r_p and C<=1.

Lower-bound attainment starts at each floor r_p, selects correct mass first and includes precisely (r_p-a_p)_+ wrong mass. Its initial aggregate wrong mass is D. The still available correct capacity is T=sum w_p(a_p-r_p)_+. Since R=Abar+D-T, raising total coverage from R to C first fills T correct mass, then wrong mass. The resulting E=D+max(0,C-R-T)=max(D,C-Abar). Fractional filling is always possible because all remaining weighted capacities sum to 1-R.

Upper-bound attainment starts at each floor, selects wrong mass first and includes precisely (r_p+a_p-1)_+ correct mass. Initial error is R-H. Add available wrong mass before additional correct mass. The result is E=min(C-H,1-Abar). Convex mixtures of lower- and upper-attaining selectors keep every participant above its floor and preserve C, so every intermediate E is feasible under randomization. For deterministic finite participant populations only the actual per-person lattices are attainable.

S4.10. Acceptance bounds: Objective minimization, boundaries and weighting

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

At fixed C, the lower objective is kappa+max(D,C-Abar)+γ(1-C). Let C0=Abar+D=sum w_p max(a_p,r_p). For C<C0 its slope is -γ; for C>C0 its slope is 1-γ. Thus for 0<γ<1 and C>=max(q,R), the unique optimum in total coverage is C*=max(C0,q). Substitution gives kappa+γ(1-Abar)+(1-γ)max(D,q-Abar). C0>=R and C0<=1, which proves the coverage filling has sufficient capacity. For γ=0 or γ=1 the same value is correct but total-coverage minimizers need not be unique.

An attaining participant allocation starts at c_p=max(a_p,r_p), which includes all correct mass. Increase any c_p within [c_p,1] until the weighted sum reaches q if necessary. This yields the executable witness, including per-person error e_p=(c_p-a_p)_+. A per-person cost kappa_p that is constant across its examples simply enters as weighted kappa=sum w_p kappa_p; history-dependent or action-dependent spending must not be substituted without a new proof.

For a fixed required C>0, the exact oracle minimum selective risk is max(D,C-Abar)/C. If one is free to choose C>=q>0, the minimum ratio occurs at C=clamp(Abar+D, max(q,R),1) when Abar>0; the formula follows from D/C decreasing below the kink and 1-Abar/C increasing above it. Degenerate Abar=0 gives risk 1 for every positive C. These ratio statements describe oracles and do not certify a deployment policy.

A weighting witness separates pooled and participant-macro quantities: participant1 has N=1 with accuracy1, participant2 has N=3 with accuracy0. Pooled accuracy is1/4, macro accuracy is1/2. With macro floors1/4, the correct oracle objective with zero acquisition cost and gamma2/5 is11/40, while using pooled accuracy in the no-floor macro formula at q1/2 gives9/20. Conversely, heterogeneous a=(1,0) and homogeneous a=(1/2,1/2) have the same macro accuracy1/2 but floor penalties D=1/8 and0; their optimal J at q1/2 and zero cost are11/40 and1/5.

S4.11. Acceptance bounds: Union sharpness and permitted-world distinction

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

For each p, every correct event is contained in their union, yielding u_p>=max_s a_ps. Subadditivity yields u_p<=min(1,sum_s a_ps). To attain the lower endpoint, nest events [0,a_ps] on a unit interval. For the upper endpoint, place intervals of lengths a_ps consecutively on a circle of circumference1. If the total length is at most1 they are disjoint; if at least1 they cover the circle. Rational lengths can be expanded to a common finite denominator, giving an exact finite construction. Mixtures of the two constructions retain every marginal and yield intermediate unions.

The fixed-rights oracle can select a correct predictor wherever the union occurs; outside it every available terminal predictor is wrong. It therefore reduces exactly to a correctness indicator with probability u_p. Applying the participant theorem gives an oracle envelope L(u). This function is nonincreasing in each u_p: adding correct mass cannot worsen the relaxed optimum. Consequently L(u_upper)<=L(u_actual)<=L(u_lower), with both endpoints attained across unrestricted per-person event couplings. If marginal data are only upper bounds, only the optimistic lower certificate is retained; the lower union endpoint is not inferred from upper bounds.

Sharpness is relative to aggregate correctness-event information, not arbitrary changes to P(Y|observed history) while keeping a supplied model fixed. A fixed observed joint prediction table, binary disagreement pattern, conditional-risk restrictions, dependence on previously revealed channels or participant identity restrictions can narrow the feasible unions and selectors. Any acquisition safety claim at a history requires the correct conditional population, permitted history and original model family. We have not proved a universal adaptive or conditional-world safety theorem.

S4.12. Acceptance bounds: Eight-atom adaptive witness and deployment-gap witness

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

EXACT_CHECKS.json lists every equally weighted (Z,Y,B) in {0,1}^3. The adaptive rule buys channel Z, whose value is exactly Y, and predicts it. Its query count is1 on every example; C=1, E=0 and J=3/10. Fixed-full pays2 queries, hence J>=3/5 even at accuracy1. Fixed-one observes its relevant channel on half the atoms, and an independent fair bit on the other half; with free Z its Bayes accuracy is3/4. A label oracle can accept its correct3/4 and achieve3/10+(2/5)(1/4)=2/5, so it cannot strictly beat2/5 either.

The empty-information label-free action has error C/2 for any positive coverage. At required C>=1/2 it has J>=1/4+1/5=9/20. Thus the adaptive3/10 rule beats all unconditional fixed sets in this specified world, while satisfying q1/2 and per-person1/4. This is an existence counterexample, not evidence that current ProbeFlow policies can implement it.

Separately, for constant observed information and fair Y, constant predictors0 and1 have union1. A randomized label-free selector chooses each terminal with probabilities p0,p1, accepting with C=p0+p1. Its accepted error is p0/2+p1/2=C/2. The label oracle with union1 has zero error. This gap holds in a completely specified conditional world and does not depend on an invalid empirical recoupling.

S4.13. Acceptance bounds: Exact checks, resource bounds and preserved failures

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

exact_checks94.py exhausts every correctness/selection table for N1..7, every event coupling for N1..4 with K1..3, and rational row-selection vertices. It separately enumerates two-participant piecewise-linear coverage vertices with weights (1/2,1/2), (1/3,2/3), (1/5,4/5), multiple floors and gamma0,2/5,1, evaluating actual row losses rather than the proposed closed form. This establishes finite computational evidence for equality/boundary witnesses; the general proof is separate.

The first harness run failed: an empty Python integer sum divided by n became float0, so comparison to exact1/3 could fail. The initial failed receipt is preserved as EXACT_CHECKS_FAILED_01.json. The fix

seeds the row-loss sum with Fraction(0), and the corrected exact enumeration passes31,036 cases. This was an oracle arithmetic bug, not a discovered counterexample to the theorem. These are author checks, not independent review.

The executable checks use only the standard library with a120-second CPU and300-second wall limit; the actual measured time is retained in EXACT_CHECKS.json. No experimental model call, predictor fitting, private payload read, raw archive read, FINAL read, old actor import or Orca lifecycle mutation is performed. Primary-source HTML retrieval is separate literature work. Two initial public JSON inspections produced truncated console output; no private payload was read, no omitted output is used as proof, and bounded aggregate extraction replaced them.

The finite brute-force work is O(N*4^N) for binary correctness/acceptance tables through N=7 and O(K*2^(NK)) for K event subsets through N=4,K=3. Row acceptance vertices use at most N*2^(N-1) candidates before direct row-loss evaluation. The participant harness is explicitly two-dimensional; it enumerates finitely many coverage breakpoints and feasible boundary intersections. These costs belong to theorem checking, not the O(PK) certificate algorithm.

S4.14. Acceptance bounds: Six method areas, strong controls and next acceptance

Scope. Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector.

Algorithm: a complete one-sided decision rule, explicit rights, exact inputs and failure returns are implemented in certificate94.py. Architecture: declared aggregates or valid upper bounds flow into rights normalization, participant relaxation, threshold comparison and a scope-limited result; there is no classifier or deployment engine. Complexity: O(PK) rational operations for rights preprocessing and O(P) for the certificate, distinct from the exponential bounded theorem-witness harness.

Evaluation: proofs and31,036 finite/rational checks are primary; already exposed public aggregates are illustrative only. Baselines: same-information single-predictor no-floor relaxation, participant-floor relaxation, correct-rights union relaxation, and explicit deployable policies in the conditional-world witness are compared without mixing synthetic and actual results. Related work: four pinned primary records establish classical context and the fixed/adaptive distinction; novelty remains unclaimed.

Next acceptance is deliberately empirical and remains unmet here: freeze the stronger predictor family and all allowed terminal rights; measure participantwise correctness intersections without re-opening FINAL; fit/select an implementable policy using only permitted history; retain q>=1/2 and every c_p>=1/4; compare feasible full, myopic, static, order and always-predict controls under identical costs and exposed-development selection; record no_gain/ties/empty or infeasible families; use a legitimately controlled new evaluation before a generalization or safety claim. An oracle lower bound below a target is never an acceptance test for useful acquisition.

S4.15. Paid-fusion theory: Paid histories, terminal rights and the estimand

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/transport conditions remain external.

An acquisition policy makes decisions from previously acquired information and stops at a terminal history. For the probability-only fusion studied here, H contains the acquired mask, permitted action history and eligible probability vectors with aligned classes. It contains neither labels nor unbought features. Paid raw feature values or participant identity are additional inputs only if explicitly authorized and declared; they are excluded from this probability-only contract. A raw-feature learner and a probability-only learner need not have the same information even when they pay for the same channels.

Let p index participants with positive weights w_p summing to one; the target macro distribution draws p with w_p and then draws an example inside p. Histories can have different conditional label laws across participants. Pooling defines one specified macro mixture, not transport to unseen participants. The same observable rule g(H) in [0,1] gives randomized acceptance, and f(H) gives a terminal class. Every acquisition contributes its nonnegative cost even if the final decision abstains. Eligibility means s is a subset of the paid mask M(H).

$$C = \sum_p w_p c_p, \quad E = \sum_p w_p e_p, \quad \kappa = \sum_p w_p k_p$$

Here c_p=E_p[g], e_p=E_p[g · 1{f(H)≠Y}], and k_p is expected total acquired cost, including abstentions.

$$J = \kappa + E + \gamma(1 - C), \quad C \geq q, \quad c_p \geq r_p$$

We retain γ=0.4, q=0.50, participant floors r_p=0.25 and virtual cost0.05 per distinct axis. Selective risk is E/C for C>0 and undefined at zero coverage.

S4.16. Paid-fusion theory: What the expert union does and does not bound

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Define U as the indicator that at least one eligible expert argmax equals Y, and Q as the indicator that the deployed terminal prediction equals Y. Define V as accepted union mass, F as accepted failure inside the expert union, and G as accepted fusion success outside that union. These quantities are evaluation diagnostics because U and Q require the label. F is selection failure for an expert selector; for a general fusion rule it is the broader terminal failure inside the union.

Proposition 1. The identity below holds for every fixed or adaptive paid-history policy and every label-free randomized acceptance rule, and separately within every participant. It follows pointwise from Q=UQ+(1−U)Q. For a selector restricted to eligible expert argmax labels, Q≤U, so G=0 and the expert union is a correct-decision ceiling. Arbitrary probability fusion can have G>0; the ceiling then fails. Reusing paid information can enlarge the terminal predictor family without acquiring new sensor information.

$$V = \mathbb{E}[gU], \quad F = \mathbb{E}[gU(1-Q)], \quad G = \mathbb{E}[g(1-U)Q]$$

All expectations use the declared participant-macro mixture; U and Q are evaluated only after predictions are fixed.

$$E = C - V + F - G$$

Accepted error equals accepted mass outside the union, plus failure inside it, minus correct fusion outside it.

$$J = \kappa + \gamma + (1-\gamma)C - V + F - G$$

An improvement can come from different acquisition cost, acceptance, union availability, inside-union recovery or outside-union fusion. Report the terms instead of attributing every improvement to selector recovery.

S4.17. Paid-fusion theory: An explicit failure of the union ceiling for fusion

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Let Y=0 and let two eligible experts output p1=(0.45,0.50,0.05) and p2=(0.45,0.05,0.50). Their argmax labels are1 and2, hence U=0. Their arithmetic mean is (0.45,0.275,0.275), whose argmax is0. With acceptance1, G=1 and E=0. This constructive example is a property of a three-class finite problem, not a measured activity-recognition improvement.

A correctness union remains valid for any terminal rule forced to output an eligible expert argmax, including a vote whose winner must be among those labels. It is not a universal upper bound on class-probability stacking, geometric pooling or an arbitrary classifier of H. Even own-mask affine recalibration can change its sole expert argmax and have G>0. Thus G>0 alone does not identify multi-mask benefit; compare G and F against the equally trained own-mask refit. Source94/95 bounds are retained for their stated restricted terminal family; extending them to unrestricted fusion would change the premise.

S4.18. Paid-fusion theory: Recoverable selection error and irreducible ambiguity

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Freeze the acquisition policy, base experts and training outcome before defining conditional quantities under the evaluation distribution. Let eta_s(H) be the probability that eligible expert s is correct conditional on permitted H, eta_*(H) its maximum, and u(H)=P(U=1|H). These are theoretical conditional probabilities, not the experts' reported confidence. For a label-free selector j(H), a fixed H-measurable acceptance g and the same paid histories, Proposition 2 gives an exact decomposition of its gap to a label-informed oracle with that same acceptance.

The intrinsic term can remain positive with unlimited data and perfect conditional accuracy estimates. It vanishes exactly when, on accepted histories, all posterior label mass represented among expert argmax labels belongs to a single such label, up to zero-mass ties. This is a strong recognizability condition. A high union alone provides no estimate of it. Let H be constant, Y a fair binary label and the two experts predict0 and1. Then u=1, eta_*=1/2 and every selector has error C/2.

$$E_j - E_{\text{oracle},g} = \mathbb{E}[g(u-\eta_*)] + \mathbb{E}\big[g\big(\eta_* - \eta_j\big)\big]$$

The oracle sees correctness labels when choosing an expert but uses the same fixed label-free acceptance g. Its error is C−E[g u]. The first term is information ambiguity; the second is selector estimation/decision regret.

$$0 \le E_j - E_{\text{best-selector},g} \le 2\varepsilon C$$

Sufficient assumption: every eligible estimated conditional accuracy differs from its true eta_s by at most epsilon almost surely. Choose j to maximize those estimates. This is a deterministic conditional-error implication, not a finite-data guarantee.

S4.19. Paid-fusion theory: A useful decision rule and its scope

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

For a fixed acquisition state, the best eligible selector chooses an expert maximizing conditional correctness. With no coverage constraints, it accepts when that maximum is at least$1-\gamma$; otherwise it abstains. Previously paid cost is sunk in this terminal comparison. A general class-posterior rule instead chooses the most likely label, even if that label is absent from all expert argmax outputs. Its Bayes action set is larger. The same2epsilonC argument applies to uniformly accurate estimates of all class posterior coordinates at fixed acceptance.

Coverage constraints change this rule. One global confidence threshold need not satisfy every participant floor. Constrained tuning must report infeasibility or use a declared constrained rule; it cannot silently apply participant-specific thresholds when participant identity is unavailable at deployment. Before buying another channel, a sequential rule must compare its price and expected downstream terminal value, using only the current history. This study derives no acquisition-value estimator or acquisition-policy regret guarantee.

Uniform conditional accuracy, stable participant transport and oracle recognizability are assumptions to investigate. Participant-separated held-out predictions can falsify poor ranking, severe calibration error, low recovery or subgroup coverage failures. Eight development participants and dependent overlapping windows cannot establish a uniform almost-sure bound or a population guarantee.

S4.20. Paid-fusion theory: A stronger counterexample to maximum confidence

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Even exact marginal probability calibration of each expert does not imply calibration after selecting the largest confidence across experts. Consider the four weighted cells in Supplement2. Expert A assigns P(Y=1)=0.6 on its first row and0.9 on its second; B assigns0.2 in its first column and0.7 in its second. Each reported probability equals its true positive fraction when grouped by that expert's own forecast. Yet maximum confidence has accuracy254/375, below the fixed A accuracy17/25 by1/375.

The failure arises because selection conditions on the other expert's forecast. Required comparability is conditional correctness given the joint permitted history, or an explicitly justified weaker ranking condition. Per-expert marginal reliability plots, temperature scaling and lower log loss alone do not establish improvement in J. The same-participant, same-fit own-mask recalibration control is needed to separate general recalibration gains from useful cross-expert information.

S4.21. Paid-fusion theory: A falsifiable evaluation contract

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

The planned independent experimental slice uses frozen HGB probability vectors, an L2 log-probability stacker and equally trained own-mask recalibration. Its authorized plan has11 configurations with four held-out participant-pair fits over eight TUNE participants plus one all-TUNE refit per configuration, totaling55 fits. Configuration choices, refits and acceptance must be locked before any CAL reading. This manuscript does not consume its mutable results or claim its outcome. CAL and TUNE already have development exposure; the current exercise cannot create an untouched final test.

The paired controls are own-mask fixed prediction, maximum confidence, arithmetic pooling, geometric pooling and own-mask recalibration, all with the identical paid information, costs, classes and decision splits. Old ET saved predictions are historical controls, not capacity-matched new training. Record corrected and damaged decisions relative to the fixed comparator and U/Q cells before and after acceptance, per participant. Report both differences at a common frozen acceptance and the actual end-to-end acceptance change.

At full paid cost0.15, beating all-abstain loss0.4 requires E<0.4C−0.15. At the minimum macro coverage0.50 this requires accepted error mass below0.05, equivalently selective risk below0.10. This is a virtual-cost break-

even condition, not evidence that any method achieves it. The reference has coverage0 and is outside the useful-coverage feasible set.

Algorithm S9. Rights-respecting terminal fusion and recovery audit
Require: Frozen acquisition policy and eligible expert/mask library; permitted terminal history H. Base probabilities with class alignment and participant-separated fitting/selection splits. Frozen terminal predictor, acceptance rule, gamma, virtual channel prices and coverage floors.
Ensure: Prediction or abstention without unbought features or labels. Evaluation-only participant masses C, V, F, G, E, cost and J; explicit feasibility result.

1 Freeze information rights, class order, tie rules and allowed metadata. At each state include only experts whose required mask is a subset of the paid mask. An expert selector with no eligible expert must abstain.
2 Fit any proposed meta-rule using only declared training information and participant-separated out-of-fold predictions. Lock configurations, refits and acceptance before evaluation labels.
3 At inference construct H from paid masks/history and eligible probability vectors. Apply the frozen terminal predictor and acceptance rule; charge all acquisitions including rejected examples.
4 After decisions are fixed, use evaluation labels solely to compute U, Q and the four accepted cells for each participant. Return C,V,F,G,E and verify E=C−V+F−G.
5 Compare paired controls at identical paid rights, prices and splits. Report both macro coverage and every participant floor; distinguish same-acceptance comparisons from changed acceptance.
6 Return needs_evidence if useful coverage, matched-control improvement, custody or untouched-evaluation requirements fail. A large label-informed union never overrides those checks.

S4.22. Paid-fusion theory: Primary method comparisons

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Table S14: Primary comparisons A. Rights and splits describe the inspected source; the last column states compatibility work, not a completed reproduction. Guarantees are factored into the third table.

Work	Information rights	Fitting split	Decision	Baseline compatibility
SL2007	Prespecified base-prediction library	V-fold predictions for meta-learning	Functional combination (abstract scope)	Useful stacking control; no acquisition rule reproduced
CSL2019	Covariates plus library; restrict to paid H here	Cross-validated experts; iterative routing/refit	Covariate-dependent expert routing	Frozen-probability stacking does not reproduce iterative expert refits
DES2018	Query features, output profiles and reference set	Separate pool/meta-training/DSEL in inspected protocol	Competence learning then majority voting	Reference neighbors must use paid dimensions only
SGR2017	Fixed predictor and scalar confidence	Labeled selection sample under stated IID setting	Risk-bound threshold search	Different objective; our J/ coverage screening supplies no SGR guarantee

Table S15: Primary comparisons B continues the same five fields. The third table supplies guarantee and assumption fields for all eight works.

Work	Information rights	Fitting split	Decision	Baseline compatibility
GUO2017	One model logit vector; no extra features	Validation NLL fits post-hoc parameters	Matrix/vector or scalar temperature scaling	Own-mask log-probability affine refit is related, with different inputs/regularization
GSM2021	Acquired state; model-based distributions of missing features	Surrogate, policy and prediction training	Sequential acquire or stop	Requires new models, same masks/costs and matched budget
ACO2024	Acquired state; conditional distribution or training approximation	Approximate oracle and optional behavioral cloning	Nongreedy subset choice then acquisition	Separate unavailable-label teacher from deployable oracle
AFAPE2025	Retrospective measured histories and target policy	Nuisance fitting separated by cross-fitting	Counterfactual cost estimation	Cached full-feature masking does not establish causal/ support premises

Table S16: Guarantees and assumptions for comparisons A/B, keyed by the same work IDs. This completes all requested comparison dimensions without dropping fields.

Work	Guarantee scope	Required assumptions / limit
SL2007	Author-reported asymptotic oracle comparison	Library/loss/CV assumptions; abstract-only proof scope

Work	Guarantee scope	Required assumptions / limit
CSL2019	Oracle/rate statements under regularity premises	IID model, function/loss and complexity restrictions; not transferred
DES2018	Empirical competence-selection comparison	No paid-history risk guarantee established in this read
SGR2017	Desired-risk control with stated confidence	IID labeled selection setting and bound-search procedure
GUO2017	Post-hoc calibration methods studied empirically	Fitting NLL alone proves neither calibration nor J dominance
GSM2021	Model-based acquisition and shaping argument	Conditional generative/policy modeling; full theory not audited
ACO2024	Acquired-information conditional oracle formulation	Unknown joint distribution and subset search need approximation
AFAPE2025	Identification/estimation with explicit assumptions	NUC, NDE and view-specific positivity; cross-fitting for flexible nuisances

S4.23. Paid-fusion theory: Proof of the decomposition and the scope of the ceiling

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

For each realized history, label and terminal output, write accepted correct mass as gQ=gUQ+g(1−U)Q. Since gUQ=gU−gU(1−Q), taking the declared macro expectation gives accepted correct mass V−F+G. Subtract from C to obtain E=C−V+F−G. Add the unconditional acquisition term and $\gamma(1-C)$ for J. This is pointwise algebra, so dependence among windows, histories, participants and decisions does not invalidate the identity. It grants no sampling inference.

When f equals h_j for some eligible j, Q=1 implies U=1. Thus G=0, accepted correct mass≤V≤P(U), and the full-coverage expert union is a selector ceiling. For general fusion Q need not imply U: the three-class arithmetic example refutes the extension. A model trained on all paid probability vectors may predict any class, even with no additional channels. To obtain a valid oracle ceiling for an enlarged terminal family, redefine its oracle over that family; the old union cannot simply be reused.

The diagram is a partition of accepted mass: UQ contributes V−F; U(1−Q) contributes F; (1−U)Q contributes G; (1−U)(1−Q) contributes C−V−G. All four cells are nonnegative. Rejected mass1−C remains separate and still pays previously incurred cost.




Figure S12: Accepted-mass partition under a fixed paid-history policy. Columns distinguish expert-union availability; rows distinguish terminal correctness. G is correct fusion outside the union and vanishes for eligible-expert selectors. All cells refer to label-informed evaluation diagnostics.

S4.24. Paid-fusion theory: Exact calibrated maximum-confidence counterexample

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Use binary labels and four cells whose counts and positive labels are shown below. The750 atoms are an exact synthetic population. On the first two cells A reports positive probability3/5 and on the last two9/10. B reports1/5 on cells1/3 and7/10 on cells2/4. Both A probabilities exceed1/2, so fixed A always predicts1. Maximum confidence switches to B on the first two cells and keeps A on the last two. Only cell1 changes the predicted label.

Calibration checks: A's low-probability group has330 positive labels among550, and its high group180 among200. B's low group has6 among30, and high group504 among720. Thus both full binary forecast vectors are exactly marginally calibrated. A has510 correct among750. Max confidence has508 correct: on cell1 it turns six previously correct positives into errors while recovering four negatives. Accuracy falls from17/25 to254/375. Every decision can be accepted with identical paid cost, so J increases by1/375.

Table S17: Synthetic finite calibration example. Counts are constructed mathematical atoms, never experimental activity windows.

Cell	Count	Y=1 count	A: P(Y=1)	B: P(Y=1)
1	10	6	3/5	1/5
2	540	324	3/5	7/10
3	20	0	9/10	1/5
4	180	180	9/10	7/10

S4.25. Paid-fusion theory: Conditional selection gap and proof of the bounded statement

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

Condition on a fixed training outcome and a fixed acquisition policy. All expert labels and the deployed choice j(H) must be measurable in the permitted H; tie-breaking is fixed without evaluation labels. The expert family is finite and nonempty on accepted histories; a selector must abstain otherwise. Independent algorithm randomization can be included in H without revealing labels. Let the target distribution be the declared participant mixture and let g be any H-measurable [0,1] function. Taking conditional expectation gives E_j=E[g(1−eta_j)] and E_oracle,g=E[g(1−u)]. Add and subtract eta_* to obtain Proposition2. Because u is the posterior probability of a union of distinct predicted labels and eta_* is its largest component, u≥eta_*. Both terms are nonnegative.

Let s* maximize eta_s and j maximize estimated eta_s. Under the uniform bound |estimated eta_s−eta_s|≤epsilon for every eligible s almost surely, eta_s*−eta_j≤(eta_s*−estimated eta_s*)+(estimated eta_j−eta_j)≤2epsilon. Multiply by g and integrate to obtain regret≤2epsilonC. The same proof holds with an H-dependent error envelope epsilon(H), yielding2E[g epsilon(H)]. The guarantee is against the best measurable expert selector with that same g and acquisition policy. It is not against arbitrary fusion, an oracle allowed label-dependent acceptance, or an optimized adaptive acquisition policy.

A learned acceptance function can be included only after conditioning on the training outcome and asserting the error bound under the actual evaluation distribution for that realized function. Dependence of future g on evaluation labels breaks the deployment contract. Finite calibration residuals or cross-validation estimates do not prove the almost-sure premise. If participant ID is unavailable, eta_s is conditioned only on H under the specified mixture; individual participant Bayes actions cannot be substituted.

$$E_j - E_{\mathrm{oracle},g} \le \mathbb{E}[g(u-\eta_*)] + 2\mathbb{E}[g\varepsilon(H)]$$

Recovering the complete union requires both small intrinsic ambiguity and small conditional estimation error on accepted histories. A small second term cannot remove the first.

S4.26. Paid-fusion theory: Identifiability and recoverability conditions

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

No-label identifiability failure: with constant H and experts predicting0 and1, a world with Y=0 surely and a world with Y=1 surely have identical deployment histories and expert outputs. Any deterministic decision rule has identical output in both worlds and fails completely in one. Randomization cannot guarantee accuracy above1/2 across the two worlds. Labeled participant-separated data distinguish these worlds only with an assumption linking training to deployment; an unconstrained participant shift can exchange the label laws afterward.

Even when the evaluation label law is known exactly, independent fair Y leaves intrinsic error1/2. Thus insufficient training labels and irreducible conditional ambiguity are different failure mechanisms. Source94 already proves classical marginal-event coupling limitations. We do not present those sharp coupling bounds as a new theorem here. Our added concern is terminal-family scope and conditioning on the information actually available to a decision rule.

For selector recovery, sufficient assumptions are: deployment-measurable joint history; stable conditional label law in the target mixture; a library covering the desired outputs; negligible u−eta_* on accepted histories; and controlled conditional estimation error. For arbitrary fusion, replace the library action maximum by the maximum over all class posterior coordinates. An additive fusion advantage is then possible if a high-posterior class is absent from all expert argmax outputs. Linear log-probability stacking need not represent the Bayes class posterior, and no realizability claim is made for that specific parametric family.

S4.27. Paid-fusion theory: Cost, coverage and comparative attribution

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

For methods0 and1, Delta J=Delta kappa+(1−γ)Delta C−Delta V+Delta F−Delta G. At common histories and common g, C and V are unchanged. If the baseline is an expert selector, its G is0; a fusion improvement is then reduction of F plus new G. When each method uses a different acceptance threshold, every term must be reported. A drop in errors caused by accepting fewer examples cannot be labeled selection recovery alone.

At fixed paid cost kappa and positive coverage C, the all-abstain loss threshold γ is beaten exactly when E<gammaC−kappa. A necessary condition is C>kappa/γ. For fullpaid kappa3/20 and gamma2/5 this requires C>3/8; at C1/2 the selective-risk threshold is1/10, and at C1 the threshold is1/4. A method must also retain every participant's1/4 coverage floor. Aggregate break-even can coexist with a participant-floor violation.

Paired correction/damage counts should use the same participant weights and common sample identities. Under identical acceptance, error reduction equals corrected mass minus newly damaged mass. Report denominator, zero-coverage handling and failures. For dependent activity windows, uncertainty must respect participant clustering; treating windows, repeated predictions or four folds as independent participants is invalid.

S4.28. Paid-fusion theory: Minimum benchmark and acceptance gates

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

For the probability-only terminal question, equalize cached base predictors, class order, eligible masks, cost accounting and TUNE/CAL access. Include fixed own-mask, raw maximum confidence, arithmetic pooling, geometric pooling, equally trained own-mask recalibration and learned stacking. Match optimization tolerance, regularization menu, participant folds and fit-count budgets for learned terminal controls. Explain parameter-count differences. A success against an unrecalibrated fixed model alone cannot isolate cross-expert fusion.

Required diagnostics are: per-participant C,E,J; macro and per-person coverage feasibility; U, V,F,G before and after abstention; common-acceptance corrected/damaged mass; class-level degradation; out-of-fold log loss and conditional ranking/calibration slices; fitting/refit and decision timestamps; and all failed/infeasible configurations. The four held-out participant pairs produce eight held-out participant observations, not four independent repeated experiments and not a new untouched evaluation.

For an AFA comparison, additionally freeze an online state/action/cost interface, a sequential stopping contract and permissible conditional-model training data. Reproduce at least one acquisition baseline under the same channel grouping, split and compute budget; terminal pooling alone cannot answer that question. For live logged acquisition, establish logging-policy support, known randomization or a justified alternative identification design. Complete-feature masking does not reproduce sensor latency, missingness, intervention effects or physical energy.

Improvement acceptance for this development question requires a locked method with macro coverage≥0.50 and every participant coverage≥0.25, smaller J than matched equally trained controls at the declared rights/ costs, no custody violation and explicit correction/damage accounting. Stronger scientific claims additionally require appropriately authorized untouched participant-disjoint evaluation. If these gates fail, retain the failure and needs_evidence; do not use oracle diagnostics to override them.

S4.29. Paid-fusion theory: Source verification, reproducibility and access limits

Scope. Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/ transport conditions remain external.

PRIMARY_EVIDENCE99.json maps each comparison to inspected primary HTML sections, URL, archive version and actual response hash. RETRIEVAL99.json preserves17 permitted HTML responses: the selected eight-paper comparison and earlier retrieved history, linked preprint versions and one author note. Earlier SelectiveNet and replay retrievals are preserved as history and excluded from the final eight comparisons. Original HTML and full visible text are private audit material under _private_primary_HTML and must not be included in public artifacts. Public prose contains paraphrases and no direct source quotation. The author note is ancillary context, never counted as a ninth primary paper or a theorem proof.

The CSL arXiv abstract concatenates its last two author names in one rendered link; the versioned full HTML resolves four authors. ACO's2023 preprint and2024 proceedings are separated, as are GSM's2021 archive version and proceedings. META-DES's2018 deposit is not treated as a2018 original publication. One exploratory guessed arXiv lead2406.03901 resolved to unrelated segmentation work; it was discarded, contributes no comparison or claim, and no PDF was fetched. Search snippets identify leads only.

exact_tests99.py checks66,879 rational assertions across finite atomic identities, conditional posterior lattices, counterexamples, rights and malformed inputs. The measured test CPU and wall time are retained in EXACT_CHECKS99.json; both are below the120s CPU/300s wall bounds. The proofs establish only the stated mathematical implications. These finite tests validate their implementation on small cases and do not verify any population premise.

This author's file writes remain inside the reserved methods scope. No child, lifecycle/portfolio/Git mutation, dependency install, private experiment data, model fit or model API is used. Effective native model telemetry is unavailable; the requested routing label is not evidence of the actual model.

S5. Conditional transfer, exact projections and sensitivity

Every target statement below is conditional on its declared common-law or joint-law assumption. Retrospective projection values reuse overlapping exposed groups and are not calibrated confidence radii. The structure-aware certificate improves an additive upper bound over a named finite portfolio; it is not a new predictive result.

S5.1. Finite model / MHEALTH: Transport beyond the empirical law hull

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Algorithm S10. Exact common-theta finite risk projection
Require: Frozen T5/T6 endpoint J risks of all eleven original named selectors and original reference_b Frozen labeled aggregate J risks for nine overlapping T/C/exposed-DEV diagnostic units
Ensure: Absolute radius eta and contrast radius delta with complete optimal theta intervals All affine candidates, named active witnesses, exact lower certificates and one independent oracle result

1 Set theta to the T5 weight. Form one residual a theta+c for every selector.
2 For contrast projection subtract the same original baseline at target and both T endpoints.
3 Expand both residual signs. Preserve duplicate selector identities as separate constraints.
4 Enumerate theta=0,1 and every in-domain pairwise signed-affine intersection using exact fractions.
5 Evaluate the full maximum at every candidate and find the minimum radius.
6 Intersect every affine inequality at that radius to recover the whole minimizer interval and all active witnesses.
7 Certify the matching global lower bound with a zero-slope convex pair, flat plane, or domain-boundary slope.
8 Check leave-one-selector-out monotonicity without substituting those fits for the full-portfolio result.
9 Run the separately implemented dual-bound oracle once; retain first failures and all local cost scope limits.

$$d_Q(p) = R_Q(p) - R_Q(b)$$

The same actual reference b is used in the target and both nominal T endpoint laws.

$$d_\theta(p) = \theta d_5(p) + (1-\theta) d_6(p)$$

One common θ weights the T5 law for every policy in the fixed portfolio.

$$\delta_Q = \min_{\theta\in[0,1]} \max_{p\in P} \left| d_Q(p) - d_\theta(p) \right|$$

This exact minimum is a retrospective finite-portfolio projection. It is not a population confidence radius.

Table S18: Six-decimal retrospective display. Full exact nine-unit radii and optimal intervals are preserved in Supplement S5.10; units overlap.

Diagnostic unit	Absolute radius η	Paired radius δ	Frozen paired J difference
C5	0.050551	0.074491	0.064338
C6	0.074459	0.026890	-0.027448
Cmacro	0.044413	0.028598	0.018445
DEV7	0.095643	0.101384	0.087081
DEV8	0.113219	0.142422	-0.136946
DEVmacro	0.045844	0.032414	-0.024932




Figure S13: Retrospective transport diagnostics. (a) Candidate-minus-reference contrasts, with nominal T values±Γ shown as vertical dashed lines. (b) Exact paired-risk projection residuals. Units overlap; points and lines are descriptive exact aggregates, not confidence intervals or calibrated safety thresholds.

S5.2. Finite model / MHEALTH: Conditional transfer and an identification limit

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$R_Q(\pi) - R_Q(b) \le -\Gamma + \delta$$

Conditional on a valid common-θ componentwise contrast residual bound δ and nominal mixture contrast at most minus Γ.

$$R_Q(\pi) - R_Q(b) \le -\Gamma + 2\eta$$

Separate absolute risk residuals at most η for every component and the same reference imply the looser contrast bound.

S5.3. Finite model / MHEALTH: Structure-aware conditional safety

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Algorithm S11. Shared-state oscillation and exact conditional TV portfolio design
Require: Original11 named frozen selector forests/weights, exact T5/T6 J endpoints and original b A shared fixed multiclass predictor state contract and independently justified joint-law TV radius rho in[0,1]
Ensure: Exact additive-certificate envelope, all rational boundaries/active mixture vertices and baseline fallback Shared-h oscillation witnesses and whole-interval primal/dual certificates, or explicit failure

1 Expand every frozen component forest on16 binary feature worlds into observed mask/value, terminal action and exact tariff, retaining initial quote.
2 At each world combine selector-minus-b STOP coefficients by shared state before maximizing any prediction.
3 Enumerate256 ordered world pairs and same/different label patterns; for different labels include prediction equal to either label or neither.
4 Sum statewise maxima to obtain exact sup_h oscillation s_i and a simultaneous shared-h witness; keep all11 names/duplicates.
5 Form every singleton and every opposite-sign endpoint-difference balanced pair with fixed rational weights.
6 Construct each candidate line max_g(sum_i w_i d_ig)+rho sum_i w_i s_i. Enumerate all line intersections in[0,1] and recover the complete lower envelope and ties.
7 At every breakpoint intersect all named dual inequalities to obtain the full theta interval and nonnegative row slacks.
8 On each segment interpolate endpoint duals and retain one fixed primal mixture; affine row slacks certify the entire interval.

9 Use a negative-bound fixed ex ante mixture; at a zero bound use the exact b. The guarantee requires the external common-theta joint-law TV assumption.

10 Run the separately written explicit-assignment/parametric-dual oracle once; preserve first failures, original strong controls, no_gain and unknown whole costs.

$$\mathrm{TV}(Q^\star, P_\theta^\star) \le \rho, \quad P_\theta^\star = \theta P_5^\star + (1-\theta) P_6^\star$$

One common θ and a joint law over tokens, labels and per-mask predictions are required. The target-radius assumption remains unverified.

$$B_s(\rho) = \min_{w \in \Delta_{11}} \max_{g \in \{5,6\}} \sum_i w_i \left(d_{ig} + \rho s_i\right)$$

Delta_11 is the probability simplex over the eleven named selectors, including the exact reference. d_{ig} is the frozen nominal candidate-minus-reference endpoint loss.

$$B_s(\rho) = \min\left(0, -\frac{2091}{205940} + \left(\frac{5989}{2942}\right)\rho\right)$$

The complete radius result for the structure-aware additive certificate. The coarse comparison replaces 5989/2942 with 11/5 for nonbaseline names; baseline sensitivity stays zero in both.

Table S19: Exact conditional certificate with the same frozen11-name portfolio and exact-zero baseline. B(ρ) is the best additive upper bound on excess loss; use b at the zero-boundary tie.

Sensitivity rule	B(ρ)	Fallback radius
Structure	min(0,-2091/205940+(5989/2942)ρ)	2091/419230
Uniform coarse	min(0,-2091/205940+(11/5)ρ)	2091/453068




Figure S14: Conditional analytical upper certificate under an externally justified joint-law TV radius. Blue and dashed vermillion curves use the same nominal portfolio and baseline. The lightly shaded interval is the additional certified-radius range; it is not a confidence interval, target measurement or predictive gain.

S5.4. Finite model / MHEALTH: Risk units, reference identity and preserved controls

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

All eleven original selector names, weights and forest identities are pinned. Equal risk vectors are not deduplicated. The original the original reference b endpoints and source identity are retained and the published C/DEV paired gaps are checked against direct subtraction. A substituted reference is rejected.

The existing loss charges errors 1 and abstention 2/5 and retains the common initial quote where applicable. The new computation consumes J aggregates only. No raw cache, policy actor, sealed source import/replay, new data, network or model call is used. The toy and synthetic tests are separate from these retained empirical rows.

Table S20: Exact retained risks, not new evaluation runs; all identities including duplicates are kept.

Selector	T5	T6
Tmean A	43/280	111/385

Selector	T5	T6
Tmean F	37/280	967/3080
Tmean M	43/280	111/385
Tmean committed2	289/1680	929/3080
Tmean no abstain A	43/280	111/385
paired A	42039/205940	638949/2265340
paired M	42039/205940	638949/2265340
reference b	3/14	45/154
robust A	377/1680	123/440
robust F	3/14	45/154
robust M	377/1680	123/440

Table S21: Exact retained risks, not new evaluation runs; all identities including duplicates are kept.

Selector	C5	C6	Cmacro
Tmean A	4/15	7/20	37/120
Tmean F	247/960	313/960	7/24
Tmean M	4/15	7/20	37/120
Tmean committed2	27/128	71/192	223/768
Tmean no abstain A	4/15	7/20	37/120
paired A	423301/1412160	159677/470720	225583/706080
paired M	423301/1412160	159677/470720	225583/706080
reference b	113/480	11/30	289/960
robust A	601/1920	643/1920	311/960
robust F	113/480	11/30	289/960
robust M	601/1920	643/1920	311/960

Table S22: Exact retained risks, not new evaluation runs; all identities including duplicates are kept.

Selector	DEV7	DEV8	DEVmacro
Tmean A	11/35	187/645	1364/4515
Tmean F	214/665	459/1720	134663/457520
Tmean M	11/35	187/645	1364/4515
Tmean committed2	75/266	647/2580	182801/686280
Tmean no abstain A	11/35	187/645	1364/4515
paired A	349964/978215	1018933/3795180	316099513/1009517880
paired M	349964/978215	1018933/3795180	316099513/1009517880
reference b	36/133	523/1290	115999/343140
robust A	499/1330	447/1720	145279/457520
robust F	36/133	523/1290	115999/343140
robust M	499/1330	447/1720	145279/457520

S5.5. Finite model / MHEALTH: Exact envelope algorithm and complete optimal intervals

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For each target and mode the residuals are a_p θ+c_p. The objective is max of their positive and negative affine forms. It is convex and piecewise affine on [0,1]. A minimum occurs at a boundary or an affine intersection, or along a flat segment whose endpoints are included. Exhaustive candidate evaluation therefore recovers the exact minimum without a regular grid.

After finding ρ^*, intersect all inequalities a_i θ+c_i<=ρ^* with [0,1]. This returns the whole closed optimizer interval, including flat intervals and coincident ties. Every plane active anywhere on the interval is recorded with its exact active subinterval. Positive and negative zero residuals and duplicate names remain explicit.

S5.6. Finite model / MHEALTH: Lower certificates, independent oracle and subset checks

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A convex combination of signed planes lies below their maximum everywhere. Its global minimum on [0,1] is c_bar+min(0,a_bar). The main solver selects a matching active zero-slope pair, constant plane, or valid boundary slope. The certificate lower bound equals the feasible upper value exactly, so the primal-dual gap is zero.

The oracle independently parses the two original aggregate JSON files and uses all single-plane boundary bounds and zero-slope opposite-slope pairs to find the radius. It imports neither the main solver nor its parser. It verifies all candidate intersections/evaluations, optimizer intervals, active witnesses, lower certificates and 198 leave-one-selector-out intervals. Independent code is not independent data.

Dropping a selector weakly decreases the objective at every θ, hence cannot increase its minimum. These subset checks are negative consistency checks; their fitted θ never replaces the declared full-portfolio common θ. With m<=22 signed planes, the main enumeration takes O(m^3) rational operations plus O(m^2 log m) sorting, and O(m^2) stored candidates. Fraction bit complexity is not bounded by this operation count.

Table S23: Matching lower bounds certify the exact minima; complete active witnesses and candidate ties are in PROJECTIONS.json. Every optimal interval here is a singleton; its sole θ value is shown.

Unit	Mode	Radius	$\theta^\star$
T5	absolute	0	1
T5	contrast	0	1
T6	absolute	0	0
T6	contrast	0	0
Tmacro	absolute	0	1/2
Tmacro	contrast	0	1/2
C5	absolute	579877/11471040	4229/13656
C5	contrast	245451/3295040	8149/11768
C6	absolute	86/1155	0
C6	contrast	141007/5243840	6397/18728
Cmacro	absolute	469/10560	0
Cmacro	contrast	282697/9885120	1803/5884
DEV7	absolute	5597/58520	0
DEV7	contrast	1262649/12454120	30828/44479
DEV8	absolute	5623/49665	0
DEV8	contrast	7078537/49701120	12391/29584
DEVmacro	absolute	173039/3774540	0
DEVmacro	contrast	25581757/789222000	2213003/2348875

Table S24: Matching lower bounds certify the exact minima; complete active witnesses and candidate ties are in PROJECTIONS.json.

Unit	Mode	Dual planes	Lower bound
T5	absolute	1*Tmean A:-1	0
T5	contrast	1*Tmean A:-1	0
T6	absolute	1*Tmean A:1	0
T6	contrast	1*Tmean A:1	0
Tmacro	absolute	1/2*Tmean A:-1 + 1/2*Tmean A:1	0
Tmacro	contrast	1*paired A:-1	0
C5	absolute	1019/3414*Tmean committed2:-1 + 2395/3414*robust A:1	579877/11471040
C5	contrast	1*paired A:1	245451/3295040
C6	absolute	1*reference b:1	86/1155
C6	contrast	421/2341*Tmean F:-1 + 1920/2341*robust A:-1	141007/5243840
Cmacro	absolute	1*robust A:1	469/10560
Cmacro	contrast	1*paired A:1	282697/9885120
DEV7	absolute	1*robust A:1	5597/58520
DEV7	contrast	1920/2341*robust A:1 + 421/2341*Tmean F:1	1262649/12454120
DEV8	absolute	1*reference b:1	5623/49665
DEV8	contrast	421/1376*Tmean committed2:-1 + 955/1376*robust A:-1	7078537/49701120
DEVmacro	absolute	1*reference b:1	173039/3774540
DEVmacro	contrast	384/575*Tmean committed2:-1 + 191/575*Tmean F:1	25581757/789222000

S5.7. Finite model / MHEALTH: Conditional transfer proof, sharpness and fallback

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Conditional transfer. Fix deterministic components p_i and ex ante weights w_i>=0 with sum w_i=1, sampled independently of each episode. Use the same reference b, loss/cost definition and finite expectations. For a common θ suppose sum_i w_i[R_theta(p_i)-R_theta(b)]<=-Γ and |[Q(p_i)-Q(b)]-[R_theta(p_i)-R_theta(b)]|<=δ for every positive-weight component. Then Q(pi)-Q(b)<=-Γ+δ. The proof is linearity of expectation followed by the componentwise upper residual bound; no independent component outcomes are required.

If component and reference absolute residuals are each at most η, subtraction gives contrast residual at most 2eta and the bound becomes -Γ+2eta. Both constants are attainable when a bounded-risk construction permits opposite signed perturbations. A certificate at both T endpoints holds for every θ. Projection of aggregate randomized selectors does not certify their unavailable deterministic-component residuals.

A fixed baseline mixture (1-α)b+α pi has contrast bound α(-Γ+δ); uncertainty scales with the nonbaseline weight. Fallback to b is justified only when an independently valid target uncertainty set fails to certify nonpositive contrast for the fixed proposal. No such uncertainty set is supplied or fitted here, no new policy is selected, and no generic optimal-switch theorem is asserted.

Proof detail: Q(pi)-Q(b)=sum_i w_i{R_theta(p_i)-R_theta(b)+h_i(θ)}. The certified T term is at most -Γ and sum_i w_i h_i<=δ. The absolute-risk statement follows from h_i=e_i-e_b<=2eta. For one component, taking h_i=δ attains the first constant. Raising component risk by η and lowering baseline risk by η attains the second, provided the chosen base risks keep the construction feasible. These are logical constructions, not empirical measurements.

$$R_Q(\pi) - R_Q(b) \le -\Gamma + \delta$$

Conditional on a valid common-θ componentwise contrast residual bound δ and nominal mixture contrast at most minus Γ.

$$R_Q(\pi) - R_Q(b) \le -\Gamma + 2\eta$$

Separate absolute risk residuals at most η for every component and the same reference imply the looser contrast bound.

S5.8. Finite model / MHEALTH: Same unlabeled observations with opposite gain signs

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Unlabeled nonidentifiability. The same frozen predictor returns 0 on a constant initial observation and 1 after a constant acquired observation. Acquisition costs 1/20 in both laws. If Y=1 always, candidate-minus-baseline is -19/20; if Y=0 always, it is +21/20. Every unlabeled history has the same law. Common initial quotes cancel; abstention is unused. This general toy is not a membership claim about the actual 38-history grammar or the foreign noisy-repeat study.

The initial score is fixed at 1/2 and the acquired value is fixed at 1 in both worlds. The shared predictor depends only on which history is available. With error loss 1, the acquired policy has risk 1/20 versus baseline 1 in the all-one label world; it has risk 21/20 versus baseline 0 in the all-zero world. Thus even infinite unlabeled observations cannot distinguish the two gain signs. The construction establishes an identification limit without asserting the actual benchmark admits these histories.

S5.9. Finite model / MHEALTH: Execution provenance, costs and next acceptance

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The study is retrospective. Root had already seen the aggregates; the author physically read and parsed whole aggregate JSON files for schema inspection before sealing, without displaying or semantically analyzing numeric risks. Strict sealing before all physical numeric access was not met. Source/tests/contract were sealed before the one main numeric analysis and the one separately implemented oracle. No blind preregistration is claimed.

The durable ledger declares 18 primary cells and 198 subset checks, then records starts and outcomes. Main and oracle each have one allowed attempt, with sealed-source checks and user-control gates. First errors, exhaustion or unknown outcomes are preserved rather than retried or repaired after sealing. The current success statement is local arithmetic validation only.

The measured costs below cover only the two local Python processes. Explicit input/output bytes sum the declared files, rather than OS-wide I/O. Wall times are displayed to six decimals; COSTS.json retains their full recorded precision and separate supervisor observations. Schema-inspection I/O and preparation/finalization

CPU were not metered. Native authoring, host CPU, RAM, external account costs and total research cost remain unknown; no whole-cost closure is claimed.

Next acceptance requires independent review of exact rows, identity, assumptions, proof and sealing limitation. A performance claim requires a separately authorized untouched labeled final evaluation with frozen controls and a justified independently supplied uncertainty model. Related-work priority and scientific certification remain separate review boundaries.

Table S25: Observed local Python process costs only. File bytes are explicit-file counts, not physical I/O counters. No whole-research efficiency claim follows.

Process	PID	CPU seconds	Wall seconds	Input bytes	Output bytes
main	9840	0.953125	3.652569	43118	238400
oracle	72008	0.656250	2.158472	262421	10200

S5.10. Finite model / MHEALTH: Full exact projection tables behind the main display

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

These are the original exact author tables; the main display rounds only for readability. Diagnostic units overlap and are not independent evaluation samples. The two tables together preserve every field of the original seven-column table.

Table S26: Exact retrospective projection of all eleven selectors. Theta weights T5. Units overlap; radii require target labels. Every optimal interval here is a singleton; its sole θ value is shown.

Unit	η	$\theta^\star$
T5	0	1
T6	0	0
Tmacro	0	1/2
C5	579877/11471040	4229/13656
C6	86/1155	0
Cmacro	469/10560	0
DEV7	5597/58520	0
DEV8	5623/49665	0
DEVmacro	173039/3774540	0

Table S27: Exact retrospective projection of all eleven selectors. Theta weights T5. Units overlap; radii require target labels. Every optimal interval here is a singleton; its sole θ value is shown.

Unit	δ	$\theta^\star$	paired A minus b	committed2 minus b
T5	0	1	-2091/205940	-71/1680
T6	0	0	-2091/205940	29/3080
Tmacro	0	1/2	-2091/205940	-607/36960
C5	245451/3295040	8149/11768	6057/94144	-47/1920
C6	141007/5243840	6397/18728	-38761/1412160	1/320
Cmacro	282697/9885120	1803/5884	26047/1412160	-41/3840
DEV7	1262649/12454120	30828/44479	85184/978215	3/266
DEV8	7078537/49701120	12391/29584	-519733/3795180	-133/860
DEVmacro	25581757/789222000	2213003/2348875	-5033909/201903576	-16399/228760

S5.11. Finite model / MHEALTH: Frozen architecture and trust boundaries

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Data flow: hash-checked original T_SOLUTIONS/RESULT and derived grammar -> new forest-state compiler -> shared-state oscillation -> finite candidate LP envelope -> exact certificates -> independent oracle -> frozen report. Original scientific modules and cached examples are never imported or replayed.

The author owns only the science directory. Main and oracle are separate bounded local processes with one attempt each after source sealing. Existing campaign control is read-only at phase boundaries. Root owns actual Task lifecycle, FIFO, separate reviewer and publication integration. Native support is not a canonical campaign intake. The detailed permissions and metadata are in POLICY.md and SEAL.json.

The state contract is h(mask,values), shared across policies and both probability laws. Additional hidden predictor state or order-sensitive inputs would require a different theorem. Acquisition/abstention tariffs are exact; no quote reduction is reinterpreted as physical sensor savings.

S5.12. Finite model / MHEALTH: Proof and full continuous-radius procedure

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For D_i^h(x,y)=c_i(x)+sum_s a_i(x,s)1{h(s)!=y}, interchange the finite maxima over h and ordered worlds. For each shared state maximize the combined two-world coefficient over correct/other when labels coincide, and equal-first/equal-second/other when they differ. K>=3 allows every chosen state category to be realized by a single global h. This proves exact sup_h oscillation and rules out incompatible predictor extrema.

For TV=sup_A|Q(A)-P(A)|, any bounded f satisfies |E_Q f-E_P f|<=TV(Q,P)osc(f), by scaling f into[0,1] and integrating level sets. Apply this to each selector contrast under one common P_theta and sum fixed nonnegative ex ante weights. The maximum over θ is attained at a T endpoint. The additive sensitivity bound need not equal the actual mixture oscillation.

An optimal basic solution of the two-endpoint simplex LP has at most two positive weights. Two-positive solutions balance Delta_i=d_i5-d_i6, so their rational weights are independent of ρ. All singleton/opposite-sign balanced pairs yield a complete candidate vertex family; their affine lower envelope gives the exact value for every ρ. The full optimal mixture set is the convex hull of active vertices, including named duplicate policies.

Every breakpoint dual interval is obtained by intersecting all 11 exact inequalities. On each segment, interpolating endpoint dual thetas yields affine slacks nonnegative at both ends and therefore throughout; one fixed primal mixture has the same affine value. Raw candidate intersections, ties, row slacks and all positive-radius boundaries are retained in CERTIFICATES.json. No radius grid is used. The full derivation is THEORY.md.

S5.13. Finite model / MHEALTH: Independent oracle, complexity and cost scope

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The independent oracle uses a separately written recursive state walker and explicit products of 2/3 prediction categories on every relevant state, with at most6 states and729 assignments per pair. It independently checks all 5632 pair maxima. It constructs feasible parametric dual bases, their exact validity intervals and their arrangement envelope, rather than importing the main primal solver.

For n selectors, W worlds and k relevant shared states, main sensitivity costs O(n W^2 k) rational operations and explicit oracle O(n W^2 3^k k). Main candidate count is at most n(n+1)/2; transparent complete intersection/evaluation costs O(c^3) rational operations. These are arithmetic-operation bounds with input-dependent bit cost. Retaining all pair rows and candidate intersections costs O(n W^2 k+c^2) storage.

Actual main/oracle local process CPU and wall clocks, executable/source/input/output hashes and byte counts are in the execution ledger and cost artifact. They do not measure native authoring tokens, host CPU/RAM, physical I/O, or total research cost. Each own process has a600s bound and scientific attempts are main1/oracle1. First failures and unknowns remain preserved.

S5.14. Finite model / MHEALTH: Uncertainty assumption, failure cases and next acceptance

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Without an independently justified ρ and common-θ joint-law coverage, the certificate supplies no target safety guarantee. A nominal optimum on the T mixture is not a calibrated population certificate. Same unlabeled histories can coexist with different label laws; prior transport review47 already preserves this identification limit and overlapping-unit dependence.

Baseline fallback is exact because L_b-L_b=0. A zero optimized certificate includes baseline ties and does not mean an actual nonbaseline policy is harmful. A negative certificate is sufficient conditional on the assumption; failure of that certificate does not prove all actual contrasts positive.

Distinct arithmetic/provenance/method review is the next acceptance step. A population or prediction claim additionally requires a separately authorized untouched labeled final, justified uncertainty coverage, strong fixed controls and measured costs. Related-work primary citations and priority are unresolved in this no-network study.

S5.15. Finite model / MHEALTH: Independent larger-world applicability proof

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The original shared-token h theorem does not establish sufficiency of the binary history for the per-mask cache. The separate reviewer expands all frozen component forests and permits unrelated predictions at different masks within an episode, sharing only identical terminal masks. Distinct episodes have no prediction-equality constraint. For each binary token world it enumerates the allowed correctness choices and takes exact pointwise extrema.

The verified intervals are T-mean adaptive/M/no-abstain:[-1,1], T-mean fixed:[-21/20,1], the two-additional committed control:[-19/20,21/20], robust adaptive/M:[-1,21/20], paired adaptive/M:[-1,3047/2942], and the baseline identities:[0,0]. Thus the same 2,41/20 and5989/2942 upper sensitivities apply in the larger joint (tokens,label,per-mask-predictions) space. These are valid uniform upper bounds; the original finite-token sharpness is not transferred to a more restricted actual predictor or claimed as sharp mixture DRO.

At a fixed policy, TV(Q,P_theta)<=ρ in that common joint space implies excess loss <=d_i(θ)+ρ*s_i. Linearity and max over the two nominal endpoints give the outer-mixture certificate. The independent review reconstructs original endpoints, shared-state witnesses, all candidate mixtures and every exact radius interval without executing either frozen scientific actor. Actual source/Task/hash bindings are retained in the method-review record; the external target radius is still unverified.

Marginal coverage is insufficient. As a synthetic logical example, keep x=8 and y=0. T-mean adaptive terminates at mask5 and b at mask9 with the same quote count. A point mass with p5=0,p9=1 has contrast -1; reversing these two predictions gives contrast+1. The token/label marginals have TV0, while the augmented laws have TV1. This illustrates the required joint-law assumption, not an observed cache violation or a new empirical sample.

Mask-based sharing assumes the same episode and acquired mask give the same frozen prediction across policies and query orders. A stateful, order-sensitive or newly randomized classifier needs another bound. Hidden prediction-vector coordinates are available only to mathematical evaluation, not to the online policy.

$$\Omega = \{0,1\}^4 \times \mathcal{Y} \times \mathcal{Y}^{\mathcal{M}}$$

The augmented world contains tokens x, target label y and one prediction p_m per permitted acquired mask. A richer original feature distribution is pushed forward to this joint space.

$$D_i(\omega) = c_i(x) + \sum_m a_i(x,m)\mathbf{1}\{p_m \neq y\}$$

Collect coefficients at identical terminal masks before minimizing or maximizing the correctness bits.

$$\ell_i(x) = c_i(x) + \sum_m \min(0, a_i(x,m)), \quad u_i(x) = c_i(x) + \sum_m \max(0, a_i(x,m))$$

Global pointwise ranges follow by minimizing and maximizing over the sixteen token worlds. Distinct episodes need no prediction-equality assumption.

S6. MHEALTH: complete methods, controls and participant outcomes

This chapter concerns the historical MHEALTH token/prediction cache only. T/C reuse fitting people 5 and 6; DEV uses already exposed people 7 and 8 with 266 and 258 dependent windows. The paid mandatory initial token is included. The strong historical committed token-2 control and the distinct two-additional global-order control are never merged.

S6.1. Finite model / MHEALTH: Frozen empirical study

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$J(\pi) = \left(\frac{1}{2}\right) \sum_{s\in\{7,8\}} \frac{E_s + \left(\frac{2}{5}\right)A_s + \left(\frac{1}{20}\right)C_s}{n_s}$$

Compute each participant objective first and average participants equally; the mandatory initial quote is included in C.

$$r_T = \frac{e_T}{n_T}, \quad r_{\text{cal}} = \frac{e_C + 64 r_T}{n_C + 64}$$

Empty T uses risk 1/2; empty C returns the empirical risk. Both estimators retain T-based acquisition transitions.

S6.2. Finite model / MHEALTH: Strong static controls and negative findings

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

$$\frac{10667}{1372560} = \left(-\frac{49}{44880}\right) + \left(\frac{9479}{1069453}\right)$$

Exact decomposition of the empirical adaptive-minus-selected-order contrast. A zero arithmetic residual does not identify a causal mechanism.

S6.3. Finite model / MHEALTH: Learning over the complete supported grammar

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Algorithm S12. Exact global-law acquisition with a fixed same-law reference
Require: Frozen seven-mask predictor cache; two empirical T group laws; common support and two-query rights. Prediction loss 1, abstention loss 2/5, quote cost 1/20; predeclared ties and unsupported-state fallback.
Ensure: Complete-class fixed reference vector b, adaptive mixture, primal/dual witnesses and Gamma. Frozen training solution and once-read C diagnostic / DEV metrics with all controls.

1. Seal source, contract, synthetic tests and source hashes before scientific T access.
2. Compute unnormalized two-group occupancy and error masses at every legal history.
3. Construct exact rational lower envelopes for STOP, abstention and each supported query; keep a feasible global forest with every active affine piece.
4. Sum both root envelopes. For F, minimize over one global query order after summing roots. Never reset theta inside a branch.
5. Maximize the F lower envelope; recover a feasible one- or two-forest reference and freeze b.
6. Maximize V_A(theta)-theta*b5-(1-theta)*b6. Recover active one-sided forest witnesses and verify both endpoint inequalities. Use the reference if Gamma is not strictly positive.
7. Freeze every selected forest, mixture weight, tie and coefficient before C scoring and first DEV read; C is diagnostic only.
8. Check all legal global forests in separately written code, then obtain a distinct native reviewer. Retain every no-gain and regression; report mixtures as exact expectations.

S6.4. Finite model / MHEALTH: Positive reference-relative evidence and its limits

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Table S28: New complete-grammar experiment: expected DEV metrics, including initial acquisition cost. Values rounded to six decimals; exact rational values appear in Supplement S6.35. Lower J is better. Each row uses the same exposed 524 windows.

Policy	J	Error	Abstain	Quotes	Coverage
Mean adaptive	0.302104	0.202104	0.000000	2.000000	1.000000
Selected fixed	0.294332	0.215145	0.000000	1.583741	1.000000
Committed static	0.251294	0.151294	0.000000	2.000000	1.000000
Robust fixed	0.338052	0.174317	0.159337	2.000000	0.840663
Robust adaptive	0.317536	0.163461	0.100790	2.275179	0.899210
Paired adaptive	0.313119	0.174521	0.071944	2.196423	0.928056





Figure S15: Complete-grammar evidence. (a) Exposed-DEV macro loss retains the stronger historical committed-token2 control. (b) Endpoint dumbbells show the fixed reference and paired policy on T5/T6; both reductions equal 2091/205940. Mixture totals are exact expectations, not fresh randomized episodes.

S6.5. Finite model / MHEALTH: Negative development findings

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Supplement Figure S16 shows the central negative comparison. Empirical adaptive and myopic acquisition have identical objective 1364/4515, approximately 0.302104. The fitting-selected fixed_2 order has 134663/457520, approximately 0.294332, and the separately selected forced subset_2 has 28743/114380, approximately 0.251294. Lower is better. Empirical adaptive acquisition regresses against both controls. It and fixed_2 predict on all windows, so their difference cannot be attributed to different prediction coverage. The saved paired counts show that fewer errors fail to offset the extra quote cost.




Exposed DEV: 2 participants, 524 dependent windows; independent final participants = 0.

Figure S16: Frozen exposed-DEV objectives with empirical and calibrated selectors in separate panels. Adaptive/myopic ties, optional fixed orders and forced subsets retain their actual selection and stopping rights. Both panels use the same 524 dependent windows from two previously exposed participants.

S6.6. Finite model / MHEALTH: Coverage, correction, harm, and cost

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Supplement Figure S17 separates the outcome components that a single objective hides. Calibrated adaptive acquisition predicts on 441 of 524 windows, leaving 83 abstentions. The pooled coverage 441/524 differs from participant-macro coverage 19231/22876 because the participants have different denominators. The error panel uses unconditional participant-macro error contribution, not error conditional on prediction. Coverage and error are shown in separate labeled panels precisely because their denominators and weights differ.



Calibrated abstentions: 83/524. Coverage and error use different weights; neither panel is conditional accuracy.

Figure S17: Different outcome units in the exposed DEV diagnostic. (a) Pooled predicted-window coverage:441/524 under calibration. (b) Unconditional participant-macro error contribution. The83 abstentions change coverage; neither panel gives conditional accuracy on predictions.

S6.7. Finite model / MHEALTH: Learning over the complete supported grammar

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The new learner removes that menu restriction. After mandatory initial token 0, it may acquire at most two distinct tokens among 1, 2 and 3. Legal masks are 1,3,5,9,7,11,13; mask 15 is forbidden. At every history, STOP with the frozen predictor and abstention remain available. Additional acquisitions require raw T support at least 30 with both participants at the state and every positive child. Loss is prediction error plus (2/5) abstention plus quotes/20, including the initial quote.




Figure S18: Complete-law acquisition procedure. Both initial roots use one common law parameter. The full fixed-order reference and its endpoint vector are frozen before direct reference-relative optimization and exposed-target evaluation. No prospective target safety is inferred.

S6.8. Finite model / MHEALTH: Cached bank, fitting split, and eligible states

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Mandatory group 0 corresponds to mask bit 1. At most two of optional groups 1, 2, and 3 may be added, so eligible masks are 1, 3, 5, 9, 7, 11, and 13. The last three are terminal, and mask 15 is not in the bank's domain. The domain predicate must run before prediction metadata and successor lookup. Asking for metadata at an impossible future mask reproduced a prior execution failure; the corrected shared rule applies consistently to planning and execution.

A state stores already observed group tokens. The frozen bank has 38 eligible states per estimator. State identity is shared by metadata, transition, and execution functions, although a policy's chosen action can also depend on family, remaining depth, and fixed-order suffix. The 1,444 saved state-decision checks are therefore a different count from 38. They describe verification work, not additional states or scientific samples. Tokens summarize an existing bank rather than fresh physical acquisitions.

Fitting rows come from participants 5 and 6. The preserved split puts rows with the index-block predicate $((\text{index}//8)\%5)<3$ into T and the rest into C. T has 168 and 154 rows, totaling 322; C has 96 from each, totaling 192. The combined fitting bank has 514 complete rows. Row-uniform and participant-uniform distributions differ because the T counts differ. An equal-participant development objective does not automatically make the risk estimator participant-balanced.

The current empirical terminal risk is the compatible T error rate, using 1/2 at empty T. Calibrated terminal risk adds compatible C errors to 64 times empirical risk and divides by C count plus 64; if C is empty it returns empirical risk. Both acquisition kernels use conditional T token counts. These choices define a finite surrogate, but no common joint posterior is asserted for the statewise calibrated risk and T transition combination. Its exact plan is a plan in that surrogate.

S6.9. Finite model / MHEALTH: Support, terminal rights, and frozen selection

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Current support requires at least 30 compatible T rows and the participant set exactly {5,6}. A proposed acquisition must satisfy support at the current state and every successor with positive T transition probability. Unsupported actions disappear from the acquisition menu. STOP and abstention remain, choosing the smaller estimated risk and 2/5, with STOP on an exact tie. Empty orders, blocked next steps, unsupported states,

and exhausted depth all share this terminal rule. A control is not forced to make a bad prediction solely because it cannot continue.

The order fixed_23 may acquire group 2 and then group 3, but it can stop before either query based on observed history. It does not promise to measure subset {2,3} on every window. The empirical fixed_2 mean quote count 15527/9804 includes the mandatory quote and optional continuation only on some windows. A strict subset_2 instead acquires group 2 whenever supported, without an early risk-based stop, and has mean quote count two. Their names do not make them interchangeable controls.

Each forced subset uses a canonical increasing order and the common support fallback. Completion and blocked continuation both select the common best terminal. Some two-group subsets fail to attain their target, so attainment and fallback are reported. The selected empirical subset_2 and calibrated subset_3 attain every window and have zero support fallback. The former is therefore a completed strong static counterexample under the actual support contract, not an impossible idealized measurement set.

Selection uses T and C only in the current execution. The fitting-selected empirical order is fixed_2 and the calibrated order fixed_32; selected forced subsets are determined separately. Every policy table and reference selection is frozen before the recorded first DEV byte read. Looking at all DEV rows remains useful descriptively, but replacing the chosen reference with the smallest DEV row would be post-hoc selection. Preserved selection chronology is a cooperative provenance fact and does not certify that the research lineage had never seen these participants.

S6.10. Finite model / MHEALTH: Complete core-policy and forced-subset tables

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The next tables retain all 24 core policies and all 14 forced-subset policies. Rows are copied from the final frozen source with exact fractions and unchanged policy identifiers. Column headings and captions are translated into English. Macro means each participant's rate is computed first and the two participants are weighted equally. Unconditional error, mean quotes, coverage, estimated objective, and target attainment have separate meanings. Fallback totals are counts, not participant-macro rates.

Equal rows are retained because different permitted orders can lead to the same realized policy. Estimated J and DEV J refer to different distributions and should not be compared as repeated estimates of one fixed quantity. Empirical fixed_32 is better than the selected empirical order on DEV but was not the fitting-selected reference. Likewise, a better DEV calibrated subset does not change the selected subset_3. Keeping both selected and post-hoc alternatives makes the selection mismatch visible without granting retroactive selection rights.

The empirical subset_2 exact objective is 28743/114380, whose six-place display is 0.251294. The calibrated selected subset_3 exact objective is 115999/343140, displayed as 0.338052. Displays are rounded only for readability; checks and source comparisons use fractions. The tables do not merge their units with logical routed-model expectations or external paper performance. They contain no confidence intervals because no new independent final sample or sampling design supports one.

Table S29: S5. All 24 core policies; exact participant-macro quantities.

Policy	Macro J	Error contribution	Mean quotes	Coverage	Estimated J
empirical::adaptive	1364/4515	365/1806	2	1	2648/12155
empirical::myopic	1364/4515	365/1806	2	1	2648/12155
empirical::fixed empty	7057/16340	312/817	1	1	482899/1896180
empirical::fixed 1	7057/16340	312/817	1	1	482899/1896180
empirical::fixed 2	134663/457520	14765/68628	15527/9804	1	127741/583440
empirical::fixed 3	115999/343140	1709/9804	2	19231/22876	15881/63206
empirical::fixed 12	7057/16340	312/817	1	1	482899/1896180
empirical::fixed 13	7057/16340	312/817	1	1	482899/1896180
empirical::fixed 21	134663/457520	14765/68628	15527/9804	1	127741/583440
empirical::fixed 23	134663/457520	14765/68628	15527/9804	1	127741/583440
empirical::fixed 31	115999/343140	1709/9804	2	19231/22876	15881/63206
empirical::fixed 32	182801/686280	5587/68628	83191/34314	19231/22876	591057/2528240
calibrated::adaptive	10141/39216	463/4902	3205/1596	19231/22876	188791397/841903920
calibrated::myopic	10141/39216	463/4902	3205/1596	19231/22876	188791397/841903920
calibrated::fixed empty	7057/16340	312/817	1	1	220433119/864658080
calibrated::fixed 1	7057/16340	312/817	1	1	220433119/864658080

Policy	Macro J	Error contribution	Mean quotes	Coverage	Estimated J
calibrated::fixed 2	157023/457520	10565/68628	15527/9804	16581/22876	651047/2585700
calibrated::fixed 3	453329/1372560	2143/11438	15527/9804	19231/22876	28990279/118037205
calibrated::fixed 12	7057/16340	312/817	1	1	220433119/864658080
calibrated::fixed 13	7057/16340	312/817	1	1	220433119/864658080
calibrated::fixed 21	157023/457520	10565/68628	15527/9804	16581/22876	651047/2585700
calibrated::fixed 23	157023/457520	10565/68628	15527/9804	16581/22876	651047/2585700
calibrated::fixed 31	453329/1372560	2143/11438	15527/9804	19231/22876	28990279/118037205
calibrated::fixed 32	10141/39216	463/4902	3205/1596	19231/22876	188791397/841903920

Table S30: S6. All 14 forced subsets, including target attainment and support fallback.

Policy	Macro J	Error contribution	Mean quotes	Coverage	Subset attainment	Fallback count
empirical::subset empty	7057/16340	312/817	1	1	1	0
empirical::subset 1	156491/343140	18425/68628	2	26801/34314	1	0
empirical::subset 2	28743/114380	3461/22876	2	1	1	0
empirical::subset 3	115999/343140	1709/9804	2	19231/22876	1	0
empirical::subset 12	112319/343140	3761/34314	44657/17157	26801/34314	10343/17157	208
empirical::subset 13	175531/457520	1531/11438	174521/68628	11896/17157	37265/68628	239
empirical::subset 23	1213/4515	2629/17157	39608/17157	1	5294/17157	364
calibrated::subset empty	7057/16340	312/817	1	1	1	0
calibrated::subset 1	163319/343140	25801/68628	2	1	1	0
calibrated::subset 2	1807/6020	2061/22876	2	16581/22876	1	0
calibrated::subset 3	115999/343140	1709/9804	2	19231/22876	1	0
calibrated::subset 12	135343/343140	2225/11438	44657/17157	14165/17157	10343/17157	208
calibrated::subset 13	36927/91504	1183/4902	174521/68628	10435/11438	37265/68628	239
calibrated::subset 23	54479/171570	1579/17157	39608/17157	16581/22876	5294/17157	364

S6.11. Finite model / MHEALTH: Participant-level outcomes and paired raw counts

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Participant 7 has n=266 and participant 8 has n=258. Each core-policy row below retains errors, abstentions, quote sum, total objective, coverage, and fallback. Recompute J by adding error count, 2/5 times abstention count, and 1/20 times quote sum, then dividing by that participant's n. Error excludes abstention, while J charges it explicitly. The two participant values are not confidence-interval endpoints and are insufficient to establish subgroup generalization.

The paired table preserves candidate, participant, reference, corrections, harms, jointly predicted windows, transitions into abstention, transitions out of abstention, and path differences. Its direction is part of its definition: reversing candidate and reference exchanges correction with harm and exchanges the two abstention transitions. Some reciprocal rows therefore describe the same paired windows from opposite directions and must not be added as independent events. The main text uses calibration as candidate when reporting 28 corrections and 14 harms.

The path-difference column is not automatically a quote difference, and a fallback count does not necessarily imply abstention. A policy can hit a support boundary and still make its best supported prediction. To explain total-objective differences one must return to error, abstention, and quote counts rather than substitute a more convenient trace statistic. All pairs join the same window identifiers; 48 paired rows do not create 48 independent studies.

Table S31: S7. Participant 7: n=266, all 24 core policies.

Policy	Errors	Abstentions	Quote sum	J	Coverage	Fallback
empirical::adaptive	57	0	532	11/35	1	46
empirical::myopic	57	0	532	11/35	1	46
empirical::fixed empty	98	0	266	159/380	1	0
empirical::fixed 1	98	0	266	159/380	1	0
empirical::fixed 2	66	0	392	214/665	1	0
empirical::fixed 3	35	26	532	36/133	120/133	0
empirical::fixed 12	98	0	266	159/380	1	0
empirical::fixed 13	98	0	266	159/380	1	0

Policy	Errors	Abstentions	Quote sum	J	Coverage	Fallback
empirical::fixed 21	66	0	392	214/665	1	26
empirical::fixed 23	66	0	392	214/665	1	100
empirical::fixed 31	35	26	532	36/133	120/133	72
empirical::fixed 32	33	26	632	75/266	120/133	166
calibrated::adaptive	42	26	492	11/38	120/133	26
calibrated::myopic	42	26	492	11/38	120/133	26
calibrated::fixed empty	98	0	266	159/380	1	0
calibrated::fixed 1	98	0	266	159/380	1	0
calibrated::fixed 2	52	100	392	279/665	83/133	0
calibrated::fixed 3	44	26	392	37/133	120/133	0
calibrated::fixed 12	98	0	266	159/380	1	0
calibrated::fixed 13	98	0	266	159/380	1	0
calibrated::fixed 21	52	100	392	279/665	83/133	26
calibrated::fixed 23	52	100	392	279/665	83/133	100
calibrated::fixed 31	44	26	392	37/133	120/133	26
calibrated::fixed 32	42	26	492	11/38	120/133	26

Table S32: S8. Participant 8: n=258, all 24 core policies.

Policy	Errors	Abstentions	Quote sum	J	Coverage	Fallback
empirical::adaptive	49	0	516	187/645	1	56
empirical::myopic	49	0	516	187/645	1	56
empirical::fixed empty	102	0	258	383/860	1	0
empirical::fixed 1	102	0	258	383/860	1	0
empirical::fixed 2	47	0	437	459/1720	1	0
empirical::fixed 3	56	57	516	523/1290	67/86	0
empirical::fixed 12	102	0	258	383/860	1	0
empirical::fixed 13	102	0	258	383/860	1	0
empirical::fixed 21	47	0	437	459/1720	1	134
empirical::fixed 23	47	0	437	459/1720	1	45
empirical::fixed 31	56	57	516	523/1290	67/86	113
empirical::fixed 32	10	57	638	647/2580	67/86	136
calibrated::adaptive	8	57	559	235/1032	67/86	57
calibrated::myopic	8	57	559	235/1032	67/86	57
calibrated::fixed empty	102	0	258	383/860	1	0
calibrated::fixed 1	102	0	258	383/860	1	0
calibrated::fixed 2	29	45	437	459/1720	71/86	0
calibrated::fixed 3	54	57	437	1973/5160	67/86	0
calibrated::fixed 12	102	0	258	383/860	1	0
calibrated::fixed 13	102	0	258	383/860	1	0
calibrated::fixed 21	29	45	437	459/1720	71/86	134
calibrated::fixed 23	29	45	437	459/1720	71/86	45
calibrated::fixed 31	54	57	437	1973/5160	67/86	57
calibrated::fixed 32	8	57	559	235/1032	67/86	57

Table S33: S9. Stored directional paired counts; correction and harm are restricted to jointly predicted windows.

Candidate	Participant	Reference	Corrections	Harms	Both predict	To abstention	From abstention	Path differences
empirical::adaptive	7	fixed	10	1	266	0	0	140
empirical::adaptive	7	myopic	0	0	266	0	0	0
empirical::adaptive	7	other estimator adaptive	11	9	240	0	26	266
empirical::adaptive	7	other estimator same family	11	9	240	0	26	266
empirical::adaptive	8	fixed	2	4	258	0	0	79
empirical::adaptive	8	myopic	0	0	258	0	0	0
empirical::adaptive	8	other estimator adaptive	3	19	201	0	57	258
empirical::adaptive	8	other estimator same family	3	19	201	0	57	258
empirical::myopic	7	fixed	10	1	266	0	0	140
empirical::myopic	7	myopic	0	0	266	0	0	0

Candidate	Participant	Reference	Corrections	Harms	Both predict	To abstention	From abstention	Path differences
empirical::myopic	7	other estimator adaptive	11	9	240	0	26	266
empirical::myopic	7	other estimator same family	11	9	240	0	26	266
empirical::myopic	8	fixed	2	4	258	0	0	79
empirical::myopic	8	myopic	0	0	258	0	0	0
empirical::myopic	8	other estimator adaptive	3	19	201	0	57	258
empirical::myopic	8	other estimator same family	3	19	201	0	57	258
calibrated::adaptive	7	fixed	0	0	240	0	0	0
calibrated::adaptive	7	myopic	0	0	240	0	0	0
calibrated::adaptive	7	other estimator adaptive	9	11	240	26	0	266
calibrated::adaptive	7	other estimator same family	9	11	240	26	0	266
calibrated::adaptive	8	fixed	0	0	201	0	0	0
calibrated::adaptive	8	myopic	0	0	201	0	0	0
calibrated::adaptive	8	other estimator adaptive	19	3	201	57	0	258
calibrated::adaptive	8	other estimator same family	19	3	201	57	0	258
calibrated::myopic	7	fixed	0	0	240	0	0	0
calibrated::myopic	7	myopic	0	0	240	0	0	0
calibrated::myopic	7	other estimator adaptive	9	11	240	26	0	266
calibrated::myopic	7	other estimator same family	9	11	240	26	0	266
calibrated::myopic	8	fixed	0	0	201	0	0	0
calibrated::myopic	8	myopic	0	0	201	0	0	0
calibrated::myopic	8	other estimator adaptive	19	3	201	57	0	258
calibrated::myopic	8	other estimator same family	19	3	201	57	0	258
empirical::fixed 2	7	fixed	0	0	266	0	0	0
empirical::fixed 2	7	myopic	1	10	266	0	0	140
empirical::fixed 2	7	other estimator adaptive	1	8	240	0	26	126
empirical::fixed 2	7	other estimator same family	0	0	166	0	100	100
empirical::fixed 2	8	fixed	0	0	258	0	0	0
empirical::fixed 2	8	myopic	4	2	258	0	0	79
empirical::fixed 2	8	other estimator adaptive	1	15	201	0	57	179
empirical::fixed 2	8	other estimator same family	0	0	213	0	45	45
calibrated::fixed 32	7	fixed	0	0	240	0	0	0
calibrated::fixed 32	7	myopic	0	0	240	0	0	0
calibrated::fixed 32	7	other estimator adaptive	9	11	240	26	0	266
calibrated::fixed 32	7	other estimator same family	1	10	240	0	0	140
calibrated::fixed 32	8	fixed	0	0	201	0	0	0
calibrated::fixed 32	8	myopic	0	0	201	0	0	0
calibrated::fixed 32	8	other estimator adaptive	19	3	201	57	0	258
calibrated::fixed 32	8	other estimator same family	4	2	201	0	0	79

S6.12. Finite model / MHEALTH: Exact macro arithmetic and outcome decomposition

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Empirical adaptive J is the equal average of 11/35 and 187/645, giving 1364/4515. Calibrated adaptive J is the equal average of 11/38 and 235/1032, giving 10141/39216. Participant coverage is 240/266 and 201/258,

whose equal average is 19231/22876. Pooling yields 441/524 instead. Both are legitimate descriptive quantities with different weights; they are not interchangeable. The figure labels the pooled coverage explicitly and uses macro error contribution in a separate panel.

Relative to selected empirical fixed_2, empirical adaptive acquisition corrects 12 errors and harms 5 jointly predicted windows but adds 219 quotes. The aggregate quote difference is not simply multiplied by a pooled weight to recover the participant-macro objective; person-specific counts and denominators are needed. Relative to forced subset_2, empirical adaptive acquisition instead corrects 5 and harms 32. These results show both a cost trade-off against one control and a stronger predictive counterexample against another.

Calibration versus empirical adaptive acquisition has 441 jointly predicted windows. Within them, 28 corrections and 14 harms are prediction changes. Its 83 new abstentions comprise 42 formerly wrong and 41 formerly correct empirical predictions. Counting all 42 avoided errors as corrections would conceal the 41 lost correct predictions and the reduced prediction domain. Conditional accuracy would require its own stated denominator; Figure S5 deliberately shows unconditional error contribution and coverage separately.

The surrogate adaptive-minus-selected-order contrast is -49/44880. DEV gives 10667/1372560, and their exact difference is 9479/1069453. The arithmetic residual is zero. This identity is a diagnostic decomposition, not a causal decomposition whose second term has a uniquely identified source. Risk estimation, transition estimation, fitting-to-development shift, and a surrogate not derived from one joint law can all matter. A more informative experiment would change one such factor while fixing predictor, kernel, selection, support, and evaluation groups.

$$\frac{\left(\frac{11}{35}\right)+\left(\frac{187}{645}\right)}{2}=\frac{1364}{4515}$$

Equal-participant empirical adaptive objective.

$$\frac{\left(\frac{11}{38}\right)+\left(\frac{235}{1032}\right)}{2}=\frac{10141}{39216}$$

Equal-participant calibrated adaptive objective.

$$\frac{\frac{240}{266}+\frac{201}{258}}{2}=\frac{19231}{22876},\quad \frac{441}{524}\neq\frac{19231}{22876}$$

Macro and pooled coverage have different weights and are not equal.

S6.13. Finite model / MHEALTH: Surrogate Bellman optimality and the earlier coherent variant

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For a finite surrogate, depth decreases on every acquisition and terminal choices are always available. At depth zero, the value is the smaller of estimated prediction risk and abstention loss. Inductively, the recurrence compares those terminals with every supported paid acquisition followed by an optimal shorter continuation. This proves finite-horizon optimality for the declared risk and transition functions. A fixed-order suffix restricts the action menu, and a forced-subset policy uses its separately specified continuation constraint.

A one-step myopic policy replans at every visited state. Its first one-step value excludes later queries bought after replanning, so it must not be equated with the total value of its eventual executed tree. Adaptive and myopic paths happened to coincide in the frozen cached evaluation. This observation does not prove that non-myopic acquisition never helps, just as different names do not prove different behavior. All realized path ties and their objective ties remain no_gain.

An earlier coherent estimator first formed participant-balanced complete-row laws P_T and P_C, then mixed them before conditioning. Its terminal risk, kernel, and initial mass were derived from that one law. Conditioning changes local mixture weights according to state masses, so they need not remain the global 1/4 and 3/4. The partition identity can make direct tree loss equal its Bellman value internally. This is an algebraic consistency property, not a guarantee that its law describes DEV.

That earlier variant tied its own fixed and myopic policies at J=157023/457520 for total budgets two and three and regressed against relevant empirical or statewise controls. It is not the present calibrated estimator. The coherent change altered participant weighting, risk, kernel, and initial mass together, so its result does not identify coherence alone as a cause. The lineage preserves the negative result rather than presenting successive estimator names as a monotone improvement.

$$V_d(h) = \min\left(r(h), \eta, \min_{a \in A(h,d)}\left[\lambda c_a + \sum_z p(z|h,a) V_{d-1}(haz)\right]\right)$$

Finite surrogate Bellman recurrence; it proves internal planning optimality, not generalization.

$$P_J = \frac{64P_T + 192P_C}{256}, \quad P_D = \frac{P_{D,5} + P_{D,6}}{2}$$

Earlier coherent complete-row mixture, distinct from current statewise calibration.

S6.14. Finite model / MHEALTH: Question and data scope

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The causal question is narrowly controlled: with the same cached predictor, candidate actions, support, stopping loss and logical request budget, does matching empirical training selection to participant-macro weighting change the selected behavior and development performance? Changing the weighting in this deterministic finite experiment isolates its computational effect on this cache. It does not identify population causation, model-quality changes or the cause of prior DEV regression.

The original W49 training/cache bytes have SHA256 63cf79ae01c7567d630cf9cd1684cd145e56676add90aab8ff863c485f3ae18a and the DEV bytes 5625b00000c8bb88a4b751b020968b0a69076656e91d4dc8aa296fb4b3ebed6c. T uses index blocks satisfying ((index//8)%5)<3: participant 5 contributes 168 and participant 6 contributes 154 windows. The remaining 96+96 C windows are parsed only to validate the pinned partition; no C risk, calibration or policy selection is used. DEV contains 266+258 unique windows from participants 7/8. The previous W48 predictor fit/export is historical metadata, not re-fit or re-certified here.

The author wrote separately written code and did not import or execute any historical sealed main/oracle, train a predictor, request a model, download data, inspect a hidden final group or access UCI470 H. This standalone native support neither claims a campaign worker nor takes over a research owner. Source, contract and data bindings were sealed before the first scientific T/C read; actual selection bytes were then saved and hashed before the first scientific DEV read.

S6.15. Finite model / MHEALTH: Two joint laws and the target distinction

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Let i index the 322 T windows, g(i) its participant and r(i) its initially observed token. The target law P_i=1/(2*n_g(i)) assigns each participant total mass 1/2. A state s denotes a subset of acquired tokens; P(s) is the sum of these global row weights over matching rows. STOP risk is weighted error mass/P(s); transitions are P(child)/P(s). After observing s, participant masses generally cease to be1/2. Re-equalizing groups at every state would change the joint law and is explicitly forbidden.

For the old law set q_t=sum(P_i:r(i)=t), n_t=count(r(i)=t), and Q_i=q_r(i)/n_r(i). Every legal state contains its initial token, so the Q multiplier is constant over that state. Its conditional risks and transitions therefore equal the pooled-count estimates, while Q has the same participant-macro root distribution q. The old rule is a valid coherent surrogate. Its mismatch is with participant-macro target P, not a probability contradiction or a DP implementation bug.

The actual root0 contains96 rows from participant 5 and 73 from6. Under P its participant 5 posterior is88/161; after observing token 3=1 it becomes143/201. Neither equals1/2. At root0 STOP risk changes from old Q 46/169 to P 533/1932. These numerical changes are real even though they do not cross an action-selection boundary in this experiment.

Algorithm S13. Globally weighted empirical acquisition with an explicitly matched target

Require: Frozen seven-mask predictor cache; T participants5/6, 168 and154 windows; allowed masks1,3,5,9,7,11,13. Two additional requests, initial quote1, loss(error)=1, loss(abstain)=2/5, each quote1/20. Observed state contains acquired token positions/values only. Common raw-T count>=30 and both participants at the state and every positive child.

Ensure: Exact state/transition/terminal probabilities under P_macro and old root-reweighted Q. 44 frozen policies, two T-only references per law, exact T checks and once-read development outcomes.

---

[1] Assign every T row i the global weight P_i=1/(2*n_subject(i)); never rebalance participants after conditioning.

[2] Set q_t=sum(P_i: initial token=t) and Q_i=q_t/n_t. For either joint law normalize its fixed weights on the rows matching each observed state.

3 Compute cached-predictor STOP risk and positive-child transition masses from the same normalized weights. Keep raw-count support and acquisition rights identical between laws.
4 At each terminal choose STOP on risk<=2/5 and abstain otherwise. Solve the depth-two finite legal tree; purchase only on strict improvement, using ascending action ties.
5 Also construct myopic depth-one replanning, all10 fixed orders with contingent early STOP, and all10 committed orders with forced supported purchases. Seven canonical subsets are aliases of committed orders.
6 Score every behavior table under both P and Q. Choose fixed and committed references by exact own-law T loss then policy ID. Save selection bytes and their hash before any scientific DEV read.
7 Read exposed DEV7/8 once, roll each frozen policy without future-token/label/group access in its decision function, and retain every path and outcome.
8 In separate code enumerate finite legal programs, directly score their integer-twentieth losses on raw T rows, independently roll all T/DEV paths, and verify exact identities, paired summaries, reference choices and TV bounds.

S6.16. Finite model / MHEALTH: Finite policy classes and exact guarantees

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

There are exactly seven permitted masks 1,3,5,9,7,11,13 and 38 binary-token states. Mask 15 is outside the domain, including metadata and recursion. Initial context costs one quote; at most two additional acquisitions cost1/20 each. An erroneous prediction costs1 and abstention2/5. Raw T support requires at least 30 matching windows and both participants, at the current state and every positive-probability child. Support only removes acquisitions; it never removes the shared STOP/abstain terminal choice.

For each law we enumerate adaptive depth-two DP, depth-one myopic replanning, ten full-rights fixed orders, and ten ordered committed controls: empty, three singletons and six directed pairs. Fixed orders allow observation-dependent early stopping. Committed orders relinquish that early-stopping right while the next purchase is supported, but use the common terminal rule after completion or support block. The seven unordered canonical subsets are aliases of seven of those ten committed orders. Reverse pairs remain separate because support can depend on order.

For any fixed legal behavior table, row sets at a positive child partition its parent. Conditioning one fixed joint law therefore makes each Bellman expectation equal its directly weighted rollout by finite backward induction. Including initial quote 1/20, this proves both J_P=participant-macro T rollout and J_Q=Q-weighted T rollout. The adaptive legal class can imitate every fixed/committed path because each uses the same predictor, observations, support, budget and terminal actions; choosing to continue is available to the class even when an optimizer would prefer STOP. The DP optimum is consequently no larger than every control under its own training law. These are finite empirical optimization statements, not DEV guarantees.

For δ=TV(P,Q), any legal policy has total loss in[1/20,23/20], giving |J_P-J_Q|<=(11/10)*δ. For exact minimizers over the same adaptive class, J_P(pi_Q)-J_P(pi_P)<=(11/5)*δ. Here δ=1361/63206, the same-class realized T regret is 0, and every one of 44 objective differences obeys 1361/57460. These bounds compare training distributions; they do not bound a DEV advantage or attribute the DEV regression to weighting.

S6.17. Finite model / MHEALTH: Development results and negative outcome

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Under both laws T-only exact selection picks fixed_2 and committed_2 as the corresponding references. New macro adaptive T J=1361/6160 equals its exact P rollout. Its unchanged old Q score 2648/12155 differs by Q-P=-841/272272. The previous reported score is retained rather than retroactively replaced. All 22 corresponding action tables match across all 38 legal states, and adaptive=myopic on the whole domain. Matching the target changes scores but no selected behavior here.

Adaptive and myopic DEV J=1364/4515 (about 0.302104), with full prediction coverage and mean quotes2. Selected fixed_2 has J134663/457520 (about 0.294332); adaptive minus fixed is10667/1372560. Selected committed_2 has J28743/114380 (about 0.251294); adaptive minus committed is3487/68628. Thus objective alignment produces no DEV gain and preserves both regressions. The hindsight-best full-rights fixed order is32, J182801/686280; this is descriptive only and was not used for selection.

The order correction matters even with no estimator effect. Committed23 reaches the requested pair on 26/266 and 134/258 windows; committed_32 reaches it on 100/266 and 122/258. Their exact macro attainment rates are5294/17157 and 14563/34314, respectively, and their DEV J values differ. At root0/token 2=0, querying

3 is blocked because a positive child has 29 T rows; beginning with 3=1 permits querying 2. These are the same support rights, not a budget increase.

Table S34: Selected and order-sensitive policies under the participant-macro law. All corresponding old-law behaviors are identical.

Policy	Macro T J	Macro DEV J	DEV coverage	Mean quotes	Requested-mask attainment
adaptive	1361/6160	1364/4515	1	2	None
myopic	1361/6160	1364/4515	1	2	None
fixed 2	687/3080	134663/457520	1	15527/9804	5723/9804
committed 2	1401/6160	28743/114380	1	2	1
committed 23	2983/12320	1213/4515	1	39608/17157	5294/17157
committed 32	8753/36960	182801/686280	19231/22876	83191/34314	14563/34314

S6.18. Finite model / MHEALTH: Paired outcomes and interpretation

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Against fixed_2, adaptive corrects 10 errors and harms 1 correct prediction for participant 7, and corrects 2 and harms 4 for participant 8. All 524 windows are predicted by both. Adaptive uses 532/516 quotes versus fixed 392/437. Its better error count does not offset additional logical acquisition cost under the predefined macro loss. Complete action sequence agreement is 126/266 and 179/258.

Against committed_2, adaptive has 0 corrections/26 harms for participant 7 and 5 corrections/6 harms for8. Quotes are identical at 532/516 and neither policy abstains. The selected committed subset is attained on all 524 windows; adaptive ends at masks 5 or 9 and therefore represents a different sensor choice. Corresponding old-versus-new policies have zero corrections, harms or abstention transitions and full action agreement. All per-participant errors, abstentions, quotes, coverage, conditional error and terminal masks for every arm are retained in RESULT.json.

The correction repairs target bookkeeping and expands committed controls from seven canonical aliases to all ten orders. It does not empirically improve this predictor/cache. A larger feasible adaptive class can have a lower training objective yet lose on DEV. This experiment does not distinguish distribution shift, predictor errors or finite-sample model selection as the cause, and cannot establish statistical significance from dependent windows belonging to only two development participants.

S6.19. Finite model / MHEALTH: Verification and limits

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

One scientific main completed 14168 T and 23056 DEV policy paths, totaling 37224 repeated-policy paths from 322 T plus 524 DEV unique windows. Per-policy/per-participant planned, started and completed counts agree; failed, exhausted, unknown and unstarted are all 0. There were no main/oracle retries or post-seal code changes. The separately written same-author oracle passed 377968 checks, including 88 exact P/Q rollout identities, 1672 independent finite-program minima, 80 adaptive/control root inequalities and 880 paired-summary comparisons. Synthetic validation passed 67 checks; one earlier synthetic expectation failure was recorded and corrected before source sealing.

The main Python measured interval was CPU 1.000000s/wall 1.139314s, and oracle interval CPU 1.187500s/wall 1.192983s, including the final result/report writes and ending just before exit output. Explicit content reads totaled 9255243 bytes and artifact writes 821134 bytes. A conservative addition of all 7604125 uncompressed archive-member bytes gives 8425259 write bytes. Budgets 120 CPU seconds, 300 wall seconds, 64MiB read and 16MiB write were not exhausted in their declared scientific interval. Main full process CPU is unknown because its launcher was python.cmd; its observed wrapper CPU is not Python CPU. Oracle direct-python full CPU/wall are 1.296875s/1.332978s. Imports, authoring/native usage, exit tails, physical OS I/O and peak memory are not fully measured.

Guards are cooperative Python checks and do not create OS isolation or a hard scheduler deadline. Quote cost is logical, not measured hardware latency, energy or sensor reliability. The cache contains no provider failures; observed failure 0 does not establish reliability. No confidence interval, calibration guarantee, new external baseline score, novelty certification, skill activation, submission, deployment or campaign registration is claimed. A distinct native reviewer subsequently completed 75,750 numeric and 311 semantic checks on this frozen study. A new unexposed benchmark is still required; scientific status remains needs_evidence.

S6.20. Finite model / MHEALTH: Exact empirical law and conditioning proof

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For a finite set of T rows with nonzero group counts, sum_i P_i=1. For any state s with positive mass, define I_s as its matching row indices, R_P(s)=sum_i-in-I_s P_i*error_i(mask(s))/sum_i-in-I_s P_i, and T_P(t|s,a)=P(I_child)/P(I_s). STOP contributes R_P(s), abstention2/5, and acquisition1/20 plus the child expectation. At maximum acquisition depth the identity with row losses is immediate. Replacing child values by their weighted row losses and partitioning I_s proves the parent identity. The fixed initial quote adds1/20 to both sides. The same induction applies to Q. Zero-mass states have a declared fallback risk 1/2, no acquisition support, and no contribution to an on-distribution expectation.

The P/Q distinction is exactly the participant weighting target. Q_i=q_r/n_r is positive for every observed row and normalized because sum_r q_r=1. Since every history includes r, its constant factor cancels in any conditional state, yielding pooled terminal error and pooled next-token frequency. Re-equalizing groups at each conditional state would instead replace the Bayesian posterior by an artificial 1/2 mixture and would generally destroy the P rollout identity.

In the source tables root0 P participant posterior is(88/161,73/161); state(0,-1,-1,1) has(143/201,58/201); state(0,-1,0,1) has(55/94,39/94). These values are training/scoring metadata. A participant identifier is not present in an observed policy key.

S6.21. Finite model / MHEALTH: Total-variation derivation and scope

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For bounded policy loss L in[a,b], subtract a constant and use the positive/negative parts of P-Q to obtain |E_P L-E_Q L|<=(b-a)*TV(P,Q). Here a=1/20 and b=23/20, so b-a=11/10. If pi_P and pi_Q are exact minimizers over the same legal adaptive class, insert and subtract their Q expectations; the Q-optimality middle term is nonpositive and the two remaining terms each contribute at most(11/10)*δ. This gives regret at most(11/5)*δ. The claim is restricted to exact minimizers and common policy rights, not arbitrary family references or DEV.

With n5=168>n6=154, δ=(1/(2*154)-1/(2*168))*sum_r[n5r*n6r/(n5r+n6r)]=1361/63206<=7/322. Every44 policy score difference obeys 1361/57460. The largest observed absolute difference is47525/10618608 at committed_empty (and its aliases); adaptive Q-P=-841/272272. Both adaptive minimizers implement the same behavior, making the actual same-class P training regret 0 despite the nonzero upper bound 1361/28730. None of these quantities is a development generalization bound.

S6.22. Finite model / MHEALTH: All policies, selection, and stopping rights

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The table retains all 44 arms, including duplicates, ties and regressions. T estimate is each arm's own declared law objective; macro T always uses P. E7/E8, A7/A8 and Q7/Q8 are raw DEV error, abstention and quote counts. Requested-mask attainment is null for adaptive/myopic and is descriptive for early-stopping fixed orders. It is a required-subset completion measure for committed orders. Exact per-participant fractions and paired details are in RESULT.json; raw paths are in RAW.zip.

The complete order menu is empty,1,2,3,12,13,21,23,31,32. Seven canonical subset aliases omit21,31,32 as separate aliases but those policies remain in the ten-order scientific menu. Myopic means a depth-one lookahead recomputed after each observation; it can acquire twice. Full-rights fixed means fixed acquisition order with observation-contingent terminal choice; it does not imply every scheduled sensor is always acquired. Committed controls explicitly remove optional early stopping while supported, with no other information/ cost advantage.

Table S35: All frozen laws and policies; no arm omitted.

Law and policy	Own-law T estimate	Macro T J	Macro DEV J	E7/E8	A7/A8	Q7/Q8	Macro coverage	Mask attainment
old rootmacro pooled::adaptive	2648/12155	1361/6160	1364/4515	57/49	0/0	532/516	1	None
old rootmacro pooled::myopic	2648/12155	1361/6160	1364/4515	57/49	0/0	532/516	1	None
old rootmacro pooled::fixed empty	482899/ 1896180	4789/18480	7057/16340	98/102	0/0	266/258	1	1
old rootmacro pooled::fixed 1	482899/ 1896180	4789/18480	7057/16340	98/102	0/0	266/258	1	0

Law and policy	Own-law T estimate	Macro T J	Macro DEV J	E7/E8	A7/A8	Q7/Q8	Macro coverage	Mask attainment
old rootmacro pooled::fixed 2	127741/583440	687/3080	134663/457520	66/47	0/0	392/437	1	5723/9804
old rootmacro pooled::fixed 3	15881/63206	39/154	115999/343140	35/56	26/57	532/516	19231/22876	1
old rootmacro pooled::fixed 12	482899/1896180	4789/18480	7057/16340	98/102	0/0	266/258	1	0
old rootmacro pooled::fixed 13	482899/1896180	4789/18480	7057/16340	98/102	0/0	266/258	1	0
old rootmacro pooled::fixed 21	127741/583440	687/3080	134663/457520	66/47	0/0	392/437	1	0
old rootmacro pooled::fixed 23	127741/583440	687/3080	134663/457520	66/47	0/0	392/437	1	0
old rootmacro pooled::fixed 31	15881/63206	39/154	115999/343140	35/56	26/57	532/516	19231/22876	0
old rootmacro pooled::fixed 32	591057/2528240	8753/36960	182801/686280	33/10	26/57	632/638	19231/22876	14563/34314
old rootmacro pooled::committed empty	482899/1896180	4789/18480	7057/16340	98/102	0/0	266/258	1	1
old rootmacro pooled::committed 1	143254/474045	471/1540	156491/343140	82/59	34/80	532/516	26801/34314	1
old rootmacro pooled::committed 2	16343/72930	1401/6160	28743/114380	31/48	0/0	532/516	1	1
old rootmacro pooled::committed 3	15881/63206	39/154	115999/343140	35/56	26/57	532/516	19231/22876	1
old rootmacro pooled::committed 12	30013/94809	143/448	112319/343140	48/10	34/80	696/668	26801/34314	10343/17157
old rootmacro pooled::committed 13	2400823/7584720	23543/73920	175531/457520	31/39	59/101	692/641	11896/17157	37265/68628
old rootmacro pooled::committed 21	47969/189618	271/1056	189589/686280	31/48	0/0	678/632	1	17131/34314
old rootmacro pooled::committed 23	904967/3792360	2983/12320	1213/4515	31/49	0/0	558/650	1	5294/17157
old rootmacro pooled::committed 31	537037/1896180	501/1760	26753/72240	35/56	26/57	726/661	19231/22876	44311/68628
old rootmacro pooled::committed 32	591057/2528240	8753/36960	182801/686280	33/10	26/57	632/638	19231/22876	14563/34314
coherent macro::adaptive	1361/6160	1361/6160	1364/4515	57/49	0/0	532/516	1	None
coherent macro::myopic	1361/6160	1361/6160	1364/4515	57/49	0/0	532/516	1	None
coherent macro::fixed empty	4789/18480	4789/18480	7057/16340	98/102	0/0	266/258	1	1
coherent macro::fixed 1	4789/18480	4789/18480	7057/16340	98/102	0/0	266/258	1	0
coherent macro::fixed 2	687/3080	687/3080	134663/457520	66/47	0/0	392/437	1	5723/9804
coherent macro::fixed 3	39/154	39/154	115999/343140	35/56	26/57	532/516	19231/22876	1
coherent macro::fixed 12	4789/18480	4789/18480	7057/16340	98/102	0/0	266/258	1	0
coherent macro::fixed 13	4789/18480	4789/18480	7057/16340	98/102	0/0	266/258	1	0
coherent macro::fixed 21	687/3080	687/3080	134663/457520	66/47	0/0	392/437	1	0
coherent macro::fixed 23	687/3080	687/3080	134663/457520	66/47	0/0	392/437	1	0
coherent macro::fixed 31	39/154	39/154	115999/343140	35/56	26/57	532/516	19231/22876	0
coherent macro::fixed 32	8753/36960	8753/36960	182801/686280	33/10	26/57	632/638	19231/22876	14563/34314
coherent macro::committed empty	4789/18480	4789/18480	7057/16340	98/102	0/0	266/258	1	1
coherent macro::committed 1	471/1540	471/1540	156491/343140	82/59	34/80	532/516	26801/34314	1
coherent macro::committed 2	1401/6160	1401/6160	28743/114380	31/48	0/0	532/516	1	1
coherent macro::committed 3	39/154	39/154	115999/343140	35/56	26/57	532/516	19231/22876	1
coherent macro::committed 12	143/448	143/448	112319/343140	48/10	34/80	696/668	26801/34314	10343/17157
coherent macro::committed 13	23543/73920	23543/73920	175531/457520	31/39	59/101	692/641	11896/17157	37265/68628
coherent macro::committed 21	271/1056	271/1056	189589/686280	31/48	0/0	678/632	1	17131/34314

Law and policy	Own-law T estimate	Macro T J	Macro DEV J	E7/E8	A7/A8	Q7/Q8	Macro coverage	Mask attainment
coherent macro::committed 23	2983/12320	2983/12320	1213/4515	31/49	0/0	558/650	1	5294/17157
coherent macro::committed 31	501/1760	501/1760	26753/72240	35/56	26/57	726/661	19231/22876	44311/68628
coherent macro::committed 32	8753/36960	8753/36960	182801/ 686280	33/10	26/57	632/638	19231/22876	14563/34314

S6.23. Finite model / MHEALTH: Per-participant results and paired components

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The following selected/order-sensitive policies show all loss components for each participant. Full per-participant records for all 44 policies are preserved in RESULT.json. Conditional error uses only predicted windows and is null for an empty prediction denominator. Error rate instead divides by all windows. Macro ratios average participant ratios rather than pooling their numerators and denominators.

For adaptive versus fixed_2, participant 7 J difference is-1/133 and participant 8 difference119/5160; their mean is10667/1372560. There are12 corrections and 5 harms among524 both-predict windows, but219 extra total quotes. Against committed_2 the corresponding J differences are13/133 and 1/258, with 5 corrections and 32 harms. All abstention transitions in these selected contrasts are0. Other arms do abstain: committed_32 has26+57 abstentions, which are retained rather than merged into accuracy.

Table S36: Participants7 and8, exposed DEV. Quote totals include the initial quote.

Policy	Person	Windows	Errors	Abstain	Quotes	J	Coverage	Conditional error	Mask attained
adaptive	7	266	57	0	532	11/35	1	3/14	None
adaptive	8	258	49	0	516	187/645	1	49/258	None
fixed 2	7	266	66	0	392	214/665	1	33/133	126
fixed 2	8	258	47	0	437	459/1720	1	47/258	179
committed 2	7	266	31	0	532	144/665	1	31/266	266
committed 2	8	258	48	0	516	123/430	1	8/43	258
committed 23	7	266	31	0	558	31/140	1	31/266	26
committed 23	8	258	49	0	650	163/516	1	49/258	134
committed 32	7	266	33	26	632	75/266	120/133	11/80	100
committed 32	8	258	10	57	638	647/2580	67/86	10/201	122

S6.24. Finite model / MHEALTH: Question, scope and exposure

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The completed upstream task_f12947a77db1 reported that a coherent group-law change altered numerical targets but none of22 corresponding action tables. Its unchanged coherent_macro22 objects are our only candidates. We ask whether C selection chooses useful behavior and whether paired arbitration adds value over equally informed C mean selection and a strong C static minimax reference. No predictor, action table, risk/support rule, terminal function or hyperparameter is learned from C or changed.

F20 consists of10 fixed acquisition orders with precompiled contingent STOP/abstain decisions and 10 committed-prefix orders. A22 adds adaptive and myopic tables. F20 is not every possible history-specific static terminal/STOP function, and A22 is not all admissible adaptive programs. Optimality below is restricted to these frozen menus and ex ante mixtures. This C-menu study did not optimize the full grammar; the separate empirical full-grammar study is described in source-local Section 13.

C has96 windows each from participants 5/6 satisfying ((index//8)%5)>=3. Those blocks were held out only within the original T construction and were previously used in wider research. DEV contains266+258 exposed, dependent windows from7/8. All MHEALTH 1-10 were previously used; independent final-test participants=0. The combined TRAIN_C file also contains T 168+154 rows: these bytes were read, but T rows only validate the partition, never fit/rescore/replay a policy. Historical predictor fit/export metadata is not freshly certified.

S6.25. Finite model / MHEALTH: Frozen policy contract and algorithm

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The predictor and masks1,3,5,9,7,11,13 remain fixed; mask15 is forbidden. The action interface accepts only acquired token positions/values, excluding participant, index, label and unacquired tokens. Group ID serves scoring and selector weights only. Loss is I(error)+(2/5)I(abstain)+quotes/20, counting the initial quote and at most two additional requests. Existing raw-T count>=30 plus both participants at state and each positive child, terminal/fallback and request rules are inherited unchanged.

Every C procedure sees the same C losses, frozen menu access, predictor and logical acquisition/terminal budget. The F/A restriction is the declared class difference. Committed tables deliberately relinquish early stopping while supported as in the upstream menu. C mean-F/A and C minimax-A are equally informed selector controls. Historical T adaptive/fixed/committed choices are information ablations, not fair novelty comparators for a C-informed method.

Algorithm S14. Frozen-menu C selection with direct same-law paired arbitration
Require: T-precompiled F20 static tables plus2 T-derived dynamics, A22; fixed predictor/support/terminal rules. Exposed C5/6:96+96 windows; seven masks1,3,5,9,7,11,13. Initial quote1 plus two requests; error1, abstain2/5, each quote1/20; presealed ties/controls/bounds.
Ensure: Exact22x2 C loss matrix, static-menu minimax reference and endpoint vector b. Direct A-minus-b LP with all-original-row primal/dual certificates, Gamma and gated mixture. Predeclared C controls and one DEV exact-expectation comparison of all22 tables and selectors.

1 Seal unchanged T menu, code, contract and bounds before C raw bytes.
2 Compute C loss separately for participants5 and6. Policy action lookup receives only acquired token state.
3 Enumerate pure F rows and every two-row diagonal crossing; minimize worst endpoint, then endpoint5, endpoint6, sparse index tuple and exact weights. Save b.
4 Directly solve min_p max_g sum_i p_i*(L_ig-b_g) over A. Verify simplex/group bounds, all-row dual inequalities and strong duality. Gamma=-value.
5 Use direct mixture only if Gamma>0, otherwise retain the F reference. Independently fix pure C mean-F/A, mixture C minimax-A, pure-F diagnostic and historical T ablations.
6 Write and hash actual C_FROZEN matrix/reference/certificates/selectors before permitting the first DEV raw read.
7 Evaluate every frozen pure table once on DEV; combine preserved outcomes in exact expectation. Different selectors use independent ex ante coins independent of the episode; self comparison shares the draw. No realized random episodes.
8 Preserve failure/unknown/unstarted denominators, derived traces and costs. Run separate-code oracle once; never refit or revise using DEV.

S6.26. Finite model / MHEALTH: Reference, direct contrast and empirical certificate

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For C rows L_i=(L_i5,L_i6), minimize max_g sum_i p_i L_ig over simplex(F). Ties minimize endpoint5, endpoint6, lexicographic nonzero index tuple and its rational weight tuple among sparse primal candidates. Freeze its vector b. Direct arbitration solves v=min_{p in simplex(A)} max_g sum_i p_i(L_ig-b_g), Γ=-v. This uses the same empirical group law and is not the difference of separately minimized robust values.

The dual maximizes z with λ in[0,1] and λ*D_i5+(1-λ)*D_i6>=z for every original row D_i=L_i-b. Certificates retain every row coefficient, primal weight, dual value/slack and group slack, including aliases. Because F is included in A, reference feasibility implies v<=0. If Γ>0, all q in[0,1] satisfy q*(J_C5-b5)+(1-q)*(J_C6-b6)<=-Γ. If Γ<=0, the declared fallback retains the reference.

This certificate concerns only the convex hull of these two empirical C participant laws. It supplies no finite-sample, population, new-participant or DEV safety guarantee. No SPIBB/RBR or LP novelty claim is made. Exact arithmetic and a separate-code oracle verify calculations, not scientific independence.

S6.27. Finite model / MHEALTH: Results: selection criteria and incremental arbitration

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The complete F20 mixture minimax solution is pure fixed_2 at index2, b=(247/960,313/960), worst endpoint313/960. C minimax-A and the pure-F diagnostic tie it. The direct LP has v=0, Γ=0 and contrast(0,0), so arbitration retains the reference. Both reference and direct dual λ=0 support the certificates:

fixed_2 attains the smallest participant 6 C loss in A, preventing a strict improvement of both endpoint contrasts. The mixture search is complete and synthetically tested even though its actual optimum is pure.

C mean-F and C mean-A choose fixed_empty/index0. Its C endpoints(13/160,97/240) yield mean233/960, below the minimax reference mean7/24, but a worse maximum. DEV favors the reference over mean controls by 62933/457520. That descriptive contrast compares C selection criteria; arbitration itself contributes no increment. C minimax also retains the same behavior as historical T_fixed.

Reference DEV participant 7 J=214/665 and participant 8 J=459/1720. Against T_adaptive it regresses on7 by 1/133 and improves8 by 119/5160; macro improvement is10667/1372560. Against T_committed it regresses on7 by 2/19 and improves8 by 33/1720, leaving macro regression2813/65360. All ties/regressions remain in RESULT; favorable comparator selection is not general superiority.

Table S37: All predeclared selectors. Participant-macro exact expectations; all actual optimal mixtures are pure.

Selector	Components	C J	DEV J	DEV error	DEV abstain	DEV quotes	DEV coverage
reference minmax F	1*fixed 2	7/24	134663/457520	14765/68628	0	15527/9804	1
paired arbitration A	1*fixed 2	7/24	134663/457520	14765/68628	0	15527/9804	1
C minmean F	1*fixed empty	233/960	7057/16340	312/817	0	1	1
C minmean A	1*fixed empty	233/960	7057/16340	312/817	0	1	1
C minmax A	1*fixed 2	7/24	134663/457520	14765/68628	0	15527/9804	1
best pure F diagnostic	1*fixed 2	7/24	134663/457520	14765/68628	0	15527/9804	1
T adaptive	1*adaptive	37/120	1364/4515	365/1806	0	2	1
T fixed	1*fixed 2	7/24	134663/457520	14765/68628	0	15527/9804	1
T committed	1*committed 2	331/960	28743/114380	3461/22876	0	2	1

S6.28. Finite model / MHEALTH: Paired behavior, verification and cost

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Against C mean-A/F, reference/arbitration has expected corrections/harms39/7 on participant 7 and 72/17 on8, with complete action agreement140/266 and 79/258. Those arms abstain zero times. Arbitration and the minimax reference agree on all 524 complete DEV traces and have zero corrections, harms or loss difference. Fractional mixture counts would remain expectations, never realized stochastic events.

The192 C and 524 DEV unique windows generate 4,224 C and 11,528 DEV policy paths, not 15,752 independent observations. All 88 policy/split/participant denominators complete; failed, budget_exhausted, unknown and unstarted are each0. Before seal, 23 main synthetic checks and 5 separate-oracle checks passed. One main and one separate-code oracle exited0; the oracle verified 161,712 assertions on derived artifacts without raw benchmark rereads. Assertions are bookkeeping checks, not samples.

Actual launched Python processes used 1.171875 CPU seconds and 1.3613009 summed launch-to-wait wall seconds. Cooperative actor reads=5837779 bytes, writes=876581 bytes, conservative summed paths29. Bounds were 120 CPU/300 wall seconds,64MiB reads/16MiB writes/4096 paths. Imports/exit cost decomposition, source/report authoring, native tokens/cost, OS physical IO, peak RAM and whole-host use remain unknown or outside this accounting.

S6.29. Finite model / MHEALTH: Decision and limitations

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Scientific status remains needs_evidence; incremental arbitration outcome is no_gain. Implementation artifacts and local calculations were produced, without promotion of a policy/global skill or any campaign state change. Logical quote savings are not measured physical sensor energy/latency, and this is not a model/native-agent benchmark.

Finite menus inherit a fitted predictor and T terminal functions. Richer terminal/policy fitting, other costs and unexposed evaluation remain outside scope. Previously exposed C/DEV can bias wider research choices even with this Task sealed before raw reads. The same native author wrote the separate oracle; a distinct native review is completed, while unexposed participant evaluation remains missing. The oracle checks derived cache-prediction consistency rather than independently rereading original values. No confidence interval or population guarantee is supplied.

S6.30. Finite model / MHEALTH: Why the two-column optimization is complete

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Policy mixtures map into the convex hull of two-column loss rows. On a row-pair segment, max(x,y) is piecewise linear; a minimum is at an endpoint or the x=y crossing unless flat, when lexicographic endpoint minimization suffices. An optimal point lies on a lower supporting boundary with nonnegative normal and can be represented on an edge by at most two original rows. Enumerating all rows and all interior pairwise diagonal crossings is therefore complete for this menu-mixture objective, not the entire policy grammar.

The dual lower envelope min_i[λ*D_i5+(1-λ)*D_i6] is concave piecewise linear on [0,1]. Its maximum is at 0, 1 or a row-line intersection. Enumerating every pairwise intersection is a finite superset of relevant breakpoints. Fraction arithmetic verifies simplex and group inequalities, all included-row dual slacks, exact strong duality and complementary slackness. Reference, direct contrast and A minimax certificates store all 22 rows; the reference marks 20 included rows and two excluded dynamics.

The shortcut regression fixture uses F={(0,2)}, A=F union {(1,0)}, b=(0,2). Separately minimized worst losses differ by 2/3-2=-4/3, but the direct same-law contrast rows are (0,0),(1,-2), whose minimax value is 0. Subtraction would suggest a uniform improvement that is infeasible. This is a synthetic unit counterexample, kept separate from benchmark performance.

Different selector arms use independent ex ante policy draws with mass p_i*q_j, independent of episode data. A self comparison shares the draw. Paired expected corrections/harms weight deterministic both-predict counts; abstention transitions are separate. No realized stochastic episodes are generated. Conditional error is explicitly the ratio of expected errors to expected predictions; empty denominators are null.

S6.31. Finite model / MHEALTH: All policies and aliases

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

There are 22 declared rows, 16 distinct full 38-state action tables and 12 distinct action traces over the 16 possible complete binary token vectors. Duplicates remain rows for auditable ties and are not extra independent evidence. Seven canonical committed subset labels alias existing ascending orders. Reverse orders remain explicit. No worse or duplicate policy was removed.

The table preserves every C endpoint and DEV outcome; RESULT adds full participant/macro errors, abstentions, quotes, coverage, terminal-mask/subset attainment and paired agreement for every policy and all nine selector labels. Mean quotes include the initial quote.

Table S38: Entire frozen menu. DEV uses equal participant macro averaging.

Index	Policy	C5 J	C6 J	DEV J	DEV error	DEV abstain	DEV quotes	DEV coverage
0	fixed empty	13/160	97/240	7057/16340	312/817	0	1	1
1	fixed 1	13/160	97/240	7057/16340	312/817	0	1	1
2	fixed 2	247/960	313/960	134663/457520	14765/68628	0	15527/9804	1
3	fixed 3	113/480	11/30	115999/343140	1709/9804	3645/22876	2	19231/22876
4	fixed 12	13/160	97/240	7057/16340	312/817	0	1	1
5	fixed 13	13/160	97/240	7057/16340	312/817	0	1	1
6	fixed 21	247/960	313/960	134663/457520	14765/68628	0	15527/9804	1
7	fixed 23	247/960	313/960	134663/457520	14765/68628	0	15527/9804	1
8	fixed 31	113/480	11/30	115999/343140	1709/9804	3645/22876	2	19231/22876
9	fixed 32	27/128	71/192	182801/686280	5587/68628	3645/22876	83191/34314	19231/22876
10	committed empty	13/160	97/240	7057/16340	312/817	0	1	1
11	committed 1	7/40	9/20	156491/343140	18425/68628	7513/34314	2	26801/34314
12	committed 2	4/15	203/480	28743/114380	3461/22876	0	2	1
13	committed 3	113/480	11/30	115999/343140	1709/9804	3645/22876	2	19231/22876
14	committed 12	217/640	149/320	112319/343140	3761/34314	7513/34314	44657/17157	26801/34314
15	committed 13	187/640	5/12	175531/457520	1531/11438	5261/17157	174521/68628	11896/17157
16	committed 21	7/24	109/240	189589/686280	3461/22876	0	85759/34314	1
17	committed 23	521/1920	899/1920	1213/4515	2629/17157	0	39608/17157	1
18	committed 31	25/96	727/1920	26753/72240	1709/9804	3645/22876	181567/68628	19231/22876
19	committed 32	27/128	71/192	182801/686280	5587/68628	3645/22876	83191/34314	19231/22876
20	adaptive	4/15	7/20	1364/4515	365/1806	0	2	1
21	myopic	4/15	7/20	1364/4515	365/1806	0	2	1

S6.32. Finite model / MHEALTH: Participant and paired results

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Counts below are exact expectations per participant. All selected mixtures are pure in this run, so they happen to be integers; the method does not reinterpret fractional mixtures as realized events. The macro objective averages participants equally. No DEV outcome selected or changed a policy, criterion, threshold or mixture.

All paired abstention transitions for these selected reference comparisons are zero, including both-abstain, to-abstain-from-correct/error and from-abstain-correct/error; they remain explicit in RESULT. Complete/root/query-sequence/terminal-mask/prediction agreement and every gain/tie/regression are also retained there.

Table S39: DEV per participant; expectation semantics apply.

Selector	Participant	Windows	Expected errors	Expected abstentions	Expected quotes	J	Coverage
C minmean A	7	266	98	0	266	159/380	1
C minmean A	8	258	102	0	258	383/860	1
reference minmax F	7	266	66	0	392	214/665	1
reference minmax F	8	258	47	0	437	459/1720	1
paired arbitration A	7	266	66	0	392	214/665	1
paired arbitration A	8	258	47	0	437	459/1720	1
T adaptive	7	266	57	0	532	11/35	1
T adaptive	8	258	49	0	516	187/645	1
T committed	7	266	31	0	532	144/665	1
T committed	8	258	48	0	516	123/430	1

Table S40: Arbitration minus comparator, per participant; corrections/harms among both-predict windows.

Comparator	Participant	Corrections	Harms	Both abstain	Complete action agreement	J difference
C minmean A	7	39	7	0	140	-257/2660
C minmean A	8	72	17	0	79	-307/1720
reference minmax F	7	0	0	0	266	0
reference minmax F	8	0	0	0	258	0
T adaptive	7	1	10	0	126	1/133
T adaptive	8	4	2	0	179	-119/5160
T committed	7	0	35	0	126	2/19
T committed	8	5	4	0	179	-33/1720

S6.33. Finite model / MHEALTH: Question, cache and predeclared scope

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The prior group-weighting study changed scores without changing any of22 corresponding compiled behavior tables. A subsequent selector over frozen policies could not relearn their terminal or acquisition decisions. This study instead changes the optimization class: every legal history may choose STOP using the same frozen masked predictor, abstain at loss2/5, or query a supported unobserved position. No selector32 C/DEV statistics are read or used to choose this study.

The exact same W49 training/cache bytes, SHA25663cf79ae01c7567d630cf9cd1684cd145e56676add90a ab8ff863c485f3ae18a, supply participants 5/6. The T rule ((index//8)%5)<3 gives168 and 154 windows. The remaining C groups contain96 windows each. The TRAIN_C file physically contains C bytes; the main reads them while filtering T, so this experiment makes no C-byte-blindness claim. C labels and predictions are not used in optimization, and C scoring starts only after all T solutions, coefficients, ties and reference endpoints have been frozen.

DEV SHA2565625b00000c8bb88a4b751b020968b0a69076656e91d4dc8aa296fb4b3ebed6c contains266+258 unique windows from participants 7/8. The main reads that separate raw file once after the T freeze. The oracle subsequently uses an exact copy in the author archive. Predictor fitting, inference, new data, NPZ/

UCI470H access, network and model calls are absent. The historical fit/export is provenance metadata and is not re-certified here.

S6.34. Finite model / MHEALTH: Policy rights and the two finite classes

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

An episode starts after mandatory token0 is observed, with one quote already charged. The observation state contains acquired positions and their binary values. At most two further distinct queries are allowed among1,2,3. The seven masks1,3,5,9,7,11,13 give38 observed states; mask15 is forbidden in metadata, recursion and rollout. A prediction error costs1, abstention2/5, and each quote1/20 including the initial quote. Group identity, sample index, label, unacquired tokens and cached predictions are not arguments to the policy decision function.

Raw-T support blocks acquisition unless the current state and every positive-T child have at least30 rows and both groups. This same support is used in both classes. STOP and abstain remain available at unsupported states. A state with zero total T mass has an unidentified terminal decision; returned canonical witnesses use abstention there. Positive-T states break terminal ties by STOP, then abstain, then ascending query. No C/DEV-dependent completion of unseen states is permitted.

Full A contains all legal depth-two contingent root forests. Full F first chooses a single global order from empty,1,2,3,12,13,21,23,31,32 and then may terminate with STOP or abstention at any observed history. Both initial token values share that same order. A fixed order optimizes its full STOP/A grammar, including committed continuation policies, rather than choosing from twenty old T-compiled tables. Both classes allow independent exante mixtures of global forests. Seven canonical unordered subset aliases add no samples or new policies.

S6.35. Finite model / MHEALTH: New policies and complete development comparisons

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The Tmean control exactly reproduces1361/6160 and all 38 historical31 actions, with zero tie changes. Its forest queries2 at initial token0 and 3 at initial token1, then predicts. Robust F chooses global order3: at initial0 it queries3, abstains when the result is0 and predicts when1; at initial1 it queries3 and predicts. The new robust-A forest queries2 at initial0, then queries1 on token2=0 and abstains on token1=1; on token2=1 it predicts. Initial1 queries3 and predicts. Thus terminal and query behavior are newly learned over the grammar.

The main and separate-code oracle agree on all 18 split-policy metric cells and 54 paired-comparison cells. The table retains every predeclared policy. No C or DEV criterion is used to choose mixture weights, terminal ties, the reference or a query order. Fractional expected totals are retained as fractions. For example, paired-A participant 7 abstentions are34650/1471 expected events across266 unique cached windows; this is not an observed integer count of newly sampled randomized episodes.

Relative to robust F, paired-A improves DEV macro J by 5033909/201903576. The participant-specific gaps are85184/978215 for7 and-519733/3795180 for8: participant 7 regresses while8 improves. Against committed2, the macro gap is12482759/201903576>0; against fixed2 it is37931207/2019035760>0. Its DEV J also exceeds Tmean-A. These development regressions prevent a claim of broad improvement even though the T paired certificate is positive.

Table S41: All predeclared solutions. T endpoints refer only to participants5/6; DEV is exposed7/8.

Policy	T J5	T J6	T macro J	DEV macro J	DEV error	DEV A	DEV quotes	DEV coverage
Tmean A	43/280	111/385	1361/6160	1364/4515	365/1806	0	2	1
historical fixed2	37/280	967/3080	687/3080	134663/457520	14765/68628	0	15527/9804	1
historical committed2	43/280	116/385	1401/6160	28743/114380	3461/22876	0	2	1
robust F	3/14	45/154	39/154	115999/343140	1709/9804	3645/22876	2	19231/22876
robust A	377/1680	123/440	9313/36960	145279/457520	5609/34314	6917/68628	52047/22876	61711/68628
paired A	42039/205940	638949/ 2265340	550689/ 2265340	316099513/ 1009517880	8809085/ 50475894	172925/ 2403614	5279353/ 2403614	2230689/ 2403614

Table S42: DEV per-participant metrics for the three robust objectives. Conditional error is error/coverage.

Policy	Group	Unique windows	J	Error	A	Quotes	Coverage	Conditional error
robust F	7	266	36/133	5/38	13/133	2	120/133	7/48
robust F	8	258	523/1290	28/129	19/86	2	67/86	56/201
robust A	7	266	499/1330	55/266	33/266	316/133	233/266	55/233
robust A	8	258	447/1720	31/258	10/129	187/86	119/129	31/238
paired A	7	266	349964/978215	81747/391286	2475/27949	63398/27949	25474/27949	81747/356636
paired A	8	258	1018933/ 3795180	53179/379518	3500/63253	134381/63253	59753/63253	53179/358518

Table S43: Expected paired-A minus comparator results on exposed DEV. Coins are independent across compared policies, on the same source window.

Comparator	Macro J gap	Corrections	Harms	Both predict	To A	From A
historical committed2	12482759/201903576	5/516	346/5719	2230689/2403614	172925/ 2403614	0
historical fixed2	37931207/2019035760	389/17157	661/68628	2230689/2403614	172925/ 2403614	0
robust F	-5033909/201903576	2654693/ 25237947	1067947/ 33650596	25867851/33650596	172925/ 2403614	3645/22876

S6.36. Finite model / MHEALTH: Complete T, C and DEV diagnostics

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

All six predeclared solutions are evaluated on322 T,192 C and 524 DEV unique windows. The18 split-policy denominators have planned=started=completed and failed=budget_exhausted=unknown=unstarted=0. These counts describe expected-policy evaluation on fixed source windows. Mixture component traces, repeated predictions, seven subset aliases and grammar rows are not independent observations.

Per-participant exact expected errors, abstentions, quotes, losses, coverage, conditional errors, corrections, harms and abstention transitions are retained in RESULT.json; the macro is an equal average across the two split participants. Macro conditional error is macro error divided by macro coverage. Paired events use independent exante coins across candidate and comparator, on the same cached window; the loss difference itself does not depend on that coin coupling. Undefined coverage denominators are preserved as null rather than zero.

Table S44: Every split-policy macro metric; C is diagnostic only.

Split	Policy	J	Error	A	Quotes	Coverage
T	Tmean A	1361/6160	149/1232	0	2	1
T	historical committed2	1401/6160	157/1232	0	2	1
T	historical fixed2	687/3080	181/1232	0	67/44	1
T	paired A	550689/2265340	15789/164752	2975/32362	143023/64724	29387/32362
T	robust A	9313/36960	317/3696	17/132	1413/616	115/132
T	robust F	39/154	23/308	11/56	2	45/56
C	Tmean A	37/120	5/24	0	2	1
C	historical committed2	331/960	47/192	0	2	1
C	historical fixed2	7/24	7/32	0	35/24	1
C	paired A	225583/706080	12085/70608	2275/23536	25811/11768	21261/23536
C	robust A	311/960	5/32	13/96	109/48	83/96
C	robust F	289/960	11/192	23/64	2	41/64
DEV	Tmean A	1364/4515	365/1806	0	2	1
DEV	historical committed2	28743/114380	3461/22876	0	2	1
DEV	historical fixed2	134663/457520	14765/68628	0	15527/9804	1
DEV	paired A	316099513/ 1009517880	8809085/ 50475894	172925/2403614	5279353/2403614	2230689/2403614
DEV	robust A	145279/457520	5609/34314	6917/68628	52047/22876	61711/68628
DEV	robust F	115999/343140	1709/9804	3645/22876	2	19231/22876

S6.37. Finite model / MHEALTH: Operational cost scope and cell outcomes

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Each prospective scientific process had CPU240 seconds, wall600 seconds, explicit reads128MiB and writes64MiB; the retained author scope had32MiB and2048 paths. The cooperative actor checks CPU238/ wall598 to reserve reporting time. The own-process supervisor observes the exact Popen handle and records final Windows GetProcessTimes CPU. Guards are neither OS security isolation nor peak-RAM measurement.

The actor ledger predeclares cells and records started/completed/failed/exhausted. Remaining cells stay unstarted after failure; an unavailable final measurement remains unknown. No scientific exception permits source editing or a retry. Synthetic preparation snapshots and all failures stay in the author scope. The native Task has no invented strict180s total authoring cap.

COSTS.json separates actor explicit IO, exact final process CPU/wall, supervisor observations and measured synthetic-preparation wall. Terminal-report emission and document preparation are separately scoped. Native authoring and whole-host usage are not replaced by zeros.

Finite-harness complexity: direct history aggregation is O(nS). If C is the total child-kink affine-cell count, a is the number of candidates and K is the union-cut count, local partitioning uses O(Ca^2) pair tests and complete-signature evaluation uses O(KSa). FullA output has N_A=R0R1 rows and fullF output has N_F=sum_order R0(order)R1(order) rows. The simple LP implementation sorts unique slopes in O(N log N) and evaluates all rows at H dual candidates in O(NH), with O(N) stored rows. These are rational-operation counts with bit cost separate. Actual family/cut/row counts are 11/16/4836/1064. Exponential grammar growth is not hidden behind the38-state example. No polynomial-in-features claim or RAM measurement follows.

Actual completed study-37 supervisor measurements are main CPU 1.328125 seconds, Popen wall 1.813000 seconds, and oracle CPU 0.812500 seconds, Popen wall 1.015000 seconds, with one attempt each, no retries and exit code 0. CPU is the final GetProcessTimes measurement on each exact launched Python process handle; wall includes launch/wait overhead. These numbers are not the older study-33 measurements preserved in R6. Study-37 explicit actor reads/writes remain separately recorded in COSTS and runtime receipts. No addition of measured CPU subtotals would measure native authoring, platform usage, host cost, physical I/ O or peak RAM.

S6.38. Finite model / MHEALTH: Negative findings and historical comparability

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Earlier P/Q31 no_gain and Cmenu32 Gamma0 remain negative findings. Original33 T certificates coexist with mixed DEV results, a strong committed policy and DEV7 harms. None becomes a new independent final result by adding policies, intervals or repeated predictions.

The earlier0.38353 versus0.25112 experiment used another loss contract and is not pooled into the present performance table. The32-to33 change also altered the T/C law. This reanalysis isolates the objective-matched finite class comparison under the33 law; it does not identify the cause of every earlier difference.

S6.39. Finite model / MHEALTH: Distinct strong static controls, exact forests and selection objectives

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A forest [root0,root1] branches on the mandatory initial token's value. S means STOP using the frozen predictor at the acquired mask, A means abstention, and [j,left,right] buys token j and branches on its observed bit. All listed forests include the initial quote in their endpoint and diagnostic costs. A string such as committed2 is a historical name; its numeral is not sufficient to infer how many additional purchases occur.

The historical committed_2 buys token 2 after either initial value and then uses the common supported terminal. It acquired its target on all 524 exposed DEV windows, with no abstention, mean quotes 2, T endpoints (43/280,116/385) and T macro J=1401/6160. Its source is the preserved historical31 control, also retained in cumulative R5 and independently recomputed among the 18 historical metric objects by review39. It is a strong static control with DEV J=28743/114380, approximately 0.251294.

The new the two-additional committed control chooses a supported global order for two additional purchases, forcing continuation while legal before the common terminal/fallback. The T-mean selected order is 3 then 2. Its forest may abstain when a further purchase is unsupported, and its second root need not acquire the

second token when support forbids it. The actual forest is [[3,A,[2,S,S]],[3,S,S]], not the simpler high-θ Bayes witness below. Its T endpoints are (289/1680,929/3080), T macro J=8753/36960 and DEV J=182801/686280, approximately 0.266365. The saved T_SOLUTIONS and RESULT of study37 bind this selection. This policy is distinct from the historical token-2 control even though a previous hindsight full-rights order attained the same DEV scalar; neither a name nor a scalar establishes policy identity.

The new T-mean fixed matches the historical fixed_2 forest [[2,S,S],S] under this exact loss. In contrast, original33 b is global order 3 with an abstention branch, and is the unchanged paired reference. A newly optimized F tie cannot replace its original C/DEV behavior. Full F contains all ten global orders and all eligible STOP/A decisions, so a two-step A-versus-M gap must also be compared with F. Mean no-abstain A is additionally reported and coincides here with T-mean adaptive; this equality is an observed finite result, not a license to remove the control.

Table S45: Actual forests and objectives, with source lineage. S and A have the same meaning in every row; fractions are exact.

Policy	Forest / episode mixture	Selection and source	DEV J
Historical committed token 2	[[2,S,S],[2,S,S]]	T-mean forced subset {2}; historical31 / R5	28743/114380
New Tmean committed2	[[3,A,[2,S,S]],[3,S,S]]	T-mean global two-additional order 3 then 2, forced while legal	182801/686280
Tmean F / historical fixed 2	[[2,S,S],S]	T-mean best full global order with STOP/A	134663/457520
Tmean A = Tmean M	[[2,S,S],[3,S,S]]	T-mean; M at α=1/2	1364/4515
Original reference b	[[3,A,S],[3,S,S]]	Original33 robust-F, identity frozen before scoring	115999/343140
robust A = robust M	[[2,[1,S,A],S],[3,S,S]]	Matched absolute minimax	145279/457520
paired A = paired M	421/1471 mean forest + 1050/1471 robust forest	Direct paired to original frozen b	316099513/1009517880

S6.40. Finite model / MHEALTH: Complete new diagnostic tables and retained historical evidence

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

These tables transcribe the completed RESULT, T_SOLUTIONS and independent numerical review. There are 11 policies times three splits, hence 33 new metric objects, plus six candidates times two diagnostic splits, hence 12 paired objects. The total is 45, correcting an informal 42-object message. The reviewer separately recomputed 18 historical metric objects. Repetition over policies does not create new data: T has 168+154 windows, C has 96+96 and DEV has 266+258 dependent windows from two previously exposed people.

For a participant, J=error+(2/5)abstain+quotes/20. The macro averages participant-specific rates, not pooled counts. Mixtures are exact expectations over complete policies drawn ex ante; fractional abstentions, corrections and harms are not observed randomized integer episodes. The paired statistic uses the same source window and original b on both sides. Error reduction through abstention is separated from prediction correction and does not imply better accuracy at common coverage.

For paired M/A on DEV, participant 7 has J=349964/978215 against b's 36/133, giving harm 85184/978215. Participant 8 has J=1018933/3795180 against 523/1290, giving -519733/3795180. Their macro gap -5033909/201903576 does not erase the first participant's harm or imply a safe new subgroup effect. The older P/Q31 no_gain, Cmenu32 Gamma0, calibrated tie with 83 abstentions, W60 failed/unstarted identification cases and separate W61 finite-catalog outcomes remain in the unchanged cumulative sections. The different-loss .38353/.25112 comparison remains excluded from all of these same-loss performance tables.

Table S46: T study37 complete macro diagnostics. Each participant is weighted equally. T selects; C and DEV diagnose only.

Policy	J	Error	Abstain	Quotes	Coverage
Tmean A	1361/6160	149/1232	0	2	1
Tmean F	687/3080	181/1232	0	67/44	1
Tmean M	1361/6160	149/1232	0	2	1
Tmean committed2	8753/36960	155/3696	11/56	1433/616	45/56
Tmean no abstain A	1361/6160	149/1232	0	2	1
paired A	550689/2265340	15789/164752	2975/32362	143023/64724	29387/32362
paired M	550689/2265340	15789/164752	2975/32362	143023/64724	29387/32362
reference b	39/154	23/308	11/56	2	45/56
robust A	9313/36960	317/3696	17/132	1413/616	115/132
robust F	39/154	23/308	11/56	2	45/56

Policy	J	Error	Abstain	Quotes	Coverage
robust M	9313/36960	317/3696	17/132	1413/616	115/132

Table S47: C study37 complete macro diagnostics. Each participant is weighted equally. T selects; C and DEV diagnose only.

Policy	J	Error	Abstain	Quotes	Coverage
Tmean A	37/120	5/24	0	2	1
Tmean F	7/24	7/32	0	35/24	1
Tmean M	37/120	5/24	0	2	1
Tmean committed2	223/768	1/24	23/64	403/192	41/64
Tmean no abstain A	37/120	5/24	0	2	1
paired A	225583/706080	12085/70608	2275/23536	25811/11768	21261/23536
paired M	225583/706080	12085/70608	2275/23536	25811/11768	21261/23536
reference b	289/960	11/192	23/64	2	41/64
robust A	311/960	5/32	13/96	109/48	83/96
robust F	289/960	11/192	23/64	2	41/64
robust M	311/960	5/32	13/96	109/48	83/96

Table S48: DEV study37 complete macro diagnostics. Each participant is weighted equally. T selects; C and DEV diagnose only.

Policy	J	Error	Abstain	Quotes	Coverage
Tmean A	1364/4515	365/1806	0	2	1
Tmean F	134663/457520	14765/68628	0	15527/9804	1
Tmean M	1364/4515	365/1806	0	2	1
Tmean committed2	182801/686280	5587/68628	3645/22876	83191/34314	19231/22876
Tmean no abstain A	1364/4515	365/1806	0	2	1
paired A	316099513/ 1009517880	8809085/50475894	172925/2403614	5279353/2403614	2230689/2403614
paired M	316099513/ 1009517880	8809085/50475894	172925/2403614	5279353/2403614	2230689/2403614
reference b	115999/343140	1709/9804	3645/22876	2	19231/22876
robust A	145279/457520	5609/34314	6917/68628	52047/22876	61711/68628
robust F	115999/343140	1709/9804	3645/22876	2	19231/22876
robust M	145279/457520	5609/34314	6917/68628	52047/22876	61711/68628

Table S49: Historical controls remain separate from the 33 new split-policy metric objects. Recomputed historical loss contract matches this table.

Historical policy	T macro J	C macro J	DEV macro J
historical committed2	1401/6160	331/960	28743/114380
historical fixed2	687/3080	7/24	134663/457520

Table S50: All 12 new direct paired diagnostic objects against the same original b. Rates are participant-macro expected events; independent ex ante policy coins share each source window.

Split / candidate	Candidate-b J	Corrected	Harmed	To A	From A
C Tmean A	7/960	1/64	0	0	23/64
C Tmean M	7/960	1/64	0	0	23/64
C paired A	26047/1412160	771/94144	0	1225/47072	27183/94144
C paired M	26047/1412160	771/94144	0	1225/47072	27183/94144
C robust A	11/480	1/192	0	7/192	25/96
C robust M	11/480	1/192	0	7/192	25/96
DEV Tmean A	-2467/68628	3841/34314	1357/22876	0	3645/22876
DEV Tmean M	-2467/68628	3841/34314	1357/22876	0	3645/22876
DEV paired A	-5033909/201903576	2654693/25237947	1067947/33650596	172925/2403614	3645/22876
DEV paired M	-5033909/201903576	2654693/25237947	1067947/33650596	172925/2403614	3645/22876
DEV robust A	-28159/1372560	7033/68628	11/532	6917/68628	3645/22876
DEV robust M	-28159/1372560	7033/68628	11/532	6917/68628	3645/22876

S6.41. Strong static control: Question and result

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

The unresolved historical comparator is empirical::subset_2. It acquires token position2 after the initially observed position0, then always predicts with the unchanged mask5 predictor. Its restored T endpoint is

S=(43/280,116/385), with macro J=1401/6160. Its exposed DEV loss28743/114380=0.251294 is distinct from the new two-additional policy with DEV182801/686280=0.266365.

S is already feasible in complete fixed-order F and adaptive A. Restoring it changes neither feasible set. Against S, direct paired Γ is6/1015 for both A and the complete shared-α myopic M, while F has0. Additional two-step planning value over this M is0 under both anchors and under minimax. On DEV the S-anchored A/M policy has J497487/1658510=0.299960, worse than S. These exact finite-cache findings are retrospective; independent final participants remain0.

Algorithm S15. Restore historical static identity and certify matched finite families
Require: Frozen seven-mask T/C/DEV prediction cache and hashes; historical38-action table; original b forest; support30/both-groups; error1, abstain2/5, quote1/20.
Ensure: Restored historical endpoint/forest, complete F/A/M and explicit MplusS, exact primal/dual witnesses, paired diagnostics and preserved failure status.

1. Verify sealed new code and all input bytes. Split T/C by floor(index/8) mod5; keep previously exposed DEV diagnostic.
2. Compile the old decision table from both initial roots. Compare all38 actions, distinguishing off-path differences from reachable forest equality.
3. Recursively enumerate STOP/A and every legal query with both child programs. A parent and every positive-T child require30 rows and both participants; empty histories canonically use A.
4. Multiply both initial roots for A; for F first fix one common order of length0..2 before multiplying the roots. Include the initial quote.
5. Construct M from every exact child-terminal kink, affine-score intersection, exact point and open interval; keep a shared alpha fixed over each episode.
6. Verify S membership in F/A and M. Name the addition to M explicitly MplusS. If common F/A membership fails, require a symmetric extended grammar rather than extra rights for one class.
7. Optimize minimax and direct paired objectives against each of b and S. Return feasible exante mixtures and all-row rational dual inequalities.
8. Freeze primary T selector bytes before C-label use and DEV reading. Evaluate the predeclared C-derived terminal control and fixed-path interventions afterward, without retuning.
9. Independently verify integer-state grammar, convex-polygon primal optima, overpartitioned M signatures and all outcome rows. Preserve failed/exhausted runs; do not restart accepted actors.

S6.42. Strong static control: Policy identity and equal rights

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

The frozen historical source is projects/probeflow_dev_advance_20261029_01/author/main_001/SELECTION.json, strict_subset_policies id empirical::subset_2. It was selected among the historical empirical strict subsets by a T surrogate, rather than by a new DEV selection. Its reachable forest is [[2,S,S],[2,S,S]], indexed by initial token0 value0/1. Every row uses mask5, exactly2 quotes and no abstention.

The coherent_macro::committed_2 table yields the same reachable forest, but only35 of38 full action-table entries match. At (0,-1,-1,1), (0,0,-1,-1), and (1,0,-1,-1), historical strict_subset_2 queries2 while committed_2 stops. These histories are unreachable from the two initial roots under token2. We establish reachable-policy identity and retain the off-path differences rather than claiming complete action-table equality.

All queries use support30 and both T participants at the parent and every positive-T child. STOP/A remain available at every nonempty history, independent of support; an empty history canonically uses A. Mask15 and a third additional query are forbidden. Each family pays the initial quote1/20. S is feasible under common orders[2],[2,1],[2,3]; no grammar extension is needed. M does not contain S, so MplusS explicitly augments M under the same observable information and query rights.

S6.43. Strong static control: Complete families and matched objectives

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

L_g(pi) is mean wrong-prediction loss plus2/5 times abstention plus1/20 times all quotes over T participant g. An exante mixture coin is independent of participant and window. We separately minimize max_g L_g(pi),

and max_g[L_g(pi)-L_g(anchor)] for original b and historical S. Γ is negative of the latter optimum. Subtracting two separately optimized robust values would not calculate this paired objective.

A contains4836 forests from78 and62 initial-root programs. F has1064 order-indexed rows over all10 global orders, including aliases. M has11 complete38-history signatures from a shared episode-fixed α one-step replanning rule. Alpha is a design parameter; θ belongs to the separate outer endpoint adversary. Exact rational breakpoints and point ties establish completeness, not an α grid. MplusS explicitly adds S.

Table S51: Exact T objectives: lower minimax loss and larger paired Γ are better.

Family	Minimax loss	Γ vs b	Γ vs S
F	45/154	0	0
A	123/440	2091/205940	6/1015
M	123/440	2091/205940	6/1015
MplusS	123/440	2091/205940	6/1015

S6.44. Strong static control: The restored anchor changes the question, not the complete grammar

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Against b=(3/14,45/154), A=M attains2091/205940 with the original two-component witness. S was already in F/A, and its addition to M leaves the lower hull and optimum unchanged. Minimax loss remains45/154 for F and123/440 for A=M=MplusS. No generalization or population safety follows from these T equalities.

Against S, the A/M/MplusS optimizer mixes8/29 of [[2,S,S],S] with21/29 of [[2,S,S],[3,S,S]]. Its endpoint (1199/8120,3298/11165) equals S-(6/1015,6/1015), with dual theta79/145. Paired F achieves0 by retaining S; theta28/215 certifies it. History-dependent first-query/termination choices improve the finite T paired objective relative to one global order, but full two-step planning adds nothing over the stated M.

Gamma2091/205940 and6/1015 use different anchors. Neither is predictive DEV improvement or a calibrated uncertainty radius. The earlier8.07% conditional certificate-radius result is not recomputed here and must not be relabeled as performance.

$$R_{\mathcal{A}} = R_{\mathcal{M}} = \frac{123}{440}, \quad R_{\mathcal{F}} = \frac{45}{154}$$

Minimax loss under the same two frozen training laws and legal policy rights.

$$\Gamma_S(\mathcal{A}) = \Gamma_S(\mathcal{M}) = \frac{6}{1015}, \quad \Gamma_S(\mathcal{F}) = 0$$

The exact paired gain relative to the restored static policy S. Adding S to the myopic family leaves this value unchanged.

S6.45. Strong static control: Exposed T/C/DEV outcomes

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Primary T selectors and weights were hash-frozen before C-label use and before the new DEV raw read. A separately named TC-shrink64 terminal control uses C only after this primary freeze. All10 original participants were already exposed in the project. Current inputs contain322 T windows and192 C windows from participants5/6, and524 DEV windows from7/8. Repeated policy outcomes are not independent samples.

The mean-T A/M policy beats S on T but loses on DEV. The original-b paired selector has DEV0.313119. Switching the declared anchor while holding class and T fixed yields a different selector with DEV0.299960, still above S0.251294. C favors these complex policies relative to S, so C success does not remove the DEV reversal. The new two-additional comparator also remains worse than historical S on DEV. No hindsight optimum over the entire DEV F/A family is claimed.

Table S52: Frozen named policy macro J; all C/DEV values are diagnostic.

Policy	T	C	DEV
Historical S token2	1401/6160	331/960	28743/114380
Original b	39/154	289/960	115999/343140
New two-additional	8753/36960	223/768	182801/686280
Tmean F	687/3080	7/24	134663/457520
Tmean A=M	1361/6160	37/120	1364/4515
Minimax A=M	9313/36960	311/960	145279/457520

Policy	T	C	DEV
Paired A=M vs b	550689/2265340	225583/706080	316099513/1009517880
Paired A=M vs S	39573/178640	1057/3480	497487/1658510

S6.46. Strong static control: Controlled failure attribution

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Let P be the original-b paired A selector and P_stop the same mixture and acquisition forests with every A leaf replaced by STOP. The fixed predictor at each acquired mask is unchanged, as are per-row acquisition and quote counts. Since S always predicts, J(P)-J(S)=[J(P)-J(P_stop)]+[error(P_stop)-error(S)]+[quotes(P_stop)-quotes(S)]/20. All terms are actual frozen-policy interventions on the same cached rows.

The DEV excess0.06182535 decomposes into terminal change0.00119404, mask/predictor error0.05081016, and quote cost0.00982115, with exact residual0. P_stop still has DEV0.311925, so removing abstention alone does not resolve the failure. Most of this particular gap is the selected predictor mask error, followed by extra quotes. This is a controlled cache-level effect, not an estimator-only causal effect on new populations or hardware.

For participant7,140 initial-token1 windows switch from S position2/mask5 to P position3/mask9. Both have2 quotes and STOP, but mask9 produces26 net additional errors, with0 corrections and26 harms. Participant8 has5 corrections and6 harms on the same root1 path, while a different path benefits from abstention. P-minus-S J is27628/195643 for participant7 and-13333/759036 for participant8; macro reporting must preserve this harm.

Table S53: Fixed-policy decomposition of original-b paired P minus S.

Term	T	C	DEV
Terminal on fixed P path	755/64724	35/23536	1435/1201807
Mask error, both STOP	-1/154	-7/192	3487/68628
Quote cost, both STOP	2715/258896	455/47072	94425/9614456
Total P minus S	28377/1812272	-7147/282432	12482759/201903576

S6.47. Strong static control: Conditional risk versus actual frozen predictor errors

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

With token2 acquisition fixed, both T-pooled and coherent Tmacro terminal rules choose STOP at every reachable leaf and reproduce S. The predeclared TC-shrink64 control changes only the terminal at history (0,-1,0,-1), still mask5. T has23 errors among95 matching rows and C32 among52. Its blended risk (32+64*(23/95))/(52+64)=1128/2755 exceeds abstention cost2/5, so it chooses A.

At the same history DEV participant7 has14/100 errors and participant8 has18/45=2/5. Abstention therefore hurts participant7 and ties participant8. At identical acquisition and quote cost, macro J rises from S0.251294 to1807/6020=0.300166 on DEV, while falling from331/960 to55/192 on C. Estimated conditional risk, the action selected from it and observed error of the unchanged predictor are separate quantities.

S6.48. Strong static control: Where the static policy wins

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.




Figure S19: Exact cached-row reanalysis on two exposed DEV participants (524 dependent windows). The stronger-static-anchored selector still loses to static token 2. The three terms in panel (b) sum exactly to the original paired selector's excess loss. No independent final evaluation or population causal claim is implied.

S6.49. Strong static control: Source identity, policy and exposure

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Actual Task task_89d46feba97a, Run run_edf0173ced28, native executor /root/probeflow_baseline60 writes only this author directory. This is not a canonical campaign wave or supervised Dispatch. Root owns lifecycle, Git, independent review and rendering. The current coordination POLICY_INPUT_HASHES matched actual policy/reviewer/builder bytes before seal.

Training/C cache SHA256:63cf79ae01c7567d630cf9cd1684cd145e56676add90aab8ff863c485f3ae18a. DEV cache SHA256:5625b00000c8bb88a4b751b020968b0a69076656e91d4dc8aa296fb4b3ebed6c. MODEL metadata SHA256:7715e75101d9db6fa55269b4413be96534480f84e1df5c662fa4c24fb15c673f; it reports predictor export identity97bb82dae0c271a75882dbf48fd0feb5b11392a3c6cd4a71f1cd70a7bd9332b2. Metadata identity is a provenance binding, not new verification of the fit.

Before seal the author actually read old code, results, action tables and conditional statistics; raw training/dev JSONL bodies were first read by sealed main. This does not erase prior exposure. No original cache rows are copied into delivery. RAW POLICY_ROWS contains derived local outcome traces, explicitly distinct from new independent observations.

Table S54: Actual policy, reviewer and rendering fingerprints.

Role	SHA256
AGENTS	fd95bd3617f06296d07a4700b3c11dc473acbf0e2a9fca0549ff5ff62d0c55b9
POLICY	8cc2186af0c31a224a8898edca18664176b27badb6bf11f4853b6da46766e1eb
Method reviewer	5ab3e12480b8bf43f3716f24c9b1f54304231276b8ce1a4bd58f73ceef7d4dfc
Base builder	b89b3ee7abdb802d4f14a161a139513d41b80c2cd56e24541025a8b8839c7fad
Actual renderer	919bb36e3316fbf21d54d6a3c6941381140b251029cddccec70d3bc3d3b207e1

S6.50. Strong static control: Exhaustive observable grammar and complexity

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

At every nonempty history include STOP/A and, for each legal query, every Cartesian product of child programs. Empty histories use canonical A. Induction on remaining depth proves local completeness, and multiplying both roots proves all A forests. F first chooses a common order before observing token0, then restricts depth-d queries to the d-th entry, retaining contingent STOP/A. This avoids granting an initial-value-dependent order to F.

F order counts for (),1,2,3,12,13,21,23,31,32 are4,36,36,36,196,196,196,84,196,84. A root counts78/62 yield4836 forests. Without support exclusions a depth1 node has at most2+2*(2*2)=10 programs and a root2+3*(10*10)=302, giving an upper bound91204. Actual support restrictions reduce these counts. All38 off-path old actions are preserved separately from reachable forest membership.

For R training rows and H histories, direct aggregation uses O(R*H) row tests. Grammar work is the sum of legal child-product sizes and K=R0*R1 root products, with O(K) retained rows. Main line-envelope optimization uses O(K log K) rational comparisons plus all-row verification. Bit complexity of exact fractions is additional. Shared-α family enumeration evaluates H decisions at finitely many candidate intersections; if E cuts are retained this costs O(H*E) one-step scores. These are arithmetic counts, not hardware efficiency claims.

Algorithm S16. S1: Independent integer-state oracle
Require: Frozen T rows and common support/mask rules; stored main witnesses only for final comparison.
Ensure: Independent complete endpoint multisets and explicit mismatch/failure.

1 Represent histories as integer mask and observed bit value. Count errors and support separately for both groups.
2 Build all legal child products bottom-up using integer twentieth-loss counts. Import no main or historical scientific code.
3 Add one initial quote per row, then divide by original global group denominators. Enumerate both-root products and common F orders.
4 Compare complete forest/endpoint multisets, including order aliases, and verify each selected cached outcome independently.

S6.51. Strong static control: Complete M and an independent superset partition

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

The shared α one-step query score is current quote mass/20 plus the sum of child min(STOP error mass,A cost mass). No second acquisition enters this score. After a query, replan with the same α and remaining rights. Zero raw-T histories choose A; positive raw-T histories tie STOP, A, ascending query. Zero weighted mass at alpha0/1 is not zero raw support.

Main partitions at child terminal kinks and all score equalities on their affine validity intervals, evaluating exact points and open representatives. Oracle instead intersects every affine line from every child-terminal choice, including inactive choices. Any true change must be a child-choice change or intersection of two listed affine pieces, so this independent superset partition is complete. Its61 cuts and121 locations yield exactly the same11 full38-action signatures.

S is outside M but inside F/A. MplusS adds it explicitly; all computed lower-hull objectives remain unchanged. This states a result about this globally parameterized one-step family, not all possible myopic algorithms.

S6.52. Strong static control: Exact primal-dual proof and witnesses

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Against anchor a the primal is min_lambda max_k(sum_i lambda_i v_ik-a_k). For any θ in[0,1], min_i[$\theta^\star$ (v_i5-a5)+(1-θ)*(v_i6-a6)] is a lower bound: convex mixtures preserve the weighted average and a maximum endpoint is at least that weighted average. Main finds an exact lower-envelope maximizer and a feasible deterministic or two-row mixture attaining it. This proves equality without a numerical tolerance.

Oracle independently constructs the full convex polygon of endpoint points, evaluates its vertices and boundary intersections with the shifted equal-loss diagonal, then checks all main dual inequalities, mixture weights, component legality and endpoint equality. A two-component witness suffices here because the endpoint space is two-dimensional; this does not extend automatically to arbitrary dimension. All12 objectives were independently verified.

Original-b paired weights are421/1471 on [[2,S,S],[3,S,S]] and1050/1471 on [[2,[1,S,A],S],[3,S,S]]. Strong-S paired weights are8/29 on [[2,S,S],S] and21/29 on [[2,S,S],[3,S,S]]. The anchors and resulting policies differ, and both are retained.

Table S55: Important frozen identities.

Identity	Reachable forest	T endpoint
Historical S	[[2,S,S],[2,S,S]]	43/280 ; 116/385
Original b	[[3,A,S],[3,S,S]]	3/14 ; 45/154
New two-additional	[[3,A,[2,S,S]],[3,S,S]]	289/1680 ; 929/3080
Minimax A=M	[[2,[1,S,A],S],[3,S,S]]	377/1680 ; 123/440

S6.53. Strong static control: Denominators and participant outcomes

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

T participant5 has168 unique windows and participant6 has154; C has96 each; DEV has266/258 for participants7/8. Macro averages give participants equal weight. Fractional expected counts arise from analytically evaluated exante mixture coins and are not extra episodes. Conditional error is error/coverage, with null for zero coverage. Macro conditional error is macro error divided by macro coverage, rather than the average of participant-conditional errors.

Every expected count, path, terminal mask and quoted acquisition appears in MAIN and POLICY_ROWS. Eight distinct selected forests across1038 total source windows give8304 derived outcomes. Main does not optimize the entire F/A family on DEV, and no DEV oracle-best hindsight selector is reported.

Table S56: Participant means for all primary frozen comparator identities.

Split	Policy	g	J	Error	Abstain	Quotes
T	S	5	43/280	3/56	0	2
T	S	6	116/385	31/154	0	2
T	Paired b	5	42039/205940	3713/82376	175/1471	6559/2942
T	Paired b	6	638949/2265340	3019/20594	1050/16181	35437/16181
T	Paired S	5	1199/8120	3/56	0	382/203
T	Paired S	6	3298/11165	905/4466	0	4142/2233
T	Two-additional	5	289/1680	1/168	3/28	69/28
T	Two-additional	6	929/3080	6/77	2/7	337/154
C	S	5	4/15	1/6	0	2
C	S	6	203/480	31/96	0	2
C	Paired b	5	423301/1412160	11243/70608	875/11768	52147/23536
C	Paired b	6	159677/470720	4309/23536	175/1471	51097/23536
C	Paired S	5	919/3480	5/29	0	11/6
C	Paired S	6	239/696	1/4	0	325/174
C	Two-additional	5	27/128	0	25/96	205/96
C	Two-additional	6	71/192	1/12	11/24	33/16
DEV	S	7	144/665	31/266	0	2
DEV	S	8	123/430	8/43	0	2
DEV	Paired b	7	349964/978215	81747/391286	2475/27949	63398/27949
DEV	Paired b	8	1018933/3795180	53179/379518	3500/63253	134381/63253
DEV	Paired S	7	6101/19285	1725/7714	0	1022/551
DEV	Paired S	8	1768/6235	1405/7482	0	7166/3741
DEV	Two-additional	7	75/266	33/266	13/133	316/133
DEV	Two-additional	8	647/2580	5/129	19/86	319/129

S6.54. Strong static control: Paired correction/harm and path ledger

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Corrections and harms refer only to both-predict rows. Abstention also removes observed prediction errors while incurring2/5 loss, so corrections minus harms alone does not determine J. The raw pair output retains both-predict, to/from-A, both-A, path disagreement, errors, abstentions, quotes and J, with per-path expected counts.

DEV participant7 root1 has140 equal-cost STOP paths with26 net extra mask9 errors. On its root0 branch, added position1 after token2=0 produces no error change when predicting; the A path has expected34650/1471 windows and removes2100/1471 errors relative to S. Participant8 root1 has79 rows and1 net extra error; its A path has expected21000/1471 windows and removes18900/1471 errors. Thus participant8 can improve while participant7 is harmed. All fractional counts retain the declared mixture, rather than silently sampling or selecting a favorable component.

Table S57: Original-b paired P minus S; rates use each participant denominator.

Split	g	Correct	Harm	To A	Error gap	Quote gap	J gap
T	5	0	0	175/1471	-25/2942	675/2942	595/11768
T	6	5/77	4/77	1050/16181	-6196/113267	3075/16181	-8719/453068
C	5	0	0	875/11768	-175/23536	5075/23536	3115/94144
C	6	11/96	1/24	175/1471	-19747/141216	4025/23536	-23639/282432

Split	g	Correct	Harm	To A	Error gap	Quote gap	J gap
DEV	7	0	13/133	2475/27949	18073/195643	7500/27949	27628/195643
DEV	8	5/258	1/43	3500/63253	-17429/379518	7875/63253	-13333/759036

S6.55. Strong static control: Fixed-acquisition terminal control and surrogate mismatch

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

At (0,-1,0,-1), T counts/errors are54/9 and41/14. Pooled conditional risk23/95 and coherent conditional macro risk89/362 both choose STOP. C counts/errors29/16 and23/16 push TC-shrink64 to1128/2755>2/5 and choose A. This diagnostic control is explicitly C-derived after the T-primary freeze. It does not receive different acquisition or predictor rights.

On DEV the same history has100/14 and45/18. Changing only S to A increases participant7 loss by(100/266)*(2/5-14/100) and ties participant8. On C both group conditional errors exceed2/5 and the intervention lowers macro J by7/120. The DEV macro increase is1807/6020-28743/114380. These are actual fixed-policy cache effects, not population calibration certification.

The old empirical selector combined macro initial-root weights with pooled conditionals, inducing row law Q=Pmacro(root=t)/n(root=t), while current law P gives1/(2*n_g) per group row. Fresh reweighting of the frozen historical seven strict policies reconstructs every old estimated_J. S has old Q surrogate16343/72930 versus actual P Tmean1401/6160. It is historically T-surrogate-selected, whereas full P TmeanF and TmeanA/M prefer other policies that lose on DEV. This is an algebraic selection/generalization contrast, not a new independent generalization estimate.

S6.56. Strong static control: Reproduction boundary, actual failure and budgets

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

The two actual single scientific commands are python -X utf8 -B research.py –main and python -X utf8 -B test_research.py –oracle. They must not be repeated in this accepted scope. All command arguments, PIDs, stdout, stderr and exit codes are in EXECUTION.json. Three preparation synthetic invocations are also retained, latest18 checks; they read no real cache. Oracle mode imports no main or historical scientific module.

Main completed all scientific cells and RAW saving, then exited1 at research.py line615 during final stdout Fraction serialization. No postseal code change or main retry was made. Oracle exit0 verified22 groups: all grammar rows, all M signatures, all12 certificates, all selected aggregates and8304 row outcomes. That same-author arithmetic oracle is distinct from the different-author scientific review still pending.

Scientific-body timers in RUNTIME are not whole-process timers. Final Windows CPU is1.703125s main/1.734375s oracle; supervisor wall is1.922s/1.781s. Main read663250 bytes; oracle read1630306 including decompressed members. Runtime was serialized before the final archive write, so explicit_write_bytes=0 there is a prewrite snapshot. Actual main output is the persisted RAW.zip byte size in RESULT. No exhaustion occurred under CPU180/wall600/read128MiB/write32MiB. Cooperative guards and own-child termination are not OS security isolation. Authoring, implicit module IO, physical IO, peak RAM and host costs remain unmeasured.

Integration erratum: the frozen author text used incorrect shorthand command names. The displayed commands above match EXECUTION.json. The original DOCUMENT bytes and this correction are both retained; neither scientific command was rerun.

S6.57. Strong static control: Contribution, related work and next acceptance

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Established within frozen bytes: historical reachable identity and exact T endpoints; explicit35/38 action comparison; F/A inclusion and M exclusion with named augmentation; matched-anchor objective certificates; no extra planning value; controlled terminal/path/cost accounting and source-level arithmetic verification. Preserved failure: main process exit1 after successful scientific archive. Preserved negative results include historical S DEV superiority among these named controls, participant7 harm, C/DEV reversal and M/fullA ties.

This no-network lane retrieved no new external primary source or priority evidence, and references are deliberately empty. Standard finite convex-mixture arguments are proved here without claiming a new general

robust-RL principle. Root must integrate the separately assigned literature/theory lane and preserve verified URLs, access scope and source hashes for external attributions.

Evaluation and related work remain partial. Root needs a different-author completed reviewer Task bound to frozen DOCUMENT/contract/RESULT. A new target evaluation must predeclare strong static/myopic/full-adaptive selectors, independent labels, full failure denominators and actual acquisition costs. Any broader TV/DRO certificate must justify an augmented common joint law for tokens, labels and shared per-mask predictions; no such coverage or original fit recertification is supplied here.

S6.58. Strong static control: Exact source-bound diagnostic figure

Scope. MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights.

Panel (a) reads macro J directly from the recorded DEV metric rows. Panel (b) reads the three controlled decomposition terms from MAIN.json inside RAW.zip, whose rational sum is checked before plotting. The main process saved these results but exited with a final stdout serialization error; that failure and the separately executed arithmetic oracle remain visible in the execution record. This figure is a display of saved results, not a replay.

S6.59. Reference routes: Question, intervention and principal result

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

Algorithm S17. Reference-Paired Reserve with coupled temporal laws

Require: Frozen mask predictions and binary acquisition observations for T/C, subject identifiers used only in fitting, support30/both T subjects, error1, abstention2/5 and quote1/20. Historical reference S that buys token2 after initial token0 and predicts at mask5; maximum two additional purchases; the presealed R/F/A/menu and input hashes.

Ensure: An executable finite policy forest or the actual charged reference fallback, exact finite-law selection values, complete comparator policies and explicit no_gain/failure. Per-participant paired losses, errors, abstentions, quotes, coverage, corrections and harms, plus a record that no population certificate has been obtained.

1. Verify fresh-code seal, current policy/source bindings and frozen prediction hashes. Form T and C by the fixed index-block rule; use the same fitting access for every comparator.
2. Enumerate every legal STOP/A/query continuation using only T-derived query support. R permits initial STOP or A; otherwise it purchases reference token2 before any optional refinement. F first fixes one global order; A allows every legal history-contingent query.
3. For every candidate and each of T5,T6,C5,C6, compute the same-window candidate loss minus S loss, charging the initial observation and every purchase. S predictions used by the estimator are training counterfactuals, never free online observations.
4. Minimize the maximum of these four paired differences. Prefer lower T/C macro quote use and canonical policy bytes among strict improvers. If the best objective is nonnegative, return the actual S policy.
5. At execution, consult only the acquired observation history. A refinement buys its feature and commits to the unchanged current-mask predictor or A. It cannot substitute the mask5 prediction after buying another feature.
6. Serialize and hash fitted selection before evaluating DEV outcomes. Report all prelisted estimator/action-family/myopic controls without DEV tuning, retain no_gain and failed attempts, and verify the finite results with the separate own oracle.

S6.60. Reference routes: Policy structure and information access

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The figure summarizes information access in the predeclared policy family.




Figure S20: Reference-first routing and its separation from offline selection. All candidates use the same T/C information; these are four repeated temporal laws from two people. Online baseline information must be bought. Early termination cannot access unpurchased reference predictions. This diagram describes the admissible family, not an observed performance improvement.

S6.61. Reference routes: Information, charging and support contract

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

A state records four binary acquisition observations, using -1 for an unobserved token. Position0 is observed initially; positions1,2,3 may be purchased at most twice. The allowed predictor masks are 1,3,5,9,7,11,13, and mask15 is unavailable. These observations control acquisition; no sufficiency claim is made that the frozen classifier depends only on the binary tokens. Every terminal prediction uses the existing prediction recorded for the features actually acquired at that mask.

Every nonempty state permits STOP, which emits the current-mask forecast, or A, which abstains. A query requires at least30 T records and both fitting participants at its parent and every positive-T child. Zero-T histories canonically abstain. Subject identity is unavailable to the executing policy. Support is derived from T once and shared across R, F, A and all myopic controls; C labels influence selection equally but cannot create new query rights.

Loss is an incorrect-prediction indicator, plus2/5 for abstention, plus1/20 per quote including the initial observation. S buys position2 and predicts at mask5, so it pays exactly two quotes. R can stop early, or acquire position2 and then refine using position1 or3. It can never forecast with an unbought reference feature. Once a refinement is purchased, current-mask STOP/A applies; the method does not assume the old reference forecast remains a free terminal option. The charge is an artificial logical objective, not measured sensor energy, latency or provider billing.

S6.62. Reference routes: Paired value estimation under temporal disagreement

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

Let J(g,d,pi) be mean charged loss for participant g in temporal partition d. The primary score is U_TC(pi)=max over g in{5,6}, d in{T,C} of[J(g,d,pi)-J(g,d,S)]. Candidate and reference confront the same empirical temporal law. This keeps their covariance and common difficulty shift. T5,T6,C5,C6 are four finite laws formed from two participants, not four independent people.

The matched separate-risk score is max over g of[max_d J(g,d,pi)-min_d J(g,d,S)]. It allows candidate and reference to shift to different temporal laws, so it is at least the same-law paired score. The exact S identity is retained as a zero-score fallback atom. For a single fixed set of weights, direct paired means and subtraction of separate means are algebraically identical. The present distinction concerns the uncertainty set, not a newly improved nominal predictor or a bias reduction from subtracting losses.

For any common mixture of the four empirical laws, paired excess is at most U_TC by linearity. This is an assumption-qualified finite statement: the target must face the same mixture of those fixed joint laws and the same predictions, costs and policy. It supplies no evidence that an unseen participant is such a mixture, no probability coverage for a population uncertainty set, and no deployment safety certificate. Within-person

temporal windows are dependent. No statistical calculation treats their count as an independent-participant sample size.

A one-label-per-T-participant perturbation is prelisted only as a narrow ablation. Its exact paired bound preserves cancellation when forecasts agree. It is not a model of the previously observed26-error route failure. The primary temporal criterion was fixed before new cache outcomes, following the prior mechanism diagnosis; it was not relaxed after seeing a return to S.

S6.63. Reference routes: Complete controls and equivalence checks

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The same T support yields4836 adaptive deterministic forests A and532 reference-prefix forests R. Complete fixed-order stopping F has836 distinct forests, represented1064 times when aliases across all ten length0..2 orders are retained. An order is shared before observing the initial token; STOP/A may still depend on observations. Four allSTOP fixed-subset/order forests are feasible under the stricter requirement to complete their order on every positive path. The larger F contains all legal conditional stopping variants.

The prelisted matched factorial compares R/F/A with same-law temporal pairing, independently perturbed temporal risks and T-only pairing. R/A additionally receive the one-label stress. Strong controls include the immutable S and T minimax F/A. Local myopic controls use the same conditional T/C information and one-step queries; nominal shared-α myopic policies are enumerated from exact terminal kinks, action-line intersections, exact points and open intervals. The nominal family has11 complete38-state signatures but only3 reachable forests. S is absent from that family, so selections that add S are explicitly named MplusS.

The new optimization is over deterministic forests. Earlier reported convex-mixture improvements, including the strong-reference Gamma6/1015, are preserved historical results and are not reoptimized here. They cannot be contradicted by a deterministic no-improvement result or used as a reproduced new benchmark. This deliberate scope leaves randomized reference-route optimization open.

The selected RPR forest equals S and belongs to complete F. Its reachable behavior also equals the new same-law temporal myopic control. It is not one of the original nominal shared-α signatures, but that difference does not establish a planning advantage: adding the lawful S atom makes the selected behavior identical. This is a measured equivalence result on the finite policy representations, not an algorithmic improvement obtained by renaming fixed-order stopping.

Table S58: Complete finite policy denominators; aliases are not independent policies or observations.

Family	Count	Selection access
Reference-prefix R	532	T/C same-law or matched ablation
Fixed-order stopping F	836 distinct;1064 aliases	same T/C access and support
Adaptive A	4836	same T/C access and support
AllSTOP fixed orders/subsets	4 feasible	same objective
Nominal shared-α myopic	11 full signatures;3 reachable forests	T rule construction;T/C matched selector
Reported selectors	21;5 distinct forests	DEV never used for selection

S6.64. Reference routes: Outcomes, coverage and failure to improve

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The primary acceptance rule required a strict negative T/C paired objective, a changed policy, strictly lower C and DEV macro loss than S, no participant loss regression and no macro coverage decrease. C is a fitting temporal law, and DEV compatibility is retrospective rather than a held-out test. The rule fails because the primary equals S and its objective is zero. No threshold or candidate menu was changed afterward.

T-only paired selection, temporal separate-risk selection and the one-label stress also return S for all prelisted factorial families. Thus the experiment does not isolate an estimator benefit or a benefit from restricting the action family. Even the full deterministic A cannot attain a strict negative worst-T paired score. A randomized-policy investigation would be a separate question; the current data do not justify a claim that temporal coupling itself caused the reference fallback.

All primary windows predict, none abstain, and every primary quote total equals twice its window denominator. Against S, primary corrections, harms, abstention transitions, error difference and quote difference are all zero for every reported participant and split. Lower losses relative to historically inferior selected policies reflect restoration of the strong comparator, not new acquisition gain.

Table S59: Macro charged loss of the five distinct selected forests. Full per-policy metrics and paired counts are in RAW.zip/MAIN.json.

Named selector	T	C	DEV
RPR and every global paired/separate factorial selector=S	1401/6160	331/960	28743/114380
T minimax F	39/154	289/960	115999/343140
T minimax A	9313/36960	311/960	145279/457520
Local independent-temporal myopic A	127/480	251/960	99665/274512
Local independent-temporal myopic R	9857/36960	47/192	243829/686280

Table S60: Primary RPR=S counts; T and C repeat the same two fitting participants.

Law	Windows	Errors	Abstentions	Quotes	J
T5	168	9	0	336	43/280
T6	154	31	0	308	116/385
C5	96	16	0	192	4/15
C6	96	31	0	192	203/480
DEV7	266	31	0	532	144/665
DEV8	258	48	0	516	123/430

S6.65. Reference routes: Route-specific mechanism and the limits of recovery

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The predeclared historical failure is visible in the new controlled execution: participant7 has140 DEV windows with initial token1. Mask5 makes0 errors there, whereas mask9 makes26; both use two quotes when acquired directly and both predict. RPR stays at mask5. T minimax A and local independent-temporal myopic A still buy position3 at this root and retain26 paired harms for participant7. Their DEV macro losses are respectively145279/457520 and99665/274512, both above S.

Actual fitting data show route disagreement rather than a universal good or bad sensor. At state(0,-1,-1,1), the mask9-minus-mask5 conditional error difference for participant5 moves from11/78 in T to3/13 in C; for participant6 it moves from-1/29 to0. At state(1,-1,-1,1), participant6 differences are-7/27 and-9/17. These are fitted-law diagnostics for an already specified route, not posthoc subgroup primary tests or estimates of future participant harm.

Reference restriction prevents terminal mask9 acquisition in R, but it is not sufficient to improve the general outcome. The independently perturbed local myopic R stops early at initial token1 and uses an abstaining refinement elsewhere. It reduces average DEV quotes to63787/34314 while increasing DEV loss to243829/686280. The local independent-temporal myopic A has DEV quotes52047/22876 and loss99665/274512. Their poor transfer shows why a purchase-saving or uncertainty label alone cannot certify useful acquisition.

The full paired controller declines all such deviations and returns S, but the same paired myopic and fixed-order selections do so too. Route recovery relative to a previously harmful policy is observed; additional planning value, an estimator-specific causal improvement and population protection remain unestablished.

S6.66. Reference routes: Exact split, loss and the observed failure basis

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

Training cache rows belong to participants5/6. T uses floor(index/8) mod5<3 and has168/154 windows; C is its complement and has96/96. DEV contains participants7/8 with266/258. There are1038 unique records across these partitions,514 from two fitting participants and524 from two exposed development participants. Other original participants were historically exposed too. The1038 records and5190 policy-row traces are not independent participant samples.

The preceding frozen report identified original paired-mixture DEV excess12482759/201903576, decomposed exactly into terminal1435/1201807, both-STOP mask error3487/68628 and quote94425/9614456. These are earlier reported results linked by source hashes. They motivated reference routing; this lane never imported or replayed that actor. New main independently verifies the immutable S T endpoint43/280,116/385 and reproduces its stored DEV loss through the new evaluator.

For each window, integer loss units are20*wrong+8*abstain+quotes. Divide by20 and by the participant window count, then average participants equally for macro reporting. Conditional error is macro error divided by macro coverage, while per-participant conditional errors are retained separately. Empty coverage returns null rather than a fictitious zero error. No constraint at a populated global T/C law is empty; the local conditional-law log is also empty in this execution.

S6.67. Reference routes: Coupled and separate temporal bounds

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

For any candidate pi and each participant g, let a_T,a_C be its two temporal risks and b_T,b_C the corresponding reference risks. Then max(a_T-b_T,a_C-b_C)<=max(a_T,a_C)-min(b_T,b_C). Equality need not hold because the right side may combine different temporal laws. This finite inequality needs no stochastic independence. It is the actual difference between the prelisted value-estimation rules.

The synthetic covariance test makes T reference error0 and C reference error1 while a refinement preserves exactly the same forecast and adds one quote. The paired upper excess is1/20; the independently shifted upper excess is21/20. Both nominal same-weight estimators still have the same mean. This establishes a computational cancellation property, not an empirical performance improvement on the real cache.

If U_TC(pi)<=0, every common convex mixture of the four empirical laws has nonpositive paired excess. For proof, each component difference is<=U_TC; multiply by common nonnegative weights summing to one and sum. Allowing different mixture weights for candidate and reference invalidates that conclusion and corresponds to the separate-risk uncertainty set. Neither statement demonstrates that a future population lies in either set. Two temporally partitioned people cannot supply four-person confidence coverage.

The fallback is an identity atom: pi=S has exactly zero paired excess even when the separate-risk interval bound max b-min b is loose. Retaining that identity avoids charging uncertainty for a policy compared with itself. Every family gets the same atom and selection tie/fallback rule. The method returns S unless there is a strict negative selected score.

Algorithm S18. S1: Same-law temporal endpoint selector
Require: Candidate forests, S, the four exact empirical loss/quote vectors and a fixed mode.
Ensure: A strict finite-law improver or S, plus the selected objective and vector.

1. Use paired_TC, independent_TC, paired_T or the predeclared label1_T score without changing the candidate family or data rights.
2. For paired_TC subtract S at the same participant/time law before taking the maximum. For independent_TC take candidate maximum and reference minimum separately per participant, retaining the exact S identity.
3. Rank by worst-law score, then mean T/C quotes, then canonical forest bytes.
4. If the best score is nonnegative and S is feasible, return the actual S forest. Serialize the choice before DEV evaluation.

S6.68. Reference routes: Exact finite label-stress ablation

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

Holding covariates, forecasts and a deterministic forest fixed, one label replacement changes only one window's prediction-loss difference; query costs remain unchanged. When candidate and reference both predict the same class, paired error cancellation is exact for every replacement. When their predicted classes differ, the maximal candidate-minus-reference error is1. If the candidate abstains, the maximum is2/5, reached by a label equal to the reference prediction.

The main aggregates the largest nonnegative increase over T rows of each participant and adds it to that participant's nominal paired excess. This is exact for at most one relabeled window per participant. The oracle independently substitutes the original, candidate and reference class labels to obtain leaf gains and exhausts candidate minima. Its selected witnesses are also checked by direct rowwise substitutions.

An already perfect reference makes the abstention excess2/5-0 maximal, so a label change cannot raise it further. Two preseal test runs initially expected a positive extra uplift on that fixture and failed. The final test creates actual reference errors before checking positive abstention uplift. All tests and corrections preceded cache opening and sealing. This narrow stress test is not the primary robustness set and does not imitate the26-window development route failure.

S6.69. Reference routes: Online information and route reserve

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The offline estimator can compare counterfactual frozen predictions from all masks on T/C. The online policy receives only the currently acquired binary history and, on STOP, the forecast attached to its acquired features. Root policy actions are fixed by the compiled forest. The reference forecast at mask5 does not influence a root decision as an observed value before position2 is bought; it influenced only training-time endpoint construction.

R's reserve is structural: before any optional off-reference refinement, the missing reference position2 is purchased. Thus the controller cannot spend the remaining budget on an off-reference position and then falsely claim a free S fallback. Once optional refinement occurs, the fixed current-mask STOP/A rule is binding. A general off-reference detour with a stored-reference terminal prediction would require a symmetrically enlarged terminal grammar and is not implemented here.

The family is potentially adaptive because the extra probe after position2 may be1 or3 depending on observed tokens. Synthetic membership tests exhibit such a forest in R and A but outside complete fixed-order F. The measured winner, however, uses no such adaptive branch and is exactly S. Potential expressiveness is distinct from realized advantage.

S6.70. Reference routes: Complete controls and policy identity

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

RAW.zip/POLICIES.json contains all21 named selectors, full reachable action maps, family memberships, strict-reference equality, nominal myopic matching signatures and exact T/C score vectors. RAW.zip/GRAMMAR.json contains complete R/F/A forests and every A four-law loss and quote vector. RAW.zip/POLICY_ROWS.jsonl contains one row per distinct selected forest/window, keyed by split, forest ID, subject and original index. FOREST_IDS.json maps the five IDs to immutable forest values.

R_paired_TC, F_paired_TC, A_paired_TC, their independent_TC and paired_T variants, both label1_T variants, the strong fixed-subset control, both nominal MplusS selectors and both paired_TC local myopic controls all equal S. The four other forests are F_minimax_T, A_minimax_T and local independent_TC myopic R/A. This exhausts the prelisted menu rather than retaining only the primary or the most favorable control.

Complete F includes observation-contingent STOP/A and is stronger than a static sensor-subset-only comparison. The stricter forced allSTOP order menu contains four feasible forests under T support; unsupported orders are not forced through illegal histories. A/M comparisons with exante randomization remain historical and are explicitly outside this new deterministic selector. Eleven nominal M signatures collapsing to three reachable forests must not be counted as eleven independent behavioral replications.

S6.71. Reference routes: Paired error, abstention and quote decomposition

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

For each participant and selected policy, MAIN.json/paired reports both-predict counts, reference-error corrections, reference-correct harms, predict-to-abstain and abstain-to-predict transitions, matched masks, and signed error/abstention/quote changes. The exact identity is δ J=δ errors/n+(2/5)δ abstentions/n+(1/20)δ quotes/n. The same-author oracle checks this identity and all integer denominators independently.

For primary=S every signed term and paired correction/harm is0. For T minimax A on DEV participant7, δ errors=24, δ abstentions=33 and δ quotes=100 over266 records; δ J=211/1330. Its26 both-predict harms are not equal to its24 net error increase, because abstention transitions also change error counts. On participant8 its δ J=-9/344, illustrating why reporting only macro improvement or only error conditional on prediction can conceal participant regression.

For local independent_TC myopic R on DEV participant7, quote change=-40 but error change=23 and abstention change=67, giving δ J=239/1330. Participant8 quote change=-34, error change=-1 and abstention change=25, giving δ J=73/2580. Fewer purchases coexist with worse charged loss. These are descriptive controlled outputs; the study does not infer that independent temporal bounds cause future harms beyond this particular compiled local rule.

S6.72. Reference routes: Tests, oracle scope and process outcomes

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

The final fifteen synthetic tests cover initial/current-mask costs, lawful reference membership, zero paired self-risk, nominal paired/separate mean identity, exact temporal cancellation, covariance-sensitive bounds, off-reference mask exclusion, empty-history canonical A, label-stress cancellation, non-fixed-order R expressiveness, nominal one-step family membership, paired decomposition, aligned-window adapter rejection and complete main-object serialization. Their fixture is explicitly synthetic, not an MHEALTH performance sample.

The new main and own oracle are each single, supervisor-recorded scientific attempts. Main exit0 and oracle exit0 are preserved with commands, PIDs, stdout, stderr, process CPU and wall timings in EXECUTION.json. No failed scientific main was retried; the two preseal failures were fixture-assertion development failures. Postseal code/contract/source hashes match SEAL.json.

The own oracle imports no research module. It reconstructs4836 A,836 F and532 R forests bottom-up, checks all endpoint vectors, exhausts every factorial optimum, checks selected relabeling witnesses and5190 row outcomes, and verifies all per-participant paired metrics. It does not substitute for Root's different-author review of the full method, novel claims, nominal one-step completeness or local conditional greedy logic. The46 assertions are grouped verification evidence, not scientific certification.

S6.73. Reference routes: Provenance, eligibility and remaining method gaps

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

SOURCE_HASHES.json binds actual current repository policy/checker/builder/routing files, actual Task/ coordination instructions, previous source/result/archive/document and independent review, and the original cache lineage/MODEL metadata. Training and DEV hashes are verified again in both scientific actors. The delivery contains derived policy rows, not duplicated original cache records. Publication is Root-owned and has not been performed by this author.

Original four-stream WISDM evaluation is unexecuted. Root denied value release on clock/alignment eligibility grounds before any fitting or FINAL access. The synthetic adapter never invents stream correspondences. No external data reading, classifier training, model API, native benchmark episode, download or dependency addition occurred. A later single-device axis experiment would require its own new contract.

Algorithm and finite complexity are implemented and checked. Architecture remains partial for live acquisition and predictor-fit recertification; evaluation remains partial for independent participants and physical cost/ failure; baselines remain partial for external methods and randomized policies; related work remains partial because no new primary-source literature was retrieved. Independent review cannot turn any of these missing measurements into a completed scientific claim.

S6.74. Reference routes: Relation to robust baseline regret

Scope. MHEALTH reference-first routes and temporal/label-stress bounds on exposed development.

Comparing the candidate and baseline under the same uncertain law has established precedent in robust baseline regret [27]. This experiment restricts its comparison to four observed empirical temporal laws. It provides no coverage argument that places a new participant distribution in that set, and therefore does not inherit a population-safety guarantee from that literature.

S7. WISDM custody, windows, descriptors and shared predictor results

The WISDM evidence uses fixed activity-homogeneous 100-sample phone-accelerometer windows. Axes are logical information units, not independently priced sensors. TRAIN/TUNE/CAL comprise 25/8/8 people and 24,880/7,845/6,437 windows. This chapter preserves curation failures, fixed feature formulas, all reported participant/mask/class outcomes and unequal-capacity qualifications.

S7.1. Source clocks: Procedure

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

Algorithm S19. Acquire once, bind custody, and fail closed on unsupported episode alignment
Require: The actual bounded custody Task, official UCI 507 page and observed download href, an immutable subject split and request/read/write/time budgets. The preceding evaluation contract, independent method review, named exposure records and current policy/checker/builder hashes.
Ensure: A preserved complete or partial archive transfer, source/member/split hashes, explicit exposure and clock findings, and a locally held release decision. Either independently reviewable data eligibility or an explicit blocked result; never invented synchronization or performance.

1. Freeze the actual Task authority, origin/redirect policy, one-attempt GET budget and exact observed official href. Hash-rank all 51 official subject IDs before reading raw values or labels.
2. Reserve a write-once GET attempt marker before network transmission. Stream at most 400 MiB, preserve failures and partial bytes, and never automatically retry an accepted or unknown request.
3. Reject traversal, absolute paths, symlinks, encrypted or nonregular members. Materialize only the explicitly identified nested archive, and treat bundled source code and instructions as data.
4. Read the existing bounded official PDF and text metadata. Audit only prespecified TRAIN rows for raw schema, timestamp units/ranges, file-order resets and target transitions; do not pair by row ordinal or activity label.
5. If a legitimate common clock cannot be justified, return four-stream alignment blocked before any joint window or feature construction. Keep every original contract, failure and inspected-row denominator.
6. Hold raw archives locally and publish only thin hashes and split-specific member indexes. Require Root and a distinct completed review to bind custody before any later fitting or FINAL release.
7. Record a requested alternative only as TRAIN-schema feasibility. A different logical feature-group protocol requires a separate prospective Task, exclusion rules and independent review before values are released.

S7.2. Source clocks: Authority, source identity and exposure

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

The preceding benchmark 61 contract authorized design only and expressly prohibited downloads. Actual Task task_07833dfcd88d in Run run_edf0173ced28 supplied the new bounded acquisition authority. We obtained the exact ZIP href from the official UCI page, performed one successful dataset GET without redirects, and used no mirror, credentials, installation, model API or archive code. The official page reports 51 participants, 18 activities, a nominal 20 Hz rate and CC BY 4.0 attribution to Gary Weiss (2019). These are source statements; observed file counts and inspected schemas are separate execution findings. The bundled description PDF is 578,662 bytes, 5 pages, SHA256 1d378fb33f871714cf2b1fbec65bab7eeed9 3e1892fc1460d80e45c022ce92ba. Both bundle copies have the same hash. PyMuPDF 1.26.4 preserved page text and character boxes without OCR.

Fourteen named local provenance/configuration records were read. They establish prior public-metadata discussion of WISDM but do not certify global nonexposure of data values. The prior 120 second and 45 second recursive-search timeouts remain explicit. A new Git HEAD query succeeded; worktree enumeration and a bounded path-specific log query timed out at 15 seconds each. Unlisted ignored/untracked files, other worktree contents, accounts and model pretraining are outside this audit. The 10 FINAL subjects are a newly frozen protocol holdout, not globally certified unseen people.

S7.3. Source clocks: Clock evidence and the preserved alignment failure

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

The official page and README name Unix time, while the bundled description calls the integer field Linux time. None of the inspected documentation specifies a phone-watch epoch, offset, synchronization marker or

transformation. The description also warns that 20 Hz is a request to the operating system and sampling may be delayed. We therefore do not equate a row count with elapsed time or assume that equal activity codes identify simultaneous measurements.

For the SHA-ranked first TRAIN subject 1612, the first 4000 rows of each of four streams were inspected. The phone accelerometer prefix spans timestamp 3,741,356,837,350..4,131,852,130,754; the watch accelerometer prefix spans 5,095,185,812,517..5,485,716,828,014. Positive median increments are 50,354,004 for both phone sensors and 49,915,760 for both watch sensors. Combined with the source's nominal 20 Hz, these values are consistent with nanoseconds; this is an inference, not a documented cross-device clock. Each prefix has one nonpositive step. Separated prefix ranges are evidence against naive common-time matching in this inspected scope, not a proof that every recording is intrinsically unsynchronizable. No common-clock mapping was established, so four-stream joint episodes are blocked.

The schema contains the expected six fields and finite x/y/z values in the inspected rows. The archive contains all 204 expected member names, but most payloads were not opened. File presence is not certification of complete activities, valid timestamps or absence of missing samples in all 51 people. Four-stream window eligibility, transition exclusions and missingness rates therefore remain unmeasured rather than being set to zero.

S7.4. Source clocks: A bounded same-row alternative, not a substituted benchmark

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

Root requested a TRAIN-schema assessment of treating the x/y/z fields of one phone-accelerometer row as three logical measurement groups. Reading the full preselected TRAIN 1612 phone-accelerometer file found 64,312 valid rows,17 activity transitions,7 nonpositive timestamp steps, all 7 at activity transitions, and no consecutive duplicate timestamp. Original order yields 8 monotone epochs. All valid rows contain three finite axes together; no cross-device pairing is needed to access these three logical groups.

Under the explicitly conditional nanosecond interpretation, a zero-origin grid of 5,000,000,000 timestamp units yields 665 observed metadata bins;16 are first/last bins of monotone epochs. Bin sample counts range 7..100 with median 99. There are 649 interior single-activity bins, but this is not the number of eligible complete windows: forward gaps, activity-boundary partial bins and any minimum-coverage rule have not been admitted. We created no episode or feature file. A separate prospective Task must confirm the time-unit assumption and freeze reset epochs, grid origin, gap limits, activity-transition and partial-bin exclusions, minimum samples, all exclusion denominators and learning rights before fitting. Rows must retain their original order; separated intervals cannot be silently sorted or joined.

Axis queries would measure access to cached feature channels of one already recorded sensor. They cannot demonstrate physical sensor activation, energy savings, network latency or safe deployment. Three logical groups permit different query choices, but grammar alone proves no advantage over a complete matched fixed-order stopping baseline. A two-group device-restricted alternative is even more limited and likewise cannot establish adaptive query-choice superiority from its grammar. No alternative protocol is authorized by this custody result.

S7.5. Source clocks: Exact subject split and local release permissions

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

The dataset tag is UCI507-WISDM-2019. For each decimal identifier 1600..1650 without padding, compute SHA256 of the UTF-8 string ProbeFlow-benchmark61-v1|UCI507-WISDM-2019|{decimal_subject_id}; sort by ascending digest bytes and assign the first 25 TRAIN, next 8 TUNE, next 8 CALIBRATION and final 10 FINAL. SPLIT_MANIFEST.json was frozen before GET and before raw values. Its SHA256 isfdf67acf4662 d6f49eb59e2a16a83bc5602fec60de1c61a5383416b31c93e598. The acquisition contract hash is71db1b3e54d8 7071f391817771389b3caef368d37cbc00e0e1d598aceca86f09. All 51 official IDs and four expected filenames per person were found; this establishes file-identity coverage only.

The first TRAIN subject is 1612. Its four 4000-row prefixes and full phone-accelerometer file were inspected. There were 80,312 raw member row visits and 76,312 unique inspected member rows, because 4000 phone-accelerometer rows were visited twice. The public PDF contains three illustrative rows for subject 1600, also assigned TRAIN; these public-document examples are separately recorded exposure. No FINAL raw member rows were read, no FINAL feature/label values were sent to Root or the method author, and no fitting release was made. Public aggregate tables are source metadata, not evaluation outcomes.

S7.6. Source clocks: Request, parsing and failure evidence

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

The allowed dataset GET was at most 419,430,400 bytes and 600 seconds; the observed GET completed once in 78.063 seconds with HTTP 200 and zero redirects. Two small official metadata reads were used, counting the web view and saved page capture; HEAD requests were zero. No accepted or unknown GET was retried. The archive contains executable-looking bundled source files, which were enumerated as data and never imported, compiled or executed.

The first synthetic test run exposed Windows ZipInfo normalization of backslashes; validation was corrected to check orig_filename as well as filename, and the failure is preserved. The first preparation pass stopped before raw access because the parser expected filename components in device/sensor order, whereas official names use sensor/device. The actual official schema was inspected, a regression test added, and preparation resumed from the completed local nested ZIP without another GET. The failure record, conservative prior-read carry and both code/test corrections are retained. Worktree and path-specific Git-log timeouts remain unresolved scope limitations rather than negative exposure results.

S7.7. Source clocks: Prospective axis protocol acceptance, without authorization

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

Any successor must preserve this failed four-stream contract, issue a new actual Task and freeze the revised logical-group target before feature construction. Its training-only schema evidence may justify a same-row x/y/z access model; it does not yet supply 51 people's verified window denominators. Confirm or explicitly condition the timestamp unit, retain original-order epochs at nonpositive steps, exclude partial/transition/gap-invalid bins by predeclared rules and report their union and overlap denominators. Do not use labels to reconstruct cross-stream alignment. Do not count windows or random seeds as independent subjects.

Before fitting, bind the exact accepted source/split/feature code and permission manifests to a distinct completed custody review. Then fit only under a separately authorized predictor/comparison contract, hold FINAL values and target outcomes locally and untouched by tuning, preserve all failures, and report any changed eligibility without favorable subject substitution. Physical sensing/energy/latency and external published-method reproduction require separate evidence.

S7.8. Source clocks: Reproducibility and byte-bound evidence

Scope. WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance.

research.py contains the one-attempt acquisition, safe member checks, split construction, bounded exposure audit and TRAIN-only schema audit. test_research.py exercises origin/credential rejection, traversal/symlink rejection, exact split determinism and counts, actual filename identity, malformed/nonfinite rows, unknown-request no-retry behavior, bounded prefix denominators and reset/transition/edge accounting with synthetic inputs. These tests are code checks, not sensor-performance observations.

SOURCE_HASHES.json binds current input policies, checker, document builder, routing files, the actual request, prior independent review, source metadata and local evidence. ACQUISITION.json, CLOCK_AUDIT.json, EXPOSURE.json, SPLIT_MANIFEST.json and LOCAL_CUSTODY.json carry the thin observed records. Raw archives, extracted full source text/character boxes and partition-member indexes stay under private/ and are excluded from the canonical report/Git delivery. SESSION_REPORT.json uses the exact five-field contract and path/hash evidence; FREEZE.json binds final report artifacts without a self-hash cycle.

S7.9. Window construction: Construction question and explicit algorithm

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

We prepare a distinct subject-disjoint, single-device logical-feature benchmark before any predictive fit or outcome. Three co-recorded phone accelerometer axes provide six unchanged statistics each. The question is whether a fixed sample-count protocol can construct data without assuming a universal absolute clock rate. The prior fixed-time preparation remains unchanged.

A purchased logical axis reveals its six already-curated values. This is not three physical sensors, measured sensor acquisition, energy reduction, or deployable transition detection. Homogeneous ground-truth activity segments define an offline curation restriction.

Algorithm S20. Sealed relative-gap fixed100sample logical-axis construction
Require: Hash-bound existing official outer/inner UCI507 archives; exact51-person subject split; original phone accelerometer ASCII rows 18-class map; fixed100sample size; relative gap multiplier4; unchanged six statistics perx/y/z; bounded one-shot resources
Ensure: Private paired features/metadata CSVs and exclusion/audit files for TRAIN,TUNE,CAL,FINAL Thin all-person denominators, schemas, hashes, measured construction counters, explicit failure or completion; all values held

1 Verify the pre-value seal, policy/checker/builder/source pins and exact subject split. Accept at most one new execution marker.
2 Verify both archive SHA256 and byte sizes. Check safe names/types and exactly51 phone accelerometer members; allow only the exact frozen .DS_Store metadata identity.
3 Read original rows in order. A nonincreasing timestamp starts a new epoch; an activity change starts a segment. Preserve malformed rows; any unreadable timestamp excludes the whole person with unknown full denominators.
4 Within each segment use only positive dt between consecutive original rows that are both valid and finite. Sort those integers and represent the median exactly as an integer numerator over2.
5 Break runs at invalid-row boundaries or gaps strictly above4 times the segment median using integer arithmetic. Never join across a segment/epoch or unknown timestamp.
6 From each run start emit nonoverlapping chunks of exactly100 rows. Preserve the shorter trailing remainder as exclusion; a segment lacking positive dt emits no chunk.
7 Compute the unchanged18 finite sample statistics. Write identical row_index/window_id into both CSVs; write targets/subjects/ticks only as metadata and exclude all identity/metadata from predictor inputs.
8 Validate headers, row counts, paired identities/order and finite feature values; hash every private output and retain every assigned person, including zero eligible.
9 Return thin construction evidence only. Any accepted/unknown failure keeps partial files and is never restarted. No fit, normalization, network, model call or value release occurs.

S7.10. Window construction: Preserved source, protocol history and exposure

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

The source is the already acquired official UCI507 WISDM bundle [32, 33]. We retain exact51subject identities, the SHA-bound25/8/8/10 split and all18official activity codes. No new HTTP request, dataset, subject reassignment, imputation, relabelling, timestamp sort or cross-device ordinal pairing is used.

Axes69 failed before raw opening because it counted the known .DS_Store metadata member as a sensor file. Axes73 repaired that inventory defect in a separate preparation, then retained18,135 windows with17/7/5/4 contributing people from25/8/8/10 assigned. Its TRAIN-only stored audit found that all5,216 bins for eight zero-eligible TRAIN people failed the absolute interval-scale gate; segment medians were about20million or39.9million ticks. This explains the prospective redesign, not a posthoc repair of a predictive score.

Root had already seen axes73's aggregate FINAL contributor count4/10 before this new protocol. That ancillary exposure is permanent. Historical global payload or model exposure remains unknown. No predictor/acquisition-policy fit or final predictive outcome has run. Custodian access for construction is distinct from later value release; no perfectly blinded or globally untouched confirmation claim is made.

S7.11. Window construction: Data flow, identities and failure boundaries

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

The sealed code verifies source/control bytes before accepting one execution marker, verifies both archive identities, parses only exact phone accelerometer members, constructs original-order epochs/segments/runs/chunks, writes private paired CSVs, checks their common identities and hashes outputs. Raw/features remain local under private; thin CUSTODY and DENOMINATORS carry schema/counts/provenance only. Root and another completed review must bind exact new construction inputs before any fit release; FINAL requires a later policy/model freeze and separate gate.

Both CSVs contain the same row_index and subject/epoch/segment/run/chunk window_id. Feature CSV has those two excluded identity columns plus18numeric feature_columns; metadata contains labels, subjects, times and source references. Only the18declared feature columns may enter a predictor or acquisition policy. The complete column and class schema and original subject-then-source order are explicit.

A known-time invalid/nonfinite row breaks continuity and remains recorded. Any unreadable timestamp excludes the whole person, eligible0; full construction denominators are unknown while locatable observations remain separate. The sample-count protocol has no time grid. Trailing remainders, gap boundaries, zero-eligible people and failures remain visible. This is cooperative custody, not OS isolation.

S7.12. Window construction: Construction verification and observed denominators

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

Before opening new raw values,21author checks passed: frozen486member metadata, exact .DS_Store identity, parser/archive/clock/error boundaries, cadence20/25/50 fixtures, positive-integer time rescaling/translation, exact100row tails, and all51subjects across four output partitions with paired identity/schema/hash writes. One new preparation completed with exit0. It read4,804,403source rows and produced47,573eligible chunks. Assigned people remain[25, 8, 8, 10]; contributing people are[25, 8, 8, 10]; zero-eligible people total0. These counts are construction observations, not independent predictive samples.

Malformed rows observed:0; subjects with unreadable timestamp:0. Per-subject assigned/eligible counts and exclusions are retained in DENOMINATORS; detailed segment/line audits stay private. No FINAL per-class label summary or predictive result appears in this report. The unchanged prior fixed-time variant remains available with its attrition.

Table S61: Assigned and contributing people and eligible fixed100sample chunks; no per-class or predictive outcomes.

Partition	Assigned people	Contributing people	Zero eligible	Eligible chunks	Rows read
TRAIN	25	25	0	24880	2512167
TUNE	8	8	0	7845	793855
CALIBRATION	8	8	0	6437	650240
FINAL	10	10	0	8411	848141

S7.13. Window construction: Complexity and measured scope

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

For n source rows and segment lengths m_j, original-order parsing/chunking is O(n); sorting segment increments costs O(sum_j m_j log m_j). Feature computation is O(18n) with fixed100row blocks. This implementation buffers one person's parsed rows, segment indices/increments and accepted chunk references, so its storage is O(n_person) plus output and CSV identity-validation sets. It is not a streaming constant-memory implementation.

The accepted preparation measured CPU91.250s, wall98.766s, conservatively counted read1020756986bytes and write25555236bytes before the execution receipt. Limits were CPU600s/wall1200s/read2GiB/write256MiB and starting free disk1GiB. Command-wrapper wall/exit and separately counted post-check/documentation work are retained. Counters intentionally include compressed/decompressed reads and output checks; physical I/O, peak memory and physical clock seconds are not established.

S7.14. Window construction: Exact constructor, accounting and rejection rules

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

A positive dt enters a segment median only if its endpoints are consecutive original rows, in the same monotone activity segment, both valid and finite. Invalid rows do not contribute either adjacent dt. For an even number of increments the middle pair sum is the numerator over2; for odd count twice the middle value is the numerator. The gap inequality2*dt>4*median_twice is exact under positive integer timestamp rescaling and translation preserving order and representability. Median includes all such positive gaps before the run split; it is not pooled over separated activity segments.

Run numbering starts0within each segment; chunk numbering starts0within each run. Segments use monotonically increasing original-order ordinals across the subject's epochs. Every emitted chunk has100rows,99positive within-run intervals, one official activity and finite axes. A complete chunk from a subject with an unlocatable row is rejected, and its possible count is only a locatable observation. Gap events have zero row weight; invalid rows have one; tails preserve their row counts. Valid-row accounting equals100times candidate chunks plus tail rows before whole-person exclusion.

S7.15. Window construction: Prespecified schema, statistics and local custody

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

Features retain the exact parent source AST: mean=sum/100; population standard deviation=sqrt(sum squared deviations/100); min; max; RMS=sqrt(sum squares/100); mean absolute successive difference=sum of99absolute differences/99. They are ordered six values forx,theny,thenz. Nonfinite derived values fail preparation, without automatic repair. No statistic uses target/subject/timestamp/partition as a predictor.

CUSTODY declares feature_columns18, feature_csv_columns20, identity_columns2, full metadata_columns, fixed class_map, ordering, source_license/license and per-file role/path/SHA256/bytes/rows. Each partition retains assigned_subject_ids and eligible_subject_ids. Features/metadata share iden-

tical row_index/window_id and are checked together, including row count, unique identity, complete headers and finite18features. Metadata and identity are explicitly excluded from predictor and policy inputs. Exclusion JSONL, per-person audits and raw-member hashes preserve traceability without transporting FINAL class observations.

S7.16. Window construction: Validation and resources are author evidence

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

The synthetic suite uses only synthetic values and the immutable486member-name inventory. It does not import or replay the old research actors. The actual parent failures, completed references and new source diff are pinned, including exact forge.digest(forge.encoded(original Task.result string)) reference derivation. These checks establish concrete implementation boundaries, not independent scientific review.

The actual accepted marker permits one new preparation. Cooperative read/write/time counters and an owned-child wall timeout enforce the declared application policy; they are not an OS sandbox. A failed or unknown accepted execution is preserved and never restarted. Wrapper command, log, exit, preparation counters, exact output hashes and later verification costs are recorded separately. Maximum RAM and physical I/O remain unmeasured.

S7.17. Window construction: All-person denominators, unchanged history and exposure

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

The original51subject assignment is unchanged. New eligible chunks are[24880, 7845, 6437, 8411]in TRAIN/TUNE/CAL/FINAL order. New contributing people are[25, 8, 8, 10]against[25, 8, 8, 10]assigned. Zero-eligible people remain in per-subject denominators, never replaced. Exclusions are row/tail/gap events, not a fictitious fixed-time grid. This is a newly declared benchmark variant; parent73's18,135fixed-time windows and17/7/5/4contributors are retained unchanged.

Root's prior FINAL4/10aggregate eligibility knowledge and the stored TRAIN interval metadata motivated/preceded this new protocol. FINAL feature values, per-class labels and predictive outcomes remain withheld from Root and the method author. Global historical nonexposure is not proven. No outcome-based protocol optimization or perfectly blinded confirmation is claimed.

S7.18. Window construction: Six-area gaps and next gates

Scope. WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting.

Algorithm and architecture are concrete construction components. Complexity has analytical costs and measured counters but lacks peak-memory/physical-I/O evidence. Evaluation has author construction fixtures and actual denominator records but lacks a distinct completed reviewer and predictive evidence. Baselines and related-method evaluation remain partial; no scientific completion gate is closed by the author map.

Root owns lifecycle, completed independent review and any exact six-file TRAIN/TUNE/CAL release. A later exact two-file FINAL release requires frozen predictor/policy bytes. No library artifact, global skill, existing experiment, shared automation or common source was modified by this custody work. Native SOL max is a requested configuration, not independently verified effective identity.

S7.19. Failed representation record: Failed delivery and observed forecast scalars

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

One classifier using the fixed 54 feature representation was actually fit and evaluated. The final result serialization failed, and the complete paired record for41 people was not saved. The original failed receipt is preserved;81 was not restarted.

TRAIN: 91.00% to 93.00%, gain +2.00 percentage points; TUNE: 28.07% to 30.76%, gain +2.68 percentage points; CAL: 25.08% to 33.39%, gain +8.31 percentage points. These are partial stdout observations awaiting separate independent review.

Algorithm S21. Fixed representation experiment and explicit failure return

Require: Exact released six TRAIN/TUNE/CAL CSVs, original51person split,41 phone-accel members of the pinned inner archive Frozen71 fullmask classifier; sealed54features, forest settings, weights, costs, resource limits and development checks

Ensure: One private enhanced classifier/mean/scale payload, observed stdout scalars and immutable failed EXECUTION receipt Incomplete result flag: full41person paired details were not saved, so no completed acceptance or scientific gain claim

1 Before actual values, validate source schemas, manual container decoding and tiny synthetic reconstruction/ feature/fit/evaluation tests; seal exact scientific code and formulas.
2 Read only exact41 allowed phone-accel members. Reconstruct windows exclusively from released metadata ranges; verify100rows, identities, subjects/activities, timestamps and every original18feature.
3 Retain18old columns, append12fixed within-axis descriptors for each xyz axis. Exclude all metadata/labels from predictors; use sample-index spectral bins only.
4 Decode the pinned71baseline through inert source-correct holders and an installed NumPy/sklearn allowlist. Verify all forest parameters, TRAIN normalization and79aggregates.
5 Fit one enhanced fullmask ExtraTreesClassifier on TRAIN only with equal-person weights,128trees, depth12, leaf5, max_features1.0 and seed6101. Predict TRAIN/TUNE/CAL once with coverage1 and cost0.15.
6 Attempt to save full paired person/confusion/model-size results. On the observed NumPy-int64 JSON failure, preserve EXECUTION and the already saved private model; never restart, fit, reconstruct or predict again in81.
7 Return partial stdout observations and a failed delivery. A separately registered82review may independently reconstruct and infer with the saved models, without any new fit.

S7.20. Failed representation record: Fixed representation and architecture

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

Each axis retains the six75statistics. Center u_i=x_i-fsum(x)/100. Add autocorrelations at lags1,2,4,8,16,32 with numerator over valid pairs and denominator sum(u_i^2) over all100 samples. For P_k=abs(rFFT(u)[k])^2,k=1..50, use q=P/sum(P), without positive-bin doubling; append mass fractions for1..5,6..15,16..50,max(q),entropy -sum(q log q)/log(50),and mean[(u_i<0)!=(u_(i+1)<0)]. Exactly constant axes return twelve zeros. Both signed zeros are nonnegative. These are sample-index bins, not Hz or physical time.

TRAIN25 people/24,880windows, TUNE8/7,845 andCAL8/6,437were fixed before execution. Every observed stdout reconstruction stage completed, with447,840,141,210and115,866 exact old feature values, respectively. Window eligibility was not rebuilt. The code asserts exact identities, labels, timestamp endpoints and old weighted TRAIN normalization; the later fit/evaluation stdout demonstrates control passed these assertions, while the detailed in-memory result was lost.

Data flow was hash-pinned75metadata plus permitted raw member → exact window/old-feature checker →54numeric columns →TRAIN-only normalizer and one forest →paired offline scoring. Activity boundaries supported the inherited offline window construction; online transition detection and physical sensing savings were not evaluated.

S7.21. Failed representation record: Partial development observations

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

TRAIN: 91.00% to 93.00%, gain +2.00 percentage points; TUNE: 28.07% to 30.76%, gain +2.68 percentage points; CAL: 25.08% to 33.39%, gain +8.31 percentage points

Stdout reported nonworse counts TRAIN22/25, TUNE6/8 andCAL8/8. Both models answered every window with the same logical-axis cost0.15;J=error+0.15. Corrections, harms and confusion for each person were computed in memory but not preserved, so those details cannot be reconstructed from these aggregates alone.

Table S62: Partial scalar observations copied from actual stdout

Split	Frozen18	Fixed54	Gain pp	Nonworse
TRAIN	91.00%	93.00%	+2.00	22/25
TUNE	28.07%	30.76%	+2.68	6/8
CAL	25.08%	33.39%	+8.31	8/8




Figure S21: Partial actual stdout aggregates only. The missing full paired result and failed task status are unchanged; no uncertainty or confirmation claim is implied.

S7.22. Failed representation record: Serialization failure and verification gap

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

The actual scientific process ended failed at the final EXPERIMENT.json write. Tree.n_leaves produces NumPy int64; sum over tree leaves retains that type in model_sizes.baseline.total_leaves. Plain json.dumps rejected it. The complete result never reached disk. The saved enhanced model is14,416,660 bytes, SHA256 e0205233a62c4ce96eccde0107566a2648d0927b5e9f63383411631a741cdf56. No private feature matrix, raw windows, row labels or prediction arrays exist.

Preseal tests exercised tiny paired CSV/ZIP reconstruction, feature formulas, one36 window fixture fit,18 window evaluation, inert decoder boundaries and Win64 counters. They did not serialize the complete report including tree model-size metadata. Two successful tiny preseal test processes each fit one fixture classifier; SELF_CHECKS and PRE_VALUE_SEAL describe the latest process only. Neither fixture is part of actual-data performance. A postmortem manually assembled one-node Tree reproduced the exact scalar-type failure without fitting or opening either actual model.

S7.23. Failed representation record: Baseline, finite computation and resource scope

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

The original71 fullmask model was the frozen baseline, without refitting. The enhanced model used the same128 trees, maximum depth12, minimum leaf5,max_features1.0,seed6101,n_jobs1and TRAIN equal-person weighting/normalization. More input features change split opportunities and realized trees, so effective capacity is not proven identical. The112 MB71 bundle includes seven predictors and two risk families; neither that bundle size nor the older whole-fit time is directly comparable to this one new classifier.

Feature extraction has O(nL log L) FFT work withL=100plus fixed-lag/statistic work. Normalization stores O(54n) feature values. Inference requires at most128*12tree comparisons per window after features; depth12bounds each binary tree by8191nodes. Realized model node/leaf totals were not saved and are not invented in this report.

Failed process totals were CPU96.50s,wall100.84s,peak working set868.0MiB,read634.1MiB,and write13.8MiB. The actual enhanced fit printed CPU20.90625s and wall21.5s. These are absolute measured scopes, not speed or memory improvements over71. All were below the sealed limits; failure was serialization. The typed Win64 monitor and instrumentation thread are not OS isolation.

S7.24. Failed representation record: Immutable inputs and predictor contract

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

The original18columns precede x12,y12,z12new descriptors, for54total. FREEZE fixes this exact order, all estimator parameters and TRAIN-only normalization formula. Private payload fields are classifier,mean,scale;

no raw data or row labels are included. The six released CSV expected pins, raw41member allowlist and source archive hash remain in evaluation_contract and PRE_VALUE_SEAL.

S7.25. Failed representation record: Failure provenance and incomplete output

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

PARTIAL_RESULT stores the seven observed stdout JSON lines verbatim, parsed scalar copies, the immutable failure receipt and exact traceback. Capture occurred after process exit from the exec/write_stdin tool outputs; the process had not created a separate on-disk stdout log. No EXPERIMENT.json exists. All41paired confusion/corrections/harms and comparable isolated model sizes remain missing.

S7.26. Failed representation record: Resources and independent reconstruction boundary

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

TUNE and CAL were already exposed development data; TRAIN is resubstitution. FINAL10 people remained unopened here. Earlier FINAL eligibility4/10 ancillary exposure and unknown global historical exposure remain disclosed. The partial numbers satisfy the scalar CAL gain/TUNE gain/nonworse targets, but complete paired denominators/confusions are unavailable and the task remains failed. No independent FINAL gain, statistical significance, safety, deployment, MNAR identification, newest-AFA reproduction or new acquisition-algorithm claim follows.

The82 review must verify the saved model hash,54column order, TRAIN normalizer, original split/windows and old-feature values before inference. No additional classifier fit is needed.81 makes no further data reads, predictions or scientific actor invocation after its failure.

S7.27. Failed representation record: Prior work and contribution limits

Scope. Original fixed temporal/spectral representation execution: partial observations with failed durable serialization.

The fixed autocorrelation/FFT/sign descriptors are established feature engineering. This task changed a representation under matched hyperparameters and already exposed development splits. It did not introduce an acquisition algorithm, reproduce newest AFA baselines or establish physical cost, safety or scientific novelty.

Inherited source capsules preserve URLs, byte hashes and original read scopes.81 did not retrieve new network evidence. All71/75/78/79results and failures remain unchanged.

S7.28. Saved-predictor comparison: Motivation and observed development gain

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Algorithm S22. Fixed temporal and spectral representation comparison

Require: The released TRAIN, TUNE and CAL participant assignments and fixed 100-sample phone-accelerometer windows. The frozen 18-feature classifier and the single 54-feature classifier trained by producer 81, with their saved TRAIN normalizers. The prespecified development continuation criteria and exact input hashes.

Ensure: Paired participant and pooled-window accuracy, errors, confusion counts, corrections, harms and full-coverage objective values. A durable descriptive development result or an explicit failed attempt with completed journals preserved.

---

1 Verify the archive, six released CSVs and two model input files. Restore only the source ranges in the released metadata; retain every assigned participant and window.

2 Recompute six original statistics on each axis and require exact equality to all 18 released feature values.

3 Center each axis. Append autocorrelations at lags 1, 2, 4, 8, 16 and 32, three non-DC spectral power fractions, dominant power fraction, normalized spectral entropy and centered sign-change fraction. Return twelve zeros for an exactly constant axis.

4 Recompute TRAIN-only normalization with equal total weight per TRAIN participant. Check the saved normalizers and use the saved values for inference.

5 Decode the two frozen classifiers into inert state with an allowlisted NumPy/scikit-learn decoder. Predict both representations on the same windows without fitting a model.

6 For each participant, compute the paired aggregate and confusion counts and publish a flushed journal atomically before continuing. Preserve participant and pooled denominators separately.

7 Save the complete scientific report before optional model-size diagnostics. Apply the fixed continuation criteria as a description of exposed development data.

S7.29. Saved-predictor comparison: Representation, training and information access

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Each window contains 100 ordered samples from the x, y and z axes of the phone accelerometer. For each axis, the baseline computes the mean, population standard deviation, minimum, maximum, RMS and mean absolute successive difference. The extension retains these 18 values and appends 12 descriptors per axis, giving 54 values. Identity, participant number, activity label and timestamps are used to preserve and verify the inherited windows, then to score predictions. They do not enter the classifier. Because the inherited windows follow activity-defined segments, the evaluation does not test online activity-boundary detection.

Let the centered samples on one axis be u. Each autocorrelation divides its lagged inner product by the same whole-window squared norm, without a lag-specific correction. A real FFT supplies bins 1 through 50 after excluding DC. Their raw squared magnitudes are normalized without doubling. Three fractions cover bins 1 to 5, 6 to 15 and 16 to 50; the remaining spectral descriptors are the largest fraction and entropy divided by log(50). The sign-change rate compares adjacent signs under the rule $u < 0$, so both signed zeros are nonnegative. An exactly constant axis returns twelve zeros. FFT bins describe sample order and are not interpreted as hertz, cadence or physical energy.

Both saved classifiers are ExtraTrees ensembles with 128 trees, maximum depth 12, minimum leaf size 5, max_features = 1.0, Gini criterion, no bootstrap, seed 6101 and one compute thread. The original 54-feature fit used TRAIN only, with each TRAIN participant receiving equal total weight in fitting and normalization. This study verifies the saved parameters and recomputes the normalizers; it does not refit to certify the full historical training process. The expanded feature set changes available splits and realized tree structure, so equal hyperparameters do not prove equal effective capacity.

S7.30. Saved-predictor comparison: Paired evaluation on fixed windows

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

The evaluation retains all 25 TRAIN, eight TUNE and eight CAL participants, with 24,880, 7,845 and 6,437 windows respectively. Both classifiers receive the same 39,162 windows. All 704,916 original feature values match their released float64 values exactly. The 1,409,832 new descriptor values are evaluated through scalar-sum and vectorized formula forms; their maximum absolute difference is below 7.78e-16, within the declared 1e-12 absolute and relative tolerances. Recomputed baseline normalization is exact; the largest 54-feature mean and scale differences are 2.22e-16 and 5.56e-17.

The primary summaries give every participant equal weight. Pooled-window summaries add counts across windows and therefore give more weight to participants with more windows. Corrections count windows where the baseline is wrong and the 54-feature classifier is right; harms count the reverse. These are paired outcome counts, and many windows from one participant do not become independent participants.

Table S63: Participant-mean accuracy on identical windows. Gains are percentage points; TRAIN is resubstitution and TUNE/CAL are exposed development.

Split	People	Windows	18 acc. %	54 acc. %	Gain pp	Nonworse
TRAIN	25	24880	91.00	93.00	2.00	22/25
TUNE	8	7845	28.07	30.76	2.68	6/8
CAL	8	6437	25.08	33.39	8.31	8/8




Figure S22: Each line joins the two accuracies for one development participant. CAL improves for all eight; TUNE includes two regressions. This plot does not estimate sampling uncertainty.

S7.31. Saved-predictor comparison: Where corrections and residual errors occur

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Across the 6,437 CAL windows, the 54-feature classifier corrects 680 baseline mistakes and introduces 199 harms, yielding 481 additional correct predictions. The pooled accuracy gain is 7.47 percentage points, while the equally weighted participant-mean gain is 8.31 percentage points. CAL participant gains range from 2.50 to 23.04 percentage points. Two TUNE participants regress by 1.94 and 4.09 percentage points, despite a positive TUNE mean. The complete supplement retains these regressions and all 41 participant results.

Descriptive analysis of the predeclared activity codes shows that A (walking), M (kicking), C (stairs) and B (jogging) account for 85, 82, 73 and 71 net corrected CAL windows. Their combined 311 windows comprise 64.7% of the net improvement. The extension also harms some classes: O has 15 corrections and 32 harms, and I has five corrections and six harms. The largest remaining error counts are Q: 354, J: 349, G: 347, K: 341 and D: 315. Together they contribute 1,706 of the 4,366 remaining pooled errors, or 39.1%. In particular, writing (Q) has 354 errors in 355 windows, pasta (J) has 349 in 355 and drinking (K) has 341 in 355. Names follow the saved official activity mapping. These summaries diagnose this fixed comparison and do not select a new model, threshold or feature set.

Table S64: Paired pooled-window counts. The final column is a pooled accuracy gain, not the participant-mean gain.

Split	Corrections	Harms	Both wrong	Pooled gain pp
TRAIN	818	329	1500	1.97
TUNE	469	330	5246	1.77
CAL	680	199	4167	7.47

S7.32. Saved-predictor comparison: Coverage, cost and computational scope

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Every window purchases three axes at a declared accounting cost of 0.05 per axis, for a total of 0.15, and every window receives a prediction. The participant-mean objective is error fraction plus 0.15. On CAL it improves from 0.899199 to 0.816102, but remains above the zero-purchase, all-abstain reference of 0.4. In this always-predict, full-purchase regime alone, accuracy must exceed 75% to beat that reference. This threshold does not transfer to a policy with selective prediction or variable purchases. The present evidence establishes neither an acquisition-policy gain nor a favorable cost-coverage frontier.

For n windows of length L, extraction uses fixed-lag work of order nL and FFT work of order nL log L, with L fixed at 100 here. A stored 54-column matrix uses order 54n values. Each ensemble follows at most 128

paths of depth 12 per window after feature extraction. The realized baseline and 54-feature classifiers contain 232,260 and 230,034 nodes, and 116,194 and 115,081 leaves. An isolated classifier-plus-normalizer serialization compresses to 13,895,486 and 14,416,686 bytes under the same encoder settings. These are derived, noncanonical payload sizes; the 112,464,328-byte original baseline bundle also contains other predictors and risk models and is not a matched size comparator.

The single successor verification process used 100.84 CPU seconds, 112.81 wall seconds and 873.1 MiB peak working set. It read 663.7 MiB and wrote 1.60 MiB during the measured scope, below the sealed limits. This includes hashing, reconstruction, decoding, normalization, prediction and optional serialization, with zero fits. It does not isolate descriptor-extraction latency, measure physical sensing cost or establish a speed advantage.

S7.33. Saved-predictor comparison: Fixed feature and window contract

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

The six permitted CSVs are the TRAIN, TUNE and CAL feature/metadata pairs in the hash-pinned FIT_INPUT_RELEASE. Only the 41 phone-accelerometer members enumerated in the contract are opened. Metadata source_first_line and source_last_line specify each inherited range of exactly 100 contiguous rows. The verifier checks participant and activity identity on all rows in each selected range, strictly increasing ticks, exact endpoint timestamps, nonoverlap and the original window identifier. It never recalculates eligibility, drops an assigned participant, selects a different window or opens another device stream.

For axis values x_i, the original six statistics use math.fsum for population mean and variance, RMS and mean absolute successive difference. The twelve added values use the centered sequence u_i = x_i - mean(x): six whole-norm autocorrelations; spectral power fractions on bins 1 to 5, 6 to 15 and 16 to 50; maximum fraction; normalized entropy; and adjacent centered sign changes. Exactly constant axes return zeros before spectral normalization. Nonpositive or nonfinite nonconstant spectral mass fails. There is no epsilon imputation, automatic truncation or conversion to physical frequency.

For each TRAIN participant s with n_s windows, every window receives weight 1/(25 n_s). The normalizer is the weighted mean and weighted population standard deviation, with a scale at most 1e-12 replaced by one. The original enhanced fit uses the same equal-person weighting. The successor verifies saved normalizers using the fixed 1e-12 absolute and relative tolerance and uses the saved normalizers for all predictions. No TUNE or CAL value is used to fit them.

S7.34. Saved-predictor comparison: Participant-level accuracy, errors and paired changes

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

The following three tables contain every assigned participant in the original split order. Accuracy is within-participant percent, and gain is a percentage-point difference. Corrections and harms count the same participant windows. The numerical report also preserves all 18 class counts, sparse true-class/predicted-class confusion triples, both-correct, both-wrong and changed-prediction counts for every participant. These aggregates contain no row-level sensor values, features, model weights or individual window labels.

S7.35. Saved-predictor comparison: All TRAIN participants

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

TRAIN contains 25 participants and 24,880 windows. The participant-mean accuracies are 91.00% and 93.00%, with a gain of 2.00 percentage points. The count of participants who do not worsen is 22/25.

Table S65: All TRAIN participant results. The 18 and 54 columns denote the two feature representations.

ID	Windows	18 acc. %	54 acc. %	Gain pp	18 errors	54 errors	Corrected	Harmed
1612	630	96.98	97.46	0.48	19	16	5	2
1633	846	89.95	95.04	5.08	85	42	44	1
1624	630	80.00	82.22	2.22	126	112	27	13
1602	837	89.37	89.13	-0.24	89	91	31	33
1630	630	91.11	93.97	2.86	56	38	27	9
1642	1424	93.89	93.54	-0.35	87	92	18	23
1613	813	93.97	93.48	-0.49	49	53	16	20
1650	1602	91.26	92.70	1.44	140	117	48	25
1627	1541	86.63	88.77	2.14	206	173	53	20
1614	1623	95.13	96.30	1.17	79	60	40	21
1617	630	95.40	97.62	2.22	29	15	16	2

ID	Windows	18 acc. %	54 acc. %	Gain pp	18 errors	54 errors	Corrected	Harmed
1639	645	93.02	95.35	2.33	45	30	21	6
1645	1602	82.90	86.27	3.37	274	220	85	31
1608	954	93.92	95.07	1.15	58	47	18	7
1604	630	88.25	93.49	5.24	74	41	50	17
1600	630	97.30	98.10	0.79	17	12	9	4
1643	1513	91.87	92.99	1.12	123	106	35	18
1615	630	94.44	95.24	0.79	35	30	14	9
1632	630	93.81	94.44	0.63	39	35	13	9
1616	963	66.46	76.74	10.28	323	224	102	3
1637	648	96.30	97.22	0.93	24	18	14	8
1625	1136	94.89	96.21	1.32	58	43	31	16
1648	1602	89.70	92.20	2.50	165	125	56	16
1635	1276	94.83	96.00	1.18	66	51	24	9
1603	815	93.62	95.34	1.72	52	38	21	7

S7.36. Saved-predictor comparison: All TUNE participants

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

TUNE contains 8 participants and 7,845 windows. The participant-mean accuracies are 28.07% and 30.76%, with a gain of 2.68 percentage points. The count of participants who do not worsen is 6/8.

Table S66: All TUNE participant results. The 18 and 54 columns denote the two feature representations.

ID	Windows	18 acc. %	54 acc. %	Gain pp	18 errors	54 errors	Corrected	Harmed
1646	1602	20.54	18.60	-1.94	1273	1304	68	99
1631	630	32.54	34.60	2.06	425	412	36	23
1610	797	34.76	40.28	5.52	520	476	73	29
1611	630	26.67	32.38	5.71	462	426	44	8
1628	1072	26.68	34.79	8.12	786	699	121	34
1638	647	31.07	35.70	4.64	446	416	52	22
1629	1368	33.04	28.95	-4.09	916	972	42	98
1620	1099	19.29	20.75	1.46	887	871	33	17

S7.37. Saved-predictor comparison: All CAL participants

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

CAL contains 8 participants and 6,437 windows. The participant-mean accuracies are 25.08% and 33.39%, with a gain of 8.31 percentage points. The count of participants who do not worsen is 8/8.

Table S67: All CAL participant results. The 18 and 54 columns denote the two feature representations.

ID	Windows	18 acc. %	54 acc. %	Gain pp	18 errors	54 errors	Corrected	Harmed
1621	814	23.83	28.75	4.91	620	580	65	25
1640	644	34.01	38.04	4.04	425	399	55	29
1626	738	22.76	45.80	23.04	570	400	179	9
1618	596	30.70	43.79	13.09	413	335	96	18
1641	1602	22.78	25.28	2.50	1237	1197	86	46
1619	812	25.99	31.40	5.42	601	557	62	18
1609	601	19.13	25.96	6.82	486	445	65	24
1606	630	21.43	28.10	6.67	495	453	72	30

S7.38. Saved-predictor comparison: All CAL activity-code error counts

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Activity codes and class indices remain in their original predeclared order. These are pooled-window counts. A code with more windows contributes more opportunities for both corrections and errors; this table is not a participant-weighted class estimate. The descriptive concentrations in the main paper are calculated after the fixed evaluation and do not alter the classifier or continuation criteria.

Table S68: CAL pooled class counts for all 18 predeclared activity codes.

Code	Class	Windows	18 errors	54 errors	Corrected	Harmed	Net corrected
A	0	355	195	110	109	24	85

Code	Class	Windows	18 errors	54 errors	Corrected	Harmed	Net corrected
B	1	374	82	11	79	8	71
C	2	357	188	115	104	31	73
D	3	356	328	315	23	10	13
E	4	355	209	207	15	13	2
F	5	355	320	313	12	5	7
G	6	411	354	347	19	12	7
H	7	355	319	305	17	3	14
I	8	355	290	291	5	6	-1
J	9	355	349	349	4	4	0
K	10	355	344	341	9	6	3
L	11	355	283	265	19	1	18
M	12	359	199	117	94	12	82
O	13	320	240	257	15	32	-17
P	14	355	194	153	64	23	41
Q	15	355	355	354	1	0	1
R	16	355	324	282	42	0	42
S	17	355	274	234	49	9	40

S7.39. Saved-predictor comparison: Pooled counts, objective and denominator checks

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

A participant-mean accuracy gives each participant weight 1/N. A pooled accuracy divides all correct windows by all windows. No pooled count is reported as an independent participant sample. Corrections minus harms equals the difference in correct-window counts for each participant and for every pooled split. Both confusion matrices sum to the same window denominator, and their off-diagonal sums equal the reported errors.

At full coverage, each participant objective is one minus accuracy plus 0.15. The baseline-to-54 participant-mean objectives are TRAIN 0.239993 to 0.220042, TUNE 0.869281 to 0.842433 and CAL 0.899199 to 0.816102. These accounting values use the declared costs rather than measured battery, bandwidth or sensing latency. The all-abstain comparison is 0.4 with zero purchases; the CAL forecast gain does not win this objective.

Table S69: Pooled-window accounting, separate from participant means.

Split	Windows	18 correct	54 correct	Both correct	Both wrong	Changed
TRAIN	24880	22562	23051	22233	1500	1455
TUNE	7845	2130	2269	1800	5246	1937
CAL	6437	1590	2071	1391	4167	1861

S7.40. Saved-predictor comparison: Realized model size and measured inference scope

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

The original baseline file is a multi-model bundle of 112,464,328 bytes. The original enhanced file is 14,416,660 bytes with SHA256 e0205233a62c4ce96eccde0107566a2648d0927b5e9f63383411631a741cdf56. Both original identities are checked before decoding. Isolating and reserializing the decoded enhanced classifier yields 14,416,686 compressed bytes and a different hash, while preserving the evaluated estimator. This derived serialization is noncanonical and does not replace the verified original input identity.

The realized node and leaf totals below compare the extracted classifiers under the same inspection code. Feature count and available split opportunities differ. Prediction timings use already constructed feature matrices and include subtraction/division by the saved normalizer and the classifier call, with the baseline call first. They exclude raw reconstruction and descriptor extraction and have no repetition or uncertainty estimate. They cannot support a speed ranking.

Table S70: Derived isolated classifier-plus-normalizer sizes; both models contain 128 trees of realized maximum depth 12.

Features	Nodes	Leaves	Pickle bytes	Gzip bytes
18	232260	116194	48367548	13895486
54	230034	115081	47905283	14416686

Table S71: One ordered prediction pair per split, in seconds. Descriptor extraction is excluded.

Split	18 CPU	54 CPU	18 wall	54 wall
TRAIN	0.546875	0.562500	0.532000	0.578000
TUNE	0.156250	0.218750	0.204000	0.218000

Split	18 CPU	54 CPU	18 wall	54 wall
CAL	0.125000	0.140625	0.125000	0.141000

S7.41. Saved-predictor comparison: Failure provenance, corrected reuse and durable execution

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

Producer 81 performed its one actual enhanced TRAIN fit and evaluated the three splits, but its final report save failed because a NumPy int64 leaf count was not JSON serializable. Its original failed EXECUTION record, saved classifier and partial stdout record remain unchanged. Verifier 82 independently reconstructed the inputs and evaluated the two saved classifiers, but then incorrectly required a decoded estimator reserialized in isolation to have the exact original gzip bytes and SHA256. It failed before saving its complete paired report. Its original failure also remains unchanged.

Producer 83 is a separately registered successor, not a restart of either actor. It copies verifier 82 at SHA256 79c97823df0bdad699d41f692fe7e4d109473b2555f6f0f2be79b07609a50215 and makes bounded corrections for durable saves and noncanonical serialization. Reuse is explicit; the new verifier is not claimed as an independently authored scientific implementation. Each participant aggregate and confusion record is encoded with explicit NumPy conversion and nonfinite-value rejection, flushed to a temporary file and atomically renamed immediately after scoring. Every complete partition is saved before its comparison checks, and the complete numerical report is saved before optional model diagnostics. Any failure ends the single attempt while preserving completed journals; there is no automatic retry.

Before opening actual values, the corrected code completes a synthetic ZIP-to-CSV-to-54-feature-to-inert-model path using manually assembled trees and zero fits. The test persists person journals, a partition, the full scientific JSON and optional metadata. It checks unequal participant weights, macro versus pooled summaries, corrections and harms, NumPy nested counts, rejection of nonfinite JSON before opening an output file, and equal predictions despite noncanonical repickle bytes. Typed Win64 process handles, PID identity, peak working set and read/write counters pass the same path. Code, contract, sources, release identities and limits are sealed before the actual run.

The one actual verification uses zero fits, six partition-level model predictions, no network or model API, one compute thread and no original scientific actor import or replay. Its resource limits are 600 CPU seconds, 1,200 wall seconds, 2 GiB RAM, 3 GiB reads and 64 MiB writes. The watchdog is process instrumentation, not an operating-system security sandbox. The final receipt is written after the reported resource snapshot. Document assembly and packaging are separate from that measured scientific process.

S7.42. Saved-predictor comparison: Source scope, policy identity and unresolved comparisons

Scope. Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development.

The input archive, six released CSVs, fixed model files and original actor records retain their exact path, size and hash bindings in the contract, pre-value seal and numerical report. The scalar baseline results reproduce the frozen diagnostic 79, and both classifier results reproduce the saved stdout aggregates from 81 and 82 within 1e-14. This corroboration does not prove the absence of unrecorded historical activity. This producer opens no raw FINAL body or FINAL CSV payload; the prior four-of-ten eligibility aggregate and unknown global exposure remain.

The coordinator separately disclosed a metadata-search incident in ROOT_METADATA_SEARCH_EXPOSURE.json. A faulty exclusion pattern included private cached JSON in the search set, including a FINAL cache path. The output was truncated, so an exhaustive match audit is unavailable and absence of cached FINAL JSON exposure cannot be asserted. That JSON-only search did not read FINAL feature/metadata CSVs or raw ZIP member bodies, invoke fitting/inference, or select a threshold, model or policy. The producer does not reopen private paths to reconstruct that incident. Official activity names here come only from the exact nonprivate CLOCK_AUDIT.json mapping.

The inherited references retain their URLs, response/captured-text hashes and original reading scopes. The WISDM capsule covers official dataset metadata; SEFA and Learning-To-Measure cover the cited primary-paper sections; the tree-based batch reinforcement-learning capsule covers a landing-page abstract and bibliography. They do not supply new representation-literature coverage or a direct external baseline reproduction. No new retrieval was made for this successor study.

Current policy/checker/builder identities are recorded in SOURCE_AUDIT.json. The method checker SHA256 is 5ab3e12480b8bf43f3716f24c9b1f54304231276b8ce1a4bd58f73ceef7d4dfc; the actual document builder SHA256 is b89b3ee7abdb802d4f14a161a139513d41b80c2cd56e24541025a8b8839c7fad. The configured legacy builder pin is 54bd2e21af5a1e153b837074d24a60758b5ac0c89acd1043d82427ca8989b99e. These differ, so this separately registered standalone task does not claim canonical-wave method-intake approval. Six author-supplied method areas link concrete source evidence and manuscript anchors; distinct review, final document rendering, official lifecycle settlement and Git delivery belong to the coordinator.

Unresolved scientific work is a matched-capacity/compute control, acquisition-policy comparison at matched cost and coverage, and a documented independent cohort for confirmation. This study does not resolve PI/MNAR behavior, physical costs, population safety, statistical significance, external state-of-the-art comparisons or scientific novelty.

S7.43. Shared paid-mask ET family: Procedure and method

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

Algorithm S23. Shared paid-mask family with a frozen fullmask

Require: Exact six released TRAIN/TUNE/CAL CSV identities,41 allowed phone-acceleration members and frozen18/54 model byte hashes. Original100-row window metadata and frozen TRAIN normalizers;128-tree/depth12/leaf5/seed6101 classifier settings.

Ensure: Six new proper-mask classifiers plus unchanged frozen fullmask and TRAIN prior, all using canonical paid columns. Private row-aligned two-family predictions/confidence; durable participant/mask aggregates and complete descriptive result, or a preserved failed attempt.

1. Verify Root release and every source/input pin; hash the opaque archive and two exact frozen model files under process counters.
2. Reconstruct exactly the released41people/39162windows; require every old18 value and complete54 feature hash to match83; persist private row/window/label snapshots.
3. Decode only hash-verified allowlisted model globals into inert source-named states. Drop risk/value states; retain frozen old classifiers1..7 and frozen improved fullmask.
4. Recompute TRAIN equal-person normalizers and prior, verify saved hashes/tolerances, and use frozen saved normalizers. No TUNE/CAL fitting.
5. At mask0 use the TRAIN prior. At mask7 reuse the original54 classifier; require exact complete83 aggregate reproduction.
6. For mask1..6, select sorted original columns from old18 then new36 layout, fit one TRAIN classifier, serialize it privately and atomically journal the completed fit.
7. For each fixed mask/partition/family compute one posterior pass. Persist class/max-probability/top-two-margin with exact row identity before optional metadata; atomically journal each participant aggregate and partition.
8. Write the complete finite scientific JSON before optional model metadata and documents. Preserve every harm/no_gain and explicit resource failure; never retry or choose a policy/threshold.

S7.44. Shared paid-mask ET family: Information access and architecture

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

This standalone complement completes predictors only. Acquisition/value fitting and participant-exclusion proofs belong to separate registered work. Every future policy family must share these exact predictors and terminal rights; this execution provides no policy-performance comparison.

The feature layout is the original 18 columns (six per axis), followed by 36 added columns (12 per axis). Axis x owns columns 0–5 and 18–29; y owns columns 6–11 and 30–41; z owns columns 12–17 and 42–53. A mask takes their sorted union. The full mask, columns 0–53, therefore preserves the frozen classifier's column order. Contiguous 18-column axis slicing would leak unpaid axes and is explicitly rejected by synthetic tests.

Labels, subject identity, times and activity-defined window boundaries validate inherited curation and score outcomes; they never enter classifier features. Synthetic unpaid-axis perturbations, including nonfinite unpurchased inputs at the selection boundary, leave observed paid data and posterior outputs unchanged. The offline activity-homogeneous windows do not establish an online segmentation method.

S7.45. Shared paid-mask ET family: Cohort, fitting and evaluation

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

TRAIN contains 25 participants and 24,880 windows; TUNE contains 8 and 7,845; CAL contains 8 and 6,437. Participant assignment, original row/window order, source-member ranges, all labels and timestamps are verified without re-running eligibility or modifying partitions. No FINAL CSV or raw member body is opened by this producer.

Weights are w_i=1/(25*n_person) on TRAIN only. The saved 54-feature TRAIN means and scales normalize all masks; recomputed statistics must agree within 1e-12 and hashes from verification83 must match. Each proper-mask forest uses 128 trees, depth 12, minimum leaf size 5, max_features=1.0, seed 6101 and n_jobs=1. The original 18-feature baseline retains its original saved normalizer/models. Empty mask uses the equal-person TRAIN prior.

For each participant, J=mistake fraction+popcount(mask)/20; the same logical cost cancels in each paired family comparison. Coverage is one for every fixed mask. We report equal-person accuracy/J, pooled counts, all 18-class confusions and classwise corrections/harms. Participant is the descriptive averaging unit; no window-level inference or significance claim is made.

S7.46. Shared paid-mask ET family: Complete mask results

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

The tables list every prespecified mask/split. Positive and negative gains, nonworse people, corrections and harms are retained. No all-mask winner is chosen and no gain is described as acquisition success.

Table S72: All prespecified masks and partitions: equal-person means.

Mask	Split	People	Windows	Original %	Improved %	Gain (pp)
None	TRAIN	25	24,880	6.15	6.15	+0.00
None	TUNE	8	7,845	5.40	5.40	+0.00
None	CAL	8	6,437	5.53	5.53	+0.00
X	TRAIN	25	24,880	66.73	74.82	+8.09
X	TUNE	8	7,845	23.27	28.80	+5.53
X	CAL	8	6,437	20.30	27.49	+7.19
Y	TRAIN	25	24,880	68.34	75.59	+7.25
Y	TUNE	8	7,845	25.25	30.11	+4.86
Y	CAL	8	6,437	25.20	29.54	+4.34
XY	TRAIN	25	24,880	87.65	89.91	+2.26
XY	TUNE	8	7,845	25.31	31.41	+6.10
XY	CAL	8	6,437	28.80	34.43	+5.62
Z	TRAIN	25	24,880	66.21	75.69	+9.49
Z	TUNE	8	7,845	18.71	24.96	+6.25
Z	CAL	8	6,437	21.36	26.14	+4.77
XZ	TRAIN	25	24,880	87.31	90.44	+3.13
XZ	TUNE	8	7,845	23.12	27.51	+4.39
XZ	CAL	8	6,437	23.40	29.60	+6.20
YZ	TRAIN	25	24,880	87.48	89.80	+2.32
YZ	TUNE	8	7,845	27.82	30.94	+3.12
YZ	CAL	8	6,437	21.96	28.83	+6.87
XYZ	TRAIN	25	24,880	91.00	93.00	+2.00
XYZ	TUNE	8	7,845	28.07	30.76	+2.68
XYZ	CAL	8	6,437	25.08	33.39	+8.31

Table S73: Same paired windows: pooled accuracy and paired changes; pooled rows are not independent people.

Mask	Split	Original %	Improved %	Corrections	Harms	Nonworse people
None	TRAIN	6.18	6.18	0	0	25
None	TUNE	5.40	5.40	0	0	8
None	CAL	5.51	5.51	0	0	8
X	TRAIN	65.23	73.45	2903	858	25
X	TUNE	22.80	28.36	760	324	7
X	CAL	20.57	26.89	632	225	8

Mask	Split	Original %	Improved %	Corrections	Harms	Nonworse people
Y	TRAIN	67.45	74.27	2688	990	25
Y	TUNE	24.35	28.71	656	314	8
Y	CAL	24.78	28.40	651	418	5
XY	TRAIN	86.83	89.00	1088	549	23
XY	TUNE	24.32	30.59	748	256	8
XY	CAL	28.32	33.52	625	290	7
Z	TRAIN	65.33	74.84	3273	907	25
Z	TUNE	18.32	24.38	858	382	8
Z	CAL	21.41	25.48	545	283	7
XZ	TRAIN	86.53	89.84	1304	480	25
XZ	TUNE	22.51	26.60	516	195	7
XZ	CAL	23.71	29.41	524	157	8
YZ	TRAIN	86.84	89.12	1116	549	23
YZ	TUNE	27.53	29.66	397	230	6
YZ	CAL	20.82	26.97	611	215	8
XYZ	TRAIN	90.68	92.65	818	329	22
XYZ	TUNE	27.15	28.92	469	330	6
XYZ	CAL	24.70	32.17	680	199	8




Figure S23: Matched paid-mask prediction on the exposed TUNE and CAL groups. Hollow circles use the original statistics; blue squares include the fixed temporal and spectral descriptors. Every point weights the eight participants equally. XYZ reuses the frozen full-mask model. These are prediction accuracies, not acquisition-policy gains or independent-test estimates.

S7.47. Shared paid-mask ET family: Complexity and measured scope

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

For N windows of fixed L = 100 samples, fixed-lag descriptors cost O(NL), per-axis FFTs O(NL log L), and feature storage O(54N). At inference a forest follows at most 128 paths of depth 12 per window. Canonical mask selection stores 18 or 36 inputs for new proper masks. A full 18-class posterior is transient; only class and two confidence floats per row/family persist.

Six fits run sequentially; each model is saved and its participant aggregates journaled before it is dropped. The large baseline bundle is decoded once, with risk/value states discarded. Same tree/depth/leaf settings leave split opportunities and realized tree structures different, so equal effective capacity is not established.

NUMERICAL_RESULTS records scope-matched per-family posterior inference times for every mask/split and fit receipts include serialization. These are one ordered execution without repeats/warmup/order balance and cannot establish a speed advantage. EXECUTION provides full process CPU/wall/peak working set/read/write counts through report generation; instrumentation is not OS isolation.

S7.48. Shared paid-mask ET family: Reproducibility and release

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

PRE_VALUE_SEAL binds owned code, meaningful synthetic results, the exact Root-pinned83 sources, six allowed CSV hashes,41 allowed member names and the two original frozen model hashes/byte sizes before values. Root's exact accepted release hash is retained; opaque archive hashing is counted but is not a FINAL-body read.

Raw command/log/exit records and SOURCE_AUDIT accompany the result. Private features, labels, identity metadata, models and predictions/confidence are represented only by custody paths/hash/byte counts in nonprivate artifacts. Original upstream bytes are unchanged; own-source hashes and post-attempt execution evidence are frozen separately.

S7.49. Shared paid-mask ET family: Feature formulas and numerical edge cases

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

For each axis, the old six statistics are population mean/std,min,max,rms and mean absolute successive difference, using the inherited math.fsum implementation and exact released decimal values. New descriptors center with fsum/100, compute autocorrelations at1,2,4,8,16,32 using one full centered sum-of-squares denominator, and rFFT non-DC power fractions for bins1..5,6..15,16..50, dominant fraction and normalized entropy.

The twelfth new descriptor is the centered sign-change fraction over99 adjacent pairs. Signed zero is nonnegative. Exactly constant axes, including nonbinary decimal0.1, yield twelve zeros; otherwise zero centered energy also yields zeros. Nonfinite raw inputs fail, nonpositive/nonfinite spectral mass fails, and near-zero normalization scales<=1e-12 become1. Fsum and vectorized forms agree within 1e-12. Frequency is in sample-index bins; no Hz or energy interpretation is made.

S7.50. Shared paid-mask ET family: Participant paired outcomes

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

Cells give improved-minus-old accuracy gain followed by corrections/harms. Every original participant is retained. Complete class counts, sparse confusions and transition summaries reside in NUMERICAL_RESULTS and atomic journals.

Table S74: All 41 participants, masks0..3; these are the same 41 people in both tables. Gains are percentage points; C/H denotes corrections/harms.

Split	Person	Windows	None pp (C/H)	X pp (C/H)	Y pp (C/H)	XY pp (C/H)
TRAIN	1612	630	+0.00 (0/0)	+5.24 (42/9)	+7.78 (60/11)	+0.16 (9/8)
TRAIN	1633	846	+0.00 (0/0)	+11.23 (134/39)	+9.10 (94/17)	+4.37 (47/10)
TRAIN	1624	630	+0.00 (0/0)	+5.24 (46/13)	+10.48 (85/19)	+1.59 (24/14)
TRAIN	1602	837	+0.00 (0/0)	+8.48 (98/27)	+3.46 (79/50)	-1.79 (31/46)
TRAIN	1630	630	+0.00 (0/0)	+11.43 (92/20)	+8.25 (102/50)	+4.44 (40/12)
TRAIN	1642	1,424	+0.00 (0/0)	+8.15 (168/52)	+13.76 (236/40)	+1.69 (45/21)
TRAIN	1613	813	+0.00 (0/0)	+6.03 (99/50)	+6.27 (82/31)	+1.85 (32/17)
TRAIN	1650	1,602	+0.00 (0/0)	+8.36 (192/58)	+5.24 (143/59)	+2.37 (72/34)
TRAIN	1627	1,541	+0.00 (0/0)	+8.57 (182/50)	+8.24 (191/64)	+2.86 (88/44)
TRAIN	1614	1,623	+0.00 (0/0)	+13.92 (299/73)	+8.19 (173/40)	+1.66 (64/37)
TRAIN	1617	630	+0.00 (0/0)	+13.49 (97/12)	+9.52 (77/17)	+3.33 (23/2)
TRAIN	1639	645	+0.00 (0/0)	+8.53 (67/12)	+16.28 (117/12)	+0.93 (17/11)
TRAIN	1645	1,602	+0.00 (0/0)	+8.24 (208/76)	+6.74 (198/90)	-1.44 (71/94)
TRAIN	1608	954	+0.00 (0/0)	+6.81 (102/37)	+4.51 (67/24)	+1.47 (33/19)
TRAIN	1604	630	+0.00 (0/0)	+3.81 (45/21)	+5.24 (68/35)	+4.76 (43/13)
TRAIN	1600	630	+0.00 (0/0)	+4.76 (57/27)	+6.51 (52/11)	+1.27 (12/4)
TRAIN	1643	1,513	+0.00 (0/0)	+6.21 (139/45)	+1.65 (103/78)	+1.65 (46/21)
TRAIN	1615	630	+0.00 (0/0)	+10.95 (98/29)	+7.14 (68/23)	+2.38 (27/12)
TRAIN	1632	630	+0.00 (0/0)	+10.63 (85/18)	+3.17 (49/29)	+0.16 (18/17)
TRAIN	1616	963	+0.00 (0/0)	+9.87 (121/26)	+7.79 (118/43)	+11.21 (128/20)
TRAIN	1637	648	+0.00 (0/0)	+5.40 (53/18)	+16.36 (127/21)	+3.09 (22/2)

Split	Person	Windows	None pp (C/H)	X pp (C/H)	Y pp (C/H)	XY pp (C/H)
TRAIN	1625	1,136	+0.00 (0/0)	+7.22 (109/27)	+3.52 (95/55)	+2.55 (50/21)
TRAIN	1648	1,602	+0.00 (0/0)	+9.05 (191/46)	+0.50 (77/69)	+2.75 (67/23)
TRAIN	1635	1,276	+0.00 (0/0)	+4.08 (107/55)	+6.90 (158/70)	+1.25 (42/26)
TRAIN	1603	815	+0.00 (0/0)	+6.63 (72/18)	+4.54 (69/32)	+1.96 (37/21)
TUNE	1646	1,602	+0.00 (0/0)	+6.24 (163/63)	+0.56 (123/114)	+7.30 (178/61)
TUNE	1631	630	+0.00 (0/0)	+5.24 (57/24)	+5.71 (54/18)	+6.19 (57/18)
TUNE	1610	797	+0.00 (0/0)	+7.65 (101/40)	+7.03 (99/43)	+7.53 (102/42)
TUNE	1611	630	+0.00 (0/0)	+1.90 (35/23)	+4.44 (40/12)	+4.44 (47/19)
TUNE	1628	1,072	+0.00 (0/0)	+9.98 (130/23)	+10.17 (129/20)	+10.35 (127/16)
TUNE	1638	647	+0.00 (0/0)	+8.04 (82/30)	+4.64 (57/27)	+3.09 (63/43)
TUNE	1629	1,368	+0.00 (0/0)	+5.26 (124/52)	+1.61 (74/52)	+3.07 (78/36)
TUNE	1620	1,099	+0.00 (0/0)	-0.09 (68/69)	+4.73 (80/28)	+6.82 (96/21)
CAL	1621	814	+0.00 (0/0)	+4.55 (70/33)	+4.05 (94/61)	+4.79 (78/39)
CAL	1640	644	+0.00 (0/0)	+5.43 (70/35)	+4.35 (63/35)	-0.47 (56/59)
CAL	1626	738	+0.00 (0/0)	+12.47 (101/9)	+15.31 (141/28)	+19.38 (152/9)
CAL	1618	596	+0.00 (0/0)	+14.60 (103/16)	-1.68 (28/38)	+5.87 (77/42)
CAL	1641	1,602	+0.00 (0/0)	+2.12 (95/61)	-0.81 (97/110)	+2.12 (80/46)
CAL	1619	812	+0.00 (0/0)	+4.68 (54/16)	-0.99 (86/94)	+2.34 (64/45)
CAL	1609	601	+0.00 (0/0)	+7.32 (81/37)	+4.33 (57/31)	+3.33 (57/37)
CAL	1606	630	+0.00 (0/0)	+6.35 (58/18)	+10.16 (85/21)	+7.62 (61/13)

Table S75: All 41 participants, masks4..7; these are the same 41 people in both tables. Gains are percentage points; C/H denotes corrections/harms.

Split	Person	Windows	Z pp (C/H)	XZ pp (C/H)	YZ pp (C/H)	XYZ pp (C/H)
TRAIN	1612	630	+4.29 (48/21)	+0.95 (10/4)	+2.22 (17/3)	+0.48 (5/2)
TRAIN	1633	846	+7.80 (115/49)	+5.56 (73/26)	+5.08 (54/11)	+5.08 (44/1)
TRAIN	1624	630	+12.22 (107/30)	+2.54 (27/11)	+2.38 (32/17)	+2.22 (27/13)
TRAIN	1602	837	+4.66 (63/24)	+3.46 (60/31)	+1.79 (38/23)	-0.24 (31/33)
TRAIN	1630	630	+7.14 (66/21)	+2.70 (28/11)	+2.38 (38/23)	+2.86 (27/9)
TRAIN	1642	1,424	+8.43 (190/70)	+0.91 (53/40)	-0.84 (41/53)	-0.35 (18/23)
TRAIN	1613	813	+8.49 (95/26)	+1.23 (22/12)	+2.09 (34/17)	-0.49 (16/20)
TRAIN	1650	1,602	+7.43 (176/57)	+2.06 (58/25)	+1.94 (74/43)	+1.44 (48/25)
TRAIN	1627	1,541	+10.45 (220/59)	+4.15 (87/23)	+1.82 (69/41)	+2.14 (53/20)
TRAIN	1614	1,623	+16.88 (346/72)	+9.61 (193/37)	+2.28 (57/20)	+1.17 (40/21)
TRAIN	1617	630	+13.65 (91/5)	+4.13 (28/2)	+1.75 (14/3)	+2.22 (16/2)
TRAIN	1639	645	+15.04 (111/14)	+2.02 (22/9)	+3.26 (27/6)	+2.33 (21/6)
TRAIN	1645	1,602	+9.80 (215/58)	+4.24 (95/27)	+3.75 (105/45)	+3.37 (85/31)
TRAIN	1608	954	+4.72 (83/38)	+0.94 (31/22)	-0.63 (23/29)	+1.15 (18/7)
TRAIN	1604	630	+11.75 (100/26)	+2.70 (41/24)	+1.43 (29/20)	+5.24 (50/17)
TRAIN	1600	630	+7.30 (68/22)	+2.86 (23/5)	+2.06 (16/3)	+0.79 (9/4)
TRAIN	1643	1,513	+5.42 (122/40)	+2.18 (54/21)	+2.45 (59/22)	+1.12 (35/18)
TRAIN	1615	630	+10.79 (77/9)	+6.51 (53/12)	+2.70 (24/7)	+0.79 (14/9)
TRAIN	1632	630	+11.90 (94/19)	+3.97 (36/11)	+2.38 (31/16)	+0.63 (13/9)
TRAIN	1616	963	+5.30 (122/71)	+3.84 (67/30)	+8.31 (98/18)	+10.28 (102/3)
TRAIN	1637	648	+10.65 (78/9)	+1.70 (20/9)	+2.31 (24/9)	+0.93 (14/8)
TRAIN	1625	1,136	+11.00 (157/32)	+1.32 (34/19)	+2.02 (43/20)	+1.32 (31/16)
TRAIN	1648	1,602	+10.42 (226/59)	+6.05 (129/32)	+2.93 (91/44)	+2.50 (56/16)
TRAIN	1635	1,276	+11.05 (191/50)	+0.24 (31/28)	+0.94 (45/33)	+1.18 (24/9)
TRAIN	1603	815	+10.55 (112/26)	+2.45 (29/9)	+1.23 (33/23)	+1.72 (21/7)
TUNE	1646	1,602	+3.12 (103/53)	+1.12 (60/42)	-0.44 (69/76)	-1.94 (68/99)
TUNE	1631	630	+3.33 (56/35)	+4.60 (43/14)	+6.51 (49/8)	+2.06 (36/23)
TUNE	1610	797	+7.03 (98/42)	+9.79 (106/28)	+6.90 (86/31)	+5.52 (73/29)
TUNE	1611	630	+8.25 (63/11)	+4.13 (35/9)	+4.60 (37/8)	+5.71 (44/8)
TUNE	1628	1,072	+10.17 (177/68)	+7.93 (95/10)	+0.75 (32/24)	+8.12 (121/34)
TUNE	1638	647	+6.18 (65/25)	+2.78 (53/35)	+7.42 (65/17)	+4.64 (52/22)
TUNE	1629	1,368	+6.43 (206/118)	+5.56 (96/20)	+0.44 (38/32)	-4.09 (42/98)
TUNE	1620	1,099	+5.46 (90/30)	-0.82 (28/37)	-1.18 (21/34)	+1.46 (33/17)

Split	Person	Windows	Z pp (C/H)	XZ pp (C/H)	YZ pp (C/H)	XYZ pp (C/H)
CAL	1621	814	+4.91 (81/41)	+1.11 (49/40)	+4.42 (63/27)	+4.91 (65/25)
CAL	1640	644	+5.12 (54/21)	+7.92 (68/17)	+2.64 (37/20)	+4.04 (55/29)
CAL	1626	738	+10.03 (102/28)	+13.01 (107/11)	+20.33 (163/13)	+23.04 (179/9)
CAL	1618	596	+7.72 (75/29)	+6.54 (56/17)	+7.89 (70/23)	+13.09 (96/18)
CAL	1641	1,602	-0.37 (79/85)	+3.31 (80/27)	+1.37 (88/66)	+2.50 (86/46)
CAL	1619	812	+4.19 (76/42)	+4.80 (45/6)	+6.03 (64/15)	+5.42 (62/18)
CAL	1609	601	+1.83 (33/22)	+4.49 (45/18)	+7.65 (59/13)	+6.82 (65/24)
CAL	1606	630	+4.76 (45/15)	+8.41 (74/21)	+4.60 (67/38)	+6.67 (72/30)




Figure S24: Every CAL participant and nonempty paid mask. Cell values are paired accuracy changes in percentage points. Both improvements and regressions remain visible; the shared symmetric color scale represents magnitude, not statistical significance.

S7.51. Shared paid-mask ET family: Private prediction and confidence schema

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

Each mask/partition NPZ contains baseline and enhanced class arrays(dtype int16), row_index(int64), baseline/enhanced maximum probability(float64) and top-two margin(float64). The numerical report records exact uncompressed C-order array hashes, NPZ hashes and the original feature/label/person/window snapshot hash. Class order is0..17 mapped to ABCDEFGHIJKLMOPQRS.

Class and confidence summaries use the same posterior computation. Maximum probability is the largest class posterior; margin is largest minus second largest. Empty mask broadcasts the TRAIN prior. No full 18-class probability tensor is stored and no posterior feature is used to select or fit a risk policy here.

S7.52. Shared paid-mask ET family: Durability and failure semantics

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

Fit models and fit receipts are atomically persisted before later masks; private predictions and participant/mask aggregates precede optional metadata. Finite JSON is fully encoded before opening the target, fsynced and atomically renamed. Nested NumPy scalars are converted and the complete scientific schema is round-tripped in synthetic tests.

Any identity, normalization, decoder, fullmask reproduction, resource or serialization failure ends the sole actual attempt. Completed journals and failure receipts remain. No cap increase, actual dry run, automatic retry, original actor import/replay or interrupted model-call retransmission is allowed.

S7.53. Shared paid-mask ET family: Method-review areas

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

Algorithm, architecture, complexity, evaluation and baselines have explicit paper/supplement anchors and source/execution evidence. Related work is partial: local lineage is available, new primary-literature comparison and external-method runs were out of scope. These author-supplied evidence mappings are not an independent review or a completed canonical method gate.

S7.54. Shared paid-mask ET family: Resource and capacity evidence

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

MODEL_METADATA reports actual input dimensions/tree/node/leaf/depth counts for all seven nonempty improved masks. PRIVATE_CUSTODY reports actual serialized model/snapshot/prediction sizes; original mixed112MB baseline bundle is not a matched isolated-classifier size comparator.

The pre-value plan reserved CPU900s,wall1200s,peakRAM2GiB,read2GiB,write256MiB with one compute thread and six actual fits. Process counters include scientific imports and all meaningful reporting; the external terminal exit receipt and later hash freeze are outside that bounded process. Repeated latency and physical sensing costs were not measured.

S7.55. Shared paid-mask ET family: Complete predictor-family procedure

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

The same original procedure and single-run boundary apply to all six newly fitted masks.

S7.56. Shared paid-mask ET family: Launcher observation boundary

Scope. Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask.

The internal scientific receipt and durable results report six completed fits within every cap. The PowerShell launcher did not return the child exit code (null); its exact OS start time was also unobserved. The original finalizer rejected the missing exit-zero evidence. A separately identified metadata-only successor preserved that failure and produced the report without replaying science. Internal success and an observed exit-zero status remain different claims.

S8. Participant-excluded risk construction and matched fitted acquisition

Whole-pipeline outer exclusion closes a specified computational own-person label path; it does not remove within-training fitted-minimum optimism. The early WISDM pipeline, coverage diagnostics and later 1,008-risk-fit comparison retain their own predictor, feature, terminal, split and support contracts. They are not pooled into one performance experiment.

S8.1. Original fitted acquisition: Question, scope and contribution

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

Algorithm S24. Finite-horizon fitted continuation loss with equal bought-submask rights
Require: Subject-disjoint TRAIN/TUNE/CAL; separate unreleased FINAL; exactly 18 numeric features in three paid groups. Shared mask classifiers; wrong 1/query 0.05/abstain 0.4; budgets 3(primary), 1, 2; depths 3, 5; fixed menus.
Ensure: Hash-frozen predictors, terminal regressors, continuation models, policy/config and CAL selections. Once-only per-person FINAL losses/actions/cost/coverage, paired changes and assumption-qualified uncertainty after explicit Root release.

1. Verify exact Root release, distinct completed custody/review references, source schema/license/split, every path/byte/hash, assigned versus eligible IDs, paired row_index/window_id and numeric-only extraction.
2. Fit subject-equal normalization, empty prior and seven ExtraTrees 128/depth 12/leaf 5 classifiers on TRAIN only.
3. For each value depth 3 or 5 and bought mask, regress TUNE prediction errors of every bought submask using only currently observed numeric features; compare with abstention 0.4.
4. Back up from zero remaining queries. Regress query cost 0.05 plus fitted successor value on current observed features; take STOP or minimum legal query. Restrict the same operation for fixed order; use terminal successors only for replanned myopic; restrict first query for reference-first.
5. On CAL, select each prespecified family by subject-macro J, then fewer queries, greater coverage and lexical ID; no additional tuning/refitting. Include common static fallback.
6. Serialize and hash every model/policy/config plus CAL choices. Wait for a separate exact FINAL release. Reload unchanged bytes, evaluate once, expose every denominator/failure and compare with frozen matched controls.
7. Report equality with static/order/myopic as no extra acquisition benefit. Do not transfer fitted-Q or baseline-regret theory into a safety or novelty theorem.

S8.2. Original fitted acquisition: Source custody and revised window protocol

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

The 51-person immutable SHA split assigns 25 TRAIN, 8 TUNE, 8 CAL and 10 FINAL people. Assignment is distinct from eligible contribution. A purchased axis reveals exactly six fixed statistics: mean, population standard deviation, min, max, RMS, and mean absolute successive difference.

The original 5-second variant is preserved separately. Before predictive outcomes, Root observed only 17/7/5/4 contributing people across its 25/8/8/10 assignments; absolute-clock scale rules caused exclusions. Root then commissioned a separate 100 sample fixed-window relative-gap protocol with the same 18 features and original subject assignment. Its exact completed custody/review/schema/license/files must be bound by a later Root release. Prior FINAL eligibility aggregate exposure remains permanent provenance; an untainted confirmatory holdout is not claimed.

Label homogeneity is offline curation using ground truth. These are already recorded channels and logical feature-access charges, not physically independent sensors, measured energy/latency savings, continuous deployment or transition-detection performance.

S8.3. Original fitted acquisition: Prediction, terminal actions and rights

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

TRAIN alone fits subject-equal normalization, the weighted majority empty-mask prior and seven mask-specific ExtraTrees classifiers:128 trees, max_depth 12, min_samples_leaf 5, max_features 1.0, seed 6101, n_jobs 1. No subject identifier, label, time or window ID enters a predictor or policy.

At bought mask m, every family may reuse all shared predictions from submasks s contained in m. For each s, a TUNE conditional-error regressor sees only current observed features X_m. STOP selects the minimum

predicted error or abstention 0.4; abstention wins exact ties, then the smallest submask. This extends the old current-mask-only protocol equally for all controls. No unbought reference prediction is free.

S8.4. Original fitted acquisition: Fitted continuation and matched restrictions

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

The value menu is two fixed depths 3, 5 with 32 ExtraTrees, min_samples_leaf 40, max_features 1.0, seed 7101, n_jobs 1. At terminal depth, fitted conditional errors define stop value. At each legal query j, regress 0.05 plus successor value on current X_m, then minimize over STOP and legal queries. The finite backward pass is a plug-in point estimator; TUNE is reused in fitted backups without cross-fitting or a population error certificate.

Adaptive planning branches over all unbought axes. Fixed-order planning uses the identical estimator but only the next declared axis. Myopic planning scores only immediate terminal successors and replans after purchases. Reference-first allows lawful early STOP, otherwise buys one prelisted first axis and then uses the same adaptive continuation. No paired-residual or robust uncertainty-set method is silently included.

S8.5. Original fitted acquisition: Controls, selectors and primary acceptance

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

At budget 3, static has 16 configurations(8 subsets×2 capacities), fixed-order has 32(all 16 partial/full/empty orders×2), adaptive 18(2 plus 16 staticfallbacks), myopic 18, and reference 22(3 firstaxes×2 plus 16 fallbacks). Budgets 1, 2 use the same declared menus subject to budget and report aliases/equivalent traces. Every family is under 32; candidate counts and expressive powers are explicit rather than described as identical.

CAL selects by equally weighted observed-person objective J, rounded 12 decimals, then fewer queries, greater coverage, and lexical ID. The primary comparison is selected adaptive minus selected fixed-order STOP at budget 3. A positive cohort decision additionally requires strict mean gains over selected static and myopic, all 10 eligible FINAL people, and upper paired 95%t(df 9)interval below zero against order. Remaining comparisons and budgets are prespecified secondary; no FINAL menu/threshold/selection/refit changes are allowed.

S8.6. Original fitted acquisition: Architecture, failure and resource boundaries

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

The release gate checks a Root-pinned release SHA, own code seal, distinct completed custody/review references, exact source schema/license/split, stage-specific whitelist and every file path/size/hash. The two CSVs must have identical row_index/window_id pairs and counts. Exactly 18 numeric columns survive extraction; all audit columns stay outside learning inputs.

Fit and selection run once underCPU 600 s/wall 1200 s/RAM 2 GiB/read 512 MiB/write 256 MiB; FINAL once underCPU 180 s/wall 600 s/read 128 MiB/write 64 MiB. One compute thread is fixed. Windows CPU, peak working set and process read/write counters include process import work; a 0.1 second instrumentation watchdog is monitoring, not OS security containment. Resource, hash, denominator or parser failures are preserved without automatic retry.




Figure S25: Frozen information flow and gates; source and code hashes are in FIGURE_SOURCES.json. This diagram contains no application outcome.

S8.7. Original fitted acquisition: Controlled implementation validation

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.




Figure S26: Synthetic-only mechanism fixture, sourced to two exact test assertions. The fixed order and multistep curves coincide; no application result is mixed into this figure.

S8.8. Original fitted acquisition: Completed fitting, CAL collapse and unopened FINAL

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

Actual fitting and selection succeeded once: CPU 49.078 s, wall 51.203 s, peak RAM 589934592 bytes. All 15 CAL selections across budgets 1/2/3 and 5 families return zero queries, zero coverage, and J 0.4 on 8 CAL people. This is CAL collapse, not an empirical FINAL no_gain result.

The frozen compressed model is 112464328 bytes. The completed synthetic resource profile observed 35251885 nonmodel read bytes; adding the actual model projects 147716213 bytes before actual source CSV parsing/ hash reads, above the unchanged FINAL limit 134217728 bytes. This is an observed resource-risk projection, not a failed FINAL execution. Root kept FINAL unreleased: no code change, budget relaxation, refit or FINAL attempt occurred.

A Root-approved stdlib-only diagnostic read only six thin author files. Frozen code makes the empty-mask terminal and first query estimates independent of X, and every selected policy has zero CAL queries and predictions. Thus the 15 selected policies are conditionally the same STOP/abstain function on every valid nonempty input matrix. Stored-model constants were not loaded or verified; the certificate is conditional on the recorded frozen model identity and faithful serialization, and remains for distinct independent 77 review. Nonselected menu policies are not covered by this conclusion.

FINAL remains unopened and unexecuted. Its 10 assigned people are preserved; the prespecified FINAL primary gate is not passed. No 10 person FINAL outcome, empirical improvement or external validation is reported.

The original conservative K 32/n 10 gate remains unchanged: margin 1.307309577967498 exceeds the maximum possible paired improvement 1.15, so its upper bound cannot be negative. The new K 1 primary cohort statistic and paired t interval do not replace that failed safety gate. No deployment-safety certificate is issued.

Table S76: Actual CAL only: budget3 frozen selections; no FINAL outcomes

Family	Frozen candidate	Macro J	Purchased axes	Coverage	CAL people	CAL windows
adaptive	adaptive.d3	0.4	0.0	0.0	8	6437
myopic	myopic.d3	0.4	0.0	0.0	8	6437
order	order.d3.0	0.4	0.0	0.0	8	6437
reference	reference.d3.a0	0.4	0.0	0.0	8	6437
static	static.d3.m0	0.4	0.0	0.0	8	6437




Figure S27: Actual CAL collapse from the exact CAL_SELECTION.json bytes. All 15 selected policies over the 3 budgets have zero queries and coverage; the chart shows budget 3. FINAL remains unopened.

S8.9. Original fitted acquisition: Immutable protocol and data audit

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

evaluation_contract.json and PRE_VALUE_SEAL.json fix code, versions, parameters, menus, ties, weights, endpoints and limits before any author values. Later Root releases bind completed custody and a different completed review plus exact file hashes/schema/license/split. The source HOLD files stay immutable; the new Root receipt alone opens the cooperative gate.

CSV ID columns are audit metadata. Every features row_index/window_id pair must equal its metadata pair; row_index is zero-based and sequential, window_id is nonempty and unique. The exact 18 feature columns are parsed separately. A feature/metadata semantic linkage additionally relies on the pinned construction and independent custody review; hashes do not independently prove sensor truth.

S8.10. Original fitted acquisition: Executable recursion and terminal semantics

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

For each mask, multioutput squared-error trees estimate errors of all bought-submask predictors. Observed feature dimensions are sliced before every fit/predict call. At empty mask, weighted constants replace zero-dimensional tree fitting. Predicted error is clipped to[0, 1];abstention is 0.4. Query estimates are compared only at the current bought mask.

Backward targets use fitted successor minima on TUNE and can be optimistic under limited support or distribution shift. CAL is independent of TUNE fitting within the protocol but global dataset exposure is unknown. There is no assertion that a point minimum is a robust lower bound. All queried axes are charged, including a reference prefix; all-axis terminals pay 0.15.

S8.11. Original fitted acquisition: Menus, fallbacks and equivalence

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

All 16 orders include lengths 0, 1, 2, 3. Truncation at smaller budgets creates declared aliases; every nominal configuration and unique trace count is retained. Adaptive, myopic and reference families include every eligible static configuration as an explicit CAL-selectable fallback; none receives an unbought reference forecast.

Every actual FINAL candidate is summarized per person and paired against the frozen order winner. The selected adaptive route is also paired against selected static, myopic and reference controls. Both-covered corrections/harms, coverage changes, changed predictions, masks and routes are separate quantities. Equality or collapse to an all-axis/reference/fixed-order route carries no additional adaptive-choice claim.

S8.12. Original fitted acquisition: Uncertainty, selection and missing people

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

Equal weighting over observed eligible people is used in fitting and evaluation. Missing assigned people are not reassigned, imputed or treated as successful predictions. Primary acceptance requires 10 observed people; otherwise the study remains a limited cohort result regardless of its point estimate.

The primary paired interval is conditional on frozen CAL selections and the stated subject sampling assumptions. It does not cover data-dependent preprocessing history, global public dataset reuse or unobserved deployment conditions. The Hoeffding upper bound uses losses in[0, 1.15] and paired differences in[-1.15, 1.15]. Windows and random tree seeds are never independent people.

S8.13. Original fitted acquisition: Resources, serialization and failure receipt

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

The compressed model contains frozen predictors, value regressors, policy nodes and CAL selections only. TUNE training matrices/targets and ephemeral fitted backup arrays are removed before serialization. Hash-pinned local model bytes are loaded before FINAL values; no downloaded checkpoints or external models are used.

Every actual stage creates a fresh write-once private attempt directory. Exception/resource-limit receipts survive failures; there is no automatic restart or new directory fallback. The 0.1 second watchdog is sampled process monitoring, not a hard OS memory sandbox. Bulk paired traces, target labels and model weights remain local/private and outside canonical artifacts/Git.

S8.14. Original fitted acquisition: Current outcome and reproducibility

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

CAL_SELECTION.json in REPORT_ASSETS.zip retains every candidate and every CAL person: errors, queries, abstention/coverage and eligible denominators. FINAL row-level outcomes and all-candidate FINAL comparisons do not exist and are not invented. Root plans a separate task to decompose predictor error, abstention risk and acquisition cost on TRAIN/TUNE/CAL; this author task is not restarted.

S8.15. Original fitted acquisition: Preserved historical negatives

Scope. WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls.

The cached route 65 study selected the same strong static S for all principal matched paired selectors, with zero additional gain. Its time laws were two people, and all 10 MHEALTH people had prior exposure. The four-stream WISDM study remains blocked by unproved common clock alignment and was never substituted or called executed.

The axes 69 metadata inventory failure and axes 73 five-second exclusions are different historical records. The later 100 sample construction is a separate protocol revision before predictive results, with its previous eligibility exposure disclosed. None of these failures is erased or counted as a successful new application benchmark.

S8.16. Coverage diagnosis: Question and failure scope

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

This is a substantive development diagnosis of frozen ProbeFlow71, not a new acquisition method or a performance win. We separate raw forecast limitations, learned terminal-risk behavior, paid query cost and the absence of a nonzero-coverage constraint.

Full-mask raw subject-macro accuracy is TRAIN 0.910007, TUNE 0.280719, CAL 0.250801. TRAIN is optimistic classifier resubstitution; TUNE is held out for the forecast but in-sample for fitted risks; CAL was already used for selection.

S8.17. Coverage diagnosis: Procedure and trust boundary

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Algorithm S25. One-run frozen-model cause diagnosis
Require: Hash-pinned known local model; exact six authorized TRAIN/TUNE/CAL paired CSVs; frozen71 policy/ CAL contract Prespecified masks0..7, risk depths3/5, thresholds0.2/0.3/0.4/0.5/0.6/1.0 and process budgets
Ensure: Per-person forecast/terminal confusions, risk calibration, paid objective and threshold aggregates Explicit failed/blocked receipt on identity, decoding or resource failure; no retry/refit/FINAL

1. Verify pre-value code/protocol/source seal; validate exact model identity and decode only named NumPy/sklearn containers with inert author holders.
2. Validate all six file bytes/hashes, paired row/window IDs, original assigned people, activity code map,100sample count and exact18numeric feature allowlist.
3. Compute each frozen shared predictor forecast once for every mask and authorized split. Keep subject/label/time metadata out of predictor inputs.
4. Independently evaluate every stored terminal risk output for all bought-submask forecasts. Choose lowest risk, abstain at exact0.4 tie, then lowest submask.
5. Aggregate each person's forecast and terminal confusion, coverage, mistakes, estimated risk and same paid loss; average people equally.
6. Apply fixed descriptive thresholds without selecting policies. Reproduce all16 CAL static scores and decompose J-.4=.05*k+E-.4*C.
7. Interpret selected empty-root constants and record between-person error versus observed duration ticks as exploratory association.
8. Return bounded measured diagnostics and a prospective successor recommendation; leave all prior failures, frozen policies and FINAL unopened.

S8.18. Coverage diagnosis: What the forecast can currently support

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Every observed assigned person and mask is represented in DIAGNOSTIC.json, with sparse true/predicted class confusion triples, class counts, paid objective and person error distribution. A weak forecast is a limitation of this frozen representation-plus-classifier combination; these data do not isolate feature representation from estimator capacity or establish an irreducible error floor.

Table S77: Frozen full-mask forecast accuracy, equal weight per person

Split	People	Windows	Accuracy	Exposure
TRAIN	25	24,880	91.00%	Training resubstitution
TUNE	8	7,845	28.07%	Risk-model training

Split	People	Windows	Accuracy	Exposure
CAL	8	6,437	25.08%	Reused development

S8.19. Coverage diagnosis: Terminal risks and smoothing

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

depth 3 fullmask C=0.068228, J=0.541434, mean best risk=0.707458, forecast error before abstention=0.751499; depth 5 fullmask C=0.081526, J=0.547893, mean best risk=0.692388, forecast error before abstention=0.757536

Always answering with the full-mask raw forecast costs J=0.869281 on TUNE and 0.899199 on CAL. The lowest raw-mask CAL J is 0.798027. Of96 fixed depth/mask/threshold diagnostics, 0 have CAL J<.4. The frozen forecast-plus-representation has a substantive cost-adjusted utility shortfall; simply forcing more coverage or increasing these fixed thresholds does not establish a useful acquisition method. A stronger forecast/representation study is the first scientific priority, with a common nonzero-coverage contract to expose infeasibility. Risk calibration remains a separate secondary issue.

Risk trees use32 ExtraTrees regressors, maximum depth 3or5 and minimum leaf size 40. Actual leaf counts and realized depths are recorded. Shallow, pooled multioutput risk regressions can smooth heterogeneous errors, but this diagnosis does not ablate smoothing or prove it caused the entire collapse. We compare estimated and observed risks per submask, calibration bins and per-person errors before and after abstention. TUNE residuals are in-sample, so agreement there is not calibration validation.

Prespecified thresholds expose the attainable frozen risk/coverage/cost tradeoff without changing forecasts or fitting risks. Any lower J at a threshold would remain an exposed development counterfactual, not a FINAL policy selection or a new method.

On reused CAL, depth 3 minimum risk averages 0.707458 while the selected forecast is wrong at rate 0.751499 before abstention (bias -0.044041). At depth 5 the corresponding values are 0.692388 and 0.757536 (bias -0.065147). Thus the mean CAL risk is optimistic, not uniformly too conservative. TUNE biases are +0.033198 and +0.077118, but TUNE supplied the risk targets. The very large positive TRAIN bias is measured against optimistic classifier resubstitution and cannot validate risk overconservatism on new people. Local calibration errors can remain despite a negative overall bias; no risk-estimator causal ablation was performed.

S8.20. Coverage diagnosis: Cost accounting and selected roots

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Among14 paid static candidates, maximum CAL coverage is 0.081526; 14 have positive coverage. The lowest-J positive-coverage candidate is static.d5.m2 with J=0.443654488, C=0.057821369; its excess is paid 0.050000000 + covered error 0.016783035 - abstention credit 0.023128548 = 0.043654488.

All 15 selected initial decisions independently read STOP/A from stored constants. Empty forecast risk is 0.945967265; selected first-query constants span 0.437171560 to 0.449095552. Empty-mask regressions do not depend on X, so this is a conditional algebraic statement about the exact frozen objects, not a FINAL observation.

For fixed paid k, J-.4=.05*k+E-.4*C, with E the covered mistake fraction over all windows. Even perfect covered answers require C>.125*k to beat always abstain. The floors are12.5%,25%and37.5%for1,2and3axes. These are elementary accounting identities. Nonselected menus are not globally described as collapsed: all static candidates remain visible.

$$J - 0.4 = 0.05k + E - 0.4C$$

Here k is the fixed number of paid axes, E is the fraction of all windows with an incorrect covered prediction, and C is coverage.

$$J < 0.4 \Longrightarrow C > 0.125k$$

This is a necessary condition, even when every covered prediction is correct. It is elementary cost accounting, not a new safety theorem.

S8.21. Coverage diagnosis: Architecture, complexity and duration association

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Data flow is sealed custody → exact18feature-only predictor input → cached eight-mask forecasts → two frozen terminal-risk families → person-macro aggregation → thin source-bound report. No metadata enters prediction; the diagnostic alone reads labels and times after predictions to score them.

For n windows, inference is linear in n times the fixed forest/tree/path and mask counts. The working arrays are O(n times18 plus risk outputs), while frozen model storage dominates a fixed memory component. No general learned acquisition-training complexity or physical runtime saving is established.

Between-person median duration_ticks and full-mask error rank correlations are exploratory. Fixed 100-sample windows need not share physical duration. Class mix, person/device behavior and other split differences confound associations; ticks are never converted to physical seconds or interpreted as a causal sampling-rate effect.




Figure S28: Frozen forecast/coverage diagnostic, panel A printed at readable width. Source-bound development results: frozen raw forecast error; CAL estimated risk versus observed pre-abstention forecast error on the same axis; full-mask CAL fixed-threshold loss/coverage. Labels and source pointers are in FIGURE_SOURCES.json.




Figure S29: Frozen forecast/coverage diagnostic, panel B printed at readable width. Source-bound development results: frozen raw forecast error; CAL estimated risk versus observed pre-abstention forecast error on the same axis; full-mask CAL fixed-threshold loss/coverage. Labels and source pointers are in FIGURE_SOURCES.json.




Figure S30: Frozen forecast/coverage diagnostic, panel C printed at readable width. Source-bound development results: frozen raw forecast error; CAL estimated risk versus observed pre-abstention forecast error on the same axis; full-mask CAL fixed-threshold loss/coverage. Labels and source pointers are in FIGURE_SOURCES.json.

S8.22. Coverage diagnosis: Exact identifiers and arithmetic

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Model gzip bytes112464328, SHA256062b44045b6d26967ee7847ef32bcbad01bfe1c1905f4fb510d8015bcfd2bfdf; original fit freeze5b83971ebd5a046d29d59e0bfd79cdae715075a46006ba8642e0775f512c8092. PRE_VALUE_SEAL.json fixes every diagnostic code/protocol/thin source hash before the model or six CSVs are read.

The source release remains authorized_task_id71. Task79 plus Root specifically authorizes same-six-file diagnosis; it is not a fabricated new release or FINAL authority. Input bytes, hashes, original split and paired identities are checked during the sole run.

This successful diagnosis is a separately registered controlled recovery of failed78. That immutable attempt matched model identity but rejected research.Predictor before six CSVs were opened. Original71 source859 explicitly sets both container modules to research; this task maps only those source-proven containers to inert holders and retains an explicit installed NumPy/sklearn allowlist. The thin schema maps custody CALIBRATION to released directory CAL. Before the new seal, the full manually assembled constant-leaf/inert-container/CSV path and typed Win64 current-process HANDLE were checked without fitting or actual model/CSV reads. No78 actor was restarted.

S8.23. Coverage diagnosis: Metric denominators and output schema

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Raw person metrics have coverage1 and cost.05*popcount(mask). Terminal metrics include all paid axes even when the chosen forecast uses a smaller submask or abstains. Zero covered denominators are null for conditional error and never reported as zero error accuracy.

Sparse confusion triples are true class index,predicted class index,count; absent entries are zero. Codes map in the exact orderABCDEFGHIJKLMOPQRS. Person class-count and confusion aggregates contain no per-window identifiers, features or labels. Subject-macro means differ from pooled window means when people have unequal window counts.

S8.24. Coverage diagnosis: Risk calibration and threshold diagnostics

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

Each bought mask has one risk output for every predictor submask. All outputs are clipped to[0,1] identically to frozen71. The winning raw forecast uses the smallest risk and lowest submask tie. Exact0.4ties abstain. We report risk means, Brier residuals, ten fixed calibration bins and person-macro exposure.

The before-abstention minimum-risk forecast may differ from the current-mask forecast. Consequently current-mask raw accuracy, best-risk forecast error and terminal selective error are separate quantities. Fixed threshold values0.2,0.3,0.4,0.5,0.6,1.0were written before this run; risk=1ties still abstain at threshold1.

Table S78: Full-mask learned terminal risk versus observed forecast error before abstention; equal weight per person

Split	Depth	Risk	Observed error	Risk minus error	Coverage	J
TRAIN	3	0.714626	0.173590	0.541036	0.072579	0.523281
TRAIN	5	0.703739	0.179332	0.524406	0.079742	0.521446
TUNE	3	0.707579	0.674381	0.033198	0.072949	0.525139
TUNE	5	0.686506	0.609387	0.077118	0.099710	0.513119
CAL	3	0.707458	0.751499	-0.044041	0.068228	0.541434
CAL	5	0.692388	0.757536	-0.065147	0.081526	0.547893

S8.25. Coverage diagnosis: All16static CAL scores

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

All16depth 3/5-mask scores match stored71 CAL macro J, coverage, errors and query counts to1e-12. Mask0has no purchase;14nonzero masks are charged in full. Every static excess independently satisfies paid+covered_error-.4*coverage, including candidates with tiny positive coverage. Repeated appearance at different budgets does not create independent evidence.

Table S79: Independent frozen CAL static accounting

Candidate	J	C	Paid	Covered error	-.4C	J-.4
static.d3.m0	0.400000	0.000000	0.000000	0.000000	-0.000000	0.000000
static.d3.m1	0.445097	0.038675	0.050000	0.010567	-0.015470	0.045097
static.d3.m2	0.444424	0.055335	0.050000	0.016558	-0.022134	0.044424
static.d3.m3	0.491456	0.068016	0.100000	0.018663	-0.027207	0.091456
static.d3.m4	0.448172	0.012959	0.050000	0.003356	-0.005184	0.048172
static.d3.m5	0.494838	0.038172	0.100000	0.010106	-0.015269	0.094838
static.d3.m6	0.495621	0.056394	0.100000	0.018178	-0.022557	0.095621
static.d3.m7	0.541434	0.068228	0.150000	0.018725	-0.027291	0.141434
static.d5.m0	0.400000	0.000000	0.000000	0.000000	-0.000000	0.000000
static.d5.m1	0.445324	0.043954	0.050000	0.012905	-0.017582	0.045324
static.d5.m2	0.443654	0.057821	0.050000	0.016783	-0.023129	0.043654
static.d5.m3	0.492336	0.066893	0.100000	0.019093	-0.026757	0.092336
static.d5.m4	0.446539	0.018400	0.050000	0.003899	-0.007360	0.046539
static.d5.m5	0.495850	0.039921	0.100000	0.011819	-0.015968	0.095850
static.d5.m6	0.497270	0.060315	0.100000	0.021396	-0.024126	0.097270
static.d5.m7	0.547893	0.081526	0.150000	0.030503	-0.032611	0.147893

S8.26. Coverage diagnosis: Exposure, duration and resources

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

TRAIN25/24880windows, TUNE8/7845 and CAL8/6437are reused as declared. None is renamed FINAL. Person distributions, duration summaries and rank correlations are in DIAGNOSTIC.json; pooled41person correlation mixes exposure/split groups and is descriptive only.

Execution counters are process-wide and include imports, model identity hashing/loading and input handling. A0.1smonitor checks CPU180s, wall600s, RAM2GiB, read512MiB, write32MiB. The final snapshot precedes its small receipt; imported libraries are installed dependencies, no dependency is added. There is exactly one real inference run and no automatic retry.

Exploratory Spearman correlations of person median duration_ticks with raw full-mask error are TRAIN -0.107735 (n=25), TUNE -0.576959 (n=8), CAL +0.317168 (n=8), and pooled +0.023771 (n=41). The pooled statistic mixes exposure and split groups. The signs do not identify physical sampling rate, a time unit or a cause of forecast failure.

S8.27. Coverage diagnosis: Six method areas and unresolved work

Scope. Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention.

The algorithm, architecture and bounded complexity are documented as a diagnostic. Evaluation and baselines remain partial as acquisition-performance evidence: no FINAL or successor comparison was run. Related work is inherited primary-source context without contemporary method reproduction. Exact method pointers/ evidence hashes are carried in DOCUMENT.method_areas.

The former5second eligibility shortfall, no_gain/safety failures, resource risk and all previous files remain immutable upstream. REPORT_ASSETS.zip carries an inactive skill candidate, progress/check evidence and literal render smoke outputs; no active skill or scientific policy pointer changes.

S8.28. Participant exclusion: Procedure and dependency condition

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Let D_i contain all windows of participant i, and fix common predictors C trained only on the separate TRAIN25 group. For an outer TUNE participant u, a permissible learned decision is a function of C, fixed design/randomness, D excluding u, and u's currently paid features. Holding these inputs fixed, mutating Y_u must not change any learned risk/Q/STOP object or action. This is conditional computational noninterference; actions can still be statistically associated with Y_u through legitimate features. Excluding labels cannot repair prior data-dependent curation, feature design or selection exposure.

Naive terminal OOF only says the terminal estimate for i excludes i. If Q for u is fitted on j not equal u using globally generated terminal-OOF targets, the terminal model for j generally includes u. The path Y_u -> terminal model excluding j -> target_j -> Q excluding u -> action_u remains. A graph path denotes possible dependence, not proof of actual numerical influence; the explicit witness below establishes influence. Sufficiently removing every such ancestor path is stronger than merely dropping row u from the last regression.

The exact three-person synthetic witness has constant features, fixed paid forecast0 and empty prior forecast1. Other participants v,w have label0, so outer STOP at empty is abstention.4. When Y_u changes0 to1, direct paid terminal OOF_u stays0. Globally reused child-OOF scores for v,w change0 to.4, and Q_u changes.05 to.45: query becomes abstain. Rebuilding each child inside outer S={v,w}, with its own target person excluded, gives Q_u=.05 in both worlds. Corrected realized loss is1.05 in the label1 world whereas the leaky rule obtains.4; exclusion is not a promised numerical improvement.

Algorithm S26. Participant-excluded sequential value construction

Require: Fixed TRAIN25-normalized common mask predictors; paid-axis feature mapping; allowed TUNE participant set S and forbidden outer set E. Policy family, current mask m, remaining budget/order, depth, query .05, error1, abstention .4 and fixed RNG. Construction mode: outer-local plug-in OR full recursive targets; never mix their caches or claims.

Ensure: A terminal/Q/route artifact keyed by the complete S and state, or an explicit insufficient-participant/ resource failure. For a fixed candidate and outer person u: realized loss/coverage/purchases from routing u with u excluded, separately from fitted minima.

---

1 Verify common predictor/source/snapshot identities and require S disjoint E. At every online state expose only the purchased feature columns.
2 Fit multi-output terminal error regressors for all predictor submasks s subset m using only S; the empty-state regressor is a participant-weighted constant. Compare clipped risks and .4; abstain then lowest submask wins ties.
3 Process states backward. For each legal query, identify the exact family-specific child target state and routing state. Full and fixed-order use their continuation; myopic uses immediate terminal loss and replans.
4 Outer-local mode: construct every child using the same S and fit in-sample plug-in Q targets. Full recursive mode: the target for participant i in S uses a child built from S minus i, recursively; no global leave-i-out table is read.
5 Regress .05 plus child fitted value on current paid features with equal total weight per allowed participant. Cache by construction,S,mask,family,horizon/order,depth,RNG and common-predictor identity; canonical terminal child states may share an artifact.
6 For outer assessment of u set S=TUNE minus u and rebuild all terminal/Q/STOP objects inside that scope. Run the frozen candidate on u, score actual predictions/abstentions/queries, and never report a fitted minimum as its observed risk.
7 Keep all8 deployment artifacts and CAL selection separate from the eight smaller-cohort outer runs. Apply fixed useful-coverage and loss rules; retain infeasibility, ties, regressions and failed fits.




Figure S31: A synthetic label-feedback witness and an inherited exclusion boundary. Arrows denote computational dependencies, not a causal graph. Numerical values are from the three-participant counterexample, not observed acquisition performance.

S8.29. Participant exclusion: Two constructions and their proof boundary

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Two distinct honest constructions are useful. Outer-local evaluation trains the entire fixed learner on S=TUNE excluding u, including its in-sample Bellman minima, and then measures realized routing loss on u. It blocks u-label feedback but preserves internal plug-in/minimum bias. Full recursive targets additionally generate each training participant i's child value from a builder on S excluding i, with that exclusion inherited at every lower stage. This stronger construction prevents the tested self-target path but does not make all downstream action estimates unbiased. These are different learners; neither OOF number is the all8-person final-policy risk.

For the full construction, terminal regressors R[S,m,s] use errors of the fixed predictor s for i in S, with s subset m. Define T[S,m](x)=min(.4, all clipped R[S,m,s](x_m)). For each legal edge to child b, form q_target_i=.05+V[S excluding i,b](x_i at child mask), fit Q[S,m,a,b] on X_i,m for i in S, and set V to the minimum of T and these fitted Q values. Outer-local mode instead uses V[S,b] for every training row. Abstention at each child gives fitted V in[0,.4] and query targets in[.05,.45]; actual policy losses remain separately scored and may exceed these intervals.

Induction on remaining horizon proves the stated exclusion property: terminal artifacts read only S and fixed C; a recursive child reads a subset S excluding i; each Q regressor and its target selection therefore read only S and C. Minima, clipping and tie breaking introduce no excluded labels. Thus u absent from S stays absent from all learned descendants. The cache identity must include the complete S, predictor identity, construction, state/family/horizon/order, depth and RNG. Reusing a global table keyed only by target person

or mask invalidates the induction. Normalization, weights, calibration, stopping, model selection and eligibility decisions must obey the same boundary or be explicitly fixed/exposed.

Honest OOF assessment measures the actual loss of a fixed training procedure on a group excluded from all its fitting. Under iid/exchangeable participants, fixed design and adequate integrability, its expectation targets the learner trained on n-1 participants, not the n-person deployed learner; folds are correlated. Here previous TUNE/CAL design exposure prevents a fresh independent experiment claim. Selecting the best candidate on the same OOF outcomes adds selection optimism unless the selector is nested or uses separate data. We therefore report fixed-candidate TUNE diagnostics and label CAL selection as exposed development.

S8.30. Participant exclusion: Minimum optimism and safety limits

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Even unbiased per-action risk estimates do not make their minimum unbiased: E[min_a qhat_a] <= min_a E[qhat_a]. In a separate exact synthetic example both actions have true risk.38, with equiprobable estimated pairs(.26,.50) and(.50,.26). Each estimate has mean.38 but the fitted minimum is.26. Adding one query gives estimated.31 and actual expected.43, above abstention.4. This does not depend on the held-out label entering training. Neither cross-fitting, this algebra nor the cited abstracts establish shared-world/PI/MNAR identification, high-probability regret, individual or population safety.

S8.31. Participant exclusion: Matched information, controls and decision rule

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

The common54-column matrix keeps old x6,y6,z6 first, then new x12,y12,z12. Consequently x uses indices0..5 and18..29, y6..11 and30..41, z12..17 and42..53. A contiguous18-column-per-axis slice would leak unpurchased-axis features. Allmask columns must be sorted0..53 to preserve the existing fullmask model order. Normalization is TRAIN-only and predictors are shared identically across policies; the empty forecast is the TRAIN weighted majority prior.

For a participant-weighted cohort write C for macro coverage, E for macro covered mistakes divided by all windows, and K for macro mean queries. J-.4=.05K+E-.4C exactly. For C>0, beating abstention requires C(.4-E/C)>.05K, hence necessarily C>.125K. Zero coverage cannot strictly improve. For fixed three-query full coverage, correctness must exceed75%; that bound does not transfer unchanged to selective/variable-query policies. A synthetic C=.5,E=.1,K=1 example gives J=.35; it is not a ProbeFlow observation.

The proposed primary budget is3, with1/2 descriptive. Query cost.05, wrong1 and abstain.4 stay fixed. Enumerate every feasible static subset, every distinct no-repeat ordered prefix, myopic replanning, full continuation and zero-query abstention; fullmask always-predict is an additional budget3 anchor. Use depths3/5 with32 trees, leaf40, seed7101, one thread for all value families. Runtime initializes best to STOP, scans legal axes x,y,z and replaces only when a query score is smaller by more than1e-12; STOP and then the earlier axis win ties within that tolerance. Terminal ties remain exact, abstain then smallest submask. Static fallbacks belong equally to adaptive, myopic and order menus. Base candidate totals including anchors are21/39/54, not extra independent samples.

Select each family on exposed CAL by J rounded12 decimals, then fewer mean queries, then greater coverage, then stable ID. A separate useful-coverage comparison requires macro coverage at least.50 and every participant at least.25; if any required family is infeasible, no useful-coverage gain passes. Require strictly lower macro J than selected feasible static, order and myopic at budget3; preserve every per-person difference, harm and routing equality. Report the unconstrained optimum separately. Coverage/cost differences remain visible; this protocol does not assert identical realized cost and coverage merely because budgets match.

$$J - 0.4 = 0.05K + E - 0.4C$$

K is the participant-mean query count, C coverage, and E covered mistakes divided by all windows. Every term uses equal participant weight.

$$J < 0.4 \Longrightarrow C > 0.125K$$

The necessary coverage condition follows from E being nonnegative; it is not a sufficient gain or safety condition.

S8.32. Participant exclusion: Computational tradeoff

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Exact structural enumeration with shared allowed-set/state caches gives two-depth tree-regressor fits: outer-local all8 deployment 56, plus eight complete outer fits 504; full nested deployment 1008, nested deployment plus outer fits 2996. At32 trees each these are1792,16128,32256 and95872 trees respectively. These are prospective artifact counts, not executed fits or timing estimates. The full nested count already shares overlapping exclusion subsets; multiplying the deployment count by9 would overcount. Independent per-family refits would also overcount.

Per depth the outer-local all8 bundle contains7 terminal-tree regressions,21 query-tree regressions and22 weighted constants, hence28 tree fits; two depths and nine allowed sets give504. Full nested plus outer fits has553 terminal-tree and945 query-tree regressions per depth, plus9 terminal constants and189 query constants, hence2996 tree fits across depths. Its deepest terminal training set has4 people; deployment-only has5. Outer-local retains7 for outer runs. The constant-mean synthetic builder verifies exclusion structure, not adequacy of tree risk estimates on these small groups.

Reconstruct the41 released participants once from their exact allowlisted source ranges and reuse a frozen private54 matrix. The39,162 windows contain11,748,600 raw axis-sample values; a contiguous float64 feature matrix alone occupies16,917,984 bytes. FFT work is117,486 axis transforms of length100, before classifier/value fitting and target inference. Snapshot hashes, labels, identity, timestamp/line linkage and the old18 exact equality must be preserved. Realized nodes/bytes, target prediction passes, CPU/wall/peakRAM/IO and failures are additional costs; counts alone cannot certify the proposed7200CPU-second/2GiB limit.

Table S80: Structural tree-regressor fits only; synthetic enumeration, no actual learned-model execution.

Construction	All8 deploy fits	Deploy + outer8 fits	Trees for latter	Deepest people
Outer-local plug-in	56	504	16128	7
Full nested targets	1008	2996	95872	4

S8.33. Participant exclusion: Reuse boundary and required future snapshots

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Read-only verified source objects are pinned in SOURCE_HASHES.json with AST segment hashes/line ranges. From83 verify.py, feature_window(118), reconstruct(170) and normalize(200) define the existing representation and identity checks. Reuse their formulas and source-range verification under a separate authorized runner; do not import/restart the old actor.

From71 research.py, weights(118), submasks(114) and summary(427) provide existing weighting, information and scoring patterns. cols(110) is18-feature-specific and must be replaced with the tested noncontiguous54 mapping. Predictor(203) hardcodes18 and needs explicit reviewed adaptation or consumption of87 common predictors. ValueFit(233) uses in-sample child minima; its constructor/terminal/q/full/order/myopic logic is a starting pattern, not a recursively cross-fitted implementation. Never rename its current outputs as OOF.

Candidate-menu/trace/result formats may be adapted in a new owned successor. Metadata guards, participant exclusions, row-target lineage and the complete allowed-set cache must be explicit. Canonical artifacts contain aggregates and hashes; local private snapshots retain row errors/features without printing them. All recorded features are observed offline; this does not identify deployment behavior under purchased-feature failure or missing-not-at-random acquisition.

A separately predeclared estimator ablation may append paid-submask classifier maximum probability and top-two margin to observed descriptors, equally for every policy family. Such derived confidence requires no unpurchased feature, but is not a population calibration guarantee. Root asked87 to preserve small confidence caches if within its existing scope; this author has not read or accepted those caches. Exact risk/Q feature choice, selection and added fit counts belong to a separate successor contract. The present504/2996 counts describe one feature choice and are not silently doubled for an ablation.

S8.34. Participant exclusion: Bounded primary-source context

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

Root supplied two official landing-page abstract notes: Kallus/Uehara2020 describes cross-fold sequential off-policy evaluation; Wang/Qi/Wong2024 studies fitted-Q evaluation of a fixed policy under specified conditions. This author read only the pinned notes, performed no new retrieval, and reproduced neither proof nor experiment. Their scope does not establish the present learner's guarantees or novelty. Related-work and real application baselines remain partial until full method/version evidence and an implemented matched comparison exist.

S8.35. Participant exclusion: Failure and acceptance boundary

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

The numerical/source83 and independent aggregate/source/render84 records are read-only context. Failures81/82 remain failures. TUNE8 and CAL8 are exposed development, TRAIN25 is resubstitution, and all41 are not41 independent final-test subjects. Earlier Root private-JSON search exposure and uncertain historical FINAL exposure remain disclosed; this author read no private/FINAL payload. No independent cohort, actual acquisition result, representation capacity control, physical saving, novelty/SOTA or safety certificate is produced.

The standard-library tests exercise9 named checks: actual label-feedback witness,32 paired label-mutation evaluations across16 other-label configurations at horizon3, paid-submask tie rules, the54 mapping, minimum optimism, participant macro arithmetic, coverage selection/infeasibility, independently counted budget1 fit cases, and invalid inputs. These are implementation checks and controlled arithmetic; counts/configurations are not a scientific benchmark or an independent sample size.

No software/core/Studio integration was changed. Repository-wide forge/pilot/demo/benchmark/browser tests were not run because the scope is isolated theory/synthetic support and contains no app/runtime change. Existing build_documents.validate was called only to check source-document shape; Root owns final rendering and independent review. Current actual builder hash differs from configured legacy pin, so canonical-wave validator acceptance is not claimed.

S8.36. Participant exclusion: Complete construction procedure

Scope. Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark.

The procedure below is the same construction used in the main text; neither mode certifies population safety.

S8.37. Matched risk acquisition: Problem and matched protocol

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

We use the previously frozen WISDM phone-accelerometer windows: 25 TRAIN participants (24,880 windows), eight TUNE participants (7,845) and eight CAL participants (6,437). Each window contains 100 samples. The three logical acquisition units are x, y and z from one accelerometer, not three independently priced physical sensors. The same 54-feature predictors and TRAIN normalizers are reused by every policy.

A policy may predict with any already purchased submask, abstain, or buy one remaining axis. Wrong predictions cost 1, each purchase costs 0.05, and abstention costs 0.4. Budgets are 1–3, with budget 3 primary. The prespecified useful-coverage criterion is at least 50% mean participant coverage and at least 25% for every participant.

$$J = 0.05K + E + 0.4(1 - C)$$

All quantities first average within each participant and then equally across participants. E counts errors among covered windows but divides by all windows.

$$J - 0.4 = 0.05K + E - 0.4C$$

Lower prediction error alone does not establish acquisition value. Purchases and abstention enter the same realized objective.

S8.38. Matched risk acquisition: Algorithm and leakage boundary

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

The raw variant observes the purchased feature columns. The raw_conf variant also observes the maximum class probability and top-two probability margin of every already available submask predictor. It cannot use confidence from an unpurchased mask. The empty-state regressions are participant-weighted constants.

Every outer learner excludes its evaluation participant from all terminal-risk fits, continuation fits, targets, weights and caches. This closes the computational held-out-label path identified by the preceding counterexample. Within the permitted training participants, child targets still use fitted minima; outer exclusion does not remove that optimism.

Algorithm S27. Participant-excluded matched acquisition

Require: Frozen TRAIN classifiers and normalizers; paid-mask features and predictions; TUNE participant set S. Feature variant, tree depth, budget, fixed costs, equal-participant weights and deterministic tie rules.
Ensure: Every fixed candidate on TRAIN, participant-excluded TUNE and exposed CAL; realized losses, coverage, purchases and failure receipts.

1. Verify the frozen source, input and resource contract and the two completed independent reviews. Reuse all classifiers without refitting or inference.
2. For each feature variant and depth, build one learner on all eight TUNE participants and eight fresh learners excluding one participant each. Reuse only the TRAIN normalizer and fixed classifiers across these learners.
3. At each paid mask, regress the errors of every available submask predictor on the current paid features. Optionally add only the already available submask confidence summaries. At the empty mask, use weighted constants. Compare abstention at cost 0.4; exact ties favor abstention and then the smallest submask.
4. Construct full and ordered continuation targets backward as 0.05 plus the fitted child minimum. Myopic targets use the immediate terminal value and replan after a purchase. Share only identical canonical query targets within one complete allowed-participant set. Clip query scores to [0.05, 0.45]. These are in-sample plug-in minima.
5. Evaluate each state-local score table once, counting unrealized branches as computation. Route from the current paid state; STOP wins within 1e-12, followed by x, y and z.
6. Score realized predictions, abstentions and purchases for every participant and candidate. Save each completed fold before optional reporting. Keep TRAIN diagnostics, seven-person TUNE assessments and all-eight CAL results separate.
7. Select on exposed CAL by objective rounded to 12 decimals, fewer purchases, greater coverage and stable identifier. Apply the prespecified coverage gate. Require a genuine full-policy selection and strict improvement over all three strong families and every feasible always-predict static anchor; retain failures, ties and fallback selections.

S8.39. Matched risk acquisition: Primary result at useful coverage

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Neither prespecified risk-feature variant established useful-coverage acquisition superiority.

The table reports the best feasible member of each family on CAL. A family may select a shared static fallback. Such a selection is not a sequential-policy gain. The winner must also strictly beat the best feasible always-predict fixed-mask anchor, which is scored separately without another fit.


Table S81: Primary result at useful coverage

Risk inputs	Family	Selected candidate	J ↓	C (%)	K	Min C (%)
Raw features	Fixed subset	Infeasible	—	—	—	—
Raw features	Fixed order	Infeasible	—	—	—	—
Raw features	Myopic	Infeasible	—	—	—	—
Raw features	Full policy	Infeasible	—	—	—	—
Features + confidence	Fixed subset	Infeasible	—	—	—	—
Features + confidence	Fixed order	Infeasible	—	—	—	—
Features + confidence	Myopic	Infeasible	—	—	—	—
Features + confidence	Full policy	Infeasible	—	—	—	—

S8.40. Matched risk acquisition: Cost and coverage across budgets

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

The full frozen candidate set is shown, including poor candidates and overlapping outcomes. Increasing a nominal budget does not force a policy to buy more features. The vertical threshold is only the mean-coverage part of the gate; the per-participant threshold is checked separately.



CAL development data. Coincident candidates overlap. Horizontal line: all-abstain J = 0.4; vertical line: 50% mean coverage.

Figure S32: Realized CAL objective versus predictive coverage for every primary candidate, with identical predictors and cost definitions. Diamonds mark the best feasible always-predict static anchor. Lower is better. This is a development comparison, not a confidence region or independent test. Gray open circles denote the primary descriptive anchors (all-abstain and, at budget 3, full-mask always-predict).

S8.41. Matched risk acquisition: Where the coverage gap remains

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Among the frozen learned candidates, the largest CAL coverage was 12.60% for raw features and 14.64% with confidence. These maxima are descriptive diagnostics selected after the experiment, not newly tested methods.

The corresponding static policies bought three and two axes for every window. Even with no covered mistakes, their purchase costs would require coverage strictly above 37.5% and 25%, respectively, to beat all-abstain. Their observed coverage misses even that necessary condition. This diagnoses these candidates; it does not prove that every possible adaptive policy must fail.

$$J < 0.4 \Longrightarrow C > 0.125K$$

Because covered mistakes E are nonnegative. This is necessary, not sufficient, and every term uses the same participant weighting.

Table S82: Where the coverage gap remains

Risk inputs	Candidate	Max C (%)	K	Necessary C (%)	J
Raw features	static.d5.m7	12.60	3	37.5	0.52638
Features + confidence	static.d5.m3	14.64	2	25.0	0.46610

S8.42. Matched risk acquisition: Unconstrained selections

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Removing the coverage constraint reveals whether the objective prefers abstention. An all-abstain result has J = 0.4, C = 0 and no purchases; it cannot support a useful-prediction claim.

Table S83: Unconstrained selections

Risk inputs	Family	Selected candidate	J ↓	C (%)	K	Min C (%)
Raw features	Fixed subset	anchor.abstain	0.40000	0.0	0.000	0.0
Raw features	Fixed order	anchor.abstain	0.40000	0.0	0.000	0.0
Raw features	Myopic	anchor.abstain	0.40000	0.0	0.000	0.0
Raw features	Full policy	anchor.abstain	0.40000	0.0	0.000	0.0
Features + confidence	Fixed subset	anchor.abstain	0.40000	0.0	0.000	0.0
Features + confidence	Fixed order	anchor.abstain	0.40000	0.0	0.000	0.0
Features + confidence	Myopic	anchor.abstain	0.40000	0.0	0.000	0.0
Features + confidence	Full policy	anchor.abstain	0.40000	0.0	0.000	0.0

S8.43. Matched risk acquisition: Computational scope

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Each of 36 builders fits seven terminal and 21 query regressors. Identical canonical child targets share artifacts only within that builder. The run performs 2,128 tree-prediction passes over 11,415,264 row-model pairs, including unrealized counterfactual branches. Classifiers are neither fitted nor invoked again.

The following counters cover the scientific child through OS exit. Parent receipt writes are outside those child counters. The measurement is offline computational work, not sensor energy or physical latency.

Table S84: Computational scope

Measured quantity	Value
Risk regressors	1,008
Classifier fits / inference	0 / 0
Tree prediction passes	2,128
Row-model predictions	11,415,264
Child CPU (s)	274.578
Child lifetime (s)	294.790
Terminal reads (MiB)	168.32
Terminal writes (MiB)	43.33
Observed OS exit	0

S8.44. Matched risk acquisition: Complete matched procedure

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

The same procedure and information boundary are stated here for reproduction.

S8.45. Matched risk acquisition: Budget 1: unconstrained

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Selection is performed on exposed CAL. An infeasible entry is retained. Exact unrounded candidate and participant values remain in NUMERICAL_RESULTS.json.

S8.46. Matched risk acquisition: Always-predict static anchors

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Masks use x=1, y=2 and z=4. Budget feasibility is the number of set bits. There are 4, 7 and 8 feasible anchors for budgets 1, 2 and 3. These descriptive anchors strengthen the comparison without altering the primary menus.

Table S85: Always-predict static anchors

Anchor	Mask	CAL J	C (%)	K
always.m0	0	0.944738	100.0	0
always.m1	1	0.775150	100.0	1
always.m2	2	0.754622	100.0	1
always.m3	3	0.755746	100.0	2
always.m4	4	0.788642	100.0	1
always.m5	5	0.804001	100.0	2
always.m6	6	0.811710	100.0	2

Anchor	Mask	CAL J	C (%)	K
always.m7	7	0.816102	100.0	3

S8.47. Matched risk acquisition: Raw features: anchor.abstain

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

Every CAL participant is retained; these are paired development units, not independent window-level replications.

Table S86: Raw features: anchor.abstain

Participant	J	C (%)	K	E
1606	0.400000	0.0	0.0000	0.00000
1609	0.400000	0.0	0.0000	0.00000
1618	0.400000	0.0	0.0000	0.00000
1619	0.400000	0.0	0.0000	0.00000
1621	0.400000	0.0	0.0000	0.00000
1626	0.400000	0.0	0.0000	0.00000
1640	0.400000	0.0	0.0000	0.00000
1641	0.400000	0.0	0.0000	0.00000

S8.48. Matched risk acquisition: Computational accounting

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

The public numerical record preserves all 36 builder lineages, exact score and route file identities, fit counts and separate partitions. Private row arrays and models are excluded from the publication Git archive.

S8.49. Matched risk acquisition: Residual bias, exposure and prior failures

Scope. Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner.

TRAIN25 is classifier resubstitution; TUNE8/CAL8 are exposed development. Fixed-candidate TUNE OOF evaluates a seven-person value learner, not the final all8 learner. Whole-pipeline outer exclusion removes a computational heldout-label path conditional on fixed design/predictors, but internal Bellman minima remain in-sample and optimistic. CAL selects development candidates; no independent final test, significance, probability calibration, safety, physical sensing/energy/latency saving, novelty/SOTA or deployment claim. Logical axes belong to one phone accelerometer;100 samples is a fixed sample count, not physical duration. Previous81/82 failures and83 corrected-source/84 review roles persist. Root historical private-JSON exposure and global FINAL exposure are unknown; current process FINAL body reads0 does not erase that. Predictor87 child OS exit code remains null/unknown despite its internal six-fit success. Native effective author model/ effort telemetry is unknown. No external primary methods were reread or reproduced here. Terminal counter capture covers the scientific child through its exit; launcher metadata writes are outside that child. The instrumentation watchdog is not OS security isolation.

S9. HGB intervention, failed fusion and calibrated terminal mixtures

The HGB fixed-mask intervention, the first-fit multinomial convergence failure and the successful bias/simplex terminal study are separate executions. All chosen policies remain TUNE-frozen and CAL-exposed. Failed or unattempted work is not relabeled as efficacy or no_gain evidence. A paid prediction remains charged when the terminal abstains.

S9.1. HGB shared family: Procedure and algorithm

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

Algorithm S28. Fixed-family, fixed-subset selective diagnosis
Require: Exactly28 hash-pinned87 NPZ files: TRAIN/TUNE/CAL54feature snapshots, frozen TRAIN normalizers/ prior and24 cached ET posteriors. Fixed HGB parameters, equal-participant mean1 TRAIN weights, thresholds0,.05,...,1 plus all abstain; gamma=.4 and axis-query price .05. Root release bound to the exact source/input seal; user-stop gate and resource envelope.
Ensure: Seven privately serialized HGB models and21 complete privately saved probability arrays, or explicit stopped/failed/unknown receipt without retries. TUNE-frozen subset/threshold IDs; paired participant/class diagnostics and fixed exposed-CAL loss/coverage/cost summaries. Label-informed available-submask correctness unions, explicitly separated from the deployed confidence selector.

1. Verify release identity and all source hashes; create the exclusive actual marker; enforce user-stop and the one-process resource watchdog.
2. Load only the28 released NPZ inputs, validate exact row/window identity and disjoint people, and verify the inherited normalizers using TRAIN only.
3. For each nonempty mask1..7, check user-stop, use its original6 and added12 columns per purchased axis, and fit one fixed HGB on TRAIN with equal-person mean1 weights and no early stopping.
4. Before each split probability pass check user-stop; call predict_proba exactly once, save the complete18class posterior privately, and derive argmax classes/confidence without extra inference.
5. For each purchased subset, use only already-paid submasks including the prior; choose highest stored confidence and the smallest mask on exact confidence ties. Keep direct-own-mask results separate.
6. For each budget1,2,3 evaluate the fixed TUNE menu; select unconstrained/useful/always-predict anchors by unrounded Python float J,K,-C,then lexicographic ID. Useful means macro coverage>=.50 and every TUNE person coverage>=.25.
7. Write and hash TUNE_CHOICES93.json before computing CAL choice metrics. Charge .05 per purchased axis on every window, including abstentions; use error1 and abstention.4.
8. Report the fixed choices on exposed CAL and direct-mask prediction corrections/harms for every split. Compute label-informed correctness union only as an offline diagnostic using existing predictions.
9. After actual child exit, capture terminal HANDLE CPU/IO/exit, preserve failures/unknowns without retry, freeze scientific outputs, and generate the metadata-only documents.

S9.2. HGB shared family: Architecture and paid information

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

The column layout is original6/axis in columns0..17 followed by added12/axis in columns18..53. A mask exposes exactly18 columns per purchased axis; tests perturb unpaid columns with NaN and confirm observed paid values remain identical. Frozen TRAIN normalizers are used unchanged. Equal-person sample weights sum to N/P per TRAIN person and have global mean1. Labels and participant IDs affect TRAIN fitting/ weighting or offline scoring, never terminal confidence selection.

The deployed terminal rule compares already-paid cached submasks only, includes the frozen prior and breaks exact ties toward the smallest mask. Its information rights are shared by both predictor families. The direct-own-mask ablation discards paid submask predictions. The correctness-union oracle may inspect labels and is not deployable.

S9.3. HGB shared family: Predictive change at every fixed mask

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

Every prespecified mask and partition is retained, including harms and negative gains. Participant macro accuracy and pooled corrections/harms use the same original windows; full class counts and sparse confusions are in NUMERICAL_RESULTS.json.

Table S87: Direct-own-mask paired prediction comparison. Fixed split denominators (windows / people): TRAIN: 24880 / 25, TUNE: 7845 / 8, CAL: 6437 / 8.

Mask	Split	ET87 acc	HGB93 acc	Gain	Corrections	Harms	Improved people	Harmed people
0	TRAIN	0.061521	0.061521	0.000000	0	0	0	0
0	TUNE	0.054033	0.054033	0.000000	0	0	0	0
0	CAL	0.055262	0.055262	0.000000	0	0	0	0
1	TRAIN	0.748212	0.844262	0.096049	2970	726	25	0
1	TUNE	0.287959	0.290706	0.002747	555	547	3	3
1	CAL	0.274850	0.263553	-0.011297	308	364	5	3
2	TRAIN	0.755856	0.853671	0.097815	3010	685	25	0
2	TUNE	0.301122	0.304834	0.003712	459	449	3	4
2	CAL	0.295378	0.295295	-0.000083	411	430	3	5
3	TRAIN	0.899120	0.968804	0.069684	1949	195	25	0
3	TUNE	0.314093	0.315393	0.001300	516	565	5	3
3	CAL	0.344254	0.329981	-0.014273	394	500	1	7
4	TRAIN	0.756912	0.820811	0.063899	2432	1105	24	1
4	TUNE	0.249608	0.259834	0.010226	484	459	5	3
4	CAL	0.261358	0.259323	-0.002035	371	373	4	4
5	TRAIN	0.904393	0.964271	0.059878	1660	249	25	0
5	TUNE	0.275101	0.302730	0.027629	627	421	6	2
5	CAL	0.295999	0.283147	-0.012852	368	496	3	5
6	TRAIN	0.898018	0.963429	0.065412	1833	261	25	0
6	TUNE	0.309430	0.316790	0.007360	534	505	6	2
6	CAL	0.288290	0.284250	-0.004040	381	394	4	4
7	TRAIN	0.929958	0.985705	0.055747	1435	85	25	0
7	TUNE	0.307567	0.319800	0.012233	636	529	5	3
7	CAL	0.333898	0.305540	-0.028359	358	534	1	7




Figure S33: Direct-own-mask equal-person accuracy. Source NUMERICAL_RESULTS.json SHA256 adb60209786e1f5068f3c455b36a599f3a3fbc188b83d87622de23c8b92e2aaf. All masks shown; no CAL winner is selected.

S9.4. HGB shared family: Frozen selective choices and covered-cost condition

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

J=0.05K+E+0.4(1-C), where E counts wrong covered predictions per all windows, C is coverage and K is purchased axes per window. Macro means give each person equal weight. Improvement over free all-abstain J=0.4 requires0.4C-E>0.05K. Reported covered_error_margin is0.4C-E-0.05K. Selective error E/C is undefined at zero coverage and remains null. Buying a subset costs0.05K even if every prediction abstains. Thresholds are exactly0,.05,...,1 plus explicit all-abstain. Budgets allow masks with popcount at most1/2/3; each family/rights menu has eight masks times22 thresholds. TUNE selection uses unrounded float J,K,-C,ID. Always-predict anchors restrict threshold to0. CAL is scored after the TUNE choice receipt is written;

CAL performance never changes chosen IDs. No TUNE-selected HGB93 paid-submask option simultaneously retained the useful-coverage constraints and J<0.4 on exposed CAL.




Figure S34: Coverage and unit-loss of paid-submask TUNE-selected policies; solid=useful, dashed=unconstrained. CAL is exposed development evidence. Source SHA256 adb60209786e1f5068f3c455b36a599f3a3fbc188b83d87622de23c8b92e2aaf.

S9.5. HGB shared family: Complexity and measured resource scope

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

With M=7 models, d<=54 columns, I=100 iterations and L=18 classes, the implementation performs exactly M TRAIN fits and3M probability passes. It constructs finite menus of8 masks by22 threshold cases per family/ rights and does no value/risk learner fit. A terminal comparison visits at most eight stored confidence values per window; the oracle union uses existing labels/predictions and no inference. The actual HGB tree/capacity intervention is bounded by the frozen parameters, not a new asymptotic speed theorem.

The matched comparator is frozen87 enhanced54feature ExtraTrees predictions; no old model was opened, decoded, imported or inferred. The fixed HGB family has a different capacity and optimization procedure:100 multiclass boosting iterations per mask produce1800 trees per mask for18 classes,12600 trees over seven masks, versus the frozen ET128 trees per mask (896 over seven nonempty masks). Tree counts are not equivalent complexity or equal learning capacity. Current measured HGB CPU/wall receipts do not recreate a matched prior ET timing experiment.

The retained Windows process HANDLE establishes child exit code 0 and terminal CPU 189.046875 s, lifetime 204.116482 s, read 136281449 B and write 52517548 B. Maximum observed PeakWorkingSetSize was 222154752 B across 3619 successful memory queries. Scientific imports, input hashing/loading, all fits, all probability passes, diagnostics and private serialization are inside this child. The parent froze this receipt before metadata-only plot/document rendering.

Maximum of live Windows PeakWorkingSetSize observations and any terminal query; no postexit query is guaranteed. Sampling can miss a peak after its last successful sample. This is observed usage plus a watchdog, not OS memory isolation.

S9.6. HGB shared family: Reproducibility and exact input custody

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

PRE_VALUE_SEAL93.json pins all executable source files, the evaluation contract, exact28 scientific inputs, installed defaults, synthetic evidence, launcher noop and hard attempt/resource caps. Root INPUT_RELEASE93.json binds that exact seal. ACTUAL_STARTED93.json and LAUNCH_STARTED93.json are exclusive markers; no retry is allowed. Dynamic campaign enabled metadata is read at launcher admission and before every new fit/probability pass. A disabled or unknown gate stops the owned attempt and preserves completed journals.

PRIVATE_CUSTODY93.json retains hashes of all seven private models and21 complete private probability files. Scientific inputs are three54feature snapshots, one normalizer/prior NPZ and24 ET cache NPZs. No raw archive, private CSV/metadata JSON, old model or FINAL file is read. Source87 schema helpers and launch91 HANDLE logic were read as source and minimally reimplemented, never imported/executed.

S9.7. HGB shared family: All selected policies and exact denominators

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

The rows retain unconstrained, useful and always-predict anchors for each budget and both terminal rights. TUNE has8 people/7845 windows; CAL has8 different people/6437 windows; TRAIN has25 other people/24880 windows. Windows are repeated observations within a participant. Threshold1 uses >= and can cover exactly certain predictions; all-abstain is a separate option.

Table S88: TUNE choices applied unchanged to CAL: paid_submasks. Family=ET87, rights=paid_submasks. Criterion labels: unconstrained, useful, always_predict_anchor (shown as always predict).

Budget	Criterion	Split	Buy mask	Threshold	J	C	Min person C	E	K	0.4C-E-0.05K
1	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
1	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
1	useful	TUNE	1	0.300000	0.563629	0.516803	0.389445	0.320351	1.000000	-0.163629
1	useful	CAL	1	0.300000	0.591552	0.576890	0.390940	0.372308	1.000000	-0.191552
1	always predict anchor	TUNE	2	0.000000	0.748878	1.000000	1.000000	0.698878	1.000000	-0.348878
1	always predict anchor	CAL	2	0.000000	0.754622	1.000000	1.000000	0.704622	1.000000	-0.354622
2	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
2	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
2	useful	TUNE	1	0.300000	0.563629	0.516803	0.389445	0.320351	1.000000	-0.163629
2	useful	CAL	1	0.300000	0.591552	0.576890	0.390940	0.372308	1.000000	-0.191552
2	always predict anchor	TUNE	2	0.000000	0.748878	1.000000	1.000000	0.698878	1.000000	-0.348878
2	always predict anchor	CAL	2	0.000000	0.754622	1.000000	1.000000	0.704622	1.000000	-0.354622
3	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
3	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
3	useful	TUNE	1	0.300000	0.563629	0.516803	0.389445	0.320351	1.000000	-0.163629
3	useful	CAL	1	0.300000	0.591552	0.576890	0.390940	0.372308	1.000000	-0.191552
3	always predict anchor	TUNE	2	0.000000	0.748878	1.000000	1.000000	0.698878	1.000000	-0.348878
3	always predict anchor	CAL	2	0.000000	0.754622	1.000000	1.000000	0.704622	1.000000	-0.354622

Table S89: TUNE choices applied unchanged to CAL: paid_submasks. Family=HGB93, rights=paid_submasks. Criterion labels: unconstrained, useful, always_predict_anchor (shown as always predict).

Budget	Criterion	Split	Buy mask	Threshold	J	C	Min person C	E	K	0.4C-E-0.05K
1	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
1	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000

Budget	Criterion	Split	Buy mask	Threshold	J	C	Min person C	E	K	0.4C-E-0.05K
1	useful	TUNE	2	0.450000	0.561423	0.575583	0.352684	0.341656	1.000000	-0.161423
1	useful	CAL	2	0.450000	0.541547	0.497893	0.311111	0.290704	1.000000	-0.141547
1	always predict anchor	TUNE	2	0.000000	0.745166	1.000000	1.000000	0.695166	1.000000	-0.345166
1	always predict anchor	CAL	2	0.000000	0.754705	1.000000	1.000000	0.704705	1.000000	-0.354705
2	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
2	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
2	useful	TUNE	2	0.450000	0.561423	0.575583	0.352684	0.341656	1.000000	-0.161423
2	useful	CAL	2	0.450000	0.541547	0.497893	0.311111	0.290704	1.000000	-0.141547
2	always predict anchor	TUNE	2	0.000000	0.745166	1.000000	1.000000	0.695166	1.000000	-0.345166
2	always predict anchor	CAL	2	0.000000	0.754705	1.000000	1.000000	0.704705	1.000000	-0.354705
3	unconstrained	TUNE	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
3	unconstrained	CAL	0	0.100000	0.400000	0.000000	0.000000	0.000000	0.000000	0.000000
3	useful	TUNE	2	0.450000	0.561423	0.575583	0.352684	0.341656	1.000000	-0.161423
3	useful	CAL	2	0.450000	0.541547	0.497893	0.311111	0.290704	1.000000	-0.141547
3	always predict anchor	TUNE	2	0.000000	0.745166	1.000000	1.000000	0.695166	1.000000	-0.345166
3	always predict anchor	CAL	2	0.000000	0.754705	1.000000	1.000000	0.704705	1.000000	-0.354705

S9.8. HGB shared family: Participant prediction corrections and harms

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

These are direct-own-mask predictive comparisons, separate from selective losses. Every TUNE/CAL person is shown. TRAIN people, class breakdowns, complete confusion counts and all union diagnostic person rates remain in NUMERICAL_RESULTS.json.

Table S90: All TUNE/CAL people at every mask

Mask	Split	Person	Windows	ET87 acc	HGB93 acc	Gain	Corrections	Harms
0	TUNE	1610	797	0.043915	0.043915	0.000000	0	0
0	TUNE	1611	630	0.055556	0.055556	0.000000	0	0
0	TUNE	1620	1099	0.031847	0.031847	0.000000	0	0
0	TUNE	1628	1072	0.083022	0.083022	0.000000	0	0
0	TUNE	1629	1368	0.051170	0.051170	0.000000	0	0
0	TUNE	1631	630	0.055556	0.055556	0.000000	0	0
0	TUNE	1638	647	0.055641	0.055641	0.000000	0	0
0	TUNE	1646	1602	0.055556	0.055556	0.000000	0	0
0	CAL	1606	630	0.055556	0.055556	0.000000	0	0
0	CAL	1609	601	0.058236	0.058236	0.000000	0	0
0	CAL	1618	596	0.058725	0.058725	0.000000	0	0
0	CAL	1619	812	0.055419	0.055419	0.000000	0	0
0	CAL	1621	814	0.055283	0.055283	0.000000	0	0
0	CAL	1626	738	0.047425	0.047425	0.000000	0	0
0	CAL	1640	644	0.055901	0.055901	0.000000	0	0
0	CAL	1641	1602	0.055556	0.055556	0.000000	0	0
1	TUNE	1610	797	0.417817	0.417817	0.000000	86	86
1	TUNE	1611	630	0.220635	0.236508	0.015873	52	42
1	TUNE	1620	1099	0.253867	0.253867	0.000000	63	63
1	TUNE	1628	1072	0.241604	0.278918	0.037313	81	41
1	TUNE	1629	1368	0.323099	0.302632	-0.020468	62	90
1	TUNE	1631	630	0.252381	0.176190	-0.076190	12	60
1	TUNE	1638	647	0.353941	0.428130	0.074189	80	32
1	TUNE	1646	1602	0.240325	0.231586	-0.008739	119	133
1	CAL	1606	630	0.236508	0.239683	0.003175	25	23
1	CAL	1609	601	0.262895	0.264559	0.001664	26	25

Mask	Split	Person	Windows	ET87 acc	HGB93 acc	Gain	Corrections	Harms
1	CAL	1618	596	0.318792	0.261745	-0.057047	18	52
1	CAL	1619	812	0.252463	0.213054	-0.039409	27	59
1	CAL	1621	814	0.214988	0.228501	0.013514	53	42
1	CAL	1626	738	0.322493	0.294038	-0.028455	36	57
1	CAL	1640	644	0.344720	0.354037	0.009317	44	38
1	CAL	1641	1602	0.245943	0.252809	0.006866	79	68
2	TUNE	1610	797	0.422836	0.421581	-0.001255	78	79
2	TUNE	1611	630	0.277778	0.288889	0.011111	37	30
2	TUNE	1620	1099	0.186533	0.169245	-0.017288	28	47
2	TUNE	1628	1072	0.319963	0.296642	-0.023321	47	72
2	TUNE	1629	1368	0.296784	0.327485	0.030702	108	66
2	TUNE	1631	630	0.414286	0.457143	0.042857	55	28
2	TUNE	1638	647	0.273570	0.273570	0.000000	27	27
2	TUNE	1646	1602	0.217228	0.204120	-0.013109	79	100
2	CAL	1606	630	0.185714	0.211111	0.025397	61	45
2	CAL	1609	601	0.254576	0.252912	-0.001664	41	42
2	CAL	1618	596	0.317114	0.342282	0.025168	40	25
2	CAL	1619	812	0.431034	0.397783	-0.033251	43	70
2	CAL	1621	814	0.321867	0.315725	-0.006143	40	45
2	CAL	1626	738	0.372629	0.344173	-0.028455	29	50
2	CAL	1640	644	0.299689	0.326087	0.026398	59	42
2	CAL	1641	1602	0.180400	0.172285	-0.008115	98	111
3	TUNE	1610	797	0.419072	0.445420	0.026349	84	63
3	TUNE	1611	630	0.292063	0.273016	-0.019048	40	52
3	TUNE	1620	1099	0.208371	0.172884	-0.035487	43	82
3	TUNE	1628	1072	0.300373	0.311567	0.011194	53	41
3	TUNE	1629	1368	0.220760	0.311404	0.090643	142	18
3	TUNE	1631	630	0.331746	0.344444	0.012698	35	27
3	TUNE	1638	647	0.383308	0.426584	0.043277	76	48
3	TUNE	1646	1602	0.357054	0.237828	-0.119226	43	234
3	CAL	1606	630	0.285714	0.288889	0.003175	41	39
3	CAL	1609	601	0.267887	0.244592	-0.023295	31	45
3	CAL	1618	596	0.399329	0.380872	-0.018456	39	50
3	CAL	1619	812	0.359606	0.350985	-0.008621	37	44
3	CAL	1621	814	0.316953	0.309582	-0.007371	56	62
3	CAL	1626	738	0.405149	0.399729	-0.005420	60	64
3	CAL	1640	644	0.440994	0.419255	-0.021739	43	57
3	CAL	1641	1602	0.278402	0.245943	-0.032459	87	139
4	TUNE	1610	797	0.378921	0.460477	0.081556	97	32
4	TUNE	1611	630	0.192063	0.220635	0.028571	46	28
4	TUNE	1620	1099	0.183803	0.151046	-0.032757	34	70
4	TUNE	1628	1072	0.369403	0.356343	-0.013060	64	78
4	TUNE	1629	1368	0.247076	0.217836	-0.029240	88	128
4	TUNE	1631	630	0.233333	0.234921	0.001587	30	29
4	TUNE	1638	647	0.231839	0.275116	0.043277	49	21
4	TUNE	1646	1602	0.160424	0.162297	0.001873	76	73
4	CAL	1606	630	0.239683	0.263492	0.023810	40	25
4	CAL	1609	601	0.204659	0.191348	-0.013311	16	24
4	CAL	1618	596	0.370805	0.345638	-0.025168	27	42
4	CAL	1619	812	0.286946	0.261084	-0.025862	32	53
4	CAL	1621	814	0.255528	0.266585	0.011057	60	51
4	CAL	1626	738	0.334688	0.302168	-0.032520	51	75
4	CAL	1640	644	0.189441	0.222050	0.032609	47	26
4	CAL	1641	1602	0.209114	0.222222	0.013109	98	77
5	TUNE	1610	797	0.437892	0.481807	0.043915	82	47
5	TUNE	1611	630	0.214286	0.265079	0.050794	65	33
5	TUNE	1620	1099	0.176524	0.195632	0.019108	55	34
5	TUNE	1628	1072	0.259328	0.347948	0.088619	118	23
5	TUNE	1629	1368	0.378655	0.352339	-0.026316	128	164
5	TUNE	1631	630	0.261905	0.253968	-0.007937	23	28
5	TUNE	1638	647	0.323029	0.344668	0.021638	47	33

Mask	Split	Person	Windows	ET87 acc	HGB93 acc	Gain	Corrections	Harms
5	TUNE	1646	1602	0.149189	0.180400	0.031211	109	59
5	CAL	1606	630	0.280952	0.247619	-0.033333	24	45
5	CAL	1609	601	0.227953	0.237937	0.009983	29	23
5	CAL	1618	596	0.387584	0.375839	-0.011745	40	47
5	CAL	1619	812	0.279557	0.251232	-0.028325	18	41
5	CAL	1621	814	0.239558	0.217445	-0.022113	29	47
5	CAL	1626	738	0.317073	0.329268	0.012195	96	87
5	CAL	1640	644	0.340062	0.368012	0.027950	69	51
5	CAL	1641	1602	0.295256	0.237828	-0.057428	63	155
6	TUNE	1610	797	0.377666	0.456713	0.079046	107	44
6	TUNE	1611	630	0.333333	0.355556	0.022222	51	37
6	TUNE	1620	1099	0.202002	0.202912	0.000910	77	76
6	TUNE	1628	1072	0.363806	0.367537	0.003731	57	53
6	TUNE	1629	1368	0.352339	0.364035	0.011696	68	52
6	TUNE	1631	630	0.363492	0.293651	-0.069841	14	58
6	TUNE	1638	647	0.293663	0.338485	0.044822	71	42
6	TUNE	1646	1602	0.189139	0.155431	-0.033708	89	143
6	CAL	1606	630	0.244444	0.233333	-0.011111	42	49
6	CAL	1609	601	0.242928	0.229617	-0.013311	20	28
6	CAL	1618	596	0.337248	0.367450	0.030201	43	25
6	CAL	1619	812	0.365764	0.293103	-0.072660	22	81
6	CAL	1621	814	0.294840	0.326781	0.031941	66	40
6	CAL	1626	738	0.413279	0.372629	-0.040650	28	58
6	CAL	1640	644	0.271739	0.295031	0.023292	49	34
6	CAL	1641	1602	0.136080	0.156055	0.019975	111	79
7	TUNE	1610	797	0.402760	0.473024	0.070263	122	66
7	TUNE	1611	630	0.323810	0.336508	0.012698	63	55
7	TUNE	1620	1099	0.207461	0.156506	-0.050955	22	78
7	TUNE	1628	1072	0.347948	0.393657	0.045709	92	43
7	TUNE	1629	1368	0.289474	0.271930	-0.017544	112	136
7	TUNE	1631	630	0.346032	0.303175	-0.042857	16	43
7	TUNE	1638	647	0.357032	0.386399	0.029366	62	43
7	TUNE	1646	1602	0.186017	0.237203	0.051186	147	65
7	CAL	1606	630	0.280952	0.225397	-0.055556	26	61
7	CAL	1609	601	0.259567	0.232945	-0.026622	22	38
7	CAL	1618	596	0.437919	0.389262	-0.048658	34	63
7	CAL	1619	812	0.314039	0.296798	-0.017241	33	47
7	CAL	1621	814	0.287469	0.283784	-0.003686	59	62
7	CAL	1626	738	0.457995	0.392954	-0.065041	36	84
7	CAL	1640	644	0.380435	0.395963	0.015528	63	53
7	CAL	1641	1602	0.252809	0.227216	-0.025593	85	126

S9.9. HGB shared family: Label-informed diagnostic oracle

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

For a fixed purchased subset S, correctness union is the fraction of windows where at least one submask of S predicts the true class, including prior. It upper bounds accuracy for any selector restricted to choosing those stored classes at that fixed subset; it is not a general Bayes ceiling. Adaptive purchased subsets can have a different union. The maxconfidence selector cannot observe correctness and may fall below this union. Marginal union bounds belong to the separate theory study; these empirical rates use no extra fit/inference.

Table S91: Oracle union and deployed maxconfidence accuracy: identical paid-submask availability

Family	Mask	Split	Oracle union macro	Maxconfidence macro	Gap
ET87	0	TUNE	0.054033	0.054033	0.000000
ET87	0	CAL	0.055262	0.055262	0.000000
ET87	1	TUNE	0.324120	0.287959	0.036161
ET87	1	CAL	0.293120	0.274850	0.018270
ET87	2	TUNE	0.327935	0.301122	0.026813
ET87	2	CAL	0.334404	0.295378	0.039026

Family	Mask	Split	Oracle union macro	Maxconfidence macro	Gap
ET87	3	TUNE	0.512446	0.332159	0.180287
ET87	3	CAL	0.496946	0.323107	0.173839
ET87	4	TUNE	0.290887	0.249608	0.041279
ET87	4	CAL	0.289777	0.261358	0.028419
ET87	5	TUNE	0.496025	0.282315	0.213710
ET87	5	CAL	0.455484	0.299878	0.155606
ET87	6	TUNE	0.475970	0.300830	0.175140
ET87	6	CAL	0.480442	0.304341	0.176101
ET87	7	TUNE	0.624570	0.317784	0.306785
ET87	7	CAL	0.592264	0.328995	0.263269
HGB93	0	TUNE	0.054033	0.054033	0.000000
HGB93	0	CAL	0.055262	0.055262	0.000000
HGB93	1	TUNE	0.327330	0.290706	0.036624
HGB93	1	CAL	0.283854	0.263553	0.020301
HGB93	2	TUNE	0.331659	0.304834	0.026824
HGB93	2	CAL	0.334892	0.295295	0.039597
HGB93	3	TUNE	0.527756	0.335296	0.192460
HGB93	3	CAL	0.501910	0.322561	0.179349
HGB93	4	TUNE	0.303475	0.259834	0.043641
HGB93	4	CAL	0.293899	0.259323	0.034576
HGB93	5	TUNE	0.507573	0.308959	0.198614
HGB93	5	CAL	0.472056	0.291240	0.180816
HGB93	6	TUNE	0.508444	0.330905	0.177539
HGB93	6	CAL	0.498151	0.297553	0.200598
HGB93	7	TUNE	0.649056	0.332929	0.316126
HGB93	7	CAL	0.624096	0.322140	0.301956

S9.10. HGB shared family: Resource, timing and historical uncertainty

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

The old87 scientific pipeline did not retain independently resolved OS exit evidence; old89 terminal-counter-tail and Root prior FINAL/cached-JSON exposure uncertainties are inherited and unresolved. Hash-pinned cached bytes establish the present input identity, not the original acquisition process or scientific accuracy. This run has its own retained process HANDLE and terminal exit/counters; it does not repair the historical receipts.

The actual child ran once in a fixed mask/split order with no warmup, repeat or order balancing. Per-fit/per-pass timings include serialization. Parent metadata rendering is outside the terminal scientific-child resource envelope and is reported separately; Codex authoring/model cost is unmeasured. No network model call occurred.

S9.11. HGB shared family: Six method areas and next acceptance

Scope. Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting.

Algorithm and architecture have executable, source-bound procedures; complexity has actual operation counts and terminal resource receipts; baselines use matched stored-information menus and always-predict anchors. Evaluation is partial because TUNE/CAL are exposed development data. Related work is partial because official API/landing pages do not substitute for external primary-paper method comparisons. Author-supplied mappings are not independent review or scientific certification.

A future acceptance test must preregister one participant-disjoint untouched comparison, retain all harms/failures and exact denominators, preserve the same prices and paid-submask rights, and require useful coverage and positive covered-cost margin together. Any new dynamic policy, additional fitting, raw reconstruction or extra inference needs a new explicit Task and budget.

S9.12. Failed multinomial fusion: Research question and contribution

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

Algorithm S29. Paid-submask crossfitting with fail-closed convergence and a CAL boundary
Require: Hash-bound TUNE/CAL cached18-class HGB probabilities and ET class/confidence controls; labels and participant/window IDs in separate arrays. Prespecified11 configurations, four sorted adjacent held-out participant pairs, C1/lbfgs/L2/max_iter1000/tol10^-6/intercept true and one CPU thread. Fixed costs, coverage constraints, threshold grid, budgets and Root input release.
Ensure: On success:55 converged fits, frozen OOF choices, then fixed CAL metrics and complete public aggregates. On any convergence failure: explicit failure receipt and terminal resources, preserved journals, no retry and no downstream choices.

1 Verify the exact release, all sealed source bytes and installed estimator defaults. Do not read any CAL file, including for hashing.
2 Hash each allowed TUNE archive, then decode only its declared keys. Never decode snapshot X or read TRAIN, raw archives, predecessor models or FINAL.
3 Sort the8 TUNE participant IDs into4 adjacent held-out pairs. For each stack mask concatenate log probabilities of ascending nonempty paid submasks; owncal uses the mask alone.
4 Fit the fixed multinomial logistic rule on the six non-held-out participants using mean-one equal-participant weights. Catch ConvergenceWarning and reject n_iter>=1000 without retry.
5 If a fit fails, preserve its start and failure receipt, exit with nonzero status and return no predictions, selected policies or efficacy estimate. This execution returned here at its first fit.
6 If every fit succeeds, fill each held-out row exactly once, perform all-TUNE refits, complete exactly55 fits and fix OOF policy choices to disk. Single-axis owncal reuses identical stack models.
7 Only after the completed-fit journal and OOF choice hashes are durably bound may CAL files be hashed/ decoded and the fixed models applied.
8 Retain participant/class costs, abstentions, paired action transitions, accepted-union V/F/G diagnostics and descriptive bootstrap, then freeze retained-HANDLE terminal CPU/I/O/exit counters.

S9.13. Failed multinomial fusion: Frozen sources and permitted information

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The seal names32 scientific archives:14 complete HGB93 probability files for7 nonempty masks on TUNE/ CAL;16 enhanced ET87 prediction/maxprob files for masks0..7; and2 snapshot archives supplying labels and identities. The actual child opened the16 TUNE files before fitting. The CAL16 remain unaccessed by this execution.

Each snapshot was decoded only for y, subjects, row_index and window_id. Whole-archive integrity hashing includes the compressed X member's bytes, but X was never requested or decoded as an array. HGB vectors, cached actions/confidences and all loaded private labels stayed inside the measured process. It wrote no private model or probability output. Labels and IDs were not prediction features.

The7 HGB and ET caches were inherited fixed predictors. No predecessor model was loaded and no base-model inference or fit occurred. Mask0 supplied the free prior's cached action/confidence, so the task required neither a full prior vector nor a TRAIN/normalizer read.

S9.14. Failed multinomial fusion: The planned matched terminal comparison

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

For paid mask S and class k, the stack feature is log(max(p_A,k,10^-6)) for every nonempty A contained in S, ordered by integer mask then class0..17. Its dimension is18(2^K−1):18,54 or126 for K=1,2,3 axes. Owncal uses the18 transformed probabilities of S only. The feature rule has no label, participant or window identity coordinate.

Both rules were fixed at C1, lbfgs, L2, intercept true, max_iter1000, tol10^-6, no standardization, no class weighting and one thread. Complete installed defaults, effective settings, versions and the local LogisticRegression implementation hash were frozen before private access. A finite cap and small tolerance were part of the requested contract, not tuned after seeing this failure.

Single-axis stack and owncal have identical inputs and fitting rules, so their trained objects would be reused. Seven stack configurations plus four multi-axis owncal configurations yield11 distinct configurations. Each was to have4 held-out-pair fits and1 all-TUNE refit, or55 fits in total. The observed failure occurred before that reuse or any paired comparison could be exercised on the real data.

S9.15. Failed multinomial fusion: Participant crossfitting and selection boundary

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The8 sorted TUNE subject IDs determine adjacent held-out pairs. The first fit used6 training participants and held out2 with no overlap; the journal records their identities and aggregate training-row count. Equal-participant sample weights are N/(P n_s), with mean1 within the fitted sample. This is group crossfitting, not a random window split.

The intended selection menu used only pooled held-out TUNE predictions. TUNE in-sample meta-predictions were to be computed after choices were fixed and used only for shift diagnostics. All-TUNE models would then predict CAL. None of these prediction or selection stages was reached.

CAL access, including its whole-file hash check, required55 completed fits and a disk-fixed completed-fit/OOF-choice barrier. No TUNE_FIXED or choice file exists, and the input-open ledger contains only TUNE entries. The program's failure therefore preserved the stronger access order; it did not produce a newly independent dataset. TUNE/CAL remain previously exposed development participants.

S9.16. Failed multinomial fusion: Observed first-fit failure

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The failure receipt records stage fit:stack:1:0, RuntimeError and the underlying lbfgs termination after1000 iterations. The source catches convergence warnings and rejects reaching the iteration cap; it does not accept the solver's partial coefficients as a completed learner. The failed object was not serialized.

The terminal process exited with code1. No automatic retry, altered C, extra iterations, feature scaling or alternative solver followed. The remaining54 fits were not attempted, and the same accepted actual call was not retransmitted. This preserves the experiment's prespecification instead of turning a numerical failure into an unlogged tuning step.

Table S92: First attempted fit, from the public fit-start journal. Participant IDs are aggregation/partition identities, never model features.

item	observed
configuration	stack; purchased X(mask1)
held-out pair	1610, 1611
training subjects	1620, 1628, 1629, 1631, 1638, 1646
training windows	6418
log-probability features	18
maximum iterations	1000
tolerance	0.000001
solver	lbfgs
termination	iteration limit; ConvergenceWarning
completed fit	no

S9.17. Failed multinomial fusion: What was and was not evaluated

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

A planned execution count is not an achieved count. The public audit distinguishes one attempted fit from zero converged fits. Likewise, absence of a metric stream does not mean zero error, zero coverage or a numerical tie. All participant/class policy outcomes and paired deltas are explicitly unavailable.

Because both X stack and X owncal would use the same learner and input matrix, their equality is a structural property checked synthetically. It does not authorize reporting real X accuracy or a useful-policy tie after the first fit failed. No multi-axis fit reached evaluation, so neither the extra submask information nor owncal's benefit can be estimated here.

Table S93: Planned and observed execution. Unavailable outcomes are not zeros of a performance metric.

stage	planned	observed	status
distinct configurations	11	first configuration entered	incomplete
meta-fit calls	55	1 started;0 completed	first fit failed
held-out OOF probability passes	44	0	not reached
all-TUNE refits	11	0	not reached
TUNE-refit diagnostic passes	11	0	not reached

stage	planned	observed	status
CAL meta-probability passes	11	0	not reached
scientific archive reads	32	16 TUNE only	CAL16 never opened
OOF choice rows	90	unavailable	no choice file
policy/fold metric records	10017	unavailable	no performance stream
paired subject bootstrap	2000	unavailable	not performed

S9.18. Failed multinomial fusion: Useful coverage, abstention and unresolved acceptance

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The fixed loss is J=0.05K+E+0.4(1−C), with costs paid on abstentions, E the covered-error fraction over all windows and C the response fraction. Macro metrics average participants equally; the free all-abstain reference has J=0.4. Useful policies require macro C≥0.5 and every-person C≥0.25. Threshold and mask selection use unrounded J/K/−C/lexicographic ID.

Two questions must remain separate. A coverage-constrained stack improvement over a feasible owncal policy concerns the useful domain. Whether that policy also beats free all-abstention is the additional J<0.4 test, whose reference is outside that coverage-constrained domain. An infeasible baseline requires an explicit feasibility comparison, not an automatic no_gain conclusion.

The sealed acceptance required both useful CAL policies plus strict stack J<owncal J and J<0.4. This failure changes none of those gates. It leaves useful-domain improvement, baseline feasibility and free-abstention dominance all unevaluated. The result uses not_evaluated_convergence_failure and never substitutes a false gain flag for a measured no_gain result.

S9.19. Failed multinomial fusion: Selector union and arbitrary probability fusion

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

A selector that returns a stored expert argmax can only be correct where at least one eligible expert argmax is correct. Probability fusion has a larger terminal action set. For y=0, p1=(0.45,0.50,0.05) and p2=(0.45,0.05,0.50) both have an incorrect argmax, while their mean has a correct argmax. The expert correctness union is therefore a selector diagnostic and not a ceiling for arbitrary fusion.

The planned ledger implements E=C−V+F−G over accepted rows: V is accepted expert-union correctness mass, F is accepted union-correct but terminal-wrong mass and G is accepted union-wrong but terminal-correct mass. It retains the nonempty union and the union including the free prior, per participant and in macro form. Selectors have G=0 for the latter union; learned fusion and pooling can have G>0.

Synthetic tests verify the identity and three-class witness. The failed real attempt produced no V/F/G estimates, rescue counts or observed fusion harms. These mathematical and synthetic facts are kept distinct from the unavailable experiment; the independent theory99 author develops the general distinction separately.

S9.20. Failed multinomial fusion: Resource and access accounting

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The launcher retained the Windows process HANDLE through actual child exit, then read terminal CPU, I/O, lifetime and exit code. Scientific imports, source/input hashes, decoding, the attempted fit and failure serialization are inside this process. The run stayed below all fixed resource caps. Its failure was the solver contract's convergence failure, not an observed overall CPU, wall, RAM or I/O cap violation.

RAM is the maximum successful observed PeakWorkingSetSize, with171 successful memory queries. Sampling may miss a final peak after the last successful query. These observations and the watchdog do not provide OS memory isolation or a security sandbox. Later metadata-only auditing and document rendering are outside the actual-child envelope.

Table S94: Retained-HANDLE terminal measurements for the single failed scientific child. RAM is observed, not an OS isolation guarantee.

quantity	observed	fixed cap	interpretation
CPU seconds	7.312500	1800	terminal CPU
wall seconds	9.531741	2400	kernel process lifetime
peak working-set bytes	169103360	2147483648	maximum successful live/terminal query
read bytes	53093251	536870912	includes imports and whole-file hashes

quantity	observed	fixed cap	interpretation
write bytes	12791	268435456	includes failure/journals/log output
exit code	1	expected success0	scientific attempt failed

S9.21. Failed multinomial fusion: Source hierarchy and exact chronology

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The registered Task is task_6ce8233c9031 under run_edf0173ced28, executor /root/probeflow_fusion98. The prevalue seal binds38 public source/metadata/policy records and32 custody-derived input records. Its SHA256 is89e5c62cbc0e8904affa437e7a7fc5585268ca971153854eb8023094dba8f0f6. Root issued the exact INPUT_RELEASE98 before launch; the release hash and original bytes remain in the evidence bundle.

Final-source synthetic receipts were regenerated after the scientific source changed during preparation, preserving older receipts. The final seal is bound to the final20-check suite, size/transition checks and retained-HANDLE noop. The source/public metadata were fixed before any private input hash or decode.

The actual first-fit failure and terminal counter record were frozen before this metadata-only failure writer ran. Sealed science, thresholds and access logic remain byte-identical. report98.py remains the sealed success-report builder; failure_report98.py is an explicitly separate aggregate-only successor. An unused editorial plotting draft is preserved as unexecuted source and supplies no result.

S9.22. Failed multinomial fusion: Input allowlist and partial reads

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The planned input set consists of2 snapshots,14 HGB complete-probability archives and16 ET class/confidence archives. Public predecessor custody gives their file hashes and sizes without opening payloads. No data arrays were entered into the author's model context.

The actual read ledger contains16 hash operations and16 selected-key decodes, all with stage TUNE_before_fit. The selected NPZ keys for snapshots are exactly y/subjects/row_index/window_id; HGB keys are probabilities/prediction/max_probability/row_index; ET keys are enhanced/enhanced_max_probability/row_index. No X key occurs.

File integrity hashes cover whole NPZ bytes. This includes compressed bytes of unused snapshot members and is counted in the process I/O. The claim is specifically no X decode or feature use, not a claim that the archive byte stream excluded X. CAL archive bytes were not hashed or decoded; TRAIN, raw archive, model payloads and FINAL were outside the allowlist.

S9.23. Failed multinomial fusion: Planned crossfit/refit accounting

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The11 distinct configurations were ordered as stack masks1..7, then owncal masks3/5/6/7. Each configuration was to use folds0..3 followed by an all-TUNE refit. The first fit was stack/mask1/fold0. Its start journal is the only fit journal entry.

The source deliberately increments started and completed counters separately. The started counter became1 before the library fit; completed remained0 because the convergence check raised. A partial library object does not satisfy the completed-fit count. The other54 planned fits are unattempted, not failed trials with observed outcomes.

The planned prediction total was66:44 held-out passes,11 in-sample TUNE-refit diagnostics and11 CAL passes. None ran because the first prediction occurs only after a successful fit. No all-TUNE models, complete learned probabilities or private output directory were produced.

S9.24. Failed multinomial fusion: Learner, weights and class space

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The installed estimator is scikit-learn1.8.0 LogisticRegression. Default/effective parameter dictionaries and the estimator implementation hash are in the prevalue seal. Explicit C1/lbfgs/L2/intercept true/max_iter1000/tol10^-6 settings were unchanged. Thread environment and threadpoolctl restrict the actual scientific computation to one thread.

Per-participant training weights N/(P n_s) have mean1 and equal participant total mass within each fitted set. They do not make fold and all-TUNE training totals equal, and the same C does not imply equal effective complexity across feature dimensions or training sizes. These limitations were fixed before access.

Model classes_ would be aligned to canonical0..17 probability columns, rejecting duplicate/out-of-range axes. A missing fitted class would receive zero probability in that canonical space. Synthetic tests cover permuted/ missing classes. No completed actual model or actual predicted class array exists, so class alignment is an implementation check rather than a reported real prediction result.

S9.25. Failed multinomial fusion: Planned baseline family and paid rights

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

HGB_rawown uses the bought mask's fixed posterior. HGB_maxconfidence compares all paid submask argmax confidences plus mask0 and takes the smallest-mask exact tie. HGB_mean and HGB_logpool mix complete probabilities from nonempty paid submasks; logpool clips below10^-6 and normalizes exponentials. HGB_owncal and HGB_stack share the fixed logistic learner.

ET_own and ET_maxconfidence use enhanced87 cached class/maxprob values only. No full ET probability fusion is fabricated. Prior and all-abstain are explicit free controls. General families also admit mask0, allowing a policy not to purchase axes. Mean/log pooling excludes the prior by declared design; maxconfidence includes its free action.

The comparison holds row identity, prices, budget, threshold grid, OOF selection and aggregation fixed. It changes terminal functions and their parameter count. Same information does not establish identical learned action sets or identical model capacity. Because the first learned fit failed, none of these controls was evaluated on the real rows in this attempt.

S9.26. Failed multinomial fusion: Policy selection and unavailable outcomes

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

Within each family and budget1/2/3, the planned selector minimizes participant-macro unrounded J, then K, minus C and lexicographic policy ID. Numeric thresholds0,0.05,…,1 use confidence≥threshold; explicit index21 means all-abstention. Always-predict uses threshold0 only.

The useful menu requires macro response≥0.5 and every-person response≥0.25. An empty menu would be unavailable, not replaced by a purported feasible fallback. The CAL score was to use frozen choices only. The first failure prevented even the TUNE OOF menu, so useful infeasibility was not observed for stack or owncal.

There would have been1431 candidates per scope and10017 records across pooled OOF plus4 held-out folds, TUNE-refit diagnostic and CAL. The current absence of that stream is explicitly recorded. There are no paired participant estimates to put in a result plot or table; no placeholder values or predecessor performance numbers replace them.

S9.27. Failed multinomial fusion: Loss and separate acceptance questions

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

For participant s, C_s is accepted count/n_s and E_s is covered errors/n_s. Cost J_s=.05K+E_s+.4(1−C_s) is averaged equally across participants; pooled rates would be reported separately. Positive paid K is charged even if all actions abstain. E_s/C_s is undefined at zero acceptance and is retained as null.

The useful-coverage feasible domain excludes free all-abstention. A lower J than a feasible useful control can be a constrained-domain improvement even if J≥.4. The separate comparison to .4 concerns the unconstrained free-abstain reference. A baseline with no useful choice creates a feasibility result, not a paired numeric loss improvement.

The frozen combined development acceptance included both useful CAL policies, strict gain over owncal and strict J<.4. This report preserves that rule and separately lists all three questions as not evaluated. It does not relabel an unavailable comparison as no_gain merely because a boolean acceptance flag could not become true.

S9.28. Failed multinomial fusion: Union witness and accepted-error identity

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The three-class witness p1=(.45,.50,.05), p2=(.45,.05,.50), y=0 demonstrates a fusion class absent from both expert argmaxes. It applies to an arbitrary fusion function's action set, independent of whether the logistic fit succeeds. It does not predict how often the effect occurs on HGB93.

For accepted actions, partitioning on expert-union correctness U and terminal correctness H gives C=mass(A), V=mass(AU), F=mass(AU(1−H)) and G=mass(A(1−U)H). Then E=mass(A(1−H))=C−V+F−G. Averaging that equality equally across participants preserves it.

The source includes both nonempty-union and prior-enlarged-union diagnostics, ensuring G=0 for selectors under the latter rights. Synthetic tests cover every binary cell, prior/paid rights and the mean-fusion rescue witness. Real accepted V/F/G, nonexisting-base corrections and harms remain unmeasured because prediction was never reached.

S9.29. Failed multinomial fusion: Planned paired transitions and sensitivity

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

Correctness gained counts reference-not-correct→candidate-correct, which includes abstain→correct. Correctness lost includes correct→abstain. The source separates wrong→correct, abstain→correct, correct→wrong and correct→abstain so that a coverage change cannot masquerade as an error correction. Synthetic transition tests confirm the decomposition.

Fixed-mask full-coverage comparisons would isolate additional submask probability inputs at identical purchase cost. Separately selected policies can buy different masks within the same maximum budget, and their δ K would remain visible. No real comparison of either type exists in this run.

A paired participant bootstrap with2000 draws and seed9801 was planned for CAL, using the same resampled subject positions for candidate/reference. It was not run. It would in any case be descriptive sensitivity on8 exposed participants rather than confirmatory population inference. No interval, p-value or effective sample size is invented.

S9.30. Failed multinomial fusion: Resource measurement, noop and write estimate

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The retained-HANDLE noop writes/reads65536 fixture bytes and exercises CPU time, then verifies terminal counters and exit0. It is a synthetic accounting check, not a scientific fit or an operating-system isolation test. Its exact source-bound receipt precedes the input release.

The final synthetic size estimate is209427406 bytes against a268435456-byte write cap. It anticipates detailed policy serialization and private outputs; actual failure wrote12791 bytes before parent metadata receipts. A prevalue estimate is not a guarantee, so actual OS counters remain decisive.

The actual failed child has171 successful memory samples, zero monitor errors and terminal counters available. Kernel creation/exit times identify the measured lifetime. The observed RAM peak is169103360 bytes; read count53093251 includes imports and integrity checks, not just the sum of scientific file sizes. Metadata rendering does not retroactively enter those counters.

S9.31. Failed multinomial fusion: Synthetic checks and preparation provenance

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

Twenty final-source tests cover group separation, exact55-fit plan, paid-submask feature rights with poisoned unpaid inputs, complete-probability rejection, class alignment, one-axis reuse, prior/pooling rules, confidence/threshold ties, abstention costs, empty denominators, unrounded selection, accepted-union identities, a synthetic multinomial fit, convergence failure and selected archive keys. They validate mechanisms on fixtures; they cannot ensure convergence on a different real feature geometry.

Two additional checks cover output-size accounting and paired action transitions. Empty artifact lists are explicitly rejected by the independent author-side transport validator, closing a permissive edge in the inherited precheck. Final receipts pin the current scientific source bytes; earlier receipts remain preserved rather than overwritten.

A duplicate synthetic size invocation hit the existing-output guard after the first successful invocation. PREPARATION_DUPLICATE98.json retains the incident. It launched no actual experiment and read no real scientific payload. The actual launch remains singular and its nonzero termination is retained unchanged.

S9.32. Failed multinomial fusion: Metadata audit and report transport

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

The failure audit verifies all38 sealed source/metadata hashes unchanged, retained-HANDLE terminal exit1 with caps passed, exactly16 TUNE hashes/decodes and no X/CAL, a single fit-start entry, and absence of downstream output files. No private array is reopened and no alternative model is fit during reporting.

The source bundle contains all original code plus separately named metadata writers. The evidence bundle retains the exact Root release, original/final synthetic receipts, control checkpoints, failure logs and private-custody metadata. The latter contains only paths/hashes/access information and no arrays or model payloads.

The five-field SESSION_REPORT uses decision produced for implementation delivery and includes failed checks for55 converged fits and availability of the controlled comparison. Its artifacts are nonempty public contained paths, capped at16 and8MB. Root owns official Task completion, independent review and any next research authorization.

S9.33. Failed multinomial fusion: Six method areas and remaining work

Scope. One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes.

Algorithm exists as an explicit success/failure procedure with a renderable block; its intended performance path is unexecuted. Architecture exists as source/metadata preparation, release, one actual child, private access ledger, terminal freeze and metadata-only report. Complexity is specified for feature dimension and finite fit count, with actual first-fit resources; broader numerical scaling remains untested.

Evaluation is partial because no controlled prediction comparison occurred. Baselines are implemented but unmeasured here, with no fresh external adaptive benchmark or matched base-model capacity. Related work is partial: installed estimator source and inherited primary API/provider capture metadata support provenance, while a systematic current stacking/AFA comparison is absent.

The failure is a completed record, not a completed empirical answer. Any follow-up must preserve both the failed attempt and the earlier exposed-data limits, choose its numerical contract independently of CAL and establish actual useful-cost evidence before stronger claims.

Under a new Task and fresh contract/seal, separately diagnose and prespecify a numerically viable meta-fit rule before any further private fitting. Preserve this failure, do not reissue this actual call, and do not select solver/scaling/regularization settings using CAL. Any later efficacy study must distinguish useful-coverage-constrained gain, infeasible controls and the separate free-abstention $J<0.4$ comparison; an untouched participant evaluation and deployable adaptive baseline remain necessary for broader claims.

S9.34. Bias and simplex terminals: End-to-end method

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

Each fitting scope first fits seven calibrators and then four mixtures. The mixture weights see the same fitting rows used for those calibrators; this is a disclosed two-stage training procedure. The held-out participant pair enters neither stage. We select policies from held-out outputs only and report the all-TUNE in-sample shift only after choices are fixed.

The method holds class order 0..17 fixed and uses no subject ID at prediction. Subject identity defines the fitting weights, held-out splits and evaluation groups. A free prior class/confidence is eligible at mask 0 and in maximum-confidence selection; mean, log pool and convex mixtures exclude its unavailable full vector.

Algorithm S30. Participant-crossfitted 18-bias calibration and convex paid-submask probability mixture

Require: Fixed 18-class HGB probabilities for seven paid masks, ET saved class/confidence including the free prior, participant and row identities, and TUNE labels only during fitting. Four sorted held-out TUNE pairs, L 2=.01, floor 1 e-6, exact Newton and SLSQP settings; budgets 1/2/3, costs.05/axis, gamma.4 and useful coverage floors.

Ensure: Seven own-mask calibrators and four convex paid-submask mixtures,55 successful fit receipts or one explicit failed attempt. OOF-fixed mask/threshold choices, exposed CAL participant/class/fold diagnostics and distinct feasibility/useful-gain/free-abstention verdicts.

1 Verify source, installed implementation, exact 32-input metadata, resource and user-stop bindings against the Root release; import scientific libraries inside the one actual child.
2 Decode only 16 allowed TUNE archives and declared keys. Sort eight participant IDs and hold out adjacent pairs. Never decode X, TRAIN or FINAL. The offline evaluator may load the authorized cache bank; each policy may use only its paid-submask outputs.
3 For each of four folds, fit all seven class-bias calibrators on the other six participants using floor-smoothed log probabilities, equal-person log loss plus isotropic.01 L 2, zero-start damped Newton, analytic gradient/Hessian and Armijo backtracking. Require infinity-gradient<=1 e-8 within 100 iterations.
4 After that fold calibrators, fit each mask 3/5/6/7 convex mixture on the same training rows. Use only its calibrated nonempty submasks. Start uniform and call installed SLSQP once with analytic gradient, ftol 1 e-10 and maxiter 1000. Require success, feasible weights and FWgap<=1 e-4; project only <=1 e-8 raw roundoff.
5 Evaluate each held-out pair once. Repeat the same 11 fits on all eight TUNE participants. Single-axis mixtures exactly reuse own-mask bias outputs. No participant ID enters a prediction function.
6 Require 35 bias+20 simplex successful calls. Select each family/mask/threshold policy from held-out OOF predictions alone by unrounded J, then K, then -C, then policy ID. Freeze the entire journal and 117 choices durably before ANY CAL archive hash/value.
7 Apply the all-TUNE refit to TUNE only as an after-selection shift diagnostic, then read 16 CAL archives and evaluate the frozen choices. Charge purchased axes even on abstention.
8 Record paired transitions by participant/class/fold, common-acceptance controls, raw/calibrated expert-union C,V,F,G,E and descriptive paired subject bootstrap 2000 seed 10201. Return infeasible comparisons explicitly and evaluate J<.4 separately from useful-domain improvement.

S9.35. Bias and simplex terminals: Strongly convex 18-bias calibration

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

We apply fixed floor smoothing to all 18 class probabilities before fitting additive class offsets. Unlike scalar temperature scaling, these offsets may change the predicted class. The map is narrower than a full affine or multinomial transformation.

The Hessian is a participant-weighted sum of categorical covariance matrices plus the isotropic regularizer. Thus the objective is strongly convex and has a unique minimizer. The unregularized softmax term is invariant to a common offset; the regularizer makes the sum of class offsets zero at the exact optimum without selecting a reference class.

Minimizing the strong-convexity supporting quadratic gives the optimization-error bound below. The infinity-gradient tolerance implies an upper bound of 9 times 10 to the power minus 14 in exact arithmetic. Computed residuals are numerical diagnostics; they are neither confidence bounds nor guarantees of calibration on CAL.

Algorithm S31. Zero-start strongly convex class-bias Newton calibration
Require: An N by 18 probability matrix, training labels and participant IDs. epsilon=1 e-6, lambda=.01, max 100 Newton steps, gradient infinity tolerance 1 e-8, Armijo c=1 e-4, beta=.5, at most 60 backtracks from step 1.
Ensure: An 18-vector b and optimization diagnostics, or explicit no-retry failure.

1 Validate finite 18-class probability rows and nonempty labels. Set a_i=1/(P*n_person), ptilde=(1-epsilon)p+epsilon/18 and b=0.
2 Evaluate L(b)=sum_i a_i[-log softmax(log ptilde_i+b)_{y_i}]+lambda||b||²/2.
3 Compute g=sum_i a_i(q_i-onehot(y_i))+lambda b and H=sum_i a_i[diag(q_i)-q_i q_iᵀ]+lambda I analytically.
4 Stop only if max|g_j|<=1 e-8. Otherwise solve H d=-g, require a finite descent direction, and accept the first Armijo step among 1,1/2,... with at most 60 trials.
5 After at most 100 steps return only a passing fit. Record objective, gradients, all line-search decisions, bias sum and ||g||²/(2 lambda). A failure ends the actual attempt.

$$\tilde{p}_i = (1-\varepsilon)p_i + \frac{\varepsilon}{18}, \quad q_i(b) = \mathrm{softmax}(\log \tilde{p}_i + b)$$

The fixed smoothing constant is epsilon=10^-6; class offsets are fitted separately for each mask.

$$\mathcal{L}(b) = -\sum_i a_i \log q_{i,y_i}(b) + \frac{\lambda}{2} b^\top b$$

Each participant has equal total weight; λ=0.01.

$$H(b) = \sum_i a_i(\mathrm{diag}(q_i) - q_i q_i^\top) + \lambda I$$

The covariance term is positive semidefinite, hence the Hessian is bounded below by λ I.

$$\mathcal{L}(b) - \mathcal{L}(b^\star) \le \frac{g^\top g}{2\lambda}$$

Here g is the gradient at the recorded iterate. The bound concerns training log loss only.

S9.36. Bias and simplex terminals: Convex paid-submask mixture and an auditable certificate

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

For a multi-axis mask M, the eligible library contains every nonempty s subseteq M in ascending integer order, including M itself. There are 3 members at masks 3/5/6 and 7 at mask 7. Single-axis mixture outputs are exactly the own-bias outputs. The learned coefficients are one fixed simplex vector per purchased mask, shared across all prediction rows.

The mixture likelihood is an affine function of its weights, and negative log likelihood is convex on positive arguments. Smoothing and finite class offsets keep every training-label probability positive. The Hessian below is positive semidefinite. Multiple optimal weight vectors are allowed.

For any feasible alternative, the convex supporting-plane inequality lower-bounds its objective. Minimizing that plane over the simplex selects the smallest gradient coordinate, giving the displayed Frank–Wolfe gap. This proof is specific and self-contained. SLSQP success alone is insufficient: the recorded gap must also satisfy the fixed numerical tolerance. Neither condition certifies decision risk.

Installed SciPy 1.16.1 source, binary, local docstring and signature are hashed. The version-matched official SLSQP reference and latest 1.18.0 page were inspected on 2026-11-01. We supply derivatives and single-thread execution explicitly. The inspected docs describe solver tolerances; they do not certify our statistical model. [66, 67]

Algorithm S32. Single-call convex calibrated-submask probability mixture
Require: Calibrated training probability vectors from exactly the nonempty submasks of a purchased multi-axis mask, labels and equal-person weights. Installed SciPy 1.16.1 SLSQP; analytic gradient, uniform start, ftol 1 e-10, maxiter 1000; box and sum-one constraints.
Ensure: Nonnegative sum-one mixture weights, solver/raw/projected diagnostics and FWgap, or explicit failure.

1. For row i and eligible expert s define T_is as its calibrated probability of the training label. Minimize f(w)=-sum_i a_i log(sum_s w_s T_is) on the simplex.
2. Supply derivative g_s=-sum_i a_i T_is/(sum_t w_t T_it); use analytic equality-constraint derivative and no numerical differentiation workers.
3. Call SLSQP exactly once. Reject non-success or iteration-limit termination. Compute the Euclidean simplex projection but accept it only when the largest change from the raw result is<=1 e-8.
4. Require each projected weight in[0,1], sum within 1 e-12 and finite independent gap w · g-min_s g_s in[-1 e-12,1 e-4]. Log every raw and projected weight.
5. At inference use the same fixed weights to average all 18 coordinates of paid calibrated vectors. Predict the smallest-index argmax and compare confidence with the OOF-fixed threshold.

$$f(w) = -\sum_i a_i \log(T_i^\top w), \quad w_s \ge 0, \quad \sum_s w_s = 1$$

T contains the calibrated probability of each training label for the eligible nonempty paid submasks.

$$\nabla^2 f(w) = \sum_i a_i \frac{T_i T_i^\top}{(T_i^\top w)^2}$$

The simplex problem is convex, but its optimum need not be unique.

$$0 \le f(w) - f(w^\star) \le w^\top g - \min_s g_s$$

The last expression is the Frank–Wolfe gap. Exact inequalities are distinct from the declared floating-point tolerances.

S9.37. Bias and simplex terminals: Participant separation, selection and estimand

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

TUNE contains 7845 windows from 8 participants; CAL contains 6437 windows from 8 different participants. Repeated activity windows are not independent people. The four folds hold out adjacent pairs after sorting TUNE subject IDs and train on the remaining six. Within each fitting scope, a_i=1/(P*n_person), so every person has total mass 1/P even when window counts differ.

Five scopes each contain 7 bias+4 simplex calls:35 bias and 20 simplex, totaling 55. There is no hyperparameter search or retry. The actual child includes imports, source/input hashes, allowed decoding, optimization,66 output probability passes,35 training-calibration evaluations, all aggregate diagnostics and private/public serialization. Its one process is bounded by CPU 1800 s,wall 2400 s,observedRAM 2 GiB,read 512 MiB,write 256 MiB.

For each of 13 families and each budget 1/2/3, TUNE OOF chooses an unconstrained policy, a useful policy and an always-predict policy. Thresholds are 0,.05,...,1 and explicit all-abstain. Confidence>=threshold accepts. The criterion is unrounded equal-person J, then K, then minus C, then lexicographic policy ID. Always-predict considers only threshold 0. Useful selection enforces both empirical coverage floors.

A fixed purchased mask pays.05 per axis on every window, including abstentions. E is accepted wrong mass per all windows; selective error E/C is undefined when C=0. All-abstain at free mask 0 has J=.4 and C=0, outside the useful feasible domain. Strictly beating it is a separate criterion rather than a necessary definition of coverage-constrained gain.

S9.38. Bias and simplex terminals: Matched controls and attribution

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

The primary controls use exactly the same fold-specific and all-TUNE bias calibrators as the learned mixture: HGB_biasown, HGB_biasmean, HGB_biaslogpool and HGB_biasmaxconfidence. Arithmetic and geometric pooling combine only paid nonempty calibrated submasks. Bias maximum confidence includes the saved free prior. Its ties choose the smallest eligible mask.

Historical raw HGB own-mask, maximum confidence, arithmetic mean and clipped-log geometric pool remain unchanged as controls. Raw log pool uses log(max(p,1 e-6)); calibrated log pool uses log(q) directly because q is strictly positive. Saved ET own/maxconfidence, the free prior and all-abstain complete the menu. ET and HGB base capacity/compute are not matched new trainings.

We compare mixture versus calibrated own at the same paid mask, and compare each family's independently frozen OOF useful choice at each budget. A raw-to-bias comparison measures calibration-associated change; bias-to-mixture change isolates the added terminal combination relative to that control. Common candidate acceptance is applied to the reference prediction at the same mask as an additional diagnostic, keeping acquisition and acceptance fixed.

S9.39. Bias and simplex terminals: Actual process, custody and failure policy

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

The single actual process completed 55 prescribed optimization calls and the frozen development comparison.

The parent launcher retains the exact Windows process HANDLE through wait and records terminal CPU/I/O/exit counters. Memory is the largest observed live PeakWorkingSetSize and any available terminal observation; a final peak after the last sample may be missed. This is a watchdog and observed accounting, not an OS security or RAM isolation guarantee. Parent metadata rendering and native authoring are outside the experimental child counters.

The 32 input file paths, byte lengths and hashes come from predecessor custody metadata. Before release no NPZ payload is hashed or decoded. After release the whole snapshot archive is hashed, including compressed X bytes, but only y/subjects/row_index/window_id are decoded. Each probability file is checked for 18 class range, normalization, row order and saved argmax/maxconfidence agreement; ET reads only its saved enhanced class/confidence and row index.

Any nonconvergence, invalid probability/class/identity, material projection, large gap, unknown user-stop state, unknown process termination or resource violation fails the one attempt. The complete failure record remains scientific evidence. No fallback solver, refit retry or accepted/unknown call replay is allowed.

Table S95: Observed actual child counters and explicit execution counts. These exclude authoring and parent report construction.

Quantity	Observed
cpu seconds	153.453125
ram bytes	376139776
read bytes	131512984
wall seconds	184.846487
write bytes	79393599
Started calls	55
Completed calls	55
Input archive hashes	32
Input archive decodes	32
CAL hashes	16
CAL decodes	16
X decodes	0
Experimental model APIs	0

S9.40. Bias and simplex terminals: Development results and feasibility

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

The tables below report already-frozen TUNE choices on exposed CAL. A row with an infeasible CAL reference is labeled reference_infeasible; it is not evidence of a valid useful-domain win over that reference. A candidate that fails either CAL coverage floor is candidate_infeasible. When both are feasible, the unrounded sign of deltaJ determines improvement or no_gain; a tie is no_gain.

The extra stronger_joint_gate requires a feasible candidate and reference, lower candidate J and candidate J<.4. Its failure alone does not determine whether there was useful-domain gain. All flags use unrounded values; printed six-decimal cells are descriptive only.

Table S96: Primary calibrated families: TUNE OOF frozen useful choices.

Family	Budget	Frozen choice	TUNE J	TUNE C	TUNE min C	Useful
HGB mixture	1	HGB mixture:m2:t09	0.562608	0.580287	0.350187	True
HGB mixture	2	HGB mixture:m2:t09	0.562608	0.580287	0.350187	True
HGB mixture	3	HGB mixture:m2:t09	0.562608	0.580287	0.350187	True
HGB biasown	1	HGB biasown:m2:t09	0.562608	0.580287	0.350187	True
HGB biasown	2	HGB biasown:m2:t09	0.562608	0.580287	0.350187	True
HGB biasown	3	HGB biasown:m2:t09	0.562608	0.580287	0.350187	True
HGB biasmean	1	HGB biasmean:m2:t09	0.562608	0.580287	0.350187	True
HGB biasmean	2	HGB biasmean:m6:t08	0.550248	0.509854	0.272784	True
HGB biasmean	3	HGB biasmean:m6:t08	0.550248	0.509854	0.272784	True
HGB biaslogpool	1	HGB biaslogpool:m2:t09	0.562608	0.580287	0.350187	True
HGB biaslogpool	2	HGB biaslogpool:m3:t09	0.548892	0.511229	0.353933	True
HGB biaslogpool	3	HGB biaslogpool:m3:t09	0.548892	0.511229	0.353933	True
HGB biasmax-confidence	1	HGB biasmaxconfidence: m2:t09	0.562608	0.580287	0.350187	True
HGB biasmax-confidence	2	HGB biasmaxconfidence: m2:t09	0.562608	0.580287	0.350187	True
HGB biasmax-confidence	3	HGB biasmaxconfidence: m2:t09	0.562608	0.580287	0.350187	True

Table S97: The identical frozen choices on exposed CAL. Hollow plot markers denote CAL infeasibility.

Family	Budget	Frozen choice	CAL J	CAL C	CAL min C	Useful
HGB mixture	1	HGB mixture:m2:t09	0.538803	0.507772	0.361905	True
HGB mixture	2	HGB mixture:m2:t09	0.538803	0.507772	0.361905	True
HGB mixture	3	HGB mixture:m2:t09	0.538803	0.507772	0.361905	True
HGB biasown	1	HGB biasown:m2:t09	0.538803	0.507772	0.361905	True
HGB biasown	2	HGB biasown:m2:t09	0.538803	0.507772	0.361905	True
HGB biasown	3	HGB biasown:m2:t09	0.538803	0.507772	0.361905	True
HGB biasmean	1	HGB biasmean:m2:t09	0.538803	0.507772	0.361905	True
HGB biasmean	2	HGB biasmean:m6:t08	0.543879	0.444020	0.324594	False
HGB biasmean	3	HGB biasmean:m6:t08	0.543879	0.444020	0.324594	False
HGB biaslogpool	1	HGB biaslogpool:m2:t09	0.538803	0.507772	0.361905	True
HGB biaslogpool	2	HGB biaslogpool:m3:t09	0.555919	0.509146	0.447619	True

Family	Budget	Frozen choice	CAL J	CAL C	CAL min C	Useful
HGB biaslogpool	3	HGB biaslogpool:m3:t09	0.555919	0.509146	0.447619	True
HGB biasmax-confidence	1	HGB biasmaxconfidence: m2:t09	0.538803	0.507772	0.361905	True
HGB biasmax-confidence	2	HGB biasmaxconfidence: m2:t09	0.538803	0.507772	0.361905	True
HGB biasmax-confidence	3	HGB biasmaxconfidence: m2:t09	0.538803	0.507772	0.361905	True

Table S98: Separate useful-domain and stronger free-abstention decisions; candidate minus reference J.

Budget	Reference	CAL candidate useful	CAL reference useful	Comparison	Delta J	J<.4	Stronger joint
1	HGB biasown	True	True	no gain	0.000000	False	False
1	HGB biasmean	True	True	no gain	0.000000	False	False
1	HGB biaslogpool	True	True	no gain	0.000000	False	False
1	HGB biasmaxconfidence	True	True	no gain	0.000000	False	False
1	HGB rawown	True	False	reference infeasible	-0.002744	False	False
2	HGB biasown	True	True	no gain	0.000000	False	False
2	HGB biasmean	True	False	reference infeasible	-0.005076	False	False
2	HGB biaslogpool	True	True	improved	-0.017116	False	False
2	HGB biasmaxconfidence	True	True	no gain	0.000000	False	False
2	HGB rawown	True	False	reference infeasible	-0.002744	False	False
3	HGB biasown	True	True	no gain	0.000000	False	False
3	HGB biasmean	True	False	reference infeasible	-0.005076	False	False
3	HGB biaslogpool	True	True	improved	-0.017116	False	False
3	HGB biasmaxconfidence	True	True	no gain	0.000000	False	False
3	HGB rawown	True	False	reference infeasible	-0.002744	False	False




Figure S35: Frozen useful policies evaluated on exposed CAL. Dashed references are J=.4, macro C=.5 and min-participant C=.25. Filled markers meet both coverage floors; hollow markers fail at least one. The J=.4 baseline is outside the useful feasible set.

S9.41. Bias and simplex terminals: Paired recovery, calibration and uncertainty

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

For each selected/fixed policy the accepted-error identity is E=C−V+F−G. V is accepted mass where an eligible expert argmax is correct; F is accepted terminal error inside that union; G is accepted terminal

correctness outside it. We calculate both raw-HGB and calibrated-HGB expert unions, separately with and without the free prior. The identity is pointwise and holds per participant before averaging.

An expert-label selector has G=0 when its own eligible library is used. General probability fusion and even own-mask bias correction may have G>0. Thus raw expert-union size is not an arbitrary fusion ceiling, and positive G does not by itself establish a multi-expert gain. We preserve correction/harms by participant, true class and held-out fold, plus the candidate's common acceptance comparison. The frozen local methods/ DOCUMENT.json supplies the attributed methodological context.

The paired CAL bootstrap draws 8 participants with replacement 2000 times from the eight observed paired participant deltaJ values using NumPy seed 10201. It reports 2.5/97.5 percentiles. This is descriptive sensitivity to these exposed development participants. It neither resamples independent windows nor corrects repeated development exposure, multiple comparisons, model selection or the small number of people.




Figure S36: Public aggregate diagnostics only. Top: equal-mask, always-predict CAL deltaJ for raw-to-bias calibration and calibrated-own-to-mixture addition. Bottom: fixed mask7 mixture-minus-calibrated-own deltaJ per participant, with correctness gained/lost counts. Above zero is harm. This fixed-coverage diagnostic is separate from the frozen useful-policy comparison.

S9.42. Bias and simplex terminals: Exact prospective settings and no-search boundary

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

The fixed prospective knobs are epsilon 10^-6,λ.01,18 bias coordinates, Newton start 0,max 100,infinity-gradient 1 e-8,Armijo c 10^-4,beta 1/2,start 1,max 60 trials; SLSQP uniform start,ftol 10^-10,maxiter 1000,analytic gradients and equality Jacobian,bounds[0,1]. Only<=10^-8 max-coordinate simplex roundoff projection is accepted, with sum tolerance 10^-12 and independent FWgap<=10^-4. These are sealed before 102 TUNE access.

The installed NumPy/SciPy versions, SLSQP Python implementation and binary hashes, local docstring hash and signature are part of the environment seal. The official version-matched reference confirms the interface; the latest page is labeled 1.18.0 and is not substituted for installed 1.16.1 behavior. [66, 67]

There are no random optimization starts, candidate penalties, temperature grids, scaling alternatives, solver retries or learned subject-specific parameters. Failure ends this Task's single actual attempt. A future change requires a fresh contract and cannot retroactively rescue 102.

S9.43. Bias and simplex terminals: Derivations and interpretation

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

Write q_i=softmax(log ptilde_i+b) and a_i=1/(P n_person). The categorical log-likelihood derivative is q_i−e_y and the second derivative is diag(q_i)−q_iq_i^T. Adding λ b and λ I gives the implemented analytic gradient and Hessian. For any vector v, v^T[diag(q)−qq^T]v is the variance of the coordinates v_j under q, hence nonnegative.

The common-shift direction 1 satisfies the likelihood Hessian times 1=0 and likelihood gradient dot 1=0. The isotropic penalty therefore fixes the otherwise undetermined shift; the exact optimum bias sum is 0. This keeps all 18 class coordinates symmetric without dropping a reference class. Missing training classes remain represented and produce finite outputs from smoothing.

For mixture truth matrix T, each Hessian term is a nonnegative multiple of T_iT_i^T, proving convexity. On a simplex the minimum of a linear form is a smallest-gradient vertex; the supporting-plane inequality proves the recorded gap bound. Projection admission measures actual raw-to-projected coordinate change and records both; it is not a substantive repair or second optimization call.

The bias and simplex certificates concern the training objectives at their reported numerical points. They do not bound independent population log loss, maximum-confidence postselection calibration, accepted 0/1 error or J. The mixture's training inputs were fitted on the same training rows, so even a globally minimized mixture log loss is an in-sample meta-stage quantity.

S9.44. Bias and simplex terminals: Public lineage and input boundary

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

Input metadata is copied from frozen 98 evaluation/custody, whose original references identify the 87/93 custody records. The exact allowed set is 2 snapshots+16 ETprediction archives+14 HGBprobability archives, split 16 TUNE/16 CAL. The source seal contains metadata identities rather than prevalue NPZ hashes. After release each payload is hashed exactly once and decoded through selected-key access.

The predecessor 93 public independent audit reconstructed 704 TUNE candidates and 36 choices from cached results and described its HGB useful CAL coverage 0.4978925361520835 and J 0.541547058872187. These are inherited reports motivating the intervention; they are not 102 measurements or untouched evidence.98 supplies a separate numerical failure without CAL results. [local predictors/RESULT.json and predictors_review/independent_review.json]

Snapshot X may exist as compressed bytes inside the archive that is hashed. It is never accessed through NumPy. Model files, normalizers, raw recordings, TRAIN and FINAL are outside the allowed set. No imported predecessor actor starts private reads. The copied aggregation/Windows runner code is reengineered in this owned folder, with original source hashes in PROVENANCE 102.json.

S9.45. Bias and simplex terminals: Synthetic checks, size and execution accounting

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

The synthetic checks use fixed seeds 10200 and 10202 and are explicitly separate from actual study fitting. They compare bias gradients/Hessians and simplex gradients against central finite differences; test positive Hessian curvature, zero/one-hot/skew/missing-class calibration, equal-person duplication invariance, known simplex vertex/interior/identical-expert optima, solver failure and false-success gap rejection.

Boundary checks exercise exact paid submasks, free prior, sorted held-out pairs, probability class alignment, invalid/empty denominators, lowest-class and smallest-mask ties, cost on abstention, unrounded coverage floors, CAL-before-barrier rejection and selected NPZ keys without X. A miniature complete synthetic 55 call plan tests 35 bias+20 simplex fits. All synthetic fitting is labeled synthetic and contributes 0 to actual study fit counts.

The full-shape synthetic serializer writes 13713 policy records for TUNEall+4 folds, refitTUNE and CAL shapes using fabricated predictions/unions. Its bytes estimate write load; its scores are not empirical results. A separate retained-HANDLE no-op creates known I/O and exits, validating counter acquisition without private data. All preparation failures, if any, are retained rather than silently overwritten.

S9.46. Bias and simplex terminals: Historical controls and all frozen policies

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

Every family may use the same free mask 0 prior; the abstain family has only explicit free abstention. For each eligible paid mask, all 21 confidence thresholds plus explicit all-abstain are enumerated. All-abstain at a paid mask still incurs its purchased cost; selection can prefer the free action. The nonempty-only union at mask 0 is empty by definition.

Maximum-confidence combines saved class/confidence values with ascending-mask first argmax; exact ties choose the smallest mask including prior. Mean/log pool use ascending nonempty paid submasks and canonical class 0..17. A lowest-class first argmax resolves exact class ties. Same-mask, independently selected mask and common-acceptance comparisons answer different attribution questions and are labeled separately.

Table S99: Raw/historical controls on exposed CAL at frozen useful choices.

Family	Budget	Choice	J	C	Min C	Useful
HGB rawown	1	HGB rawown:m2:t09	0.541547	0.497893	0.311111	False
HGB rawown	2	HGB rawown:m2:t09	0.541547	0.497893	0.311111	False
HGB rawown	3	HGB rawown:m2:t09	0.541547	0.497893	0.311111	False
HGB maxconfidence	1	HGB maxconfidence:m2:t09	0.541547	0.497893	0.311111	False
HGB maxconfidence	2	HGB maxconfidence:m2:t09	0.541547	0.497893	0.311111	False
HGB maxconfidence	3	HGB maxconfidence:m2:t09	0.541547	0.497893	0.311111	False
HGB mean	1	HGB mean:m2:t09	0.541547	0.497893	0.311111	False
HGB mean	2	HGB mean:m3:t08	0.560812	0.520269	0.431746	True
HGB mean	3	HGB mean:m3:t08	0.560812	0.520269	0.431746	True
HGB logpool	1	HGB logpool:m2:t09	0.541547	0.497893	0.311111	False
HGB logpool	2	HGB logpool:m6:t09	0.554993	0.453816	0.339683	False
HGB logpool	3	HGB logpool:m6:t09	0.554993	0.453816	0.339683	False
ET own	1	ET own:m1:t06	0.591552	0.576890	0.390940	True
ET own	2	ET own:m1:t06	0.591552	0.576890	0.390940	True
ET own	3	ET own:m1:t06	0.591552	0.576890	0.390940	True
ET maxconfidence	1	ET maxconfidence:m1:t06	0.591552	0.576890	0.390940	True
ET maxconfidence	2	ET maxconfidence:m1:t06	0.591552	0.576890	0.390940	True
ET maxconfidence	3	ET maxconfidence:m1:t06	0.591552	0.576890	0.390940	True
prior	1	prior:m0:t00	0.944738	1.000000	1.000000	True
prior	2	prior:m0:t00	0.944738	1.000000	1.000000	True
prior	3	prior:m0:t00	0.944738	1.000000	1.000000	True
abstain	1	unavailable	unavailable	unavailable	unavailable	False
abstain	2	unavailable	unavailable	unavailable	unavailable	False
abstain	3	unavailable	unavailable	unavailable	unavailable	False

S9.47. Bias and simplex terminals: Paired participant, class and held-out-fold results

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

Paired counts treat abstention as action−1. Correctness gained equals wrong-to-correct plus abstain-to-correct; correctness lost equals correct-to-wrong plus correct-to-abstain. Counts, errors and denominators are retained per participant and true class. We also retain OOF paired fixed-mask comparisons separately within each held-out participant-pair fold.

The tables below focus on the budget 3 useful candidate versus calibrated-own comparator when available. They are a readable slice; the evidence bundle retains all budgets, criteria, fixed masks, primary comparators and common-acceptance outcomes. Zero-class denominators are never fabricated into rates.

Table S100: CAL paired participants, budget3 useful: mixture minus biasown.

Person	N	Delta J	Delta C	Delta E	Gained	Lost	Wrong to correct	Correct to wrong
1606	630	0.000000	0.000000	0.000000	0	0	0	0

Person	N	Delta J	Delta C	Delta E	Gained	Lost	Wrong to correct	Correct to wrong
1609	601	0.000000	0.000000	0.000000	0	0	0	0
1618	596	0.000000	0.000000	0.000000	0	0	0	0
1619	812	0.000000	0.000000	0.000000	0	0	0	0
1621	814	0.000000	0.000000	0.000000	0	0	0	0
1626	738	0.000000	0.000000	0.000000	0	0	0	0
1640	644	0.000000	0.000000	0.000000	0	0	0	0
1641	1602	0.000000	0.000000	0.000000	0	0	0	0

Table S101: CAL paired true classes for the same choices.

Class	N	Gained	Lost	Abstain to correct	Correct to abstain
0	355	0	0	0	0
1	374	0	0	0	0
2	357	0	0	0	0
3	356	0	0	0	0
4	355	0	0	0	0
5	355	0	0	0	0
6	411	0	0	0	0
7	355	0	0	0	0
8	355	0	0	0	0
9	355	0	0	0	0
10	355	0	0	0	0
11	355	0	0	0	0
12	359	0	0	0	0
13	320	0	0	0	0
14	355	0	0	0	0
15	355	0	0	0	0
16	355	0	0	0	0
17	355	0	0	0	0

Table S102: OOF held-out pair results at fixed mask7, always predicting, versus biasown.

Fold	Held-out IDs	Delta J	Delta E	Gained	Lost
0	[1610, 1611]	0.004785	0.004785	126	127
1	[1620, 1628]	-0.021961	-0.021961	159	110
2	[1629, 1631]	-0.086821	-0.086821	351	124
3	[1638, 1646]	-0.014950	-0.014950	171	160

S9.48. Bias and simplex terminals: Raw versus calibrated expert unions and refit shift

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

We calculate raw-HGB and calibrated-HGB argmax unions separately; adding free prior is a second axis. Calibration can move an expert's argmax and therefore change U,V,F,G even before mixture learning. Refit shift records mean and maximum absolute probability differences, mean confidence shifts and argmax changes between OOF and all-TUNE-refit outputs. It is computed after selection and cannot change a chosen threshold.

At the same fixed paid mask, raw-to-calibrated-own transitions are calibration-associated and calibrated-own-to-mixture transitions are added-combination diagnostics. At common candidate acceptance and same purchased mask, any correction/harms exclude an acquisition/coverage change. In independently frozen policies, acquisition mask, acceptance and terminal rule can all differ. No single G or F statistic establishes useful economic gain.

Table S103: CAL accepted raw/calibrated unions at each family's frozen budget3 useful choice.

Family	Union	C	V	F	G	E	Residual
HGB mixture	calibrated including prior	0.507772	0.244789	0.028929	0.000000	0.291912	0.000000
HGB mixture	calibrated nonempty only	0.507772	0.215860	0.000000	0.000000	0.291912	0.000000
HGB mixture	raw including prior	0.507772	0.242561	0.030620	0.003919	0.291912	0.000000
HGB mixture	raw nonempty only	0.507772	0.210821	0.001690	0.006729	0.291912	0.000000
HGB biasown	calibrated including prior	0.507772	0.244789	0.028929	0.000000	0.291912	0.000000
HGB biasown	calibrated nonempty only	0.507772	0.215860	0.000000	0.000000	0.291912	0.000000
HGB biasown	raw including prior	0.507772	0.242561	0.030620	0.003919	0.291912	0.000000

Family	Union	C	V	F	G	E	Residual
HGB biasown	raw nonempty only	0.507772	0.210821	0.001690	0.006729	0.291912	0.000000

Table S104: After-selection OOF-to-refit probability shifts.

Kind	Mask	Mean absolute	Max absolute	Argmax changed
bias	1	0.004855	0.141891	451
bias	2	0.005017	0.185906	555
bias	3	0.006929	0.204526	639
bias	4	0.004853	0.141838	468
bias	5	0.005757	0.253102	488
bias	6	0.005989	0.203929	528
bias	7	0.006561	0.194594	610
mixture	3	0.006414	0.132797	917
mixture	5	0.005063	0.127541	665
mixture	6	0.006462	0.127993	842
mixture	7	0.007041	0.134224	1007

S9.49. Bias and simplex terminals: Descriptive participant bootstrap and six-area completion

Scope. Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished.

For each available candidate/reference selected pair, all 2000 bootstrap replicates use the same pre-generated 2000 by 8 participant index draws so the subject resampling is paired across J comparisons. Percentile intervals describe the observed eight participant deltas only. The mean is the equal-participant deltaJ, not a pooled-window difference.

Method areas: algorithm exists as two-stage crossfitting plus inspectable optimizer blocks; architecture exists as release/rights/fit/CAL/resource boundaries; complexity exists as dimensioned bounds and observed counters. Evaluation remains partial because development has been exposed. Baselines remain partial because no external adaptive method or matched fresh base-model compute is reproduced. Related work remains partial because this Task inspects solver documentation and uses an attributed predecessor source comparison rather than reproducing external methods.

The bounded public evidence bundle transports all 117 selected policies and complete paired/fold/common-acceptance/bootstrap aggregates. The larger 13713-policy local aggregate file is audited record by record and pinned by exact path, byte size and SHA 256 in LOCAL_EVIDENCE_INDEX 102.json; it is retained locally rather than declared as a transported artifact. No private arrays/models or large synthetic serializer file is included in the public bundle. Public transport is therefore an inspectable aggregate subset, not a claim that every local record is shipped.

A separately authorized study must fix genuinely untouched participants, information rights, classes, budgets, virtual or measured costs, equal-person objective, useful coverage and participant floors, terminal actions, matched own-calibration/pooled and deployable adaptive controls, compute limits and one stopping rule before any evaluation access. Retain every failure, exclusion, harm and infeasible comparator. Require lower unrounded J beyond the calibrated controls at feasible useful coverage; evaluate J<0.4 separately. Do not tune these 102 parameters from CAL. No operational activation or new data collection is authorized here.

Table S105: Descriptive exposed-CAL participant bootstrap; candidate minus reference J.

Budget	Reference	Mean δ J	2.5%	97.5%
1	HGB biasown	0.000000	0.000000	0.000000
1	HGB biasmean	0.000000	0.000000	0.000000
1	HGB biaslogpool	0.000000	0.000000	0.000000
1	HGB biasmaxconfidence	0.000000	0.000000	0.000000
2	HGB biasown	0.000000	0.000000	0.000000
2	HGB biasmean	-0.005076	-0.023822	0.016471
2	HGB biaslogpool	-0.017116	-0.041962	0.006850
2	HGB biasmaxconfidence	0.000000	0.000000	0.000000
3	HGB biasown	0.000000	0.000000	0.000000
3	HGB biasmean	-0.005076	-0.023822	0.016471
3	HGB biaslogpool	-0.017116	-0.041962	0.006850
3	HGB biasmaxconfidence	0.000000	0.000000	0.000000

S10. Observable-history acquisition: every primary control and path

The primary terminal is the frozen calibrated confidence-.45 own-mask rule. The actor sees only paid-submask argmax/confidence bins. All data-based laws are person-weighted and coherent. The complete controls, support fallbacks, harmful transitions, purchases ending in abstention and terminal-changing diagnostics retain separate scope.

S10.1. Observable acquisition: Information rights and a coherent empirical world

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The evaluator holds complete counterfactual probability archives for masks 1 through 7. This offline custody is deliberately broader than deployed information. At paid mask M, the policy observes only an argmax class and a confidence bin for each nonempty submask ofM. The confidence cuts are fixed prospectively at .45,.60,.80; the smallest class index resolves argmax ties. No raw sensor values, unbought probability vectors, labels, subject identifiers or row identifiers enter the action function.

The history retains all paid-submask tokens, not only the newest own-mask output. For this experiment there are no modeled order-dependent prices, delays or purchase failures. Consequently, the paid mask and its accumulated tokens are sufficient for the declared decision model: two acquisition orders reaching the same paid observations have the same future feasible observations and losses. An order-dependent physical acquisition problem would require an expanded history; foreignW71 receipt/deadline/no-resend research is explicitly excluded here.

Each TUNE row is a complete possible world consisting of all mask tokens and its label. Its mass is 1/(P n_p), so selecting a participant uniformly and then a row within that participant reproduces the equal-person objective. Histories partition these same worlds. An acquisition transition refines the partition by revealing newly legal submask tokens, using the parent-normalized mass of its child cells. Conditional label errors and future-observation probabilities therefore arise from one joint empirical law, rather than independently optimized marginal extrema.

$$a_i = \frac{1}{Pn_{p(i)}}, \quad \hat{P}(H = h) = \sum_{i:H_i=h} a_i$$

The fitting distribution is an explicitly chosen equal-person empirical mixture; participant identity defines weights only during fitting.

$$\hat{P}(h' \mid h, a) = \frac{\sum_{i:H_i=h, H_i^a=h'} a_i}{\sum_{i:H_i=h} a_i}$$

Every child probability is a refinement of the same immutable row-world distribution.

S10.2. Observable acquisition: Fixed terminal loss, support and stopping

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

At a nonempty mask, the primary terminal rule returns that family's current-mask argmax if its calibrated maximum probability is at least .45 and otherwise abstains. It does not choose the label with the largest empirical conditional correctness. TUNE labels estimate the expected loss of this already fixed action: an accepted error costs 1 and abstention costs .4. The policy can stop with this action or purchase another distinct axis for .05. At the empty mask the terminal action abstains. Every previously paid query remains charged even when the final action abstains.

A state supports further acquisition only when its exact history cell contains at least 16 training rows from at least 2 training participants. Sparse or unseen states stop immediately with the same .45 terminal. We do not smooth, drop history components, or construct a new posterior after discovering sparse support. This purchase-veto fallback prevents unsupported branching and keeps the training conditional graph coherent. It also restricts the policy class and can discard useful opportunities. The threshold is a fixed design choice, not a validation-selected claim of sufficient sample size.

For a separately labeled empirical-stopping diagnostic, supported states may instead predict the current argmax when its fitted conditional error is strictly below .4. Ties abstain. Sparse/unseen states still use the .45 fallback. This diagnostic changes both stopping and acquisition, so its gain cannot establish the primary acquisition effect. In either mode, empirical fit quality supplies no uniform conditional-risk bound, and having two supporting training participants does not certify transport to a new person.

S10.3. Observable acquisition: Finite-history planning and exact scope

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The planning recursion compares stopping loss with .05 plus the empirical expectation of the downstream value for each unbought axis. Full depth equals the number of remaining possible purchases. The primary budget is 3 including the mandatory firstYpurchase, leaving at most 2 additional purchases; therefore anchored depth 2 and depth 3 must agree. Unanchored depth 3 is the actual complete three-purchase horizon. Myopic depth 1 and depth 2 replan after each newly purchased observation, using the same fitted graph, support restriction and terminal action.

In a finite acyclic graph formed by increasing paid masks, backward induction minimizes expected loss over policies measurable with respect to these quantized histories and obeying the support veto. This statement concerns the fitted point distribution and the declared terminal action. It does not establish optimality among policies using complete probability vectors, raw features, different terminal labels or unknown real-world distributions. Limited-horizon replanning need not have the root value of its initial truncated plan; its actual simulated decisions are evaluated directly.

At numerical action ties within 10^-12 the implementation prefers stopping and thenX,Y,Z. Fixed-order controls restrict the available purchase to the next unbought axis in their frozen order while retaining the same full remaining-horizon stopping calculation. This gives orders fair optional stopping. A fixed subset instead purchases its declared axes and applies the same terminal rule once; its unavoidable purchase cost is retained.

Algorithm S33. Observable joint-world acquisition with a fixed terminal rule
Require: Authorized TUNE_OOF counterfactual token trajectories and labels for fitting; fixed family, quantizer, support veto, .45terminal, budget and depth. At deployment only History(paidmask, paid-submask tokens); no row, label, subject or unbought value.
Ensure: Stop with the fixed current-mask prediction/abstention, or buy exactly one unbought axis. Locked graph/action maps and public aggregate end-to-end evaluation.

1. Assign equal-person TUNErow masses and group complete world trajectories by every paidmask/history.
2. For every state, record the fixed terminal-action loss and support. Build child masses by refining the same worlds after each admissible acquisition.
3. Use backward induction for full remaining horizon, and matched depth1/depth2 controls. PreferstopthenX/Y/Zwithin10^-12. Sparse/unseen histories cannot purchase.
4. Instantiate every frozen subset/order/dynamic configuration. Evaluate TUNEas training, select only the prespecified static/order controls and materialize every supported action map.
5. Durably hash the complete private policy and lock all comparisons before any CALstat/hash/read.
6. During CALsimulation, expose newly paid submask tokens only after purchase. Decide from Historyalone and charge.05for every distinct acquired axis.
7. After decisions are fixed, score errors, abstentions, coverage, costs, paired harms and all support/path branches; preserve infeasibility and no_gain.

$$V_{d,b}(h) = \min\left\{ \ell(h),\ \min_{a \in A(h)} \left[0.05 + \sum_{h'} \hat{P}(h' \mid h, a) V_{d-1,b-1}(h') \right] \right\}$$

For d=0, b=0 or purchase-veto states, only the terminal loss remains. The empirical graph is fixed before CAL.

S10.4. Observable acquisition: Controls and the frozen development protocol

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The two terminal families reuse 102 own-bias probabilities at all seven masks and its convex-mixture probabilities at multi-axis masks. At single-axis masks the mixture exactly reuses own-bias. We neither fit nor invoke a base predictor, recalibrator or mixture. Strong controls cover every affordable fixed subset, all six full-axis orders truncated by budgets 0 through 3, fixedY/.45, depth 1/depth 2/full planning, forcedY-first variants and global unanchored policies. Fixed subsets additionally include always-predict outputs to expose any benefit hidden by acceptance. The 416 configuration records include duplicate effective anchored orders and repeated budget policies; they are not independent experimental samples.

The primary comparisons are fixed prospectively: mixture/Y-first/full horizon at budget 3 against fixed calibratedY/.45 and the useful-feasible Y-containing subset and Y-first order selected from TUNE training.

Controls are selected by unrounded macroJ, then K, then larger C, then lexical policyID. A missing feasible training control remains missing. All global controls and the matched own-bias family remain available for inspection; the primary contrast is not chosen from CAL.

TUNE contains 8 participants and 7845 windows; CAL contains 8 different participants and 6437 windows. Both groups were historically exposed in earlier development. Existing 102 OOF means that each probability row was held out of a particular upstream fitting fold. It does not provide nested outer validation for this new policy learner: other probability rows and upstream fitting can depend on the would-be held-out person. We train one fixed policy rule on all TUNE OOF rows, perform no policy hyperparameter search, lock it, then evaluate once on reused CAL as exploratoryDEV. TUNE fitted scores are training scores. CAL also uses 102 all-TUNE-refit probability layers, preserving a training-view mismatch rather than pretending the OOF and refit views are identical.

S10.5. Observable acquisition: Real development outcome and useful coverage

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The frozen Y-first full-horizon policy had J=0.466022, C=0.310066, minimum-person C=0.211111 and K=1.426129. Relative to fixed calibratedY/.45, deltaJ=-0.072781; the useful-domain outcome is candidate_infeasible. Actual full-horizon and matched myopic aggregate results coincide; no additional nonmyopic gain was observed.

The loss reduction does not pass the useful-domain gate: the candidate fails both the macro .50 coverage floor and the .25 minimum-person floor. The TUNE-selected useful static comparator is the same fixedYsubset, so its primary contrast duplicates the anchor comparison rather than supplying independent evidence. No Y-first fair-order policy meets the useful TUNE training criteria; this missing primary comparator remains explicitly unavailable, while its unconstrained selected order and all individual orders remain reported. We do not replace it with a CAL-selected feasible order.

The strong TUNE-selected unconstrained Y-first fair order (mixture:B3:order 124:confidence 45:Y first) has CAL J=0.464206, compared with candidate J=0.466022. Candidate-minus-order deltaJ=0.001816; the candidate therefore has no raw-loss advantage over that order either. Both policies are infeasible. This comparison is retained as a separate strong-control diagnostic rather than turning their failed coverage into a useful-domain claim.

The primary candidate's E/C is 0.382958; its strict comparison with free all-abstention is False. The fixedYanchor has J=0.538803 and C=0.507772. Useful-domain status is calculated with both policies' macro coverage at least .5 and every participant's coverage at least .25. A lowerJagainst an infeasible reference is not labeled a useful-domain win. An infeasible candidate remains infeasible even if it reduces total loss.

The table uses unrounded values for every decision and printed six-decimal values only for presentation. Candidate-minus-reference differences are paired on exactly the same CAL windows and participant weights. J<.4 is displayed separately because free all-abstention has zero coverage and lies outside the useful-coverage domain. No feasibility constraint is imposed by the unconstrained Bellman recursion; reporting the floor honestly is part of the experimental result.

Table S106: Frozen policies on reused CAL DEV. Empirical stopping is a separate diagnostic, and Y-first is an explicit intervention.

Policy	J	C	Min person C	E/C	K	Feasible
mixture:B3:fixedY45	0.538803	0.507772	0.361905	0.574888	1.000000	True
mixture:B3:depth1:confidence45:Yfirst	0.466022	0.310066	0.211111	0.382958	1.426129	False
mixture:B3:depth2:confidence45:Yfirst	0.466022	0.310066	0.211111	0.382958	1.426129	False
mixture:B3:depth3:confidence45:Yfirst	0.466022	0.310066	0.211111	0.382958	1.426129	False
mixture:B3:depth3:confidence45	0.400000	0.000000	0.000000	undefined	0.000000	False
bias:B3:depth3:confidence45:Yfirst	0.508233	0.400114	0.271429	0.501254	1.354395	False
mixture:B3:depth3:empirical:Yfirst	0.437753	0.172619	0.106742	0.287310	1.144106	False
mixture:B3:static2:confidence45	0.538803	0.507772	0.361905	0.574888	1.000000	True
mixture:B3:order124:confidence45:Yfirst	0.464206	0.310586	0.202247	0.380636	1.404410	False

Table S107: Prespecified primary comparisons: candidate minus reference, with the fixed .45 terminal on both sides.

Reference	Delta J	Delta K	Delta E	Delta C	Both feasible	Outcome
mixture:B3:fixedY45	-0.072781	0.426129	-0.173170	-0.197706	False	candidate infeasible
mixture:B3:static2:confidence45	-0.072781	0.426129	-0.173170	-0.197706	False	candidate infeasible
TUNE useful Y-first fair order	unavailable	unavailable	unavailable	unavailable	False	no TUNE feasible control




Figure S37: Data-derived vector summary of fixed-terminal CAL loss, coverage and acquisition cost, with actual primary branch counts. No synthetic observations are mixed into this figure.

S10.6. Observable acquisition: Which paths corrected or damaged decisions?

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

A lower estimator error or a larger correctness union does not specify the mechanism of an end-to-end acquisition effect. We therefore retain every realized primary purchase path, its accepted errors and all query charges. The branch list includes purchases ending in abstention. Pooled path counts describe the observed windows; equal-person branch masses are reported separately because participants contribute different numbers of windows.

Paired corrections and harms below compare the candidate with fixedY/.45. A correction requires both policies to accept while the reference is wrong and the candidate is correct; a harm reverses those outcomes. Newly accepted correct and wrong predictions, removed correct and wrong predictions, and shared abstentions are kept separately. These are post-decision label-based diagnostics, never policy inputs. They cannot be used to define a favorable test subgroup or a future-label oracle acquisition rule.

The primary terminal-support counts are {"sparse": 1631, "supported": 3698, "unseen": 1108}. Queries spent on ultimately abstained windows total 6007. The candidate-minus-anchor loss difference decomposes into .05 deltaK=0.021306, deltaE=-0.173170, and -.4 deltaC=0.079082; its numerical identity residual is 6.94 e-17. This separates purchase expense, wrong accepted predictions and changed abstention rather than describing every lower loss as correction of expert mistakes.

Table S108: All actual primary paths. Axis codes1/2/4areX/Y/Z. Errors count only accepted wrong predictions; all queries are charged.

Path	Windows	Accepted	Errors	Queries	Macro mass	Macro error mass
2:abstain	3031	0	0	3031	0.463942	0.000000
2:predict	698	698	190	698	0.113542	0.026895
2>1:abstain	996	0	0	1992	0.153965	0.000000
2>1:predict	925	925	425	1850	0.150727	0.067527
2>1>4:predict	25	25	3	75	0.003612	0.000234
2>4:abstain	492	0	0	984	0.072026	0.000000
2>4:predict	270	270	156	540	0.042186	0.024086

Table S109: Paired movements relative to fixedY/.45. Corrected/harmed restrict to rows both policies accepted.

Event	Pooled count	Equal-person mass
both abstain	3148	0.481709
both predict	1849	0.299547
corrected	118	0.018236
harmed	45	0.007561
new correct	53	0.007661
new predictions	69	0.010519
new wrong	16	0.002858
removed correct	287	0.042872
removed predictions	1371	0.208225
removed wrong	1084	0.165352

S10.7. Observable acquisition: Architecture, custody and single-attempt execution

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

Public metadata from 102 custody, its pre-value seal and the independent 104 input ledger specify 24 exact inputs: eleven probability archives and one identity/label snapshot for each partition. Only probabilities/ classes or y/subjects/row_index/window_id are decoded. Snapshot integrity hashes cover the complete compressed archive, including compressedXbytes; X members are never accessed or decoded. No raw/TRAIN/ FINAL/TUNE_REFIT/model/pickle file enters this experiment. These bindings establish the bytes reused here, not independent reproduction of original data collection, model fitting or upstream historical exposure.

The deployed DecisionRule.decide interface accepts only History. A separate ObservationBank owns full authorized counterfactual arrays for offline simulation and reveals a token only after its mask has been purchased. Fitted models contain aggregated state losses and child masses, not participant identifiers as action inputs. Complete model/action maps and row-level decision arrays remain private. Public results contain indexed participant counts and compact path/paired aggregates only.

One retained-HANDLE Windows child completed with CPU60.953 s, wall 63.726 s, observedRAM238.60 MiB, read 42370015 bytes and write 6266760 bytes. The limits were CPU600 s/wall 900 s/observedRAM2 GiB/ read 512 MiB/write 128 MiB. Terminal process CPU/I/O counters and the retained creation/exit identity are preserved. Sampled memory is not OS isolation and can miss a final peak. Native authoring, report rendering, earlier base fitting, host activity and physical sensor acquisition are outside these counters. No experimental model API call was made.

Table S110: Graph/support and observed terminal fallback. Support counts refer to training states; terminal counts refer to actual primary CAL paths.

Family	Training states	Supported states	State/action groups
bias	21125	224	14419
mixture	15600	283	9226

S10.8. Observable acquisition: Complexity and matched computation

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

Let N denote training rows, G the number of axes, L the number of classes, S observed quantized history cells, and T observed parent-child transition entries. Building argmax/confidence tokens costs O(N L 2^G) time and O(N 2^G) token storage when every nonempty mask is available. Grouping accumulated histories uses at most O(N G 3^G) token work with the direct implementation; summed over masks, the number of paid-

submask token positions is 3^G-2^G. The experiment has G=3 and L=18, and supplies no asserted scalable solution for hundreds of feature groups.

For one terminal rule and horizon configuration, cached finite-graph planning costs O(S+T), with bounded G, horizon and order choices, and stores O(S+T) values and edges. Materializing the prespecified horizons and orders multiplies this by their fixed configuration count. Exporting the complete graph and maps is included in the measured scientific child. A deployed decision uses a history-key lookup and an already computed action; the direct simulator additionally constructs at most 2^G-1 paid-submask tokens per observation.

All controls use exactly the same probability archives and training distribution. Static controls need fewer planning operations but the same terminal cache; orders restrict available actions instead of receiving cheaper or more informative predictors. We report the aggregate one-child resource cost, not per-policy inference benchmarks or measured sensor energy. The numerical benchmark therefore isolates decisions under matched cached information and virtual prices, while leaving physical acquisition and modern large-scale AFA reproduction unresolved.

S10.9. Observable acquisition: Exact state, terminal and action definitions

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

Encode each token as 4 times the smallest-index argmax plus its confidence bin 0,1,2,3. Bins are left-inclusive at .45,.60,.80 via searchsorted(side=right), so a maximum probability exactly .45 is accepted and .449999 is rejected. Nonempty submasks are listed in ascending integer order, which places the current mask last. The history constructor rejects the wrong number of tokens or values outside the 18 class/four-bin alphabet. Mask 0 has an empty tuple and no prior prediction vector.

For a supported state and fixed-terminal mode, terminal loss is the equal-person conditional accepted-error frequency if bin>=1 and .4 otherwise. Sunk purchase cost is excluded from this local terminal comparison and added exactly once by each transition. For empirical-stopping mode only, compare conditional current-argmax error with .4; use a strict less-than rule and abstain on ties. An unknown history has no fitted conditional distribution and cannot be expanded. Sparse state losses remain computed from the same row-world law, but those cells may not purchase further.

State merging ignores purchase order only because this experiment assumes identical unit prices, deterministic successful acquisition and no deadlines. All previously purchased submask outputs remain in the merged token history. The simulator never reconstructs an unbought token for the action function. Hidden complete trajectories are used to train the empirical law and to reveal outcomes after a simulated purchase, which is a disclosed full-counterfactual offline setting.

S10.10. Observable acquisition: Backward induction, fixed orders and limited lookahead

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

For a state with remaining budget b, terminal risk ell and supported outgoing edges, compute each purchase value as .05 plus the normalized-mass sum of child values at budget b-1 and depth d-1. At depth zero use terminal risk. Recursion strictly increases mask cardinality, so there is no cycle. Memo keys include mask, exact token tuple, remaining budget, depth, order restriction and terminal mode. The finite-horizon optimum follows by conditioning on the first action and applying the inductive optimal child rule.

Before CAL, the implementation materializes every supported state's action for every reachable remaining budget and each prespecified depth/order/terminal mode. All graph states, transitions, terminals and action maps are written to a private deterministic gzipJSON. Sparse states have the explicit no-buy fallback and need no learned purchase map. CAL is forbidden to create a new memoized supported action; the frozen map-count invariant is checked after its evaluation. This locks the full learner rather than merely a best-policy identifier.

A fixed order chooses the first not-yet-purchased axis in its permutation; it may stop before buying it. Y-firstforcesYat the empty history, after which anyYentry in the order is skipped. Different three-axis permutations can therefore induce the same anchored remaining order. Their configuration records remain in the complete aggregate file, but neither their count nor the 416 total configurations is used as a sample size. The independent grouping unit for descriptive uncertainty is the participant.

S10.11. Observable acquisition: Full control inventory and training selection

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

For each family and budget, enumerate every fixed subset with cardinality at most the budget under empirical, fixed .45 and always-predict terminals. Enumerate all six orders for fixed .45 and empirical terminals, both unanchored andY-first. Enumerate depths 1,2,3 with the same two terminals and two anchoring conditions. Add fixedY/.45 at each budget. Budget 0 policies all abstain without a query; fixedYbuys only if its budget permits. No duplicate axis is purchased to create a fictitious larger budget.

The control-selection ledger is complete in NUMERICAL_RESULTS107.json. For each terminal/family/budget/anchoring condition, select static and order controls separately in unconstrained and useful-training domains. Anchored static controls must containY; anchored orders forceY first. Selection uses training macroJ,K,-C,ID. No selected candidate hyperparameter changes, no held-out TUNE policy score is claimed, and no CAL outcome influences control identities.

The table below presents all fixed .45 Y-first full-horizon budget/family outcomes. The complete 416 configuration metrics for both partitions remain in the aggregate JSON rather than being reduced to only favorable table rows. Empty denominators are null, every infeasible comparison remains labeled, and empirical-stop rows are never pooled with fixed-terminal acquisition evidence.

Table S111: Every fixed-terminal anchored full-horizon budget/family result on CAL.

Family	Budget	J	C	Min C	K	Feasible
bias	0	0.400000	0.000000	0.000000	0.000000	False
bias	1	0.538803	0.507772	0.361905	1.000000	True
bias	2	0.508233	0.400114	0.271429	1.354395	False
bias	3	0.508233	0.400114	0.271429	1.354395	False
mixture	0	0.400000	0.000000	0.000000	0.000000	False
mixture	1	0.538803	0.507772	0.361905	1.000000	True
mixture	2	0.465842	0.310066	0.211111	1.422517	False
mixture	3	0.466022	0.310066	0.211111	1.426129	False

S10.12. Observable acquisition: Loss identities and descriptive uncertainty

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

Within participant p, C_p is accepted count divided by n_p, E_p is accepted-error count divided by n_p, and K_p is acquired-axis count divided by n_p. J_p=.05 K_p+E_p+.4(1-C_p). Macro metrics average these participant quantities uniformly. The reported macro selective-error ratio is E/C, while individual selective-error ratios are also retained and may be undefined. It is not an unweighted average of the participant ratios. Pooled metrics divide summed counts by all windows and may differ from macro metrics.

For candidateaandreferenceb, deltaJ=.05 deltaK+deltaE-.4 deltaC. The implementation checks this identity to 10^-12 and preserves all components. Correction and harm counts require shared acceptance. New/removed acceptance cells explain why the net error difference need not equal corrections minus harms. Every branch's pooled query count includes all purchases on rows that later abstain.

For every prespecified paired comparison, resample the eight participant-level deltaJvalues with replacement 2000 times using seed 10701 and retain 2.5/97.5 percentiles. The same predetermined seed and count are applied without selecting intervals. These are descriptive sensitivity summaries for eight reused development participants, not calibrated confidence intervals for a population or independent confirmation. Correlated windows are not resampled as independent participants.

Table S112: Primary participant differences against fixedY/.45; indexed aggregates disclose no row-level predictions.

Person index	Delta J	Delta K	Delta E	Delta C
0	-0.098413	0.412698	-0.179365	-0.150794
1	-0.077704	0.482529	-0.183028	-0.202995
2	-0.065520	0.374161	-0.145973	-0.154362
3	-0.040825	0.385468	-0.142857	-0.206897
4	-0.053317	0.525799	-0.189189	-0.273956
5	-0.078252	0.353659	-0.173442	-0.193767
6	-0.070963	0.462733	-0.169255	-0.187888
7	-0.097253	0.411985	-0.202247	-0.210986

S10.13. Observable acquisition: Synthetic checks kept separate from real development results

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

Thirteen public synthetic checks passed before the input release. A complementary two-axis fixture makes myopic acquisition stop while depth 2 buys; a three-way fixture makes unanchored depth 2 stop and depth 3 buy. After a forcedYpurchase the three-way fixture requires both remaining axes, so depth 1 stops while depth 2 anddepth 3 agree. A separate perfect-single-axis fixture verifies that dynamic planning ties the strong fixed control and refuses useless additional purchases.

Boundary checks cover paid-submask rights, duplicate-purchase rejection, class and action ties, empty input rejection, no-budget abstention,16 row/2 person support veto, unseen histories, complete query cost on abstention and paired correction/harm identities. The deployed action signature is checked to contain onlyHistorybesides self. Unbought token changes leave identical prefix histories and actions unchanged.

The complete executeentry is tested with 24 synthetic archives and an Xmember that cannot be decoded under allow_pickle=False. Before the TUNE lock, CAL path access and a request forXare rejected without reading bytes. A second complete entry with altered CAL labels and participant identities preserves all 416 policy decision/cost/mask arrays and frozen control choices while evaluation errors change. These checks test the actual scientific path but are author tests, not independent validation. Their synthetic rows and metric tables are never merged with the real development result.

S10.14. Observable acquisition: Source and resource accounting

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The source seal binds policy 107.py,test_policy 107.py,launch 107.py,prepare 107.py,the final proposal,evaluation_contract.jsonand the actual TASK. A Root release binds that seal to Tasktask_d 031 ed 79 db 33,Runrun_edf 0173 ced 28 and nativeexecutor/root/probeflow_observable 107. A retained-HANDLEnoop verifies terminal CPU/I/O and memory observation before one actual child. The launcher is an isolated copy of reviewed 104 mechanics with the original lineage hash retained; there is no new detached process supervisor or retry path.

Actual child accounting includes library imports, source/input integrity checks, selected-key decoding, graph fitting, all policy simulations, action-map export, paired diagnostics and serialization. Whole compressed snapshot hashing reads compressedXbytes for integrity; X decode remains zero. Native authoring, public metadata preparation and this editorial report generator are outside the child counters and remain unmeasured. The report generator reads only public aggregates and process receipts, never the private policy or decision arrays.

The original upstream probabilities are accepted through their fixed archive hashes and public custody records. This experiment does not re-audit all original base training, data collection, user-provided licenses or historical FINALexposure uncertainties. The control gate is checked at phase boundaries. A child failure or a resource violation remains a failure with no source change and no relaunch. A completed numerical child is not by itself scientific certification, a publication submission, operational deployment or scheduler adoption.

S10.15. Observable acquisition: Primary-work compatibility and proof boundaries

Scope. Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL.

The following comparisons summarize the primary-source reading scopes inherited from 99. Version identifiers and inspected sections are retained in the reference records. The proposed compatibility adaptations are not completed implementations, and no runtime or accuracy from another paper is entered into our own performance table.

Table S113: Information, fitting and decision compatibility with primary works.

Work	Information	Fitting separation	Decision	Compatibility limit
SL2007	Base-prediction library	V-fold meta-learning	Weighted combination	No acquisition policy reproduced
CSL2019	Covariates plus expert library	Cross-validation and iterative expert refit	Conditional routing	Paid-only covariates; refits absent here
DES2018	Query profiles and reference neighborhood	Pool/meta/DSEL structures	Competence selection and vote	No unbought dimensions in a fair adaptation
SGR2017	Fixed predictor confidence	Labeled selection under stated IIDsetting	Risk-bound rejection	Our threshold has no inherited guarantee
GUO2017	Model logits	ValidationNLL	Post-hoc scaling	LowerNLLdoesnotproveacquisitiongain
GSM2021	Acquired state and missing-feature model	Surrogate/policy/prediction training	Sequential acquire/stop	Freshmodelsandmatchedcostneeded

Work	Information	Fitting separation	Decision	Compatibility limit
ACO2024	Acquired state and conditional law	Approximate oracle/cloning	Nonmyopic subset choice	No label-informed deployment oracle
AFAPE2025	Retrospective histories	Cross-fitted nuisances	Counterfactual policy evaluation	Identification/support-notestablishedhere

Table S114: Guarantees cannot be transferred by name.

Work	Inspected guarantee scope	Assumption or unresolved boundary
SL2007	Author-reported asymptotic oracle comparison	Abstract-only source scope; not audited proof
CSL2019	Conditional-oracle/rate statements	IID,function/loss/complexity assumptions
DES2018	Empirical meta-selection study	No paid-history risk guarantee established
SGR2017	Desired-risk bound under its procedure	IIDlabeled-selection and bound search premises
GUO2017	Empirical post-hoc calibration methods	No automatic conditional-risk guarantee
GSM2021	Model-based acquisition framework	Surrogate/model adequacy; full theory not audited
ACO2024	Conditional acquisition oracle formulation	Unknown joint distribution/search approximation
AFAPE2025	Identification/estimation assumptions	NUC,NDE,positivityandcross-fitting

S11. Nominal coverage optimization: full expected outcomes and costs

These finite-library mixtures use one independent coin shared across people and cases. Coverage is imposed after convexification. TUNE outcomes use upstream out-of-fold probability views; CAL uses the all-TUNE refit. Fractional expected counts describe the coin and are not new observed physical episodes. Unidentifiable intersections are left unidentifiable.

S11.1. Nominal common mixtures: Public input, data identity and inherited exposure

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The only numerical data source is public NUMERICAL_RESULTS107.json, SHA256 e946082872ba 332d83f992efc310f1b85e3ee2dadb5b8cfb05143543873ee945. It contains 416 configuration records per partition, including duplicates of effective policies, together with per-person counts and aggregate route summaries. We reconstruct C, E, K and J from public integer accepted/error/query counts and verify the published rates before solving. Configuration count and window count are not independent sample sizes.

The data lineage is inherited from the frozen public DATASET_LINEAGE106 record: WISDM, Gary Weiss (2019), UCI 507, CC BY4.0, DOI10.24432/C5HK59, with upstream member prefix wisdm-dataset/raw/ phone/accel/. The logical X/Y/Z axes are co-recorded phone accelerometer axes, not three independently measured physical sensor energy budgets. The original dataset download, licence, extraction, partition formation and fitting are not independently reproduced here.

TUNE has eight participants and 7,845 windows; reused CAL has eight different historical participants and 6,437 windows. Source 107 used TUNE OOF predictor layers for policy fitting and all-TUNE-refit layers for CAL, leaving a training-view mismatch. These inherited OOF rows do not provide nested outer validation for the new policy mixture. Historical FINAL exposure is not globally excluded by the public lineage, and CAL has already been used in development.

Hashing and decoding the combined public JSON exposes its CAL bytes. Our selector accesses only TUNE_training, and selected weights/checks are durably frozen before CAL metric calculation; this is a computational selection boundary, not fresh blinding. The original publication, reviews and all prior source bytes remain unchanged.

S11.2. Nominal common mixtures: Exact libraries and matched information rights

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The primary static library contains the four B3 mixture/confidence45 subsets whose final masks contain Y: 2,3,6,7; all six first_y=true conditional early-stop orders; and the fixedY45 anchor. These are eleven exact source IDs. The enriched library is their union with the three first_y=true depth1, depth2, depth3 configurations, for fourteen IDs. It is the available frozen library, not all mathematically possible early-stop fixed-order policies or all dynamic policies.

Every primary policy uses the same already fitted mixture predictor and accepts its current-mask argmax iff confidence is at least .45. Acquiring a distinct axis costs .05; total budget is three axes including mandatory Y. Further decisions in source107 use only tokens of already paid submasks, with the original sixteen-row/ two-person purchase-support veto and sparse/unseen fallback. Neither this optimizer nor its policy coin is allowed to inspect labels, participant IDs or unbought token values during deployment.

The source static-subset implementation visits selected axes in sorted X, Y, Z order. Reordering a terminal-only Y-containing subset to buy Y first preserves its terminal mask, retained paid-submask history and total cost under the inherited deterministic-success, equal-price, no-deadline assumptions. This is an explicit conditional outcome equivalence. It does not permit the same reinterpretation under failures, order-dependent prices, transient observations or deadlines.

Anchor/static2, forced-Y permutations with the same remaining order, and anchored depth2/depth3 are prespecified semantic aliases. We retain their exact IDs and verify matching group metrics. No duplicate configuration is counted as independent evidence or given an extra statistical weight. Equality of depth1 with a deeper policy in the actual source is an empirical tie, distinct from the forced-horizon depth2/depth3 equivalence.

Two secondary libraries preserve the unanchored confidence45 catalogue and the anchored empirical-terminal catalogue. Their constraints and randomization are computed separately. Empirical stopping changes the terminal decision as well as acquisition; unanchored policies can avoid Y. Neither diagnostic silently replaces the matched primary comparison.

Table S115: Primary library composition. Exact source IDs and semantic aliases are preserved in the Supplement.

Policy family	IDs	Library
Fixed subsets containing Y	4	Static and enriched
Forced-Y early-stop orders	6	Static and enriched
Fixed-Y anchor	1	Static and enriched
Adaptive depths 1, 2 and 3	3	Enriched only

S11.3. Nominal common mixtures: A common-mixture finite-library problem

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Let g index the P observed fitting participants and j index a frozen library policy. C_{gj} is the fraction of accepted windows; E_{gj} is the fraction of all windows that are both accepted and wrong; K_{gj} is the mean number of paid axes. J_{gj} includes all paid axes even if the terminal action abstains. A bar denotes the equal-person mean, not a pooled-window average.

Choose a single nonnegative weight vector w whose entries sum to one. Before seeing each case, draw j from w using an independent coin, then execute policy j. The same w applies to all subjects. Conditional on the frozen per-policy empirical rates, iterated expectation gives C_g(w), E_g(w), K_g(w) and J_g(w) as the corresponding weighted sums. No raw joint trace is required for these marginal expectations.

The feasible set is a compact polytope. If it is nonempty, a linear objective has an optimal solution. Conversely, any common independent policy mixture corresponds to one feasible vector with exactly these expected rates. Therefore the LP solves the declared finite-library common-mixture problem, subject to numerical solver tolerance. It does not solve a larger class merely because its component policies were originally produced by a Bellman planner.

Algorithm S34. one universal policy coin under fitted useful-coverage constraints
Require: Frozen public107 per-policy, per-participant integer counts; exact predeclared policy IDs and configurations TUNE groups; acquisition price .05; abstention loss .4; mean floor .50 and every-person floor .25
Ensure: One common static-library mixture and one common enriched-library mixture, or explicit infeasibility Durable TUNE selection lock, numerical primal/dual certificates and fixed-mixture reused-CAL expectations

1. Validate policy IDs/configurations, participant denominators, count/rate identities and prespecified semantic aliases.
2. Construct J and coverage columns from TUNE counts only. Keep every component, even individually infeasible ones.
3. Solve both constrained finite-library LPs. On the numerical optimum face minimize K, maximize C, then maximize weights by ascending policy ID.
4. Check primal residuals, dual signs, reduced costs, complementarity and an independently feasible dual lower bound. Preserve phase-I infeasibility.
5. Compute deterministic feasible and unconstrained controls. Compute the separately labelled TUNE-person-informed oracle bound.
6. Poison every non-TUNE selection input and require bitwise JSON equality of all selected weights/checks.
7. Write and hash the complete TUNE lock before constructing or validating CAL metrics. The combined public JSON has already exposed CAL bytes.
8. Evaluate the locked common mixtures by linear expectation on reused CAL. Report both policies' floors, ratios, participant differences and all query charges.
9. A deployment interpretation draws one independent policy index before each case and executes that frozen policy; no participant ID or future value selects the coin.

$$J_{gj} = 0.05K_{gj} + E_{gj} + 0.4\big(1 - C_{gj}\big)$$

E is unconditional accepted-error mass; every acquisition remains paid.

$$\overline{J}(w) = \sum_j w_j \overline{J}_j, \quad C_g(w) = \sum_j w_j C_{gj}$$

A single coin distribution, independent of group and values, makes the expected metrics linear.

$$\min_{w \geq 0} \sum_j w_j \overline{J}_j$$

The mean and all observed TUNE-person coverage floors couple the policy choices globally.

$$\sum_j w_j = 1$$

The same nonnegative mixture weights sum to one.

$$\sum_j w_j \overline{C}_j \geq 0.50$$

The equal-person expected coverage must be at least 0.50.

$$\sum_j w_j C_{gj} \geq 0.25$$

Every TUNE person has expected coverage at least 0.25.

S11.4. Nominal common mixtures: Certificates, information-expanded bounds and omitted policies

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Write the coverage matrix as D with its mean row followed by person rows and the floor vector as f. The implementation passes A=-D and b=-f to SciPy, so all inequalities have the required upper-bound form. For a minimization problem its reported inequality marginals y are nonpositive. With equality marginal z, reduced costs are c-A^Ty-z; nonnegative reduced costs and y≤0 give the dual lower bound b^Ty+z. Primal feasibility, weight normalization, complementarity and the primal-minus-dual gap are checked independently from the solver success flag. [73]

The published lower bound additionally clips y towards zero and replaces z by the smallest component of c-A^Ty. This produces a dual-feasible bound for the floating-point coefficient matrix without trusting a slightly negative solver reduced cost. All residuals and objective shifts are retained unrounded. These checks are numerical certificates for this matrix; they are not exact rational proofs of the public-data optimum or population risk certificates.

For infeasibility, a phase-I LP adds a shared nonnegative coverage relaxation t and minimizes it. A positive primal optimum with a positive feasible dual lower bound certifies that every common mixture needs at least that much uniform relaxation, within the recorded numerical tolerance. We preserve unavailable deterministic comparators rather than substituting a CAL-selected one.

A separate TUNE-only oracle permits one weight vector for each known fitting person while retaining the same catalogue and coverage floors. It can condition on training-person identity, unlike the deployable universal coin. Its lower objective bounds the cost of the common-distribution restriction within that catalogue. A small oracle gap would not identify missing observable conditional signal, and a large gap would not supply a group identifier or future-person policy.

For any larger class containing the library under the same Y-for-every-case constraint, its unknown constrained optimum cannot exceed a feasible library solution. Also J≥.05 because every case pays for Y and the other terms are nonnegative. Thus a coarse all-policy gap bound is at most library J minus .05, conditional on feasibility and class inclusion. We do not estimate the true approximation gap to omitted policies. The .05 lower bound does not apply to unanchored/no-purchase classes; their generic lower bound is zero.

$$A = -D, \quad b = -f, \quad y \leq 0, \quad c - A^T y - z1 \geq 0$$

The dual feasibility signs follow from the minimization/upper-bound convention.

$$b^T y + z \leq c^T w, \quad z_{\text{safe}} = \min_j \Big(c_j - (A^T y)_j \Big)$$

Weak duality gives a finite-library objective lower bound for any feasible primal/dual pair.

Table S116: Constrained floating-point objective or phase-I relaxation, with independent dual bounds

Library	Method	Status	Primal	Dual bound	Gap
empirical terminal diagnostic	adaptive	infeasible	0.137622563811	0.137622563811	0.000000000000
empirical terminal diagnostic	static	infeasible	0.137622563811	0.137622563811	0.000000000000
primary	adaptive	numerically certified	0.528717373347	0.528717373347	0.000000000000
primary	static	numerically certified	0.530337707107	0.530337707107	0.000000000000
unanchored diagnostic	adaptive	numerically certified	0.539392819100	0.539392819100	0.000000000000
unanchored diagnostic	static	numerically certified	0.539392819100	0.539392819100	0.000000000000

Table S117: TUNE-only known-person oracle; information is expanded relative to the universal coin

Pool	Common J	Person oracle J	Oracle lower bound	Common minus oracle
adaptive	0.528717	0.520351	0.520351	0.008366
static	0.530338	0.521545	0.521545	0.008793

S11.5. Nominal common mixtures: Selection, ties and the single-attempt protocol

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Exact IDs, configurations, floors, objective, diagnostics, resource limits and tie handling were fixed before reading the numerical source in this study. Preparation used public contracts, source code, reviews and inherited manuscript evidence. Synthetic tests include an independent Fraction vertex enumerator, meaningful infeasibility and dual perturbation checks, duplicate/missing records, paid abstention, and a full-shaped entry fixture covering selection, lock, evaluation and manuscript schema.

The selector first minimizes J. It then fixes that numerical optimum with an equality, minimizes K, fixes it, maximizes C, and lexicographically maximizes weights in ascending exact policy-ID order. HiGHS uses 10^-9 primal/dual feasibility tolerances. These are numerical optimum faces, not intentional economic slack; final objective shifts and residuals are reported. The deterministic feasible optimum uses J, K,-C, ID. All components remain eligible before the coverage LP.

A poison check preserves only TUNE_training and replaces every other selection input, including CAL outcomes, choices and comparisons. Selected weights and checks must serialize identically. The source contains historically exposed CAL values, so passing this test proves only the selector's information dependence. The complete weights, aliases, controls, oracle and poison result are written to TUNE_LOCK112.json before CAL validation or expectation calculation.

The actual aggregate-analysis child is single-attempt, with CPU 120s, wall 180s, sampled RAM512 MiB and output16 MiB limits. Its retained Windows process HANDLE supplies creation/exit identity and terminal CPU/I/O counters; memory is sampled and is not OS isolation. Source or implementation changes after the seal abort the child; a failure is preserved rather than retried.

S11.6. Nominal common mixtures: Locked empirical result and both-policy feasibility

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The locked common-mixture comparison on reused CAL has status infeasible. Adaptive-minus-static expected J is 0.000509611661675291; joint useful-coverage feasibility is False.

The constrained static mixture is: mixture:B3:fixedY45 = 0.6904301381091379; mixture:B3:order 124:confidence45:Yfirst = 0.30956986189086216. The constrained enriched mixture is: mixture:B3:depth1:confidence45:Yfirst = 0.31029245935197936; mixture:B3:fixedY45 = 0.6897075406480206. Weights are displayed with their stored float precision; no CAL value chooses them.

The following table includes constrained randomization, the best individually feasible deterministic component, the unconstrained mixture and fixedY. "Strict feasible" uses the literal .50/.25 comparisons; "tolerance feasible" permits at most 10^-9 floating-point residual. Borderline numerical equality is therefore visible. A lower J is called a useful-domain gain only when both locked mixtures meet their reused-CAL floors and the unrounded loss difference is less than -10^-9.

Free all-abstention has J=.4, C=0, E=0 and K=0. It lies outside the useful-coverage feasible class. J<.4 is reported separately from useful feasibility; defeating an infeasible comparator or having lower error by refusing more cases does not establish the targeted improvement.

Table S118: Equal-person expected rates; TUNE is fitted and CAL is reused exploratory development

Policy	J	Mean C	Min C	E	K	E/C	Strict feasible	Tolerance feasible
TUNE fitted static constrained	0.530338	0.500000	0.292022	0.273420	1.138362	0.546839	True	True
TUNE fitted static unconstrained	0.458365	0.320937	0.162297	0.114392	1.446949	0.356432	False	False
TUNE fitted static deterministic	0.562608	0.580287	0.350187	0.344723	1.000000	0.594056	True	True
TUNE fitted adaptive constrained	0.528717	0.500000	0.288013	0.271458	1.145179	0.542917	True	True
TUNE fitted adaptive unconstrained	0.453386	0.321541	0.149813	0.108608	1.467877	0.337774	False	False

Policy	J	Mean C	Min C	E	K	E/C	Strict feasible	Tolerance feasible
TUNE fitted adaptive deterministic	0.562608	0.580287	0.350187	0.344723	1.000000	0.594056	True	True
TUNE fitted fixedY/.45	0.562608	0.580287	0.350187	0.344723	1.000000	0.594056	True	True
CAL reused static constrained	0.515710	0.446729	0.318663	0.238142	1.125193	0.533079	False	False
CAL reused static unconstrained	0.464206	0.310586	0.202247	0.118220	1.404410	0.380636	False	False
CAL reused static deterministic	0.538803	0.507772	0.361905	0.291912	1.000000	0.574888	True	True
CAL reused adaptive constrained	0.516220	0.446425	0.315115	0.238179	1.132225	0.533524	False	False
CAL reused adaptive unconstrained	0.466022	0.310066	0.211111	0.118742	1.426129	0.382958	False	False
CAL reused adaptive deterministic	0.538803	0.507772	0.361905	0.291912	1.000000	0.574888	True	True
CAL reused fixedY/.45	0.538803	0.507772	0.361905	0.291912	1.000000	0.574888	True	True




Figure S38: Source-bound primary catalogue, locked common mixtures, participant floors and mixture weights. All points are analytic expectations on historical public outputs; no new randomized trial.

S11.7. Nominal common mixtures: Transport, ratios and what the aggregates cannot identify

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Participant tables preserve the independent grouping unit and every coverage slack. TUNE training identities and CAL person indices are partition-local; matching index numbers are not the same person. The fitted constraints say nothing deterministic about a new person. Changes from TUNE to CAL may reflect participant transport, the inherited OOF/refit view change, frozen-library inadequacy or estimator/quantizer limitations; the present marginal table cannot identify their separate causes.

Macro E/C is the ratio of equal-person mean accepted-error mass to equal-person mean coverage. It is not the mean of person selective-error ratios. We report that latter mean separately where every person's coverage is positive; a zero-coverage person makes the corresponding mean undefined. Pooled-window ratios use different weights. Each is an expectation conditional on the fixed empirical component rates, not an unbiased ratio estimate from a finite randomized deployment.

Adaptive-minus-static J, C, E, K can be subtracted per person without a joint row trace. However, their marginal aggregates do not identify which individual windows were corrected, harmed, newly accepted or removed, nor the covariance of coupled policy coins. We do not manufacture transition counts, raw paired tests, Monte Carlo standard errors or independent confirmation. The per-person difference range is a descriptive summary of eight reused groups.

Table S119: All primary constrained-mixture participant rates; person indices are local to each partition

Partition	Method	Person	n	J	C	E	K	Person E/C
TUNE	static	0	797	0.478300	0.587011	0.254695	1.168185	0.433885
TUNE	static	1	630	0.546521	0.473834	0.279618	1.128742	0.590117
TUNE	static	2	1099	0.671283	0.564350	0.439108	1.158306	0.778076
TUNE	static	3	1072	0.523320	0.511052	0.271402	1.126773	0.531066
TUNE	static	4	1368	0.523272	0.517425	0.272752	1.149806	0.527134
TUNE	static	5	630	0.440895	0.546660	0.202900	1.133164	0.371164
TUNE	static	6	647	0.526958	0.507645	0.272935	1.141627	0.537649
TUNE	static	7	1602	0.532152	0.292022	0.193946	1.100291	0.664148
TUNE	adaptive	0	797	0.474095	0.591887	0.252207	1.172861	0.426107
TUNE	adaptive	1	630	0.544832	0.468215	0.275493	1.132490	0.588390
TUNE	adaptive	2	1099	0.670000	0.561846	0.436338	1.167993	0.776616
TUNE	adaptive	3	1072	0.520379	0.511204	0.268377	1.129674	0.524990
TUNE	adaptive	4	1368	0.519160	0.519929	0.269374	1.155146	0.518098
TUNE	adaptive	5	630	0.441218	0.553327	0.205703	1.136923	0.371757
TUNE	adaptive	6	647	0.528943	0.505580	0.273262	1.158264	0.540491
TUNE	adaptive	7	1602	0.531112	0.288013	0.190913	1.108079	0.662865
CAL	static	0	630	0.545154	0.318663	0.216772	1.116949	0.680255
CAL	static	1	601	0.556426	0.475745	0.290182	1.130833	0.609953
CAL	static	2	596	0.437838	0.460603	0.166340	1.114790	0.361135
CAL	static	3	812	0.452486	0.465596	0.182758	1.119329	0.392525
CAL	static	4	814	0.571198	0.570743	0.341281	1.164293	0.597959
CAL	static	5	738	0.466741	0.432498	0.184371	1.107385	0.426292
CAL	static	6	644	0.524732	0.492154	0.265225	1.127385	0.538906
CAL	static	7	1602	0.571106	0.357831	0.258209	1.120582	0.721594
CAL	adaptive	0	630	0.544543	0.315115	0.214186	1.128057	0.679707
CAL	adaptive	1	601	0.559666	0.476114	0.292625	1.149725	0.614612
CAL	adaptive	2	596	0.439401	0.460492	0.167793	1.116099	0.364378
CAL	adaptive	3	812	0.451618	0.466590	0.182273	1.119608	0.390650
CAL	adaptive	4	814	0.568346	0.569785	0.338102	1.163151	0.593385
CAL	adaptive	5	738	0.466369	0.434456	0.184665	1.109738	0.425049
CAL	adaptive	6	644	0.525186	0.486731	0.262699	1.143583	0.539721
CAL	adaptive	7	1602	0.574629	0.362123	0.263087	1.127836	0.726512




Figure S39: Reused-CAL coverage by person, descriptive expected loss differences, cost/error/coverage decomposition and TUNE-only group-ID oracle bounds. Oracle information is explicitly expanded.

S11.8. Nominal common mixtures: Costs survive abstention and diagnostic changes

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The loss difference decomposes exactly as .05ΔK+ΔE-.4ΔC. The error term uses all-window accepted-error mass, so it decreases if a policy rejects difficult windows even when selective error does not improve. Expected branch query mass and pooled queries spent on ultimately abstained cases are retained. Fractional expected counts arise from averaging over an unexecuted independent coin, not from observing fractional people or physical queries.

The empirical-terminal diagnostic and the non-Y diagnostic are retained below with their own static/enriched fair randomization. They are useful failure probes but have different terminal or acquisition rights. Their outcomes cannot reverse a failed matched primary contrast. Any unattained coverage, absent deterministic component or negative difference remains visible.

Table S120: Separately prespecified unmatched diagnostics, constrained on TUNE then locked for CAL

Policy	J	Mean C	Min C	E	K	E/C	Strict feasible	Tolerance feasible
unanchored diagnostic TUNE static	0.539393	0.500000	0.301485	0.271498	1.357892	0.542996	True	True
unanchored diagnostic TUNE adaptive	0.539393	0.500000	0.301485	0.271498	1.357892	0.542996	True	True
unanchored diagnostic CAL static	0.525429	0.456049	0.347703	0.239954	1.357892	0.526158	False	False
unanchored diagnostic CAL adaptive	0.525429	0.456049	0.347703	0.239954	1.357892	0.526158	False	False
empirical terminal diagnostic TUNE static	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable
empirical terminal diagnostic TUNE adaptive	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable
empirical terminal diagnostic CAL static	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable
empirical terminal diagnostic CAL adaptive	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable	unavailable

S11.9. Nominal common mixtures: Architecture, complexity and measured execution

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The reader is a hash-bound public JSON decoder; the validator reconstructs group rates and semantic aliases; the selector consumes TUNE only; the lock serializes the complete selected objects; the evaluator forms fixed weighted sums; the reporter reads only the resulting public summaries and process receipt. These modules share no private predictor loader or execution path with 107. A malformed record, inconsistent denominator, absent policy, alias mismatch or failed certificate is an explicit failure.

For P groups and M catalogue entries, storing the rate matrix costs O(PM), and one fixed-mixture evaluation costs O(PM) plus its branch-summary size. Parsing and verifying the 4.13MB input is linear in public JSON size. Each lexicographic LP solution uses at most M+2 linear solves with O(PM) coefficient storage; duplicate effective columns may cause degeneracy but do not enlarge the convex hull. HiGHS dual simplex is not assigned a polynomial worst-case guarantee here. General LP solvability and this small observed runtime are separate facts.

The scientific child used CPU 0.984375s and wall 1.328000s, with sampled peak 82.613 MiB. Its receipt records exit, process identity, resource samples and limits. Native authoring, reference preparation, synthetic tests, document rendering and figure production are outside those child counters and remain unmeasured. Model/API calls, upstream fits, private payload reads and realized randomized trials are zero.

The common-coin deployment overhead is drawing an index and running one component, not executing every component on each case. This study does not measure that deployed runtime, sensor energy, acquisition failure or deadline behavior. Those physical questions and the separate W71 owner's receipt/deadline scope remain outside this task.

S11.10. Nominal common mixtures: Convexification theorem and expected feasibility

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Fix a participant distribution, deterministic component policies and all their paid costs. Let U be an independent policy-index coin with probabilities w. For any bounded component outcome L_j, the law of total expectation gives E[L_U|g]=Σ_j w_j E[L_j|g]. Apply this separately to coverage indicators, accepted-error indicators and query counts; linearity of the declared loss gives the same identity for J. Thus every common randomized policy produces the LP rates, and every LP vector is implementable by drawing U before any observation. This proves equivalence only for common per-case randomization over the frozen library.

The coverage conditions are expectations, so a finite batch can miss a floor even when its expected rate lies exactly on it. A deterministic quota controller or a coin conditional on participant or history is a different policy class. Group membership is used for fitting/evaluation constraints, not as a deployment routing feature. Independence of the coin from the case values is essential to the weighted-sum interpretation.

A feasible vector need not have individually feasible support policies. In the synthetic example below, neither of the first two components satisfies both group floors, but their mixture does. Conversely, individually feasible components can always be mixed feasibly by convexity. The LP must therefore consider the full predeclared library, not a filtered list of feasible components.

S11.11. Nominal common mixtures: Weak duality, numerical lower bounds and phase-I proof

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

For A w≤b, 1^Tw=1 and w≥0, choose y≤0 and z with A^Ty+z1≤c. Multiplication by w gives c^Tw≥y^TAw+z; since y≤0 and Aw≤b, y^TAw≥y^Tb. Therefore b^Ty+z is a lower bound. Setting z to min_j(c_j-(A^Ty)_j) enforces the reduced-cost inequalities directly. The published certificate stores weights, signs, slacks, reduced costs, complementarity and objective residuals independently of solver-reported feasibility.

For an infeasible constrained library, minimize t≥0 with D w+t1≥f, 1^Tw=1 and w≥0. This relaxation is always feasible for sufficiently large t. Its dual requires y≤0, D^Ty-z1≥0 and 1+Σy≥0. Clip y to the correct sign, scale it if needed so -Σy≤1, and set z=min_j(D^Ty)_j. A positive dual objective $(-f)^T$y+z forces positive t and therefore excludes zero-relaxation feasibility. The retained record includes the numerical primal/dual relaxation values.

The source coefficients originate from exact public counts, but SciPy operates on reconstructed floating-point rates. The result is reported as an optimum with a numerical finite-library certificate. The separate Fraction oracle uses exact rational arithmetic only for small synthetic cases; it does not convert the whole public-data solution into an exact rational optimum. A certificate for this finite matrix is not a bound on an unknown real-world distribution or on all omitted policies.

S11.12. Nominal common mixtures: Independent rational oracle and a concrete mixture example

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The exact oracle enumerates vertices by selecting n-1 active coverage/nonnegativity constraints together with sum(w)=1, solves the resulting square system by Fraction Gaussian elimination, and rejects any vertex violating any inequality. It shares no SciPy or NumPy linear-algebra operation with the tested optimizer. Singular active sets are skipped. The minimum over all feasible rational vertices is an independent exact optimum for this finite toy LP.

There are two synthetic groups with eight windows each. Policy a covers all group0 and none of group1, has no accepted error and buys one axis per case: macro C=.5 and J=.25. Policy b reverses the coverage groups and has two errors among group1's eight accepted windows: macro E=.125 and J=.375. Requiring each group's coverage at least .25 constrains the a weight to [.25,.75]. The minimizing mixture is .75a+.25b, with J=9/32=.28125. A third individually feasible control has coverage .75 in both groups, two paid axes per case and E=.375, giving J=.575.

The test also removes all feasible vertices to verify positive phase-I relaxation; creates exact policy ties; introduces missing policies, duplicated IDs and missing people; deletes paid-abstention expense; perturbs a feasible weight vector until a certificate must fail; and changes all CAL objects while keeping TUNE fixed. The full entry fixture makes CAL access illegal until the selection-lock writer is invoked, then evaluates every primary/diagnostic configuration and builds the complete publication schema. These synthetic checks are implementation evidence and are never mixed into the WISDM performance table.

S11.13. Nominal common mixtures: Full participant expectations and ratio conventions

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The table provides all primary constrained-mixture participant expectations. The machine-readable NUMERICAL_RESULTS112 file additionally retains every prespecified diagnostic's participants, all unconstrained/deterministic controls, macro and pooled rates, selected component weights, training aliases, branch summaries and unrounded comparison differences. No favorable subgroup is selected from CAL.

E_g counts accepted wrong cases divided by all windows, while E_g/C_g conditions on acceptance and is undefined at zero C_g. Macro E/C first averages E and C across people, then divides; mean_person_covered_error_ratio averages the individual ratios only when all exist. A finite random rollout would have a random denominator, so neither analytic ratio is asserted to be the expectation of its realized sample ratio.

Table S121: Primary participant expectations, without treating windows as independent people

Partition	Method	Person	n	J	C	E	K	E/C
TUNE	static	0	797	0.478300	0.587011	0.254695	1.168185	0.433885

Partition	Method	Person	n	J	C	E	K	E/C
TUNE	static	1	630	0.546521	0.473834	0.279618	1.128742	0.590117
TUNE	static	2	1099	0.671283	0.564350	0.439108	1.158306	0.778076
TUNE	static	3	1072	0.523320	0.511052	0.271402	1.126773	0.531066
TUNE	static	4	1368	0.523272	0.517425	0.272752	1.149806	0.527134
TUNE	static	5	630	0.440895	0.546660	0.202900	1.133164	0.371164
TUNE	static	6	647	0.526958	0.507645	0.272935	1.141627	0.537649
TUNE	static	7	1602	0.532152	0.292022	0.193946	1.100291	0.664148
TUNE	adaptive	0	797	0.474095	0.591887	0.252207	1.172861	0.426107
TUNE	adaptive	1	630	0.544832	0.468215	0.275493	1.132490	0.588390
TUNE	adaptive	2	1099	0.670000	0.561846	0.436338	1.167993	0.776616
TUNE	adaptive	3	1072	0.520379	0.511204	0.268377	1.129674	0.524990
TUNE	adaptive	4	1368	0.519160	0.519929	0.269374	1.155146	0.518098
TUNE	adaptive	5	630	0.441218	0.553327	0.205703	1.136923	0.371757
TUNE	adaptive	6	647	0.528943	0.505580	0.273262	1.158264	0.540491
TUNE	adaptive	7	1602	0.531112	0.288013	0.190913	1.108079	0.662865
CAL	static	0	630	0.545154	0.318663	0.216772	1.116949	0.680255
CAL	static	1	601	0.556426	0.475745	0.290182	1.130833	0.609953
CAL	static	2	596	0.437838	0.460603	0.166340	1.114790	0.361135
CAL	static	3	812	0.452486	0.465596	0.182758	1.119329	0.392525
CAL	static	4	814	0.571198	0.570743	0.341281	1.164293	0.597959
CAL	static	5	738	0.466741	0.432498	0.184371	1.107385	0.426292
CAL	static	6	644	0.524732	0.492154	0.265225	1.127385	0.538906
CAL	static	7	1602	0.571106	0.357831	0.258209	1.120582	0.721594
CAL	adaptive	0	630	0.544543	0.315115	0.214186	1.128057	0.679707
CAL	adaptive	1	601	0.559666	0.476114	0.292625	1.149725	0.614612
CAL	adaptive	2	596	0.439401	0.460492	0.167793	1.116099	0.364378
CAL	adaptive	3	812	0.451618	0.466590	0.182273	1.119608	0.390650
CAL	adaptive	4	814	0.568346	0.569785	0.338102	1.163151	0.593385
CAL	adaptive	5	738	0.466369	0.434456	0.184665	1.109738	0.425049
CAL	adaptive	6	644	0.525186	0.486731	0.262699	1.143583	0.539721
CAL	adaptive	7	1602	0.574629	0.362123	0.263087	1.127836	0.726512

S11.14. Nominal common mixtures: Complete expected branch costs and nonidentifiable transitions

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

Branches are inherited labels for paid paths and terminal predict/abstain outcomes. Weighting each component branch by its common coin mass preserves pooled expected queries and equal-person query mass. Every branch, including paid acquisitions ending in abstention, contributes to J. The integer inputs can yield noninteger expected branch counts; these are modeled expectations, not additional actual executions.

Neither a positive error difference nor two policies' marginal accepted-correct counts identifies their intersection. The same marginals can arise from very different overlap of corrected and harmed windows. Source 107 has some paired comparisons for its original deterministic contrasts, but those are not complete joint traces for the newly selected randomized portfolios. We preserve the missing transition information instead of combining incompatible comparisons into invented correction counts.

Table S122: All primary expected branch counts and equal-person masses

Partition	Method	Path	Expected n	Expected queries	Macro mass	Macro E mass	Macro K mass
TUNE	static	2:abstain	3417.854	3417.854	0.416918	0.000000	0.416918
TUNE	static	2:predict	3385.753	3385.753	0.447609	0.249866	0.447609
TUNE	static	2>1:abstain	636.166	1272.332	0.082157	0.000000	0.164315
TUNE	static	2>1:predict	380.461	760.923	0.050427	0.022814	0.100854
TUNE	static	2>1>4:abstain	8.049	24.146	0.000925	0.000000	0.002774
TUNE	static	2>1>4:predict	16.717	50.150	0.001964	0.000740	0.005892
TUNE	adaptive	2:abstain	3387.699	3387.699	0.412900	0.000000	0.412900
TUNE	adaptive	2:predict	3343.662	3343.662	0.442509	0.247002	0.442509
TUNE	adaptive	2>1:abstain	453.648	907.295	0.058559	0.000000	0.117117
TUNE	adaptive	2>1:predict	285.159	570.318	0.037954	0.015388	0.075908
TUNE	adaptive	2>1>4:abstain	0.310	0.931	0.000060	0.000000	0.000180

Partition	Method	Path	Expected n	Expected queries	Macro mass	Macro E mass	Macro K mass
TUNE	adaptive	2>1>4:predict	4.965	14.894	0.000528	0.000024	0.001583
TUNE	adaptive	2>4:abstain	222.790	445.580	0.028481	0.000000	0.056962
TUNE	adaptive	2>4:predict	146.768	293.537	0.019010	0.009044	0.038019
CAL	static	2:abstain	3192.854	3192.854	0.488697	0.000000	0.488697
CAL	static	2:predict	2455.672	2455.672	0.388769	0.212272	0.388769
CAL	static	2>1:abstain	428.135	856.270	0.064132	0.000000	0.128264
CAL	static	2>1:predict	343.003	686.007	0.055744	0.025305	0.111488
CAL	static	2>1>4:abstain	2.786	8.358	0.000442	0.000000	0.001326
CAL	static	2>1>4:predict	14.550	43.649	0.002217	0.000565	0.006650
CAL	adaptive	2:abstain	3159.286	3159.286	0.483451	0.000000	0.483451
CAL	adaptive	2:predict	2437.442	2437.442	0.385445	0.209679	0.385445
CAL	adaptive	2>1:abstain	309.051	618.103	0.047774	0.000000	0.095549
CAL	adaptive	2>1:predict	287.021	574.041	0.046769	0.020953	0.093539
CAL	adaptive	2>1>4:predict	7.757	23.272	0.001121	0.000073	0.003363
CAL	adaptive	2>4:abstain	152.664	305.328	0.022349	0.000000	0.044698
CAL	adaptive	2>4:predict	83.779	167.558	0.013090	0.007474	0.026180

S11.15. Nominal common mixtures: Catalogue aliases, controls and TUNE-only identity oracle

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The exact primary IDs appear in the main catalogue table. FixedY45/static2 have identical information and actions. Forced-Y orders124/142/214 leave X then Z, whereas241/412/421 leave Z then X; those groups must match. Anchored depth2/depth3 have only two post-Y acquisitions left and are the same full remaining horizon. Outcomes of those prespecified aliases are checked in both partitions. A metrics-only equality of two other policies is reported as a tie, not silently used to deduplicate their identity.

The static and enriched common-mixture LPs receive the same cost, predictor, .45 threshold, budget, data, randomization and fitting constraints. The deterministic comparator searches every individually feasible catalogue entry; the unconstrained comparator removes only the coverage rows. The strongest available frozen early-stop order rights are retained, but the optimizer does not re-learn every possible stopping map for the fixed orders.

The identity oracle replaces one shared w with separate w_g vectors. Its objective is the equal-person mean of their group losses; its mean and each-person floors are retained in a single joint LP. Since the universal solution is a special case, an optimal oracle value cannot exceed the common-mixture optimum when that solution exists. The difference isolates only the common-weight restriction in the same finite catalogue, not the value of a deployable observable group detector, hidden sensor signal or a better all-history policy. CAL is never re-optimized.

Table S123: TUNE oracle and common-mixture objectives

Pool	Common J	Known-person oracle J	Oracle dual bound	Common minus oracle
adaptive	0.528717	0.520351	0.520351	0.008366
static	0.530338	0.521545	0.521545	0.008793

S11.16. Nominal common mixtures: Reproducibility, custody and execution accounting

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

evaluation_contract.json fixes the exact libraries, floors, objective, tie order, diagnostic rights and single-attempt limits. PRE_VALUE_SEAL112 binds that contract, implementation/test source, source3/provenance hashes and the actual synthetic test transcript. TUNE_LOCK112 records the selected distributions before CAL calculation. ACTUAL_PROCESS112 retains the command, native author task identity, process creation/exit times, counters, failure text and sampled resource limits. SOURCE_HASHES records actual applicable policy/checker/builder bytes.

The only numerical file opened is the permitted public aggregate JSON. Earlier public manuscripts, contracts, review and data-lineage records are provenance and interpretation inputs. Private arrays, probability caches, raw/TRAIN/FINAL, models/pickles, APIs, new dependencies, operational lifecycle changes and 107 reruns

are absent. Python3.11, NumPy 2.3.2 and SciPy 1.16.1 were already installed. The renderer is not edited by this author.

The actual-run gate is consumed by the existing process receipt. Repeating –launch in this directory is refused. Reproducing a scientific result requires a separately authorized fresh output directory and retained failure boundary; report rendering from the frozen result is not a second scientific run. Authoring effort was requested as SOL max, but effective-model telemetry is unavailable and is not fabricated.

S11.17. Nominal common mixtures: Source reading and remaining method gaps

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

The inherited source107 manuscript and independent109 audit establish the starting failed-coverage comparison and absence of additional observed depth gain. The public next-method contract requires useful constraints, matched static controls, honest exposure, coherent loss, failures and independent review. This study addresses the finite-library constrained-optimization slice; it leaves new-participant confirmation, modern AFA reproduction, physical acquisition and true-world inclusion open.

External primary-method reading scopes are inherited from 107's versioned records. They are neither full-paper re-audits nor reproduced benchmarks. The official SciPy 1.16.1 documentation was newly checked for linprog inequality conventions and dual marginal interpretation. The group oracle and weak-duality results are derived explicitly in this manuscript; they do not borrow statistical coverage guarantees from selective classification or calibration.

No SKILL is activated, no operational app is changed, no scientific gate is closed and no submission receipt is claimed. A distinct completed review task must inspect the final source3 and decisive numerical checks before publication integration. Any unresolved gap is retained in the report rather than hidden by a successful process exit.

S11.18. Nominal common mixtures: Exact primary source catalogue

Scope. Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL.

This table preserves the full policy-ID and semantic-alias inventory from the frozen author manuscript. IDs are catalogue entries, not independent samples or necessarily distinct deployed policies.

Table S124: Exact primary catalogue and predeclared semantic aliases

Source ID	Pool role	Semantic key
mixture:B3:depth1:confidence45:Yfirst	added adaptive	depth1:confidence45True
mixture:B3:depth2:confidence45:Yfirst	added adaptive	depth2:confidence45True
mixture:B3:depth3:confidence45:Yfirst	added adaptive	depth2:confidence45True
mixture:B3:fixedY45	static library	static2:confidence45
mixture:B3:order124:confidence45:Yfirst	static library	order214:confidence45
mixture:B3:order142:confidence45:Yfirst	static library	order214:confidence45
mixture:B3:order214:confidence45:Yfirst	static library	order214:confidence45
mixture:B3:order241:confidence45:Yfirst	static library	order241:confidence45
mixture:B3:order412:confidence45:Yfirst	static library	order241:confidence45
mixture:B3:order421:confidence45:Yfirst	static library	order241:confidence45
mixture:B3:static2:confidence45	static library	static2:confidence45
mixture:B3:static3:confidence45	static library	static3:confidence45
mixture:B3:static6:confidence45	static library	static6:confidence45
mixture:B3:static7:confidence45	static library	static7:confidence45

S12. Known-person robust coverage: all radii, people and certificates

The uncertainty set reweights eight known TUNE response vectors. It is not a population confidence region. Both primary mixtures fail the original CAL mean floor; fixedY45 passes that original gate; ρ=1/2 and ρ=1 produce positive finite-library infeasibility certificates. The vector-hull witness is finite and retrospective.

S12.1. Robust known-person transport: Evidence and exposure boundary

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

The only actual numerical input is NUMERICAL_RESULTS107.json, SHA256 e946082872ba332d83f992ef c310f1b85e3ee2dadb5b8cfb05143543873ee945. It contains public marginal integer counts for frozen policies. TUNE contributes eight historical people and7845 windows; CAL contributes eight other historical people and6437 windows. Window counts are repeated observations within people. They are not independent participant counts, and neither the eight uncertainty vertices nor190 LP solver calls increase the number of independent people.

All CAL material has been used in prior development. The combined JSON is decoded in the actual child, so its CAL bytes are exposed even before the selector accesses only TUNE_training. Selection invariance under poisoned non-TUNE fields tests a program boundary; it does not restore blinding or remove the historical influence of earlier results on the follow-up question. There is no independent final test in this study.

Rates are reconstructed from each person's n, accepted, errors and queries. Public floating-point rates and macro means are checked against those counts. Missing or duplicate policy IDs, changed specifications, person-order changes, invalid counts, inconsistent denominators and a source-hash mismatch are rejected. We do not infer individual corrected/harmed transitions from marginal counts, inspect private/raw payloads or rerun upstream107 models.

The inherited upstream views differ: TUNE uses out-of-fold predictions, whereas CAL uses the all-TUNE refit. This study does not perform nested outer validation or a common-model refit. Consequently, the observed finite-vector inclusion failure and CAL performance cannot isolate participant composition from the upstream fitting-view change; they do not certify population OOD or a causal mechanism of shift.

S12.2. Robust known-person transport: A matched finite policy problem

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

The static library contains four Y-including fixed subsets (masks2,3,6,7), all six frozen conditional acquisition orders and the fixedY45 anchor: eleven exact IDs. The enriched library adds the three frozen depth policies, giving fourteen IDs. Every policy belongs to the same mixture family, budget3 and confidence45 terminal rule. Y is paid before conditional acquisitions. Some IDs are semantic aliases after Y-first normalization; they remain in both the frozen input and tie rule rather than being counted as independent algorithms.

A common policy coin is drawn independently before a case's observations. The weights cannot use participant ID, labels, unpurchased values or CAL. Once selected, a policy follows its already frozen acquisition/ stopping behavior. This is ex-ante randomization over existing policies, not new observation-dependent gating. Individually infeasible components are retained because a mixture can satisfy coverage even when no one component does.

Coverage C is the probability of producing a prediction, E is unconditional error mass, and E/C is selective error only when C is positive. K is expected paid acquisition count. Equal-person means are primary; pooled-window metrics are also retained. Buying Y and then abstaining costs .45 under the model, while a free no-purchase all-abstain action has J=.4 and C=0. The latter violates the useful-coverage domain and is reported as an external reference, not silently made feasible.

$$J_{gj} = 0.05K_{gj} + E_{gj} + 0.4\big(1 - C_{gj}\big)$$

C and E use all windows as denominator; K is modelled paid acquisitions, including acquisitions followed by abstention.

S12.3. Robust known-person transport: Prespecified robust mixture and executable procedure

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

For every radius we solve one common-mixture epigraph LP per library. The uncertainty set consists exactly of eight vertices. Coverage is constrained at every vertex and for every observed TUNE person. The objective

is worst-vertex J, computed from a coherent J vector derived from the same person-policy counts. We do not construct a fictitious loss by separately combining the worst E, worst K and worst C from different vertices.

The primary radius is1/4. Sensitivities0,1/8,1/2 and1 were fixed before decoding numerical input. At rho0 the eight vertices coincide with uniform TUNE weighting, giving the nominal112 problem. At rho1 the mean-coverage requirement becomes coverage at least .50 for every TUNE person; the separate .25 person floor is then redundant. Intermediate radii interpolate between these known-person constraints, not between unknown real populations.

After minimizing worst J we minimize mean K, maximize mean C and lexicographically maximize ascending exact-ID weights on the numerical optimum faces. Both libraries get the same tie rule and solver tolerances. All selected weights and controls are durably locked before CAL metrics are constructed. The procedure returns certified finite-library infeasibility rather than a fabricated mixture if the constraints cannot be met.

Algorithm S35. One common policy coin under prespecified person reweighting
Require: Hash-bound public107 policy-by-person integer aggregates and exact static11/enriched14 specifications TUNE only; rho in {0,1/8,1/4,1/2,1}; B3, paid Y first, confidence45, price .05, abstention .4 Mean coverage .50 at every reweighting vertex; each TUNE person coverage .25
Ensure: TUNE-locked common mixtures or certified finite-library infeasibility for both equally randomized libraries Analytic reused-CAL metrics, all participant denominators, diagnostics, primal/dual certificates and retained failures

1 Reject mismatched input/source hashes, policy lists/configurations, participant order, noninteger counts and denominator/rate inconsistencies.
2 Reconstruct each person-policy J,C,E,K from integer counts. Retain individually infeasible components for possible feasible mixtures.
3 Construct the eight q vertices for each prespecified rho. Compute each vertex J from one coherent person vector, and its corresponding coverage separately.
4 Solve the same minimax epigraph LP for static11 and enriched14. On its optimum face minimize mean K, maximize mean C, then lex-max weights in ascending exact policy-ID order.
5 If infeasible, solve the common-slack phase-I LP. Independently reconstruct and check the primal and a feasible dual lower bound from integer counts.
6 Using TUNE alone select feasible deterministic controls; lock uniform-order and fixedY anchors. Poison every non-TUNE field and require identical selected weights and diagnostics.
7 Write the complete TUNE lock before constructing any CAL metrics. Combined historical CAL bytes remain exposed development, not a fresh blind test.
8 Evaluate each locked mixture on all eight CAL people by linear expectation. Preserve coverage failure, worse loss, null E/C and all infeasible rho cases.
9 Call useful gain only when both CAL means exceed .50, every CAL person exceeds .25 within the fixed tolerance, and the unrounded enriched-minus-static loss is below -1e-9. Report unequal actual coverage.
10 Freeze accepted execution, source3, numerical evidence and limitations for a different completed review Task; do not rerun an accepted scientific child.

$$q^h = (1-\rho)u + \rho e_h, \quad u_g = \frac{1}{8}, \quad h = 1, ..., 8$$

Eight extreme points exactly describe the stated uncertainty set; ρ is fixed before outcomes, not selected on CAL.

$$\min_{w,t} t \quad \text{subject to} \quad \sum_j w_j = 1, \quad w_j \geq 0$$

The common mixture weights are chosen before observations and cannot depend on person identity.

$$\sum_{g,j} q_g^h J_{gj} w_j \leq t, \quad \sum_{g,j} q_g^h C_{gj} w_j \geq 0.50$$

Both inequalities hold for every h. Each observed TUNE person also satisfies sum_j C_(g j)w_j >= .25.

S12.4. Robust known-person transport: What the convex-mixture condition guarantees

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

Let c_g be the row vector of coverage rates for all policies for TUNE person g. If an unseen world's full coverage vector equals a reweighting of these rows with q in the declared uncertainty set, then any feasible w has expected coverage at least .50 in that world. The proof is direct: the coverage of a fixed common coin

is linear in the response vector, every q is a convex combination of declared vertices, and each vertex passes the same lower bound. No independence of policy outcomes within a window is needed for this expectation.

The conclusion is conditional on vector membership. It is not a population probability statement, a confidence interval, a sample-path quota or a theorem that future people resemble the eight TUNE people. If only ordinary convex-hull membership is assumed, the separate person constraints transport the weaker .25 floor. To transport the .50 bound at the primary radius requires membership in the smaller mapped uncertainty set, or another independently justified condition.

Coverage results can themselves witness a failure of the stronger membership premise. The primary static coin has fitted minimum-vertex C approximately .50 but CAL mean C=.489186. Thus the aggregate CAL coverage vector is outside the primary mapped set, within the small certificate tolerance. This is an a posteriori separation witness, not a test chosen to tune ρ. An additional coordinate check excludes CAL person7 even from the full TUNE coverage-vector hull: static7 C=.161673 is below every TUNE value, whose minimum is .166042. It does not assert that all CAL people, or the CAL mean at rho1, are outside that hull.

$$c^\star = \sum_g q_g c_g, \quad q \in U(\rho) \Rightarrow c^\star w \geq 0.50$$

The premise concerns an entire common-policy coverage vector; observing one favourable marginal or knowing a person label cannot establish it.

S12.5. Robust known-person transport: Verification before interpreting performance

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

Before numerical107 input, TASK, evaluation_contract, the implementation, independent reference and tests were written and sealed along with23 source/context/policy hashes. Ten synthetic tests passed. Tiny minimax examples are checked by exact Fraction vertex enumeration; observable-mode advantage, hidden-mode ties, complementarity and high-cost rejection are kept separate from actual participant metrics. Individually infeasible components that become feasible after mixing and a genuinely infeasible case are both exercised.

The independent_reference module imports neither research.py nor NumPy/SciPy. It reconstructs J and coverage from integer counts, rebuilds all robust constraints and checks primal feasibility, dual signs, reduced costs, complementarity and a feasible dual lower bound. A positive phase-I lower bound certifies infeasibility within the finite library. Certificate perturbations and bad IDs are rejected. This is an independent arithmetic implementation inside the author Task, not the later distinct-person review or independent data evaluation.

A full synthetic actual-entry fixture exercises input hashing, selection, locking and evaluation without touching real107 values. The real selector is also rerun internally with every non-TUNE field replaced by poison; its entire selection object remains identical. That duplicate selector check is not a second scientific child or a new data experiment. The accepted actual child is never retried.

S12.6. Robust known-person transport: Primary result: fitted robustness fails the CAL floor

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

At rho1/4, the static optimum is .905741429286 fixedY45 plus .094258570714 order124/Yfirst. The enriched optimum is .906771494229 fixedY45 plus .093228505771 depth1/Yfirst. These weights were fixed from TUNE alone. Both fitted worst-vertex coverage values are .50 up to floating-point errors below6e-15. Their worst-vertex TUNE losses are .590699703272 and .590383742672 respectively; the enriched library has the expected weak fitted advantage from being a superset.

The locked CAL means are C=.489185592512 and .489340248133, below .50 by .010814407488 and .010659751867. All individual CAL people exceed .25, so the failure is the equal-person mean floor. Mean J is .531771719061 for static and .532017868971 for enriched. The unrounded enriched-minus-static contrast is +.000246149910, with a small increase in actual coverage of .000154655621. Equal constraints therefore do not imply equal attained coverage.

The primary gate fails twice: both randomized policies miss the predeclared mean floor and the enriched loss is higher. The same-radius CAL worst-reweighting losses are .547465072889 and .547948326635, also favouring static descriptively. The main CAL difference is reported as an equal-person mean, while the fitting objective remains minimax. No interpretation of this mean-versus-worst distinction rescues the failed coverage gate. The scientific result is no_gain; independent generalization remains needs_evidence.

Table S125: Primary locked mixtures: equal-person expected metrics; E/C is ratio of macro masses.

Part	Library	J	Mean C	Min C	E/C
TUNE	static	0.552782	0.555841	0.332477	0.581124
TUNE	enriched	0.552426	0.556164	0.331507	0.580243
CAL	static	0.531772	0.489186	0.348738	0.563263
CAL	enriched	0.532018	0.489340	0.347846	0.563550

Table S126: TUNE-locked nonzero primary weights; the remaining exact-ID weights are zero.

Library	Frozen component	Weight
static	fixedY45	0.905741429286
static	order124/Y	0.094258570714
enriched	depth1/Y	0.093228505771
enriched	fixedY45	0.906771494229




Figure S40: Prespecified uncertainty sensitivities and retained failures. Panels A-B use locked randomized mixtures only; missing points at rho1/2 and1 mean TUNE infeasibility, not zero performance. Panel C shows all eight reused CAL people at primary ρ. Panel D reports positive phase-I relaxations, with equal values for both libraries.

S12.7. Robust known-person transport: Radius sensitivity and genuine infeasibility

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

Nominal rho0 reproduces the earlier common-mixture transport failure numerically: CAL C is .446729 for static and .446425 for enriched, with enriched-minus-static J=+.000509612. At rho1/8 the means rise to .467200 and .467260 but remain below the same .50 floor. The primary radius raises them further to about .489, while CAL losses rise as more mass shifts to fixedY45. This is descriptive movement along a constrained tradeoff, not successful transport or a post-hoc choice of a better radius.

At rho1/2 neither library can satisfy the TUNE constraints. The minimum common coverage relaxation is .034762885669, with an equal feasible dual lower bound. At rho1 it is .149812734082. These are not solver timeouts or missing runs. They are positive finite-library infeasibility witnesses. No CAL performance is assigned to a nonexistent selected mixture, and no feasible result is extrapolated between the tested radii.

The uncertainty sets expand monotonically with ρ: a smaller-radius reweighting is a larger-radius reweighting with a distribution closer to uniform. Therefore the feasible mixture set shrinks and the optimum worst loss cannot decrease while feasible. The synthetic geometry check and actual result check enforce these expectations. At a fixed radius, the enriched catalogue contains static11, so its exact optimum cannot be worse. This fitted containment fact says nothing about CAL ranking; the observed reversal is entirely compatible with it.

Table S127: All fixed radii. Optimal J is the TUNE worst-vertex objective; CAL columns are equal-person means.

ρ	Library	TUNE status	TUNE worst J	CAL C	CAL J
0	static	optimal	0.530338	0.446729	0.515710
0	enriched	optimal	0.528717	0.446425	0.516220
1/8	static	optimal	0.559424	0.467200	0.523454
1/8	enriched	optimal	0.558528	0.467260	0.523890
1/4	static	optimal	0.590700	0.489186	0.531772
1/4	enriched	optimal	0.590384	0.489340	0.532018
1/2	static	infeasible	undefined	not evaluated	not evaluated
1/2	enriched	infeasible	undefined	not evaluated	not evaluated
1	static	infeasible	undefined	not evaluated	not evaluated
1	enriched	infeasible	undefined	not evaluated	not evaluated

S12.8. Robust known-person transport: Strong controls and the fixedY distinction

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

The main control is the optimally randomized static11 library under exactly the same robust constraints, not a single arbitrarily chosen order. The deterministic diagnostic is selected separately within each library using TUNE feasibility at the same radius and the same objective/tie ordering. At both rho0 and primary rho1/4, its feasible exact IDs are fixedY45 and static2. The frozen lexical tie chooses fixedY45 in both libraries. This equality is read from each actual selection record, not assumed from their names.

At primary ρ, fixedY45 is a genuine feasible alternative in the same robust TUNE problem. Its worst-vertex C=.522762038538 gives mean-constraint slack+.022762038538; minimum-person C=.350187265918 gives person slack+.100187265918. Its TUNE worst J=.601699192336 is higher than either randomized optimum. On CAL it passes the original mean/person gate with C=.507772045856 and minimum C=.361904761905, at mean J=.538803120435. The randomized fits have lower CAL J but fail coverage, so that lower number is not a useful-coverage gain.

The fixedY control does not pass every analogous CAL reweighting vertex at primary ρ. We distinguish the original CAL mean/person gate from a new adversarial CAL gate and do not tune anything to the latter. Uniform mixing over all six orders also stays visible: CAL mean C=.302284 and minimum C=.188095, so it is infeasible even for the original floors. A uniform-order control is much weaker than the optimized randomized static control; neither is presented as a reproduced modern AFA method.

Table S128: Same primary selection contract: randomized static, TUNE-chosen feasible deterministic and fixed uniform-order coin. True refers only to the original mean/person floors.

Part	Control	Mean J	Mean C	Min C	Floors pass
TUNE	randomized static	0.552782	0.555841	0.332477	True
TUNE	best deterministic	0.562608	0.580287	0.350187	True
TUNE	uniform six orders	0.464576	0.329619	0.157303	False
CAL	randomized static	0.531772	0.489186	0.348738	False
CAL	best deterministic	0.538803	0.507772	0.361905	True
CAL	uniform six orders	0.465276	0.302284	0.188095	False

S12.9. Robust known-person transport: Architecture, complexity and measured resources

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

The research entrypoint has a hash/Task boundary, integer-count reconstruction, TUNE-only selector, durable selection lock and post-lock CAL evaluator. The separate reference module checks numerical certifi-

cates. The reporting script reads the accepted receipts and writes the document and figure; it never refits weights. All writes stay inside the new study directory. Old W71 state, source3, reservations and dispatches remain untouched. This local Task binding is not a new independent attestation of the old runtime.

With G people and M policies, the primary epigraph LP has M+1 nonnegative variables,3G inequality rows and one equality. Here this is12 or15 variables and24 inequalities. The phase-I LP has2G inequalities and the same variable count. Matrix construction takes O(GM) storage/work per radius; evaluating one fixed mixture costs O(GM). There are M+2 LP calls for a feasible lexicographic solution and two for an infeasible phase-I case. This is a finite-catalogue numerical procedure; no special polynomial runtime or optimality for omitted acquisition policies is claimed.

The single accepted child used1.735s wall time,1.203125s total CPU and79269888bytes peak working set. It recorded22753761read bytes and467400write bytes, with467400new output bytes and190 LP calls including the poison repeat. The installed Windows Job accepted90s per-process user CPU,1GiB committed memory and one active process. Total CPU, wall, working set and direct output were also polled. Assignment follows process creation; polling can overshoot. Thread count was requested as1 in HiGHS/BLAS but not independently observed.

These measurements describe the scientific child, not the cost of writing the study. Model authoring usage, token cost and money cost are unknown and are not encoded as zero. No model/API call, predictor fit, raw/private read or actual randomized trial was performed by this numerical child. Modelled purchase K and price .05 are not measured sensor energy, physical savings or end-to-end deployment latency.

S12.10. Robust known-person transport: Failure interpretation and what remains unidentified

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

Robustifying prevalence among eight known patterns improved descriptive CAL coverage here but did not include the actual shift tightly enough to guarantee the original mean floor. Increasing the radius further exhausted the frozen library's coverage capacity. This distinguishes a misspecified transport set from a numerical optimization failure: the primal/dual checks pass while the external membership premise fails or remains unsupported. We cannot identify the best uncertainty construction for new people from these same reused data.

The public aggregates identify linear expectations of fixed policy coins. They do not identify case-level joint correctness, the identity of helped/harmed windows, randomized-trial variance or a deployable observation-based gating function. Nor can they separate upstream model quality from the completeness of the frozen policy catalogue. A participant-ID oracle would add forbidden information; it is not needed to explain the present coverage failure and is not used as a deployable comparator.

All primary fitted and CAL mean losses exceed the free all-abstain reference .4. The coverage requirement is therefore a substantive decision restriction, not a claim that these classifiers beat doing nothing under the same loss. New observation-dependent policies, modern AFA reproductions, physical acquisition experiments or independent people require a separate authorized contract. No existing active skill or model is changed by this study.

S12.11. Robust known-person transport: Coherent robust LP and inclusion proof

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

For a fixed library, let C and J be G-by-M matrices with rows given by people and columns by policy IDs. Store the policy vectors in the same exact order throughout reconstruction, solving, certificates and evaluation. For ρ the Q matrix has rows q^h. The objective constraints are QJw-t1<=0; coverage is -QCw<=-.50; observed-person coverage is -Cw<=-.25; and sum(w)=1 with w,t nonnegative. Since the actual loss is nonnegative, the epigraph lower bound t>=0 cannot remove a true optimum.

Every r in the simplex has r=sum_h r_h e_h. Therefore q=(1-ρ)u+ρ*r=sum_h r_h q^h. Both objective and coverage are affine in q, so the eight vertices exactly suffice for this specified set. This argument does not use or discover an uncertainty set for unobserved policy outcomes. At rho0 repeated vertex rows are deliberately retained; there are eight declarations but only one distinct weighting.

For 0<=a<=b with b>0, write r_prime=(a/b)r+(1-a/b)u. This is a simplex distribution and (1-a)u+a*r=(1-b)u+b*r_prime. Thus U(a) is contained in U(b), feasible w shrink as ρ grows, and the minimax optimum is nondecreasing while feasible. Static11 is contained in enriched14, so at any common radius enriched fitted objective cannot be higher. These are elementary convexity facts, not new robust-optimization theorems.

A CAL individual coordinate below the minimum TUNE coordinate excludes that person from the entire convex hull, but the converse coordinate test cannot establish inclusion. The observed CAL mean floor failure supplies a separate linear separation witness for the primary mapped mean set. We do not replace the conditional premise with eight people's empirical appearance, and we do not infer a coverage probability for a new population.

$$QJw - t1 \le 0, \quad -QCw \le -0.50, \quad -Cw \le -0.25$$

Rows and signs correspond to the actual SciPy A_ub convention; all matrices use one frozen policy order.

S12.12. Robust known-person transport: Numerical primal/dual and infeasibility certificates

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

Write the epigraph or phase-I problem as min c^T x subject to Ax<=b, a^T x=1, x>=0, where a has ones on policy weights and zero on the last auxiliary variable. A valid dual has y<=0 and c-A^T y-za>=0. Its lower bound is b^T y+z. The reference checker recomputes these expressions from counts without importing the solver or implementation module.

To obtain a numerically feasible bound from solver marginals, clip positive inequality multipliers to zero and scale their total on rows with auxiliary coefficient-1 to magnitude at most1. Choose z as the smallest weight-column value of c-A^T y before the equality term. This enforces nonnegative reduced costs, including the auxiliary column. The checker additionally tests normalized nonnegative weights, all original inequalities, complementarity and primal-minus-bound gap within2e-8. Negative gaps of a few e-15 reflect floating-point rounding, not a claimed negative mathematical gap.

For infeasibility, introduce one nonnegative s subtracting it from every coverage upper-bound row. Minimize s over common weights. A feasible dual lower bound s_min>0 proves that no weights satisfy all original floors. Here both libraries give s_min=.034762885668555954 at rho1/2 and .14981273408239698 at rho1. A relaxation applies to every declared coverage row simultaneously; it is not a count of people who failed, an uncertainty interval or a chosen replacement floor.

Six feasible catalogue/radius solutions and four infeasible cases are checked. The largest absolute reported gap is below3e-15. The arithmetic check certifies only these finite floating-point matrices at the stated tolerance. It does not certify upstream data truth, new-person validity, the completeness of acquisition policies, causal benefit or an external reviewer's decision.

$$y \le 0, \quad c - A^T y - za \ge 0 \Rightarrow b^T y + z \le c^T x$$

Weak duality gives a lower bound; complementarity and a small gap support finite-library numerical optimality.

Table S129: Independent reconstructed certificates. In infeasible rows the primal/lower columns are phase-I coverage relaxations.

ρ	Library	Status	Primal	Lower bound	Gap
0	static	optimal	0.5303377071	0.5303377071	0
0	enriched	optimal	0.5287173733	0.5287173733	1.1e-16
1/8	static	optimal	0.5594242573	0.5594242573	-1.1e-16
1/8	enriched	optimal	0.5585280787	0.5585280787	2.3e-15
1/4	static	optimal	0.5906997033	0.5906997033	-2.2e-16
1/4	enriched	optimal	0.5903837427	0.5903837427	-2.7e-15
1/2	static	infeasible	0.0347628857	0.0347628857	0
1/2	enriched	infeasible	0.0347628857	0.0347628857	0
1	static	infeasible	0.1498127341	0.1498127341	0
1	enriched	infeasible	0.1498127341	0.1498127341	0

S12.13. Robust known-person transport: Exact catalogue, tie rules and controls

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/ enriched14 and exposed CAL.

All names below abbreviate the literal prefix mixture:B3: and confidence45 terminal. /Y denotes first_y=true. Static masks2,3,6,7 pay Y and possibly the other groups; the six orders are frozen conditional early-stopping policies, not forced full acquisition. fixedY45 is a separate anchor ID even when its integer outcomes equal static2. Added depth policies are the original frozen policies, not newly learned depth estimators.

The independent common coin is available to the static library and enriched library alike. The tie rule is worst J, mean K, negative mean C and lexicographic maximal weights by ascending full ID. This avoids using CAL

to select among equivalent TUNE optima. ID aliases may make representations nonunique, but not improve the feasible objective. Their inclusion does not make eleven or fourteen independent scientific methods.

The deterministic control is selected from all components feasible under the same ρ constraints, using worst J then K, negative C and ID. At rho0 and rho1/4 the only feasible IDs in either catalogue are fixedY45 and static2; the tie resolves to fixedY45. At rho1/4 it has positive robust TUNE mean slack .0227620 and person slack .1001873, so it is an actual feasible alternative rather than a post-CAL rescue. Uniform-order weights are1/6 on each order ID and0 elsewhere and are never fitted to CAL.

Table S130: Frozen exact-ID catalogue and library membership.

Abbreviated ID	Kind	Static11
depth1/Y	dynamic	added
depth2/Y	dynamic	added
depth3/Y	dynamic	added
fixedY45	anchor	yes
order124/Y	order	yes
order142/Y	order	yes
order214/Y	order	yes
order241/Y	order	yes
order412/Y	order	yes
order421/Y	order	yes
static2	static	yes
static3	static	yes
static6	static	yes
static7	static	yes

S12.14. Robust known-person transport: All primary participants, errors and purchase costs

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

The four tables expose all eight TUNE and all eight CAL people for each primary locked policy. Indices are partition-local, and TUNE index0 is not CAL index0. The raw denominators are inherited from the input. Every policy shares the same denominator vector within a partition. Window counts sum to7845 and6437 respectively, but the primary mean gives each of the eight people weight1/8 regardless of n.

For an individual, coverage=accepted/n, unconditional error=errors/n and modelled query count=queries/n before policy mixing. After mixing, expected accepted/errors/queries need not be integers. They are expectations of randomized policy selection, not observed randomized trial counts. Selective error E/C is null when C=0; the macro E/C is a ratio of macro masses, not the mean of individual E/C. Pooled metrics and all eight vertex coverages/losses remain in NUMERICAL_RESULTS.

The primary CAL static/enriched mean errors are .275540000713/.275767599969 and K values are1.038119107055/1.039727365103. Their modelled purchase costs are .051905955353/.051986368255. Errors cost one per erroneous prediction and abstention costs .4 per window. Both policies meet every CAL individual .25 floor, but their mean deficits are .010814407488/.010659751867. A good minimum alone does not close the mean-coverage gate.

Table S131: TUNE static primary: partition-local indices; expected rates reconstructed from fixed integer counts.

Person	n	J	C	E	K	E/C
0	797	0.495793	0.642122	0.300081	1.051209	0.467327
1	630	0.573008	0.533985	0.334642	1.039200	0.626688
2	1099	0.704451	0.637623	0.507090	1.048201	0.795283
3	1072	0.541487	0.552025	0.310367	1.038600	0.562234
4	1368	0.552437	0.582585	0.333191	1.045613	0.571917
5	630	0.454514	0.614671	0.248355	1.040546	0.404046
6	647	0.550187	0.551240	0.318526	1.043123	0.577836
7	1602	0.550383	0.332477	0.231847	1.030537	0.697333

Table S132: TUNE enriched primary: partition-local indices; expected rates reconstructed from fixed integer counts.

Person	n	J	C	E	K	E/C
0	797	0.494631	0.643906	0.299596	1.051937	0.465279
1	630	0.572654	0.532645	0.333721	1.039807	0.626536

Person	n	J	C	E	K	E/C
2	1099	0.704258	0.637295	0.506652	1.050474	0.795005
3	1072	0.540709	0.552308	0.309684	1.038961	0.560709
4	1368	0.551370	0.583715	0.332526	1.046614	0.569671
5	630	0.454690	0.617068	0.249460	1.041139	0.404267
6	647	0.550917	0.550872	0.318889	1.047551	0.578880
7	1602	0.550176	0.331507	0.231156	1.032473	0.697288

Table S133: CAL static primary: partition-local indices; expected rates reconstructed from fixed integer counts.

Person	n	J	C	E	K	E/C
0	630	0.565968	0.348738	0.253683	1.035609	0.727429
1	601	0.575449	0.519811	0.331381	1.039836	0.637504
2	596	0.453065	0.493839	0.198854	1.034952	0.402669
3	812	0.460693	0.510938	0.213252	1.036334	0.417373
4	814	0.580721	0.629200	0.379900	1.050024	0.603782
5	738	0.483370	0.475677	0.222006	1.032697	0.466716
6	644	0.540362	0.528931	0.299996	1.038787	0.567173
7	1602	0.594545	0.406350	0.305249	1.036715	0.751198

Table S134: CAL enriched primary: partition-local indices; expected rates reconstructed from fixed integer counts.

Person	n	J	C	E	K	E/C
0	630	0.565904	0.347846	0.253119	1.038475	0.727675
1	601	0.576533	0.520177	0.332354	1.044985	0.638926
2	596	0.453623	0.493998	0.199478	1.034882	0.403804
3	812	0.460480	0.511500	0.213283	1.035937	0.416975
4	814	0.579919	0.629251	0.379168	1.049019	0.602571
5	738	0.483355	0.476515	0.222313	1.032971	0.466538
6	644	0.540589	0.527515	0.299438	1.043140	0.567639
7	1602	0.595740	0.407921	0.306987	1.038409	0.752567

S12.15. Robust known-person transport: Contrast, nominal comparison and anchor interpretation

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

Primary enriched-minus-static mean J decomposes exactly as .05*deltaK+deltaE-.4*deltaC. The observed components are +.000080412902, +.000227599256 and -.000061862248 respectively. The modest extra coverage reduces abstention loss, but the higher query and error terms dominate. The sum is +.000246149910. This is a descriptive conditional contrast on reused people; no paired individual harm table or p-value is identified.

The static nominal-to-primary CAL coverage increase is .042456333016 and mean J increases by .016061564453. Enriched coverage increases .042914759303 while J increases .015798102701. These are differences between prespecified fits, not a reason to declare rho1/4 optimally tuned for CAL. The radius sensitivity is a fixed diagnostic family, and no untested radius is interpolated into an accepted result.

The selected deterministic fixedY45 has CAL mean C=.507772045856, min-person C=.361904761905, E=.291911938777, K=1 and J=.538803120435. It passes the original .50/.25 CAL gate but not every primary CAL reweighting vertex. Primary randomized fits have lower J but lower C. Neither comparison holds actual C equal; reporting a common floor is not the same as estimating a matched-coverage loss advantage. Since the fitted randomized policies fail the floor, their lower J versus the anchor is not a qualifying gain.

Free abstention J=.4 is below all these selected mean losses but has C=0. It documents the cost of requiring predictions under this inherited loss. A uniform six-order coin has CAL mean C=.302284400915 and J=.465275995438; its lower loss is accompanied by severe infeasibility. Omitting either diagnostic would hide the role of the useful-coverage constraint.

S12.16. Robust known-person transport: Synthetic controls and entrypoint coverage

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

The exact observable-mode construction has two complementary static policies, each predicting perfectly in one mode and abstaining in the other. Their separate person floors fail, but the common .5/.5 mixture is

feasible and has worst J=.25. A policy that acquires the informative mode before using the correct branch has J=.10. This is a synthetic information example, not evidence that the real frozen depth policy observes such a mode.

In the hidden-mode control, adding a duplicated uninformative policy leaves the same feasible risk and the deterministic ID tie unchanged. In a separate abstract complementarity control, a joint measurement lowers J from .25 to .10; raising its abstract acquisition cost makes the extra policy unhelpful and restores no_gain. Those abstract costs are explicitly separate from the real .05-price experiment. They exercise value-of-information logic without importing synthetic gains into the WISDM table.

Other tests exhaust Fraction vertices, establish positive infeasibility and monotonicity under expanding uncertainty, reject poisoned certificate signs/weights/IDs, and check null selective-error behavior. Missing/duplicate/out-of-order lists, changed policy specs, reordered people, float counts, zero denominators, unpaid-Y queries, wrong rates, bad hashes and malformed source schemas are rejected. The full synthetic actual-entry fixture traverses checked_input, analyze, TUNE lock and numerical output in an isolated owned temporary folder.

The accepted actual selector's poisoned repeat keeps the same TUNE object while replacing every other top-level value. Byte-canonical selection JSON is identical. This guards against a direct CAL read in selection but cannot undo historical design exposure. No new statistical claim is based on the ten tests, their repeated runs or the190 LP calls.

S12.17. Robust known-person transport: Process evidence, limits and reproducibility

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

PRE_VALUE_SEAL fixes23 paths before actual input decoding, including TASK, contract, research/reference/tests, public107, frozen112 context, Root's author Task/spec/request, the current method/session policies and the renderer reference. The actual child rechecks the seal, assigned Task/run/scope and exact107 SHA before input decoding. This is a local assignment integrity guard; it does not query or mutate Orca lifecycle or establish new ownership of an old run.

ACTUAL_PROCESS records the exact argv/cwd, stdout/stderr, exit0, retained process-HANDLE exit evidence, times, I/O, memory and limits. Windows Job assignment succeeded for90s user CPU,1GiB process committed memory and one active process. Total CPU/wall/RAM/output checks poll every25ms. The assignment happens just after creation; polling, thread requests and output observation have stated gaps. This is bounded execution, not a security sandbox. No shared process or model server is stopped.

The child created467400bytes of new direct-study output under the1MiB cap. The report writer later creates prose and the figure from the accepted output; those are authoring artifacts outside the scientific-child cap. CPU and I/O values describe the child, not the whole session. Author-model usage and writing cost are null/unknown. No effective-model telemetry is fabricated from requested settings.

The handoff order is TASK/contract, PRE_VALUE_SEAL, source/tests, ACTUAL_PROCESS, TUNE_LOCK, NUMERICAL_RESULTS, DOCUMENT/RESULT, final FREEZE. There is one actual analysis attempt. A fresh different review Task may rerun independent checks on the frozen evidence under its own contract; this author does not replay the accepted computation. No upstream dataset, active skill, Git branch, old dispatch or shared publication pointer is changed.

Table S135: Observed accepted scientific-child resource counters.

Counter	Observed value
CPU seconds	1.203125
RAM peak bytes	79269888
output bytes	467400
read bytes	22753761
samples	60
wall seconds	1.7349999999860302
write bytes	467400

S12.18. Robust known-person transport: Claim limits, literature scope and follow-up conditions

Scope. Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL.

The contribution is an executed, source-bound negative follow-up: fair randomized static controls, a prespecified robustification family, infeasibility witnesses and an explicit transport-set exclusion. It is not a new robust method, learned gating rule, global Bellman solution or demonstration of nonmyopic superiority. The depth policies are reused frozen components and their small fitted benefit cannot become a new acquisition-theory claim.

External sources in this new chapter are deliberately narrow. SciPy documentation supports the solver interface and local installed docstrings were read. Root supplied the DRO abstract pointer; the author did not inspect full external papers or reproduce contemporary AFA algorithms. PRE_VALUE_SEAL keeps precise internal source-context hashes instead of manufacturing DOI or paper identity. The earlier cumulative manuscript remains the place for its already reviewed broader literature.

New-person claims require a new authorized dataset split with participant exclusion at all learning stages, a TUNE-only uncertainty construction whose inclusion premise is evaluated on new groups, frozen hyperparameters and equal information/budget/randomization for strong baselines. Acquisition failures, physical energy and real latency need their own measurement. Both policies must satisfy coverage before ranking loss; infeasible/no_gain and omitted denominator cases must remain visible.

The numerical record is preserved with scoped independent review. The actual useful-gain result remains no_gain, and scientific generalization remains needs_evidence. Neither a checksum, model agreement, passed numerical certificate nor completed editorial package constitutes scientific certification.

S13. Reproducibility, measured resources and preserved failures

Frozen source identities and explicit read/process scopes distinguish direct results, author reports, independent saved-output checks and incomplete records. Historical scientific counters exclude native authoring and usually exclude parent/rendering work. This editorial reconstruction executes no scientific actor, external API or model experiment; native authoring usage remains unmetered.

S13.1. Finite model / MHEALTH: Complexity, bit cost, and measured resources

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

For the two-law tree study, let P be the number of policies, M the number of evaluated atoms, depth b, response branching r, and T the number of generated or referenced subtrees. Path evaluation has O(PMb) action visits. Explicit grammar generation and serialization can expand shared subtrees and need a conservative node-visit allowance. Sorting duplicate and dominated vectors uses O(P log P) comparisons; with Q skyline rows, primal pair candidates and dual intersections are quadratic, and checking every dual point against all original rows costs O(Q squared P) rational operations.

Exact arithmetic must include maximum intermediate integer bit length B. Addition, multiplication, division, comparison, and reduction use nonconstant arithmetic cost a(B). Decimal conversion has its own cost, and raw output bytes must be written. The retained allowance below includes these terms. The corresponding source discussion uses object counts, reference words, B, and maximum output size for a conservative space allowance; it is not an exact CPython allocator or operating-system RSS bound. Fraction serialization guards do not measure peak native memory.

The cached code has additional preparation work. It first creates 81 Cartesian state candidates and filters to 38 eligible states. Generalizing that construction yields (K+1)^G candidates for G coordinates and K token values plus the unobserved symbol. Domain checking uses linear membership in a tuple of H states and can compare G coordinates for each candidate. Child construction and frozen execution repeat validity and key work. Memoization does not erase these checks. Thus expressions such as O(HNG) for fitting-row information counts or O(P N_D (b+1)) for path visits are component expressions under particular primitive assumptions, not the current implementation's complete time bound.

A full cached bound must jointly account for Cartesian preparation, tuple membership, key construction, compatible-row scans, branches, memoized solves, initial scoring, frozen execution, rational arithmetic, raw serialization, and separate oracle reinterpretation and negative tests. Python dict, tuple, and Fraction allocations and host peak RAM were not measured as a complete bound. H=38, 4,024 grammar candidate values, 1,444 decisions, and 19,912 paths show completion at one fixed size, not scaling in G, K, or b.

The preserved W59 receipts report actor CPU 4.234375 seconds, launcher CPU prefixes 4.78125 seconds, execution wall sum 9.4141898 seconds, and retained artifacts excluding FROZEN of 4,408,952 bytes. Actor explicit reads of 22,312,331 bytes are an incomplete subtotal because an early smoke helper's ledger reads were omitted. A manual 12 MiB read allowance is a reservation, not measurement. Authorship, tools, shell tail, implicit imports, physical I/O, energy, and host peak RAM are outside these figures. A subtotal below a cap does not certify the omitted total.

$$O\big(\big(Tr^b b + PMb + P\log P + Q^2 P\big)a(B) + Z + S_{\mathrm{num}} d_{\mathrm{dec}}(B)\big)$$

Scoped conservative allowance for the two-law enumerator, including arithmetic and serialization; it is not a measured whole-host bound.

S13.2. Finite model / MHEALTH: Preserved failures and the unexecuted identification study

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Earlier cached execution failed by looking up terminal-external mask 15 and began none of its planned 12,576 DEV paths. The later cached correction unified domain validation and preserved common terminal fallback, enabling an honest completed diagnostic that still regressed or tied. Fixing an execution-domain bug is not evidence of positive acquisition benefit. Original failed code and receipts remain part of the source lineage, while the corrected study has its own frozen inputs and results.

An older oracle expected 312 visits where the original structure had 156. The actual subtotal was broad 104 plus narrow 52, already including the two regimes. Multiplying by the regime count again caused the mismatch. The later source reading confirmed the count from frozen states without rerunning the historical main or oracle. Another correction includes evaluation-denominator bit length by using the maximum of grid

and evaluation denominator scales. Neither correction retroactively changes a failed original run, an unknown CPU, or retained quarantined resources into a successful measurement.

W60 asked whether a masked logging law identifies conditional point gains and whether a common-set paired guarantee can vanish despite a positive minimax-value gap. Its contract declares finite catalogs, projections, expected outcomes, and four designed cases. Its static source contains the corresponding proposed computations. However RESULT has status and science_status failed, actual_results planned_cases four, cases empty, case_ledger null, and oracle null. Expected values in a contract and code that was never scientifically executed are not result observations. This English paper does not promote any of them into a completed theorem or measurement.

PIPELINE_FINAL has eight planned phases: four started, three completed, one failed, zero exhausted, zero unknown, and four unstarted. The smoke phase failed; main, oracle, seal, and the first optional preparation entry are unstarted in that final phase ledger. A separate preparation-admission ledger records two planned, two started, one completed, and one failed, preserving an earlier bootstrap problem. These are different denominators. The initial bootstrap's original sources and receipts remain preserved, with its incomplete I/O accounting. Four planned scientific cases and four unstarted pipeline phases are numerically equal but semantically unrelated.

Review-code development failures are another separate category. The historical model review first assumed a field existed in an old failure JSON, then assumed a nonexistent handle-closed marker field; later correction followed actual schema and disposal order. The cached reviewer also corrected an encoded-result-hash assumption. These are not new experiment failures or independent data. They remain documented so a later review does not silently claim an infallible verification process. This derivative neither replays accepted calls nor repairs another session's lifecycle.

S13.3. Finite model / MHEALTH: Source custody, exact reading scopes, and reproducibility

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The principal editorial source is the final corrected source.DOCUMENT.json whose exact path and SHA-256 are in SOURCE_BINDINGS.json. Its paper and supplement provide the scientific synthesis, 28 native Typst equations, all numeric tables, and the inherited reference list. The Korean explainer is outside this English rewrite; its existing source identity and three PDF byte sequences are carried by the integration owner without new translation or typesetting. The prior final method review is accepted only within its stated document and evidence scope.

Additional local bindings connect the model result and evaluation contract, the cached manuscript and static implementation, the related-work manifest, the later failed RESULT and phase ledger, policy and routing configuration, and the document builder. Hashes identify consumed bytes; they do not authenticate a scientific claim by themselves. JSON pointers and named code ranges identify which part was used. SOURCE_BINDINGS records whether an input was read as scientific content, static code, contextual policy, inherited metadata, or an inventory pin.

The current figures use either saved exact fractions or curves derived from the preserved closed-form envelope. Every figure has a distinct question, evidence-kind label, source bindings, and limits. Model curves and cached-development bars are separate figures with separate units. No interpolation is reported as observed application performance. SVG and PNG outputs are rendering artifacts; their hashes and arithmetic checks make the displayed values inspectable. Building these artifacts does not generate new independent benchmark outcomes.

External reading remains the preserved local record. No external paper was newly fetched and none of the five closer primary methods was directly reproduced. English reference scopes retain exact edition and section limits; passage hashes are not full-article identity checks.

S13.4. Finite model / MHEALTH: Falsifiable next questions and completion boundary

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A general-law extension should first define its policy rights, law-set construction, reference tie-break, and target quantifiers. For three or more vertices it must use valid general LP witnesses rather than reuse the two-row theorem. If the set is inferred from observations, it must state a structural identification argument and any finite-sample inclusion guarantee. A positive point-law value selected from multiple compatible laws

is not a uniform certificate. Failed identification must remain an explicit result, not a request to choose a convenient law.

An application extension needs a genuinely unseen group split, a fixed predictor or an explicit matched predictor-training design, and preselected references. Core adaptive, receding-myopic, all feasible fixed orders, and strong forced subsets should share support, terminal, budget, attempted-failure, and information rights. Report participant and pooled quantities separately, retain every planned, started, completed, failed, exhausted, unknown, and unstarted denominator, and separate logical quotes from directly observed physical latency or energy. Ties remain no_gain.

A targeted estimator study should vary risk estimation without simultaneously changing the predictor, transition law, initial distribution, support menu, and evaluation groups. It should preserve paired correction, harm, abstention transitions, and per-person quote differences. A coherent surrogate can demonstrate algebraic consistency while failing externally; a calibrated surrogate can lower total J by abstaining. Both can be legitimate results if their scope is explicit. Neither should be advertised as acquisition benefit solely from an internal Bellman optimum.

Independent application evidence, full external reproduction, and a justified observation-derived law set remain unresolved. Editorial completeness and document review do not close those scientific gaps.

S13.5. Finite model / MHEALTH: Provenance, freeze sequence and program-level oracle

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

PINS.json records actual source SHA256 for AGENTS, policy, review contract/checker, builder and read-only historical/audit metadata. TASK.md and CONTRACT.json fix the question, 44-arm menu, zero tuning and bounds. SEAL.json fixes those sources and both independent program files before any scientific cache read. SELECTION.json hash ca08e7ba59018d75202f11c2e7af91c5eb0c176c068b22ce9f572da70cb5c1a6 was fixed in SELECTION_FROZEN.json before raw DEV access. The saved IO ledger records that order. This is a cooperative code-order/content-hash check, not proof of lifetime data non-exposure.

The main uses rational weighted state masses and Bellman recursion. The oracle does not import it: it enumerates all finite supported programs, permits arbitrary STOP/A leaves, and directly integrates cached row losses as integer twentieths. It independently reconstructs every one of 1672 law-policy-state action/value choices and every 37224 T/DEV path, and checks all per-participant/macro metrics, paired transitions and T-only selected references. Whole-domain action equivalence and zero residuals are directly checkable in the frozen outputs. This numerical oracle is by the same author; an independent Task reviewer remains separate.

Synthetic tests include unequal group sizes and a posterior 5/7 rather than 1/2; Q risk1/3 versus P2/7; exact mass additivity; all 44 P/Q rollout identities; order-blocking child29; reverse-pair completion; STOP on exact abstention tie; depth-one replanning through two acquisitions; balanced-group no_gain; mask15 rejection; a token lease that throws on unrequested future-token reads; invariance of actions to subject/index/label changes; read/write exhaustion and pre-freeze DEV denial. The first synthetic mismatch test mistakenly chose an adaptive whose acquired perfect predictor erased the mismatch; the recorded pre-seal failure was repaired by choosing fixed_empty. It is not counted as a successful first attempt.

S13.6. Finite model / MHEALTH: Costs, denominators, and unstarted work

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The scientific main and oracle each ran once, with no automatic retry, historical execution, post-DEV tuning, fit/inference/API/network call or externally spawned scientific child process. They completed 14168 T plus23056 DEV paths. All 176 split/policy/participant denominator cells have planned=started=completed and failed=exhausted=unknown=unstarted=0. These are repeated computations on 846 unique windows, not 37224 independent observations. C is 192 additional cache rows excluded from policy estimation.

COSTS_PROGRESS.json distinguishes measured Python intervals and launcher observations from authoring/native/import/physical-resource costs. The main launcher resolved to a python.cmd wrapper, so its0.015625 s CPU is explicitly not presented as full Python CPU; the complete main CPU is unknown. Direct oracle process CPU 1.296875s and wall 1.3329784 s are measured separately from its 1.1875 s/1.1929826 s cooperative interval. Explicit scientific content reads 9255243 and writes 821134 bytes, plus archive uncompressed payload 7604125 bytes shown separately. Both conventional compressed-artifact counting and conservative compressed-plus-uncompressed counting remain below 16MiB. No hardware speed/energy comparison follows.

Inactive next questions are: whether the same target alignment changes behavior on an unexposed accepted benchmark; whether fixed and committed selection differences persist with independent participants; and which predictor/distribution/selection errors explain the observed regression. No Task, worker, schedule, campaign claim or hidden-final evaluation is created for these questions. W61/full-latent-logger-inverse work remains outside scope.

S13.7. Finite model / MHEALTH: Data rights and scientific limits

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Permission is restricted to the already pinned development cache and the owned author output directory. Original projects, source bundles, research campaign, other Tasks/Runs, shared UI/config, DB, keys and trust files remain outside write scope. No new dataset rights or public redistribution license are established. Source/selection hashes demonstrate content binding; they do not certify dataset validity, historical predictor identity, independent final exposure or scientific truth.

All MHEALTH1-10 have previously been used and DEV 7/8 was previously used in model/policy evaluation. The results answer a deterministic local development question and provide no new independent benchmark, confidence certification or general adaptive advantage. There is no external baseline reproduction or novelty assessment. References are intentionally empty because this author performed no new external primary-source retrieval. Historical dataset/predictor metadata are attributed to pinned local records, not newly verified external sources. The final scientific status is needs_evidence.

S13.8. Finite model / MHEALTH: Source, exposure and read boundaries

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Upstream T-only SELECTION SHA256 ca08e7ba59018d75202f11c2e7af91c5eb0c176c068b22ce9f572da70cb5c1a6 supplied the only 22 candidate objects, preserved unchanged in MENU_SEAL. The source/contract/menu seal SHA256 is 1c9bcd98f4328fae1b5f721de76e8aa48b99cec81f425e8f47a91904b97be81a. Upstream result reference 3e36e97f4d676a8654907cdd423a8d3f356f4c3b593fec0f69c1cea7c6ed11e2 is Root-supplied provenance, not a new predictor certification.

Original combined TRAIN_C SHA256 is 63cf79ae01c7567d630cf9cd1684cd145e56676add90aab8ff863c485f3ae18a; DEV SHA256 is 5625b00000c8bb88a4b751b020968b0a69076656e91d4dc8aa296fb4b3ebed6c. PINS supplies exact paths/bytes. IO_LEDGER in RAW.zip orders source seal verification, first C read, actual C_FROZEN write/hash and first/only main DEV raw read. Preseal reads were T-derived tables, metadata, source and the exposed upstream document format/summary, never raw C/DEV. Prior C/DEV exposure remains inherited; this is not blind, unseen or preregistration certification.

Raw benchmark datasets are not copied into the package. Acquired-policy traces, terminal cached predictions, labels and logical outcomes are derived rows bound to actual source hashes. The oracle reads those own derived artifacts, never original benchmark caches. No new data, UCI470H, NPZ, hidden final partition, predictor fit, download, model or network call occurs.

S13.9. Finite model / MHEALTH: Architecture, failure model and complexity

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Flow: frozen Task/menu/source/contract → pinned combined TRAIN_C → C group loss matrix → reference/direct LP/C controls → actual C_FROZEN bytes/hash → one DEV read and pure rollouts → exact expectation summaries/derived archive → separate-code oracle → documents/report/freeze. Only acquired token state reaches the action lookup; subject/index/label/unacquired tokens are scoring or cache transport data, never policy features.

Upstream main/oracle sources were consulted read-only with actual SHA attribution in PINS and were never imported or executed. New selector and separate oracle files are sealed independently. Neither scientific Python actor creates external children. The outer launcher records actual child CPU/wall/exit; cooperative guards are not OS isolation. No campaign claim, lifecycle, scheduling, app/config/shared-source/Git, DB/key/trust or foreign-Run state is mutated.

The denominator state machine requires planned=started+unstarted and started=completed+failed+budget_exhausted+unknown. It is synthetically tested with all categories, not a helper that ignores failure. Partial completed traces are retained if failure occurs. A budget rejection permits only a

disclosed emergency diagnostic write, never a successful completion or scientific retry. A started process without completion evidence remains unknown; this source does not infer success from a stale marker.

For n rows, primal/dual candidates take O(n^2); scoring all dual breakpoints against all rows takes O(n^3) here with n=22. Pure rollout is O(22*N*d), with d<=3 quotes. Stored derived traces take O(22*N*d); deterministic pair counts are cached as needed. These are algorithmic counts, not measured RAM/physical IO. Only Python standard library was used; no dependency was added.

S13.10. Finite model / MHEALTH: Actual checks, costs, failures and limits

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

PREPARATION retains final 23 main plus 5 oracle synthetic checks and hashes, initial preseal source versions, the authoring-only PowerShell -c metadata NameError, and a preseal change preserving partial failure traces plus stronger guard checks. COSTS_PROGRESS also preserves a document-authoring command-length rejection before process creation. Neither authoring failure started a scientific main. There was no scientific failure or replay; sealed source was unchanged.

One main and one oracle each exited 0. ORACLE reports 161,712 assertions for reference/direct/A LPs, original-row certificates, derived trace legality, exact C matrix, controls, expected metrics/paired transitions and 88 complete denominators. Its dual-envelope-first formulation and primal recovery are separate code, but the same author wrote both. It is not independent scientific review, and it does not independently compare reported terminal cached predictions against original raw cache values.

COSTS_PROGRESS records executable, arguments, PID, exit and stdout/stderr. Actual Python main CPU=0.53125s and oracle CPU=0.640625s, total 1.171875s; launch-to-wait wall sum=1.3613009s. Main explicit read/write=645398/871327 bytes; oracle=5192381/5254 bytes. Cumulative actor explicit read/write=5837779/876581 bytes; conservative summed paths=29. Guard scope includes derived archive-member reads, not OS physical IO. All declared actor bounds passed.

Import/exit CPU decomposition, report/source/pin/seal authoring, receipt writes, native/tool/token costs, peak RAM and whole-host costs remain unknown/outside actor accounting. Logical requests are not physical sensor costs. Root owns independent review, document compilation and integration/publication; those steps are not executed or claimed here. Scientific status stays needs_evidence and arbitration stays no_gain.

S13.11. Finite model / MHEALTH: Verification, complexity and measured cost

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The actual grammar has root catalogs of78 and 62 distinct trees, yielding4,836 full-A global forests. Full F has1,064 order-tagged forests and 836 distinct forests after deduplication; per-order counts are4,36,36,36,196,196,196,84,196,84. Every F forest belongs to A. The oracle directly rolls all 140 root programs on original T rows to verify their integer twentieth-loss counts, then forms every global endpoint row. It does not test all pairs of4,836 policies. All selected-dual inequalities are checked over every applicable raw endpoint row.

Local/global certificate verification checks923 and 45 exact critical-point values, respectively, plus each interval's feasible endpoint vector and source tree/forest. Equality at both interval ends together with feasibility of its affine witness proves the whole interval: every alternative line is no lower at the ends and hence throughout. The oracle also checks5,190 saved source-witness paths and every exact expected metric. It is separate scientific code by the same author; a distinct native review of the frozen study is now completed.

There are38 observed states and 418 state/order Bellman subproblems in the saved certificate, with 505 total local pieces. For a node with d candidate actions and a union of B inherited interval boundaries, the implemented min routine considers O(B*d^2) pair intersections plus sorting and O(d) winner comparisons per produced interval. Query summation merges child breakpoints. The largest saved exact number uses31 numerator/denominator bits. Rational-operation cost depends on operand bit lengths. This is a bit- and output-sensitive bound in the actual state/action/interval output; state and envelope counts can grow exponentially when the feature count or depth grows. No general polynomial-in-features claim follows.

The outer supervisor measures actual Python311.exe full-process CPU/wall, including scientific imports and exit: main1.390625 CPU seconds and 1.651248 wall seconds; oracle1.59375 CPU seconds and 1.792619 wall seconds. Internal guards separately account explicit content IO, including decompressed oracle archive members. Limits are CPU 240/wall 600 seconds per actor, read128MiB/write64MiB, retained artifacts32MiB,2048 filesystem paths and rational4096 bits. These are cooperative checks, not OS isolation or peak-RAM measurements. Native authoring, supervisor own cost, whole-host cost and physical IO remain unknown.

S13.12. Finite model / MHEALTH: Interpretation and remaining evidence

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

This experiment certifies an exact optimization procedure on a fixed empirical cache, with a full static-prefix comparator and a correctly coupled global mixture law. It does not propose a new Bellman/minimax principle, establish a new robust-RL or SPIBB/RBR theorem, certify predictor quality, or establish physical latency, energy or sensor savings. Cached logical quotes are an accounting convention.

All MHEALTH participants 1–10 were used before this study. Exposed DEV7/8 contains development feedback and dependent windows from only two participants; no independent final cohort or population confidence claim is available. C is a post-freeze diagnostic, not a selector. Implementation decision is produced; scientific status remains needs_evidence. A different-author review and truly independent data would be necessary before broader scientific claims. Existing campaign/Task/Run ownership, runtime, shared software, Git and original experiments were left to their owners.

S13.13. Finite model / MHEALTH: Artifact and source audit trail

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

TASK.md is the exact full public brief. CONTRACT.json binds the compact actual Task and full scientific requirements. PINS.json binds source cache provenance and historical T-only controls; it records no raw pre-seal cache reads. SEAL.json hashes both scientific programs, IO guard, launcher, tests and contracts before the first new scientific TRAIN_C read. T_FROZEN.json and the main read ledger bind actual full T_SOLUTION bytes before C scoring and the first separate DEV raw read.

RAW.zip preserves exact TRAIN_C/DEV bytes, the frozen T solution and every source-witness trajectory. ORACLE_RAW.zip preserves GRAMMAR.json and every raw integer endpoint loss row for A and F, with denominator36,960, root-program IDs and global-order IDs. SOURCE.zip is named SOURCES.zip and contains the complete sealed scientific source set. The post-run report program only reads produced JSON receipts and validates documents; it is not a second scientific main. FREEZE.json hashes all final files except itself. RESULT.json correctly records oracle unstarted at the instant main finished; the later separate ORACLE.json and COSTS_PROGRESS.json prove that oracle completion.

Table S136: Actual SHA256 bindings; full paths and byte counts are in FREEZE.json.

Artifact	SHA256
learner.py	6c1ba59b9f92333d90ed856620002bc16d898dfdb26dee0fc4dac840761f6c49
oracle.py	6858cb50960ba6163276548d144c2b3ac1b854c411e2ab715328cb7d02a62373
runtime.py	ac3f4a34a98cee444dca738d72c142a7e1dee30413695435578c9437f3644d5f
CONTRACT.json	d2ae80fcebedc48329435a3b16bbb586cd4522b86d543c006631627e0d401360
SEAL.json	c0af1b2f9ef01eebe0b3bab32a28a9d822e66ac3a9fc55a76c041a779512f4da
T SOLUTIONS.json	cf62df2a6145263791534210357f5b77e791da284cb4055bbbc589f9035068d0
RAW.zip	7d8a72e103706758d877500fab14b49836590af903ea468fcdcb65e0c2cc78e7
ORACLE RAW.zip	29066c27e98476e9384a830540356c8927a333c5d55417a25b0dd3d5f8349207

S13.14. Finite model / MHEALTH: Resource and authorship limits

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

The actor snapshots stop immediately before the reserved terminal progress write; the full-process supervisor measurements include that write and process exit. Up to64KiB and one filesystem path are reserved inside output bounds for a terminal receipt after a scientific budget failure. There is no OS sandbox, physical IO meter or RAM certificate. A timer failure is classified separately from an assertion/data failure and does not silently trigger replay.

For these pinned counts an arithmetic-size bound is also available without timing or RAM claims. Every T policy endpoint has denominator dividing D=lcm(20*168,20*154)=36,960 and lies between0 and 23/20. Every Bellman intersection is a ratio of integer coefficient differences with magnitude below2.3D<85,008. A midpoint of two such breakpoints has denominator below2*85,008^2; its affine evaluation has denominator below D times that bound. Reduced quantities and the raw cross-products used for exact comparison remain well below512 bits. The actually selected reference is deterministic; its paired recovery and all expected metrics use the stored weights421/1471 and 1050/1471, at most524 source windows and the fixed twentieth-loss palette. Their common-denominator sums and cross-products also fit this conservative512-bit bound.

All serialized Fractions additionally pass the4096-bit guard. Transient Python Fraction operations are not independently instrumented; this is an analytical size bound for the actual pinned computation.

The same native author wrote learner and separate oracle code; the oracle does not import learner or its envelope operations. Shared runtime.py supplies only IO/hash/serialization/time guards, not scientific optimization. This separation reduces shared scientific implementation errors but is not a different-author independent review. A distinct native reviewer subsequently completed 189 checks on the frozen successful result; this completed review is separate from the same-author oracle. Native model/authoring usage is unmetered; zero scientific API calls does not mean total cost is zero.

S13.15. Finite model / MHEALTH: Independent review and historical failure boundaries

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

A distinct native reviewer verified the weighting study with 75,750 numeric and 311 semantic checks, and the C-menu study with 230,425 checks without importing its author program. Numeric acceptance of C selection is limited: its original Korean text is corrupted and remains publication-held. This publication uses freshly written Korean derivative text, preserving the original bytes and failed check. Implementation produced, numeric acceptance and scientific success are distinct statuses.

The weighting-study failure helper ignores its failure argument, so accepted numerical scope is the successful frozen run only. Its oracle budget handoff uses a pre-final main CPU snapshot; the whole main Python CPU is unknown. These limitations remain attached to the original experiment and are not silently repaired by newer studies.

The full-grammar author wrote the learner and its separate-code oracle; a different native Task subsequently reviewed the frozen result. The final publication review is a further stage and does not add independent evaluation participants. All task, source, contract, code, outcome and reviewer hashes are recorded in the companion provenance manifest.

S13.16. Finite model / MHEALTH: Data sequence and provenance

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Before raw access, the author froze new source files, a contract, meaningful synthetic tests and budgets. Public old33 definitions and static source structure were read for schema design. Old b, Γ and Tmean values were already exposed contract inputs. No claim of historical data blindness is made.

The main then verified the original W49 TRAIN_C byte hash and formed T with(index//8)%5<3. The remaining rows are C. All T selectors and actual original robustF reference were serialized and hash-frozen before C scoring or a new DEV file read. DEV groups7/8 contain266 and258 cached windows. The oracle consumes the newly preserved archive and never triggers a main replay.

SOURCE_HASHES.json connects the original33 CONTRACT/PINS/SEAL/T_SOLUTIONS/RESULT/DOCUMENT/RAW/SOURCES and independent review with actual bytes. Sealed historical source was not imported, executed or replayed. The original cache predictor was not refit or re-certified.

S13.17. Finite model / MHEALTH: Reproduction boundaries and next acceptance

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

SOURCES.zip and SEAL.json identify exactly the successfully tested source bytes. RAW.zip preserves original TRAIN_C/DEV bytes, full freshly generated grammar rows, frozen new selectors and the original fixed reference data. T_FAMILY.json contains all local pieces, every rational cut, all point/open atoms and every complete38 signature. ORACLE.json provides independent-code interval and all-row certificates.

At the author's main freeze, the different-author review was still pending; that is the provenance of the original RESULT field, not the final execution status. Different-author Task task_4a81a15eaaeb subsequently completed an independent cache reconstruction without executing author main/oracle code. Its report accepts 23 numerical/protocol checks, 45 new diagnostic objects (33 split metrics plus 12 paired objects), 18 historical split metrics and the post hoc three-regime algebra. Scientific status remains needs_evidence. The original author report's three omitted evidence declarations were corrected in a separate completion adapter without changing original bytes, 22 checks, decisions or scientific results.

The next substantive acceptance is an independently governed, previously unexposed target and a declared ambiguity model, with purchase failures, latency and full measured cost. Strong full F, historical committed token 2, new forced-order, no-abstain, T-mean and complete M controls must remain visible under matched

objectives. A strict predeclared target benefit must survive failure and coverage accounting. This derivative source assembly itself reads only completed derived reports and endpoint rows, not RAW.zip or its TRAIN_C/DEV members, and does not rerun either scientific actor.

S13.18. Finite model / MHEALTH: Source bindings, completed review and manuscript-assembly boundary

Scope. MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct.

Study37 author Task task_fbbb5871f816 completed with official result reference 1bdb3fee037f16ab569a3f0c107329fa9b826c7a6c9e169033b938d4acfd2397. Different-author review Task task_4a81a15eaaeb completed with result reference 4b624391ef6ed4cc3f87976c8c6fa3968fd5cbae67b3b3b18fad98f476b121a0. The review's numerical acceptance and needs_evidence status are both preserved. Same-author separate scientific code and different-author review have different evidentiary roles; neither is scientific certification.

The primary endpoint source T_SOLUTIONS has SHA256 fbcbaec33cc8469ed7bb91f82c47849791a5b0c89e42b08219a764301fe83b94, and T_FAMILY is 4084c7ff1aedb5027ee20aa760566d2a56142b2e89ca1ce2c0116b886fe048d2. The different-author NUMERIC_VERIFICATION is 5a67e1bb7ee9f672998bad46ad16cf0daca8d3b36543221406fbf3c913f042cf and its PROTOCOL_VERIFICATION is c22fea39cd95785921b6e2816f69a66c1d0fc33d8fce0dd79b99fd6019dd2a2d. The new derivative manifest binds actual source bytes for the conditional algebra, derived grammar, both figures and all completed reading records.

The approved cumulative baseline carried a 17-page English paper, 43-page Supplement and 155-page Korean guide in four volumes. All baseline Supplement sections and source figures are retained. Its six study lineages include conditional two-law theory, the failed W60 and completed W61 identification studies, P/Q31 weighting, Cmenu32 selection and global-law33 learning. Their differing evidence and loss contracts remain visible. This derivative adds the matched37 and conditional analyses without overwriting those originals or combining synthetic model cases with cache results.

This source-writing Task assembles reports, tables, exact fractions and completed derived rows; it does not open RAW.zip or TRAIN_C/DEV members, run main/oracle, fit a model, call an API, fetch a paper, compile a PDF or change Git/runtime/app state. The source ZIP includes publication assets and assembly/validation evidence, not original subject-level caches. Final typesetting, rendered page inspection, publication review and Git delivery belong to the integration owner and are not claimed complete by source validation.

S13. Source-section concordance

This printed concordance makes the two PDFs sufficient for navigation without opening SOURCE_COVERAGE.json. Original source labels and headings are scoped by the construction named in each caption. A new article section is a synthesis destination; a new supplement section retains technical detail. The full byte/hash/paragraph and duplicate-treatment map remains in the editable artifact.

Every row uses the original source JSON section index (p = paper, s = supplement), its original heading and the chosen destination. The actual PDF page is printed and linked after compilation. Old editorial navigation or explicitly marked duplicate lineage is synthesized rather than republished as another abstract or conclusion.

S13. Concordance: 01_complete

Table S137: MHEALTH complete finite-law and frozen-cache construction; exact controlled laws and exposed empirical groups remain distinct. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §Abstract	1
p1 1. Introduction	Article §1	1
p2 2. Related work	Article §2	2
p3 3. Information, actions and objectives	Supplement S1.1	3
p4 3.1. Fair policy classes and execution	Supplement S1.2	3
p5 4. Exact same-law certification	Supplement S2.1	6
p6 4.1. Cost envelope and no-gain boundaries	Supplement S2.2	6
p7 4.2. Designed finite regimes	Article §5	4
p8 5. Frozen empirical study	Supplement S6.1	68
p9 5.1. Strong static controls and negative findings	Supplement S6.2	68
p10 5.2. Coverage, correction, harm and cost	Article §12	12
p11 5.3. Why the original policy menu was insufficient	Article §12	12
p12 5.4. Learning over the complete supported grammar	Supplement S6.3	68

Original source section	New location	Page
p13 5.5. Positive reference-relative evidence and its limits	Supplement S6.4	68
p14 6. Objective-matched myopic controls	Supplement S2.3	7
p15 6.1. Conditional known-law planning regimes	Supplement S2.4	8
p16 7. Transport beyond the empirical law hull	Supplement S5.1	59
p17 7.1. Conditional transfer and an identification limit	Supplement S5.2	60
p18 8. Structure-aware conditional safety	Supplement S5.3	60
p19 8.1. Comparator and applicability limits	Article §8	7
p20 9. Limitations and next evaluation	Article §19	18
p21 10. Conclusion	Article §20	19
s0 Technical Supplement	Technical supplement: navigation and evidence boundaries	2
s1 Visual diagnostic 1. Finite verification and the nine designed regimes	Supplement S2.5	9
s2 Visual diagnostic 2. Negative development findings	Supplement S6.5	69
s3 Visual diagnostic 3. Coverage, correction, harm, and cost	Supplement S6.6	70
s4 Visual diagnostic 4. Learning over the complete supported grammar	Supplement S6.7	70
s5 S1. Scope, notation, and evidence units	Supplement S1.3	4
s6 S2. Atoms, observations, and loss components	Supplement S1.4	4
s7 S3. Public histories and complete policy grammar	Supplement S1.5	5
s8 S4. Grammar counts and retained raw rows	Supplement S1.6	5
s9 S5. Primal existence, two-row candidates, and dual witnesses	Supplement S2.6	9
s10 S6. Same-law improvement and the minimax-gap counterexample	Supplement S2.7	10
s11 S7. Deriving all fixed-order and adaptive envelopes	Supplement S2.8	11
s12 S8. Breakpoints, degenerate regimes, and rejection rules	Supplement S2.9	11
s13 S9. Every designed-regime result and witness summary	Supplement S2.10	12
s14 S10. Separate fixed-subset interval-width problem	Supplement S2.11	13
s15 S11. Bound directions, frontier coverage, and strong DP	Supplement S2.12	13
s16 S12. Seven engineering conditions and complementarity	Supplement S2.13	14
s17 S13. Cached bank, fitting split, and eligible states	Supplement S6.8	71
s18 S14. Support, terminal rights, and frozen selection	Supplement S6.9	71
s19 S15. Complete core-policy and forced-subset tables	Supplement S6.10	72
s20 S16. Participant-level outcomes and paired raw counts	Supplement S6.11	73
s21 S17. Exact macro arithmetic and outcome decomposition	Supplement S6.12	75
s22 S18. Surrogate Bellman optimality and the earlier coherent variant	Supplement S6.13	76
s23 S19. Complexity, bit cost, and measured resources	Supplement S13.1	205
s24 S20. Preserved failures and the unexecuted identification study	Supplement S13.2	205
s25 S21. Source custody, exact reading scopes, and reproducibility	Supplement S13.3	206
s26 S22. Falsifiable next questions and completion boundary	Supplement S13.4	206
s27 S23. Completed finite-catalog identification context	Supplement S2.14	14
s28 G1. Question and data scope	Supplement S6.14	77
s29 G2. Two joint laws and the target distinction	Supplement S6.15	77
s30 G3. Finite policy classes and exact guarantees	Supplement S6.16	78
s31 G4. Development results and negative outcome	Supplement S6.17	78
s32 G5. Paired outcomes and interpretation	Supplement S6.18	79
s33 G6. Verification and limits	Supplement S6.19	79
s34 G7. Exact empirical law and conditioning proof	Supplement S6.20	80
s35 G8. Total-variation derivation and scope	Supplement S6.21	80
s36 G9. All policies, selection, and stopping rights	Supplement S6.22	80
s37 G10. Per-participant results and paired components	Supplement S6.23	82
s38 G11. Provenance, freeze sequence and program-level oracle	Supplement S13.5	207
s39 G12. Costs, denominators, and unstarted work	Supplement S13.6	207
s40 G13. Data rights and scientific limits	Supplement S13.7	208
s41 C1. Question, scope and exposure	Supplement S6.24	82
s42 C2. Frozen policy contract and algorithm	Supplement S6.25	82
s43 C3. Reference, direct contrast and empirical certificate	Supplement S6.26	83

Original source section	New location	Page
s44 C4. Results: selection criteria and incremental arbitration	Supplement S6.27	83
s45 C5. Paired behavior, verification and cost	Supplement S6.28	84
s46 C6. Decision and limitations	Supplement S6.29	84
s47 C7. Source, exposure and read boundaries	Supplement S13.8	208
s48 C8. Why the two-column optimization is complete	Supplement S6.30	85
s49 C9. Architecture, failure model and complexity	Supplement S13.9	208
s50 C10. All policies and aliases	Supplement S6.31	85
s51 C11. Participant and paired results	Supplement S6.32	86
s52 C12. Actual checks, costs, failures and limits	Supplement S13.10	209
s53 R1. Question, cache and predeclared scope	Supplement S6.33	86
s54 R2. Policy rights and the two finite classes	Supplement S6.34	87
s55 R3. One shared law and the exact Bellman construction	Supplement S2.15	15
s56 R4. Finite-class optimality and the paired certificate	Supplement S2.16	16
s57 R5. New policies and complete development comparisons	Supplement S6.35	87
s58 R6. Verification, complexity and measured cost	Supplement S13.11	209
s59 R7. Interpretation and remaining evidence	Supplement S13.12	210
s60 R8. Exact grammar and no cross-root fixed-order adaptation	Supplement S2.17	16
s61 R9. Global-law and paired-objective counterexamples	Supplement S2.18	16
s62 R10. Complete T, C and DEV diagnostics	Supplement S6.36	88
s63 R11. Artifact and source audit trail	Supplement S13.13	210
s64 R12. Resource and authorship limits	Supplement S13.14	210
s65 A1. Independent review and historical failure boundaries	Supplement S13.15	211
s66 M1. Exact law and state sufficiency	Supplement S2.19	17
s67 M2. Parametric completeness proof	Supplement S2.20	17
s68 M3. Grammar completeness and M inclusion	Supplement S2.21	17
s69 M4. Direct paired objective and exact saddle certificate	Supplement S2.22	18
s70 M5. Data sequence and provenance	Supplement S13.16	211
s71 M6. Operational cost scope and cell outcomes	Supplement S6.37	89
s72 M7. Negative findings and historical comparability	Supplement S6.38	89
s73 M8. Reproduction boundaries and next acceptance	Supplement S13.17	211
s74 M9. Distinct strong static controls, exact forests and selection objectives	Supplement S6.39	89
s75 M10. Complete new diagnostic tables and retained historical evidence	Supplement S6.40	90
s76 M11. Known-θ Bayes-risk algebra, six-piece static comparison and proof	Supplement S2.23	18
s77 M12. How to use the conditional result and when to stop	Supplement S2.24	20
s78 M13. Source bindings, completed review and manuscript-assembly boundary	Supplement S13.18	212
s79 T1. Risk units, reference identity and preserved controls	Supplement S5.4	61
s80 T2. Exact envelope algorithm and complete optimal intervals	Supplement S5.5	62
s81 T3. Lower certificates, independent oracle and subset checks	Supplement S5.6	62
s82 T4. Conditional transfer proof, sharpness and fallback	Supplement S5.7	63
s83 T5. Same unlabeled observations with opposite gain signs	Supplement S5.8	64
s84 T6. Execution provenance, costs and next acceptance	Supplement S5.9	64
s85 T7. Full exact projection tables behind the main display	Supplement S5.10	65
s86 Editorial lineage: Abstract	Article §Abstract	1
s87 Editorial lineage: 2. Related work and the comparison contract	Article §2	2
s88 Editorial lineage: 7. Finite verification and the nine designed regimes	Article §5	4
s89 Editorial lineage: 11. Computational scope, incomplete evidence, and limitations	Article §18	17
s90 Editorial lineage: 13. Learning over the complete supported grammar	Article §4	3
s91 Editorial lineage: 15. Identification, evidence limits and the next falsifiable test	Article §8	7
s92 Editorial lineage: 16. Complete myopic controls under matched objectives	Article §12	12
s93 Editorial lineage: 20. Conclusion	Article §20	19

Original source section	New location	Page
s94 V1. Frozen architecture and trust boundaries	Supplement S5.11	65
s95 V2. Proof and full continuous-radius procedure	Supplement S5.12	66
s96 V3. Independent oracle, complexity and cost scope	Supplement S5.13	66
s97 V4. Uncertainty assumption, failure cases and next acceptance	Supplement S5.14	66
s98 V5. Independent larger-world applicability proof	Supplement S5.15	67

S13. Concordance: 02_author

Table S138: MHEALTH restored strong historical static comparator, with unchanged exposed T/C/DEV and matching paid rights. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §12	12
p1 1. Question and result	Supplement S6.41	91
p2 2. Policy identity and equal rights	Supplement S6.42	92
p3 3. Complete families and matched objectives	Supplement S6.43	92
p4 4. The restored anchor changes the question, not the complete grammar	Supplement S6.44	93
p5 5. Exposed T/C/DEV outcomes	Supplement S6.45	93
p6 6. Controlled failure attribution	Supplement S6.46	94
p7 7. Conditional risk versus actual frozen predictor errors	Supplement S6.47	94
p8 8. Verification and preserved process failure	Article §12	12
p9 9. Claims that remain open	Article §12	12
p10 Where the static policy wins	Supplement S6.48	94
s0 S1. Source identity, policy and exposure	Supplement S6.49	95
s1 S2. Exhaustive observable grammar and complexity	Supplement S6.50	95
s2 S3. Complete M and an independent superset partition	Supplement S6.51	96
s3 S4. Exact primal-dual proof and witnesses	Supplement S6.52	96
s4 S5. Denominators and participant outcomes	Supplement S6.53	97
s5 S6. Paired correction/harm and path ledger	Supplement S6.54	97
s6 S7. Fixed-acquisition terminal control and surrogate mismatch	Supplement S6.55	98
s7 S8. Reproduction boundary, actual failure and budgets	Supplement S6.56	98
s8 S9. Contribution, related work and next acceptance	Supplement S6.57	98
s9 Exact source-bound diagnostic figure	Supplement S6.58	99

S13. Concordance: 02_benchmark

Table S139: Partial-identification strong-fixed benchmark: declared finite mathematical worlds and a prospective external design, not an executed external benchmark. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §6	5
p1 1. Common-law comparison and information authority	Supplement S3.1	21
p2 2. A paid perfect observation and the exact feasibility boundary	Supplement S3.2	21
p3 3. Exact counterexample and computational evidence	Supplement S3.3	22
p4 4. Robust constraints after baseline selection and estimation	Supplement S3.4	23
p5 5. Primary literature and the distinct contribution	Article §6	5
p6 6. External evaluation design and preserved empirical status	Article §6	5
p7 Computed boundary of comparator safety	Supplement S3.5	23
s0 S0. Full model, rights and trusted assumptions	Supplement S3.6	23
s1 S1. Proof of the law-specific best fixed value	Supplement S3.7	24
s2 S2. Proof of both minimax values, including every mixture	Supplement S3.8	24
s3 S3. Proof of all-fixed regret and the if-and-only-if boundary	Supplement S3.9	25
s4 S4. Hand-reproducible primary-case table	Supplement S3.10	25
s5 S5. Nine predeclared cases and full raw evidence	Supplement S3.11	25
s6 S6. Solver correctness and complexity	Supplement S3.12	25
s7 S7. Proof of the simultaneous estimation statements	Supplement S3.13	26
s8 S8. Concrete external execution contract and its remaining gates	Supplement S3.14	26
s9 S9. Primary-source capture and source-code existence	Supplement S3.15	27
s10 Source-bound display of the exact cases	Supplement S3.16	27

S13. Concordance: 03_author

Table S140: MHEALTH reference-first routes and temporal/label-stress bounds on exposed development. Original source labels are local to this construction.

Original source section	New location	Page
p0 1. Question, intervention and principal result	Supplement S6.59	99
p1 Policy structure and information access	Supplement S6.60	99
p2 2. Information, charging and support contract	Supplement S6.61	100
p3 3. Paired value estimation under temporal disagreement	Supplement S6.62	100
p4 4. Complete controls and equivalence checks	Supplement S6.63	101
p5 5. Outcomes, coverage and failure to improve	Supplement S6.64	101
p6 6. Route-specific mechanism and the limits of recovery	Supplement S6.65	102
p7 7. Architecture, verification and resource boundary	Article §12	12
p8 8. Complexity and reproducibility scope	Article §12	12
p9 9. External benchmark boundary, novelty and remaining evidence	Article §12	12
p10 Relation to robust baseline regret	Article §12	12
s0 S1. Exact split, loss and the observed failure basis	Supplement S6.66	102
s1 Policy structure and information access	Supplement S6.60	99
s2 S2. Coupled and separate temporal bounds	Supplement S6.67	103
s3 S3. Exact finite label-stress ablation	Supplement S6.68	103
s4 S4. Online information and route reserve	Supplement S6.69	103
s5 S5. Complete controls and policy identity	Supplement S6.70	104
s6 S6. Paired error, abstention and quote decomposition	Supplement S6.71	104
s7 S7. Tests, oracle scope and process outcomes	Supplement S6.72	104
s8 S8. Provenance, eligibility and remaining method gaps	Supplement S6.73	105
s9 Relation to robust baseline regret	Supplement S6.74	105

S13. Concordance: 03_data

Table S141: WISDM official local source/clock eligibility and preserved four-stream alignment failure; metadata and bounded preparation, not benchmark performance. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §9	8
p1 Procedure	Supplement S7.1	106
p2 1. Authority, source identity and exposure	Supplement S7.2	106
p3 2. Clock evidence and the preserved alignment failure	Supplement S7.3	106
p4 3. A bounded same-row alternative, not a substituted benchmark	Supplement S7.4	107
p5 4. Architecture, complexity and baseline obligations	Article §9	8
p6 5. Six method-area judgments and limits	Article §9	8
s0 S 1. Exact subject split and local release permissions	Supplement S7.5	107
s1 S 2. Request, parsing and failure evidence	Supplement S7.6	108
s2 S 3. Prospective axis protocol acceptance, without authorization	Supplement S7.7	108
s3 S 4. Reproducibility and byte-bound evidence	Supplement S7.8	108

S13. Concordance: 03_axes_samples

Table S142: WISDM fixed-100-sample logical-axis window construction and fixed split/curation accounting. Original source labels are local to this construction.

Original source section	New location	Page
p0 1. Construction question and explicit algorithm	Supplement S7.9	108
p1 2. Preserved source, protocol history and exposure	Supplement S7.10	109
p2 3. Data flow, identities and failure boundaries	Supplement S7.11	109
p3 4. Construction verification and observed denominators	Supplement S7.12	110
p4 5. Complexity and measured scope	Supplement S7.13	110
p5 6. Remaining evaluation, baselines and related work	Article §9	8
s0 S1. Exact constructor, accounting and rejection rules	Supplement S7.14	110
s1 S2. Prespecified schema, statistics and local custody	Supplement S7.15	110
s2 S3. Validation and resources are author evidence	Supplement S7.16	111
s3 S4. All-person denominators, unchanged history and exposure	Supplement S7.17	111
s4 S5. Six-area gaps and next gates	Supplement S7.18	111

S13. Concordance: 03_external

Table S143: WISDM original learned multistep logical-axis acquisition on the original representation and frozen stopping controls. Original source labels are local to this construction.

Original source section	New location	Page
p0 1. Question, scope and contribution	Supplement S8.1	128
p1 2. Source custody and revised window protocol	Supplement S8.2	128
p2 3. Prediction, terminal actions and rights	Supplement S8.3	128
p3 4. Fitted continuation and matched restrictions	Supplement S8.4	129
p4 5. Controls, selectors and primary acceptance	Supplement S8.5	129
p5 6. Architecture, failure and resource boundaries	Supplement S8.6	129
p6 7. Controlled implementation validation	Supplement S8.7	130
p7 8. Completed fitting, CAL collapse and unopened FINAL	Supplement S8.8	130
p8 9. Complexity and prior work	Article §4	3
s0 S1. Immutable protocol and data audit	Supplement S8.9	131
s1 S2. Executable recursion and terminal semantics	Supplement S8.10	132
s2 S3. Menus, fallbacks and equivalence	Supplement S8.11	132
s3 S4. Uncertainty, selection and missing people	Supplement S8.12	132
s4 S5. Resources, serialization and failure receipt	Supplement S8.13	132
s5 S6. Current outcome and reproducibility	Supplement S8.14	132
s6 S7. Preserved historical negatives	Supplement S8.15	132

S13. Concordance: 03_coverage_diagnostic_v2

Table S144: Diagnostic of the frozen original WISDM forecast, terminal-risk, cost and coverage failure; no new acquisition intervention. Original source labels are local to this construction.

Original source section	New location	Page
p0 1. Question and failure scope	Supplement S8.16	133
p1 2. Procedure and trust boundary	Supplement S8.17	133
p2 3. What the forecast can currently support	Supplement S8.18	133
p3 4. Terminal risks and smoothing	Supplement S8.19	134
p4 5. Cost accounting and selected roots	Supplement S8.20	134
p5 6. Architecture, complexity and duration association	Supplement S8.21	134
p6 7. Justified successor; no implementation	Article §13	12
p7 8. Prior work, resources and claim limits	Article §13	12
s0 S1. Exact identifiers and arithmetic	Supplement S8.22	137
s1 S2. Metric denominators and output schema	Supplement S8.23	138
s2 S3. Risk calibration and threshold diagnostics	Supplement S8.24	138
s3 S4. All16static CAL scores	Supplement S8.25	138
s4 S5. Exposure, duration and resources	Supplement S8.26	139
s5 S6. Six method areas and unresolved work	Supplement S8.27	139

S13. Concordance: 03_representation

Table S145: Original fixed temporal/spectral representation execution: partial observations with failed durable serialization. Original source labels are local to this construction.

Original source section	New location	Page
p0 1. Failed delivery and observed forecast scalars	Supplement S7.19	111
p1 2. Fixed representation and architecture	Supplement S7.20	112
p2 3. Partial development observations	Supplement S7.21	112
p3 4. Serialization failure and verification gap	Supplement S7.22	113
p4 5. Baseline, finite computation and resource scope	Supplement S7.23	113
p5 6. Exposure and remaining evidence	Article §9	8
s0 S1. Immutable inputs and predictor contract	Supplement S7.24	113
s1 S2. Failure provenance and incomplete output	Supplement S7.25	114
s2 S3. Resources and independent reconstruction boundary	Supplement S7.26	114
s3 S4. Prior work and contribution limits	Supplement S7.27	114

S13. Concordance: 03_representation_verification

Table S146: Durable saved-model comparison of original18 versus enhanced54 features, without new fitting; all people remain development. Original source labels are local to this construction.

Original source section	New location	Page
p0 Motivation and observed development gain	Supplement S7.28	114
p1 Representation, training and information access	Supplement S7.29	115
p2 Paired evaluation on fixed windows	Supplement S7.30	115
p3 Where corrections and residual errors occur	Supplement S7.31	116
p4 Coverage, cost and computational scope	Supplement S7.32	116
p5 Relation to prior evidence and the next comparison	Article §9	8
p6 Evidence boundaries	Article §9	8
s0 S1. Fixed feature and window contract	Supplement S7.33	117
s1 S2. Participant-level accuracy, errors and paired changes	Supplement S7.34	117
s2 S2.1. All TRAIN participants	Supplement S7.35	117
s3 S2.2. All TUNE participants	Supplement S7.36	118
s4 S2.3. All CAL participants	Supplement S7.37	118
s5 S3. All CAL activity-code error counts	Supplement S7.38	118
s6 S4. Pooled counts, objective and denominator checks	Supplement S7.39	119
s7 S5. Realized model size and measured inference scope	Supplement S7.40	119
s8 S6. Failure provenance, corrected reuse and durable execution	Supplement S7.41	120
s9 S7. Source scope, policy identity and unresolved comparisons	Supplement S7.42	120

S13. Concordance: 04_method

Table S147: Participant-excluded target construction: self-contained dependency proof and exact synthetic witnesses, not an acquisition benchmark. Original source labels are local to this construction.

Original source section	New location	Page
p0 Scope and contribution	Article §4	3
p1 Procedure and dependency condition	Supplement S8.28	139
p2 Two constructions and their proof boundary	Supplement S8.29	140
p3 Minimum optimism and safety limits	Supplement S8.30	141
p4 Matched information, controls and decision rule	Supplement S8.31	141
p5 Computational tradeoff	Supplement S8.32	141
p6 Evidence and related-work limits	Article §4	3
s0 Exact information and cache contract	Supplement S8.28	139
s1 Full-pipeline outer refit versus recursively excluded targets	Supplement S8.29	140
s2 Executable synthetic witnesses	Supplement S8.28	139
s3 Matched protocol and fixed denominators	Supplement S8.31	141
s4 Complexity and resource accounting	Supplement S8.32	141
s5 Reuse boundary and required future snapshots	Supplement S8.33	142
s6 Bounded primary-source context	Supplement S8.34	142
s7 Failure and acceptance boundary	Supplement S8.35	143
s8 Complete construction procedure	Supplement S8.36	143

S13. Concordance: 04_predictors

Table S148: Shared enhanced54-feature paid-mask ET family: six missing proper-mask TRAIN fits plus the frozen full mask. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §9	8
p1 Procedure and method	Supplement S7.43	121
p2 Information access and architecture	Supplement S7.44	121
p3 Cohort, fitting and evaluation	Supplement S7.45	122
p4 Complete mask results	Supplement S7.46	122
p5 Complexity and measured scope	Supplement S7.47	123
p6 Baselines, lineage and related-work limits	Article §9	8
p7 Interpretation and next questions	Article §9	8
p8 Launcher observation boundary	Article §9	8
s0 Reproducibility and release	Supplement S7.48	124
s1 Feature formulas and numerical edge cases	Supplement S7.49	124
s2 Participant paired outcomes	Supplement S7.50	124
s3 Private prediction and confidence schema	Supplement S7.51	126
s4 Durability and failure semantics	Supplement S7.52	126

Original source section	New location	Page
s5 Method-review areas	Supplement S7.53	126
s6 Resource and capacity evidence	Supplement S7.54	127
s7 Complete predictor-family procedure	Supplement S7.55	127
s8 Launcher observation boundary	Supplement S7.56	127

S13. Concordance: 04_policy

Table S149: Matched WISDM raw/raw-confidence acquisition with1,008 risk fits; whole-pipeline seven-person outer learners and an all-TUNE CAL learner. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8
p1 Problem and matched protocol	Supplement S8.37	143
p2 Algorithm and leakage boundary	Supplement S8.38	143
p3 Primary result at useful coverage	Supplement S8.39	144
p4 Cost and coverage across budgets	Supplement S8.40	144
p5 Where the coverage gap remains	Supplement S8.41	145
p6 Unconstrained selections	Supplement S8.42	145
p7 Computational scope	Supplement S8.43	146
p8 Interpretation and remaining work	Article §10	8
s0 Complete matched procedure	Supplement S8.44	146
s1 Budget 1: unconstrained	Supplement S8.45	146
s2 Budget 1: useful coverage	Supplement S8.45	146
s3 Budget 2: unconstrained	Supplement S8.45	146
s4 Budget 2: useful coverage	Supplement S8.45	146
s5 Budget 3: unconstrained	Supplement S8.45	146
s6 Budget 3: useful coverage	Supplement S8.45	146
s7 Always-predict static anchors	Supplement S8.46	146
s8 Raw features: anchor.abstain	Supplement S8.47	147
s9 Features + confidence: anchor.abstain	Supplement S8.47	147
s10 Computational accounting	Supplement S8.48	147
s11 Residual bias, exposure and prior failures	Supplement S8.49	147

S13. Concordance: 05_theory

Table S150: Sharp randomized correctness-selection/fixed-paid bounds under declared accuracy and person coverage conditions; oracle, not deployable selector. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §6	5
p1 1. Population, loss and terminal rights	Supplement S4.1	46
p2 2. Sharp error and participant-floor bounds	Supplement S4.2	46
p3 3. The fixed-action oracle envelope and exclusion rule	Supplement S4.3	47
p4 4. Certificate procedure and cost	Supplement S4.4	47
p5 5. Paid-submask union: identifiable limits and deployment gap	Supplement S4.5	48
p6 6. Fixed-full failure does not imply adaptive failure	Supplement S4.6	48
p7 7. Already exposed development aggregates	Supplement S4.7	48
p8 8. Related work and claim boundaries	Article §6	5
s0 S1. Four-cell proof and equality conditions	Supplement S4.8	49
s1 S2. Participant-floor proof at exact coverage	Supplement S4.9	49
s2 S3. Objective minimization, boundaries and weighting	Supplement S4.10	49
s3 S4. Union sharpness and permitted-world distinction	Supplement S4.11	50
s4 S5. Eight-atom adaptive witness and deployment-gap witness	Supplement S4.12	50
s5 S6. Exact checks, resource bounds and preserved failures	Supplement S4.13	50
s6 S7. Six method areas, strong controls and next acceptance	Supplement S4.14	51

S13. Concordance: 05_predictors

Table S151: Seven-fit HGB shared predictor replacement versus the frozen ET family; exposed TUNE selection and CAL reporting. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8

Original source section	New location	Page
p1 Procedure and algorithm	Supplement S9.1	148
p2 Architecture and paid information	Supplement S9.2	148
p3 Predictive change at every fixed mask	Supplement S9.3	148
p4 Frozen selective choices and covered-cost condition	Supplement S9.4	149
p5 Complexity and measured resource scope	Supplement S9.5	150
p6 Baselines, lineage and primary references	Article §10	8
p7 Interpretation and limits	Article §10	8
s0 Reproducibility and exact input custody	Supplement S9.6	151
s1 All selected policies and exact denominators	Supplement S9.7	151
s2 Participant prediction corrections and harms	Supplement S9.8	152
s3 Label-informed diagnostic oracle	Supplement S9.9	154
s4 Resource, timing and historical uncertainty	Supplement S9.10	155
s5 Six method areas and next acceptance	Supplement S9.11	155

S13. Concordance: 06_fusion

Table S152: One prespecified multinomial paid-submask fusion attempt; first fit fails convergence at18 inputs; no efficacy outcomes. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8
p1 Research question and contribution	Supplement S9.12	155
p2 Frozen sources and permitted information	Supplement S9.13	156
p3 The planned matched terminal comparison	Supplement S9.14	156
p4 Participant crossfitting and selection boundary	Supplement S9.15	157
p5 Observed first-fit failure	Supplement S9.16	157
p6 What was and was not evaluated	Supplement S9.17	157
p7 Useful coverage, abstention and unresolved acceptance	Supplement S9.18	158
p8 Selector union and arbitrary probability fusion	Supplement S9.19	158
p9 Resource and access accounting	Supplement S9.20	158
p10 Interpretation and next acceptance	Article §10	8
p11 Claim limits and status	Article §10	8
s0 S1. Source hierarchy and exact chronology	Supplement S9.21	159
s1 S2. Input allowlist and partial reads	Supplement S9.22	159
s2 S3. Planned crossfit/refit accounting	Supplement S9.23	159
s3 S4. Learner, weights and class space	Supplement S9.24	159
s4 S5. Planned baseline family and paid rights	Supplement S9.25	160
s5 S6. Policy selection and unavailable outcomes	Supplement S9.26	160
s6 S7. Loss and separate acceptance questions	Supplement S9.27	160
s7 S8. Union witness and accepted-error identity	Supplement S9.28	161
s8 S9. Planned paired transitions and sensitivity	Supplement S9.29	161
s9 S10. Resource measurement, noop and write estimate	Supplement S9.30	161
s10 S11. Synthetic checks and preparation provenance	Supplement S9.31	161
s11 S12. Metadata audit and report transport	Supplement S9.32	162
s12 S13. Six method areas and remaining work	Supplement S9.33	162

S13. Concordance: 06_methods

Table S153: Paid-information expert-union, selection and arbitrary probability-fusion theory; recognizability/transport conditions remain external. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §6	5
p1 1. Paid histories, terminal rights and the estimand	Supplement S4.15	51
p2 2. What the expert union does and does not bound	Supplement S4.16	52
p3 3. An explicit failure of the union ceiling for fusion	Supplement S4.17	52
p4 4. Recoverable selection error and irreducible ambiguity	Supplement S4.18	52
p5 5. A useful decision rule and its scope	Supplement S4.19	53
p6 6. A stronger counterexample to maximum confidence	Supplement S4.20	53
p7 7. A falsifiable evaluation contract	Supplement S4.21	53
p8 8. Primary method comparisons	Supplement S4.22	54

Original source section	New location	Page
p9 9. Comparison of assumptions and guarantees	Article §6	5
p10 10. Public evidence, complexity and limits	Article §6	5
s0 S1. Proof of the decomposition and the scope of the ceiling	Supplement S4.23	55
s1 S2. Exact calibrated maximum-confidence counterexample	Supplement S4.24	56
s2 S3. Conditional selection gap and proof of the bounded statement	Supplement S4.25	56
s3 S4. Identifiability and recoverability conditions	Supplement S4.26	56
s4 S5. Cost, coverage and comparative attribution	Supplement S4.27	57
s5 S6. Minimum benchmark and acceptance gates	Supplement S4.28	57
s6 S7. Source verification, reproducibility and access limits	Supplement S4.29	58

S13. Concordance: 06_mixture

Table S154: Successful class-bias calibration and convex paid-submask terminal mixture study;35 bias+20 simplex calls; OOF versus refit distinguished. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8
p1 1. Question and intervention boundary	Article §10	8
p2 2. End-to-end method	Supplement S9.34	162
p3 3. Strongly convex 18-bias calibration	Supplement S9.35	163
p4 4. Convex paid-submask mixture and an auditable certificate	Supplement S9.36	164
p5 5. Participant separation, selection and estimand	Supplement S9.37	165
p6 6. Matched controls and attribution	Supplement S9.38	165
p7 7. Actual process, custody and failure policy	Supplement S9.39	165
p8 8. Development results and feasibility	Supplement S9.40	166
p9 9. Paired recovery, calibration and uncertainty	Supplement S9.41	167
p10 10. Complexity, numerical scope and related work	Article §10	8
p11 11. Limits and next acceptance	Article §10	8
s0 S 1. Exact prospective settings and no-search boundary	Supplement S9.42	168
s1 S 2. Derivations and interpretation	Supplement S9.43	169
s2 S 3. Public lineage and input boundary	Supplement S9.44	169
s3 S 4. Synthetic checks, size and execution accounting	Supplement S9.45	169
s4 S 5. Historical controls and all frozen policies	Supplement S9.46	170
s5 S 6. Paired participant, class and held-out-fold results	Supplement S9.47	170
s6 S 7. Raw versus calibrated expert unions and refit shift	Supplement S9.48	171
s7 S 8. Descriptive participant bootstrap and six-area completion	Supplement S9.49	172

S13. Concordance: 07_observable

Table S155: Observable-history planning with frozen confidence-.45 terminal, paid Y anchor, common support and exact strong controls on exposed CAL. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8
p1 1. The acquisition question after terminal calibration	Article §10	8
p2 2. Information rights and a coherent empirical world	Supplement S10.1	173
p3 3. Fixed terminal loss, support and stopping	Supplement S10.2	173
p4 4. Finite-history planning and exact scope	Supplement S10.3	174
p5 5. Controls and the frozen development protocol	Supplement S10.4	174
p6 6. Real development outcome and useful coverage	Supplement S10.5	175
p7 7. Which paths corrected or damaged decisions?	Supplement S10.6	176
p8 8. Architecture, custody and single-attempt execution	Supplement S10.7	177
p9 9. Complexity and matched computation	Supplement S10.8	177
p10 10. Relation to primary methods and guarantees	Article §10	8
p11 11. Limits, negative evidence and the next discriminating experiment	Article §10	8
s0 S1. Exact state, terminal and action definitions	Supplement S10.9	178
s1 S2. Backward induction, fixed orders and limited lookahead	Supplement S10.10	178
s2 S3. Full control inventory and training selection	Supplement S10.11	178
s3 S4. Loss identities and descriptive uncertainty	Supplement S10.12	179

Original source section	New location	Page
s4 S5. Synthetic checks kept separate from real development results	Supplement S10.13	179
s5 S6. Source and resource accounting	Supplement S10.14	180
s6 S7. Primary-work compatibility and proof boundaries	Supplement S10.15	180

S13. Concordance: 07_joint_world

Table S156: Deterministic complete-policy joint-world partial-identification theory and controlled finite cases. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §7	6
p1 1. Outcome, worlds and observable information	Supplement S3.17	27
p2 2. The estimand: one world, two complete policies	Supplement S3.18	28
p3 3. Strong static comparison and the certificate	Supplement S3.19	28
p4 4. Acquisition conditions and limits of local reasoning	Supplement S3.20	29
p5 5. Computation and architecture	Supplement S3.21	29
p6 6. Prospective evaluation and finite complexity	Supplement S3.22	30
p7 7. Exact controlled results and coverage	Supplement S3.23	31
p8 8. Ambiguity, incompatible extrema and true-world exclusion	Supplement S3.24	32
p9 9. Time consistency and primary-method comparisons	Supplement S3.25	32
p10 10. Contribution, limitations and next acceptance	Article §7	6
s0 S1. Proof of joint-world comparison and comparator envelope	Supplement S3.26	33
s1 S2. Proof of replacement criterion and explicit context condition	Supplement S3.27	33
s2 S3. XOR and indistinguishable-mode proofs	Supplement S3.28	34
s3 S4. Nonrectangular updating and safe versus unsafe bounds	Supplement S3.29	34
s4 S5. Enumeration, reproducibility and exact denominators	Supplement S3.30	35
s5 S6. Scope, prior evidence and unresolved research	Supplement S3.31	35

S13. Concordance: 08_empirical

Table S157: Nominal common-mixture optimization of frozen static11/enriched14 policy libraries using TUNE aggregate vectors and exposed CAL. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §10	8
p1 1. Why enforce useful coverage before comparing loss?	Article §10	8
p2 2. Public input, data identity and inherited exposure	Supplement S11.1	182
p3 3. Exact libraries and matched information rights	Supplement S11.2	182
p4 4. A common-mixture finite-library problem	Supplement S11.3	183
p5 5. Certificates, information-expanded bounds and omitted policies	Supplement S11.4	184
p6 6. Selection, ties and the single-attempt protocol	Supplement S11.5	185
p7 7. Locked empirical result and both-policy feasibility	Supplement S11.6	185
p8 8. Transport, ratios and what the aggregates cannot identify	Supplement S11.7	187
p9 9. Costs survive abstention and diagnostic changes	Supplement S11.8	188
p10 10. Architecture, complexity and measured execution	Supplement S11.9	189
p11 11. Relation to existing methods	Article §10	8
p12 12. Interpretation and the next discriminating evidence	Article §10	8
s0 S1. Convexification theorem and expected feasibility	Supplement S11.10	189
s1 S2. Weak duality, numerical lower bounds and phase-I proof	Supplement S11.11	190
s2 S3. Independent rational oracle and a concrete mixture example	Supplement S11.12	190
s3 S4. Full participant expectations and ratio conventions	Supplement S11.13	190
s4 S5. Complete expected branch costs and nonidentifiable transitions	Supplement S11.14	191
s5 S6. Catalogue aliases, controls and TUNE-only identity oracle	Supplement S11.15	192
s6 S7. Reproducibility, custody and execution accounting	Supplement S11.16	192
s7 S8. Source reading and remaining method gaps	Supplement S11.17	193
s8 Exact primary source catalogue	Supplement S11.18	193

S13. Concordance: 08_theory

Table S158: Common randomized adaptive/static coverage-constrained theory: exact ten-case/43-LP comparison with stronger randomized static envelope. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §7	6
p1 1. The question and its relation to the previous construction	Article §7	6
p2 2. Worlds, bought histories and one retained random seed	Supplement S3.32	35
p3 3. Coverage after convexification	Supplement S3.33	36
p4 4. An equally randomized strong static benchmark	Supplement S3.34	36
p5 5. Epigraph program, dual certificate and algorithm	Supplement S3.35	37
p6 6. Prospective controlled cases and computation	Supplement S3.36	38
p7 7. The randomized baseline materially narrows the apparent advantage	Supplement S3.37	38
p8 8. What randomization cannot fix	Supplement S3.38	40
p9 9. Why independent occupancy LPs and local Bellman shortcuts fail	Supplement S3.39	40
p10 10. Prior art, scientific status and the next boundary	Article §7	6
s0 S1. Exact policy convexification and its assumptions	Supplement S3.40	41
s1 S2. Coverage, convex hulls and why feasibility rescue is impossible	Supplement S3.41	41
s2 S3. Benchmark quantifiers and the same-world theorem	Supplement S3.42	42
s3 S4. Dual lower bound and exact optimality audit	Supplement S3.43	42
s4 S5. Exact context calculations and stronger comparator effects	Supplement S3.44	43
s5 S6. Global coordination and occupancy counterexamples	Supplement S3.45	44
s6 S7. Finite complexity, approximation and reproducibility	Supplement S3.46	44
s7 S8. Six method-area judgments and remaining research	Supplement S3.47	44

S13. Concordance: 09_transport

Table S159: Known-person robust coverage transport, ρ=1/4 primary with four fixed sensitivities, frozen static11/enriched14 and exposed CAL. Original source labels are local to this construction.

Original source section	New location	Page
p0 Abstract	Article §15	14
p1 1. The question inherited from coverage112	Article §15	14
p2 2. Evidence and exposure boundary	Supplement S12.1	194
p3 3. A matched finite policy problem	Supplement S12.2	194
p4 4. Prespecified robust mixture and executable procedure	Supplement S12.3	194
p5 5. What the convex-mixture condition guarantees	Supplement S12.4	195
p6 6. Verification before interpreting performance	Supplement S12.5	196
p7 7. Primary result: fitted robustness fails the CAL floor	Supplement S12.6	196
p8 8. Radius sensitivity and genuine infeasibility	Supplement S12.7	197
p9 9. Strong controls and the fixedY distinction	Supplement S12.8	198
p10 10. Architecture, complexity and measured resources	Supplement S12.9	198
p11 11. Failure interpretation and what remains unidentified	Supplement S12.10	199
p12 12. Related work scope and next acceptance	Article §15	14
s0 S1. Coherent robust LP and inclusion proof	Supplement S12.11	199
s1 S2. Numerical primal/dual and infeasibility certificates	Supplement S12.12	200
s2 S3. Exact catalogue, tie rules and controls	Supplement S12.13	200
s3 S4. All primary participants, errors and purchase costs	Supplement S12.14	201
s4 S5. Contrast, nominal comparison and anchor interpretation	Supplement S12.15	202
s5 S6. Synthetic controls and entrypoint coverage	Supplement S12.16	202
s6 S7. Process evidence, limits and reproducibility	Supplement S12.17	203
s7 S8. Claim limits, literature scope and follow-up conditions	Supplement S12.18	203

S14. Reference identity and exact inspection scope

The unified bibliography uses collision-free global IDs, with all original local IDs and reading scopes retained below and in REFERENCES_SCOPE.json. A shared landing URL alone does not prove that different versioned papers, PDFs, READMEs or captures are identical. No new external retrieval or reproduction was performed for this editorial reconstruction.

S14.1. Hajin Shim, Sung Ju Hwang, Eunho Yang (2018). Joint Active Feature Acquisition and Classification with Variable-Size Set Encoding. Advances in Neural Information Processing Systems 31: 1368-1378

Bibliography identity: [1]. URL: https://proceedings.neurips.cc/paper_files/paper/2018/hash/e5841df2166dd424a57127423d276bbe-Abstract.html

01_complete; local ID shim2018. Preserved 2026-10-26 verifier record of official abstract, authors, bibliography, and selected introductory passages. No full-proof, experiment, or code reproduction. Set-encoding order invariance is not transferred to sequential-action order invariance.

S14.2. Yang Li, Junier Oliva (2021). Active Feature Acquisition with Generative Surrogate Models. Proceedings of the 38th International Conference on Machine Learning 139: 6450-6459

Bibliography identity: [2]. URL: https://proceedings.mlr.press/v139/li21p.html

01_complete; local ID li2021. Preserved verification of official PMLR title, authors, abstract, and bibliography only. No PDF, code, or numerical reproduction. Identity with a separately inherited arXiv cache is not certified.

S14.3. Gavin C. Cawley, Nicola L. C. Talbot (2010). On Over-fitting in Model Selection and Subsequent Selection Bias in Performance Evaluation. Journal of Machine Learning Research 11: 2079-2107

Bibliography identity: [3]. URL: https://jmlr.org/papers/v11/cawley10a.html

01_complete; local ID cawley2010. Preserved official bibliography and abstract verification. No full-proof or experiment reading and no certification of independence for the present split.

S14.4. Oresti Banos, Rafael Garcia, Alejandro Saez (2014). MHEALTH. UCI Machine Learning Repository. DOI 10.24432/C5TW22

Bibliography identity: [4]. URL: https://archive.ics.uci.edu/dataset/319/mhealth%2Bdataset

01_complete; local ID uci319. Preserved official UCI description, creators, citation, DOI, and variable information. No new download or raw-sample revalidation. The DOI is bibliographic identity, not dataset or medical-validity certification. Additional current publisher record: Official description: 10 volunteers, 12 activities, devices on chest, right wrist and left ankle. No raw dataset downloaded here. This experiment uses the historical seven-mask prediction/token cache; original label mapping was not newly verified.

S14.5. Daniel Golovin, Andreas Krause (2011). Adaptive Submodularity: Theory and Applications in Active Learning and Stochastic Optimization. Journal of Artificial Intelligence Research 42: 427-486. DOI 10.1613/jair.3278

Bibliography identity: [5]. URL: https://jair.org/index.php/jair/article/view/10731

01_complete; local ID adaptive-submodularity. Preserved partial verification of official metadata, abstract, edition, and correction-paper abstract. No full-proof reproduction, no established assumption match for the worst-width objective, and no transferred greedy guarantee.

S14.6. Active Feature Acquisition with Incomplete Training Data. arXiv:2609.32325v1.

Bibliography identity: [6]. URL: https://arxiv.org/html/2609.32325v1

01_complete; local ID afa-incomplete. Preserved partial reading of versioned HTML 3.1-3.2, 4.1-4.3, 5.2, and B.2-B.3. Used for fixed predictor, kernel, hard budget, STOP/Bellman, and recovery assumptions. No transfer to arbitrary participant shift or MNAR, and no numerical reproduction.

S14.7. Yuta Kobayashi, Zilin Jing, Jiayu Yao, Hongseok Namkoong, Shalmali Joshi. Learning-To-Measure: In-Context Active Feature Acquisition. ICML 2026, PMLR 306:59720–59752

Bibliography identity: [7]. URL: https://proceedings.mlr.press/v306/kobayashi26a.html

01_complete; local ID l2m. Preserved partial reading of HTML 3.1, 4.1-4.3, 5-6, and A.4-A.5, with a separate official ICML 2026 bibliography record. Scope is pretrained fixed predictor and conditional/meta-policy. No complete cost-sensitive MDP, code, or performance reproduction. Additional current publisher record: Publisher metadata and abstract only in this extension; no code or benchmark reproduction. Context: acquisition with retrospective missingness and uncertainty. Historical partial-read URL retained in prior source: https://arxiv.org/html/2510.12624v2 [Retained read record URL: https://proceedings.mlr.press/v306/kobayashi26a.html]

S14.8. Henrik von Kleist, Alireza Zamanian, Ilya Shpitser, Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Time-varying Feature Settings. JMLR 26(60):1–84, 2025

Bibliography identity: [8]. URL: https://www.jmlr.org/papers/v26/23-1635.html

01_complete; local ID afape_timevarying. Preserved separate literature-Task partial reading on 2026-10-29: v4 dated 2025-04-17, initial submission 2023-12-03. Read 3.1-3.2 observed variables, deterministic classifier and label availability; 3.5 assumptions; 4 positivity; 6.3 regional/global positivity and Theorem 3; Appendix P.2 training/nuisance/test split. JMLR metadata and arXiv passages are separate observations; published-article/v4 byte identity was not checked. Most proofs, estimator derivations, and numeric tables were not checked end to end. Direct reproductions: zero. Observation/snippet hashes bind returned passages, not a full published PDF or HTML.

S14.9. Henrik von Kleist, Alireza Zamanian, Ilya Shpitser, Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Static Feature Settings. arXiv preprint; no journal/conference venue asserted here

Bibliography identity: [9]. URL: https://arxiv.org/abs/2312.03619

01_complete; local ID afape_static. Preserved separate literature-Task partial reading on 2026-10-29: v2 dated 2023-12-07, initial submission 2023-12-06. Read 3.1-3.3 retrospective masks, sequential STOP and given classifier; 5.3 Equation 12 and Theorem 3; MAR/MNAR discussion; Appendix I.2 train/nuisance/test split. Static means time-invariant features, not nonadaptive acquisition. Hybrid-MNAR identification proofs and all empirical results were not independently verified. Direct reproductions: zero. Observation/snippet hashes do not bind a complete published article.

S14.10. Alexander Luke Ian Norcliffe, Changhee Lee, Fergus Imrie, Mihaela Van Der Schaar, Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML 2025, PMLR 267:46784–46814

Bibliography identity: [10]. URL: https://proceedings.mlr.press/v267/norcliffe25a.html

01_complete; local ID sefa. Preserved separate literature-Task partial reading on 2026-10-29: v3 dated 2025-08-06, initial submission 2025-08-03. Read 4 CMI limitations; 5.1-5.3 stochastic encoder/predictor, random-mask training and acquisition score; selected Appendix H splits; I.1 unavailable-test-feature masking; I.2 greedy Fixed MLP; Appendix K selection/repeated initialization. The August arXiv reading follows the July proceedings; published-PDF byte identity was not checked. No code or benchmark run; not every dataset or preprocessing choice audited. Direct reproductions: zero; passage hashes are not full-article hashes.

S14.11. Linus Aronsson, Morteza Haghir Chehreghani. Non-Myopic Active Feature Acquisition via Pathwise Policy Gradients. arXiv preprint; no conference acceptance asserted here

Bibliography identity: [11]. URL: https://arxiv.org/abs/2605.05511

01_complete; local ID nm_ppg. Preserved separate literature-Task partial reading on 2026-10-29: v2 dated 2026-09-29, initial submission 2026-05-06. Read 2 observed-mask actions, hard/soft budgets and STOP; 3.1 Theorem 1/Bellman objective; 3.3 straight-through surrogate and complexity; 4 baselines and E.3 selection and predictor refinement. Claims apply only to read v2 passages; title/date do not establish acceptance. Full consistency/variance proofs unchecked, no empirical performance or safety reproduction. Direct reproductions: zero; passage hashes are not full-article hashes. Separate literature Task38 on 2026-10-31 rechecked the official abstract and version history of arXiv:2605.05511v2 (2026-09-29). This additional reading did not check the full theorem/proof or reproduce performance; no peer-reviewed venue was established from that page.

S14.12. Nathan Kallus, Angela Zhou. Confounding-Robust Policy Improvement. NeurIPS 2018 official abstract record

Bibliography identity: [12]. URL: https://papers.neurips.cc/paper_files/paper/2018/hash/3a09a524440d44d7f19870070a5ad42f-Abstract.html

01_complete; local ID crpi. Preserved separate literature-Task partial reading on 2026-10-29: v3 dated 2019-11-04, initial submission 2018-05-22. Read 2 observational iid tuples, potential outcomes, propensity and policy class; regret formula and 5 assumptions 1-3; 5.1 Theorem 2 finite-sample improvement and baseline inclusion. Numbering/assumptions are from later v3 and not asserted identical to 2018 proceedings. Full proof, propensity extension, optimizer and clinical analysis were not audited. Direct reproductions: zero; observation/snippet hashes are not full published-article hashes.

S14.13. Richard D. Smallwood, Edward J. Sondik. The Optimal Control of Partially Observable Markov Processes over a Finite Horizon. Operations Research 21(5):1071–1088, 1973

Bibliography identity: [13]. URL: https://pubsonline.informs.org/doi/10.1287/opre.21.5.1071

01_complete; local ID smallwood_sondik1973. Official publisher abstract and metadata read; full proof and algorithm not independently reproduced. Finite-horizon piecewise-linear value functions are foundational prior work.

S14.14. Mohammad Ghavamzadeh, Marek Petrik, Yinlam Chow. Safe Policy Improvement by Minimizing Robust Baseline Regret. NeurIPS 2016

Bibliography identity: [14]. URL: https://proceedings.neurips.cc/paper_files/paper/2016/hash/9a3d458322d70046f63dfd8b0153ece4-Abstract.html

01_complete; local ID rbr. Official publisher metadata and abstract; no full proof, code or numerical reproduction in this extension. Reference-relative robust improvement is prior work. [Retained read record URL: https://proceedings.neurips.cc/paper_files/paper/2016/hash/9a3d458322d70046f63dfd8b0153ece4-Abstract.html]

S14.15. Romain Laroche, Paul Trichelair, Remi Tachet Des Combes. Safe Policy Improvement with Baseline Bootstrapping. ICML 2019, PMLR 97:3652–3661

Bibliography identity: [15]. URL: https://proceedings.mlr.press/v97/laroche19a.html

01_complete; local ID spibb. Official publisher metadata and abstract; no full proof or benchmark reproduction in this extension. No SPIBB-style high-probability guarantee is claimed for this cache. [Retained read record URL: https://proceedings.mlr.press/v97/laroche19a.html] Additional retained scope: Official metadata and abstract read on2026-10-31; no full-proof, code or experiment reproduction. Baseline fallback is established prior art.

S14.16. Jiaorong Feng, Qian Li, Ying Li. BRiG-AFA: Bellman Risk-to-Go Learning for Non-Myopic Active Feature Acquisition. arXiv:2608.02305v1, 2026-08-03; preprint

Bibliography identity: [16]. URL: https://arxiv.org/abs/2608.02305

01_complete; local ID brig_afa2026. Separate literature Task38 checked the official arXiv abstract and version/submission metadata on 2026-10-31. Budget-indexed supervised Bellman risk-to-go fitting and the one-step ablation are abstract-level author reports. No full theorem/proof, code or numerical performance reproduction; peer-reviewed venue not established from the inspected page.

S14.17. Nian Si, Fan Zhang, Zhengyuan Zhou, Jose Blanchet (2020). Distributionally Robust Policy Evaluation and Learning in Offline Contextual Bandits. ICML, PMLR119:8884-8894

Bibliography identity: [17]. URL: https://proceedings.mlr.press/v119/si20a.html

01_complete; local ID si2020dro. Official metadata and abstract only, read2026-10-31; no external benchmark or theorem reproduction.

S14.18. Shai Ben-David, Tyler Lu, Teresa Luu, David Pal (2010). Impossibility Theorems for Domain Adaptation. AISTATS, PMLR9:129-136

Bibliography identity: [18]. URL: https://proceedings.mlr.press/v9/david10a.html

01_complete; local ID bendavid2010impossibility. Official metadata and abstract only, read2026-10-31. The small unlabeled-acquisition counterexample illustrates an established limitation; no general novelty claim.

S14.19. Alexander Norcliffe, Changhee Lee, Fergus Imrie, Mihaela van der Schaar, Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML2025,PMLR267:46784–46814.

Bibliography identity: [19]. URL: https://arxiv.org/html/2508.01957v3

02_benchmark; local ID sefa. Actual versioned primary body:Sections3–6,AppendicesH–K; text/response hashes and UTC access inPRIMARY_SOURCES.json. Author-reported experiments,not reproduced.

S14.20. Yuta Kobayashi, Zilin Jing, Jiayu Yao, Hongseok Namkoong, Shalmali Joshi. Learning-To-Measure: In-Context Active Feature Acquisition. ICML2026,PMLR306:59720–59752.

Bibliography identity: [20]. URL: https://arxiv.org/html/2510.12624v2

02_benchmark; local ID l2m. Actual primary body Sections3–5,Theorems3.4/4.2,AppendicesA.1/A.3/A.7. Venue also confirmed at official PMLR306/kobayashi26a. No reproduction.

S14.21. Jingyuan Wang, Zhimei Ren, Ruohan Zhan, Zhengyuan Zhou. Distributionally Robust Policy Learning under Concept Drifts. ICML2025,PMLR267:64244–64281.

Bibliography identity: [21]. URL: https://arxiv.org/html/2412.14297v2

02_benchmark; local ID drift. Actual primary Sections2–5 andAppendixC,estimation conditions and main theorem statements. Deferred asymptotic proof and empirical numbers not reproduced.

S14.22. Eli Ben-Michael, D. James Greiner, Kosuke Imai, Zhichao Jiang. Safe Policy Learning through Extrapolation: Application to Pre-trial Risk Assessment. arXiv2109.11679v4,31March2025 revision.

Bibliography identity: [22]. URL: https://arxiv.org/html/2109.11679v4

02_benchmark; local ID safe. Actual primary Sections3–5,Proposition1 and statistical-safety assumptions. Fixed-baseline lineage,not a claimed new safety principle.

S14.23. Anastasios N. Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, Tal Schuster. Conformal Risk Control. ICLR2024; arXiv2208.02814v4,13June2025 revision.

Bibliography identity: [23]. URL: https://arxiv.org/html/2208.02814v4

02_benchmark; local ID crc. Actual primary Sections1–3 and4.1; bounded monotone exchangeable expected-risk control,nonmonotone limitation,not an acquisition-performance guarantee.

S14.24. Gary Weiss. WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI507,2019.

Bibliography identity: [24]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

02_benchmark; local ID wisdm. Official metadata only;51subjects/four sensor blocks. No dataset download or eligibility certification.

S14.25. Philip Schmidt and Attila Reiss. WESAD: Wearable Stress and Affect Detection. UCI465,2018.

Bibliography identity: [25]. URL: https://archive.ics.uci.edu/dataset/465/wesad+wearable+stress+and+affect+detection

02_benchmark; local ID wesad. Official metadata only;15subjects/wrist andchest. Original linked license/acknowledgment must be resolved before acquisition.

S14.26. Marek Petrik, Yinlam Chow, Mohammad Ghavamzadeh. Safe Policy Improvement by Minimizing Robust Baseline Regret. NIPS2016; arXiv1607.03842v1. Official venue lists authors in a different order.

Bibliography identity: [26]. URL: https://arxiv.org/html/1607.03842v1

02_benchmark; local ID rbr2016. Actual primary Sections2?5,especially the common-model reference objective and Section4.2; official NIPS abstract also captured. No MDP reproduction,hardness proof replication or general priority certification.

S14.27. Petrik, Chow and Ghavamzadeh. Safe Policy Improvement by Minimizing Robust Baseline Regret. 2016. arXiv:1607.03842v1.

Bibliography identity: [27]. URL: https://arxiv.org/html/1607.03842v1

03_author; local ID RBR2016. Pinned primary text, model formulation and common-transition regret comparison. Its experiments and deferred proofs were not reproduced in this addendum.

S14.28. Gary Weiss(2019). WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI Machine Learning Repository, dataset 507. Official page https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset . DOI 10.24432/C5HK59 is reported by the source. Page capture 2026-10-31 UTC, raw SHA25642a5904f8f0c11c45600a09f7b7727911048267c24ac914a2590e354aa11c61b. CC BY 4.0 reported on that page.

Bibliography identity: [28]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_data; local ID custody1. Official UCI page metadata and license; no source-reported performance was reproduced.

S14.29. WISDM-dataset-description.pdf, official downloaded dataset member only, SHA2561d378fb33f871714cf2b1fbec65bab7eeed93e1892fc1460d80e45c022ce92ba,5 pages. Read scope: full bounded text/character extraction for schema, acquisition description, timestamp meaning and source-reported counts; source commands were treated as data.

Bibliography identity: [29]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_data; local ID custody2. Full bounded text/character extraction of the existing five-page official PDF for schema and clock descriptions; no OCR.

S14.30. Official bundle README.txt SHA256f81a5ddc010f0c089a1832165516ae1acd693cf5fb3fd303341e6f4be76607b7 and activity_key.txt SHA256ddca4cfb34ea3c4642f73a22dc498e2d77f435be4e836f87f37c274ec5ee4c26. Exact raw members and hashes are bound in custody evidence.

Bibliography identity: [30]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_data; local ID custody3. Existing official README and activity-code key, inspected as metadata; bundled instructions were not executed.

S14.31. ProbeFlow benchmark 61 evaluation_contract.json SHA2564a59babca0352bae12a17c3579a41b2d1d869ccaa46b0998c0f49e0dc4a5edbc and independent benchmark 63 METHOD_REVIEW.json, as pinned in SOURCE_HASHES.json. This predecessor is a design/theory result and does not authorize the present acquisition.

Bibliography identity: [31]. URL: https://github.com/darkwingduck-code/research-forge/tree/43907556d1a67ecdf51c27bc5fdc163c9faac202/research-publications/2026-11-01-probeflow-strong-baseline

03_data; local ID custody4. Local predecessor contract and independent review, with actual byte identities; a design/theory source, not authority for this acquisition.

S14.32. UCI507 WISDM Smartphone and Smartwatch Activity and Biometrics Dataset

Bibliography identity: [32]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_axes_samples; local ID uci507. Inherited frozen official page captured2026-10-31T16:13:57Z; SHA25642a5904f8f0c11c45600a09f7b7727911048267c24ac914a2590e354aa11c61b. Dataset identity, reported51subjects/18activities/nominal20Hz and CC BY4.0 license only. No new HTTP or external method-performance inference.

S14.33. Official UCI507 bundle already acquired by data66

Bibliography identity: [33]. URL: https://archive.ics.uci.edu/static/public/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset.zip

03_axes_samples; local ID uci507-bundle. Existing local outer SHA2566e0147f181d8f5275918db65eeb9dc842a0185d37cb6b2f30cbf74ee6e205469 and inner SHA2561cf32e8d3a0ecc101bd299fba22545273dcb7de1c9565e0b7844abdfbc6b1695; both verified in one new preparation. No GET, extraction or bundled-code execution. Source lineage only.

S14.34. Ernst,Geurts,Wehenkel. Tree-Based Batch Mode Reinforcement Learning. JMLR6(18):503–556,2005.

Bibliography identity: [34]. URL: https://jmlr.org/papers/v6/ernst05a.html

03_external; local ID FQI2005. Root-captured official landing bibliography/abstract only; no PDF,full proof or experiment reproduction. Broad fitted-Q prior principle; no transferred safety guarantee.

S14.35. Stochastic Encodings for Active Feature Acquisition

Bibliography identity: [35]. URL: https://arxiv.org/html/2508.01957v3

03_external; local ID SEFA. Previously captured primary source and read scope pinned in SOURCE_HASHES.json. Not implemented or reproduced here; no SOTA comparison.

S14.36. Learning-To-Measure: In-Context Active Feature Acquisition

Bibliography identity: [36]. URL: https://arxiv.org/html/2510.12624v2

03_external; local ID L2M. Previously captured primary source/read scope only; not implemented or reproduced; source assumptions do not certify this benchmark.

S14.37. Safe Policy Improvement by Minimizing Robust Baseline Regret

Bibliography identity: [37]. URL: https://arxiv.org/html/1607.03842v1

03_external; local ID RBR2016. Previously captured primary source/read scope. Our reference-first point estimator is not a reproduction or transfer of the robust MDP guarantee.

S14.38. Gary Weiss. WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI2019,CC BY4.0,DOI10.24432/C5HK59.

Bibliography identity: [38]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_external; local ID UCI507. Official saved-source metadata/custody and later exact Root release. Public subject split is separate from global untouched provenance; only phone accelerometer logical channels used.

S14.39. Ernst, Geurts and Wehenkel (2005), Tree-Based Batch Mode Reinforcement Learning

Bibliography identity: [39]. URL: https://jmlr.org/papers/v6/ernst05a.html

03_coverage_diagnostic_v2; local ID FQI2005. Inherited frozen71 capsule: official bibliography and abstract only, SHA256 06ca7cc24bc6066c6ceb5628a5eadf2d2405bad5aa654c31c7ccaa81812d926f. Successive supervised Q approximation is prior art; no full-proof or external reproduction claim.

S14.40. SEFA primary method source, version 2508.01957v3

Bibliography identity: [40]. URL: https://arxiv.org/html/2508.01957v3

03_coverage_diagnostic_v2; local ID SEFA. Inherited71 primary-source capsule only in this task; original reader covered Sections3–6 and AppendicesH–K with scope in SOURCE_HASHES.json. No SEFA implementation or matched result executed here.

S14.41. Learning-To-Measure primary method source, version 2510.12624v2

Bibliography identity: [41]. URL: https://arxiv.org/html/2510.12624v2

03_coverage_diagnostic_v2; local ID L2M. Inherited71 capsule only in this task; original reader covered Sections3–5 and named assumptions/appendices. Distinct information, missingness and planning conditions cannot be imported as guarantees.

S14.42. Gary Weiss (2019), WISDM Smartphone and Smartwatch Activity and Biometrics Dataset

Bibliography identity: [42]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_coverage_diagnostic_v2; local ID WISDM. Inherited official metadata/license capsule; CC BY4.0 and DOI10.24432/C5HK59 are inherited, not generated here. One phone accelerometer; this author did not reopen source archives.

S14.43. SEFA (saved2508.01957v3 primary-paper capsule)

Bibliography identity: [43]. URL: https://arxiv.org/html/2508.01957v3

03_representation; local ID SEFA. Inherited local capsule. Original scope: Sections3–6;AppendicesH–K dataset/split/model/runtime conditions; theoretical CMI failure examples in4,F,G. Not every training-table cell independently checked. Response SHA256=0ce28ff7c41d2d94256a6f456650a86e718ceafae88c878226e3935534010c85; captured-text SHA256=55108784c41343dbc693eaf1f52486d02d2bd41fa19571c2821f67495284f788. No new81retrieval or reproduction.

03_representation_verification; local ID SEFA. Inherited local capsule. Original scope: Sections 3 to 6;Appendices H to K dataset/split/model/runtime conditions; theoretical CMI failure examples in4,F,G. Not every training-table cell independently checked. Response SHA256=0ce28ff7c41d2d94256a6f456650a86e718ceafae88c878226e3935534010c85; captured-text SHA256=55108784c41343dbc693eaf1f52486d02d2bd41fa19571c2821f67495284f788. No new retrieval or reproduction by producer 83.

S14.44. Learning-To-Measure (saved2510.12624v2 primary-paper capsule)

Bibliography identity: [44]. URL: https://arxiv.org/html/2510.12624v2

03_representation; local ID L2M. Inherited local capsule. Original scope: Sections3–5;Theorem3.4,4.2;Assumption3.3,A.5;AppendicesA.1,A.3,A.7 including missingness/real-vs-semisynthetic labels/baseline modifications/planning-compute controls. Response SHA256=53760f8eabe4bf304183150fe691c3246c16ae598c888d16ce5576ccb6ea169d; captured-text SHA256=0191f368275b68f532242216560e803eee833c205f98e6960d7275ac75259402. No new81retrieval or reproduction.

03_representation_verification; local ID L2M. Inherited local capsule. Original scope: Sections 3 to 5;Theorem 3.4,4.2;Assumption 3.3,A.5;Appendices A.1,A.3,A.7 including missingness/real-vs-semisynthetic labels/baseline modifications/planning-compute controls. Response SHA256=53760f8eabe4bf304183150fe691c3246c16ae598c888d16ce5576ccb6ea169d; captured-text SHA256=0191f368275b68f532242216560e803eee833c205f98e6960d7275ac75259402. No new retrieval or reproduction by producer 83.

S14.45. WISDM smartphone and smartwatch activity and biometrics dataset

Bibliography identity: [45]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

03_representation; local ID WISDM. Inherited local capsule. Original scope: Official dataset metadata, subjects, sensors, tasks, access/license links only. No archive,subject values,labels,downloaded PDF or model accessed. Response SHA256=e4059d14f8892a3adab0f7711052a217a1f978dd749d2172056c226bad2f405d; captured-text SHA256=b0f916b8a0e9cfa17c743b6dd69b2d847389d5dbab32ee18de8d95b9bd3f0490. No new81retrieval or reproduction.

03_representation_verification; local ID WISDM. Inherited local capsule. Original scope: Official dataset metadata, subjects, sensors, tasks, access/license links only. No archive,subject values,labels,downloaded PDF or model accessed. Response SHA256=e4059d14f8892a3adab0f7711052a217a1f978dd749d2172056c226bad2f405d; captured-text SHA256=b0f916b8a0e9cfa17c743b6dd69b2d847389d5dbab32ee18de8d95b9bd3f0490. No new retrieval or reproduction by producer 83.

S14.46. Tree-Based Batch Mode Reinforcement Learning

Bibliography identity: [46]. URL: https://jmlr.org/papers/v6/ernst05a.html

03_representation; local ID FQI2005. Official landing-page bibliography and abstract only; not the PDF, full algorithm/proofs or experiments. Inherited response SHA256=06ca7cc24bc6066c6ceb5628a5eadf2d2405bad5aa654c31c7ccaa81812d926f.

03_representation_verification; local ID FQI2005. Official landing-page bibliography and abstract only; not the PDF, full algorithm/proofs or experiments. Inherited response SHA256=06ca7cc24bc6066c6ceb5628a5eadf2d2405bad5aa654c31c7ccaa81812d926f.

S14.47. Double Reinforcement Learning for Efficient Off-Policy Evaluation in Markov Decision Processes

Bibliography identity: [47]. URL: https://jmlr.org/papers/v21/19-827.html

04_method; local ID DRL2020. Root-supplied official landing-page abstract notes only. Note file SHA256 018223699512c49e595fb5ba7adeaf9018417c7d0c1c7b6b4f5c1433a28d979b. No new retrieval, full proof or reproduced experiment by86.

S14.48. A Fine-grained Analysis of Fitted Q-evaluation: Beyond Parametric Models

Bibliography identity: [48]. URL: https://proceedings.mlr.press/v235/wang24be.html

04_method; local ID FQE2024. Root-supplied official landing-page abstract notes only. Note file SHA256 018223699512c49e595fb5ba7adeaf9018417c7d0c1c7b6b4f5c1433a28d979b. No new retrieval, full proof or reproduced experiment by86.

S14.49. On the Foundations of Noise-free Selective Classification

Bibliography identity: [49]. URL: https://jmlr.org/papers/v11/el-yaniv10a.html

05_theory; local ID EY2010. Primary publisher HTML abstract and bibliographic record; web open 2026-11-01. Full proofs not read. Risk–coverage trade-offs and selective classification predate this study. We do not improve their noise-free learning results; we prove a marginal-information paid-action lower bound with participant floors.

S14.50. Selective Classification for Deep Neural Networks

Bibliography identity: [50]. URL: https://papers.nips.cc/paper_files/paper/2017/hash/4a8423d5e91fda00bb7e46540e2b0cf1-Abstract.html

05_theory; local ID GE2017. Primary proceedings HTML abstract, web open 2026-11-01; algorithm and proof not audited. The authors propose selective classifiers targeting risk with high probability. Our algebra neither supplies their statistical guarantee nor validates confidence scores or a data-dependent selection policy.

S14.51. Conditions d'existence de systèmes d'événements associés à certaines probabilités

Bibliography identity: [51]. URL: https://www.numdam.org/item/JMPA_1940_9_19_1-4_51_0/

05_theory; local ID F1940. Primary digitization HTML bibliographic record; publisher-linked primary PDF read via browser only: printed pp.52–54, event existence and nonnegative atoms (web extracted lines43–127). No local PDF download; PDF bytes were not hashed. Classical dependent-event feasibility is the antecedent. We give self-contained two-event and union constructions; we make no originality or first-attribution claim for Fréchet bounds or the floor extension.

S14.52. Dynamic Sensing: Better Classification under Acquisition Constraints

Bibliography identity: [52]. URL: https://proceedings.mlr.press/v37/richman15.html

05_theory; local ID RM2015. Primary publisher HTML abstract and bibliographic record; web open 2026-11-01. Full model/generalization theorem not read. The authors allocate average resources across examples and derive generalization results. Our fixed unconditional cost assumption is narrower; the explicit routing example prevents interpreting a fixed-full certificate as an adaptive impossibility theorem.

S14.53. Official HistGradientBoostingClassifier API

Bibliography identity: [53]. URL: https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.HistGradientBoostingClassifier.html

05_predictors; local ID hgb. Official estimator API documentation only. Candidate mechanism and parameter descriptions, not a performance benchmark or a new algorithm claim. Stable documentation version may differ from the installed version; installed source/signature is frozen by author93. Root-captured 2026-11-01T03:17:35.898945+00:00; bytes SHA256 486cd347769c85d098a6a3635dba7a94bd04a5787752a94e770a711f3d9a3312. This author used the metadata notes and installed API; no full-paper review or external benchmark was performed.

S14.54. Official WISDM dataset landing page

Bibliography identity: [54]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

05_predictors; local ID wisdm. Official dataset landing page only. The existing study uses cached phone accelerometer partitions and its own fixed100sample windows; the original provider description does not

establish local timing regularity or four-stream alignment. Root-captured 2026-11-01T03:17:36.713917+00:00; bytes SHA256 329898f7fb61dfca69fbd432f1dc403b31577130748c80cada75b63ccda418e0. This author used the metadata notes and installed API; no full-paper review or external benchmark was performed.

S14.55. scikit-learn LogisticRegression installed implementation and estimator API

Bibliography identity: [55]. URL: https://scikit-learn.org/stable/modules/generated/sklearn.linear_model.LogisticRegression.html

06_fusion; local ID lr. Installed1.8.0 source/signature/defaults and byte hash inspected locally and bound before values. No new remote retrieval or systematic stacking literature review; the stable API URL identifies the estimator only.

S14.56. scikit-learn HistGradientBoostingClassifier

Bibliography identity: [56]. URL: https://scikit-learn.org/stable/modules/generated/sklearn.ensemble.HistGradientBoostingClassifier.html

06_fusion; local ID hgb. Inherited source93 primary-capture metadata, hash486cd347769c85d098a6a3635dba7a94bd04a5787752a94e770a711f3d9a3312, retrieved2026-11-01T03:17:35.898945Z. Current author read the public capture notes and predecessor source/schema, not a new performance benchmark.

S14.57. UCI WISDM smartphone and smartwatch activity and biometrics dataset

Bibliography identity: [57]. URL: https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset

06_fusion; local ID wisdm. Inherited provider-page metadata hash329898f7fb61dfca69fbd432f1dc403b31577130748c80cada75b63ccda418e0, retrieved2026-11-01T03:17:36.713917Z. No new dataset download or raw collection-independence audit.

S14.58. Mark J. van der Laan, Eric C. Polley and Alan E. Hubbard. Super Learner. Berkeley Working Paper 222, July 2007.

Bibliography identity: [58]. URL: https://biostats.bepress.com/ucbbiostat/paper222/

06_methods; local ID SL2007. Primary author-repository HTML abstract and suggested citation only. V-fold selection of a functional combination and the reported asymptotic oracle comparison; specific weighting parameterization and full proof not inspected.

07_observable; local ID SL2007. Primary author-repository HTML abstract and suggested citation only. Weighted cross-validation and the reported asymptotic oracle comparison; full proof not inspected.

08_empirical; local ID SL2007. Inherited from frozen107; no new full-paper audit here. Primary author-repository HTML abstract and suggested citation only. Weighted cross-validation and the reported asymptotic oracle comparison; full proof not inspected.

S14.59. Gilmer Valdes, Yannet Interian, Efstathios Gennatas and Mark van der Laan. Conditional Super Learner. arXiv:1912.06675v1, 13 December 2019.

Bibliography identity: [59]. URL: https://arxiv.org/html/1912.06675v1

06_methods; local ID CSL2019. Versioned primary HTML: Sections 2.1–2.4, 3.1.1–3.1.2, and the statement/assumptions around Theorem 3.1. No independent proof audit or implementation reproduction.

07_observable; local ID CSL2019. Versioned primary HTML: Sections 2.1–2.4, 3.1.1–3.1.2, and the statement/assumptions around Theorem 3.1. No independent proof audit or implementation reproduction.

08_empirical; local ID CSL2019. Inherited from frozen107; no new full-paper audit here. Versioned primary HTML: Sections 2.1–2.4, 3.1.1–3.1.2, and the statement/assumptions around Theorem 3.1. No independent proof audit or implementation reproduction.

S14.60. Rafael M. O. Cruz, Robert Sabourin, George D. C. Cavalcanti and Tsang Ing Ren. META-DES: A Dynamic Ensemble Selection Framework using Meta-Learning. arXiv:1810.01270v1, 30 September 2018.

Bibliography identity: [60]. URL: https://arxiv.org/html/1810.01270v1

06_methods; local ID DES2018. Versioned primary HTML Sections 2.3, 3.1–3.2.2 and 4.2. The primary arXiv record identifies Pattern Recognition 48(5), 1925–1935; archive date is not journal publication date. The original journal year was not independently confirmed here.

07_observable; local ID DES2018. Versioned primary HTML Sections 2.3, 3.1–3.2.2 and 4.2. The primary arXiv record identifies Pattern Recognition 48(5), 1925–1935; archive date is not journal publication date. The original journal year was not independently confirmed here.

08_empirical; local ID DES2018. Inherited from frozen107; no new full-paper audit here. Versioned primary HTML Sections 2.3, 3.1–3.2.2 and 4.2. The primary arXiv record identifies Pattern Recognition 48(5), 1925–1935; archive date is not journal publication date. The original journal year was not independently confirmed here.

S14.61. Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. NIPS 2017, volume 30; inspected arXiv:1705.08500v1, 23 May 2017.

Bibliography identity: [61]. URL: https://arxiv.org/html/1705.08500v1

06_methods; local ID SGR2017. Versioned primary HTML Sections 2–3 and Algorithm 1, with primary proceedings identity check. IID labeled-sample setting and risk-bound search inspected; no complete proof or reproduction.

07_observable; local ID SGR2017. Versioned primary HTML Sections 2–3 and Algorithm 1, with primary proceedings identity check. IID labeled-sample setting and risk-bound search inspected; no complete proof or reproduction.

08_empirical; local ID SGR2017. Inherited from frozen107; no new full-paper audit here. Versioned primary HTML Sections 2–3 and Algorithm 1, with primary proceedings identity check. IID labeled-sample setting and risk-bound search inspected; no complete proof or reproduction.

S14.62. Chuan Guo, Geoff Pleiss, Yu Sun and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. ICML2017, PMLR70:1321–1330.

Bibliography identity: [62]. URL: https://proceedings.mlr.press/v70/guo17a.html

06_methods; local ID GUO2017. Primary proceedings identity/abstract and arXiv:1706.04599v2 (3 August2017) HTML Section4.2, matrix/vector and temperature scaling. Logit inputs, validation NLL and class-change distinction inspected; no guarantee of achieved calibration or reproduction.

07_observable; local ID GUO2017. Primary proceedings identity/abstract and arXiv:1706.04599v2 (3 August2017) HTML Section4.2, matrix/vector and temperature scaling. Logit inputs, validation NLL and class-change distinction inspected; no guarantee of achieved calibration or reproduction.

08_empirical; local ID GUO2017. Inherited from frozen107; no new full-paper audit here. Primary proceedings identity/abstract and arXiv:1706.04599v2 (3 August2017) HTML Section4.2, matrix/vector and temperature scaling. Logit inputs, validation NLL and class-change distinction inspected; no guarantee of achieved calibration or reproduction.

S14.63. Yang Li and Junier Oliva. Active Feature Acquisition with Generative Surrogate Models. ICML 2021, PMLR 139:6450–6459.

Bibliography identity: [63]. URL: https://proceedings.mlr.press/v139/li21p.html

06_methods; local ID GSM2021. Primary proceedings identity/abstract and arXiv:2010.02433v2 (11 February 2021) HTML Section 2–2.1, Algorithm 1 and Prediction Model paragraph. Conference/preprint byte-equivalence not asserted.

07_observable; local ID GSM2021. Primary proceedings identity/abstract and arXiv:2010.02433v2 (11 February 2021) HTML Section 2–2.1, Algorithm 1 and Prediction Model paragraph. Conference/preprint byte-equivalence not asserted.

08_empirical; local ID GSM2021. Inherited from frozen107; no new full-paper audit here. Primary proceedings identity/abstract and arXiv:2010.02433v2 (11 February 2021) HTML Section 2–2.1, Algorithm 1 and Prediction Model paragraph. Conference/preprint byte-equivalence not asserted.

S14.64. Michael Valancius, Maxwell Lennon and Junier Oliva. Acquisition Conditioned Oracle for Nongreedy Active Feature Acquisition. ICML 2024, PMLR 235:48957–48975.

Bibliography identity: [64]. URL: https://proceedings.mlr.press/v235/valancius24a.html

06_methods; local ID ACO2024. Primary proceedings identity/abstract and arXiv:2302.13960v1 (27 February 2023) HTML Sections 3.1–3.3 and Algorithm 1. Detailed claims refer to this preprint version, without claiming final-version identity.

07_observable; local ID ACO2024. Primary proceedings identity/abstract and arXiv:2302.13960v1 (27 February 2023) HTML Sections 3.1–3.3 and Algorithm 1. Detailed claims refer to this preprint version, without claiming final-version identity.

08_empirical; local ID ACO2024. Inherited from frozen107; no new full-paper audit here. Primary proceedings identity/abstract and arXiv:2302.13960v1 (27 February 2023) HTML Sections 3.1–3.3 and Algorithm 1. Detailed claims refer to this preprint version, without claiming final-version identity.

S14.65. Henrik von Kleist, Alireza Zamanian, Ilya Shpitser and Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Time-varying Feature Settings. JMLR26(60):1–84,2025.

Bibliography identity: [65]. URL: https://www.jmlr.org/beta/papers/v26/23-1635.html

06_methods; local ID AFAPE2025. Primary journal identity/abstract and arXiv:2312.01530v4 (17 April2025) HTML Sections3.3,3.5,4.1–4.2. NDE, NUC, positivity and cross-fitting remarks inspected; semi-offline estimators author-reported from abstract only. No PDF access or full proof audit.

07_observable; local ID AFAPE2025. Primary journal identity/abstract and arXiv:2312.01530v4 (17 April2025) HTML Sections3.3,3.5,4.1–4.2. NDE, NUC, positivity and cross-fitting remarks inspected; semi-offline estimators author-reported from abstract only. No PDF access or full proof audit.

08_empirical; local ID AFAPE2025. Inherited from frozen107; no new full-paper audit here. Primary journal identity/abstract and arXiv:2312.01530v4 (17 April2025) HTML Sections3.3,3.5,4.1–4.2. NDE, NUC, positivity and cross-fitting remarks inspected; semi-offline estimators author-reported from abstract only. No PDF access or full proof audit.

S14.66. SciPy 1.16.1 minimize SLSQP official reference

Bibliography identity: [66]. URL: https://docs.scipy.org/doc/scipy-1.16.1/reference/optimize.minimize-slsqp.html

06_mixture; local ID SCIPY116. Version-matched interface and stopping criteria inspected 2026-11-01; installed Python/binary/docstring hashes are separate.

S14.67. SciPy latest SLSQP reference, labeled 1.18.0 at access

Bibliography identity: [67]. URL: https://docs.scipy.org/doc/scipy/reference/optimize.minimize-slsqp.html

06_mixture; local ID SCIPYLATEST. Inspected 2026-11-01; not substituted for installed 1.16.1.

S14.68. On Calibration of Modern Neural Networks

Bibliography identity: [68]. URL: https://proceedings.mlr.press/v70/guo17a.html

06_mixture; local ID GUO2017. Attribution through the frozen methodological predecessor's primary-source comparison; no new reproduction.

S14.69. Yang Li and Junier Oliva. Active Feature Acquisition with Generative Surrogate Models. ICML2021; inspected arXiv:2010.02433v2,11 February2021.

Bibliography identity: [69]. URL: https://arxiv.org/html/2010.02433v2

07_joint_world; local ID GSM2021. Primary versioned HTML Sections1 and2.1, equations1-2; proceedings identity previously checked in99, not byte identity.

S14.70. Michael Valancius, Maxwell Lennon and Junier Oliva. Acquisition Conditioned Oracle for Nongreedy Active Feature Acquisition. ICML2024; inspected arXiv:2302.13960v1,27 February2023.

Bibliography identity: [70]. URL: https://arxiv.org/html/2302.13960v1

07_joint_world; local ID ACO2024. Primary versioned HTML Sections3.1-3.2, equations1-4 and Algorithm1. Final ICML2024/preprint identity not asserted.

S14.71. Garud N. Iyengar. Robust Dynamic Programming. Mathematics of Operations Research30(2):257-280,1 May2005.

Bibliography identity: [71]. URL: https://pubsonline.informs.org/doi/abs/10.1287/moor.1040.0129

07_joint_world; local ID IYENGAR2005. Primary publisher abstract and bibliographic citation via web tool, lines130-188. Full theorem/proof not accessed; direct HTTP403 preserved.

S14.72. Charles F. Manski. Identification and Statistical Decision Theory. arXiv:2204.11318v2,21 March2024; primary record reports Econometric Theory41(2025):977-993.

Bibliography identity: [72]. URL: https://arxiv.org/abs/2204.11318v2

07_joint_world; local ID MANSKI2024. Versioned primary abstract/metadata only; no full-text or theorem audit. v1 HTML404 preserved as retrieval limitation.

S14.73. SciPy1.16.1 Manual: linprog(method=highs).

Bibliography identity: [73]. URL: https://docs.scipy.org/doc/scipy-1.16.1/reference/optimize.linprog-highs.html

08_empirical; local ID SCIPY116. Official versioned documentation checked2026-11-01: A_ub upper-bound convention, nonnegative bounds, inequality/equality marginals and sign notes. No optimizer implementation reproduction.

S14.74. Eitan Altman. Constrained Markov Decision Processes. First edition, Routledge, copyright1999,256 pages.

Bibliography identity: [74]. URL: https://www.routledge.com/Constrained-Markov-Decision-Processes/Altman/p/book/9781315140223

08_theory; local ID ALTMAN1999. Official publisher product metadata, description and contents only. Description covers occupation/performance vectors, LP and Lagrangian dual; contents include number of randomizations. Book proofs not inspected. This establishes classical context, not this study's theorem.

S14.75. Pascal Poupart, Aarti Malhotra, Pei Pei, Kee-Eung Kim, Bongseok Goh and Michael Bowling. Approximate Linear Programming for Constrained Partially Observable Markov Decision Processes. AAAI2015.

Bibliography identity: [75]. URL: https://ojs.aaai.org/index.php/AAAI/article/view/9655

08_theory; local ID POUPART2015. Official article metadata and abstract obtained directly as gzip-compressed HTTP200 payload, decoded locally. Web-tool earlier returned an access-control page. Title, authors and page3342 also checked against official AAAI2015 contents search result. No PDF fetched, no paper theorem audit or reproduction. Official DOI10.1609/aaai.v29i1.9655 is bibliographic metadata, not proof verification.

S14.76. Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. Advances in Neural Information Processing Systems30,2017.

Bibliography identity: [76]. URL: https://papers.neurips.cc/paper_files/paper/2017/hash/4a8423d5e91fda00bb7e46540e2b0cf1-Abstract.html

08_theory; local ID SELECTIVE2017. Official proceedings abstract and metadata only; risk/coverage tradeoff, not a group-coverage theorem or acquisition algorithm reproduction.

S14.77. Alexander Luke Ian Norcliffe, Changhee Lee, Fergus Imrie, Mihaela Van Der Schaar and Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML2025, PMLR267:46784–46814.

Bibliography identity: [77]. URL: https://proceedings.mlr.press/v267/norcliffe25a.html

08_theory; local ID NORCLIFFE2025. Official proceedings abstract and citation metadata only; stochastic-encoding AFA is a modern method family. Its trained baselines, results, architecture and complexity were not reproduced.

S14.78. Garud N. Iyengar. Robust Dynamic Programming. Mathematics of Operations Research30(2):257–280,2005.

Bibliography identity: [78]. URL: https://pubsonline.informs.org/doi/abs/10.1287/moor.1040.0129

08_theory; local ID IYENGAR2005. Current direct403 and web timeout preserved. Prior108 publisher metadata/abstract evidence read; no new full theorem verification. Our finite common-policy proof and counterexamples are self-contained.

S14.79. SciPy linprog API documentation; installed implementation1.16.1.

Bibliography identity: [79]. URL: https://docs.scipy.org/doc/scipy/reference/generated/scipy.optimize.linprog.html

09_transport; local ID SCIPY. Root supplied official URL2026-11-02; author read installed1.16.1 docstring for A_ub/bounds/method/marginals; no new network or solver-code audit.

S14.80. Distributionally Robust Optimization, arXiv:2411.02549v3.

Bibliography identity: [80]. URL: https://arxiv.org/abs/2411.02549v3

09_transport; local ID DRO. Root reported abstract-only inspection2026-11-02. Author did not download/ hash full paper or reproduce algorithms; general context only, no novelty inference.

S15. Conditional history control: full method, proof, outcomes and limits

This chapter retains the new primary source method and technical evidence under its own contract. The earlier S1-S14 constructions remain unchanged. Source-local S-numbers inside a retained derivation refer to that source, not to an older global chapter.

TUNE fitting advantage, participant OOF development selection and CAL evaluation are distinct. Generic raw comparison-label corrections are reporting-only. Full fit-LP and privileged-oracle certificate scopes are not interchangeable.

S15.1. Coherent worlds, information and constrained LP

Each original row is one coherent world containing fixed potential cached summaries for all masks. Offline fitting may use its label and person group to construct equal-person loss and coverage coefficients. The deployed actor receives neither label, identity, row index nor unbought output. It sees the order of bought axes and every past current-cumulative-mask token. A token is cached argmax class and one of four confidence bins, with equality at .45/.60/.80 entering the higher bin.

Root variables choose free prior prediction, free abstention or a first axis. Subsequent prediction/buy variables are products of policy action probabilities only. They exclude environmental observation probability. Compatible-row frequencies from the same original law enter the linear C/E/K coefficients. Rebalancing people after each observation would change that law and is not done.

For positive parent mass each child-to-parent ratio is a legal behavioral probability and the leftover is abstention. Zero parent implies all children zero and that history is unreachable. Induction on the complete paid history proves equality between row-wise actor expectations and the LP coefficients. Only TUNE-supported histories are stored; the prespecified shared fallback immediately predicts current-mask argmax on an unsupported CAL history and buys nothing further.

The optimized class is deliberately limited to these current-mask tokens. It does not expose raw paid features or all possible already-paid submask outputs. The mathematical optimum cannot be extended to every available raw feature, richer posterior or omitted terminal expert. Numerical certificates are checked to1e-7; the real-data optimum is not asserted as an exact rational theorem.

Algorithm S36. Constrained finite-history realization LP with a strong ex ante-order control

Require: Hash-bound TRAIN-only ET54 argmax/max-confidence bank for mask0..7; TUNE labels and person groups for fitting only. Paid-history current-mask tokens, cuts .45/.60/.80, max3 purchases, price .05, wrong loss1, abstention .4. Equal-person mean coverage .50 and each fitting person .25; same rights for full adaptive and six-order static.

Ensure: A frozen common actor for each class, its complete supported-history table and ex ante order mixture where applicable. TUNE/CV/CAL person-level C,E,K,J, fallback/correction/harm/cost and sparse LP/process certificates; retained no_gain or failure.

1. Validate source hashes and documented numeric schemas. Read only allowed fields locally; never import the producer actor or model pickle.
2. For each fixed participant-CV fold, make the support graph and coefficients from fitting4 people only. Enumerate complete paid token histories, keeping prior actions and past tokens.
3. Create nonnegative root and history-action realization weights. Give every observation child the same parent-action upper bound, with leftover mass assigned to abstention.
4. For static add six ex ante order masses, root-axis coupling and first-history next-purchase caps. Keep observation-dependent prediction, stopping and abstention.
5. Minimize macro J with sparse LPs, then K, then maximize C on preceding optimum faces. Reconstruct conditional actions by child/parent ratios and verify person coefficients against the actor.
6. Evaluate each CV actor on its heldout4 using the fixed unsupported-history fallback. Select adaptive only if both OOF coverage gates pass and its unrounded deltaJ<-1e-9; otherwise static.
7. Fit both final classes on all TUNE8; Y-first is a fixed paired diagnostic only. Lock support, all weights, ties, files and the CV-selected class before reading CAL.
8. On CAL only evaluate the locked actors, literal controls and separately privileged label/future-aware oracle. Run fixed-seed cached controller replay without feeding truth/identity/unbought outputs to actor.
9. Preserve all denominators and resources. A useful CAL gain requires both original strict coverage floors and adaptive deltaJ<-1e-9; process/solver/resource failure is not no_gain.
10. Freeze reporting artifacts for a different actual reviewer. Keep exposure, finite-class, physical-cost and novelty limits; activate no skill or global setting.

$$J = 0.05K + E + 0.4(1 - C)$$

E is unconditional wrong-prediction mass, C prediction mass and K expected paid axes; purchases remain charged on final abstention.

$$a_0 + f_0 + \sum_A \theta_A = 1$$

Before any observation choose free abstention, fixed free-prior prediction or first axis A.

$$p_{A,s} + \sum_{B \neq A} u_{A,s,B} \leq \theta_A$$

Different observations s each have the same parent upper bound; they are not summed as policy-flow children.

$$v_{A,s,B,t} + w_{A,s,B,t} \leq u_{A,s,B}$$

The second paid history may predict, abstain or buy the sole remaining axis.

$$z_{A,s,B,t,r} \leq w_{A,s,B,t}$$

The full paid history terminates by current-mask prediction or abstention.

$$\theta_A = \sum_{o \in O_A} \lambda_o, \quad u_{A,s,B} \leq \lambda_{A,B,C}$$

Static order masses are chosen before observations. Observation-dependent stopping remains allowed.

$$\overline{C} = \left(\frac{1}{G}\right) \sum_{g=1}^{G} C_g \geq 0.50, \quad C_g \geq 0.25$$

The same fitting coverage conditions apply to both classes; CAL gate assesses them without refitting.

S15.2. A strong static class and constructive inclusion

Static chooses one of all six complete orders before any observations. It can predict, stop or abstain after every token, and can randomize at every legal decision. For order o=(A,B,C), lambda_o is its ex ante mass. At first-history s the continued mass u_o(s) is at most lambda_o. Root-axis mass is the sum of the two orders beginning with A.

Let r_o(s)=lambda_o-u_o(s). Flow feasibility gives p(s)<=sum r_o(s). Allocate prediction mass p_o(s)=p(s)r_o(s)/sum r, or zero when sum r is zero. Conditional on the preselected order, continue with u_o/lambda_o, predict with p_o/lambda_o and abstain with the remainder. After B the order identifies the sole remaining C, so subsequent ratios are unchanged. This implements every coupled LP solution with an order selected before observing s.

Conversely any such fixed-order actor yields feasible coupled realization weights. The static LP is therefore the full matching fixed-order class on this support, not a forced-order or fixed-threshold surrogate. Adaptive contains it, so the TUNE adaptive optimum cannot exceed static. The small independent Fraction oracle gives J=1/10 versus1/8 in a synthetic routing example; those values validate the representation and are not empirical performance.

$$p_o(s) = p(s) \frac{\lambda_o - u_o(s)}{\sum_{q \in O_A} (\lambda_q - u_q(s))}$$

Defined when the denominator is positive. For zero residual capacity feasibility forces prediction mass zero.

S15.3. Participant CV, final fit and one-shot boundary

Before values were decoded, Root added a fixed twofold practical selector. The original14LP contract is preserved; the amended26LP contract retained the same CPU, RAM, wall and IO caps. The sorted TUNE people0..3 and4..7 swap fitting and holdout roles. Each fold graph, support, objective, ties and probabilities is constructed from its fitting4 only. Poisoning all heldout labels and paid tokens leaves the fit matrix/history identical in a pre-value self-check.

The two heldout sets yield eight OOF person rate vectors from two different fitted actors. These are development diagnostics, not one identity-conditioned deployable actor or a fresh cohort. Adaptive is chosen only if both OOF methods pass mean.50 and every-person.25 and adaptive J is lower by more than1e-9. Otherwise static is chosen. Both final actors are then fit on all TUNE8.

The exclusive PRE_VALUE_SEAL binds the exact contract/code/tests/input hashes. Four CV fits and four final fits each use three lexicographic LPs: J, K and then maximum C on locked optimum faces. Remaining ties follow deterministic ordered HiGHS-ds output, with no uniqueness assertion. All policy/certificate hashes

and the CV class are written in TUNE_LOCK before CAL np.load. The selector cannot change after CAL. No accepted scientific launch is retried.

S15.4. Actual outcome: fitted improvement, heldout regression

TUNE adaptive J=0.465403574 improves over static 0.474064787 while both mean coverages are approximately.50. On participant OOF, however, adaptive J=0.648135368 is worse than static 0.614714591 by 0.033420777696. Both OOF coverage gates pass. The locked practical selector therefore chooses full_static.

A generic comparison helper left a reporting-label error in the immutable raw TUNE object: it calls the fitted optimum difference a limited exposed-development gain and uses CAL-named coverage keys. REPORTING_SCOPE_CORRECTION.json binds the original result hash and corrects this interpretation to fit-only optimum difference. TUNE improvement is not heldout useful gain. Raw numbers/code/logs are preserved and were not rerun or edited.

On reused CAL the adaptive/static mean coverages are 0.579668276/0.569936044 and minimum-person coverages 0.481599895/0.459028767. Both original strict floors pass. Adaptive error mass is 0.328937230 versus 0.311608279, purchases 1.930761711 versus 1.822020128. The unrounded loss difference is +0.018873137736314383, so this result is no_gain with regression. The CV-selected actor is exactly the final static actor; its improvement relative to itself is zero.

Coverage is constrained by the same lower floors, not forced equal in realization. Adaptive predicts on more CAL mass and also makes more wrong predictions and purchases. The comparison is a common constrained-objective contrast, not an equal-realized-coverage risk curve. The Y-first paired diagnostic gives the same adaptive policy and effectively the same static result up to numerical error; it was not used to choose a winner.

Table S160: Same TRAIN-only bank, analytic policy expectations. All8people retained; E is unconditional.

Split	Class	J	C	E	K	Min C
TUNE	adaptive	0.465403574	0.500000000	0.171040798	1.887255513	0.400516550
TUNE	static	0.474064787	0.500000000	0.184219001	1.796915730	0.407557529
CAL	adaptive	0.593608005	0.579668276	0.328937230	1.930761711	0.481599895
CAL	static	0.574734868	0.569936044	0.311608279	1.822020128	0.459028767

Table S161: Prespecified twofold participant OOF on TUNE; different fold actors, not a new cohort.

Class	J	C	E	K	Min C
adaptive	0.648135368	0.614976206	0.402471158	1.833093864	0.533333333
static	0.614714591	0.577029946	0.359699664	1.716538096	0.470005136




Figure S41: A fitted adaptive advantage reverses in fixed participant CV and reused CAL. Coverage gates pass; all terminal purchase depths remain charged.

S15.5. What fallback, correction and the privileged oracle show

On CAL unsupported-history fallback contributes prediction mass 0.102309567 for adaptive and 0.106104562 for static. The fallback is fixed immediate prediction, not learned uncertainty handling. It can increase coverage and error together. These supported-history policies therefore do not provide safety or a guarantee for novel response vectors.

Relative to the fixed free-prior label, CAL adaptive corrects unconditional mass 0.226027709 and harms 0.028123477; static corrects 0.232922181 and harms 0.027652820. These transitions include only emitted predictions. Abstentions remain in1-C. They are expected masses against a deterministic prior, not counts of unique helped people or a causal physical intervention.

The separately privileged oracle knows each true label and every mask outcome. It selects the cheapest correct/wrong mask using per-person cost-category mass constraints and attains CAL J=0.193677266. This is a nonexecutable lower-bound diagnostic, not a deployment baseline or the method score. It suggests remaining label-dependent potential in the fixed bank, without proving that a permitted observable controller can identify it.

Literal fixed masks, prior, free abstention and fixedYconfidence45 are retained in a separate diagnostic table. The new uncalibrated TRAIN-only bank is not the calibrated/refit predecessor bank; its threshold-control numbers must not be substituted into previous studies. Free abstention J=.4 fails the coverage constraint, while passing coverage alone does not establish low accepted-error risk.

S15.6. Complexity, correctness and observed process

For H supported histories and G people, the three-axis model has O(H) action variables/structural nonzeros and O(GH) stored person coefficient entries. LP constraints are CSR. Complete support construction visits all legal axis orders and compatible paid-token branches of TUNE only. Full histories can grow exponentially

in a variable horizon; complexity is relative to the explicit history representation. No new polynomial-time general POMDP solution is claimed.

The final adaptive/static models have 15792/15798 variables and 12291 supported histories. Inequality nonzeros are 61811/62479. A single child completed26LPs, including the two separately privileged split diagnostics, in 79.469s wall/71.015625s CPU, peak 139259904bytes, read 46031934bytes and wrote 4053429bytes. Exit and retained HANDLE code were0; stderr was empty.

Fourteen pre-value synthetic tests cover the independent Fraction exhaustive tree optimum, static inclusion/decomposition, primal/dual checks, unequal group denominators, actor/coefficient consistency, hidden-label/unbought poison, fixed-fold exclusion, fallback/zero-parent/hash/schema/failure handling and a full fixture lock→CAL entrypoint. Fixed-seed cached replay validates action/observation/state/cost execution, but repeated rows and seeds are not independent people or LLM/native episodes.

Windows Job accepted userCPU, committed-memory and one-process limits; retained-HANDLE polling observed total CPU/wall/peak/IO. Assignment follows process creation and polling can overshoot. Actual native thread count was not observed despite requesting1. This is not OS security isolation. Authoring model tokens/money are unknown, separate from zero experimental model/API calls.

S15.7. Policy equivalence and static proof

Every legal complete-memory behavioral actor maps to feasible realization weights by multiplying only action probabilities along its histories. The reverse map divides child weights by positive parents and assigns the slack to abstention. Observation frequencies enter row coefficients, never the flow upper bounds. Different observation children each inherit the same bound; summing them would impose a false restriction.

Induction over paid history proves matching terminal and purchase expectations for each original row. Equal-person averaging then yields all person C/E/K/J coefficients. Off-support fallback is fixed and identical. Zero parent is unreachable; its safe-abstain definition has no expected effect. Floating normalization is bounded and raw-to-actor person-component shift is recorded for each of8fits.

Static necessity follows by integrating the ex ante order coin. Sufficiency follows by residual-capacity prediction allocation separately at each first token. This allocation does not alter the pre-observation order masses. After the second purchase the path uniquely identifies the order, so ordinary child/parent ratios complete the actor. METHOD_PROOF.md contains the full constructive argument and exact small-example scope.

S15.8. Source custody and information architecture

The only decoded original values are authorized snapshot y/subjects/row_index/window_id and enhanced/enhanced_max_probability/row_index from18allowlisted NPZ files, with allow_pickle=False. Snapshot X remains lazy and unread. Baseline, margins, original TRAIN, FINAL, model pickle and every other private path are excluded. No original NPZ or per-row values are copied to public artifacts or external APIs.

SOURCE_AUDIT binds producer source/contract/metadata/custody; PREPARATION_AUDIT binds headers and12current policy hashes. This is source-level provenance for the TRAIN-only predictor version, not a retrospective raw-training audit. Model fits/inference calls in this study are0. Own compressed policy/certificate files contain fitted aggregate parameters, not copied original row payloads, and are linked through PRIVATE_MANIFEST only.

Actor.py accepts policy parameters, the paid token history and (for static) the previously sampled order. Expected evaluation and stochastic replay are separate consumers of that same sanitized interface. Truth is used after a terminal decision for error/correction/harm scoring. The interface is cooperative software separation, not a security sandbox.

S15.9. All primary participant denominators and masses

Each split has8original people; TUNE7845 and CAL6437 windows. These are repeated dependent observations, not14282independent people. Indices are split-local sorted-person positions without identity lists. Correct mass is C-E; E/C is null when C=0. Macro rates average person rates equally; pooled rates are separate in NUMERICAL_RESULTS.

Both CAL classes pass strict mean and each-person floors. The full person tables, including the lowest-coverage person, remain below. Passing coverage is only one feasibility condition; accepted-error fractions are not small merely because the gate passes.

Table S162: TUNE full_adaptive: partition-local person indices, no subject ID export.

Person	n	C	E	K	J	E/C
0	797	0.596772969	0.172824163	1.802854465	0.424257699	0.289597841

Person	n	C	E	K	J	E/C
1	630	0.509915798	0.177206738	1.935027104	0.469991774	0.347521569
2	1099	0.400516550	0.187892544	2.027153295	0.529043588	0.469125542
3	1072	0.467308091	0.146119632	1.855481562	0.451970474	0.312683719
4	1368	0.522865856	0.176374627	1.790966884	0.456776629	0.337322901
5	630	0.421365663	0.066434381	1.762349985	0.386005615	0.157664440
6	647	0.611636274	0.223484573	1.974709761	0.477565551	0.365388029
7	1602	0.469618800	0.217989729	1.949501051	0.527617261	0.464184416

Table S163: TUNE full_static: partition-local person indices, no subject ID export.

Person	n	C	E	K	J	E/C
0	797	0.625284549	0.199549321	1.753281541	0.437099578	0.319133618
1	630	0.469862862	0.163964085	1.881209984	0.470079440	0.348961578
2	1099	0.407557529	0.212035674	1.771414234	0.537583374	0.520259494
3	1072	0.533090734	0.215762476	1.786242777	0.491838321	0.404738747
4	1368	0.471194991	0.177335342	1.774320989	0.477573395	0.376352349
5	630	0.421342954	0.072587035	1.650150393	0.386557373	0.172275421
6	647	0.627658763	0.251577497	1.891872879	0.495107635	0.400818902
7	1602	0.444007619	0.180940577	1.866833045	0.496679181	0.407516829

Table S164: CAL full_adaptive: partition-local person indices, no subject ID export.

Person	n	C	E	K	J	E/C
0	630	0.592150613	0.357229978	2.073083646	0.624023915	0.603275535
1	601	0.707134461	0.482808134	1.966458355	0.698277267	0.682767084
2	596	0.481599895	0.183243985	1.657943206	0.473501187	0.380490085
3	812	0.543144751	0.299302386	1.879625754	0.576025774	0.551054550
4	814	0.604902043	0.367415522	1.930439894	0.621976700	0.607396729
5	738	0.575285882	0.269982321	1.881076916	0.533921814	0.469301141
6	644	0.635789097	0.335995502	2.001794254	0.581769576	0.528470060
7	1602	0.497339469	0.335520016	2.055671665	0.639367811	0.674629779

Table S165: CAL full_static: partition-local person indices, no subject ID export.

Person	n	C	E	K	J	E/C
0	630	0.544788414	0.309867779	1.995668432	0.591735835	0.568785553
1	601	0.723884212	0.499011189	1.829923865	0.700953697	0.689352220
2	596	0.459028767	0.158443721	1.567658690	0.453215149	0.345171660
3	812	0.540124563	0.281503873	1.817368929	0.556322494	0.521183246
4	814	0.660968243	0.421194419	1.747030173	0.644158631	0.637238511
5	738	0.520581972	0.196495397	1.746704626	0.475597839	0.377453326
6	644	0.642081478	0.331270469	1.944037478	0.571639752	0.515932137
7	1602	0.468030704	0.295079384	1.927768826	0.604255544	0.630470142

S15.10. Strong static masses and literal controls

All six ex ante order variables were offered. The TUNE optimum puts all order mass on Y-X-Z while retaining observation-dependent early stopping/abstention. This observed degenerate mixture is a fitted result, not a restriction to one order. Free-prior and root-abstain masses remain legal and were optimized in both classes.

Literal fixed-mask, free-abstain and fixedYconfidence45 controls are diagnostic only. Every fixed-mask control always predicts its own cached argmax. FixedYconfidence45 buysY then predicts iff its stored confidence is at least.45; it is not the historical calibrated/refit threshold policy. None replaces full static as the primary comparator.

Table S166: Final static ex ante order weights, selected before CAL.

Order	Mass
XYZ	0.000000000000
XZY	0.000000000000
YXZ	1.000000000000
YZX	0.000000000000
ZXY	0.000000000000
ZYX	0.000000000000

Table S167: Literal diagnostic controls; useful floors assessed, no CAL winner selection.

Split	Control	J	C	E	K	Floors
TUNE	fixedY confidence45	0.445253508	0.244842079	0.093190339	1.000000000	False
TUNE	fixed mask0 predict	0.945967265	1.000000000	0.945967265	0.000000000	True
TUNE	fixed mask1 predict	0.762041301	1.000000000	0.712041301	1.000000000	True
TUNE	fixed mask2 predict	0.748877820	1.000000000	0.698877820	1.000000000	True
TUNE	fixed mask3 predict	0.785906636	1.000000000	0.685906636	2.000000000	True
TUNE	fixed mask4 predict	0.800392003	1.000000000	0.750392003	1.000000000	True
TUNE	fixed mask5 predict	0.824899013	1.000000000	0.724899013	2.000000000	True
TUNE	fixed mask6 predict	0.790569968	1.000000000	0.690569968	2.000000000	True
TUNE	fixed mask7 predict	0.842433209	1.000000000	0.692433209	3.000000000	True
TUNE	free abstain	0.400000000	0.000000000	0.000000000	0.000000000	False
CAL	fixedY confidence45	0.445403480	0.212401512	0.080364085	1.000000000	False
CAL	fixed mask0 predict	0.944737552	1.000000000	0.944737552	0.000000000	True
CAL	fixed mask1 predict	0.775149735	1.000000000	0.725149735	1.000000000	True
CAL	fixed mask2 predict	0.754622055	1.000000000	0.704622055	1.000000000	True
CAL	fixed mask3 predict	0.755745742	1.000000000	0.655745742	2.000000000	True
CAL	fixed mask4 predict	0.788642022	1.000000000	0.738642022	1.000000000	True
CAL	fixed mask5 predict	0.804000589	1.000000000	0.704000589	2.000000000	True
CAL	fixed mask6 predict	0.811709597	1.000000000	0.711709597	2.000000000	True
CAL	fixed mask7 predict	0.816101715	1.000000000	0.666101715	3.000000000	True
CAL	free abstain	0.400000000	0.000000000	0.000000000	0.000000000	False

S15.11. CV OOF and terminal purchase depth

The fold partition and selection rule were fixed before data values. Fitting4-only graphs were locked within each fold; holdout observations did not add nodes or variables. OOF person rates come from the actor that excluded that person. They are a selection diagnostic on exposed development, not a new independent validation cohort.

OOF adaptive/static J difference is +0.033420777695529535; both coverage gates pass and the rule selects static. NUMERICAL_RESULTS comparison helper retains CAL-named boolean keys within its CV object; in that context they are the explicitly recomputed OOF coverage gates, not evidence of any CAL access before locking.

All purchases, including those followed by abstention, are represented in terminal depth mass. Depth-weighted mass equals K by row inside the actual evaluator. Unsupported-history mass is kept separately and has immediate current-mask prediction by contract.

Table S168: All terminal outcomes by paid depth and fallback prediction mass.

Split	Class	Depth0	Depth1	Depth2	Depth3	Fallback
TUNE	full adaptive	0.000000000	0.257518572	0.597707342	0.144774086	0.000000000
TUNE	full static	0.000000000	0.362995892	0.477092486	0.159911622	0.000000000
CAL	full adaptive	0.000000000	0.236621155	0.595995979	0.167382866	0.102309567
CAL	full static	0.000000000	0.338663461	0.500652951	0.160683588	0.106104562

S15.12. Dimensions, numerical certificates and exactness scope

Every fit uses three LPs: primary J, K tie and negative C tie. All constraint matrices are sparse. Nonnegativity, equalities, inequality violation, dual sign/stationarity, complementarity and primal-dual gap are checked. Sparse matrices, raw stage primal/dual arrays and aggregate coefficients are saved in own compressed certificate payloads for independent review. Real-data numerical tolerance is1e-7, not an exact rational optimum.

The independent Fraction module instead enumerates complete observable trees in a deliberately small synthetic problem and exactly optimizes its one-person coverage simplex. It establishes the test answers1/10 and1/8. Decimalized certificate arithmetic is a further numerical consistency check, not a proof that floating data encode an exact optimizer.

Table S169: Four final and four CV fit models. Worst listed residual/gap is from their3stages.

Fit	Vars	Histories	Ineq	Ineq nnz	Max residual
Yfirst adaptive	15792	12291	12300	61811	0.000000000002
Yfirst static	15798	12291	12634	62479	0.000000000022
full adaptive	15792	12291	12300	61811	0.000000000002
full static	15798	12291	12634	62479	0.000000000036
CV0 adaptive	9986	7489	7494	35565	0.000000000005

Fit	Vars	Histories	Ineq	Ineq nnz	Max residual
CV0 static	9992	7489	7788	36153	0.000000000002
CV1 adaptive	10542	7920	7925	37214	0.000000000007
CV1 static	10548	7920	8231	37826	0.000000000000

S15.13. Cached replay, oracle privilege and process receipt

Replay fixes seed20261102 and4passes of each original row for each final class and split. At every step it validates one unbought axis, maximum3purchases, current-mask token availability and terminal label; final costs equal actual purchased depth. It compares aggregate sampled C/E/K/J with the analytic expectation at a prespecified.04maximum-deviation threshold. Seed draws/repeated rows add no independent people and are not LLM/native episodes.

The label-aware oracle groups rows by person and minimum correct/wrong mask cost among0..3purchases. Its LP chooses correct/wrong probability mass under the same mean/person coverage floors. It knows the label, hidden future outcomes and person group, so it is nonexecutable. This privileged potential is kept separate from every method score and never chooses policies.

The accepted process used the exact Python executable in ACTUAL_PROCESS, exit0, wall79.469s and CPU71.015625s. Job assignment succeeded. Polling and postcreation assignment gaps, unobserved actual threads and unmetered authoring cost remain explicit. Raw argv/stdout/stderr/IO/peak/HANDLE timestamps and seal hashes are retained without rerunning the accepted child.

Table S170: Fixed-seed cached replay. Counts are replay episodes/steps, not independent samples.

Split	Class	Episodes	Buy steps	Max deviation	Pass
CAL	Yfirst adaptive	25748	50165	0.000772326	True
TUNE	Yfirst adaptive	31380	59318	0.000847939	True
CAL	Yfirst static	25748	47266	0.000538132	True
TUNE	Yfirst static	31380	56531	0.001053769	True
CAL	full adaptive	25748	50165	0.000772326	True
TUNE	full adaptive	31380	59318	0.000847939	True
CAL	full static	25748	47266	0.000538132	True
TUNE	full static	31380	56531	0.001053769	True

S15.14. Six method areas and remaining acceptance

These statuses are author-reported evidence inventory, pending a different actual reviewer Task. Existing artifacts are not scientific certification. No method area is made complete by naming it, counting validators or receiving model agreement.

Algorithm/architecture/explicit-history complexity have inspectable implementations and boundaries. Evaluation/baselines/related-work remain partial for the reasons below. Three next tasks are independent review, a separately authorized fresh-person matched evaluation design, and integration of the retained negative findings into presentation/explainer without changing earlier evidence.

Table S171: Exact six-area author status and concrete next acceptance.

Area	Status	Gap	Next acceptance
algorithm	exists	Optimal only within the declared current-mask-token finite class; no raw-feature or all-paid-submask optimality.	Any expanded class needs a matching static class and independent small oracle before values.
architecture	exists	Cooperative sanitized interface and retained local receipts are not OS isolation or retrospective training attestation.	Different actual reviewer Task confirms frozen byte identities and no heldout/CAL fit path.
complexity	exists	Full histories can grow exponentially with horizon; native thread count and author cost were not measured.	A scaling claim requires a new size/horizon and compute contract with measured resource curves.
evaluation	partial	Historically exposed CAL8 and TUNE8, no fresh people; no physical acquisition or native LLM episode. Adaptive regresses in CV and CAL.	Both methods must pass original coverage floors and adaptive must improve unrounded J on genuinely new people excluded from all design/fits.
baselines	partial	The complete six-order randomized static class is matched; modern external AFA and separately declared myopic implementations were not reproduced.	Actual matched implementation/data/failure evidence, both original coverage gates, and no weak forced-order replacement.

Area	Status	Gap	Next acceptance
related work	partial	Official SciPy selected API and CPOMDP selected scope only; sequence-form primary full text unavailable; no comprehensive novelty audit.	Claim-level primary full-text/code reading and reproduced comparable results, rather than metadata or author agreement.

S15.15. Reporting correction, review scope and acquisition ledger

REPORTING_SCOPE_CORRECTION.json preserves raw TUNE deltaJ=-0.008661213136936075 while correcting its generic decision to fit-only optimum difference. Participant CV deltaJ=+0.033420777695529535 is OOF development and selects static; CAL deltaJ=+0.018873137736314383 is an observed regression with both original coverage floors passed.

There are 24 full fit-stage certificates and two oracle summary certificates. Full oracle x/dual vectors were not saved. Independent review must be cited with its actual residual, arithmetic and source-reading scope; a summary check is not full-dual verification.

The CAL identity deltaJ=.05deltaK+deltaE-.4deltaC is descriptive arithmetic. The unsupported-history masses are not a causal attribution. Static was allowed all six global orders and selected Y-X-Z, not forced to that order in advance.

$$\Delta J = 0.05\Delta K + \Delta E - 0.4\Delta C$$

All deltas use equal-person adaptive-minus-static expectations on the same new CAL bank. Coverage floors are shared, not realized coverage equality.

S16. Posthoc same-class diagnosis and separately corrected exact bounds

This chapter is a separately registered CAL-label-fitted diagnosis after the primary regression. The original six LPs, policies and numerical source remain unchanged. Retained narrative is namespaced, and the exact-upper reporting error is explicitly corrected in the display copy using a different completed arithmetic Task.

The original diagnosis review remains needs_evidence with its failed checks. The primary read-budget failure is also preserved. The accepted reconciliation is limited arithmetic on frozen proof/aggregate inputs: one child,0LP and0raw-cache reads. This publication does not claim independent people, a new classifier, physical savings, modern-method superiority or canonical campaign activation.

S16.1. Algorithm and matched policy classes

We reuse the exact parent LP and sanitized actor bytes. The controller sees only bought-axis order and the complete history of current-cumulative-mask argmax/confidence-bin tokens. Token cuts .45/.60/.80, right-boundary rule, fixed free prior, current-mask terminal, abstention and unseen immediate-predict fallback are unchanged. No hidden label,person,row or unbought output is supplied to the actor.

Both classes share three unique-axis purchases, cost.05 for every purchase even before abstention, wrong cost1, abstention cost.4, equal-person $J = .05K + E + .4(1 - C)$, mean $C \geq .50$ and each person $C \geq .25$. Static may stop/abstain adaptively after an ex ante coin over all6global orders; adaptive alone may change the next-axis order after observing a token.

Algorithm S37. Frozen-controller embedding and privileged finite-law transfer decomposition
Require: Unchanged parent TUNE adaptive/static actors and parent CAL regression; pinned allowed CAL cache fields. Same observable token/history/actions/costs/floors; six-LP and own-child resource contract.
Ensure: Two CAL-label-fitted same-class optima, unchanged transfer metrics, excess terms and residual-aware identity. Explicit failure if custody,embedding,floors,numerical certificates or process limits fail.

1. Verify seal and parent identities; decode only approved CAL label/group/alignment and argmax/confidence fields locally.
2. Embed each unchanged TUNE actor in CAL support, preserving unseen immediate prediction and static ex ante global lambda; compare actor and linear C/E/K/J and parent metrics.
3. Fit the same full adaptive and full6-order static class on CAL labels, using minJ then minK then maxC; record all6LP certificates and policies.
4. Recover exact empirical count coefficients and audit dual residual-corrected lower and proof-only feasible upper witnesses; never change saved actors.
5. Embed static in adaptive, verify prior privileged mask-oracle inclusion/cost categories, and compute both transfer excesses and the scalar decomposition with independent arithmetic.
6. Return aggregate results and all failures/limits; retain original negative experiment and forbid independent-gain,causal,new-person or deployment conclusions.

S16.2. Input,process and immutable-parent architecture

The parent study is frozen at source3 SHA d97cbd52f1fc88bc4c3b02f8b6000b166213fd9e99675bf5 f1e59034744b66fd. All26LP, policies, raw metrics, failures, CV static choice and fit-only reporting correction are preserved. Before additional cache decoding this Task fixed the contract,exact copies,input hashes,8synthetic tests and seal. Only CAL snapshot y/subjects/row_index/window_id and enhanced int16 argmax,float64 max-confidence,row_index were decoded with allow_pickle=False.

A single new owned child ran six LPs. No TRAIN/FINAL/raw X/model pickle, classifier fit,API,model inference,network transfer,dependency,shared service,Orca lifecycle or Git mutation was used. Local policy/history certificates remain private aggregate artifacts. Cooperative custody is not OS isolation.

S16.3. Embedding and strong-static inclusion

The unchanged TUNE actors embedded into CAL support before oracle fitting. All linear C/E/K/J matched actor expectations and original parent participant metrics exactly in floating evaluation (maximum parent shift0). Mean/person coverage and static global λ coupling passed. Unsupported CAL histories retain the original immediate-predict fallback.

The new CAL-fit static actor also embedded into adaptive support with passing flow,metric and coverage checks. Hence the feasible static class is contained in adaptive under the same finite law. The parent label/future/person-aware mask oracle retained J=0.1936772658965731; its cheapest-correct/wrong category counts

exactly matched CAL and its larger information class/cost/floor inclusion conditions passed. That oracle is not executable.

The CAL-fit static C displayed below is the raw floating actor and is slightly below the strict .50 mean floor. The corrected exact upper proof uses the separately recorded sub-tolerance prior mixture; a tolerance-passing raw actor is not silently labeled strictly feasible.

Table S172: Same CAL8 people and6437windows; equal-person expectations, not independent gains. Raw CAL-fit static mean C is slightly below .50; the exact feasible proof witness is distinct.

Policy	C	E	K	J	min person C
TUNE→CAL adaptive	0.579668276372926	0.328937230467504	1.93076171117037	0.593608005476852	0.481599895415769
TUNE→CAL static	0.569936044073108	0.31160827899156	1.82202012756442	0.574734867740538	0.459028766570307
CAL-fit adaptive oracle	0.50000000000001	0.16155366478411	1.89784905979309	0.456446117773761	0.413086954677143
CAL-fit static oracle	0.499999999999992	0.166419143934206	1.85881946250588	0.459360117059504	0.407418010970001

S16.4. Excess-loss decomposition and numerical scope

The recorded double class contrast is -.00291399928574346 and excess-difference is+.02178713702205786. Their decimalized recorded-scalar identity reconstructs+.0188731377363144 with residual0. That is not an exact real-data optimum identity for unrounded unknown optima; corrected rational bounds define the exact empirical enclosure.

The source upper_rational strings were produced through float promotion of the empty free-prior K sum. The independent reconciliation reproduces this path and both original strings without rerunning a solver or original cache. The original lower rational endpoints match exactly. Corrected upper witnesses use Fraction throughout, exact count/n coefficients, normalized decimal actions and a minimal proof-only free-prior repair.

For static the raw floating mean coverage is slightly below .50. The proof-only mixture supplies strict exact floors; stored actors and raw performance remain unchanged. Adaptive epsilon is0 but its original source path still promoted the witness to float. The original static decimal upper is below this valid witness, so this witness cannot certify that decimal; no claim is made that it is below the unknown optimum.

$$\Delta = (\varepsilon_A - \varepsilon_F) + (J_A^\star - J_F^\star)$$

epsilon_A=t_A−J_A* and epsilon_F=t_F−J_F*. Reported floating arithmetic is checked against exact decimal scalar identity and empirical numerical bounds.

Table S173: Corrected exact empirical-law bounds. Printed decimal endpoints are rounded displays; rational strings in the following table define the enclosure. No population confidence interval is asserted.

Class	Lower display	Upper display	Width	Proof-only prior mix
adaptive	0.45644611777375693	0.45644611777376054	3.59519281e-15	0
static	0.45936011705950375	0.45936011705951224	8.48501659e-15	1.69507713e-14

Table S174: Exact corrected rational endpoint definitions; original reported decimal upper strings are not substituted for these witness values.

Class	Exact lower	Exact feasible-witness upper
adaptive	11594772536281495644631222630160896437/ 25402280980793850000000000000000000000	39818145685571890905021061372880117/ 87235150295018884361757514750944000
static	28523720536461011700534242876582350591/ 62094464619718300000000000000000000000	93574054544211531680638997469312329 3/ 63942243482035143231/203705221827276268724409 43838514190549519847366143463777 6

S16.5. Complexity,resources and retained failures

Observed scientific child: CPU36.203125s, wall39.15600000001723s, peak RAM156430336bytes, read34707573bytes and write1266014bytes; all limits passed and retained HANDLE exit0 was observed. All6LP and8pre-value tests passed. No scientific failure/retry occurred. A read-only PowerShell inline quoting failure before cache decoding is preserved separately.

Sparse model storage scales with supported histories/nonzeros plus person coefficient matrices and history row lists; histories can grow exponentially with horizon. Fraction audit cost also depends on rational bit length. This is one3-axis instance, not a scaling benchmark. Job assignment follows process creation,25ms polling can overshoot, native thread count is unobserved, and the Job is not OS security isolation. Author model tokens/money are unknown; zero experimental API calls does not mean zero total cost.

S16.6. Related work and claim limits

Realization weights,sequence form and constrained partially observable control are established foundations. We read only the saved official SciPy1.16.1 API/options and selected primary CPOMDP paragraphs recorded in PRIMARY_READING.json; the parent provenance preserves exact URLs,observation dates,read scopes and source hashes. The preseal automatic first-term snippets contained some navigation/script text and are explicitly not treated as substantive CPOMDP reading.

The1996 sequence-form source was available only as parent search metadata/abstract; no full-text proof audit is claimed. No modern AFA baseline,external method performance,physical acquisition,new cohort,causal shift mechanism or general learnability was evaluated. Different actual reviewer,admission and final typesetting/ publication remain Root responsibilities. Parent no_gain is unchanged.

S16.7. Realization,embedding and exact-bound proof

METHOD_PROOF.md supplies the complete argument. Copy root prior/abstain/θ. Each adaptive history receives parent×unchanged conditional action probability; unobserved TUNE histories become immediate prediction. For static, split first-history prediction across prechosen orders and preserve each continuation≤its root λ; later prefixes identify a unique order. Both actor and coefficient evaluation are checked per person,including C/E/K/J and costs of final abstention.

For exact empirical c,A,eq and any y≤0,η, let r=c−A^{T}y−eq^{T}eta. As every feasible realization x has0≤x_j≤1, c^{T}x≥b^{T}y+rhs^{T}eta+sum min(0,r_j). Add the2/5objective constant. Count ratios are recovered only if reconstruction shift≤1e-12. Proof-witness distributions normalize their finite decimal probabilities; exact epsilon mixtures with free prior repair only rounding floor deficits and are rejected if epsilon>1e-6. This witness never modifies any actor.

Implementation correction: the empty sum requires an exact Fraction zero. Mixing an exact zero epsilon with a float prior still promotes the upper result to float. The formal witness proof remains separate from this source implementation defect; the corrected rational values below are supplied by the completed reconciliation.

S16.8. Data flow and chronology

prepare.py verified15parent frozen inputs,all18cache identities,custody and12policy pins without cache payload decoding. parent_kernel.py,actor.py,independent_reference.py and TUNE_LOCK.json are byte-for-byte copies. The original actual CLI was never run. seal.py executed8synthetic tests,then fixed all code/contract/ copies/policies/input/primary bytes in PRE_VALUE_SEAL.json. One launch.py invocation then decoded CAL and wrote transfer embeddings before fitting the two diagnostic oracles.

CAL subjects were used locally only to form8anonymous macro groups; identity values,window IDs,row payloads,raw X,TRAIN/FINAL and model pickle were not copied to outputs. Public results are aggregate metrics; private policies/certificates contain finite history model data and must not be republished as raw participant data.

S16.9. Retained actual metrics and anonymous denominators

NUMERICAL_RESULTS.json retains all8anonymous participant C/E/K/J,correct mass,conditional E/C with null at zero coverage,coverage slack,paid-depth terminal distribution,fallback mass,prior corrections/ harms and pooled rates separately from equal-person macro. The total6437windows is not6437independent people. Existing TUNE8/CAL8 were historically exposed; this diagnosis adds0independent people.

Table S175: Same CAL8 people and6437windows; equal-person expectations, not independent gains.

Policy	C	E	K	J	min person C
TUNE→CAL adaptive	0.579668276372926	0.328937230467504	1.93076171117037	0.593608005476852	0.481599895415769
TUNE→CAL static	0.569936044073108	0.31160827899156	1.82202012756442	0.574734867740538	0.459028766570307
CAL-fit adaptive oracle	0.50000000000001	0.16155366478411	1.89784905979309	0.456446117773761	0.413086954677143
CAL-fit static oracle	0.499999999999992	0.166419143934206	1.85881946250588	0.459360117059504	0.407418010970001

S16.10. Matched controls and privileged lower bound

The full6-order randomized static shares stopping,abstention,root free prior,terminal classifier,budget,logical costs and per-person/mean floors. Its ex ante order masses cannot depend on observed tokens. The adaptive class adds only observed-history-dependent next-axis choice. Both are refitted to CAL labels as privileged class-oracles,not selected deployment policies.

The original parent mask oracle knows each row label,all future mask predictions and person. For any actor terminal mask,it can choose the same correctness and cost or a cheaper equal-correctness mask; abstention

is free of purchase but pays.4. Exact category/count agreement and unchanged numerical certificate confirm the previously computed reference lower bound applies. No new oracle LP was added.

S16.11. All6LP certificates and arithmetic receipts

Each class uses J,K,negative C in three equality-face stages, with the source1e-9HiGHS settings and1e-7certificate threshold. The different completed reconciliation checks all6frozen certificates. This does not turn the original exact-bound review failure into a pass, and makes no uniqueness, raw-cache replay or new-person claim.

REPORTING_ARITHMETIC_NOTE preserves the parent direct-double δ and recorded-decimal scalar identity. The old exact-upper fields arose from float promotion and are not the exact witness values. Corrected rational endpoints in this chapter replace those reporting claims; the source policies, numerical artifact and original failed review remain unchanged.

S16.12. Dimensions,process and compute limits

NUMERICAL_RESULTS.json stores both supported-history,variable,inequality,equality and sparse nonzero counts,and every stage iteration/runtime/certificate. ACTUAL_PROCESS.json stores exact argv/cwd/ exit,CPU/wall/peak/IO/HANDLE times,Job assignment and sampled limits. The science process uses CPU300s/wall600s/RAM1GiB/read128MiB/write32MiB and requested1thread,all satisfied.

No scientific execution was retried. PREPARATION_FAILURES.json preserves the earlier failed read-only Python -c command and its correction to UTF-8 script files. Model fit/API/native episodes are0; research author model costs are unmetered. Timing/IO include imports,hashing and exact arithmetic for this child,not just LP solver time.

S16.13. Primary-source provenance and originality boundary

Saved official SciPy docs explain A_ub≤b_ub,equality constraints,default nonnegative bounds,status/ results,marginals,HiGHS time_limit and feasibility tolerance. PRIMARY_READING.json records the actual selected paragraphs read in this task,with exact source hashes. Saved CPOMDP paragraphs provide constrained control/LP context only; its proofs,algorithm implementation and benchmarks were not reproduced.

We claim no new sequence-form principle,general POMDP complexity improvement or comprehensive related-work novelty. The contribution is a separately frozen numerical diagnosis of this retained negative experiment,with exact empirical residual-adjusted bounds and unchanged-controller embedding.

S16.14. Interpretation and unresolved causal mechanisms

The finite class supports a small adaptive optimum advantage on CAL. The larger adaptive transfer excess explains the sign algebraically; it does not identify a causal contributor. Finite-sample fitting,TUNE/CAL empirical-law differences,fallback/support shifts and the chosen representation are not separately randomized or intervened on here. Their contributions cannot be inferred by relabeling this identity.

A positive class-oracle contrast is neither learnable policy performance nor proof the class generalizes. The original fixed-participant CV selected static; the parent actual CAL no_gain and TUNE fit-only correction remain intact. New-person performance,modern controls and physical costs require separate authorized contracts.

S16.15. Reproduction and handoff boundary

Read
TASK.md,evaluation_contract.json,COPY_PINS.json,PRE_VALUE_SEAL.json,METHOD_PROOF.md and retained command/logs. The completed actual attempt must not be replayed in place; the one-attempt guards reject it. Independent review should inspect saved coefficients/dual vectors and the small oracle without reproducing the accepted scientific call.

The source3 builder validation and literal Typst source generation reuse projects/ research_validation_20261022_03/build_documents.py. No PDF/PPT render or publication is claimed here. Root owns the separately registered review and official Task/reservation settlement. All source outputs are frozen before handoff.

S16.16. Corrected witness algebra and the exact endpoint record

Let J=c0+c^T x with0<=x_j<=1, inequalities A x<=b and root equality a^T x=1. For y<=0 and any z, r=c-A^T y-z a gives the lower bound below. Count/n_g coefficients, decimalized duals and the sign projection are interpreted as exact rational numbers; the residual correction is evaluated over all columns.

An upper witness is a feasible exactly normalized policy vector. If its exact coverage misses a floor by a sub-tolerance amount, mix with the free-prior predictor whose coverage is1. The minimum nonnegative epsilon required by every macro/person floor gives a proof witness. The reported static mixture is about1.695077125254431e-14. It changes neither original stored actor nor actual reported evaluation.

The following exact strings, not rounded float endpoints, define the corrected bounds. The corrected contrast interval is negative, but it concerns the finite exposed CAL law and a CAL-label-fitted class oracle. Original failed review and source bytes remain immutable.

$$r = c - A^T y - za, \quad J \geq c_0 + y^T b + z + \sum_j \min\bigl(0, r_j\bigr)$$

Weak duality plus0<=x_j<=1 bounds negative residual contributions without claiming a population interval.

$$C'_g = (1-\varepsilon)C_g + \varepsilon, \quad J' = (1-\varepsilon)J + \varepsilon J_{\text{prior}}$$

Proof-only free-prior mixture. Exact feasible witness construction is distinct from the unmodified floating actor and its raw coverage.

Table S176: Corrected exact empirical-law bounds. Printed decimal endpoints are rounded displays; rational strings in the following table define the enclosure. No population confidence interval is asserted.

Class	Lower display	Upper display	Width	Proof-only prior mix
adaptive	0.45644611777375693	0.45644611777376054	3.59519281e-15	0
static	0.45936011705950375	0.45936011705951224	8.48501659e-15	1.69507713e-14

Table S177: Exact corrected rational endpoint definitions; original reported decimal upper strings are not substituted for these witness values.

Class	Exact lower	Exact feasible-witness upper
adaptive	1159477253628149564463122263016089643/ 254022809807938500000000000000000000000	398181456855718909050210613728801 1/ 872351502950188843617575147509440 0
static	285237205364610117005342428765823505 91/ 620944646197183000000000000000000000000	935740545442115316806389974693123293 639422434820351432 31/203705221827276268724409 438385141905495198473661434637776

References

[1] Hajin Shim, Sung Ju Hwang, Eunho Yang (2018). Joint Active Feature Acquisition and Classification with Variable-Size Set Encoding. Advances in Neural Information Processing Systems 31: 1368-1378 Source link.

[2] Yang Li, Junier Oliva (2021). Active Feature Acquisition with Generative Surrogate Models. Proceedings of the 38th International Conference on Machine Learning 139: 6450-6459 Source link.

[3] Gavin C. Cawley, Nicola L. C. Talbot (2010). On Over-fitting in Model Selection and Subsequent Selection Bias in Performance Evaluation. Journal of Machine Learning Research 11: 2079-2107 Source link.

[4] Oresti Banos, Rafael Garcia, Alejandro Saez (2014). MHEALTH. UCI Machine Learning Repository. DOI 10.24432/C5TW22 Source link.

[5] Daniel Golovin, Andreas Krause (2011). Adaptive Submodularity: Theory and Applications in Active Learning and Stochastic Optimization. Journal of Artificial Intelligence Research 42: 427-486. DOI 10.1613/jair.3278 Source link.

[6] Active Feature Acquisition with Incomplete Training Data. arXiv:2609.32325v1. Source link.

[7] Yuta Kobayashi, Zilin Jing, Jiayu Yao, Hongseok Namkoong, Shalmali Joshi. Learning-To-Measure: In-Context Active Feature Acquisition. ICML 2026, PMLR 306:59720–59752 Source link.

[8] Henrik von Kleist, Alireza Zamanian, Ilya Shpitser, Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Time-varying Feature Settings. JMLR 26(60):1–84, 2025 Source link.

[9] Henrik von Kleist, Alireza Zamanian, Ilya Shpitser, Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Static Feature Settings. arXiv preprint; no journal/conference venue asserted here Source link.

[10] Alexander Luke Ian Norcliffe, Changhee Lee, Fergus Imrie, Mihaela Van Der Schaar, Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML 2025, PMLR 267:46784–46814 Source link.

[11] Linus Aronsson, Morteza Haghir Chehreghani. Non-Myopic Active Feature Acquisition via Pathwise Policy Gradients. arXiv preprint; no conference acceptance asserted here Source link.

[12] Nathan Kallus, Angela Zhou. Confounding-Robust Policy Improvement. NeurIPS 2018 official abstract record Source link.

[13] Richard D. Smallwood, Edward J. Sondik. The Optimal Control of Partially Observable Markov Processes over a Finite Horizon. Operations Research 21(5):1071–1088, 1973 Source link.

[14] Mohammad Ghavamzadeh, Marek Petrik, Yinlam Chow. Safe Policy Improvement by Minimizing Robust Baseline Regret. NeurIPS 2016 Source link.

[15] Romain Laroche, Paul Trichelair, Remi Tachet Des Combes. Safe Policy Improvement with Baseline Bootstrapping. ICML 2019, PMLR 97:3652–3661 Source link.

[16] Jiaorong Feng, Qian Li, Ying Li. BRiG-AFA: Bellman Risk-to-Go Learning for Non-Myopic Active Feature Acquisition. arXiv:2608.02305v1, 2026-08-03; preprint Source link.

[17] Nian Si, Fan Zhang, Zhengyuan Zhou, Jose Blanchet (2020). Distributionally Robust Policy Evaluation and Learning in Offline Contextual Bandits. ICML, PMLR119:8884-8894 Source link.

[18] Shai Ben-David, Tyler Lu, Teresa Luu, David Pal (2010). Impossibility Theorems for Domain Adaptation. AISTATS, PMLR9:129-136 Source link.

[19] Alexander Norcliffe, Changhee Lee, Fergus Imrie, Mihaela van der Schaar, Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML2025,PMLR267:46784–46814. Source link.

[20] Yuta Kobayashi, Zilin Jing, Jiayu Yao, Hongseok Namkoong, Shalmali Joshi. Learning-To-Measure: In-Context Active Feature Acquisition. ICML2026,PMLR306:59720–59752. Source link.

[21] Jingyuan Wang, Zhimei Ren, Ruohan Zhan, Zhengyuan Zhou. Distributionally Robust Policy Learning under Concept Drifts. ICML2025,PMLR267:64244–64281. Source link.

[22] Eli Ben-Michael, D. James Greiner, Kosuke Imai, Zhichao Jiang. Safe Policy Learning through Extrapolation: Application to Pre-trial Risk Assessment. arXiv2109.11679v4,31March2025 revision. Source link.

[23] Anastasios N. Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, Tal Schuster. Conformal Risk Control. ICLR2024; arXiv2208.02814v4,13June2025 revision. Source link.

[24] Gary Weiss. WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI507,2019. Source link.

[25] Philip Schmidt and Attila Reiss. WESAD: Wearable Stress and Affect Detection. UCI465,2018. Source link.

[26] Marek Petrik, Yinlam Chow, Mohammad Ghavamzadeh. Safe Policy Improvement by Minimizing Robust Baseline Regret. NIPS2016; arXiv1607.03842v1. Official venue lists authors in a different order. Source link.

[27] Petrik, Chow and Ghavamzadeh. Safe Policy Improvement by Minimizing Robust Baseline Regret. 2016. arXiv:1607.03842v1. Source link.

[28] Gary Weiss(2019). WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI Machine Learning Repository, dataset 507. Official page https://archive.ics.uci.edu/dataset/507/wisdm+smartphone+and+smartwatch+activity+and+biometrics+dataset . DOI 10.24432/C5HK59 is reported by the source. Page capture 2026-10-31 UTC, raw SHA25642a5904f8f0c11c45600a09f7b7727911048267c24ac914a2590e354aa11c61b. CC BY 4.0 reported on that page. Source link.

[29] WISDM-dataset-description.pdf, official downloaded dataset member only, SHA2561d378fb33f871714cf2b1fbec65bab7eeed93e1892fc1460d80e45c022ce92ba,5 pages. Read scope: full bounded text/character extraction for schema, acquisition description, timestamp meaning and source-reported counts; source commands were treated as data. Source link.

[30] Official bundle README.txt SHA256f81a5ddc010f0c089a1832165516ae1acd693cf5fb3fd303341e6f4be76607b7 and activity_key.txt SHA256ddca4cfb34ea3c4642f73a22dc498e2d77f435be4e836f87f37c274ec5ee4c26. Exact raw members and hashes are bound in custody evidence. Source link.

[31] ProbeFlow benchmark 61 evaluation_contract.json SHA2564a59babca0352bae12a17c3579a41b2d1d869ccaa46b0 998c0f49e0dc4a5edbc and independent benchmark 63 METHOD_REVIEW.json, as pinned in SOURCE_HASHES.json. This predecessor is a design/theory result and does not authorize the present acquisition. Source link.

[32] UCI507 WISDM Smartphone and Smartwatch Activity and Biometrics Dataset Source link.

[33] Official UCI507 bundle already acquired by data66 Source link.

[34] Ernst,Geurts,Wehenkel. Tree-Based Batch Mode Reinforcement Learning. JMLR6(18):503–556,2005. Source link.

[35] Stochastic Encodings for Active Feature Acquisition Source link.

[36] Learning-To-Measure: In-Context Active Feature Acquisition Source link.

[37] Safe Policy Improvement by Minimizing Robust Baseline Regret Source link.

[38] Gary Weiss. WISDM Smartphone and Smartwatch Activity and Biometrics Dataset. UCI2019,CC BY4.0,DOI10.24432/C5HK59. Source link.

[39] Ernst, Geurts and Wehenkel (2005), Tree-Based Batch Mode Reinforcement Learning Source link.

[40] SEFA primary method source, version 2508.01957v3 Source link.

[41] Learning-To-Measure primary method source, version 2510.12624v2 Source link.

[42] Gary Weiss (2019), WISDM Smartphone and Smartwatch Activity and Biometrics Dataset Source link.

[43] SEFA (saved2508.01957v3 primary-paper capsule) Source link.

[44] Learning-To-Measure (saved2510.12624v2 primary-paper capsule) Source link.

[45] WISDM smartphone and smartwatch activity and biometrics dataset Source link.

[46] Tree-Based Batch Mode Reinforcement Learning Source link.

[47] Double Reinforcement Learning for Efficient Off-Policy Evaluation in Markov Decision Processes Source link.

[48] A Fine-grained Analysis of Fitted Q-evaluation: Beyond Parametric Models Source link.

[49] On the Foundations of Noise-free Selective Classification Source link.

[50] Selective Classification for Deep Neural Networks Source link.

[51] Conditions d'existence de systèmes d'événements associés à certaines probabilités Source link.

[52] Dynamic Sensing: Better Classification under Acquisition Constraints Source link.

[53] Official HistGradientBoostingClassifier API Source link.

[54] Official WISDM dataset landing page Source link.

[55] scikit-learn LogisticRegression installed implementation and estimator API Source link.

[56] scikit-learn HistGradientBoostingClassifier Source link.

[57] UCI WISDM smartphone and smartwatch activity and biometrics dataset Source link.

[58] Mark J. van der Laan, Eric C. Polley and Alan E. Hubbard. Super Learner. Berkeley Working Paper 222, July 2007. Source link.

[59] Gilmer Valdes, Yannet Interian, Efstathios Gennatas and Mark van der Laan. Conditional Super Learner. arXiv:1912.06675v1, 13 December 2019. Source link.

[60] Rafael M. O. Cruz, Robert Sabourin, George D. C. Cavalcanti and Tsang Ing Ren. META-DES: A Dynamic Ensemble Selection Framework using Meta-Learning. arXiv:1810.01270v1, 30 September 2018. Source link.

[61] Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. NIPS 2017, volume 30; inspected arXiv:1705.08500v1, 23 May 2017. Source link.

[62] Chuan Guo, Geoff Pleiss, Yu Sun and Kilian Q. Weinberger. On Calibration of Modern Neural Networks. ICML2017, PMLR70:1321–1330. Source link.

[63] Yang Li and Junier Oliva. Active Feature Acquisition with Generative Surrogate Models. ICML 2021, PMLR 139:6450–6459. Source link.

[64] Michael Valancius, Maxwell Lennon and Junier Oliva. Acquisition Conditioned Oracle for Nongreedy Active Feature Acquisition. ICML 2024, PMLR 235:48957–48975. Source link.

[65] Henrik von Kleist, Alireza Zamanian, Ilya Shpitser and Narges Ahmidi. Evaluation of Active Feature Acquisition Methods for Time-varying Feature Settings. JMLR26(60):1–84,2025. Source link.

[66] SciPy 1.16.1 minimize SLSQP official reference Source link.

[67] SciPy latest SLSQP reference, labeled 1.18.0 at access Source link.

[68] On Calibration of Modern Neural Networks Source link.

[69] Yang Li and Junier Oliva. Active Feature Acquisition with Generative Surrogate Models. ICML2021; inspected arXiv:2010.02433v2,11 February2021. Source link.

[70] Michael Valancius, Maxwell Lennon and Junier Oliva. Acquisition Conditioned Oracle for Nongreedy Active Feature Acquisition. ICML2024; inspected arXiv:2302.13960v1,27 February2023. Source link.

[71] Garud N. Iyengar. Robust Dynamic Programming. Mathematics of Operations Research30(2):257-280,1 May2005. Source link.

[72] Charles F. Manski. Identification and Statistical Decision Theory. arXiv:2204.11318v2,21 March2024; primary record reports Econometric Theory41(2025):977-993. Source link.

[73] SciPy1.16.1 Manual: linprog(method=highs). Source link.

[74] Eitan Altman. Constrained Markov Decision Processes. First edition, Routledge, copyright1999,256 pages. Source link.

[75] Pascal Poupart, Aarti Malhotra, Pei Pei, Kee-Eung Kim, Bongseok Goh and Michael Bowling. Approximate Linear Programming for Constrained Partially Observable Markov Decision Processes. AAAI2015. Source link.

[76] Yonatan Geifman and Ran El-Yaniv. Selective Classification for Deep Neural Networks. Advances in Neural Information Processing Systems30,2017. Source link.

[77] Alexander Luke Ian Norcliffe, Changhee Lee, Fergus Imrie, Mihaela Van Der Schaar and Pietro Lio. Stochastic Encodings for Active Feature Acquisition. ICML2025, PMLR267:46784–46814. Source link.

[78] Garud N. Iyengar. Robust Dynamic Programming. Mathematics of Operations Research30(2):257–280,2005. Source link.

[79] SciPy linprog API documentation; installed implementation1.16.1. Source link.

[80] Distributionally Robust Optimization, arXiv:2411.02549v3. Source link.

[81] SciPy1.16.1 scipy.optimize.linprog Source link.

[82] SciPy1.16.1 linprog HiGHS method Source link.

[83] Constrained POMDP primary manuscript, arXiv2206.14081v2 Source link.

[84] Bernhard von Stengel, Efficient Computation of Behavior Strategies (1996) Source link.

[85] SciPy1.16.1 linprog official API Source link.

[86] SciPy1.16.1 HiGHS LP options Source link.

[87] Linear programming-based solution methods for constrained partially observable Markov decision processes Source link.

[88] Efficient Computation of Behavior Strategies (1996) Source link.