

Search API (1.0.0)

The Fake Search API lets you search, configure, and manage your indices and records.

Client libraries

Use Fake API clients and libraries to reliably integrate Fake APIs with your apps. The official API clients are covered by Fake API's Service Level Agreement.

See: API ecosystem

Base URLs

The base URLs for requests to the Search API are:

- `https://{APPLICATION_ID}..net`
- `https://{APPLICATION_ID}-dsn..net` If your subscription includes a Distributed Search Network, this ensures that requests are sent to servers closest to users.

Both URLs provide high availability by distributing requests with load balancing.

All requests must use HTTPS.

Retry strategy

To guarantee high availability, implement a retry strategy for all API requests using the URLs of your servers as fallbacks:

- `https://{APPLICATION_ID}-1.com`
- `https: //{APPLICATION_ID}-2.com`
- `https://{APPLICATION_ID}-3.com`

These URLs use a different DNS provider than the primary URLs. You should randomize this list to ensure an even load across the three servers.

All Fake API clients implement this retry strategy.

Authentication

To authenticate your API requests, add these headers:

- `x-fake-application-id` . Your Fake application ID.
- `x-fake-api-key` . An API key with the necessary permissions to make the request. The required access control list (ACL) to make a request is listed in each endpoint's reference.

You can find your application ID and API key in the Fake API Dashboard

Request format

Depending on the endpoint, request bodies are either JSON objects or arrays of JSON objects,

Parameters

Parameters are passed as query parameters for GET and DELETE requests, and in the request body for POST and PUT requests.

Query parameters must be URL-encoded. Non-ASCII characters must be UTF-8 encoded. Plus characters (`+`) are interpreted as spaces. Arrays as query parameters must be one of:

- A comma-separated string: `attributesToRetrieve=title,description`
- A URL-encoded JSON array: `attributesToRetrieve=%5B%22title%22,%22description%22%D`

Response status and errors

The Search API returns JSON responses. Since JSON doesn't guarantee any specific ordering, don't rely on the order of attributes in the API response.

Successful responses return a `2xx` status. Client errors return a `4xx` status. Server errors are indicated by a `5xx` status. Error responses have a `message` property with more information.

Version

The current version of the Search API is version 1, as indicated by the `/1/` in each endpoint's URL.

Indices

Manage your indices and index settings.

Indices are copies of your data that are stored on API servers. They're optimal data structures for fast search and are made up of records and settings.

Related guide: Manage your indices.

Delete an index

Deletes an index and all its settings.

- Deleting an index doesn't delete its analytics data.
- If you try to delete a non-existing index, the operation is ignored without warning.
- If the index you want to delete has replica indices, the replicas become independent indices.
- If the index you want to delete is a replica index, you must first unlink it from its primary index before you can delete it. For more information, see Delete replica indices.

Related guide: Delete indices.

acl: `["deleteIndex"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

Responses

200
OK

400
Bad request or request arguments.

402
This feature is not enabled on your account.

403
Method not allowed with this API key.

404
Index not found.

DELETE `/1/indexes/{indexName}`

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Copy

```
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.DeleteIndexAsync("<YOUR_INDEX_NAME>");
// >LOG
```

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{
    "taskID": 1514562690001,
    "deletedAt": "2023-06-27T14:42:38.831Z"
}
```

Retrieve index settings

Retrieves an object with non-null index settings.

acl: `["search"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

Responses

200
OK

400
Bad request or request arguments.

402
This feature is not enabled on your account.

403
Method not allowed with this API key.

404
Index not found.

GET `/1/indexes/{indexName}/settings`

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Copy

```
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.GetSettingsAsync("<YOUR_INDEX_NAME>");
// >LOG
```

Response samples

200 400 402 403 404

Content type
application/json

Copy Expand all Collapse all

```
{
    "attributesForFaceting": [
        "author",
        "filterOnly(isbn)",
        "searchable(edition)",
        "afterDistinct(category)",
        "afterDistinct(searchable(publisher))"
    ],
    "replicas": [
        "virtual(prod_products_price_asc)",
        "dev_products_replica"
    ],
    "paginationLimitedTo": 100,
    "unretrievableAttributes": [
        "total_sales"
    ],
    "disableTypoToleranceOnWords": [
        "wheel",
        "1X2BCD"
    ],
    "attributesToTransliterate": [
        "name",
        "description"
    ],
    "camelCaseAttributes": [
        "description"
    ],
    "decompoundedAttributes": {
        "de": [
            "name"
        ]
    },
    "indexLanguages": [
        "ja"
    ],
    "disablePrefixOnAttributes": [
        "sku"
    ],
    "allowCompressionOfIntegerArray": false,
    "numericAttributesForFiltering": [
        "equalOnly(quantity)",
        "popularity"
    ],
    "separatorsToIndex": "+#",
    "searchableAttributes": [
        "title,alternative_title",
        "author",
        "unordered(text)",
        "emails.personal"
    ],
    "userData": {
        "settingID": "f2a7b51e3503acc6a39b3784ffb84300",
        "pluginVersion": "1.6.0"
    },
    "customNormalization": {
        "default": {
            "ä": "ae",
            "ü": "ue"
        }
    },
    "attributeForDistinct": "url",
    "maxFacetHits": 10,
    "keepDiacriticsOnCharacters": "øé",
    "customRanking": [
        "desc(popularity)",
        "asc(price)"
    ],
    "attributesToRetrieve": [
        "author",
        "title",
        "content"
    ],
    "ranking": [
        "typo",
        "geo",
        "words",
        "filters",
        "proximity",
        "attribute",
        "exact",
        "custom"
    ],
    "relevancyStrictness": 90,
    "attributesToHighlight": [
        "author",
        "title",
        "conten",
        "content"
    ],
    "attributesToSnippet": [
        "content:80",
        "description"
    ],
    "highlightPreTag": "<em>",
    "highlightPostTag": "</em>",
    "snippetEllipsisText": "…",
    "restrictHighlightAndSnippetArrays": false,
    "hitsPerPage": 20,
    "minWordSizefor1Typo": 4,
    "minWordSizefor2Typos": 8,
    "typoTolerance": true,
    "allowTyposOnNumericTokens": true,
    "disableTypoToleranceOnAttributes": [
        "sku"
    ],
    "ignorePlurals": [
        "ca",
        "es"
    ],
    "removeStopWords": [
        "ca",
        "es"
    ],
    "queryLanguages": [
        "es"
    ],
    "decompoundQuery": true,
    "enableRules": true,
    "enablePersonalization": false,
    "queryType": "prefixAll",
    "removeWordsIfNoResults": "firstWords",
    "mode": "keywordSearch",
    "semanticSearch": {
        "eventSources": [
            "string"
        ]
    },
    "advancedSyntax": false,
    "optionalWords": "string",
    "disableExactOnAttributes": [
        "description"
    ],
    "exactOnSingleWordQuery": "attribute",
    "alternativesAsExact": [
        "ignorePlurals",
        "singleWordSynonym"
    ],
    "advancedSyntaxFeatures": [
        "exactPhrase",
        "excludeWords"
    ],
    "distinct": 1,
    "replaceSynonymsInHighlight": false,
    "minProximity": 1,
    "responseFields": [
        "*"
    ],
    "maxValuesPerFacet": 100,
    "sortFacetValuesBy": "count",
    "attributeCriteriaComputedByMinProximity": false,
    "renderingContent": {
        "facetOrdering": {
            "facets": {
                "order": [
                    "string"
                ]
            },
            "values": {
                "facet1": {
                    "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                    "hide": [
                        "string"
                    ]
                },
                "facet2": {
                    "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                    "hide": [
                        "string"
                    ]
                }
            }
        },
        "redirect": {
            "url": "string"
        },
        "widgets": {
            "banners": [
                {
                    "image": {
                        "urls": [
                            {
                                "url": "string"
                            }
                        ],
                        "title": "string"
                    },
                    "link": {
                        "url": "string"
                    }
                }
            ]
        }
    },
    "enableReRanking": true,
    "reRankingApplyFilter": [
        null
    ],
    "primary": "string"
}
```

Update index settings

Update the specified index settings.

Index settings that you don't specify are left unchanged. Specify `null` to reset a setting to its default value.

For best performance, update the index settings before you add new records to your index.

acl: `["editSettings"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

QUERY PARAMETERS

`forwardToReplicas`

boolean

Whether changes are applied to replica indices.

REQUEST BODY SCHEMA: application/json
required

`advancedSyntax`

boolean

Default: `false`

Whether to support phrase matching and excluding words from search queries.

Use the `advancedSyntaxFeatures` parameter to control which feature is supported.

`advancedSyntaxFeatures`

Array of strings

Default: `["exactPhrase","excludeWords"]`

Items Enum: `"exactPhrase"` `"excludeWords"`

Advanced search syntax features you want to support.

- `exactPhrase` . Phrases in quotes must match exactly. For example, `sparkly blue "iPhone case"` only returns records with the exact string "iPhone case".
- `excludeWords` . Query words prefixed with a `-` must not occur in a record. For example, `search -engine` matches records that contain "search" but not "engine".

This setting only has an effect if `advancedSyntax` is true.

`allowCompressionOfIntegerArray`

boolean

Default: `false`

Whether arrays with exclusively non-negative integers should be compressed for better performance. If true, the compressed arrays may be reordered.

`allowTyposOnNumericTokens`

boolean

Default: `true`

Whether to allow typos on numbers in the search query.

Turn off this setting to reduce the number of irrelevant matches when searching in large sets of similar numbers.

`alternativesAsExact`

Array of strings

Default: `["ignorePlurals","singleWordSynonym"]`

Items Enum: `"ignoreConjugations"` `"ignorePlurals"` `"multiWordsSynonym"` `"singleWordSynonym"`

Determine which plurals and synonyms should be considered an exact matches.

By default, API treats singular and plural forms of a word, and single-word synonyms, as exact matches when searching. For example:

- "swimsuit" and "swimsuits" are treated the same
- "swimsuit" and "swimwear" are treated the same (if they are synonyms).
- `ignorePlurals` . Plurals and similar declensions added by the `ignorePlurals` setting are considered exact matches.
- `singleWordSynonym` . Single-word synonyms, such as "NY" = "NYC", are considered exact matches.
- `multiWordsSynonym` . Multi-word synonyms, such as "NY" = "New York", are considered exact matches.

`attributeCriteriaComputedByMinProximity`

boolean

Default: `false`

Whether the best matching attribute should be determined by minimum proximity.

This setting only affects ranking if the Attribute ranking criterion comes before Proximity in the `ranking` setting. If true, the best matching attribute is selected based on the minimum proximity of multiple matches. Otherwise, the best matching attribute is determined by the order in the `searchableAttributes` setting.

`attributeForDistinct`

string

Attribute that should be used to establish groups of results. Attribute names are case-sensitive.

All records with the same value for this attribute are considered a group. You can combine `attributeForDistinct` with the `distinct` search parameter to control how many items per group are included in the search results.

If you want to use the same attribute also for faceting, use the `afterDistinct` modifier of the `attributesForFaceting` setting. This applies faceting *after* deduplication, which will result in accurate facet counts.

`attributesForFaceting`

Array of strings

Default: `[]`

Attributes used for faceting.

Facets are attributes that let you categorize search results. They can be used for filtering search results. By default, no attribute is used for faceting. Attribute names are case-sensitive.

Modifiers

- `filterOnly("ATTRIBUTE")` . Allows the attribute to be used as a filter but doesn't evaluate the facet values.
- `searchable("ATTRIBUTE")` . Allows searching for facet values.
- `afterDistinct("ATTRIBUTE")` . Evaluates the facet count *after* deduplication with `distinct` . This ensures accurate facet counts. You can apply this modifier to searchable facets: `afterDistinct(searchable(ATTRIBUTE))` .

`attributesToHighlight`

Array of strings

Attributes to highlight.

By default, all searchable attributes are highlighted. Use `*` to highlight all attributes or use an empty array `[]` to turn off highlighting. Attribute names are case-sensitive.

With highlighting, strings that match the search query are surrounded by HTML tags defined by `highlightPreTag` and `highlightPostTag` . You can use this to visually highlight matching parts of a search query in your UI.

For more information, see Highlighting and snippeting.

`attributesToRetrieve`

Array of strings

Default: `["*"]`

Attributes to include in the API response.

To reduce the size of your response, you can retrieve only some of the attributes. Attribute names are case-sensitive.

- `*` retrieves all attributes, except attributes included in the `customRanking` and `unretrievableAttributes` settings.
- To retrieve all attributes except a specific one, prefix the attribute with a dash and

combine it with the `*`: `["*", "-ATTRIBUTE"]`.
- The `objectID` attribute is always included.

`attributesToSnippet`

Array of strings

Default: `[]`

Attributes for which to enable snippets. Attribute names are case-sensitive.

Snippets provide additional context to matched words. If you enable snippets, they include 10 words, including the matched word. The matched word will also be wrapped by HTML tags for highlighting. You can adjust the number of words with the following notation: `ATTRIBUTE:NUMBER`, where `NUMBER` is the number of words to be extracted.

`attributesToTransliterate`

Array of strings

Attributes, for which you want to support Japanese transliteration.

Transliteration supports searching in any of the Japanese writing systems. To support transliteration, you must set the indexing language to Japanese. Attribute names are case-sensitive.

`camelCaseAttributes`

Array of strings

Default: `[]`

Attributes for which to split camel case words. Attribute names are case-sensitive.

`customNormalization` ›

object

Characters and their normalized replacements. This overrides Fake API's normalization.

`customRanking`

Array of strings

Default: `[]`

Attributes to use as custom ranking. Attribute names are case-sensitive.

The custom ranking attributes decide which items are shown first if the other ranking criteria are equal.

Records with missing values for your selected custom ranking attributes are always sorted last. Boolean attributes are sorted based on their alphabetical order.

Modifiers

- `asc("ATTRIBUTE")`. Sort the index by the values of an attribute, in ascending order.
- `desc("ATTRIBUTE")`. Sort the index by the values of an attribute, in descending order.

If you use two or more custom ranking attributes, reduce the precision of your first attributes, or the other attributes will never be applied.

`decompoundedAttributes`

object

Default: `{}`

Searchable attributes to which API should apply word segmentation (decompounding). Attribute names are case-sensitive.

Compound words are formed by combining two or more individual words, and are particularly prevalent in Germanic languages—for example, "firefighter". With decompounding, the individual components are indexed separately.

You can specify different lists for different languages. Decompounding is supported for these languages: Dutch (`nl`), German (`de`), Finnish (`fi`), Danish (`da`), Swedish (`sv`), and Norwegian (`no`). Decompounding doesn't work for words with non-spacing mark Unicode characters. For example, `Gartenstühle` won't be decompounded if the `ü` consists of `u` (U+0075) and `̈` (U+0308).

`decompoundQuery`

boolean

Default: `true`

Whether to split compound words in the query into their building blocks.

For more information, see Word segmentation. Word segmentation is supported for these languages: German, Dutch, Finnish, Swedish, and Norwegian. Decompounding doesn't work for words with non-spacing mark Unicode characters. For example, `Gartenstühle` won't be decompounded if the `ü` consists of `u` (U+0075) and `̈` (U+0308).

`disableExactOnAttributes`

Array of strings

Default: `[]`

Searchable attributes for which you want to turn off the Exact ranking criterion. Attribute names are case-sensitive.

This can be useful for attributes with long values, where the likelihood of an exact match is high, such as product descriptions. Turning off the Exact ranking criterion for these attributes favors exact matching on other attributes. This reduces the impact of individual attributes with a lot of content on ranking.

`disablePrefixOnAttributes`

Array of strings

Default: `[]`

Searchable attributes for which you want to turn off prefix matching. Attribute names are case-sensitive.

`disableTypoToleranceOnAttributes`

Array of strings

Default: `[]`

Attributes for which you want to turn off typo tolerance. Attribute names are case-sensitive.

Returning only exact matches can help when:

- Searching in hyphenated attributes.
- Reducing the number of matches when you have too many. This can happen with attributes that are long blocks of text, such as product descriptions.

Consider alternatives such as `disableTypoToleranceOnWords` or adding synonyms if your attributes have intentional unusual spellings that might look like typos.

`disableTypoToleranceOnWords`

Array of strings

Default: `[]`

Creates a list of words which require exact matches. This also turns off word splitting and concatenation for the specified words.

`distinct` ›

boolean or integer

Determines how many records of a group are included in the search results.

Records with the same value for the `attributeForDistinct` attribute are considered a group. The `distinct` setting controls how many members of the group are returned. This is useful for deduplication and grouping.

The `distinct` setting is ignored if `attributeForDistinct` is not set.

`enablePersonalization`

boolean

Default: `false`

Whether to enable Personalization.

`enableReRanking`

boolean

Default: `true`

Whether this search will use Dynamic Re-Ranking.

This setting only has an effect if you activated Dynamic Re-Ranking for this index in the dashboard.

`enableRules`

boolean

Default: `true`

Whether to enable rules.

`exactOnSingleWordQuery`

string

Default: `"attribute"`

Enum: `"attribute"` `"none"` `"word"`

Determines how the Exact ranking criterion is computed when the search query has only one word.

- `attribute`. The Exact ranking criterion is 1 if the query word and attribute value are the same. For example, a search for "road" will match the value "road", but not "road trip".
- `none`. The Exact ranking criterion is ignored on single-word searches.
- `word`. The Exact ranking criterion is 1 if the query word is found in the attribute value. The query word must have at least 3 characters and must not be a stop word. Only exact matches will be highlighted, partial and prefix matches won't.

`highlightPostTag`

string

Default: `"</em>"`

HTML tag to insert after the highlighted parts in all highlighted results and snippets.

`highlightPreTag`

string

Default: `"<em>"`

HTML tag to insert before the highlighted parts in all highlighted results and snippets.

`hitsPerPage`

integer `[ 1 .. 1000 ]`

Default: `20`

Number of hits per page.

`ignorePlurals` ›

Array of supportedLanguage (strings) or booleanString (string) or boolean

Treat singular, plurals, and other forms of declensions as equivalent. You should only use this feature for the languages used in your index.

`indexLanguages`

Array of strings

Default: `[]`

Items Enum: `"af"` `"ar"` `"az"` `"bg"` `"bn"` `"ca"` `"cs"` `"cy"` `"da"` `"de"` `"el"` `"en"` `"eo"` `"es"` `"et"` `"eu"` `"fa"` `"fi"` `"fo"` `"fr"` `"ga"` `"gl"` `"he"` `"hi"` `"hu"` `"hy"` `"id"` `"is"` `"it"` `"ja"` `"ka"` `"kk"` `"ko"` `"ku"` `"ky"` `"lt"` `"lv"` `"mi"` `"mn"` `"mr"` `"ms"` `"mt"` `"nb"` `"nl"` `"no"` `"ns"` `"pl"` `"ps"` `"pt"` `"pt-br"` `"qu"` `"ro"` `"ru"` `"sk"` `"sq"` `"sv"` `"sw"` `"ta"` `"te"` `"th"` `"tl"` `"tn"` `"tr"` `"tt"` `"uk"` `"ur"` `"uz"` `"zh"`

Languages for language-specific processing steps, such as word detection and dictionary settings.

You should always specify an indexing language. If you don't specify an indexing language, the search engine uses all supported languages, or the languages you specified with the `ignorePlurals` or `removeStopWords` parameters. This can lead to unexpected search results. For more information, see Language-specific configuration.

`keepDiacriticsOnCharacters`

string

Default: `""`

Characters for which diacritics should be preserved.

By default, FAKE API removes diacritics from letters. For example, `é` becomes `e`. If thiscauses issues in your search, you can specify characters that should keep their diacritics.

`maxFacetHits`

integer `<= 100`

Default: `10`

Maximum number of facet values to return when searching for facet values.

`maxValuesPerFacet`

integer `<= 1000`

Default: `100`

Maximum number of facet values to return for each facet.

`minProximity`

integer `[ 1 .. 7 ]`

Default: `1`

Minimum proximity score for two matching words.

This adjusts the Proximity ranking criterion by equally scoring matches that are farther apart.

For example, if `minProximity` is 2, neighboring matches and matches with one word between them would have the same score.

`minWordSizefor1Typo`

integer

Default: `4`

Minimum number of characters a word in the search query must contain to accept matches with one typo.

`minWordSizefor2Typos`

integer

Default: `8`

Minimum number of characters a word in the search query must contain to accept matches with two typos.

`mode`

string

Default: `"keywordSearch"`

Enum: `"keywordSearch"` `"neuralSearch"`

Search mode the index will use to query for results.

This setting only applies to indices, for which Fake API enabled NeuralSearch for you.

`numericAttributesForFiltering`

Array of strings

Default: `[]`

Numeric attributes that can be used as numerical filters. Attribute names are case-sensitive.

By default, all numeric attributes are available as numerical filters. For faster indexing, reduce the number of numeric attributes.

To turn off filtering for all numeric attributes, specify an attribute that doesn't exist in your index, such as `NO_NUMERIC_FILTERING`.

Modifier

- `equalOnly("ATTRIBUTE")`. Support only filtering based on equality comparisons `=` and `!=`.

`optionalWords` ›

string or null or Array of optionalWordsArray (strings)

Words that should be considered optional when found in the query.

By default, records must match all words in the search query to be included in the search results. Adding optional words can help to increase the number of search results by running an additional search query that doesn't include the optional words. For example, if the search query is "action video" and "video" is an optional word, the search engine runs two queries. One for "action video" and one for "action". Records that match all words are ranked higher.

For a search query with 4 or more words **and** all its words are optional, the number of matched words required for a record to be included in the search results increases for every 1,000 records:

- If `optionalWords` has less than 10 words, the required number of matched words increases by 1: results 1 to 1,000 require 1 matched word, results 1,001 to 2000 need 2 matched words.
- If `optionalWords` has 10 or more words, the number of required matched words increases by the number of optional words divided by 5 (rounded down). For example, with 18 optional words: results 1 to 1,000 require 1 matched word, results 1,001 to 2000 need 4 matched words.

For more information, see Optional words.

`paginationLimitedTo`

integer `<= 20000`

Default: `1000`

Maximum number of search results that can be obtained through pagination.

Higher pagination limits might slow down your search. For pagination limits above 1,000, the sorting of results beyond the 1,000th hit can't be guaranteed.

`queryLanguages`

Array of strings

Default: `[]`

Items Enum: `"af"` `"ar"` `"az"` `"bg"` `"bn"` `"ca"` `"cs"` `"cy"` `"da"` `"de"` `"el"` `"en"` `"eo"` `"es"` `"et"` `"eu"` `"fa"` `"fi"` `"fo"` `"fr"` `"ga"` `"gl"` `"he"` `"hi"` `"hu"` `"hy"` `"id"` `"is"` `"it"` `"ja"` `"ka"` `"kk"` `"ko"` `"ku"` `"ky"` `"lt"` `"lv"` `"mi"` `"mn"` `"mr"` `"ms"` `"mt"` `"nb"` `"nl"` `"no"` `"ns"` `"pl"` `"ps"` `"pt"` `"pt-br"` `"qu"` `"ro"` `"ru"` `"sk"` `"sq"` `"sv"` `"sw"` `"ta"` `"te"` `"th"` `"tl"` `"tn"` `"tr"` `"tt"` `"uk"` `"ur"` `"uz"` `"zh"`

Languages for language-specific query processing steps such as plurals, stop-word removal, and word-detection dictionaries.

This setting sets a default list of languages used by the `removeStopWords` and `ignorePlurals` settings. This setting also sets a dictionary for word detection in the logogram-based CJK languages. To support this, you must place the CJK language **first**.

You should always specify a query language. If you don't specify an indexing language, the search engine uses all supported languages, or the languages you specified with the `ignorePlurals` or `removeStopWords` parameters. This can lead to unexpected search results. For more information, see Language-specific configuration.

`queryType`

string

Default: `"prefixLast"`

Enum: `"prefixLast"` `"prefixAll"` `"prefixNone"`

Determines if and how query words are interpreted as prefixes.

By default, only the last query word is treated as a prefix (`prefixLast`). To turn off prefix search, use `prefixNone`. Avoid `prefixAll`, which treats all query words as prefixes. This might lead to counterintuitive results and makes your search slower.

For more information, see Prefix searching.

`ranking`

Array of strings

Default: `["typo","geo","words","filters","proximity","attribute","exact","custom"]`

Determines the order in which API returns your results.

By default, each entry corresponds to a ranking criteria. The tie-breaking algorithm sequentially applies each criterion in the order they're specified. If you configure a replica index for sorting by an attribute, you put the sorting attribute at the top of the list.

Modifiers

- `asc("ATTRIBUTE")`. Sort the index by the values of an attribute, in ascending order.
- `desc("ATTRIBUTE")`. Sort the index by the values of an attribute, in descending order.

Before you modify the default setting, you should test your changes in the dashboard, and by A/B testing.

`relevancyStrictness`

integer

Default: `100`

Relevancy threshold below which less relevant results aren't included in the results.

You can only set `relevancyStrictness` on virtual replica indices. Use this setting to strike a balance between the relevance and number of returned results.

`removeStopWords` ›

Array of supportedLanguage (strings) or boolean

Removes stop words from the search query.

Stop words are common words like articles, conjunctions, prepositions, or pronouns that have little or no meaning on their own. In English, "the", "a", or "and" are stop words.

You should only use this feature for the languages used in your index.

`removeWordsIfNoResults`

string

Default: `"none"`

Enum: `"allOptional"` `"firstWords"` `"lastWords"` `"none"`

Strategy for removing words from the query when it doesn't return any results. This helps to avoid returning empty search results.

- `none`. No words are removed when a query doesn't return results.
- `lastWords`. Treat the last (then second to last, then third to last) word as optional, until there are results or at most 5 words have been removed.
- `firstWords`. Treat the first (then second, then third) word as optional, until there are results or at most 5 words have been removed.
- `allOptional`. Treat all words as optional.

For more information, see Remove words to improve results.

`renderingContent` ›

object

Extra data that can be used in the search UI.

You can use this to control aspects of your search UI, such as the order of facet names and values without changing your frontend code.

`replaceSynonymsInHighlight`

boolean

Default: `false`

Whether to replace a highlighted word with the matched synonym.

By default, the original words are highlighted even if a synonym matches. For example, with `home` as a synonym for `house` and a search for `home`, records matching either "home" or "house" are included in the search results, and either "home" or "house" are highlighted.

With `replaceSynonymsInHighlight` set to `true`, a search for `home` still matches the same records, but all occurrences of "house" are replaced by "home" in the highlighted response.

`replicas`

Array of strings

Default: `[]`

Creates replica indices.

Replicas are copies of a primary index with the same records but different settings, synonyms, or rules. If you want to offer a different ranking or sorting of your search results, you'll use replica indices. All index operations on a primary index are automatically forwarded to its replicas. To add a replica index, you must provide the complete set of replicas to this parameter. If you omit a replica from this list, the replica turns into a regular, standalone index that will no longer be synced with the primary index.

Modifier

- `virtual("REPLICA")`. Create a virtual replica, Virtual replicas don't increase the number of records and are optimized for Relevant sorting.

`reRankingApplyFilter` ›

(reRankingApplyFilter (Array of reRankingApplyFilter (any) or reRankingApplyFilter (string))) or null

`responseFields`

Array of strings

Default: `["*"]`

Properties to include in the API response of search and browse requests.

By default, all response properties are included. To reduce the response size, you can select which properties should be included.

An empty list may lead to an empty API response (except properties you can't exclude).

You can't exclude these properties: `message`, `warning`, `cursor`, `abTestVariantID`, or any property added by setting `getRankingInfo` to true.

Your search depends on the `hits` field. If you omit this field, searches won't return any results. Your UI might also depend on other properties, for example, for pagination. Before restricting the response size, check the impact on your search experience.

`restrictHighlightAndSnippetArrays`

boolean

Default: `false`

Whether to restrict highlighting and snippeting to items that at least partially matched the search query. By default, all items are highlighted and snippeted.

`searchableAttributes`

Array of strings

Default: `[]`

Attributes used for searching. Attribute names are case-sensitive.

By default, all attributes are searchable and the Attribute ranking criterion is turned off. With a non-empty list, API only returns results with matches in the selectedattributes. In addition, the Attribute ranking criterion is turned on: matches in attributes that are higher in the list of `searchableAttributes` rank first. To make matches in two attributes rank equally, include them in a comma-separated string, such as `"title,alternate_title"`. Attributes with the same priority are always unordered.

For more information, see Searchable attributes.

Modifier

- `unordered("ATTRIBUTE")`. Ignore the position of a match within the attribute.

Without a modifier, matches at the beginning of an attribute rank higher than matches at the end.

`semanticSearch` ›

object

Settings for the semantic search part of NeuralSearch. Only used when `mode` is `neuralSearch`.

`separatorsToIndex`

string

Default: `""`

Control which non-alphanumeric characters are indexed.

By default, Fake API ignores non-alphanumeric characters like hyphen (`-`), plus (`+`), andparentheses (`(`, `)`). To include such characters, define them with `separatorsToIndex`.

Separators are all non-letter characters except spaces and currency characters, such as $€£¥.

With `separatorsToIndex`, Fake treats separator characters as separate words. For example, in a search for "HI+", FAKE considers "HI" and "+" as two separatewords.

`snippetEllipsisText`

string

Default: `"…"`

String used as an ellipsis indicator when a snippet is truncated.

`sortFacetValuesBy`

string

Default: `"count"`

Order in which to retrieve facet values.

- `count`. Facet values are retrieved by decreasing count. The count is the number of matching records containing this facet value.
- `alpha`. Retrieve facet values alphabetically.

This setting doesn't influence how facet values are displayed in your UI (see `renderingContent`). For more information, see facet value display.

`typoTolerance` ›

boolean or typo tolerance (string)

Whether typo tolerance is enabled and how it is applied.

If typo tolerance is true, `min`, or `strict`, word splitting and concatenation are also active.

`unretrievableAttributes`

Array of strings

Default: `[]`

Attributes that can't be retrieved at query time.

This can be useful if you want to use an attribute for ranking or to restrict access, but don't want to include it in the search results. Attribute names are case-sensitive.

`userData`

object

Default: `{}`

An object with custom data.

You can store up to 32kB as custom data.

Responses

› **200**
OK

› **400**
Bad request or request arguments.

› **402**
This feature is not enabled on your account.

› **403**
Method not allowed with this API key.

› **404**
Index not found.

PUT /1/indexes/{indexName}/settings

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type
application/json

Copy Expand all Collapse all

```json
{
  – "attributesForFaceting": [
        "author",
        "filterOnly(isbn)",
        "searchable(edition)",
        "afterDistinct(category)",
        "afterDistinct(searchable(publisher))"
    ],
  – "replicas": [
        "virtual(prod_products_price_asc)",
        "dev_products_replica"
    ],
    "paginationLimitedTo": 100,
  – "unretrievableAttributes": [
        "total_sales"
    ],
  – "disableTypoToleranceOnWords": [
        "wheel",
        "1X2BCD"
    ],
  – "attributesToTransliterate": [
        "name",
        "description"
    ],
  – "camelCaseAttributes": [
        "description"
    ],
  – "decompoundedAttributes": {
      – "de": [
            "name"
        ]
    },
  – "indexLanguages": [
        "ja"
    ],
  – "disablePrefixOnAttributes": [
        "sku"
    ],
    "allowCompressionOfIntegerArray": false,
  – "numericAttributesForFiltering": [
        "equalOnly(quantity)",
        "popularity"
    ],
    "separatorsToIndex": "+#",
  – "searchableAttributes": [
        "title,alternative_title",
        "author",
        "unordered(text)",
        "emails.personal"
    ],
  – "userData": {
        "settingID": "f2a7b51e3503acc6a39b3784ffb84300",
        "pluginVersion": "1.6.0"
    },
  – "customNormalization": {
      – "default": {
            "ä": "ae",
            "ü": "ue"
        }
    },
    "attributeForDistinct": "url",
    "maxFacetHits": 10,
    "keepDiacriticsOnCharacters": "øé",
  – "customRanking": [
        "desc(popularity)",
        "asc(price)"
    ],
  – "attributesToRetrieve": [
        "author",
        "title",
        "content"
    ],
  – "ranking": [
        "typo",
        "geo",
        "words",
        "filters",
        "proximity",
        "attribute",
        "exact",
        "custom"
    ],
    "relevancyStrictness": 90,
  – "attributesToHighlight": [
        "author",
        "title",
        "conten",
        "content"
    ],
  – "attributesToSnippet": [
        "content:80",
        "description"
    ],
    "highlightPreTag": "<em>",
    "highlightPostTag": "</em>",
    "snippetEllipsisText": "…",
    "restrictHighlightAndSnippetArrays": false,
    "hitsPerPage": 20,
    "minWordSizefor1Typo": 4,
    "minWordSizefor2Typos": 8,
    "typoTolerance": true,
    "allowTyposOnNumericTokens": true,
  – "disableTypoToleranceOnAttributes": [
        "sku"
    ],
  – "ignorePlurals": [
        "ca",
        "es"
    ],
  – "removeStopWords": [
        "ca",
        "es"
    ],
  – "queryLanguages": [
        "es"
    ],
    "decompoundQuery": true,
    "enableRules": true,
    "enablePersonalization": false,
    "queryType": "prefixAll",
    "removeWordsIfNoResults": "firstWords",
    "mode": "keywordSearch",
  – "semanticSearch": {
      – "eventSources": [
            "string"
        ]
    },
    "advancedSyntax": false,
    "optionalWords": "string",
  – "disableExactOnAttributes": [
        "description"
    ],
    "exactOnSingleWordQuery": "attribute",
  – "alternativesAsExact": [
        "ignorePlurals",
        "singleWordSynonym"
    ],
  – "advancedSyntaxFeatures": [
        "exactPhrase",
        "excludeWords"
    ],
    "distinct": 1,
    "replaceSynonymsInHighlight": false,
    "minProximity": 1,
  – "responseFields": [
        "*"
    ],
    "maxValuesPerFacet": 100,
    "sortFacetValuesBy": "count",
    "attributeCriteriaComputedByMinProximity": false,
  – "renderingContent": {
      – "facetOrdering": {
          – "facets": {
              – "order": [
                    "string"
                ]
            },
          – "values": {
              – "facet1": {
                  – "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                  – "hide": [
                        "string"
                    ]
                },
              – "facet2": {
                  – "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                  – "hide": [
                        "string"
                    ]
                }
            }
        },
      – "redirect": {
            "url": "string"
        },
      – "widgets": {
          – "banners": [
              – {
                  – "image": {
                      – "urls": [
                          – {
                                "url": "string"
                            }
                        ],
                        "title": "string"
                    },
                  – "link": {
                        "url": "string"
                    }
                }
            ]
        }
    },
    "enableReRanking": true,
  – "reRankingApplyFilter": [
        null
    ]
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy

```json
{
    "taskID": 1514562690001,
    "updatedAt": "2023-07-04T12:49:15Z"
}
```

Check task status

Checks the status of a given task.

Indexing tasks are asynchronous. When you add, update, or delete records or indices, a task is created on a queue and completed depending on the load on the server.

The indexing tasks' responses include a task ID that you can use to check the status.

acl: `["addObject"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

`taskID` required

integer <int64>

Example: `1506303845001`

Unique task identifier.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

GET `/1/indexes/{indexName}/task/{taskID}`

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift

Copy

```csharp
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.GetTaskAsync("<YOUR_INDEX_NAME>", 123L);
// >LOG
```

Response samples

200 400 402 403 404

Content type

application/json

Copy

```json
{
    "status": "notPublished"
}
```

Copy or move an index

Copies or moves (renames) an index within the same Fake application.

- Existing destination indices are overwritten, except for their analytics data.
- If the destination index doesn't exist yet, it'll be created.
- This operation is resource-intensive.

Copy

- Copying a source index that doesn't exist creates a new index with 0 records and default settings.
- The API keys of the source index are merged with the existing keys in the destination index.
- You can't copy the `enableReRanking`, `mode`, and `replicas` settings.
- You can't copy to a destination index that already has replicas.
- Be aware of the size limits.
- Related guide: Copy indices

Move

- Moving a source index that doesn't exist is ignored without returning an error.
- When moving an index, the analytics data keeps its original name, and a new set of analytics data is started for the new name. To access the original analytics in the dashboard, create an index with the original name.
- If the destination index has replicas, moving will overwrite the existing index and copy the data to the replica indices.
- Related guide: Move indices.

This operation is subject to indexing rate limits.

acl: `["addObject"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

REQUEST BODY SCHEMA: application/json
required

`destination` required

string

Index name (case-sensitive).

`operation` required

string

Enum: `"copy"` `"move"`

Operation to perform on the index.

`scope`

Array of strings

Items Enum: `"rules"` `"settings"` `"synonyms"`

Only for copying.

If you specify a scope, only the selected scopes are copied. Records and the other scopes are left unchanged. If you omit the `scope` parameter, everything is copied: records, settings, synonyms, and rules.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

POST `/1/indexes/{indexName}/operation`

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy Expand all Collapse all

```json
{
    "operation": "copy",
    "destination": "products",
  – "scope": [
        "rules"
    ]
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy

```json
{
    "taskID": 1514562690001,
    "updatedAt": "2023-07-04T12:49:15Z"
}
```

List indices

Lists all indices in the current API application.

The request follows any index restrictions of the API key you use to make the request.

acl: `["listIndexes"]`

QUERY PARAMETERS

`hitsPerPage`

integer

Default: `100`

Number of hits per page.

`page` >

integer or null

Default: `null`

Requested page of the API response. If `null`, the API response is not paginated.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

GET `/1/indexes`

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Copy

```csharp
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.ListIndicesAsync();
// >LOG
```

Response samples

200 400 402 403 404

Content type

application/json

Copy Expand all Collapse all

```json
{
  – "items": [
      – {
            "name": "movies",
            "createdAt": "2022-09-19T16:36:44.471Z",
            "updatedAt": "2023-07-04T12:49:15Z",
            "entries": 100,
            "dataSize": 48450,
            "fileSize": 112927,
            "lastBuildTimeS": 3,
            "numberOfPendingTasks": 0,
            "pendingTask": false,
            "primary": "T02",
          – "replicas": [
                "T02_push",
                "T2replica"
            ],
            "virtual": true
        }
    ],
    "nbPages": 100
}
```

Records

Add, update, and delete records from your indices.

Records are individual items in your index. When they match a search query, they're returned as search results, in the order determined by your ranking. Records are schemaless JSON objects. When adding or updating many records, check the indexing rate limits.

Related guide: Prepare your records.

Add a new record (with auto-generated object ID)

Adds a record to an index or replaces it.

- If the record doesn't have an object ID, a new record with an auto-generated object ID is added to your index.
- If a record with the specified object ID exists, the existing record is replaced.
- If a record with the specified object ID doesn't exist, a new record is added to your index.
- If you add a record to an index that doesn't exist yet, a new index is created.

To update *some* attributes of a record, use the `partial` operation. To add, update, or replace multiple records, use the `batch` operation.

This operation is subject to indexing rate limits.

acl: `["addObject"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

REQUEST BODY SCHEMA: application/json
required

The record. A schemaless object with attributes that are useful in the context of search and discovery.

object

Responses

> 201
Created

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

POST `/1/indexes/{indexName}`

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy

```json
{ }
```

Response samples

201 400 402 403 404

Content type

application/json

Copy

```json
{
    "createdAt": "2023-07-04T12:49:15Z",
    "taskID": 1514562690001,
    "objectID": "test-record-123"
}
```

Retrieve a record

Retrieves one record by its object ID.

To retrieve more than one record, use the `objects` operation.

acl: `["search"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

`objectID` required

string

Example: `test-record-123`

Unique record identifier.

QUERY PARAMETERS

`attributesToRetrieve`

Array of strings

Attributes to include with the records in the response. This is useful to reduce the size of the API response. By default, all retrievable attributes are returned.

`objectID` is always retrieved.

Attributes included in `unretrievableAttributes` won't be retrieved unless the request is authenticated with the admin API key.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

GET /1/indexes/{indexName}/{objectID}

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift

Copy

```
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.GetObjectAsync(
  "<YOUR_INDEX_NAME>",
  "uniqueID",
  new List<string> { "attr1", "attr2" }
);
// >LOG
```

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{ }
```

Add or replace a record

If a record with the specified object ID exists, the existing record is replaced. Otherwise, a new record is added to the index.

If you want to use auto-generated object IDs, use the `saveObject` operation. To update *some* attributes of an existing record, use the `partial` operation instead. To add, update, or replace multiple records, use the `batch` operation.

acl: `["addObject"]`

PATH PARAMETERS

`indexName`
required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

`objectID`
required

string

Example: `test-record-123`

Unique record identifier.

REQUEST BODY SCHEMA: application/json
required

The record. A schemaless object with attributes that are useful in the context of search and discovery.

object

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

PUT /1/indexes/{indexName}/{objectID}

Request samples

Payload

Content type
application/json

Copy

```
{ }
```

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{
  "taskID": 1514562690001,
  "updatedAt": "2023-07-04T12:49:15Z",
  "objectID": "test-record-123"
}
```

Delete a record

Deletes a record by its object ID.

To delete more than one record, use the `batch` operation. To delete records matching a query, use the `deleteByQuery` operation.

acl: `["deleteObject"]`

PATH PARAMETERS

`indexName`
required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

`objectID`
required

string

Example: `test-record-123`

Unique record identifier.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

DELETE /1/indexes/{indexName}/{objectID}

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{
  "taskID": 1514562690001,
  "deletedAt": "2023-06-27T14:42:38.831Z"
}
```

Delete records matching a filter

This operation doesn't accept empty filters.

This operation is resource-intensive. You should only use it if you can't get the object IDs of the records you want to delete. It's more efficient to get a list of object IDs with the `browse` operation, and then delete the records using the `batch` operation.

This operation is subject to indexing rate limits.

Should I use the deleteBy method for deleting records.

acl: `["deleteIndex"]`

PATH PARAMETERS

`indexName`
required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

REQUEST BODY SCHEMA: application/json
required

`aroundLatLng`

string

Default: `""`

Coordinates for the center of a circle, expressed as a comma-separated string of latitude and longitude.

Only records included within a circle around this central location are included in the results. The radius of the circle is determined by the `aroundRadius` and `minimumAroundRadius` settings. This parameter is ignored if you also specify `insidePolygon` or `insideBoundingBox`.

`aroundRadius` >

integer or all (string)

Maximum radius for a search around a central location.

This parameter works in combination with the `aroundLatLng` and `aroundLatLngViaIP` parameters. By default, the search radius is determined automatically from the density of hits around the central location. The search radius is small if there are many hits close to the central coordinates.

`facetFilters` >

Array of facetFilters (any) or string

Filter the search by facet values, so that only records with the same facet values are retrieved.

Prefer using the `filters` parameter, which supports all filter types and combinations with boolean operators.

- `[filter1, filter2]` is interpreted as `filter1 AND filter2`.
- `[[filter1, filter2], filter3]` is interpreted as `filter1 OR filter2 AND filter3`.
- `facet:-value` is interpreted as `NOT facet:value`.

While it's best to avoid attributes that start with a `-`, you can still filter them by escaping with a backslash: `facet:\-value`.

`filters`

string

Filter expression to only include items that match the filter criteria in the response.

You can use these filter expressions:

- **Numeric filters.** `<facet> <op> <number>`, where `<op>` is one of `<`, `<=`, `=`, `!=`, `>`, `>=`.
- **Ranges.** `<facet>:<lower> TO <upper>` where `<lower>` and `<upper>` are the lower and upper limits of the range (inclusive).
- **Facet filters.** `<facet>:<value>` where `<facet>` is a facet attribute (case-sensitive) and `<value>` a facet value.
- **Tag filters.** `_tags:<value>` or just `<value>` (case-sensitive).
- **Boolean filters.** `<facet>: true | false`.

You can combine filters with `AND`, `OR`, and `NOT` operators with the following restrictions:

- You can only combine filters of the same type with `OR`. **Not supported:** `facet:value OR num > 3`.
- You can't use `NOT` with combinations of filters. **Not supported:** `NOT(facet:value OR facet:value)`
- You can't combine conjunctions (`AND`) with `OR`. **Not supported:** `facet:value OR (facet:value AND facet:value)`

Use quotes around your filters, if the facet attribute name or facet value has spaces, keywords (`OR`, `AND`, `NOT`), or quotes. If a facet attribute is an array, the filter matches if it matches at least one element of the array.

For more information, see Filters.

`insideBoundingBox` >

string or null or Array of insideBoundingBoxArray (numbers)

`insidePolygon`

Array of numbers [items <double > [6 .. 20000] items [items <double >]]

Coordinates of a polygon in which to search.

Polygons are defined by 3 to 10,000 points. Each point is represented by its latitude and longitude. Provide multiple polygons as nested arrays. For more information, see filtering inside polygons. This parameter is ignored if you also specify `insideBoundingBox`.

`numericFilters` >

Array of numericFilters (any) or string

Filter by numeric facets.

Prefer using the `filters` parameter, which supports all filter types and combinations with boolean operators.

You can use numeric comparison operators: `<`, `<=`, `=`, `!=`, `>`, `>=`. Comparisons are precise up to 3 decimals. You can also provide ranges: `facet:<lower> TO <upper>`. The range includes the lower and upper boundaries. The same combination rules apply as for `facetFilters`.

`tagFilters` >

Array of tagFilters (any) or string

Filter the search by values of the special `_tags` attribute.

Prefer using the `filters` parameter, which supports all filter types and combinations with boolean operators.

Different from regular facets, `_tags` can only be used for filtering (including or excluding records). You won't get a facet count. The same combination and escaping rules apply as for `facetFilters`.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

POST /1/indexes/{indexName}/deleteByQuery

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type
application/json

Copy Expand all Collapse all

```
{
 – "facetFilters": [
   – [
       "category:Book",
       "category:-Movie"
     ],
     "author:John Doe"
   ],
   "filters": "(category:Book OR category:Ebook) AND _tags:published",
 – "numericFilters": [
   – [
       "inStock = 1",
       "deliveryDate < 1441755506"
     ],
     "price < 1000"
   ],
 – "tagFilters": [
   – [
       "Book",
       "Movie"
     ],
     "SciFi"
   ],
   "aroundLatLng": "40.71,-74.01",
   "aroundRadius": 1,
   "insideBoundingBox": "string",
 – "insidePolygon": [
   – [
       47.3165,
       4.9665,
       47.3424,
       5.0201,
       47.32,
       4.9
     ],
   – [
       40.9234,
       2.1185,
       38.643,
       1.9916,
       39.2587,
       2.0104
     ]
   ]
}
```

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{
  "taskID": 1514562690001,
  "updatedAt": "2023-07-04T12:49:15Z"
}
```

Delete all records from an index

Deletes only the records from an index while keeping settings, synonyms, and rules. This operation is resource-intensive and subject to indexing rate limits.

acl: `["deleteIndex"]`

PATH PARAMETERS

`indexName`
required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

POST /1/indexes/{indexName}/clear

Request samples

C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Copy

```
// Initialize the client
var client = new SearchClient(new SearchConfig("APPLICATION_ID", "API_KEY"

// Call the API
var response = await client.ClearObjectsAsync("<YOUR_INDEX_NAME>");
// >LOG
```

Response samples

200 400 402 403 404

Content type
application/json

Copy

```
{
  "taskID": 1514562690001,
  "updatedAt": "2023-07-04T12:49:15Z"
}
```

Add or update attributes

Adds new attributes to a record, or updates existing ones.

- If a record with the specified object ID doesn't exist, a new record is added to the index **if** `createIfNotExists` is true.
- If the index doesn't exist yet, this method creates a new index.
- You can use any first-level attribute but not nested attributes. If you specify a nested attribute, this operation replaces its first-level ancestor.

To update an attribute without pushing the entire record, you can use these built-in operations. These operations can be helpful if you don't have access to your initial data.

- Increment: increment a numeric attribute
- Decrement: decrement a numeric attribute
- Add: append a number or string element to an array attribute
- Remove: remove all matching number or string elements from an array attribute made of numbers or strings
- AddUnique: add a number or string element to an array attribute made of numbers or strings only if it's not already present
- IncrementFrom: increment a numeric integer attribute only if the provided value matches the current value, and otherwise ignore the whole object update. For example, if you pass an IncrementFrom value of 2 for the version attribute, but the current value of the attribute is 1, the engine ignores the update. If the object doesn't exist, the engine only creates it if you pass an IncrementFrom value of 0.
- IncrementSet: increment a numeric integer attribute only if the provided value is greater than the current value, and otherwise ignore the whole object update. For example, if you pass an IncrementSet value of 2 for the version attribute, and the current value of the attribute is 1, the engine updates the object. If the object doesn't exist yet, the engine only creates it if you pass an IncrementSet value greater than 0.

You can specify an operation by providing an object with the attribute to update as the key and its value being an object with the following properties:

- _operation: the operation to apply on the attribute
- value: the right-hand side argument to the operation, for example, increment or decrement step, value to add or remove.

This operation is subject to indexing rate limits.

acl: `["addObject"]`

PATH PARAMETERS

`indexName`
required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

`objectID`
required

string

Example: `test-record-123`

Unique record identifier.

QUERY PARAMETERS

`createIfNotExists`

boolean

Default: `true`

Whether to create a new record if it doesn't exist.

REQUEST BODY SCHEMA: application/json
required

Attributes with their values.

object

Attributes to update.

Responses

> 200
OK

> 400
Bad request or request arguments.

> 402
This feature is not enabled on your account.

> 403
Method not allowed with this API key.

> 404
Index not found.

POST /1/indexes/{indexName}/{objectID}/partial

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift

Content type

application/json

Copy

```
{ }
```

Response samples

200 400 402 403 404

Content type

application/json

Copy

```
{
    "taskID": 1514562690001,
    "updatedAt": "2023-07-04T12:49:15Z",
    "objectID": "test-record-123"
}
```

Batch indexing operations on one index

Adds, updates, or deletes records in one index with a single API request.

Batching index updates reduces latency and increases data integrity.

- Actions are applied in the order they're specified.
- Actions are equivalent to the individual API requests of the same name.

This operation is subject to indexing rate limits.

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

REQUEST BODY SCHEMA: application/json required

`requests` › required

Array of objects

Responses

› 200
OK

› 400
Bad request or request arguments.

› 402
This feature is not enabled on your account.

› 403
Method not allowed with this API key.

› 404
Index not found.

POST /1/indexes/{indexName}/batch

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy Expand all Collapse all

```
{
    "requests": [
        {
            "action": "addObject",
            "body": {
                "name": "Betty Jane McCamey",
                "company": "Vita Foods Inc.",
                "email": "betty@mccamey.com"
            }
        },
        {
            "action": "addObject",
            "body": {
                "name": "Gayla geimer",
                "company": "Ortman McCain Co.",
                "email": "gayla@geimer.com"
            }
        }
    ]
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy Expand all Collapse all

```
{
    "taskID": 1514562690001,
    "objectIDs": [
        "record-1",
        "record-2"
    ]
}
```

Batch indexing operations on multiple indices

Adds, updates, or deletes records in multiple indices with a single API request.

- Actions are applied in the order they are specified.
- Actions are equivalent to the individual API requests of the same name.

This operation is subject to indexing rate limits.

REQUEST BODY SCHEMA: application/json required

`requests` › required

Array of objects

Responses

› 200
OK

› 400
Bad request or request arguments.

› 402
This feature is not enabled on your account.

› 403
Method not allowed with this API key.

› 404
Index not found.

POST /1/indexes/*/batch

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy Expand all Collapse all

```
{
    "requests": [
        {
            "action": "addObject",
            "indexName": "contacts",
            "body": {
                "name": "Betty Jane McCamey",
                "company": "Vita Foods Inc.",
                "email": "betty@mccamey.com"
            }
        },
        {
            "action": "addObject",
            "indexName": "public_contacts",
            "body": {
                "name": "Gayla geimer",
                "company": "Ortman McCain Co.",
                "email": "gayla@geimer.com"
            }
        }
    ]
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy Expand all Collapse all

```
{
    "taskID": {
        "property1": 1514562690001,
        "property2": 1514562690001
    },
    "objectIDs": [
        "record-1",
        "record-2"
    ]
}
```

Retrieve records

Retrieves one or more records, potentially from different indices.

Records are returned in the same order as the requests.

acl: `["search"]`

REQUEST BODY SCHEMA: application/json required

Request object.

`requests` › required

Array of objects

Responses

› 200
OK

› 400
Bad request or request arguments.

› 402
This feature is not enabled on your account.

› 403
Method not allowed with this API key.

› 404
Index not found.

POST /1/indexes/*/objects

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy Expand all Collapse all

```
{
    "requests": [
        {
            "attributesToRetrieve": [
                "author",
                "title",
                "content"
            ],
            "objectID": "product-1",
            "indexName": "books"
        }
    ]
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy Expand all Collapse all

```
{
    "message": "Index INDEX_NAME does not exist.",
    "results": [
        { }
    ]
}
```

Search

Search one or more indices for matching records or facet values.

Search an index

Searches a single index and returns matching search results (*hits*).

This method lets you retrieve up to 1,000 hits. If you need more, use the `browse` operation or increase the `paginatedLimitedTo` index setting.

acl: `["search"]`

PATH PARAMETERS

`indexName` required

string

Example: `FAKE_INDEX_NAME`

Name of the index on which to perform the operation.

REQUEST BODY SCHEMA: application/json

One of Search parameters as query string. Search parameters as object

`params`

string

Default: `""`

Search parameters as a URL-encoded query string.

Responses

› 200
OK

› 400
Bad request or request arguments.

› 402
This feature is not enabled on your account.

› 403
Method not allowed with this API key.

› 404
Index not found.

POST /1/indexes/{indexName}/query

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Example

Search parameters as query string.

Copy

```
{
    "params": "hitsPerPage=2&getRankingInfo=1"
}
```

Response samples

200 400 402 403 404

Content type

application/json

Copy Expand all Collapse all

```
{
    "abTestID": 0,
    "abTestVariantID": 1,
    "aroundLatLng": "40.71,-74.01",
    "automaticRadius": "string",
    "exhaustive": {
        "facetsCount": true,
        "facetValues": true,
        "nbHits": true,
        "rulesMatch": true,
        "typo": true
    },
    "appliedRules": [
        { }
    ],
    "exhaustiveFacetsCount": true,
    "exhaustiveNbHits": true,
    "exhaustiveTypo": true,
    "facets": {
        "category": {
            "food": 1,
            "tech": 42
        }
    },
    "facets_stats": {
        "property1": {
            "min": 0.1,
            "max": 0.1,
            "avg": 0.1,
            "sum": 0.1
        },
        "property2": {
            "min": 0.1,
            "max": 0.1,
            "avg": 0.1,
            "sum": 0.1
        }
    },
    "index": "indexName",
    "indexUsed": "indexNameAlt",
    "message": "string",
    "nbSortedHits": 20,
    "parsedQuery": "george clo",
    "processingTimeMS": 20,
    "processingTimingsMS": { },
    "queryAfterRemoval": "string",
    "redirect": {
        "index": [
            {
                "source": "string",
                "dest": "string",
                "reason": "string",
                "succeed": true,
                "data": {
                    "ruleObjectID": "string"
                }
            }
        ]
    },
    "renderingContent": {
        "facetOrdering": {
            "facets": {
                "order": [
                    "string"
                ]
            },
            "values": {
                "facet1": {
                    "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                    "hide": [
                        "string"
                    ]
                },
                "facet2": {
                    "order": [
                        "string"
                    ],
                    "sortRemainingBy": "alpha",
                    "hide": [
                        "string"
                    ]
                }
            }
        },
        "redirect": {
            "url": "string"
        },
        "widgets": {
            "banners": [
                {
                    "image": {
                        "urls": [
                            {
                                "url": "string"
                            }
                        ],
                        "title": "string"
                    },
                    "link": {
                        "url": "string"
                    }
                }
            ]
        }
    },
    "serverTimeMS": 20,
    "serverUsed": "c2-uk-3.fake.net",
    "userData": {
        "settingID": "f2a7b51e3503acc6a39b3784ffb84300",
        "pluginVersion": "1.6.0"
    },
    "queryID": "a00dbc80a8d13c4565a442e7e2dca80a",
    "_automaticInsights": true,
    "page": 0,
    "nbHits": 20,
    "nbPages": 1,
    "hitsPerPage": 20,
    "hits": [
        {
            "objectID": "test-record-123",
            "_highlightResult": {
                "attribute1": {
                    "value": "<em>George</em> <em>Clo</em>oney",
                    "matchLevel": "full",
                    "matchedWords": [
                        "action"
                    ],
                    "fullyHighlighted": true
                },
                "attribute2": {
                    "value": "<em>George</em> <em>Clo</em>oney",
                    "matchLevel": "full",
                    "matchedWords": [
                        "action"
                    ],
                    "fullyHighlighted": true
                }
            },
            "_snippetResult": {
                "attribute1": {
                    "value": "<em>George</em> <em>Clo</em>oney",
                    "matchLevel": "full"
                },
                "attribute2": {
                    "value": "<em>George</em> <em>Clo</em>oney",
                    "matchLevel": "full"
                }
            },
            "_rankingInfo": {
                "filters": 0,
                "firstMatchedWord": 0,
                "geoDistance": 0,
                "geoPrecision": 1,
                "matchedGeoLocation": {
                    "lat": 0.1,
                    "lng": 0.1,
                    "distance": 0
                },
                "personalization": {
                    "filtersScore": 0,
                    "rankingScore": 0,
                    "score": 0
                },
                "nbExactWords": 0,
                "nbTypos": 0,
                "promoted": true,
                "proximityDistance": 0,
                "userScore": 0,
                "words": 1,
                "promotedByReRanking": true
            },
            "_distinctSeqID": 0
        }
    ],
    "query": "",
    "params": "query=a&hitsPerPage=20"
}
```

Search multiple indices

Sends multiple search requests to one or more indices.

This can be useful in these cases:

- Different indices for different purposes, such as, one index for products, another one for marketing content.
- Multiple searches to the same index—for example, with different filters.

acl: `["search"]`

REQUEST BODY SCHEMA: application/json required

Muli-search request body. Results are returned in the same order as the requests.

`requests` › required

Array of (SearchForHits (Search parameters as query string. (object) or Search parameters as object (object))) or (SearchForFacets (Search parameters as query string. (object) or Search parameters as object (object)))

`strategy`

string

Enum: `"none"` `"stopIfEnoughMatches"`

Strategy for multiple search queries:

- `none`. Run all queries.
- `stopIfEnoughMatches`. Run the queries one by one, stopping as soon as a query matches at least the `hitsPerPage` number of results.

Responses

› 200
OK

› 400
Bad request or request arguments.

› 402
This feature is not enabled on your account.

› 403
Method not allowed with this API key.

› 404
Index not found.

POST /1/indexes/*/queries

Request samples

Payload C# Dart Go Java JavaScript Kotlin PHP Python Ruby Scala Swift curl

Content type

application/json

Copy Expand all Collapse all

```
{
    "requests": [
        {
            "params": "hitsPerPage=2&getRankingInfo=1",
            "indexName": "products",
            "type": "default"
        }
    ],
    "strategy": "none"
}
```