

Mac Store UK

API Documentation

Version C3.26.4.1

macstore.mpx.one

Generated 27 April 2026

6 APIs documented

Overview

The MPX API uses a RESTful architecture with JSON request and response bodies. All API requests are made to a single endpoint using the Postbox system.

Base URL

All requests should be sent as POST requests to:

```
POST https://macstore.mpx.one/postbox
```

Authentication

API Tokens

All API requests require authentication via an API token passed in the request header:

```
api-token: your-api-token-here
```

Creating Tokens

API tokens can be created at two levels:

Account Level Tokens

- Created from the Account window under the "API Tokens" tab
- Provides access to data for the entire account
- Best for integrations that need to access multiple users' data

User Level Tokens

- Created from the User window under the "API Tokens" tab
- Provides access limited to that user's context
- Best for user-specific integrations

Token Scopes

Each token is assigned one or more scopes that control what actions it can perform:

Scope	Description
read	Allows reading/retrieving data
write	Allows creating, updating and deleting data

Endpoints specify which scope is required. Attempting to access an endpoint without the required scope returns an authorisation error.

Data Isolation

API responses are automatically filtered based on the token's associated account. This ensures that each account can only access its own data.

How It Works

User Level Tokens

- Data is filtered to the user's parent account
- The API will only return records belonging to that account
- Creating or updating records will associate them with that account

Account Level Tokens

- Data is filtered to the specific account
- Provides access to all data within that account
- Useful for integrations that operate on behalf of the entire account

ADMIN Scope

Tokens with the `admin` scope bypass data isolation entirely. This allows access to data across all accounts and should only be used for system-level integrations or administrative purposes.

Scope	Data Access
read	Filtered to token's account
write	Filtered to token's account
admin	Full access across all accounts

Important: The `admin` scope should be used with caution and only assigned to tokens that genuinely require cross-account access.

Request Format

All requests must include the following headers:

```
Content-Type: application/json
api-token: your-api-token-here
```

The request body should be a JSON object containing:

- `RequestType` - The endpoint identifier (e.g., `"Inventory.GetAsset"`)
- Additional parameters as required by the specific endpoint

Example Request

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: your-token' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Inventory.GetAsset",
  "AssetTag": "MP000001"
}'
```

Response Format

All responses are returned as JSON with the following structure:

Success Response

```
{
  "Result": true,
  "Payload": {
    // Response data here
  }
}
```

Error Response

```
{
  "Result": false,
  "Errors": [
    "Error message describing what went wrong"
  ]
}
```

HTTP Status Codes

Code	Description
200	Success
400	Bad Request - Invalid or missing parameters
401	Unauthorised - Invalid or missing API token
403	Forbidden - Token lacks required scope
500	Server Error

Couriers

GnomeCouriersApi

Overview

The Couriers API provides read-only endpoints for retrieving courier configuration data including courier lists, individual courier details and courier service information.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type: application/json`

Base URL

```
POST https://macstore.mpx.one/postbox
```

Endpoints

Couriers.GetCourierList

Retrieves a list of all configured couriers and their services.

Scope Required: `read`

Request:

```
{
  "RequestType": "Couriers.GetCourierList"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Couriers.GetCourierList"

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Couriers.GetCourierList"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "Messages": [],
  "Payload": {
    "Amazon": {
      "Key": "Amazon",
      "Description": "Amazon",
      "Services": {
```

```

        "AMAZON": {
            "Key": "AMAZON",
            "Description": "Amazon Shipping"
        }
    },
    "DefaultCollectionTime": "17:00"
},
"CustomerCollection": {
    "Key": "CustomerCollection",
    "Description": "Customer Collection",
    "Services": {
        "CUST-COLLECT": {
            "Key": "CUST-COLLECT",
            "Description": "Self Service"
        }
    },
    "DefaultCollectionTime": "17:00"
}
}
}

```

Notes:

- Returns all configured couriers from Config.xml plus any additional couriers added via the `GnomeCouriers.GetCourierList` event
- Each courier includes its Key, Description, Services array and DefaultCollectionTime

Couriers.GetCourier

Retrieves details for a specific courier by its key.

Scope Required: read

Request:

```

{
    "RequestType": "Couriers.GetCourier",
    "CourierKey": "Amazon"
}

```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Couriers.GetCourier"
CourierKey	string	Yes	The unique key identifying the courier

Example:

```

curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \

```

```
--header 'Content-Type: application/json' \  
--data '{  
    "RequestType": "Couriers.GetCourier",  
    "CourierKey": "Amazon"  
}'
```

Response (Success):

```
{  
  "Result": true,  
  "Errors": [],  
  "Messages": [],  
  "Payload": {  
    "Key": "Amazon",  
    "Description": "Amazon",  
    "Services": {  
      "AMAZON": {  
        "Key": "AMAZON",  
        "Description": "Amazon Shipping"  
      }  
    },  
    "DefaultCollectionTime": "17:00"  
  }  
}
```

Response (Error - Missing Parameter):

```
{  
  "Result": false,  
  "Errors": ["Missing required parameter: CourierKey"],  
  "Messages": [],  
  "Payload": []  
}
```

Response (Error - Not Found):

```
{  
  "Result": false,  
  "Errors": ["Courier not found for key: InvalidKey"],  
  "Messages": [],  
  "Payload": []  
}
```

Couriers.GetCourierService

Retrieves details for a specific courier service by its key.

Scope Required: read

Request:

```
{
  "RequestType": "Couriers.GetCourierService",
  "CourierServiceKey": "AMAZON",
  "CourierKey": "Amazon"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Couriers.GetCourierService"
CourierServiceKey	string	Yes	The unique key identifying the courier service
CourierKey	string	No	The courier key. When provided, performs a direct lookup. When omitted, searches all couriers for the service.

Example (with CourierKey):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Couriers.GetCourierService",
  "CourierServiceKey": "AMAZON",
  "CourierKey": "Amazon"
}'
```

Example (without CourierKey):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Couriers.GetCourierService",
  "CourierServiceKey": "AMAZON"
}'
```

Response (Success - with CourierKey):

```
{
  "Result": true,
  "Errors": [],
  "Messages": [],
  "Payload": {
    "Key": "AMAZON",
    "Description": "Amazon Shipping"
  }
}
```



```
}
```

Response (Success - without CourierKey, includes parent Courier):

```
{
  "Result": true,
  "Errors": [],
  "Messages": [],
  "Payload": {
    "Key": "AMAZON",
    "Description": "Amazon Shipping",
    "Courier": {
      "Key": "Amazon",
      "Description": "Amazon",
      "Services": {
        "AMAZON": {
          "Key": "AMAZON",
          "Description": "Amazon Shipping"
        }
      }
    },
    "DefaultCollectionTime": "17:00"
  }
}
```

Response (Error - Missing Parameter):

```
{
  "Result": false,
  "Errors": ["Missing required parameter: CourierServiceKey"],
  "Messages": [],
  "Payload": []
}
```

Response (Error - Not Found):

```
{
  "Result": false,
  "Errors": ["Courier service not found for key: InvalidServiceKey"],
  "Messages": [],
  "Payload": []
}
```

Notes:

- When CourierKey is omitted, the service search iterates through all couriers and returns the parent Courier object attached to the result
- When CourierKey is provided, returns only the service details without the parent Courier

Credit Notes

GnomeCreditNotesApi API

Overview

The GnomeCreditNotesApi provides API endpoints for retrieving credit note data through the Postbox system. Credit notes are stored in the GnomeInvoices table with Type = 'CRN' and represent negative invoices used to credit customers for returns, refunds or adjustments.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type: application/json`

Base URL

```
POST https://macstore.mpx.one/postbox
```

Endpoints

CreditNotes.GetCreditNotes

Retrieves credit notes based on optional filter criteria. Returns credit note header information plus associated line items.

Scope Required: `read`

Request:

```
{
  "RequestType": "CreditNotes.GetCreditNotes",
  "CreditNoteNumber": "10123",
  "ExternalRef": "EXT-456",
  "ExternalOrderRef": "ORD-789",
  "OrderRef": "SO-001",
  "PaymentStatus": "Unsettled",
  "DateFrom": "2026-01-01",
  "DateTo": "2026-02-16"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "CreditNotes.GetCreditNotes"
AccountNumber	string	No	Customer account number. *Automatically injected from the authenticated account context and cannot be overridden.*
CreditNoteNumber	string	No	Specific credit note number to retrieve
ExternalRef	string	No	External reference associated with the credit note
ExternalOrderRef	string	No	External order reference associated with the credit note
OrderRef	string	No	Order reference associated with the credit note
PaymentStatus	string	No	Filter by payment status. Common values: "Unsettled", "Part Settled", "Settled"
DateFrom	string	No	Start date filter in format YYYY-MM-DD. Filters credit notes where TaxPoint >= this date (at 00:00:00)
DateTo	string	No	End date filter in format YYYY-MM-DD. Filters credit notes where TaxPoint <= this date (at 23:59:59)

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "CreditNotes.GetCreditNotes",
  "PaymentStatus": "Unsettled",
  "DateFrom": "2026-01-01"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "Uid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
      "CreditNoteNumber": "10123",
      "AccountNumber": "ACC001",
      "AccountName": "Example Customer Ltd",
      "ExternalRef": "EXT-456",
      "ExternalOrderRef": "ORD-789",
      "OrderRef": "SO-001",
      "JobRef": "JOB-123",
      "OriginatingInvoiceNumber": "10100",
      "GoodsTotal": "-100.00",
      "GoodsTax": "-20.00",
      "CarriageTotal": "-10.00",
      "CarriageTax": "-2.00",
      "Total": "-132.00",
      "CurrencyCode": "GBP",
      "ExchangeRate": "1.00",
      "TaxScheme": "Standard",
      "PaymentStatus": "Unsettled",
      "Memo": "Credit for damaged goods",
      "Note": "Customer reference: RET-456",
    }
  ]
}
```

```

    "BillingFao": "Accounts Department",
    "BillingCompanyName": "Example Customer Ltd",
    "BillingAddressLine1": "123 High Street",
    "BillingAddressLine2": "Business Park",
    "BillingAddressLine3": "",
    "BillingTownCity": "London",
    "BillingCounty": "Greater London",
    "BillingPostcode": "SW1A 1AA",
    "BillingCountry": "GB",
    "TaxPoint": "15-02-2026 10:30:00",
    "DateCreated": "15-02-2026 10:30:00",
    "DateUpdated": null,
    "Items": [
      {
        "SqlId": "789",
        "Sku": "PROD-001",
        "ItemDescription": "Example Product",
        "UnitQty": "2",
        "UnitPrice": "50.00",
        "TaxRate": "0.20"
      }
    ]
  }
}

```

Response (No Results):

```

{
  "Result": true,
  "Messages": ["There are no credit notes."],
  "Payload": []
}

```

Response (Error):

```

{
  "Result": false,
  "Errors": ["Error message"]
}

```

Notes:

- This endpoint retrieves credit notes from the GnomelInvoices table where Type = 'CRN' and Void = 0
- All filter parameters are optional. When omitted, the endpoint returns all non-voided credit notes for the authenticated account
- The AccountNumber is always injected from the authenticated token's account context and cannot be overridden by the caller
- Date filters work on the TaxPoint field. DateFrom sets the time to 00:00:00, DateTo sets it to 23:59:59
- All monetary values in credit notes are stored as negative numbers (e.g., -132.00) to represent credits
- Each credit note includes an Items array containing line item details from the GnomelInvoiceItems table

- The `OriginatingInvoiceNumber` field references the original invoice that this credit note relates to (if applicable)
 - Results are ordered by `DateCreated` DESC (newest first)
 - `PaymentStatus` indicates whether the credit note has been applied against customer payments: "Unsettled" (not applied), "Part Settled" (partially applied), "Settled" (fully applied)
 - Date fields (`TaxPoint`, `DateCreated`, `DateUpdated`) are formatted for display as DD-MM-YYYY HH:MM:SS in the response
-
-

Fulfilment

GnomeFulfilmentApi

Overview

The Fulfilment API provides endpoints for managing the order fulfilment workflow, including picking and packing operations. This API supports the complete lifecycle of order processing from initial picking requests through to completed packing.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type`: `application/json`

Base URL

```
POST https://macstore.mpx.one/postbox
```

Picking Endpoints

Fulfilment.GetPickingRequests

Retrieves a list of picking requests, optionally filtered by status.

Scope Required: `read`

Request:

```
{
  "RequestType": "Fulfilment.GetPickingRequests",
  "Statuses": "PENDING,PICKING",
  "OrderRef": "ORD-12345",
```

```
"ExternalRef": "EXT-67890",
"PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"

}
```

Note: All filter parameters are optional. You can use any combination of filters.

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.GetPickingRequests"
Statuses	string	No	Comma separated list of statuses to filter by. *Note: Restrict the results to a comma separated list of included statuses. Valid statuses are: PENDING, PICKING, PICKED, PACKING, PACKED, COMPLETE.*
PickingRequestUId	string	No	Filter by specific picking request UId (32 character identifier). *Note: When provided, returns only the picking request matching this exact UId. Invalid length values are ignored.*
OrderRef	string	No	Filter by order reference. *Note: Returns picking requests matching this exact order reference.*
ExternalRef	string	No	Filter by external reference. *Note: Returns picking requests matching this exact external reference.*

Example (filter by status):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetPickingRequests",
  "Statuses": "PENDING,PICKING"
}'
```

Example (filter by order reference):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetPickingRequests",
  "OrderRef": "ORD-12345"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "SqlId": "123",
      "UId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
    }
  ]
}
```

```
        "Status": "PENDING",
        "AccountNumber": "12345",
        "FacilityCode": "DEFAULT",
        "DateCreated": "20251201120000"
    }
}
}
```

Response (Empty):

```
{
  "Result": true,
  "Messages": ["There are no picking requests."],
  "Payload": []
}
```

Notes:

- Results are filtered by the API token's account. Only picking requests for facilities associated with your account are returned.
- If no Statuses parameter is provided, returns all picking requests for your facilities
- The Uid field is the 32 character UUID used to reference this picking request in subsequent API calls
- The FacilityCode field indicates which fulfilment facility the picking request is assigned to

Fulfilment.GetPickingList

Retrieves the picking list for a specific picking request, including requested items, suggested assets and any already picked items.

Scope Required: read

Request:

```
{
  "RequestType": "Fulfilment.GetPickingList",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.GetPickingList"
PickingRequestUid	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetPickingList",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "PickingRequestItemId": "456",
      "Sku": "PROD-001",
      "RequestedAssetTag": "",
      "SuggestedAssetTag": "MP000001",
      "PickedAssetTag": "",
      "ItemDescription": "Example Product",
      "UnitQty": 1,
      "SalesItemId": "789",
      "LocationRef": "A01",
      "FullLocation": "Aisle A, Bay 01",
      "TrackingDisabled": 0,
      "CanAutoPick": 0
    }
  ]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid PickingRequestUid."]
}
```

Notes:

- Returns all items on the picking list with their current pick status
 - The PickingRequestItemId is used when calling Fulfilment.PickAsset to specify a particular line item
 - SuggestedAssetTag contains the system's recommended asset to pick based on FIFO logic
 - PickedAssetTag will contain the asset tag once an item has been picked
 - TrackingDisabled indicates whether the item requires individual asset tracking
 - CanAutoPick indicates whether the system can automatically assign an asset
-

Fulfilment.StartPicking

Starts the picking process for a picking request, assigning the current user as the picker.

Scope Required: `write`

Request:

```
{
  "RequestType": "Fulfilment.StartPicking",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "UserNumber": "12345"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.StartPicking"
PickingRequestUid	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*
UserNumber	integer	No	The user number of the picker. When omitted, uses the current session user. When provided, assigns the specified user as the picker.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.StartPicking",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "Messages": ["Okay, we're ready to start picking."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid PickingRequestUid."]
}
```

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to start picking."]
}
```

Notes:

- This function tells the system we have started picking the request
 - The method timestamps the request and updates its status to PICKING
 - Only works for requests in PENDING status
-

Fulfilment.RestartPicking

Resets the picking progress for a picking request, clearing all picked items.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.RestartPicking",
  "PickingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.RestartPicking"
PickingRequestId	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.RestartPicking",
  "PickingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Okay, we've reset the picking list."]
}
```

```
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to undo pick item."]
}
```

Notes:

- Clears all previously picked items and resets the picking list to its initial state
- Only works for requests in PENDING or PICKING status
- Useful when a picker needs to start over or made errors during picking

Fulfilment.PickAsset

Records an asset as picked, moving it to the specified location.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.PickAsset",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001",
  "ToLocationRef": "PACK01",
  "PickingRequestItemId": "456"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.PickAsset"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*
AssetTag	string	Yes	The asset tag to pick (case insensitive, will be converted to uppercase)
ToLocationRef	string	Yes	The destination location reference (typically a packing station)
PickingRequestItemId	string	No	The specific picking request item ID to assign this asset to. *Note: This is the PickingRequestItemId from the Fulfilment.GetPickingList method. When omitted, the system automatically assigns the asset to the first unpicked line item matching the asset's SKU. When provided, bypasses automatic selection and assigns to the specified line item.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.PickAsset",
  "PickingRequestUUID": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001",
  "ToLocationRef": "PACK01"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Asset picked successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid AssetTag"]
}
```

```
{
  "Result": false,
  "Errors": ["Unable to fetch asset [MP000001]."]
}
```

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

Notes:

- Records the asset as picked and moves it to the specified packing location
- The asset is assigned to a line item on the picking list matching its SKU
- If PickingRequestItemId is provided, the asset is assigned to that specific line item
- Asset tags are case insensitive and will be converted to uppercase
- Fails if the associated sales order has been cancelled

Fulfilment.UndoPickAsset

Reverses a previously picked asset, removing it from the picked contents.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.UndoPickAsset",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.UndoPickAsset"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*
AssetTag	string	Yes	The asset tag to undo (case insensitive, will be converted to uppercase)

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.UndoPickAsset",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Asset unpicked successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to undo pick item."]
}
```

Notes:

- Reverses the pick action and returns the asset to its previous location
- Clears the PickedAssetTag field on the picking list line item
- Only works for requests in PENDING or PICKING status

Fulfilment.CompletePicking

Completes the picking process for a request, transitioning it to the PICKED status.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.CompletePicking",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AutoPackOverride": false,
  "UserNumber": "12345"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.CompletePicking"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*
AutoPackOverride	boolean	No	When true, forces automatic packing of the request upon completion of picking. This bypasses the manual packing stage and automatically packs all picked items. When omitted or false, the request proceeds to the normal packing workflow.
UserNumber	integer	No	The user number to record as having completed picking. When omitted, uses the current session user.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.CompletePicking",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
```

```
"Result": true,
"Messages": ["Picking completed successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to complete picking."]
}
```

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

Notes:

- Marks the picking process as complete and transitions the request to PICKED status
- At least one item must be picked before completion is allowed
- Use AutoPackOverride to force automatic packing, bypassing the manual packing stage entirely
- Only works for requests in PICKING status
- Fails if the associated sales order has been cancelled

Packing Endpoints

Fulfilment.GetPackingList

Retrieves the packing list for a completed picking request.

Scope Required: read

Request:

```
{
  "RequestType": "Fulfilment.GetPackingList",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.GetPackingList"

Parameter	Type	Required	Description
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetPackingList",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "AssetTag": "MP000001",
      "Sku": "PROD-001",
      "ItemDescription": "Example Product",
      "Packed": false,
      "FromLocation": "PACK01",
      "ToLocation": ""
    }
  ]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Unable to fetch picking request."]
}
```

Notes:

- Returns all picked items that need to be packed
 - The Packed field indicates whether the item has already been packed
 - FromLocation shows where the item is currently (typically the packing station)
 - ToLocation shows the destination once packed (the parcel/pallet reference)
-

Fulfilment.StartPacking

Starts the packing process for a picking request that has completed picking.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.StartPacking",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "UserNumber": "12345"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.StartPacking"
PickingRequestUid	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*
UserNumber	integer	No	The user number of the packer. When omitted, uses the current session user. When provided, assigns the specified user as the packer.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.StartPacking",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "Messages": ["Okay, we're ready to start packing."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to start packing."]
}
```

Notes:

- This function tells the system we have started packing the request
 - The method timestamps the request and updates its status to PACKING
 - Only works for requests in PICKED status
-

Fulfilment.RestartPacking

Resets the packing progress for a picking request, clearing all packed items.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.RestartPacking",
  "PickingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.RestartPacking"
PickingRequestId	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.RestartPacking",
  "PickingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Okay, we've reset the packing list."]
}
```

Response (Error):

```
{
```

```
"Result": false,
"Errors": ["The picking request is of the wrong status to reset packing."]
}
```

Notes:

- Clears all previously packed items and resets the packing list
- Returns the request to PICKED status ready to start packing again
- Only works for requests in PICKED or PACKING status

Fulfilment.PackAsset

Records an asset as packed, moving it to the specified location (typically a shipping container or box).

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.PackAsset",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001",
  "ToLocationRef": "BOX001",
  "PalletParcelNumber": "PAL001"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.PackAsset"
PickingRequestUid	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*
AssetTag	string	Yes	The asset tag to pack (case insensitive, will be converted to uppercase)
ToLocationRef	string	Yes	The destination location reference (typically a box or container)
PalletParcelNumber	string	Yes	The pallet or parcel reference number to assign this asset to. *Note: This groups items together for shipping purposes.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.PackAsset",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001",
  "ToLocationRef": "BOX001",
  "PalletParcelNumber": "PAL001"
}
```

```
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Asset packed successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Unable to fetch asset [MP000001]."]
}
```

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

Notes:

- Records the asset as packed and moves it to the specified shipping location
- The PalletParcelNumber groups items together for shipping (e.g., all items on the same pallet)
- Only works for assets that have been picked on this picking request
- Asset tags are case insensitive and will be converted to uppercase
- Fails if the associated sales order has been cancelled

Fulfilment.UndoPackAsset

Reverses a previously packed asset, removing it from the packed contents.

Scope Required: `write`

Request:

```
{
  "RequestType": "Fulfilment.UndoPackAsset",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.UndoPackAsset"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*
AssetTag	string	Yes	The asset tag to undo (case insensitive, will be converted to uppercase)

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.UndoPackAsset",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTag": "MP000001"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Asset unpacked successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to undo pack item."]
}
```

Notes:

- Reverses the pack action and returns the asset to its previous location (typically the packing station)
- Clears the pallet/parcel assignment for this asset
- Only works for requests in PACKING status

Fulfilment.CompletePacking

Completes the packing process for a request, transitioning it to the PACKED status.

Scope Required: write

Request:

```
{
  "RequestType": "Fulfilment.CompletePacking",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "UserNumber": "12345"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.CompletePacking"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*
UserNumber	integer	No	The user number to record as having completed packing. When omitted, uses the current session user.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.CompletePacking",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Packing completed successfully."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["The picking request is of the wrong status to complete packing."]
}
```

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

Notes:

- Marks the packing process as complete and transitions the request to PACKED status
- All items must be packed before completion is allowed
- Only works for requests in PACKING status
- Fails if the associated sales order has been cancelled

Courier Booking Endpoints

Fulfilment.BookCourier

Books a courier for a packed picking request, creating a dispatch note and generating a courier label.

Scope Required: `write`

Request:

```
{
  "RequestType": "Fulfilment.BookCourier",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "CourierKey": "Amazon",
  "CourierServiceKey": "AMAZON",
  "CollectionDate": "2025-12-15",
  "CollectionTime": "17:00",
  "CarriageCost": 12.50,
  "Reference": "ORD-12345",
  "Reference2": "SHOPIFY",
  "TrackingUrl": "https://tracking.dpd.de/status/en_GB/parcel/01234567890123"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.BookCourier"
PickingRequestUid	string	Yes	The 32 character UUID of the picking request. *Note: Uid obtained from Fulfilment.GetPickingRequests method.*
CourierKey	string	Yes	The courier identifier key. *Note: Obtain this value from the Couriers.GetCourierList endpoint.*
CourierServiceKey	string	Yes	The courier service identifier key. *Note: Obtain this value from the Couriers.GetCourierList endpoint.*
CollectionDate	string	Yes	The collection date in YYYY-MM-DD format
CollectionTime	string	Yes	The collection time in HH:MM format
CarriageCost	number	No	The courier carriage cost. Defaults to 0.00 if not provided.
TrackingRef	string	No	A tracking reference if known in advance. If omitted, the courier may generate one.
TrackingUrl	string	No	A full tracking URL for the shipment. If provided, this URL is stored and used directly (e.g. when notifying marketplaces). If omitted, a tracking URL may be generated from the TrackingRef.
Reference	string	No	Primary reference (typically the OrderRef or ReturnRef)

Parameter	Type	Required	Description
Reference2	string	No	Secondary reference (typically the SalesPlatform)
DateDeliveryEstimate	string	No	Estimated delivery date
IncoTerms	string	No	Incoterms for international shipments (e.g. DDP, DAP, EXW)

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.BookCourier",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "CourierKey": "Amazon",
  "CourierServiceKey": "AMAZON",
  "CollectionDate": "2025-12-15",
  "CollectionTime": "17:00"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "Messages": ["Courier booked successfully."],
  "TrackingRef": "TRK123456789",
  "TrackingUrl": "https://tracking.dpd.de/status/en_GB/parcel/01234567890123",
  "CourierLabelFileAssetId": "r5xVEapi3zu8tZkRqACyMB",
  "CommercialInvoicePdfUrl":
    "https://macstore.mpx.one/reports/commercial-invoice/pdf?UIId=a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Note: `CommercialInvoicePdfUrl` is only included for international shipments where a Commercial Invoice exists. Domestic shipments will not include this field.

Response (Error - Invalid PickingRequestUid):

```
{
  "Result": false,
  "Errors": ["Invalid PickingRequestUid."]
}
```

Response (Error - Missing Courier):

```
{
  "Result": false,
  "Errors": ["Please select a courier service."]
}
```


Response (Error - Missing Collection DateTime):

```
{
  "Result": false,
  "Errors": ["Please enter the collection date and time."]
}
```

Response (Error - Order Cancelled):

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

Notes:

- The picking request should be in PACKED status before booking a courier (after completing both picking and packing)
 - The `CourierKey` and `CourierServiceKey` values must be obtained from the `Couriers.GetCourierList` endpoint in the Couriers API (see GnomeCouriersApi documentation)
 - On success, a draft dispatch note is created and the picking request status is updated to "AWAITING COURIER"
 - The `TrackingRef` is returned if the courier integration generates a tracking reference
 - The `CourierLabelFileAssetId` is returned if the courier integration generates a label, and can be used to retrieve the courier label for printing
 - Fails if the associated sales order has been cancelled
-

Dispatch Endpoints

Fulfilment.CompleteDispatch

Completes the dispatch for a picking request, finalising stock movements, updating the sales order status and marking the dispatch note as sent.

Scope Required: `write`

Request:

```
{
  "RequestType": "Fulfilment.CompleteDispatch",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.CompleteDispatch"
PickingRequestUId	string	Yes	The 32 character UUID of the picking request. *Note: UId obtained from Fulfilment.GetPickingRequests method.*

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.CompleteDispatch",
  "PickingRequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "Messages": ["Dispatch completed successfully."],
  "CommercialInvoicePdfUrl":
  "https://macstore.mpx.one/reports/commercial-invoice/pdf?UId=a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Note: `CommercialInvoicePdfUrl` is only included for international shipments where a Commercial Invoice exists. Domestic shipments will not include this field.

Response (Error - Invalid PickingRequestUId):

```
{
  "Result": false,
  "Errors": ["Invalid PickingRequestUId."]
}
```

Response (Error - Wrong Status):

```
{
  "Result": false,
  "Errors": ["Could not find the picking request or it is of the wrong status."]
}
```

Response (Error - Order Cancelled):

```
{
  "Result": false,
  "Errors": ["Cannot complete this action for a picking request linked to a cancelled sales order."]
}
```

```
}
```

Notes:

- The picking request must be in AWAITING COURIER status (after Fulfilment.BookCourier)
- Updates picking request status to COMPLETE
- Sets the invoice tax point to the current date (if an invoice exists)
- Finalises the dispatch note (sets DateDispatched and clears Draft flag)
- Updates the sales order status to COMPLETE or AWAITING CONCLUSION (for partial fulfilment)
- Processes all stock movements for packed items
- Logs all stock movements to the stock journal
- Fails if the associated sales order has been cancelled

Commercial Invoice Endpoints

Fulfilment.GetCommercialInvoice

Retrieves the Commercial Invoice details and PDF URL for a picking request. Used for cross-border shipments where customs documentation is required.

Scope Required: `read`

Request:

```
{
  "RequestType": "Fulfilment.GetCommercialInvoice",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Fulfilment.GetCommercialInvoice"
PickingRequestUid	string	Conditional	The 32 character UUID of the picking request. *Note: At least one of PickingRequestUid or CiRef must be provided.*
CiRef	string	Conditional	The Commercial Invoice reference (e.g. "CI-000001"). *Note: At least one of PickingRequestUid or CiRef must be provided.*

Example (by PickingRequestUid):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetCommercialInvoice",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Example (by CiRef):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Fulfilment.GetCommercialInvoice",
  "CiRef": "CI-000001"
}'
```

Response (Success):

```
{
  "Result": true,
  "Errors": [],
  "CommercialInvoicePdfUrl":
  "https://macstore.mpx.one/reports/commercial-invoice/pdf?UIId=a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "CiRef": "CI-000001",
  "Status": "ACTIVE",
  "InvoiceDate": "20251215120000"
}
```

Response (Error - No identifier provided):

```
{
  "Result": false,
  "Errors": ["Please provide PickingRequestUIId or CiRef."]
}
```

Response (Error - Not found):

```
{
  "Result": false,
  "Errors": ["Commercial Invoice not found."]
}
```

Response (Error - Picking Request not found):

```
{
  "Result": false,
  "Errors": ["Picking Request not found."]
}
```

Notes:

- Returns the Commercial Invoice PDF URL and key metadata for a given picking request or CI reference
 - Only returns non-voided Commercial Invoices
 - The CommercialInvoicePdfUrl can be accessed directly without authentication (the 32-char Uid acts as the access token)
 - Not all picking requests will have a Commercial Invoice; they are only generated for international shipments
-

Status Flow

The picking request follows this status flow:

```
PENDING -> PICKING -> PICKED -> PACKING -> PACKED -> AWAITING COURIER -> COMPLETE
```

- **PENDING:** Initial state, awaiting picking to start
 - **PICKING:** Picking in progress, items are being collected from warehouse locations
 - **PICKED:** All items picked, awaiting packing to start
 - **PACKING:** Packing in progress, items are being placed into parcels/pallets
 - **PACKED:** All items packed, ready for courier booking
 - **AWAITING COURIER:** Courier booked, dispatch note created, awaiting collection
 - **COMPLETE:** Order fulfilled and dispatched
-

Inventory

GnomeInventoryApi

Overview

The Inventory API provides endpoints for managing warehouse inventory, including retrieving asset information, listing stock locations and moving assets between locations.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type`: `application/json`

Base URL

```
POST https://macstore.mpx.one/postbox
```

Endpoints

Inventory.GetAsset

Retrieves detailed information about a specific asset by its asset tag, serial number or IMEI.

Scope Required: read

Request:

```
{
  "RequestType": "Inventory.GetAsset",
  "AssetTag": "MP000001",
  "SerialNumber": "SN123456789",
  "Imei": "359876543210123"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Inventory.GetAsset"
AssetTag	string	Optional*	The asset tag to look up (case insensitive, will be converted to uppercase)
SerialNumber	string	Optional*	The serial number to look up
Imei	string	Optional*	The IMEI to look up (searches both Imei and Imei2 fields)

*At least one of AssetTag, SerialNumber or Imei is required. If multiple are provided, the search uses OR logic.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Inventory.GetAsset",
  "AssetTag": "MP000001"
}'
```

Response (Success):

```
{
  "Result": true,
  "Payload": {
    "SqlId": "123",
    "AssetTag": "MP000001",
    "Sku": "PROD-001",
    "LocationRef": "A01",
    "Product": {
      "SqlId": "456",
      "Sku": "PROD-001",
      "ProductName": "Example Product"
    }
  }
}
```

```
}  
}  
}
```

Response (Success with LastReceivedEvent):

When the asset has a RECEIVED event, the response includes the date received. If the asset was received via a Purchase Order, additional supplier provenance information is included:

```
{  
  "Result": true,  
  "Payload": {  
    "SqlId": "123",  
    "AssetTag": "MP000001",  
    "Sku": "PROD-001",  
    "LocationRef": "A01",  
    "Product": {  
      "SqlId": "456",  
      "Sku": "PROD-001",  
      "ProductName": "Example Product"  
    },  
    "LastReceivedEvent": {  
      "DateReceived": "21-11-2025",  
      "PurchaseOrder": {  
        "PoRef": "PO-1234-12345",  
        "AccountNumber": "12345",  
        "SupplierName": "Daves Account Name"  
      }  
    }  
  }  
}
```

Notes:

- `LastReceivedEvent` is present when the asset has any RECEIVED event in the Stock Journal
- `DateReceived` is always included when `LastReceivedEvent` is present
- `PurchaseOrder` is only included when the last RECEIVED event was linked to a Purchase Order
- `SupplierName` is the supplier billing company name recorded at the time of PO creation

Response (Error):

```
{  
  "Result": false,  
  "Errors": ["At least one of AssetTag, SerialNumber or Imei is required."]  
}
```

```
{  
  "Result": false,  
  "Errors": ["Unable to find asset."]  
}
```

Inventory.GetStockLocations

Retrieves a list of all warehouse stock locations, ordered by core locations first then alphabetically by full location name.

Scope Required: read

Request:

```
{
  "RequestType": "Inventory.GetStockLocations"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Inventory.GetStockLocations"

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Inventory.GetStockLocations"
}'
```

Response (Success):

```
{
  "Result": true,
  "Payload": [
    {
      "SqlId": "1",
      "Ref": "A01",
      "FullLocation": "Aisle A, Bay 01",
      "Core": "1"
    },
    {
      "SqlId": "2",
      "Ref": "A02",
      "FullLocation": "Aisle A, Bay 02",
      "Core": "1"
    }
  ]
}
```

Response (Error):


```
{
  "Result": false,
  "Errors": ["Unable to fetch warehouse locations"]
}
```

Inventory.GetStockLocationContents

Retrieves the contents of a specific stock location. Can return either summarised or itemised results.

Scope Required: `read`

Request:

```
{
  "RequestType": "Inventory.GetStockLocationContents",
  "LocationRef": "A01",
  "Itemised": false
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Inventory.GetStockLocationContents"
LocationRef	string	Yes	The location reference code (case insensitive, will be converted to uppercase)
Itemised	boolean	No	Default: false. When omitted or false, returns a summary of stock at the given location grouped by Sku, Status and Location. When true, returns a full detailed breakdown of individual assets within the location.

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Inventory.GetStockLocationContents",
  "LocationRef": "A01",
  "Itemised": false
}'
```

Response (Success - Summary):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
```

```
        "Sku": "PROD-001",
        "Qty": "5"
    }
]
}
```

Response (Success - Itemised):

When `Itemised: true`:

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "AssetTag": "MP000001",
      "Sku": "PROD-001"
    },
    {
      "AssetTag": "MP000002",
      "Sku": "PROD-001"
    }
  ]
}
```

Response (Empty Location):

```
{
  "Result": true,
  "Messages": ["Nothing in this location."],
  "Payload": []
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Missing Location Ref."]
}
```

```
{
  "Result": false,
  "Errors": ["Invalid location."]
}
```

Notes:

- Special locations (Offsite and Assigned) cannot be queried via this endpoint.

Inventory.MoveAsset

Moves an asset from its current location to a new stock location, optionally updating its status.

Scope Required: `write`

Request:

```
{
  "RequestType": "Inventory.MoveAsset",
  "AssetTag": "MP0000001",
  "ToLocationRef": "B01",
  "ToStatus": "READY FOR SALE"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "Inventory.MoveAsset"
AssetTag	string	Yes	The asset tag of the item to move
ToLocationRef	string	Yes	The destination location reference code
ToStatus	string	No	Optional status to set on the asset after moving (e.g., "READY FOR SALE")

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "Inventory.MoveAsset",
  "AssetTag": "MP0000001",
  "ToLocationRef": "B01",
  "ToStatus": "READY FOR SALE"
}'
```

Response (Success):

```
{
  "Result": true,
  "Payload": {
    "AssetTag": "MP0000001",
    "FromLocation": "A01",
    "ToLocation": "B01"
  }
}
```

```
}  
  
}
```

Response (Error):

```
{  
  "Result": false,  
  "Errors": ["Asset not found"]  
}
```

```
{  
  "Result": false,  
  "Errors": ["Invalid destination location"]  
}
```

Sales

GnomeSalesApi API

Overview

The GnomeSalesApi provides read access to sales orders. It lets authenticated API consumers retrieve orders with flexible filtering by status, date range, account, platform, external reference and more. Each order in the response is enriched with its line items.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type: application/json`

Base URL

```
POST https://macstore.mpx.one/postbox
```

Endpoints

Sales.GetSalesOrders

Retrieves a list of sales orders matching the supplied filter criteria. Each order is returned with its associated line items nested in an `Items` array.

Scope Required: `read`

Request:

```
{
  "RequestType": "Sales.GetSalesOrders",
  "OrderRef": "ORD-0001",
  "Status": "PENDING",
  "AccountNumber": "ACC001",
  "DateFrom": "20250101000000",
  "DateTo": "20251231235959",
  "SalesPlatform": "WEB",
  "ExternalRef": "EXT-ABC123",
  "RaisedByUserNumber": "42",
  "Limit": 100
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be <code>"Sales.GetSalesOrders"</code>
OrderRef	string	No	Filter to a specific order reference. When omitted, all orders are returned subject to other filters.
Status	string	No	Filter by one or more statuses, comma-separated (e.g. <code>"PENDING"</code> or <code>"PENDING, PROCESSING"</code>). When omitted, orders of all statuses are returned.
AccountNumber	string	No	Filter to orders belonging to a specific account number. When omitted, orders across all accounts are returned (subject to the facility filter applied from the auth token's account).
DateFrom	string	No	Return only orders created on or after this date. Format: <code>YmdHis</code> (e.g. <code>"20250101000000"</code>). When omitted, no lower date boundary is applied.
DateTo	string	No	Return only orders created on or before this date. Format: <code>YmdHis</code> (e.g. <code>"20251231235959"</code>). When omitted, no upper date boundary is applied.
SalesPlatform	string	No	Filter by the sales platform the order originated from (e.g. <code>"WEB"</code> , <code>"PHONE"</code>). When omitted, orders from all platforms are returned.
ExternalRef	string	No	Filter by an external reference number (e.g. a third-party order ID). When omitted, no external reference filter is applied.
RaisedByUserNumber	string	No	Filter to orders raised by a specific user, identified by their user number. When omitted, orders raised by any user are returned.
Limit	integer	No	Maximum number of orders to return. Defaults to the configured <code>MaxLimit</code> (see <code>Config.xml</code>). Cannot exceed <code>MaxLimit</code> . When a value below <code>1</code> is supplied, it defaults back to <code>MaxLimit</code> .

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
```

```
--header 'api-token: [token]' \  
--header 'Content-Type: application/json' \  
--data '{  
  "RequestType": "Sales.GetSalesOrders",  
  "Status": "PENDING",  
  "Limit": 50  
}'
```

Response (Success):

```
{  
  "Result": true,  
  "Messages": [],  
  "Payload": [  
    {  
      "SqlId": "1",  
      "DateCreated": "20250115093000",  
      "DateUpdated": "20250115094500",  
      "DateAccepted": "20250115094500",  
      "OrderRef": "ORD-0001",  
      "SalesPlatform": "WEB",  
      "FacilityCode": "FAC01",  
      "AccountNumber": "ACC001",  
      "AccountName": "Acme Ltd",  
      "ExternalRef": "EXT-ABC123",  
      "Status": "PENDING",  
      "GoodsTotal": "99.99",  
      "CarriageTotal": "5.99",  
      "Total": "105.98",  
      "GoodsTax": "16.67",  
      "CarriageTax": "1.00",  
      "TaxScheme": "UK_VAT",  
      "Memo": "Handle with care",  
      "Note": "Customer note",  
      "DeliveryAddressLine1": "1 Example Street",  
      "DeliveryAddressLine2": "",  
      "DeliveryAddressLine3": "",  
      "DeliveryTownCity": "London",  
      "DeliveryCounty": "Greater London",  
      "DeliveryPostcode": "EC1A 1BB",  
      "DeliveryCountry": "GB",  
      "RaisedByUserNumber": "42",  
      "RaisedByUserName": "Jane Smith",  
      "Items": [  
        {  
          "UIId": "abc123def456abc123def456abc12345",  
          "Sku": "SKU-001",  
          "AssetTag": "ASSET-001",  
          "ItemDescription": "Laptop",  
          "ProductOptions": "",  
          "UnitQty": "1",  
          "UnitPrice": "99.99",  
          "UnitListPrice": "119.99",  
          "UnitDiscount": "20.00",  
          "TaxRate": "20",  
          "Memo": ""  
        }  
      ]  
    }  
  ]  
}
```

```
]
}
```

Response (No matching orders):

```
{
  "Result": true,
  "Messages": ["There are no sales orders matching your criteria."],
  "Payload": []
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Error message"]
}
```

Notes:

- The `AccountNumber` on the auth token is used to look up the facilities associated with that account via `GnomeFulfilmentFacilities`. If facilities are mapped, results are restricted to orders belonging to those facility codes. If no facilities are mapped, all orders are returned (unrestricted).
 - The `AccountNumber` request parameter is an additional filter on top of the facility restriction. It filters by the `AccountNumber` on the order itself, which may differ from the token's account in multi-account environments.
 - The `Status` filter accepts a comma-separated list, allowing you to retrieve orders in multiple statuses in a single request (e.g. "PENDING,PROCESSING,DISPATCHED").
 - `DateFrom` and `DateTo` filter against `DateCreated` using the MPX `YmdHis` format (YYYYMMDDHHmmss). Ensure dates are zero-padded (e.g. "20250101000000" not "2025-01-01").
 - Results are ordered by `DateCreated` descending, so the most recently created orders appear first.
 - The `Limit` parameter caps results at the `MaxLimit` value configured in `Config.xml` (default 500). To paginate beyond this, use `DateTo` to step back through older records.
 - Each order in the payload is enriched with a nested `Items` array containing its line items from the `GnomeSalesItems` table.
-
-

Stock Transfers

StockTransfersApi

Overview

The Stock Transfers API provides endpoints for managing stock transfers between accounts and locations. This API supports retrieving transfer information, marking transfers as received or processed and creating reverse transfers.

Authentication

All endpoints require authentication via the Postbox system:

- Header: `api-token` - Your API token
- Header: `Content-Type: application/json`

Note: The `AccountNumber` parameter is automatically injected from the authenticated user's account for all endpoints. You don't need to provide it in your request.

Base URL

POST `https://macstore.mpx.one/postbox`

Endpoints

StockTransfers.GetTransfers

Retrieves a list of stock transfers for the authenticated account, optionally filtered by status.

Scope Required: `read`

Request:

```
{
  "RequestType": "StockTransfers.GetTransfers",
  "Statuses": "PENDING,DISPATCHED",
  "ExternalRef": "EXT-12345",
  "PickingRequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Note: All filter parameters are optional. You can use any combination of filters.

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.GetTransfers"
Statuses	string	No	Comma separated list of statuses to filter by. *Note: Valid statuses are: PENDING, DISPATCHED.*

Parameter	Type	Required	Description
PickingRequestUId	string	No	Filter by specific transfer UId (32 character identifier). *Note: When provided, returns only the transfer matching this exact UId. Invalid length values are ignored.*
ExternalRef	string	No	Filter by external reference. *Note: Returns transfers matching this exact external reference.*

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example (Filter by status):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.GetTransfers",
  "Statuses": "PENDING,DISPATCHED"
}'
```

Example (Filter by external reference):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.GetTransfers",
  "ExternalRef": "EXT-12345"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "SqlId": "123",
      "UId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
      "AccountNumber": "12345",
      "TransferStatus": "PENDING",
      "DateCreated": "20251201120000"
    }
  ]
}
```

Response (Empty):

```
{
  "Result": true,
  "Messages": ["There are no stock transfers."],
  "Payload": []
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid AccountNumber"]
}
```

Notes:

- Returns all stock transfers for the authenticated account matching the specified status filters
 - If no Statuses parameter is provided, returns all transfers regardless of status
 - PENDING status indicates transfers that have been created but not yet dispatched
 - DISPATCHED status indicates transfers that have been sent and are awaiting receipt
-

StockTransfers.GetTransferManifest

Retrieves the manifest (list of items) for a specific stock transfer.

Scope Required: read

Request:

```
{
  "RequestType": "StockTransfers.GetTransferManifest",
  "RequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.GetTransferManifest"
RequestUId	string	Yes	The 32 character UUID of the stock transfer. *Note: UId obtained from StockTransfers.GetTransfers method.*

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.GetTransferManifest",
  "RequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": [],
  "Payload": [
    {
      "AssetTag": "MP000001",
      "Sku": "PROD-001",
      "ItemDescription": "Example Product"
    },
    {
      "AssetTag": "MP000002",
      "Sku": "PROD-001",
      "ItemDescription": "Example Product"
    }
  ]
}
```

Response (Empty):

```
{
  "Result": true,
  "Messages": ["There are no manifest items for this transfer."],
  "Payload": []
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid RequestUid. Must be 32 character UUID."]
}
```

Notes:

- Returns all items included in the specified stock transfer
- The manifest shows what was originally dispatched in the transfer
- Use this to verify received items against the expected manifest

StockTransfers.GetDispatchNote

Retrieves the dispatch note for a specific stock transfer.

Scope Required: read

Request:

```
{
  "RequestType": "StockTransfers.GetDispatchNote",
  "UId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.GetDispatchNote"
UId	string	Yes	The 32 character UUID of the stock transfer. *Note: UId obtained from StockTransfers.GetTransfers method.*

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.GetDispatchNote",
  "UId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Payload": {
    "DispatchRef": "DN-00123",
    "AccountNumber": "12345",
    "AccountName": "Example Ltd",
    "FacilityCode": "WH01",
    "DateCreated": "20251201120000",
    "DateDispatched": "20251202100000",
    "CourierKey": "DPD",
    "CourierServiceKey": "NEXT_DAY",
    "CourierLabelFileAssetId": "asset_abc123",
  }
}
```

```
    "TrackingRef": "DPD123456789",
    "ExternalRef": "EXT-001",
    "Reference": "REF-001",
    "Reference2": "REF-002"
  }
}
```

Response (Error - Invalid UId):

```
{
  "Result": false,
  "Errors": ["Invalid UId. Must be 32 character UUID."]
}
```

Response (Error - Not a transfer):

```
{
  "Result": false,
  "Errors": ["This is not a transfer request."]
}
```

Response (Error - No dispatch note):

```
{
  "Result": false,
  "Errors": ["No dispatch note found for this transfer."]
}
```

Notes:

- Returns dispatch note details for the specified stock transfer
- Only works for picking requests with Purpose = 'Transfer'
- Returns an error if the transfer does not yet have an associated dispatch note
- Courier information (TrackingRef, CourierKey, etc.) is sourced from courier shipment data when available, falling back to dispatch note data

StockTransfers.Received

Marks assets in a transfer as received. Can process all items or specific assets by tag.

Scope Required: write

Request:

```
{
```

```
"RequestType": "StockTransfers.Received",
"RequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
"AssetTags": ["MP000001", "MP000002"]

}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.Received"
RequestId	string	Yes	The 32 character UUID of the stock transfer. *Note: Uid obtained from StockTransfers.GetTransfers method.*
AssetTags	array	No	Array of asset tags to mark as received. When omitted, all items in the transfer are marked as received. When provided, only the specified assets are marked as received.

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example (Receive specific items):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.Received",
  "RequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTags": ["MP000001", "MP000002"]
}'
```

Example (Receive all items):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.Received",
  "RequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Transfer items marked as received."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid RequestUId. Must be 32 character UUID."]
}
```

```
{
  "Result": false,
  "Errors": ["AssetTags must be an array."]
}
```

```
{
  "Result": false,
  "Errors": ["Unable to fetch the picking request."]
}
```

Notes:

- Marks the specified items as received at the destination
- If AssetTags is omitted, all items in the transfer are marked as received
- This updates the transfer status and records receipt timestamp
- Typically used when goods arrive and need to be acknowledged

StockTransfers.Processed

Marks assets in a transfer as processed (fully completed). Can process all items or specific assets by tag.

Scope Required: write

Request:

```
{
  "RequestType": "StockTransfers.Processed",
  "RequestUId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTags": ["MP000001", "MP000002"]
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.Processed"
RequestUId	string	Yes	The 32 character UUID of the stock transfer. *Note: UId obtained from StockTransfers.GetTransfers method.*

Parameter	Type	Required	Description
AssetTags	array	No	Array of asset tags to mark as processed. When omitted, all items in the transfer are marked as processed. When provided, only the specified assets are marked as processed.

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example (Process specific items):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.Processed",
  "RequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "AssetTags": ["MP000001", "MP000002"]
}'
```

Example (Process all items):

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.Processed",
  "RequestUid": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6"
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Transfer items marked as processed."]
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid RequestUid. Must be 32 character UUID."]
}
```

```
{
  "Result": false,
```



```
"Errors": ["AssetTags must be an array."]  
}
```

Notes:

- Marks the specified items as fully processed into the destination inventory
- This is the final step in the transfer workflow
- Items marked as processed are now fully integrated into the receiving location's stock
- Use this after items have been physically put away and verified

StockTransfers.ReverseTransfer

Creates a reverse transfer to return items back. This is used when items need to be sent back from the destination to the origin.

Scope Required: write

Request:

```
{  
  "RequestType": "StockTransfers.ReverseTransfer",  
  "OriginatingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",  
  "ExternalRef": "RET-2024-001",  
  "Items": [  
    {"AssetTag": "MP000001"},  
    {"AssetTag": "MP000002"}  
  ]  
}
```

Parameters:

Parameter	Type	Required	Description
RequestType	string	Yes	Must be "StockTransfers.ReverseTransfer"
OriginatingRequestId	string	Yes	The 32 character UUID of the original outbound transfer. *Note: UId obtained from StockTransfers.GetTransfers method.*
ExternalRef	string	No	External reference for tracking (e.g., return authorisation number)
Items	array	Yes	Array of items to include in the reverse transfer. *Note: Each item must be an object with an AssetTag property, formatted as: [{"AssetTag": "MP000001"}, {"AssetTag": "MP000002"}]*

Auto-injected Parameters:

Parameter	Description
AccountNumber	Automatically injected from the authenticated user's account

Example:

```
curl --location 'https://macstore.mpx.one/postbox' \
--header 'api-token: [token]' \
--header 'Content-Type: application/json' \
--data '{
  "RequestType": "StockTransfers.ReverseTransfer",
  "OriginatingRequestId": "a1b2c3d4e5f6g7h8i9j0k1l2m3n4o5p6",
  "ExternalRef": "RET-2024-001",
  "Items": [
    {"AssetTag": "MP000001"},
    {"AssetTag": "MP000002"}
  ]
}'
```

Response (Success):

```
{
  "Result": true,
  "Messages": ["Reverse transfer created successfully."],
  "Payload": {
    "RequestId": "f6e5d4c3b2a1098765432109876543210"
  }
}
```

Response (Error):

```
{
  "Result": false,
  "Errors": ["Invalid OriginatingRequestId. Must be 32 character UUID."]
}
```

```
{
  "Result": false,
  "Errors": ["Items array is required"]
}
```

```
{
  "Result": false,
  "Errors": ["Unable to fetch account details."]
}
```

Notes:

- Creates a new transfer request in the opposite direction to the original
- The new transfer is linked to the original via OriginatingRequestId
- Only items that were part of the original transfer can be included
- The returned RequestId can be used to track the reverse transfer

- Useful for returns, refurbishment or when items were sent incorrectly
-

Status Flow

Stock transfers follow this status flow:

PENDING -> DISPATCHED

- **PENDING:** Initial state, transfer has been created but items have not yet been dispatched from the origin
- **DISPATCHED:** Items have been dispatched and are in transit or awaiting processing at the destination

Note: Transfers may have additional internal statuses for tracking receipt and processing, but the primary statuses visible via the API are PENDING and DISPATCHED.