

All 🕶

Part # / Keyword





Q



Home > NEWEST Products > New by Manufacturer > Anderson Power Products > SB®50 Connectors - APP

NEWEST PRODUCTS

∢ Back to Anderson Power Products



Anderson Power Products SB®50 Connectors



View Details

More About Anderson Power Products

View Datasheet

Anderson Power Products SB®50 Connectors feature a one-piece plastic housing using stainless steel springs to hold low-resistance contacts in place. These connectors work with wire contacts up to 6AWG (10mm²) as well as PCB and busbar contacts. The genderless design mates with itself and has a plated through-hole mounting style. Anderson SB®50 Connectors are UL-rated for hot plugging up to 50A while low-resistance silver- or tin-plated copper contacts allow UL-rated currents up to 120A.


FEATURES


- Plated through-hole mounting style
- · Wire, PCB, and busbar contacts
- · Low-resistance silver- or tin-plated copper contacts
- Works with wire sizes from 16AWG (1.5mm²) to 6AWG (13.3mm²)
- UL-rated for hot plugging up to 50A
- Genderless design mates with itself
- · Color-coded mechanical keys
- -20°C to +105°C operating temperature range for standard housings
- -40°C to +105°C operating temperature range for chemical-resistant housings
- 2200V_{AC} dielectric withstanding voltage

ADDITIONAL RESOURCE

SB Connectors Assembly Sheet

DIMENSIONS






LEARN MORE ABOUT

Anderson Power Products E-Mobility Solutions

Designed to bring power, or power and signaling, to and from e-mobility equipment.

Learn More View Products


Published: 2019-07-10 | Updated: 2022-11-29



MOUSER ELECTRONICS®

1000 North Main Street Mansfield, TX 76063 USA

CONNECT WITH US



Sitemap

Copyright ©2023 Mouser Electronics, Inc.

Mouser® and Mouser Electronics® are trademarks of Mouser Electronics, Inc. All other trademarks are the property of their respective owners. Corporate headquarters and logistics center in Mansfield, Texas USA.