

# Energy Applications of Piezoelectric Materials: Study, Analysis and Experimental Proposal

Jorge Vicente González González (Stud. Eng.)

Faculty of Physics, University of Havana

ARES Collaboration Project

Advisors: Dr. Ernesto Altshuler, Eng. Alex Manuel Rivera Rivera, Lic. Daniela Martínez Ortíz

November 12, 2025

## Abstract

Piezoelectric materials constitute a viable alternative for harvesting ambient mechanical energy, transforming it into electricity through induced polarization. This work explores their physical, chemical, and electronic fundamentals, their potential as energy generators, advantages and limitations, and a critical review of successful projects worldwide. The document concludes with recommendations oriented towards the experimental design to be developed within the ARES Project.

## Contents

|     |                                                     |   |
|-----|-----------------------------------------------------|---|
| 1   | Introduction                                        | 3 |
| 2   | Basic Concepts on Piezoelectricity                  | 3 |
| 2.1 | Physical-Chemical Basis                             | 3 |
| 2.2 | Electromechanical Coupling and Energy Efficiency    | 3 |
| 2.3 | Electronic Design in Piezoelectric Systems          | 4 |
| 3   | Piezoelectric Materials for Energy Generation       | 4 |
| 3.1 | Physical-Electronic Model                           | 4 |
| 3.2 | Use of Capacitors                                   | 4 |
| 3.3 | Enhanced Behavior Graphs                            | 5 |
| 4   | Contributions, Limitations, and Successful Examples | 6 |
| 4.1 | Contributions of Piezoelectric Systems              | 6 |
| 4.2 | Limitations                                         | 6 |
| 4.3 | Practical Successful Examples                       | 7 |
| 5   | Experimental Prototype Proposal (ARES Project)      | 7 |
| 5.1 | LoRa Data Transmission Comparison (5.1)             | 8 |



# 1 Introduction

The piezoelectric phenomenon offers an efficient pathway for energy harvesting from vibrations, pressures, or impacts, leveraging the induced charge displacements in certain crystalline materials. In a context of growing energy demand and sustainability, the study of these systems enables the development of autonomous solutions for sensors, portable devices, or environmental monitoring systems.

This report analyzes the phenomenon from an interdisciplinary perspective (physics, chemistry, and electronics), also presenting its real-world applications and associated technological  challenges.

## 2 Basic Concepts on Piezoelectricity

Piezoelectricity, discovered by Jacques and Pierre Curie in 1880, manifests when certain crystals generate an electric potential difference under mechanical deformation. At the microscopic level, the effect originates from the lack of symmetry in the crystal lattice, which causes a separation of internal charges.

### 2.1 Physical-Chemical Basis

In the direct effect, a mechanical stress  $T_j$  generates an electric displacement density  $D_i$  according to:

$$D_i = d_{ij} \cdot T_j \quad \text{$$

where  $d_{ij}$  is the piezoelectric coefficient. In the inverse effect, an electric field  $E_i$  causes a mechanical strain  $S_j$ :

$$S_j = d_{ij} \cdot E_i$$

Typical materials include quartz ( $SiO_2$ ), barium titanate ( $BaTiO_3$ ), and PZT ( $Pb[Zr_xTi_{1-x}]O_3$ ). Chemically, these compounds exhibit displacements of metal ions within unit cells, generating permanent electric dipoles.

**Scientific and Technical Expansion** The origin of piezoelectricity lies in the absence of inversion centers within the crystal structure. When the material deforms, the positive and negative charge centers separate, generating a net dipole moment. This effect is reversible and depends on the type of chemical bond, material stiffness, and crystal anisotropy.

At the microscopic level, the crystal structure determines the orientation of the dipoles. Ferroelectric materials, such as PZT or barium titanate, show spontaneous polarization that enhances conversion efficiency. Polymers like PVDF offer flexibility and adaptability, albeit with lower piezoelectric coefficients.

### 2.2 Electromechanical Coupling and Energy Efficiency

The electromechanical coupling coefficient  $k^2$  is defined as the fraction of mechanical energy converted into electrical energy:

$$k^2 = \frac{E_{\text{electrical}}}{E_{\text{mechanical}}} \approx \frac{d_{33}^2}{\epsilon_r s_{33}}$$

where  $s_{33}$  is the material's elasticity and  $\epsilon_r$  the relative dielectric constant. Efficiency depends on the excitation frequency, the design of the charging circuit, and the impedance of the electronic components.

## 2.3 Electronic Design in Piezoelectric Systems

Piezoelectric systems require:

- Signal rectification (usually Schottky diode bridges to minimize voltage loss).
- Temporary storage using capacitors or supercapacitors.
- Voltage regulation via DC-DC converters to power microcontrollers and sensors.

This design enables the implementation of autonomous, low-consumption systems capable of harvesting energy from impacts, vibrations, or periodic movements, optimizing the relationship between available energy and the demand of electronic devices. 

## 3 Piezos for Energy Generation

### 3.1 Physical-Electronic Model

Piezoelectric elements behave as current sources dependent on mechanical stress, modeled by a source  $I_p$ , a capacitor  $C_p$ , and a leakage resistance  $R_p$ :

$$I_p = d_{33} \cdot A \cdot \frac{d\sigma}{dt}, \quad E = \frac{1}{2} C_p V^2$$

The generated voltage can range from 1–100 V, with currents on the order of  $\mu\text{A}$ . For practical applications, full-wave rectifiers and storage capacitors are used to couple the signal to microcontrollers or transmission systems.

**Technical Expansion on Efficiency and Coupling** The system can be modeled using electromechanical coupling, evaluating energy transfer and losses in internal resistance or storage circuits. Optimization includes impedance matching, capacitor selection, and synchronization strategies with the mechanical excitation frequency. This is critical in applications where the harvested energy is limited and required to power autonomous sensors or data transmitters. 

### 3.2 Use of Capacitors

Storage using capacitors in piezoelectric systems allows regulation of the instantaneously generated energy, which is pulsating and irregular in nature. Capacitors accumulate charge during brief impacts and stabilize the voltage, preventing fluctuations that could damage microcontrollers. Furthermore, the choice of appropriate capacitance and dielectric influences conversion efficiency, minimizing losses due to the Joule effect and optimizing the charge/voltage ratio.

In microgenerator applications, capacitors connected to DC-DC converters allow delivering energy to sensors with intermittent consumption, improving system autonomy and enabling temporary storage strategies during periods of low mechanical excitation.

### 3.3 Enhanced Behavior Graphs

Graphs help understand the relationship between applied force, voltage, current, and generated energy:




Figure 1: Generated voltage versus applied force. PZT shows higher sensitivity and efficiency at low forces, indicating its advantage in micro-vibration harvesting.




Figure 2: Induced current in a periodic vibration cycle. The current oscillates with the mechanical excitation frequency, showing the need for rectification and temporary storage.




Figure 3: Input and output energy comparison. Losses are due to internal resistance, parasitic capacitance, and electromechanical coupling efficiency.

## 4 Contributions, Limitations, and Successful Examples

### 4.1 Contributions of Piezoelectric Systems

Piezoelectric systems offer multiple scientific and technological advantages:

- **Clean Energy Transformation:** They convert ambient mechanical energy (vibrations, footsteps, vehicular traffic, waves) into electricity without the need for fossil fuels or polluting emissions [1].
- **Autonomy in Remote Sensors:** Their ability to generate energy locally allows keeping environmental sensors and portable devices operational, reducing dependence on external sources [4].
- **Integration into Infrastructures:** They can be incorporated into pavements, bridges, roads, or biomedical structures, expanding the range of applications in civil engineering and medicine [2, 3, 6].
- **Scalability:** From microgenerators for portable devices to urban or industrial generation systems, adapting to different levels of energy demand [5].
- **Durability and Low Maintenance:** Ceramic piezoelectric materials typically have a long lifespan and require minimal maintenance under controlled conditions, optimizing operational costs.

### 4.2 Limitations

Despite their advantages, significant challenges exist:

- **Low Currents:** The generated energy is insufficient for high-consumption systems, limiting direct charging without storage circuits [4].
- **Variable Voltages:** High voltages combined with very low currents require rectification and regulation to prevent damage to connected electronics.

- **Dependence on Excitation:** Efficiency depends on the frequency, amplitude, and consistency of vibrations; mechanical optimization is crucial.
- **Environmental Sensitivity:** Temperature, humidity, and aging can affect the piezoelectric response.
- **Need for Storage:** For continuous applications, capacitors or supercapacitors are required to regulate the intermittent energy [4, 1].

### 4.3 Practical Successful Examples

Global projects demonstrate the potential of piezoelectrics:

1. **Pavegen Pavements** (airports, stations): Convert pedestrian footsteps into usable energy for lighting and sensors [2].
2. **Tokyo Bridge with PZT sensors:** Structural monitoring and energy capture from vehicular traffic, demonstrating reliability in urban infrastructure [3].
3. **MIT Energy-Harvesting Shoes:** Charge mobile devices using energy from human movement, integrating comfort and energy autonomy [4].
4. **Piezoelectric Roads in South Korea:** Energy generation from vehicular traffic; data shows acceptable efficiency for street lighting and sensors [5].
5. **Conformable Biomedical Devices** (Stanford): Harvest energy from heart, lung, and diaphragm movements, demonstrating the feasibility of flexible piezoelectric systems in biomedicine [6].
6. **Industrial Vibration Sensors:** Autonomous power for monitoring systems in machinery, reducing wiring costs and dependence on the electrical grid.

## 5 Experimental Prototype Proposal (ARES Project)

**Objective** Design a floating platform that possesses an autonomous piezoelectric structure installed on it, capable of powering pH, conductivity, and dissolved oxygen sensors using energy harvested from wave motion, evaluating its ability to complement the main buoy, which is powered by solar energy.

**Scenario and Mechanical Design** A 2 m<sup>2</sup> platform separate from the main buoy is proposed, supporting multiple piezoelectric modules distributed strategically to maximize energy capture. Each piezoelectric is coupled to an articulated piston that translates wave motion into controlled mechanical deformation, optimizing electromechanical efficiency.




Figure 4: The image shows how the mechanism moves both upwards and downwards with the wave motion. On one end, there is a floating buoy in the water, and on the other, a plate that presses against the piezoelectrics with a certain intensity, generating voltage..

### Recommended Sensors and Microcontrollers

- Arduino  Portenta H7: High speed, low consumption, LoRa support and Wi-Fi communication.
- Precision pH, electrical conductivity, and dissolved oxygen sensors.

### Practical Calculations

$$V_{\text{disc}} = \frac{d_{33} \cdot F}{C_p} \approx 0.058 \text{ V}, \quad E_{\text{cycle, total}} \approx 1.02 \times 10^{-8} \text{ J} \quad \text{🗨️}$$

## 5.1 LoRa Data Transmission Comparison (5.1)

Data transmission from the platform is analyzed:

| Transmission Frequency                                                                           | Direct to Land |             | Via Main Buoy |             |
|--------------------------------------------------------------------------------------------------|----------------|-------------|---------------|-------------|
|                                                                                                  | Consumption    | Update Rate | Consumption   | Update Rate |
|  Every minute | High           | Very High   | Medium        | High        |
| Every hour                                                                                       | Medium         | High        | Low           | Medium      |
| Every day                                                                                        | Low            | Low         | Very Low      | Low         |

Table 1: Comparison of LoRa data transmission from the piezoelectric platform.

**Conclusion** Sending data through the main buoy reduces the energy consumption of the platform, at the cost of a slight decrease in update frequency. This method is recommended when seeking to optimize autonomy and reduce energy demand peaks.

### Conclusions and Recommendations

- Piezoelectrics provide sufficient energy to power low-consumption sensors and intermittent communication systems.
- The use of supercapacitors is recommended to store energy and stabilize sensor power supply.



- The distribution and number of piezoelectrics should be adjusted to the local wave pattern to maximize efficiency.
- The platform allows comparative studies on energy generation and consumption of autonomous environmental measurement systems.

## 6 Bibliographic References

### References

- [1] Priya, S., & Inman, D. J. (2009). *Energy Harvesting Technologies*. Springer.
- [2] Pavegen Systems. Available at: <https://www.pavegen.com/>
- [3] Technical Report: Tokyo Bridge Piezoelectric Sensors (2020).
- [4] Paradiso, J. A., & Starner, T. (2005). "Energy scavenging for mobile and wireless electronics." *IEEE Pervasive Computing*, 4(1): 18–27.
- [5] Kim, H. et al. (2017). "Piezoelectric roads for sustainable energy harvesting." *Applied Energy*, 205: 624–633.
- [6] Dagdeviren, C. et al. (2014). "Conformal piezoelectric energy harvesting and storage from motions of the heart, lung, and diaphragm." *PNAS*, 111(5): 1927–1932.

