Semestral Project Announcement

Jiří Filipovič

Fall 2022

Difference of galaxies

Our quest is to implement function which computes similarity of two galaxies

- they are not fixed in space, thus nearly the same galaxies may be rotated, shifted...
- we will compare distances of the same pairs of stars
- to emphasize larger differences, distance differences are squared before summed

Used formula:

diff =
$$\sqrt{\frac{1}{N(N-1)}\sum_{i=1}^{N-1}\sum_{j=i+1}^{N}(d_{ij}^{A}-d_{ij}^{B})^{2}}$$

Wher d_{ij}^A is Euclidean distance of *i*-th star to *j*-th star of galaxy A. Galaxies are defined by Cartesian coordinates of their stars.

Implementation

You will get a framework, which:

- creates input, copies it into GPU memory
- check result of CUDA implementation against non-optimized CPU code
- benchmarks your code

Your work

 you are expected to write CUDA code (kernel and code calling the kernel in file kernel.cu)

Project Rules

Rules for the implementation

- single-precision implementation is OK
- the input size can be changed to an arbitrary number
- performance will be evaluated on 2 000 stars or more
- implementation should run at compute capability 5.0 or greater
- ullet the highest accepted error of the GPU implementation is 1 %
- this is an individual project any form of cooperation is strictly prohibited

The project has three stages:

- the working parallel CUDA implementation: 25p, by Oct 26th (including)
- the efficient CUDA implementation (75,000 mpairs/s on GTX 1070 using 50,000 stars): 25p, by Nov 23rd (including)
- the most efficient implementation that you have: by Dec 5th (including)

The First Stage

The working CUDA implementation

- performance doesn't matter (but your code must be parallelized)
- points will be assigned according to the correctness of your code
- deadline miss penalty: -2 points for each started day of delay
- also try to optimize the code (to save effort for the next deadline)

Compilation: nvcc -03 -use_fast_math -o framework framework.cu