Measuring the Coordination-Collapse Boundary in Cooperative MARL: A Phase Diagram, and How Prospect Theory Moves It

Anonymous Authors
Paper under double-blind review

Abstract

Cooperative multi-agent reinforcement learning (MARL) is known to collapse into a degenerate *lazy-agent* policy when reward centralization falls too low, but this failure has never been characterized as a quantitative object. We treat it as one: we measure the critical centralization w_{crit} at which coordination gives way to collapse—with a pre-registered collapse definition and bootstrap confidence intervals—turning a qualitative failure mode into a measurable phase boundary, the first in deep cooperative MARL. The boundary is an instrument, and our flagship use of it is a behavioral discovery: prospect theory, the best-validated model of human risk preference, hands a cooperative agent *two* components that move the boundary in *opposite* directions—probability-weighting curvature lowers the centralization required to coordinate, while loss aversion raises it. On a multi-echelon supply-chain substrate (1,524 controlled runs), curvature alone ($\alpha{=}\beta{=}0.88$, $\lambda{=}1$) shifts w_{crit} *left* by 0.100 $[0.033, 0.172]$ while loss aversion shifts it *right* by up to 0.166 $[0.135, 0.202]$; a full sweep $\lambda{=}1\ldots7$ rises then saturates and is tracked by a one-parameter, theory-bounded law (RMSE 0.014). A mean-field signal-to-noise account derives the *signs* of both effects *a priori*; the loss-aversion direction then replicates across two further environments (MPE Cooperative Navigation and Level-Based Foraging) and a second algorithm (MAPPO), confirming the prediction, while the absolute boundary and curvature sign remain substrate-specific. A headline consequence is that the boundary is set by a *minority, by network position*: a single *downstream* loss-averse node drives $w_{\mathrm{crit}} = 0.853$—statistically indistinguishable from a fully loss-averse population (0.851)—whereas the same bias placed upstream moves it far less (0.726). Loss aversion thus cascades *upstream* but not down, so a system's centralization requirement is fixed by its most downstream biased participant, not by the mean bias. The boundary doubles as a safety margin: how much more centralization a cooperative system needs once its agents are loss-averse.

Introduction

Cooperative multi-agent reinforcement learning (MARL) has a well-documented failure mode—*coordination collapse*, in which agents abandon cooperation for a degenerate zero-action *lazy-agent* policy (Liu et al., 2023; Shi and Peng, 2023)—but the field describes it only qualitatively. Whether a system collapses is known to depend on its *reward centralization* $w \in [0, 1]$, the fraction of each agent's reward drawn from the team's global outcome rather than its own local one; yet *where*, in w, coordination gives way to collapse has never been measured. This paper makes that boundary a measurable object. We treat collapse the way physics treats a phase boundary—a pre-registered, frozen collapse definition, a logistic estimate of $P(\mathrm{collapse} \mid w)$, and bootstrap confidence intervals on the critical centralization w_{crit}—and so obtain, to our knowledge, the first quantitative phase boundary of coordination collapse in deep cooperative MARL. We use "phase boundary" in the empirical sense—a sharp, metastable threshold whose asymptotic ($T \to \infty$) value is the boundary proper—rather than as a claim of a thermodynamic-limit singularity.

A measured boundary is only as useful as what it lets us discover, and our flagship use of it is behavioral. Bias in a learning agent is usually treated as a single dial—more risk-averse or less. Prospect theory, the best-validated model of human risk preference (Kahneman and Tversky, 1979; Tversky and Kahneman, 1992), says the dial has *two* independent components: the curvature of the value function, and an asymmetric penalty on losses (loss aversion). Measured against our boundary, these two components do not merely differ in magnitude—they push *cooperation itself* in *opposite* directions, and one of them *helps*. We use the boundary to quantify how each component, and the training horizon, move the threshold.

We ground the measurement in automated replenishment for multi-echelon supply chains, a canonical cooperative MARL problem in which agents coordinate ordering decisions across a network under delayed feedback, partial observability, and structurally misaligned local incentives (Oroojlooyjadid et al., 2022; Gijsbrechts et al., 2022). The domain is not incidental. First, its failure modes are economically legible: agents that hoard, under-order, or stop ordering produce the bullwhip effect, stockouts, and cascading losses — collapse here is not an abstract training pathology but a recognisable operational disaster. Second, the domain supplies the mental model this paper formalises: real replenishment decisions are made by planners who demonstrably weigh losses more heavily than equivalent gains, and the agents now being trained to replace or assist them inherit human preference structure by design — through preference-aligned training objectives that are themselves prospect-theoretic in form (Ethayarajh et al., 2024) and through human-in-the-loop deployment (Lalmohammed

et al., 2025). A team of loss-averse decision makers managing a shared pipeline is the real-world ability we are modelling; the question is what happens to *system-level* coordination when that bias is carried by learning agents.

The literature explains coordination collapse without locating it. Liu et al. (2023) formalise the lazy-agent problem and Shi and Peng (2023) relative overgeneralization, both proposing algorithmic mitigations; Weng and Lee (2026) identify representation degradation under decentralised exploration as a mechanism; Akella (2025) show empirically that decentralised reward shaping cannot close the gap to centralised baselines. All of these treat the collapse boundary qualitatively ("centralization helps") and stop short of estimating it. Near misses exist: Zhao and Xie (2025) sweep credit-assignment levels but optimise win rates rather than estimate a boundary; Jiang et al. (2020) use reward-mixing weights without isolating a critical value. Closest in spirit, Yamaguchi (2025) construct a phase diagram for independent Q-learning over environment size and agent density — but their axes are environmental, not motivational: the reward structure w and the behavioral profile of the agents are precisely the dimensions their framework holds fixed. No prior work characterises the collapse boundary as a quantitative, measurable object with confidence intervals.

A parallel literature equips MARL agents with risk preferences but cannot answer our question either. Risk-sensitive methods based on Conditional Value at Risk optimise tail outcomes (Qiu et al., 2021; Shen et al., 2023); this is mathematically distinct from loss aversion, which is an asymmetry of perceived value around a reference point, not a reweighting of tail probability. Lalmohammed et al. (2025) do bring cumulative prospect theory (CPT) into cooperative MARL, but integrate the value function and the probability weighting into the actor–critic update jointly — so the effect of curvature (α, β) and the effect of loss aversion (λ) on coordination cannot be separated. In evolutionary game theory, Mengesha et al. (2025) prove that loss aversion induces population-level lock-in, establishing the phenomenon conceptually — but in a setting without learned neural policies, function approximation, or finite-horizon training dynamics. The decomposition question — *which component of prospect theory moves the coordination boundary, and in which direction* — is open in deep MARL.

This is the gap: coordination collapse has never been measured as a boundary, and behavioral bias has never been decomposed against such a boundary. We close both halves at once, and the two halves discipline each other: a behavioral shift is only interpretable relative to a quantified null boundary, and a boundary is only worth quantifying if something scientifically meaningful moves it. Our approach treats the collapse boundary the way physics treats a phase boundary: a pre-registered, frozen binary collapse definition; logistic estimation of $P(\text{collapse} \mid w)$; bootstrap confidence intervals on the critical point w_{crit}; and a three-way null-model design (no PT / curvature only / curvature plus loss aversion) that attributes any shift to a specific CPT component. Two design choices make the attribution clean. We apply CPT as a *reward transform* rather than modifying the learning update, so the optimizer is identical in every condition and behavioral effects cannot be confounded with algorithmic ones. And we estimate the boundary at multiple training horizons, because a threshold that moves with training time (metastability) would otherwise masquerade as a fixed constant.

We ask three questions:

RQ1 (Existence and location). Does coordination collapse occur at a sharp critical value w_{crit} of reward centralization — a phase boundary rather than a gradual degradation — and where is it?

RQ2 (Stability). Is w_{crit} a structural constant of the system, or does it shift with training horizon T?

RQ3 (Behavioral decomposition). How do the two components of prospect theory — probability-weighting curvature (α, β) and loss aversion (λ) — each shift w_{crit}, and in which directions?

Across 1,524 controlled runs, the boundary is sharp—a logistic phase transition in w, not a gradual degradation—and it is not a fixed constant: it slides left with the training horizon ($w_{\text{crit}} = 0.822 \rightarrow 0.666$ from 150k to 300k steps), so collapse at intermediate w is a *metastable* attractor rather than an absorbing state. Against this null boundary the two prospect-theory components separate cleanly and oppositely. Curvature alone ($\alpha{=}\beta{=}0.88$, $\lambda{=}1$) shifts w_{crit} *left* by 0.100 $[0.033, 0.172]$, *easing* coordination; loss aversion shifts it *right*, by $+0.089$ $[0.041, 0.141]$ at $\lambda{=}3$ and $+0.166$ $[0.135, 0.202]$ at $\lambda{=}7$, *impeding* it. A full sweep $\lambda{=}1\ldots7$ rises then saturates (strictly increasing through $\lambda{=}5$, flat within noise thereafter), tracked by a one-parameter, theory-bounded affine law (RMSE 0.014; non-overlapping $\lambda{=}1$ vs $\lambda{=}7$ intervals). A mean-field signal-to-noise account fixes the *signs* of both effects before any data are seen; the loss-aversion direction then replicates across two further environments—MPE Cooperative Navigation (w_{crit} rising $0.76 \rightarrow 0.95$) and Level-Based Foraging ($0.26 \rightarrow 0.83$ over $\lambda{=}1 \rightarrow 4$, saturating thereafter), both under centralized-critic MAPPO—and under a different algorithm on the supply chain (MAPPO, $0.80 \rightarrow 0.89$; Figure 5), confirming the prediction, while the absolute boundary and curvature sign remain substrate-specific. Finally, the shift is driven by a *minority*: a single *downstream* loss-averse node moves the system boundary to $w_{\text{crit}} = 0.853$—indistinguishable from a fully loss-averse population (0.851)—while an upstream node shifts it far less (0.726), a cascade that propagates upstream along the ordering chain (Section).

To our knowledge this is the first quantitative, confidence-intervalled phase boundary of coordination collapse in deep cooperative MARL, and the first demonstration that prospect theory's two components push such a boundary in *opposite* directions. We scope these claims deliberately: that loss aversion can move a coordination tipping point is established conceptually in evolutionary game theory (Mengesha et al., 2025), and CPT has been brought into cooperative MARL before (Lalmohammed et al., 2025); our contribution is the *measured boundary* and the *decomposition* against it. Practically, the boundary is a measurable safety margin: it says how much reward centralization a cooperative system needs for reliable coordination—and how much *more* it needs once its agents are loss-averse.




Figure 1: $P(\text{collapse})$ in (w, T) space. Each cell shows the empirical collapse fraction across 20 seeds. The 150k and 300k rows are from Exp A (α=β=1); the 600k row is from Exp T (α=β=0.88). Because α=β=0.88 shifts w_{crit} left by 0.100 (§), the apparent 300k→600k slide is partially curvature-inflated. Under matched α=β=1 conditions (Exp 0b), $P(\text{collapse} \mid w{=}0.6) = 0.35$ and $P(\text{collapse} \mid w{=}0.7) = 0.20$ at 600k, confirming that metastability holds with α=β held constant; only the magnitude is curvature-inflated in this figure.

Figure 1 shows the collapse probability surface in (w, T) space, illustrating the metastability result. Figure 2 shows the behavioral decomposition: the four logistic curves separate clearly, confirming both the curvature and loss-aversion effects.

Background

In cooperative MARL, N agents share an environment and aim to maximize a joint objective. Centralised Training with Decentralised Execution (CTDE) (Lowe et al., 2017) addresses the *credit assignment* problem by allowing a centralised critic during training while agents execute independently. The degree of credit sharing is controlled by a reward mixing weight: a scalar $w \in [0, 1]$ that interpolates between purely local (w=0) and purely global (w=1) reward.

When $w \approx 0$, each agent's reward is dominated by its own performance. The contribution of cooperative action is diluted: an agent receives no signal when a teammate's action improves the global outcome. Liu et al. (2023) and Shi and Peng (2023) formalise this as the *lazy agent* problem and *relative overgeneralization* respectively: agents converge to a safe, zero-action policy that avoids coordination risk. This paper asks: at what value of w does this failure mode become probable, and how does agent-level loss aversion shift that value?

Prospect theory (Kahneman and Tversky, 1979) models human decision-making under uncertainty via a reference-dependent value function and a nonlinear probability weighting function. Cumulative prospect theory (CPT) (Tversky and Kahneman, 1992) extends this to compound lotteries via rank-dependent integration. The CPT value function is:

$$v(x) = \begin{cases} x^{\alpha} & \text{if } x \geq 0 \\ -\lambda(-x)^{\beta} & \text{if } x < 0, \end{cases} \tag{1}$$

where $\alpha, \beta \in (0, 1]$ govern curvature (probability weighting sensitivity) and $\lambda > 1$ is the loss aversion coefficient. Setting α=β=1 and λ=1 recovers linear expected utility. The parameters α, β and λ have distinct effects on agent behaviour: curvature introduces nonlinear sensitivity to outcome magnitudes, while loss aversion introduces asymmetry between gains and losses around the reference point.

We apply CPT as a *reward transform* applied after reward blending. The per-step reward for agent i is:

$$r_i^{\text{PT}} = v\big((1-w)\, r_i^{\text{local}} + w\, r^{\text{global}}\big)\,, \tag{2}$$

where $v(\cdot)$ is given by Equation (1). This differs architecturally from Lalmohammed et al. (2025), who integrate CPT into the actor and critic update mechanics; our formulation applies PT at the reward signal level and does not modify the policy gradient computation.

Method

The reward centralization parameter $w \in [0, 1]$ is the sole structural intervention. All other environment parameters, algorithm hyperparameters, and random seeds are held constant across conditions.

We define coordination collapse as a binary outcome:

$$\text{collapsed}(\text{run}) = \mathbf{1}\big[\bar{S} < 10 \;\wedge\; \bar{\pi} \leq -127.1\big]\,, \tag{3}$$

where $\bar{S}$ is the mean base-stock level and $\bar{\pi}$ is mean profit over ten evaluation episodes. This definition was pre-registered before any analysis (commit `03c3fc6`). Section demonstrates robustness to $\pm 20\%$ threshold perturbation (maximum $\Delta w_{\text{crit}} = 0.015$).

For each experimental condition, we fit:

$$P(\text{collapsed} \mid w) = \sigma(b_0 + b_1 w), \tag{4}$$

where σ is the logistic function. We estimate $w_{\text{crit}} = -b_0/b_1$ (the value of w where collapse probability equals 0.5) and its 95% confidence interval via 2,000 bootstrap resamples at the run level. We report Wilson score 95% confidence intervals for per-w collapse fractions. For conditions with very steep transitions (high λ), where the unpenalized maximum-likelihood slope is ill-conditioned, we fit b_0, b_1 with *Firth penalized* logistic regression (Jeffreys-prior penalty), which is stable in this regime; the Firth and bootstrap w_{crit} estimates agree throughout.

To attribute the observed shift in w_{crit} to specific PT components, we define three conditions with identical environments and algorithms:

1. **Null (Exp N):** α=β=1, λ=1—the linear, no-PT condition.
2. **Curvature (Exp B, λ=1):** α=β=0.88, λ=1—probability weighting with no loss aversion.
3. **Loss aversion (Exp B, $\lambda \in \{3, 7\}$):** α=β=0.88, $\lambda > 1$—full PT.

The curvature effect is defined as $w_{\text{crit}}(\text{B}, \lambda{=}1) - w_{\text{crit}}(\text{N})$, and the loss aversion increment as $w_{\text{crit}}(\text{B}, \lambda) - w_{\text{crit}}(\text{B}, \lambda{=}1)$. This decomposition is valid because the null removes all PT distortion, while the curvature condition adds nonlinearity without loss asymmetry.

Experimental Setup

We use `NetworkManagement-v1` from or-gym (Hubbs et al., 2020): a six-node multi-echelon inventory network with Poisson demand (μ=20) on the retail edge, 30-period episodes, and uniform lead times. Node 1 (the retail-facing node) follows a fixed demand-pull policy, stabilising the demand signal; nodes 2–6 are trained as cooperative PPO agents. Actions are parameterised via a base-stock wrapper that maps each agent's continuous action to a target inventory level $S \in [0, 500]$, with order quantity $Q = \max(0, S - \text{IP})$ where IP is inventory position. The substrate extends prior DRL inventory work — the Beer Distribution Game Dec-POMDP of Oroojlooyjadid et al. (2022), the multi-echelon A3C results of Gijsbrechts et al. (2022), and single-echelon MARL (Leluc et al., 2023) — to a six-node network with per-node agents.

Each agent runs PPO (Schulman et al., 2017) with a shared MLP policy (`n_steps=128`, `batch_size=256`) via Stable-Baselines3 (Raffin et al., 2021), PettingZoo (Terry et al., 2021), and SuperSuit (Terry et al., 2020) vectorisation. Evaluation is deterministic over 10 episodes with 20 seeds per condition.

Table 1 summarises all seven experiments. All designs were pre-registered before execution. Total run count: 1,524.

Results

Structural Phase Transition and Metastability

Exp A establishes a sharp logistic collapse transition. At 150k steps, $w_{\text{crit}} = 0.822$ $[0.785, 0.858]$ with transition width $\Delta w = 0.278$ (logistic slope $b_1 = -15.78$, $p = 5 \times 10^{-9}$). At 300k steps, $w_{\text{crit}} = 0.666$ $[0.635, 0.694]$ with $\Delta w = 0.199$ ($b_1 = -22.05$, $p = 3.2 \times 10^{-7}$). In both cases, collapse fractions rise steeply from near-zero to near-one within a $\Delta w < 0.3$ range, consistent with a genuine phase transition rather than a gradual degradation. We use "phase transition" throughout in the empirical sense of a sharp, metastable threshold—an exploration-driven, Kramers-style escape barrier (Section)—and not as a claim of a thermodynamic-limit singularity.

The critical boundary decreases monotonically with training horizon T: $w_{\text{crit}} = 0.822$ at 150k and $w_{\text{crit}} = 0.666$ at 300k (both from Exp A, α=β=1). Figure 1 visualises the collapse surface in (w, T) space. This constitutes a *metastability* result: the lazy-agent attractor is not absorbing. Agents trapped below the isocline at finite T can escape given sufficient training; w controls the energy barrier height of the attractor. The phase boundary proper is the asymptotic ($T \to \infty$) threshold—the deterministic crossing toward which $w_{\text{crit}}(T)$ descends (Equation (10))—so the horizon dependence we observe is the metastable *approach* to that boundary, not evidence against a sharp underlying one. The sharpening transition width (Δw decreasing from 0.278 to 0.199 across 150k to 300k) is consistent with policy convergence reducing outcome variance.

Note on the 600k row. The 600k row in Figure 1 comes from Exp T, which uses α=β=0.88. Because our decomposition shows α=β=0.88 shifts w_{crit} left by 0.100 relative to α=β=1, the 600k collapse fractions in the figure are partially curvature-deflated, not purely a horizon effect. To bound the horizon-only slide, we use Exp 0b (α=β=1, 20 seeds, 600k): $P(\text{collapse} \mid w{=}0.6) = 0.35$ and $P(\text{collapse} \mid w{=}0.7) = 0.20$, compared to 0.80 and 0.40 at 300k. The metastability result—the boundary slides left with T—holds under matched α=β=1 conditions; only the magnitude at 600k in the figure is inflated by the curvature effect.

Exp C rules out initialization as a driver of collapse. Within-w correlations between S_{init} and converged S are -0.11 (w=0.5), -0.38 (w=0.85), and -0.36 (w=1.0)— all near zero and inconsistent with initialization dominating the outcome. The collapsed/survived assignment is not sensitive to where agents start.

The structural null and its reproducibility

All behavioral shifts in this paper are measured against a single structural null: the linear, no-PT condition (α=β=1, λ=1). We adopt a *single canonical null*, the risk-neutral structural boundary at the 300k decomposition horizon, $w_{\text{crit}}^{\text{null}} = 0.666$ $[0.635, 0.694]$ (Exp A @300k), and reference it throughout. The dedicated null experiment (Exp N) independently reproduces it at $w_{\text{crit}} = 0.685$ $[0.657, 0.710]$—a difference of 0.019 with overlapping intervals. Every other null-like number in the paper is a labeled *offset* from this one canonical value, not a separate baseline:

- **Horizon offset** $w_{\text{crit}} = 0.822$ (150k steps, Exp A): the same risk-neutral null measured at the shorter, metastable horizon ($0.822 \to 0.666$ as T rises 150k$\to$300k; Section).
- **Curvature offset** $w_{\text{crit}} = 0.586$ (α=β=0.88, λ=1): the canonical null shifted *left* by -0.080 by probability-weighting curvature—a *result* (the curvature shift), not a third baseline. It is the λ=1 anchor of the loss-aversion sweep.

Behavioral Phase Boundary

We sweep loss aversion across the full range $\lambda \in \{1, 2, 3, 4, 5, 6, 7\}$ (all at α=β=0.88, 300k steps, 20 seeds per cell), combining Exp B-Reduced at $\lambda \in \{1, 3, 7\}$ with a dedicated fill-in sweep at $\lambda \in \{2, 4, 5, 6\}$. The critical centralization w_{crit} rises with loss aversion across the entire range (Table 2, Figure 2): $w_{\text{crit}} = \{0.586, 0.715, 0.774, 0.806, 0.839, 0.836, 0.851\}$ for $\lambda = 1, \ldots, 7$. The increase is monotone up to estimation noise at the high-λ plateau: w_{crit} rises strictly from λ=1 to λ=5, then saturates near 0.84–0.85, where the λ=5 and λ=6 estimates (0.839 vs 0.836) are statistically indistinguishable (overlapping CIs).[1] The behavioral claim is unambiguous at the

[1] At high loss aversion the transition is very steep and falls between two adjacent grid points—e.g. collapse fractions $1.00, 1.00, 1.00, 0.55, 0.00$ at $w \in \{0.5, 0.65, 0.75, 0.85, 0.95\}$ for λ=7—so the boundary remains identifiable (the w=0.85 cell is interior, $11/20$ collapsed) but the *unpenalized* MLE slope diverges. We therefore fit every λ with Firth penalized logistic regression (Table 2), which is stable under steep transitions; all seven slopes are significant ($p < 10^{-3}$) and the Firth w_{crit} matches the bootstrap estimate to within 0.019. A finer grid ($w \in \{0.80, 0.90\}$) would

Table 1: Experiment summary. All experiments use the same environment and algorithm. $\alpha{=}\beta{=}1$ denotes the linear (no-PT) condition.

Exp	Purpose	w values	λ	α, β	Seeds	Runs
A @150k	Structural boundary	$\{0.0, 0.1, \ldots, 1.0\}$	1	1,1	20	220
A @300k	Structural boundary	$\{0.2, \ldots, 0.8\}$	1	1,1	20	140
C	Basin control	$\{0.5, 0.85, 1.0\}$	1	1,1	12	144
N	Null baseline	$\{0.0, 0.2, \ldots, 1.0\}$	1	1,1	20	180
B-Red.	Behavioral decomposition	$\{0.5, 0.65, 0.75, 0.85, 0.95\}$	$\{1, 3, 7\}$	0.88	20	300
λ-sweep	Loss-aversion law (fill-in)	$\{0.5, 0.65, 0.75, 0.85, 0.95\}$	$\{2, 4, 5, 6\}$	0.88	20	400
T (600k only)	Metastability horizon	$\{0.5, 0.55, \ldots, 0.80\}$	1	0.88	20	140




Figure 2: Behavioral decomposition and full loss-aversion sweep on the supply chain (PPO, 300k steps, 20 seeds per cell). Each curve is the Firth-fitted $P(\text{collapse} \mid w)$; vertical dotted lines mark w_{crit}. The null ($\alpha{=}\beta{=}1$, gray dashed) is the structural baseline ($w_{\text{crit}}{=}0.685$). Probability-weighting *curvature* alone ($\lambda{=}1$, $\alpha{=}\beta{=}0.88$) shifts w_{crit} *left* of the null—facilitating coordination—while *loss aversion* ($\lambda{=}2, \ldots, 7$, $\alpha{=}\beta{=}0.88$) shifts it monotonically *right*. The two prospect-theory components thus move the boundary in opposite directions, and the full sweep traces the resulting $w_{\text{crit}}(\lambda)$ progression in one panel.

endpoints: $w_{\text{crit}}(\lambda{=}7)$ lower CI 0.845 exceeds $w_{\text{crit}}(\lambda{=}1)$ upper CI 0.624—non-overlapping by 0.221—and the seven-point trend (Figure 4) shows the relationship is systematic, not a two-point artefact.

Table 3 and Figure 2 present the three-way decomposition. Relative to the null ($w_{\text{crit}} = 0.685$):

1. **Curvature effect** ($\alpha{=}\beta{=}0.88$, $\lambda{=}1$): excess $= -0.100$, 95% CI $[-0.172, -0.033]$. The confidence interval excludes zero from above, indicating that probability weighting alone *significantly reduces* the required centralization. Agents with nonlinear probability perception but no loss aversion are *easier* to coordinate than agents with linear utility.
2. **Loss aversion at** $\lambda{=}3$: excess $= +0.089$, 95% CI $[+0.041, +0.141]$ (CI excludes zero; significant).
3. **Loss aversion at** $\lambda{=}7$: excess $= +0.166$, 95% CI $[+0.135, +0.202]$ (CI excludes zero; significant).

tighten the high-λ CIs further.

Table 2: Full loss-aversion sweep ($\alpha{=}\beta{=}0.88$, 300k steps, 20 seeds per (w, λ) cell, $n{=}100$ runs per λ). w_{crit} with bootstrap 95% CIs. Slope and p are from *Firth penalized* logistic regression (Jeffreys-prior), which is stable under steep transitions; all seven slopes are significant ($p < 10^{-3}$). The Firth $w_{\text{crit}} = -b_0/b_1$ agrees with the bootstrap estimate at every λ (max. deviation 0.019), confirming that the very large unpenalized MLE slopes previously seen at $\lambda{=}5, 7$ were a fitting artifact, not separation.

λ	w_{crit}	95% CI	Firth slope b_1	p
1	0.586	[0.539, 0.624]	-14.7	1.2×10^{-6}
2	0.715	[0.687, 0.745]	-27.2	4.4×10^{-6}
3	0.774	[0.751, 0.798]	-29.7	5.1×10^{-6}
4	0.806	[0.766, 0.841]	-36.8	5.5×10^{-6}
5	0.839	[0.788, 0.845]	-53.1	4.7×10^{-4}
6	0.836	[0.806, 0.860]	-24.7	2.5×10^{-6}
7	0.851	[0.845, 0.858]	-43.1	1.5×10^{-3}

The curvature and loss-aversion effects operate in *opposite directions*: curvature facilitates coordination, loss aversion impedes it. At $\lambda{=}7$, the loss aversion increment above the curvature baseline is $+0.265$ ($= 0.851 - 0.586$), overwhelming the curvature benefit of -0.100 for a net shift of $+0.166$ above the structural null (rounding: $-0.100 + 0.265 \approx 0.165 \approx 0.166$).

A Mean-Field Mechanism for the Collapse Boundary

The results above establish the boundary empirically. This section offers a mechanistic account of *why* it exists and how it moves; it is not a closed-form derivation of w_{crit}, and we are explicit throughout about what is derived, what is calibrated, and what is not claimed (Table 4 summarises). The central claim is qualitative and sign-level: w_{crit} marks a *signal-to-noise crossing* of the policy gradient, and the two prospect-theory components move it in *opposite* directions for reasons the mechanism fixes a priori. The model predicts these directions, the monotonic ordering, the sharpness of the transition, and the sign of the horizon dependence *without* fitting; it does not predict the numerical value of w_{crit} on any axis, which remains calibrated. We stress the scope of the novelty: that loss aversion can shift a coordination phase boundary is established—Mengesha et al. (2025)

Table 3: Three-way behavioral decomposition of w_{crit} relative to the null model. "Significant" denotes that the conservative difference confidence interval excludes zero. †For λ=7, w_{crit} is from bootstrap only; see footnote in Section .

Condition	w_{crit}	95% CI	Excess	Excess CI	Sig.?
Null (α=β=1, λ=1)	0.685	[0.657, 0.710]	0	—	—
α=β=0.88, λ=1	0.586	[0.539, 0.624]	-0.100	$[-0.172, -0.033]$	✓ (neg.)
α=β=0.88, λ=3	0.774	[0.751, 0.798]	$+0.089$	$[+0.041, +0.141]$	✓
α=β=0.88, λ=7†	0.851	[0.845, 0.858]	$+0.166$	$[+0.135, +0.202]$	✓

prove it for evolutionary game theory via replicator selection. Our contribution here is not that result but its deep-MARL *learning-dynamics* analogue: in our setting the driver is the signal-to-noise ratio of the policy gradient under exploration, not selection pressure over fixed strategies, which is what makes the account specific to gradient-trained neural policies.

Gradient flow and its noise

Each learning agent i runs PPO on a Gaussian policy over its (normalised) base-stock action $a_i \in [0,1]$ with mean μ_i and exploration scale σ. The shaped reward is the centralisation blend passed through the prospect-theory value function v,

$$r_i = v\big((1-w)\,\ell_i(a_i, a_{-i}) + w\,G(a)\big), \qquad G(a) = \textstyle\sum_j \ell_j, \tag{5}$$

where ℓ_i is node i's local profit and G the system profit. For a Gaussian policy the PPO update on the mean is a stochastic estimate of the return gradient, so the policy mean follows a mean-field Langevin (Fokker–Planck) equation

$$\mathrm{d}\mu_i = \underbrace{\eta\,\partial_{\mu_i}\mathbb{E}\big[(1-w)\ell_i + wG\big]}_{\text{drift } D(w)}\,\mathrm{d}t \;+\; \sqrt{2\,\Theta(w)}\,\mathrm{d}W. \tag{6}$$

Because each partner's local profit is itself blended into the global term, the partners' exploration (σ) enters the gradient estimate of agent i through the global channel, so the diffusion carries a centralisation- weighted, cross-agent piece,

$$\Theta(w) \;\propto\; \tfrac{\sigma^2}{B}\big[(1-w)^2 s_\ell^2 \;+\; w^2(N-1)\,\kappa^2\big], \tag{7}$$

with batch size B, local reward sensitivity s_ℓ, and cross-agent sensitivity κ.

The boundary is a signal-to-noise crossing

We instrumented the substrate directly (finite-difference of ℓ_i and G along the base-stock axis) and confirmed the qualitative asymmetry the model needs: in the replenishing regime an upstream node's inventory is a *local cost* (holding and procurement reduce its own profit) but a *global benefit* (it averts downstream stockouts). Writing the linearised marginal incentives as $\partial_a\mathbb{E}\ell \to -c$ and $\partial_a\mathbb{E}G \to +g$ ($c, g > 0$), the drift toward cooperation is

$$D(w) = \eta\big[\,w\,g - (1-w)\,c\,\big]. \tag{8}$$

What governs whether the optimiser actually climbs toward cooperation is not the drift alone but its ratio to the gradient noise. Escape from the lazy basin requires

$$\mathrm{SNR}(w) \;=\; \frac{D(w)}{\sqrt{\Theta(w)}} \;\gtrsim\; \kappa_c, \tag{9}$$

for an $\mathcal{O}(1)$ critical value κ_c set by the training budget. The cooperative signal grows only with centralisation ($\propto w$), so for small w the right-hand region of (8) is swamped by the exploration variance (7) and the lazy policy is the effective attractor (Figure 3a). The crossing $\mathrm{SNR}(w) = \kappa_c$ defines w_{crit}. In the low-noise limit $\Theta \to 0$ this reduces to the purely deterministic threshold $D(w) = 0$, i.e.

$$w^0_{\text{crit}} = \frac{c}{c+g}, \tag{10}$$

the asymptotic ($T \to \infty$) boundary; finite exploration noise raises the operative boundary above it. We emphasise that c, g, σ and κ_c are not derived in closed form from the multi-echelon cost matrix (a multi-echelon stochastic-control problem in its own right); the model is calibrated, and its content is the *functional* predictions below, not the absolute magnitude of w_{crit}.[2]

Sharpness and metastability

Two predictions follow from the noise picture without further fitting. First, escape is a Kramers first-passage problem with mean time $\tau \sim \tau_0 \exp(\Delta U/\Theta)$, exponentially sensitive to SNR; the collapse probability therefore switches abruptly as w crosses w_{crit}—an abrupt, metastable threshold, matching the steep logistic fits of Section . Second, collapse at finite horizon means $\tau > T$; as T grows, a smaller SNR (hence smaller w) suffices to escape, so $w_{\text{crit}}(T)$ decreases monotonically toward (10). This is exactly the observed metastable slide $w_{\text{crit}} = 0.822 \to 0.666$ from 150k to 300k steps, following the $\propto -\ln T$ Kramers trend (Figure 3c).

Opposite signs of the two prospect-theory components

The mechanism's most distinctive prediction is qualitative and requires no fitting: probability weighting and loss aversion shift w_{crit} in *opposite* directions. Concave–convex curvature ($\alpha, \beta < 1$) compresses the magnitude of both gains and losses, lowering the outcome variance that enters Θ; this *raises* the SNR and hence *lowers* w_{crit}. Loss aversion ($\lambda > 1$) instead magnifies the downside, inflating Θ and lowering the

[2]Three different empirical boundaries anchor different parts of this section, because each is the appropriate reference for its purpose: the ratio g/c is set by the structural boundary w_{crit}=0.666 (α=β=1, 300k); the affine λ-law is anchored to the curvature-shifted Exp B baseline w_{crit}=0.586 (α=β=0.88, λ=1); and the signal-to-noise test of Section is compared to the matched-horizon boundary w_{crit}=0.822 (150k). The axes are not interchangeable, so we state the reference explicitly in each case.

SNR, which *raises* w_{crit}. The signs are fixed by the value function before any data are seen, and they match the central empirical finding (Section): curvature alone shifts w_{crit} left by 0.100, loss aversion shifts it right by up to 0.166.

Derived form of the loss-aversion law

The *functional form* of the loss-aversion shift, not merely its sign, follows from the value function. Differentiating $\mathbb{E}[v(r)]$ and splitting the marginal mass into gain and loss domains, the loss domain is the only part scaled by λ, so the effective local term is affine in λ:

$$w_{\mathrm{crit}}(\lambda) = \frac{\phi(\lambda)}{\phi(\lambda) + g/c}, \qquad \phi(\lambda) = 1 + \rho\,(\lambda - 1), \quad (11)$$

where $\rho \in [0, 1]$ is the loss-domain share of the marginal incentive—a quantity the theory *bounds to the unit interval*. This is a genuine parametric constraint, not a free fit: a single slope ρ must explain all λ, and it must lie in $[0, 1]$. We fix both parameters *before* seeing the full sweep: g/c from the λ=1 baseline and $\rho = 0.61$ from the three Exp B-Reduced points ($\lambda \in \{1, 3, 7\}$), both of which satisfy the bound. Held fixed and tested *out of sample* against the remaining four points ($\lambda \in \{2, 4, 5, 6\}$; the full seven-point sweep in Table 2), this single-slope affine law gives

$$w_{\mathrm{crit}}^{\mathrm{pred}} = \{0.586, 0.695, 0.759, 0.800, 0.830, 0.851, 0.868\},$$
$$w_{\mathrm{crit}}^{\mathrm{meas}} = \{0.586, 0.715, 0.774, 0.806, 0.839, 0.836, 0.851\},$$

an RMSE of 0.014 across all seven points (Figure 4)—a one-parameter, theory-bounded law tracking the entire $w_{\mathrm{crit}}(\lambda)$ curve, not merely the three calibration points. (Re-fitting ρ to all seven points instead gives $\rho = 0.63$ at RMSE 0.013, a negligible change.) The one systematic residual is a mild overshoot at the high-λ plateau (λ=6, 7): the leading-order law is affine, whereas the data are mildly concave and saturate, consistent with agents endogenously reducing loss exposure as λ grows (a second-order effect we do not model). We deliberately report this derived affine law rather than a better-fitting but unmotivated power law, because the point of the section is mechanism, not goodness of fit.

Scope. The model is a representative-agent reduction with a calibrated noise scale; c, g, σ and ρ are not derived from the multi-echelon cost matrix. A direct finite-difference probe of the substrate confirms the *sign* of the local-cost/global-benefit asymmetry but shows the marginal coefficients are operating-point dependent, so the absolute boundary is a property of the stochastic multi-agent dynamics rather than a static gradient—which is why we calibrate rather than predict its magnitude. This section is not the paper's contribution— the decomposition is—but a supporting, falsifiable *mechanism*: it commits in advance to the signs, the ordering, the affine λ-law with a bounded slope, the sharpness, and the horizon and exploration-noise directions (Table 4), all of which the data bear out, consistent with exploration-driven accounts of cooperation failure in shared-policy MARL (Weng and Lee, 2026). The exploration-noise prediction is confirmed directly by the entropy ablation (Section). Section reports a direct test that measures the Langevin drift and diffusion from PPO




Figure 3: Mean-field mechanism versus empirics. (a) Mechanism (schematic): the cooperative gradient signal grows with centralisation ($\propto w\,g$) while partner exploration injects a roughly w-independent noise floor; w_{crit} is the signal-to-noise crossing (9), below which the lazy policy is the effective attractor. (b) Schematic of the *derived affine* loss-aversion law (11): CPT predicts $\phi(\lambda) = 1 + \rho(\lambda - 1)$ with slope $\rho \in [0, 1]$; the single data-implied slope $\rho = 0.61$ respects the bound. The quantitative fit against the full seven-point sweep is shown separately in Figure 4. (c) The Kramers escape picture predicts the metastable leftward slide of w_{crit} with training horizon T.




Figure 4: The derived affine loss-aversion law (11) against the full sweep. Points are the measured $w_{\mathrm{crit}}(\lambda)$ for $\lambda = 1, \ldots, 7$ with bootstrap 95% CIs (Table 2); the line is the one-parameter law with g/c fixed at the λ=1 baseline and a single theory-bounded slope $\rho = 0.61$. The law tracks all seven points to RMSE 0.014, with a mild concave residual at the high-λ saturation plateau.

Table 4: What the mean-field mechanism claims. We separate predictions made *a priori* from quantities calibrated to data and from claims we explicitly do *not* make.

Derived (no fit)	opposite signs of curvature vs. loss aversion; monotonic $w_{\mathrm{crit}}(\lambda)$; *affine* form of $\phi(\lambda)$ with slope $\rho \in [0, 1]$; abrupt (phase-transition) sharpness; w_{crit} decreasing with horizon T; w_{crit} increasing with exploration noise.
Empirically confirmed	the opposite signs and affine form (Section); the horizon slide (Exp A/T); and the exploration-noise dependence—raising the entropy coefficient moves w_{crit} right and collapses the system at large noise (Section).
Calibrated (1 param/axis)	g/c (from the λ=1 boundary); loss-domain share ρ; noise scale setting the absolute w_{crit}.
Not claimed	a closed-form value of w_{crit} from the cost matrix; the numerical magnitude on any axis; the mild concavity of $w_{\mathrm{crit}}(\lambda)$ beyond leading order.

training: it reproduces the matched-horizon boundary but leaves the magnitude calibrated, as the drift-sign observable is confounded by basin geometry.

Generalization across Environments and Algorithms

The mechanism of Section commits, before any data, to a *direction*: loss aversion inflates gradient noise and therefore raises w_{crit}. If that account is right rather than an artefact of one substrate or one optimiser, the sign should survive changing both. We test this on two further environments and a second algorithm. The headline result is that the *direction* of the loss-aversion effect is robust to both, while the absolute boundary, the curvature sign, and the precise functional form are substrate- and algorithm-specific—exactly the split the calibrated-not-predicted mechanism (Table 4) anticipates. Figure 5 summarises the headline: in all four settings w_{crit} climbs with λ, the curves converging in the mid-range and differing most at λ=1.

Across environments: incentive misalignment across domains

A central claim of this work is that the coordination cliff—a sharp, CPT-modulated collapse threshold as the reward centralization w decreases—is a *recurring* feature of multi-agent systems where individual self-interest conflicts with collective outcomes, not an artefact of the supply-chain setting. We examine this claim in two qualitatively distinct environments from different application domains—the supply chain (under PPO) and MPE Cooperative Navigation (under centralised-critic MAPPO)—both of which yield the boundary empirically. The algorithm is matched to each environment's learnability: where coordination is learnable by




Figure 5: **The loss-aversion effect generalizes.** Critical centralization w_{crit} versus loss aversion λ for four settings: the supply chain under PPO (blue) and under centralized-critic MAPPO (green), MPE Cooperative Navigation under MAPPO (red), and Level-Based Foraging under MAPPO (purple). Error bars are bootstrap 95% CIs. Across three structurally distinct environments and two algorithms, w_{crit} rises with λ then saturates—loss aversion raises the centralization a cooperative system needs to avert collapse. The *direction* is what generalizes; absolute levels differ (most at λ=1) and the curvature sign and exact functional form are substrate-specific. (LBF's high-λ points saturate against the centralization ceiling and are reported as exploratory; see Section .)

independent agents we use PPO, and where the coordination reward is shared-global we use a centralised critic, so that the measured boundary reflects the behavioural incentive w rather than the learner's capacity to assign credit.

Supply Chain (NetworkManagement-v1, logistics/operations research). Six nodes in a serial supply chain share a common upstream supplier with finite Poisson-demand ($\mu = 20$). The locally rational action is to *order aggressively*—maximising one's own on-hand inventory—which depletes the shared upstream pipeline and starves downstream nodes. At w=0 (pure individual inventory reward), agents hoard; the cascade failure of downstream nodes constitutes collapse. This is the primary experimental setting; results are reported in Section .

MPE Cooperative Navigation (simple_spread_v3, robotics/navigation). Three agents must cover three landmarks in a continuous 2-D arena (discrete action space, 50-step episodes). The locally rational action under the herding incentive is to *stay near teammates*—individually rational for proximity bonuses—but collectively disastrous, as all agents cluster and no landmark is covered. The w-dial interpolates between the herding signal (w=0, clustering collapse) and the global coverage score (w=1, coordination). We use `local_ratio=0` in `simple_spread_v3` to ensure the raw environment reward is the pure global team score; the herding term is defined by our wrapper. Collapse is measured by *per-step landmark occupancy* (the fraction of landmarks within a fixed radius of some agent), a

behavioural metric that is invariant to the reward scale and therefore unaffected by the CPT transform. Crucially, unlike the supply chain—whose incentives are *per-agent*, so that collapse is purely behavioural—MPE's coordination reward is a *shared, global* team score. Under independent learners this confounds behavioural collapse with a credit-assignment failure: with a decentralised critic the agents receive an identical learning signal and cannot learn which agent should cover which landmark, so the $w{=}1$ coordination end never trains regardless of the behavioural incentive. We therefore train MPE with *centralised-critic MAPPO* (Yu et al., 2022): each agent's actor consumes only its local observation (augmented with a one-hot agent identifier to break the symmetry of parameter sharing), while the critic receives the joint observation. This is centralised training with decentralised execution; it isolates the behavioural collapse boundary from the algorithm's ability to assign credit—precisely the confound the reward-transform design is intended to avoid. MPE is a standard benchmark introduced by Lowe et al. (2017).

Structural commonality. In both environments the incentive misalignment is identical at the level of the reward blend:

$$r_{\text{blend}}(i) = (1-w)\, r_{\text{local}}(i) \;+\; w\, r_{\text{global}}, \qquad (12)$$

where r_{local} encodes a locally rational strategy that is harmful to the collective, and r_{global} is the team score. The supply chain exhibits a *resource-competition* failure mode (hoarding stock starves downstream nodes), while MPE exhibits a *coordination-failure* mode (herding prevents coverage)—structurally distinct routes to the same collapse boundary. The collapse boundary is recovered in both environments we measure—the supply chain (PPO) and MPE (MAPPO). To make MPE a fair test of the behavioural decomposition rather than of the algorithm's capacity to coordinate, we set the herding scale so the null boundary lands in the interior ($w_{\text{crit}}{=}0.71$, rather than pinned against the centralization ceiling) and ran the full loss-aversion sweep $\lambda \in \{1,\dots,7\}$ at $\alpha{=}\beta{=}0.88$ (550 runs; Figure 6; cross-setting summary in Figure 5).

The *loss-aversion* effect replicates. On MPE, w_{crit} rises with loss aversion from 0.76 ($\lambda{=}1$) to 0.95 ($\lambda{=}7$)—monotone up to seed noise at intermediate λ—and the three-condition decomposition yields a loss-aversion excess of $+0.100$ $[+0.004, +0.194]$ at $\lambda{=}3$, significant and quantitatively matching the supply-chain $+0.089$. The qualitative law—loss aversion raises the centralization required to avert collapse—thus holds across structurally distinct environments and training algorithms (a third environment, Level-Based Foraging, is added in Section ; Figure 5).

The *curvature* effect does *not* replicate. On MPE the curvature excess is $+0.047$ $[-0.052, +0.154]$, statistically indistinguishable from the null and opposite in sign to the supply-chain -0.100; probability weighting appears to facilitate coordination only in the supply-chain substrate. The exact *functional form* of the loss-aversion law is likewise environment-specific: the affine $w_{\text{crit}}(\lambda)$ that tracks the supply chain to RMSE 0.014 fits MPE only to RMSE 0.05,




Figure 6: MAPPO on MPE Cooperative Navigation: fitted collapse-probability curves $P(\text{collapse} \mid w)$ for the full loss-aversion sweep $\lambda{=}1,\dots,7$ ($\alpha{=}\beta{=}0.88$, centralized critic, 50-step horizon, 10 seeds per cell; collapse = per-step landmark occupancy below the calibrated $\theta{=}0.164$). The family shifts rightward as λ grows, with vertical dashed w_{crit} lines ordered accordingly—the same loss-aversion signature found in the supply chain, recovered under a different environment and a different (centralized-critic) algorithm.

the MPE curve being steeper at high λ as the boundary approaches the centralization ceiling. We therefore claim cross-environment generality for the collapse boundary and for the *direction* of the loss-aversion effect—the paper's central behavioural claim—while reporting the curvature sign and the precise functional form as supply-chain-specific.

A third environment: Level-Based Foraging

MPE shares MAPPO's shared-global reward; to probe a third, structurally distinct domain we add Level-Based Foraging (LBF), a standard cooperative-MARL benchmark (Christianos et al., 2020) with a *public-goods* incentive: agents pay an effort cost to load food cooperatively, so the locally rational action is to free-ride and the team coordinates only as the global reward comes to dominate. LBF is natively discrete and unrelated to logistics or navigation; we train it under centralized-critic MAPPO—matching MPE, so that across MPE and LBF the *algorithm* is held fixed and only the *environment* varies—with the identical reward pipeline and full λ-sweep, and a collapse threshold set by the same collapsed-vs-coordinated midpoint used for MPE (1,440 runs, $w \in \{0,\dots,0.95\}$).

LBF yields the most complete decomposition outside the supply chain (Figure 5). The risk-neutral null has a low, tightly estimated boundary ($w_{\text{crit}} \approx 0.08$); probability-weighting curvature moves it *right* by $+0.18$ (impeding coordination)—*opposite* in sign to the supply chain's -0.10, reinforcing that the curvature sign is substrate-specific. Loss aversion then drives a large rightward shift: w_{crit} rises from 0.26 at $\lambda{=}1$ to 0.83 at $\lambda{=}4$, monotone with non-overlapping low- versus high-λ confidence intervals (the pre-registered criterion), and the direction is robust to the collapse threshold. For $\lambda{\geq}5$ the boundary saturates against the centralization ceiling (the logistic w_{crit} extrapolates to $w{\geq}1$), and we re-

port those points as exploratory. We flag a second, related caveat explicitly: the LBF w-grid carries only a single sampled level above 0.85 (namely w=0.95), so the high-λ critical points—which fall in exactly that $[0.85, 1]$ interval—are coarsely resolved and should be read as exploratory locations of a saturating boundary, not as precisely estimated values; finer w-spacing in $(0.85, 1)$ is left to future work. As in MPE, the *direction* of the loss-aversion effect—the paper's central behavioural claim—replicates, while curvature sign and functional form remain substrate-specific.

Across algorithms: MAPPO on the supply chain

The MPE result varies the environment *and* the algorithm at once. To isolate the algorithm, we re-run the full loss-aversion sweep on the *identical* supply-chain substrate, grid, seeds, collapse label, and hyperparameters, changing only the learner from independent PPO to centralized-critic MAPPO (Yu et al., 2022) (700 runs; $\lambda \in \{1, \ldots, 7\}$, α=β=0.88, 5 values of w, 20 seeds). The actor consumes only its local observation; the critic consumes the joint state (CTDE). This isolates the effect of credit assignment from the behavioural incentive.

The loss-aversion law replicates under MAPPO. The critical centralization rises with loss aversion from w_{crit}=0.796 $[0.742, 0.860]$ at λ=1 to w_{crit}=0.889 $[0.856, 0.917]$ at λ=7, monotone from λ=2 onward $(0.747, 0.795, 0.800, 0.851, 0.861, 0.889)$ and with non-overlapping λ=1 vs λ=7 confidence intervals (Figure 7; cross-setting summary in Figure 5). As in MPE, the *direction* generalizes while the absolute level does not: the MAPPO boundary sits above the PPO boundary at low λ (most visibly the λ=1 point, 0.796 vs 0.586), where MAPPO's transition is shallow and the w_{crit} estimate correspondingly noisier; the two boundaries converge by $\lambda \geq 4$ ($|\Delta w_{\text{crit}}| \leq 0.04$). We therefore report the loss-aversion direction and monotonicity as algorithm-independent on this substrate, and the absolute w_{crit} (especially at low λ) as algorithm-dependent.

Boundary Conditions: Two Ablations

The mean-field account (Section) makes the boundary contingent on two ingredients: a *continuous* policy gradient (the signal-to-noise crossing is a property of gradient flow), and a learner able to separate behavioural collapse from credit assignment (so that what w moves is the incentive, not the optimiser's capacity to coordinate). We ablate each. Both confirm the mechanism and delimit *where* the phenomenon lives.

Action representation

The mechanism predicts that destroying the continuous policy gradient should remove the boundary. Value-based learners require a discrete action space, so we discretised the supply-chain base-stock control into K=11 bins and ran an independent value learner (IQL) and a centralised monotonic-mixing learner (QMIX) on the identical reward pipeline, w-grid, and collapse label. Both produced a *flat, w-independent* collapse rate with no fittable w_{crit} in any condition. To isolate the cause—value-based learning vs. the discrete action space—we add a single-variable control: PPO, the learner that yields the boundary under continuous control, trained on the *same* K=11 discrete shell with everything else fixed. It too goes flat (Table 5). Holding the learner at PPO, discretisation *alone* erases the boundary, so the value-based nulls require no appeal to the learning paradigm.

We scope this precisely. The supply-chain action is a *continuous* base-stock level; coarse bins snap the policy to a stable interior level and never visit the near-threshold (s, S) region where collapse occurs, exactly as the continuous-gradient mechanism predicts. This is *not* a claim that discreteness per se removes the boundary: MPE (Section) has a *natively* discrete action space and retains it. The effect is therefore a coarse-discretisation boundary condition, substrate-specific in the same way the curvature sign is—and a confirmed prediction of the mechanism, not a negative result.

Credit assignment

The second ingredient is a learner that can coordinate at all on a shared-reward task, so that w_{crit} reflects the behavioural incentive rather than a credit-assignment failure. We ablate the centralised critic. On MPE Cooperative Navigation, an




Figure 7: Centralized-critic MAPPO on the supply chain: fitted collapse-probability curves $P(\text{collapse} \mid w)$ for $\lambda = 1, \ldots, 7$ (α=β=0.88, 300k steps, 20 seeds per cell, 700 runs). As under PPO, the family shifts rightward as loss aversion grows—each increment of λ raises the centralization required to avert collapse—confirming the effect is not an artifact of independent PPO. The PPO-vs-MAPPO $w_{\text{crit}}(\lambda)$ comparison is shown alongside MPE in Figure 5.

Learner	Action space	Boundary?
PPO / MAPPO	continuous	yes (Section)
QMIX (centralised value)	discrete K=11	no
IQL (independent value)	discrete K=11	no
PPO (control)	discrete K=11	**no**

Table 5: Action-representation ablation. The control (last row) changes only the action space while holding the learner at PPO, isolating coarse discretisation of the continuous control—not the value-based paradigm—as what erases the boundary.




Figure 8: Credit-assignment ablation on MPE (null, λ=1). Independent PPO collapses at every w (a coordination floor: it cannot learn the task regardless of incentive), while the centralised-critic learner (MAPPO) crosses the boundary. The behavioural boundary is exposed only once credit assignment is handled.

independent learner (PPO) never reaches the coordinated regime at *any* w: the collapse fraction is 1.0 across the entire w-range, including maximal centralisation (Figure 8), so behavioural collapse cannot be distinguished from the inability to assign credit. A centralised critic (MAPPO) on the identical environment recovers coordination—the collapse fraction falls to 0.35 and landmark occupancy crosses the calibrated threshold near $w{\approx}0.6$. We observe the same independent-learner floor on Level-Based Foraging, where PPO fails to coordinate while MAPPO reaches the coordinated regime. The boundary is therefore *measurable* only with a centralised critic on shared-reward coordination tasks; this is why we match a centralised critic to such environments (Section)—a necessity, not a convenience.

A Minority Sets the Boundary

The decomposition and its generalization treat the population as homogeneous—every agent carries the same λ. A deployed cooperative system rarely is: some participants are loss-averse, others are not. We therefore ask whether the boundary is an averaged, population-wide property, or whether a *minority* can set it—and whether *network position* matters. We assign λ=7 to selected nodes and λ=1 to the rest, holding the substrate, PPO configuration, collapse label, and grid identical to the main sweep ($\alpha{=}\beta{=}0.88$, 300k, 20 seeds, $w \in \{0.5, 0.65, 0.75, 0.85, 0.95\}$).

The effect is large and strongly position-dependent (Figure 9, Table 6). A single *downstream* loss-averse node drives $w_{\text{crit}} = 0.853$ $[0.849, 0.858]$—statistically indistinguishable from the *fully* loss-averse population ($w_{\text{crit}} = 0.851$ $[0.847, 0.856]$): one biased node downstream sets the centralization requirement of the entire network. The same node placed *upstream* shifts the boundary far less, to $w_{\text{crit}} = 0.726$ $[0.689, 0.763]$. Loss aversion therefore cascades *upstream*—a downstream node's bias propagates back along the ordering chain and dominates the system boundary—but not downstream, a directional asymmetry that mirrors the bullwhip structure of the substrate.

That a behavioral minority can move a system-level tipping point is itself established in evolutionary game theory via replicator selection (Mengesha et al., 2025); our contribution is the deep-MARL instantiation, where the effect emerges from gradient-learning dynamics and carries a concrete network-position signature absent from the EGT account. The operational reading is sharper than a population average would suggest: in a mixed human–agent supply chain, the centralization the system needs is set by its most downstream loss-averse participant, not by the mean bias.

Table 6: Heterogeneous-population sweep ($\alpha{=}\beta{=}0.88$; loss-averse nodes at λ=7, others λ=1; 300k, 20 seeds/cell). w_{crit} with bootstrap 95% CIs. Homogeneous references: all risk-neutral ≈ 0.586, all loss-averse 0.851.

Loss-averse nodes	w_{crit} (95% CI)
one upstream	0.726 [0.689, 0.763]
one downstream	0.853 [0.849, 0.858]
two downstream	0.851 [0.847, 0.856]
all five (homogeneous)	0.851 [0.847, 0.856]




Figure 9: Heterogeneous cognitive profiles. (a) Collapse curves: a single downstream loss-averse node (orange) tracks the fully loss-averse population (red), while a single upstream node (blue) is far milder. (b) w_{crit} by configuration: one downstream loss-averse node already reaches the homogeneous loss-averse boundary; loss aversion cascades upstream but not downstream.

Discussion

The finding that probability weighting and loss aversion exert opposite effects on the coordination boundary is, to our knowledge, novel. Prior work applies prospect theory as a unified behavioural model without decomposing its components (Lalmohammed et al., 2025; Ghaemi et al., 2024). Our null-model design isolates the two components, revealing that the beneficial effect of curvature (-0.100) is masked when combined with loss aversion (λ>1), which reverses the sign and amplifies the required centralization. This has a concrete operational interpretation: a system with λ=7 agents—calibrated to reflect human loss-aversion estimates (Tversky and Kahneman, 1992)—requires $w > 0.851$ for reliable coordination, against $w > 0.685$ for risk-neutral agents (the canonical null). That additional 0.166 in required centralization ($w_{\text{crit}}(\lambda{=}7) - w_{\text{crit}}(\text{null}) = 0.851 - 0.685$, consistent

with Table 3) is a quantified cost of deploying loss-averse agents in a cooperative system.

Two caveats sharpen this reading. On calibration, the canonical laboratory estimate of loss aversion is $\lambda \approx 2.25$ (Tversky and Kahneman, 1992); our sweep deliberately brackets the empirical human range, with λ=7 an upper, high-stakes bound rather than a typical value. The cost scales with λ (Table 3), so a domain whose participants sit nearer $\lambda \approx$ 2–3 incurs a smaller but still positive margin (the λ=3 excess is $+0.089$, against $+0.166$ at λ=7). On deployment, centralization is not free: privacy, communication cost, and organisational policy can cap the attainable w. Where the required w exceeds that cap, the boundary reframes the design problem—instead of only raising centralization, one can lower the agents' effective loss aversion (for instance through the training objective), treating λ as the second, behavioural lever the decomposition exposes.

The boundary is also not an averaged property. Section shows it is set by a *minority*: a single downstream loss-averse node moves the system boundary as far as a fully loss-averse population, cascading upstream along the ordering chain. The operational consequence is sharp—in a mixed human–agent supply chain, the required centralization is governed by the most downstream loss-averse participant, not by the population mean.

The sliding w_{crit} result is a positive finding, not a pathology. It establishes that the lazy-agent attractor is *metastable*: agents caught below the isocline at finite T can, in principle, coordinate if given more training. This is consistent with Weng and Lee (2026)'s finding that exploration breaks cooperation in shared-policy MARL during early training, before representations converge. The practical implication is that the minimum w required depends on the operational training budget: tighter horizons demand higher centralization.

Yamaguchi (2025) construct a phase diagram in (L, ρ) space for IQL, identifying analogous coordinated/fragile/jammed regimes. Our results complement theirs by demonstrating that the phase structure is not only a function of environmental complexity but also of the reward structure (w) and agent behavioral parameters (λ). Together, these works suggest that MARL coordination exhibits coherent phase structure across multiple parameter axes. More broadly, competing-bias tipping points are an established analytic phenomenon in multiagent dynamics: Capannoli et al. (2026) prove a metastable partial-adoption boundary in network opinion dynamics under competing stubbornness and disruptive biases, with an explicit critical threshold. Our contribution is the deep-MARL *learning-dynamics* analogue—a boundary set by the policy-gradient signal-to-noise ratio rather than a fixed update rule—which situates our phase-diagram framing within a recognised line of multiagent phase-transition results.

Several limitations should be noted. First, the full quantitative characterization—the decomposition, the affine λ-law, metastability, the mechanism calibration, and the heterogeneous cascade—is carried out on one substrate (NetworkManagement-v1), which serves as the primary measurement instrument because its continuous action and per-agent economic reward make w_{crit} and the affine law finely identifiable. We replicate the collapse boundary and the *direction* of the loss-aversion effect in two further domains (MPE Cooperative Navigation and Level-Based Foraging) via full λ=1, . . . , 7 sweeps (Section , Section); because that environment's coordination reward is shared-global rather than per-agent, independent PPO cannot learn its coordination end (a credit-assignment, not behavioural, failure), so MPE is trained with centralised-critic MAPPO. We thus match the algorithm to each environment's learnability rather than holding it fixed. To isolate the algorithm from the environment, we additionally re-run the full sweep with centralised-critic MAPPO on the *same* supply-chain substrate (Section): the loss-aversion direction and monotonicity replicate, confirming the effect is not specific to independent PPO. The curvature sign and the precise affine functional form do not transfer to MPE, and the absolute w_{crit} is algorithm-dependent at low λ; broader replication across further algorithms and environments remains future work. Second, the high-λ conditions (λ=5, 7) have a steep transition resolved by a single interior w-grid point; we address this with Firth penalized fits (Table 2), but a finer grid above w=0.85 would further tighten the high-λ confidence intervals. Third, the metastability result describes finite-horizon behavior; an asymptotic lower bound on w_{crit} is not estimated by our experiments. Fourth, we fix the demand distribution and lead times; the dependence of w_{crit} on these environmental parameters is unexplored. Fifth, the heterogeneity sweep uses a binary $\lambda \in \{1, 7\}$; real populations carry a continuous distribution of loss aversion. The upstream cascade (Section) implies the boundary is governed by the most loss-averse *downstream* participant—the distribution's tail, not its mean—but testing a continuous distribution directly is left to future work. Sixth, the curvature effect is the one finding that does not transfer: it lowers w_{crit} on the supply chain but is null and opposite-signed on MPE. The mechanism attributes this to substrate-specific outcome-variance compression (Section), but we have no predictive rule for when curvature aids coordination, and therefore claim only the loss-aversion *direction* as cross-substrate. Seventh, the methodology has scope conditions: it requires an environment learnable by the chosen learner *without* experience sharing and admitting a behavioural collapse label separable from mere task-unlearnability, which excludes sparse, long-credit-horizon tasks. We further conjecture the same downstream-dominated cascade arises in other directed-flow cooperative domains—traffic networks, power grids, staged healthcare resource allocation—a prediction the framework makes testable.

Conclusion

We presented the first quantitative phase diagram of cooperative MARL coordination collapse, characterising the critical centralization threshold w_{crit} as a function of reward structure, training horizon, and prospect-theoretic loss aversion. A three-way null-model decomposition reveals that the two components of prospect theory—probability weighting and loss aversion—exert statistically significant effects in opposite directions on the coordination boundary: the former facilitates coordination by 0.100; the latter impedes it by up to 0.166. These results provide concrete design constraints

for deploying cooperative MARL in behavioral settings and establish a pre-registered phase-diagram methodology applicable to any cooperative MARL system.

Natural extensions include replication across further algorithms (QMIX) and environments (SMAC), upgrading the mean-field account (Section) from a calibrated mechanism to a quantitative prediction of w_{crit} via direct measurement of the policy-gradient signal-to-noise ratio (Section), adaptive centralization scheduling based on the estimated isocline, and characterization of heterogeneous-λ populations.

Notation and Abbreviations

Symbol	Meaning
w	reward centralization weight, $\in [0, 1]$
w_{crit}	critical w where $P(\text{collapse})$=0.5
λ	loss-aversion coefficient (λ>1)
α, β	CPT value-function curvature (gain/loss)
ρ	loss-domain share of marginal incentive, $\in [0, 1]$
g, c	marginal global benefit / local cost of cooperation
$D(w), \Theta(w)$	Langevin drift / diffusion of the policy mean
$\text{SNR}(w)$	$D(w)/\sqrt{\Theta(w)}$, escape signal-to-noise ratio
σ, η, B	exploration scale / learning rate / batch size
$\Delta U, \tau$	escape barrier / Kramers first-passage time
T	training horizon (environment steps)
$\bar{S}, \bar{\pi}$	mean base-stock level / mean profit (collapse label)

Abbreviations. MARL (multi-agent reinforcement learning); CTDE (centralized training, decentralized execution); CPT (cumulative prospect theory); PPO (proximal policy optimization); MAPPO (multi-agent PPO with a centralized critic); MPE (multi-agent particle environments); SNR (signal-to-noise ratio); MLE (maximum-likelihood estimate); CI (confidence interval).

Threshold Robustness

We verify that the collapse definition (Equation (3)) is robust to perturbation of its thresholds. We re-estimate w_{crit} on Exp A @300k data under nine variants of the definition, varying $\bar{S}$ threshold over $\{8, 10, 12\}$ and $\bar{\pi}$ threshold over $\{-102.5, -127.1, -152.5\}$. Three variants with threshold $\bar{\pi} \leq -152.5$ are degenerate (the minimum profit in the dataset is -128.1, so no run satisfies this condition); they are excluded. Across the remaining six estimable variants, the maximum deviation from the baseline $w_{\text{crit}} = 0.666$ is 0.015, well below the confidence interval width. We conclude that the collapse definition is robust to $\pm 20\%$ threshold perturbation.

Pre-registered Test of the Signal-to-Noise Mechanism

The mean-field account (Section) calibrates the magnitude of w_{crit} rather than predicting it, because the relevant drift and diffusion coefficients are properties of the stochastic learning dynamics, not static quantities of the cost matrix. We pre-register here a direct measurement that would upgrade the magnitude from calibrated to predicted, and we fix its analysis before running it.

Observable. The mean-field model treats the policy's mean base-stock action μ as a Langevin variable, $\mathrm{d}\mu = D(w)\,\mathrm{d}t + \sqrt{2\,\Theta(w)}\,\mathrm{d}W$. During PPO training we log μ once per update and, over a fixed early-training window, estimate the drift $D(w)$ (mean increment) and diffusion $\Theta(w)$ (increment variance / 2), forming $\text{SNR}(w) = D(w)/\sqrt{2\Theta(w)}$.

Prediction and decision rule. We sweep $w \in \{0.50, \ldots, 0.90\}$ at the structural condition (α=β=1, λ=1), 20 seeds per w, 150k steps, and compare against the *matched-horizon* boundary $w_{\text{crit}} = 0.822$ (Section). The mechanism is corroborated iff the measured signal-to-noise crossing's bootstrap 95% CI contains 0.822.

Outcome. The result is mixed, and we report it in full. The *collapse-fraction* of this independent sweep crosses 0.5 at $w = 0.82$, reproducing the matched-horizon boundary almost exactly—a positive robustness check on the boundary itself. The *drift-sign* observable, however, was *inconclusive*: the restoring drift in the contested band is weakly positive across all w with no genuine zero-crossing, so it does not localise w_{crit}. The reason is basin geometry: PPO initialises above the cooperative optimum (S≈250 vs S≈150), and collapses often plunge through the contested band too quickly to be sampled, biasing the conditioned drift toward survivors. We therefore do *not* claim a magnitude-level prediction; the boundary magnitude remains calibrated, as stated in Table 4. The mechanism section stands on its sign-level and functional-form predictions, which are unaffected. The driver and analysis (with the decision rule encoded) are released with the code so the test can be re-run with alternative observables (e.g. a longer horizon matched to $w_{\text{crit}} = 0.666$, or a basin-flow statistic).

Exploration-Noise Ablation

A further pre-registered experiment probes the boundary along an axis the main analysis holds fixed: the exploration noise of the learner. It reuses the identical substrate, PPO configuration, and collapse label, and provides the direct empirical support for the signal-to-noise mechanism (Section). (The heterogeneous-population result is promoted to the main text, Section .)

Exploration noise (entropy coefficient). The mean-field account (Section) predicts that w_{crit} is set by the signal-to-noise ratio of the policy gradient, so increasing the exploration term should raise it. We sweep the PPO entropy coefficient at the structural condition (α=β=1, λ=1, 300k, 20 seeds, $w \in \{0.5, \ldots, 0.9\}$). The boundary rises monotonically with exploration noise (Figure 10, Table 7):

$w_{\text{crit}} = 0.685$ at ent=0 (reproducing the null baseline exactly), 0.690 at 0.001, 0.715 at 0.01, and beyond 0.05 the system collapses at *every* tested w (w_{crit} extrapolates above 1). This is direct empirical support for the signal-to-noise mechanism: the location of the boundary is not a function of the behavioral bias alone but also of the exploration noise that competes with the diluted cooperative signal, exactly as (9) predicts.

Table 7: Entropy-coefficient ablation (α=β=1, λ=1, 300k, 20 seeds/cell). w_{crit} with bootstrap 95% CIs.

entropy coef.	w_{crit} (95% CI)
0.000	0.685 [0.656, 0.710]
0.001	0.690 [0.667, 0.715]
0.010	0.715 [0.689, 0.743]
0.050	> 1 (collapse at all w)




Figure 10: Exploration-noise ablation. (a) Collapse curves shift right as the entropy coefficient grows. (b) w_{crit} rises monotonically with exploration noise, corroborating the signal-to-noise mechanism (Section); ent=0 reproduces the null boundary 0.685.

References

Aditya Akella. On the fundamental limitations of decentralized learnable reward shaping in cooperative multi-agent reinforcement learning. *arXiv preprint arXiv:2511.00034*, 2025. URL https://arxiv.org/abs/2511.00034.

Federico Capannoli, Emilio Cruciani, Hlafo Alfie Mimun, and Matteo Quattropani. A phase transition for opinion dynamics with competing biases. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 40, pages 29323–29331, 2026.

Filippos Christianos, Lukas Schäfer, and Stefano Albrecht. Shared experience multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pages 10707–10717, 2020. URL https://arxiv.org/abs/2006.07169.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. KTO: Model alignment as prospect theoretic optimization, 2024. URL https://arxiv.org/abs/2402.01306. ICML 2024.

Hafez Ghaemi, Hamed Kebriaei, Alireza Ramezani Moghaddam, and Majid Nili Ahamdabadi. Risk-sensitive multi-agent reinforcement learning in network aggregative Markov games, 2024. URL https://arxiv.org/abs/2402.05906.

Joren Gijsbrechts, Robert N. Boute, Jan A. Van Mieghem, and Dennis J. Zhang. Can deep reinforcement learning improve inventory management? Performance on lost sales, dual-sourcing, and multi-echelon problems. *Manufacturing & Service Operations Management*, 24(3):1349–1368, May 2022. ISSN 1526-5498. doi: 10.1287/msom.2021.1064. URL http://dx.doi.org/10.1287/msom.2021.1064.

Christian D. Hubbs, Hector D. Perez, Owais Sarwar, Nikolaos V. Sahinidis, Ignacio E. Grossmann, and John M. Wassick. OR-Gym: A reinforcement learning library for operations research problems, 2020. URL https://arxiv.org/abs/2008.06319.

Jiechuan Jiang, Chen Dun, Tiejun Huang, and Zongqing Lu. Graph convolutional reinforcement learning, 2020. URL https://arxiv.org/abs/1810.09202. ICLR 2020.

Daniel Kahneman and Amos Tversky. Prospect theory: An analysis of decision under risk. *Econometrica*, 47(2):263–291, March 1979. ISSN 0012-9682. doi: 10.2307/1914185. URL http://dx.doi.org/10.2307/1914185.

Sheyan Lalmohammed, Khush Gupta, Alok Shah, and Keshav Ramji. Modeling human behavior without humans: Prospect theoretic multi-agent reinforcement learning. In *International Conference on Machine Learning*, 2025.

Joel Z Leibo, Vinicius Zambaldi, Marc Lanctot, Janusz Marecki, and Thore Graepel. Multi-agent reinforcement learning in sequential social dilemmas. In *Proceedings of the 16th Conference on Autonomous Agents and Multi-Agent Systems (AAMAS)*, pages 464–473, 2017. URL https://arxiv.org/abs/1702.03037.

Rémi Leluc, Elie Kadoche, Antoine Bertoncello, and Sébastien Gourvénec. MARLIM: Multi-agent reinforcement learning for inventory management, 2023. URL https://arxiv.org/abs/2308.01649.

Boyin Liu, Zhiqiang Pu, Yi Pan, Jianqiang Yi, Yanyan Liang, and Du Zhang. Lazy agents: A new perspective on solving sparse reward problem in multi-agent reinforcement learning. In *International Conference on Machine Learning*, pages 21937–21950. PMLR, 2023.

Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *Advances in Neural Information Processing Systems*, 30, 2017. URL https://arxiv.org/abs/1706.02275.

Isaak Mengesha, Meiqi Sun, and Debraj Roy. Cognitive biases shape the evolution of zero-sum norms. *arXiv preprint arXiv:2511.16453*, 2025. URL https://arxiv.org/abs/2511.16453.

Afshin Oroojlooyjadid, MohammadReza Nazari, Lawrence V Snyder, and Martin Takáč. A deep Q-network for the beer game: Deep reinforcement learning for inventory optimization. *Manufacturing & Service Operations Management*, 24(1):285–304, 2022.

Wei Qiu, Xinrun Wang, Runsheng Yu, Rundong Wang, Xu He, Bo An, Svetlana Obraztsova, and Zinovi Rabinovich. RMIX: Learning risk-sensitive policies for cooperative reinforcement learning agents. *Advances in Neural Information Processing Systems*, 34:23049–23062, 2021.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268): 1–8, 2021. URL http://jmlr.org/papers/v22/20-1364.html.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. URL https://arxiv.org/abs/1707.06347.

Siqi Shen, Chennan Ma, Chao Li, Weiquan Liu, Yongquan Fu, Songzhu Mei, Xinwang Liu, and Cheng Wang. RiskQ: Risk-sensitive multi-agent reinforcement learning value factorization. *Advances in Neural Information Processing Systems*, 36:34791–34825, 2023.

Lin Shi and Bei Peng. Curriculum learning for relative overgeneralization. In *Adaptive and Learning Agents Workshop at Conference on Autonomous Agents and Multiagent Systems*, 2023.

J. K. Terry, Benjamin Black, and Ananth Hari. SuperSuit: Simple microwrappers for reinforcement learning environments, 2020. URL https://arxiv.org/abs/2008.08932.

J. K. Terry, Benjamin Black, Nathaniel Grammel, Mario Jayakumar, Ananth Hari, Ryan Sullivan, Luis Santos, Rodrigo Perez, Caroline Horsch, Clemens Dieffendahl, Niall L. Williams, Yashas Lokesh, and Praveen Ravi. PettingZoo: Gym for multi-agent reinforcement learning, 2021. URL https://arxiv.org/abs/2009.14471.

Amos Tversky and Daniel Kahneman. Advances in prospect theory: Cumulative representation of uncertainty. *Journal of Risk and Uncertainty*, 5(4):297–323, 1992.

Yi-Ning Weng and Hsuan-Wei Lee. How exploration breaks cooperation in shared-policy multi-agent reinforcement learning. *arXiv preprint arXiv:2601.05509*, 2026. URL https://arxiv.org/abs/2601.05509.

Azusa Yamaguchi. Emergent coordination and phase structure in independent multi-agent reinforcement learning. *arXiv preprint arXiv:2511.23315*, 2025. URL https://arxiv.org/abs/2511.23315.

Chao Yu, Akash Velu, Eugene Vinitsky, Jiaxuan Gao, Yu Wang, Alexandre Bayen, and Yi Wu. The surprising effectiveness of PPO in cooperative multi-agent games. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2022.

Xutong Zhao and Yaqi Xie. Multi-level advantage credit assignment for cooperative multi-agent reinforcement learning, 2025. URL https://arxiv.org/abs/2508.06836.