

Create Database : if port is 3306[default port]

```
<?php
//mysqli_connect(host, username, password, database, port);
$conn = mysqli_connect("127.0.0.1", "root", "", "", 3306);

if (!$conn) {
    die(mysqli_connect_error());
}

echo "Connected";
?>
```

OR

Create Database : if port number is Different

```
<?php

$conn = mysqli_connect("127.0.0.1", "root", "", "", 3307);

if (!$conn) {
    die("Connection failed: " . mysqli_connect_error());
}

$sql = "CREATE DATABASE testdb";

if (mysqli_query($conn, $sql)) {
    echo "Database created successfully";
} else {
    echo "Error: " . mysqli_error($conn);
}

mysqli_close($conn);
?>
```

Step 1: Check Required Software

- XAMPP (recommended)
 - Apache Server
 - MySQL Database
 - PHP

Step 2: Start Apache and MySQL

1. Open XAMPP Control Panel.
2. Click **Start** for:
 - Apache
 - MySQL

Both services should show a green status.

Step 3: Create a PHP File

1. Open a text editor (Notepad, VS Code, etc.).
2. Copy and paste the PHP code.
3. Save the file as:

createdb.php

Step 4: Save the File in the Correct Folder

For XAMPP, save it inside:

C:\xampp\htdocs\

Example:

C:\xampp\htdocs\createdb.php

Or create a folder:

C:\xampp\htdocs\phpdemo\

and save as:

C:\xampp\htdocs\phpdemo\createdb.php

Step 5: Modify Database Credentials

Replace:

```
$username = "username";  
$password = "password";
```

with your MySQL credentials.

For a default XAMPP installation:

```
$username = "root";  
$password = "";
```

Step 6: Open a Browser

Type:

`http://localhost/createdb.php`

or if stored in the `phpdemo` folder:

`http://localhost/phpdemo/createdb.php`

Step 7: Execute the Program

Press **Enter**.

The PHP file will run through Apache.

Step 8: View the Output

If successful:

Database created successfully

If there is an error:

Connection failed: ...

or

Error creating database: ...

Step 9: Verify the Database

1. Open browser:

`http://localhost/phpmyadmin`

2. Look in the left panel.
3. You should see:

myDB

This confirms that the database was created successfully.

=====

Create Table

<?php

```
$conn = mysqli_connect("127.0.0.1", "root", "", "testdb", 3307);
```

```
if (!$conn) {  
    die("Connection failed: " . mysqli_connect_error());  
}
```

```
$sql = "CREATE TABLE users (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(100) NOT NULL,  
    email VARCHAR(100) NOT NULL,  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
)";
```

```
if (mysqli_query($conn, $sql)) {  
    echo "Table 'users' created successfully";  
} else {  
    echo "Error creating table: " . mysqli_error($conn);  
}
```

```
mysqli_close($conn);
```

?>

=====

<?php

```
$conn = mysqli_connect("127.0.0.1", "root", "", "testdb", 3307);
```

```
if (!$conn) {  
    die("Connection failed: " . mysqli_connect_error());  
}
```

/* =====

CREATE (INSERT)

```

===== */
if (isset($_POST['insert'])) {
    $name = $_POST['name'];
    $email = $_POST['email'];

    $sql = "INSERT INTO users (name, email) VALUES ('$name', '$email')";
    mysqli_query($conn, $sql);
}

```

```

/* =====
UPDATE
===== */
if (isset($_POST['update'])) {
    $id = $_POST['id'];
    $email = $_POST['email'];

    $sql = "UPDATE users SET email='$email' WHERE id=$id";
    mysqli_query($conn, $sql);
}

```

```

/* =====
DELETE
===== */
if (isset($_POST['delete'])) {
    $id = $_POST['id'];

    $sql = "DELETE FROM users WHERE id=$id";
    mysqli_query($conn, $sql);
}

```

```

/* =====
READ
===== */
$result = mysqli_query($conn, "SELECT * FROM users");

```

?>

```

<!DOCTYPE html>
<html>
<head>
    <title>PHP CRUD</title>
</head>
<body>

<h2>Insert User</h2>
<form method="post">
    Name: <input type="text" name="name" required>
    Email: <input type="text" name="email" required>

```

```
<button type="submit" name="insert">Insert</button>
</form>
```

```
<hr>
```

```
<h2>Update Email</h2>
```

```
<form method="post">
  ID: <input type="number" name="id" required>
  New Email: <input type="text" name="email" required>
  <button type="submit" name="update">Update</button>
</form>
```

```
<hr>
```

```
<h2>Delete User</h2>
```

```
<form method="post">
  ID: <input type="number" name="id" required>
  <button type="submit" name="delete">Delete</button>
</form>
```

```
<hr>
```

```
<h2>Users List</h2>
```

```
<table border="1" cellpadding="5">
```

```
  <tr>
    <th>ID</th>
    <th>Name</th>
    <th>Email</th>
  </tr>
```

```
  <?php while ($row = mysqli_fetch_assoc($result)) { ?>
    <tr>
      <td><?php echo $row['id']; ?></td>
      <td><?php echo $row['name']; ?></td>
      <td><?php echo $row['email']; ?></td>
    </tr>
  <?php } ?>
```

```
</table>
```

```
</body>
```

```
</html>
```

```
<?php mysqli_close($conn); ?>
```

```
=====
```

`mysqli_query($conn, $sql)` is a function in PHP that is used to execute a query on a MySQL database

`mysqli_num_rows($result)` is a function in PHP used to determine the number of rows in a result set obtained from a `SELECT` query.

`mysqli_fetch_assoc($result)` is a function in PHP that fetches a result row as an associative array from the query result. This function is often used when you retrieve data from a MySQL database