

# Projections

1.0

Generated by Doxygen 1.9.1



## Chapter 1

# Projection of line

main file The program takes three arguments: name\_file x y z name\_file is file with line x, y and z are coordinates of the point The program prints output of the following form segment n parameter s point x y z n is number of segment of line s is a parameter that shows the part of the segment that the projection falls on. This parameter ranges from 0 to 1

Version

1

Date

2021-06-21



## Chapter 2

# Data Structure Index

### 2.1 Data Structures

Here are the data structures with brief descriptions:

[Point](#) . . . . . ??



## Chapter 3

# File Index

### 3.1 File List

Here is a list of all files with brief descriptions:

|                                       |  |    |
|---------------------------------------|--|----|
| include/ <a href="#">point.h</a>      |  |    |
| <a href="#">Point</a> class interface | . . . . .  | ?? |
| src/ <a href="#">main.cpp</a>         | . . . . .  | ?? |
| src/ <a href="#">point.cpp</a>        | Implementing the <a href="#">Point</a> interface | ?? |





## Chapter 4

# Data Structure Documentation

### 4.1 Point Class Reference

```
#include <point.h>
```

#### Public Member Functions

- [Point](#) ()
- [Point](#) (double x, double y, double z)
- void [setPoint](#) (double x, double y, double z)
- void [printPoint](#) () const
- double [sum\\_coordinates](#) () const
- double & [operator\[\]](#) (const int)

#### Friends

- [Point operator-](#) (const [Point](#) &, const [Point](#) &)
- [Point operator\\*](#) (const [Point](#) &, const [Point](#) &)
- [Point operator\\*](#) (const [Point](#) &, const double)
- [Point operator/](#) (const [Point](#) &, const [Point](#) &)
- [Point operator/](#) (const [Point](#) &, const double)
- [Point operator/](#) (const [Point](#) &, const double)

#### 4.1.1 Detailed Description

Definition at line 8 of file point.h.

#### 4.1.2 Constructor & Destructor Documentation

#### 4.1.2.1 Point() [1/2]

```
Point::Point ( )
```

Default constructor that defines a point at the origin.

Definition at line 14 of file point.cpp.

#### 4.1.2.2 Point() [2/2]

```
Point::Point (
    double x = 0,
    double y = 0,
    double z = 0 )
```

The constructor defines point.

##### Parameters

|              |                                 |
|--------------|---------------------------------|
| <i>x,y,z</i> | are coordinates of input point. |
|--------------|---------------------------------|

Definition at line 22 of file point.cpp.

### 4.1.3 Member Function Documentation

#### 4.1.3.1 operator[]()

```
double & Point::operator[] (
    const int index )
```

Indexing operator. It returns the x, y, z coordinate depending on the index from the range [0, 2].

##### Parameters

|              |                      |
|--------------|----------------------|
| <i>index</i> | 0 – x, 1 – y, 2 – z. |
|--------------|----------------------|

Definition at line 115 of file point.cpp.

#### 4.1.3.2 printPoint()

```
void Point::printPoint ( ) const
```

The method prints point.

## Parameters

|              |                |
|--------------|----------------|
| <i>left</i>  | left operand.  |
| <i>right</i> | right operand. |

Definition at line 42 of file point.cpp.

#### 4.1.3.3 setPoint()

```
void Point::setPoint (
    double x = 0,
    double y = 0,
    double z = 0 )
```

The method sets the coordinates of the point.

## Parameters

|              |                           |
|--------------|---------------------------|
| <i>x,y,z</i> | are coordinates of input. |
|--------------|---------------------------|

Definition at line 32 of file point.cpp.

#### 4.1.3.4 sum\_coordinates()

```
double Point::sum_coordinates ( ) const
```

Computes sum of coordinates point.

## Returns

sum of coordinates point.

Definition at line 51 of file point.cpp.

### 4.1.4 Friends And Related Function Documentation

#### 4.1.4.1 operator\* [1/2]

```
Point operator* (
    const Point & left,
    const double right ) [friend]
```

The operator calculates the multiplication point by double.

**Parameters**

|              |   |
|--------------|---|
| <i>left</i>  | left operand ( <a href="#">Point</a> ). |
| <i>right</i> | right operand (double).                 |

Definition at line 84 of file point.cpp.

**4.1.4.2 operator\* [2/2]**

```
Point operator* (
    const Point & left,
    const Point & right ) [friend]
```

The operator calculates the multiplication two points.

**Parameters**

|              |  |
|--------------|--|
| <i>left</i>  | left operand ( <a href="#">Point</a> ).  |
| <i>right</i> | right operand ( <a href="#">Point</a> ). |

Definition at line 73 of file point.cpp.

**4.1.4.3 operator-**

```
Point operator- (
    const Point & left,
    const Point & right ) [friend]
```

The operator calculates a point that is the difference between all coordinates of the other two points.

**Parameters**

|              |                |
|--------------|----------------|
| <i>left</i>  | left operand.  |
| <i>right</i> | right operand. |

Definition at line 63 of file point.cpp.

**4.1.4.4 operator/ [1/3]**

```
Point operator/ (
    const Point & left,
    const double right ) [friend]
```

The operator alculates left per double number

## Parameters

|              |   |
|--------------|---|
| <i>left</i>  | left operand ( <a href="#">Point</a> ). |
| <i>right</i> | right operand (double).                 |

Definition at line 104 of file point.cpp.

#### 4.1.4.5 operator/ [2/3]

```
Point operator/ (
    const Point & left,
    const double right ) [friend]
```

The operator calculates left per double number

## Parameters

|              |   |
|--------------|---|
| <i>left</i>  | left operand ( <a href="#">Point</a> ). |
| <i>right</i> | right operand (double).                 |

Definition at line 104 of file point.cpp.

#### 4.1.4.6 operator/ [3/3]

```
Point operator/ (
    const Point & left,
    const Point & right ) [friend]
```

The operator calculates the division of the coordinates of points

## Parameters

|              |  |
|--------------|--|
| <i>left</i>  | left operand ( <a href="#">Point</a> ).  |
| <i>right</i> | right operand ( <a href="#">Point</a> ). |

Definition at line 93 of file point.cpp.

The documentation for this class was generated from the following files:

- include/[point.h](#)
- src/[point.cpp](#)



## Chapter 5

# File Documentation

### 5.1 include/point.h File Reference

[Point](#) class interface.

#### Data Structures

- class [Point](#)

#### Macros

- `#define` [DIM](#) 3

#### 5.1.1 Detailed Description

[Point](#) class interface.

#### 5.1.2 Macro Definition Documentation

##### 5.1.2.1 DIM

```
#define DIM 3
```

Definition at line 7 of file point.h.

## 5.2 src/main.cpp File Reference

```
#include "point.h"
#include <iostream>
#include <vector>
#include <fstream>
#include <string>
#include <cmath>
#include <stdexcept>
#include <sstream>
#include <float.h>
```

### Macros

- `#define ACCUR 1e-7`  
*Distance measurement accuracy.*
- `#define DIST(x, y, z) sqrt(x * x + y * y + z * z)`  
*Calculates the sum of the squares of the coordinates of a point.*
- `#define DIST_BETWEEN(x1, x2, y1, y2, z1, z2) sqrt((x1 - x2) * (x1 - x2) + (y1 - y2) * (y1 - y2) + (z1 - z2) * (z1 - z2))`  
*Computes the distance between two input points.*

### Functions

- void `read_line` (vector< [Point](#) > &points, string namefile)
- void `calculate_projections` (vector< [Point](#) > &points, [Point](#) &input\_point)
- void `projection_print` (vector< [Point](#) > &all\_projections, vector< [Point](#) > &points, vector< unsigned int > &segments)
- int `main` (int argc, char \*argv[ ])

### 5.2.1 Macro Definition Documentation

#### 5.2.1.1 ACCUR

```
#define ACCUR 1e-7
```

Distance measurement accuracy.

Definition at line 38 of file main.cpp.

#### 5.2.1.2 DIST

```
#define DIST(
    x,
    y,
    z ) sqrt(x * x + y * y + z * z)
```

Calculates the sum of the squares of the coordinates of a point.



**Parameters**

|           |                                     |
|-----------|-------------------------------------|
| $x, y, z$ | – <a href="#">Point</a> coordinates |
|-----------|-------------------------------------|

**Returns**

the sum of the squares of the coordinates of a point

Definition at line 44 of file main.cpp.

**5.2.1.3 DIST\_BETWEEN**

```
#define DIST_BETWEEN(
    x1,
    x2,
    y1,
    y2,
    z1,
    z2 ) sqrt((x1 - x2) * (x1 - x2) + (y1 - y2) * (y1 - y2) + (z1 - z2) * (z1 - z2))
```

Computes the distance between two input points.

**Parameters**

|                            |                   |
|----------------------------|-------------------|
| $(x1, x2, y1, y2, z1, z2)$ | two input points. |
|----------------------------|-------------------|

**Returns**

distance between two input point.

Definition at line 50 of file main.cpp.

**5.2.2 Function Documentation****5.2.2.1 calculate\_projections()**

```
void calculate_projections (
    vector< Point > & points,
    Point & input_point )
```

Computes all projections.

**Parameters**

|                    |                 |
|--------------------|-----------------|
| <i>points</i>      | a line.         |
| <i>input_point</i> | an input point. |

Definition at line 135 of file main.cpp.

**5.2.2.2 main()**

```
int main (
    int argc,
    char * argv[] )
```

Definition at line 59 of file main.cpp.

**5.2.2.3 projection\_print()**

```
void projection_print (
    vector< Point > & all_projections,
    vector< Point > & points,
    vector< unsigned int > & segments )
```

Prints all projections, parameters and segments.

**Parameters**

|                        |                        |
|------------------------|------------------------|
| <i>all_projections</i> | all found projections. |
| <i>points</i>          | a line.                |
| <i>segments</i>        | all found projections. |

Definition at line 111 of file main.cpp.

**5.2.2.4 read\_line()**

```
void read_line (
    vector< Point > & points,
    string namefile )
```

Read a line from a file

**Parameters**

|                 |   |
|-----------------|---|
| <i>points</i>   | the vector of dots. The data from the file is written to this vector. |
| <i>namefile</i> | the name input file.  |

Definition at line 84 of file main.cpp.

## 5.3 src/point.cpp File Reference

Implementing the [Point](#) interface.

```
#include "point.h"
#include <stdexcept>
#include <iostream>
```

### Functions

- [Point operator-](#) (const [Point](#) &left, const [Point](#) &right)
- [Point operator\\*](#) (const [Point](#) &left, const [Point](#) &right)
- [Point operator\\*](#) (const [Point](#) &left, const double right)
- [Point operator/](#) (const [Point](#) &left, const [Point](#) &right)
- [Point operator/](#) (const [Point](#) &left, const double right)

### 5.3.1 Detailed Description

Implementing the [Point](#) interface.

### 5.3.2 Function Documentation

#### 5.3.2.1 `operator*()` [1/2]

```
Point operator* (
    const Point & left,
    const double right )
```

The operator calculates the multiplication point by double.

#### Parameters

|              |   |
|--------------|---|
| <i>left</i>  | left operand ( <a href="#">Point</a> ). |
| <i>right</i> | right operand (double).                 |

Definition at line 84 of file point.cpp.

### 5.3.2.2 operator\*() [2/2]

```
Point operator* (
    const Point & left,
    const Point & right )
```

The operator calculates the multiplication two points.

#### Parameters

|              |  |
|--------------|--|
| <i>left</i>  | left operand ( <a href="#">Point</a> ).  |
| <i>right</i> | right operand ( <a href="#">Point</a> ). |

Definition at line 73 of file point.cpp.

### 5.3.2.3 operator-()

```
Point operator- (
    const Point & left,
    const Point & right )
```

The operator calculates a point that is the difference between all coordinates of the other two points.

#### Parameters

|              |                |
|--------------|----------------|
| <i>left</i>  | left operand.  |
| <i>right</i> | right operand. |

Definition at line 63 of file point.cpp.

### 5.3.2.4 operator/() [1/2]

```
Point operator/ (
    const Point & left,
    const double right )
```

The operator alculates left per double number

#### Parameters

|              |   |
|--------------|---|
| <i>left</i>  | left operand ( <a href="#">Point</a> ). |
| <i>right</i> | right operand (double).                 |

Definition at line 104 of file point.cpp.

#### 5.3.2.5 operator/() [2/2]

```
Point operator/ (
    const Point & left,
    const Point & right )
```

The operator calculates the division of the coordinates of points

##### Parameters

|              |  |
|--------------|--|
| <i>left</i>  | left operand ( <a href="#">Point</a> ).  |
| <i>right</i> | right operand ( <a href="#">Point</a> ). |

Definition at line 93 of file point.cpp.

