

DBMS Assignment 9

- Pulkit Mahajan
- 2019ucs0073

Question 1.

```
MySQL localhost:3306 ssl SQL > create database StudentReport;
Query OK, 1 row affected (0.0192 sec)
MySQL localhost:3306 ssl SQL > show databases;
+-----+
| Database |
+-----+
| companay |
| information_schema |
| institute |
| mysql |
| performance_schema |
| sakila |
| studentreport |
| sys |
| world |
+-----+
9 rows in set (0.0009 sec)
MySQL localhost:3306 ssl SQL > use studentreport;
Default schema set to `studentreport`.
Fetching table and column names from `studentreport` for auto-completion... Press ^C to stop.
MySQL localhost:3306 ssl studentreport SQL > create table student_report(
    -> sid varchar(32) NOT NULL,
    -> name varchar(64) NOT NULL,
    -> sub1 int,
    -> sub2 int,
    -> sub3 int,
    -> sub4 int,
    -> total int,
    -> average float);
Query OK, 0 rows affected (0.0492 sec)
MySQL localhost:3306 ssl studentreport SQL > describe student_report;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| sid | varchar(32) | NO | | NULL | |
| name | varchar(64) | NO | | NULL | |
| sub1 | int | YES | | NULL | |
| sub2 | int | YES | | NULL | |
| sub3 | int | YES | | NULL | |
| sub4 | int | YES | | NULL | |
| total | int | YES | | NULL | |
| average | float | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
8 rows in set (0.0145 sec)
```

```

MySQL localhost:3306 ssl studentreport SQL > create trigger trig1
sub1 -> before insert
sub2 -> on student_report
sub3 -> for each row set
sub4 -> new.total = new.sub1 + new.sub2 + new.sub3 + new.sub4,
total -> new.average = new.total / 4;
Query OK, 0 rows affected (0.0261 sec)
MySQL localhost:3306 ssl studentreport SQL > insert into student_report
values
('2001usa0911', 'OBL', 45, 23, 67, 50),
('2008ind2611', 'LET', 34, 74, 27, 42);
ERROR: 1136 (21S01): Column count doesn't match value count at row 1
MySQL localhost:3306 ssl studentreport SQL > insert into student_report(sid, name, sub1, sub2, sub3, sub4)
values
('2001usa0911', 'OBL', 45, 23, 67, 50),
('2008ind2611', 'LET', 34, 74, 27, 42);
Query OK, 2 rows affected (0.0150 sec)
Records: 2 Duplicates: 0 Warnings: 0
MySQL localhost:3306 ssl studentreport SQL > select * from student_report;
+----+-----+-----+-----+-----+-----+-----+-----+
| sid | name | sub1 | sub2 | sub3 | sub4 | total | average |
+----+-----+-----+-----+-----+-----+-----+-----+
| 2001usa0911 | OBL | 45 | 23 | 67 | 50 | 185 | 46.25 |
| 2008ind2611 | LET | 34 | 74 | 27 | 42 | 177 | 44.25 |
+----+-----+-----+-----+-----+-----+-----+-----+
2 rows in set (0.0005 sec)

```

Question2:

```

MySQL localhost:3306 ssl studentreport SQL > create table fulfillment
(
product_id varchar(32) NOT NULL,
name varchar(64) NOT NULL,
capacity int
);
Query OK, 0 rows affected (0.0265 sec)
MySQL localhost:3306 ssl studentreport SQL > create table fulfillmentstats(
total_capacity int default 0);
Query OK, 0 rows affected (0.0253 sec)
MySQL localhost:3306 ssl studentreport SQL > describe fulfillment;
+----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+----+-----+-----+-----+-----+-----+
| product_id | varchar(32) | NO | | NULL | |
| name | varchar(64) | NO | | NULL | |
| capacity | int | YES | | NULL | |
+----+-----+-----+-----+-----+-----+
3 rows in set (0.0151 sec)
MySQL localhost:3306 ssl studentreport SQL > describe fulfillmentstats;
ERROR: 1146 (42S02): Table 'studentreport.fulfillmentstats' doesn't exist
MySQL localhost:3306 ssl studentreport SQL > describe fulfillmentcentrestats;
+----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+----+-----+-----+-----+-----+-----+
| total_capacity | int | YES | | 0 | |
+----+-----+-----+-----+-----+-----+
1 row in set (0.0018 sec)

```

```

MySQL localhost:3306 ssl studentreport SQL > delimiter #
MySQL localhost:3306 ssl studentreport SQL > create trigger trig2
-> before insert (at least 2 records to verify)
-> on fulfillment
-> for each row
-> begin
-> update fulfillmentcentrestats
-> set total_capacity = total_capacity + new.capacity;
-> end #
Query OK, 0 rows affected (0.0153 sec)
MySQL localhost:3306 ssl studentreport SQL > insert into fulfillment
-> values
-> ('2001pkm0402', 'ABC', 343);
-> #
Query OK, 1 row affected (0.0144 sec)
MySQL localhost:3306 ssl studentreport SQL > delimiter ;
MySQL localhost:3306 ssl studentreport SQL > select * from fulfillmentcentrestats;
+-----+
| total_capacity |
+-----+
|          343 |
+-----+
1 row in set (0.0004 sec)
MySQL localhost:3306 ssl studentreport SQL > insert into fulfillment
-> values
-> ('2000rme0000', 'PQR', 1024);
ERROR: 1146 (42S02): Table 'studentreport.fulfillment' doesn't exist
MySQL localhost:3306 ssl studentreport SQL > insert into fulfillment
-> values
-> ('2000rme0000', 'PQR', 1024);
Query OK, 1 row affected (0.0041 sec)
MySQL localhost:3306 ssl studentreport SQL > select * from fulfillmentcentrestats;
+-----+
| total_capacity |
+-----+
|          1367 |
+-----+
1 row in set (0.0004 sec)
MySQL localhost:3306 ssl studentreport SQL > select * from fulfillment;
+-----+-----+-----+
| product_id | name | capacity |
+-----+-----+-----+
| 2001pkm0402 | ABC | 343 |
| 2000rme0000 | PQR | 1024 |
+-----+-----+-----+
2 rows in set (0.0004 sec)

```

Question 3:

```

MySQL localhost:3306 ssl institute SQL > create trigger trig3
-> before delete
-> on instructor
DELETE FROM teachers WHERE
-> for each row
-> delete from teachers
-> where id = old.id;
Query OK, 0 rows affected (0.0268 sec)

```

Question 4:

```
MySQL localhost:3306 ssl institute SQL > create trigger trig4
-> before insert
-> on instructor
-> for each row
-> set new.monthly_sal = new.monthly_sal - 200;
Query OK, 0 rows affected (0.0173 sec)
```

Question 5:

```
Query OK, 0 rows affected (0.0032 sec)
MySQL localhost:3306 ssl institute SQL > drop trigger trig3;
Query OK, 0 rows affected (0.0121 sec)
MySQL localhost:3306 ssl institute SQL > 
```