

Lab 12

Exploiting three machines (8.3 points per row; 25 total points)

Host Machines	How did you gain access?	What <u>specific</u> harm could be done?	How can you remediate it?
Reception Desktop	I found out that port 3389 (RDP) was open when I did an nmap scan on this machine in part 1. After that I basically used the "rdesktop 73.19.46.152 -u Rachel -p vanilla" command to get access to Rachel's desktop, who is one of the users. I accessed her password from part 1 of this project (which was just her cat's name). After that, I was just granted a GUI.	Since I was granted full GUI access, I was able to browse, copy, delete any sensitive documents such as HR records which contain files, that involve a person's personal information such as their name, profession and the company in which the employee works, I can install malwar, harvest user credentials, use the desktop as a pivot point in the internal network, I can also exfiltrate any confidential data such as employee records.	We can also enforce strong, unique passwords and enable account lockout policies. Next, we can basically remove RDP access for non-admin users. Other than that, we can also implement any Network Level Authentication for RDP, and also monitor any login attempts via SIEM tools. Lastly, we can also deploy any endpoint protection to detect any kind of lateral movement or malicious tools.
Clinician Desktop	When I did the nmap scan for this machine while doing the part 1 of this project I found out that FTP access was enabled since port 21 was open and it basically allowed any anonymous login. Later, I navigated through some FTP directories and figured out and downloaded some sensitive files such as passwd and shadow, which contain the list of usernames, some other metadata and hashed passwords, and then I cracked the passwords with the help of the "john" command and the rockyou.txt wordlists. Now, from these credentials, we switched users using su in a shell on the main server	I can elevate my privileges to root level ones to completely access the system and with those privileges I can basically modify and disable any services. I can also access alter or exfiltrate any sensitive information and other than that I can create persistent backdoors or user accounts.	The hospital must implement encrypted file transfers, regularly audit /etc/passwd and /etc/shadow file permissions, ensure users have strong and complex passwords, and rotate them regularly. We must also remove unused or legacy user accounts. Lastly, we must also limit the use of sudo and sudoers to restrict commands.

	and eventually we can try and escalate our privileges to root level by using sudo.		
Tom's Project	Over here also the FTP allowed anonymous access, where I found some sensitive information in shadow and passwd files. Later on, I cracked them using john, where I obtained passwords for users for users like Alice, Eve and Rachel. Using these credentials, I logged in locally and discovered that Rachel has all the sudo privileges, which allowed us to run /bin/bash as root using sudo	Firstly, all website files are hosted at /var/www/html can be altered, defaced, or backdoored. Secondly, all the MySQL database can be dumped, modified, or deleted. Lastly, any attacker can clean the logs, hide persistence mechanisms, or install rootkits.	We can remediate it by regularly rotating passwords and avoid any kind of reuse of passwords across accounts. Secondly, restrict sudo access to essential personnel only. Thirdly, we can audit web files and databases for backdoors and data exfiltration. Next, we can also harden services like Apache and MySQL and lastly monitor and alert on privilege escalation or any suspicious command execution.

Sensitive information (8.3 points per row; 25 total points)

Host Machines	What information I found, and why it's bad that I can see it.
Reception Desktop	Over here, I found a folder named HR records on the user's desktop. It basically contained multiple .contact files which are XML-formatted address book entries. After inspection, I found out that each file revealed highly sensitive personal information such as full names, email addresses, home and work physical addresses, job titles, dates of birth and anniversaries and phone numbers as well. This kind of data can be used for identity theft, social engineering, phishing, and impersonating in targeted attacks.
Clinician Desktop	Over here, this machine basically allowed us to download /etc/passwd and /etc/shadow and these files basically contain a list of all system users, password hashes, and metadata about user accounts. Once I cracked the hashes using john and rockyou.txt, I recovered passwords of the actual users such as Rachel, Alice and Eve. This is some critical information because it enables some unauthorized login and impersonation, credentials could be reused across machines, password reuse exposes more systems and Rachel's account had root access and granted full system control
Tom's Project	Once I gained root access on Tom's project machine, I discovered /var/www/html contained login.php, connect.php, and other frontend/backend files with hardcoded database credentials. A file named flat-ui-login.php included more legacy web UI code that would expose passwords or user management interfaces. It also exposed the Apache server configuration. It is critical because hardcoded credentials are often reused, source code could be analyzed for any web vulnerabilities, and configs may expose internal IPs or keys. It also helps in exposing backend code, since it creates a path to full web server compromise, or even pivot into a database.

Remediation (8.3 points per row; 25 total points)

Host Machines	Vulnerabilities, misconfigurations, sensitive information disclosures, malpractices	Does the issue need to be fixed? Why, or why not?	If actions were taken, how did you remediate it
Reception Desktop	The RDP is exposed to the public network. I also spotted some weak or reused credentials for access. There is no multi-factor authentication and sensitive HR data is stored on the desktop in plaintext .contact files, and it does not have any encryption or access control on sensitive directories	Yes, the issue needs to be fixed over here. Open RDP with weak credentials is an attack vector for ransomware. It also exposes some personal information since it violates privacy laws, and lastly, we don't have any security layering (like firewalls), which should not be accepted for any system handling the HR data.	Firstly, the rdp must be disabled or accessed via vpn or internal networks only. Secondly, we should enforce strong, unique passwords and implement multi factor authentication, then we move HR records to a secure access controlled location and apply group policies to restrict who can rdp into the system and lastly we should also enable logging and auditing of rdp sessions.
Clinician Desktop	Over here basically the first point would be that the Ftp service allowed anonymous login, moreover the /etc/shadow and /etc/passwd were readable via ftp which is a severe misconfiguration. I also found some weak passwords and the use of some default system users. Other than that, I figured out that any service could be accessed externally, which is a major issue as well. Lastly, it was very easy for me to crack the passwords since they were commonly used by the users.	Yes, at least the anonymous ftp login must be removed immediately, since we are allowing access to critical systems files which definitely poses a compromise risk. The passwords were reused and there was a lack of access control which is a major vulnerability.	We must disable anonymous ftp access in the configuration file (vsftpd.conf). Secondly, I updated the file permissions to restrict access for /etc/shadow and /etc/passwd. Next, I removed and reset all the passwords that I cracked. Other than that I used the audited user accounts and deleted any unused or default ones. In the end, I just replaced ftp with a SFTP or SCP.
Tom's Project	Over here the anonymous ftp again allowed access to password hashes. Secondly, Rachel had the full sudo access with no restrictions. Thirdly, I	Yes, the issues must be fixed over here since by looking at the vulnerabilities we found over here, I can say that the system has used some	The first thing that I did was to remove Rachel from the sudoers file and limited administrative accounts. Next, I deleted the legacy and unused web files, then I

	figured out that web server had hardcoded credentials in PHP files. The users could also access the APACHE configurations and web files which is another security vulnerability. Lastly, the file flat-ui-login.zip contained some legacy login systems which were possibly outdated or vulnerable.	insecure coding practices, it contains some misconfigured services and file configurations and it also has a weak privilege separation. These are some major things since they can gain root level privileges very easily and it can compromise any connected web services or databases.	basically reset all the user passwords and reviewed the Apache configuration and removed public access to sensitive web files. Lastly, it disabled anonymous Ftp and enforced minimal access principles.
--	---	--	--

Be specific in what you find, being vague will get you 0 points.

Host IP	1.) What was accessed? 2.) How was it accessed? 3.) What was the impact of the incident? 4.) How did you respond to the incident? 5.) Screenshot of what was accessed
73.19.46.150	1) I accessed the website source code through files like index.php, login.php and connect.php. I was also able to access configuration files which contain hardcoded database credentials and later through the flat-ui-login.zip, I was able to access the web interface with a possible legacy login system. 2) I was able to gain root access via cracked credentials and sudo privilege escalation and then later, I navigated to /var/www/html using terminal. In the end just used cat, less and ls to inspect files. 3) I was able to expose database credentials could allow access to medical records or any backend systems, the malware and webshells could be implanted and fully compromise any publicly accessible server 4) I basically documented all findings and file locations. I also suggested removal of hardcoded credentials and recommended security audit of the entire web application and in the end I suggested using environment variables for sensitive data.

```

root@surprise:/root# ls -la /var/www/html
total 84
drwxr-xr-x 5 root root 4096 Apr 15 2024 .
drwxr-xr-x 3 root root 4096 Oct 14 2017 ..
-rw-r--r-- 1 root root 250 Oct 15 2017 action.php
-rw-r--r-- 1 root root 1028 Oct 15 2017 changepassword.php
-rw-r--r-- 1 root root 724 Oct 15 2017 changeusername.php
-rwxrwxrwx 1 root root 63 Oct 15 2017 comments.txt
-rw-r--r-- 1 root root 856 Oct 14 2017 connect.php
-rw-r--r-- 1 root root 207 Oct 14 2017 create_table.mysql
drwxr-xr-x 2 root root 4096 Oct 15 2017 css
-rw-r--r-- 1 root root 1126 Oct 15 2017 editprofile.php
-rw-r--r-- 1 root root 3361 Oct 14 2017 flat-ui-login.zip
-rw-r--r-- 1 root root 911 Oct 15 2017 index.html
-rw-r--r-- 1 root root 252 Apr 15 2024 insert.mysql
drwxr-xr-x 2 root root 4096 Oct 15 2017 js
-rw-r--r-- 1 root root 1109 Oct 14 2017 license.txt
-rw-r--r-- 1 root root 431 Oct 14 2017 login.php
-rw-r--r-- 1 root root 77 Oct 15 2017 logout.php
-rw-r--r-- 1 root root 857 Oct 15 2017 profile.php
-rw-r--r-- 1 root root 240 Oct 14 2017 README.txt
drwxr-xr-x 2 root root 4096 Oct 14 2017 scss
-rw-r--r-- 1 root root 103 Oct 14 2017 vars.inc

```

```

root@surprise:/root# ss -tulnp
Netid State  Recv-Q Send-Q           Local Address:Port      Peer Address:Port
udp    UNCONN 0        0           127.0.0.53%lo:53         0.0.0.0:*
users:((("systemd-resolve",pid=538,fd=12))
udp    UNCONN 0        0           73.19.46.175%ens18:68    0.0.0.0:*
users:((("systemd-network",pid=527,fd=19))
tcp    LISTEN 0        80           0.0.0.0:3306             0.0.0.0:*
users:((("mysqld",pid=1477,fd=28))
tcp    LISTEN 0       128           0.0.0.0:80              0.0.0.0:*
users:((("apache2",pid=19812,fd=3),("apache2",pid=19803,fd=3),("apache2",pid=
17132,fd=3),("apache2",pid=17131,fd=3),("apache2",pid=17130,fd=3),("apache2",
pid=17129,fd=3),("apache2",pid=17128,fd=3),("apache2",pid=1481,fd=3))
tcp    LISTEN 0       128           0.0.0.0:14580           0.0.0.0:*
users:((("sshd",pid=1823,fd=3))
tcp    LISTEN 0       128           127.0.0.53%lo:53         0.0.0.0:*
users:((("systemd-resolve",pid=538,fd=13))
tcp    LISTEN 0         1           0.0.0.0:1337            0.0.0.0:*
users:((("nc",pid=19873,fd=3))
tcp    LISTEN 0       100           0.0.0.0:25              0.0.0.0:*
users:((("master",pid=1644,fd=13))
tcp    LISTEN 0       128           0.0.0.0:27017           0.0.0.0:*
users:((("mongod",pid=1005,fd=11))
tcp    LISTEN 0         64              *:79                    *:79
users:((("xinetd",pid=1345,fd=5))
tcp    LISTEN 0       128           [::]:14580              [::]:*

```

```

root@surprise:/root# ps aux
USER      PID %CPU %MEM    VSZ   RSS TTY      STAT START   TIME COMMAND
root         1  0.0  0.8 159860 8548 ?        Ss   Nov17    0:52 /sbin/init
root         2  0.0  0.0      0     0 ?        S    Nov17    0:00 [kthreadd]
root         4  0.0  0.0      0     0 ?        I<   Nov17    0:00 [kworker/0:0
root         6  0.0  0.0      0     0 ?        I<   Nov17    0:00 [mm_percpu_w
root         7  0.0  0.0      0     0 ?        S    Nov17    0:07 [ksoftirqd/0
root         8  0.0  0.0      0     0 ?        I    Nov17    0:35 [rcu_sched]
root         9  0.0  0.0      0     0 ?        I    Nov17    0:00 [rcu_bh]
root        10  0.0  0.0      0     0 ?        S    Nov17    0:00 [migration/0
root        11  0.0  0.0      0     0 ?        S    Nov17    0:02 [watchdog/0]
root        12  0.0  0.0      0     0 ?        S    Nov17    0:00 [cpuhp/0]
root        13  0.0  0.0      0     0 ?        S    Nov17    0:00 [kdevtmpfs]
root        14  0.0  0.0      0     0 ?        I<   Nov17    0:00 [netns]
root        15  0.0  0.0      0     0 ?        S    Nov17    0:00 [rcu_tasks_k
root        16  0.0  0.0      0     0 ?        S    Nov17    0:00 [kauditd]
root        17  0.0  0.0      0     0 ?        S    Nov17    0:00 [khungtaskd]
root        18  0.0  0.0      0     0 ?        S    Nov17    0:00 [oom_reaper]
root        19  0.0  0.0      0     0 ?        I<   Nov17    0:00 [writeback]
root        20  0.0  0.0      0     0 ?        S    Nov17    0:00 [kcompactd0]
root        21  0.0  0.0      0     0 ?        SN   Nov17    0:00 [ksmd]
root        22  0.0  0.0      0     0 ?        SN   Nov17    0:21 [khugepaged]
root        23  0.0  0.0      0     0 ?        I<   Nov17    0:00 [crypto]
root        24  0.0  0.0      0     0 ?        I<   Nov17    0:00 [kintegrityd
root        25  0.0  0.0      0     0 ?        I<   Nov17    0:00 [kblockd]
root        26  0.0  0.0      0     0 ?        I<   Nov17    0:00 [ata_sff]

```

```

5277/systemd-network
root@surprise:/root# which apache2
/usr/sbin/apache2
root@surprise:/root# which httpd
root@surprise:/root# which nginx
root@surprise:/root# ps aux | grep -Ei 'apache|httpd|nginx'
root      1481  0.0  2.5 260444 25920 ?        Ss   Nov17    0:32 /usr/sbin/ap
ache2 -k start
www-data  1502  0.0  0.0 199904 176 ?        Ss   Nov17    0:22 /usr/bin/htc
ache2clean -d 120 -p /var/cache/apache2/mod_cache_disk -l 300M -n
www-data  17128  0.0  1.1 264904 11580 ?        S    06:25    0:00 /usr/sbin/ap
ache2 -k start
www-data  17129  0.0  1.1 264904 11536 ?        S    06:25    0:00 /usr/sbin/ap
ache2 -k start
www-data  17130  0.0  1.1 264904 11528 ?        S    06:25    0:00 /usr/sbin/ap
ache2 -k start
www-data  17131  0.0  1.1 264904 11532 ?        S    06:25    0:00 /usr/sbin/ap
ache2 -k start
www-data  17132  0.0  1.1 264904 11528 ?        S    06:25    0:00 /usr/sbin/ap
ache2 -k start
www-data  19803  0.0  1.1 264896 11532 ?        S    13:53    0:00 /usr/sbin/ap
ache2 -k start
www-data  19812  0.0  1.1 264896 11540 ?        S    13:53    0:00 /usr/sbin/ap
ache2 -k start
root      22952  0.0  0.1 13136 1012 pts/0    S+   22:09    0:00 grep --color

```

```

root@surprise:/root# systemctl list-units --type=service
UNIT                                LOAD    ACTIVE SUB    DESCRIPTION
accounts-daemon.service            loaded active running Accounts Service
apache-htcacheclean.service        loaded active running Disk Cache Cleaning Daemon
apache2.service                    loaded active running The Apache HTTP Server
apparmor.service                   loaded active exited AppArmor initialization
apport.service                     loaded active exited LSB: automatic crash repor
atd.service                        loaded active running Deferred execution schedul
blk-availability.service            loaded active exited Availability of block devi
console-setup.service              loaded active exited Set console font and keyma
cron.service                       loaded active running Regular background program
dbus.service                       loaded active running D-Bus System Message Bus
ebtables.service                   loaded active exited ebtables ruleset managemen
evil.service                       loaded active running netcat fun things
getty@tty1.service                 loaded active running Getty on tty1
grub-common.service                loaded active exited LSB: Record successful boo
inetutils-inetd.service            loaded active exited LSB: inetd sysv init scrip
keyboard-setup.service             loaded active exited Set the console keyboard l
kmod-static-nodes.service          loaded active exited Create list of required st
lvm2-lvm2metad.service             loaded active running LVM2 metadata daemon
lvm2-monitor.service              loaded active exited Monitoring of LVM2 mirrors
lxcfs.service                      loaded active running FUSE filesystem for LXC
lxd-containers.service             loaded active exited LXD - container startup/sh
mongodb.service                   loaded active running An object/document-oriente

```

```

root@surprise:/root# curl -I http://localhost
HTTP/1.1 500 Internal Server Error
Server: squid/4.10
Mime-Version: 1.0
Date: Mon, 01 Dec 2025 04:12:21 GMT
Content-Type: text/html; charset=utf-8
Content-Length: 3819
X-Squid-Error: ERR_CANNOT_FORWARD 0
Vary: Accept-Language
Content-Language: en
X-Cache: MISS from keyhole1
X-Cache-Lookup: MISS from keyhole1:3128
Via: 1.1 keyhole1 (squid/4.10)
Connection: keep-alive

```

73.19.46.158

- 1) I was able to access the passwd and shadow files obtained and cracked multiple user credentials such as alice, rachel etc.
- 2) Since the Ftp service was open and allowed any autonomous login, I used it to download system files and cracked hashes offline using john and rockyou.txt.
- 3) Firstly, the credential reuse across systems enabled lateral movement. Then, I figured out that Rachel had full root access and I also found out that could also allow installation of malware or unauthorized services. I also found out that some sensitive information were exposed.
- 4) First I removed disabled the anonymous login through FTP. I also recommended rotating all users' passwords and restricting access to admins only. Later, I also started using encrypted transfer protocols to secure the hospital's network.

```

backdoor:x:0:0:haha,,,:/root:/bin/bash
bob:x:1001:1002:,,,:/home/bob:/bin/bash
alice:x:1003:1003:,,,:/home/alice:/bin/bash
alex:x:1004:1004:,,,:/home/alex:/bin/bash
eve:x:1005:1005:,,,:/home/eve:/bin/bash
sshd:x:110:65534:/:var/run/sshd:/usr/sbin/nologin
telnetd:x:111:117:/:nonexistent:/bin/false
mongodb:x:112:65534:/:var/lib/mongodb:/bin/false
ftp:x:113:120:ftp daemon,,:/srv/ftp:/bin/false
mysql:x:114:121:MySQL Server,,:/nonexistent:/bin/false
postfix:x:115:122:/:var/spool/postfix:/bin/false
landscape:x:103:105:/:var/lib/landscape:/usr/sbin/nologin
pollinate:x:116:1:/:var/cache/pollinate:/bin/false
cpre231:x:1006:1007:Jenny,,867-5309,:/home/cpre231:/bin/bash
rachel:x:1007:1008:Rachel,,,:My cat's name is my password. I reuse passwords
./home/rachel:/bin/bash
cindy:x:1008:1009:Cindy Rizen,,,:my dog rulez:/home/cindy:/bin/bash

```

```

(cpre2310@kali)-[~]
$

```

(cat passwd)

```

$ cat shadow
root!:17394:0:99999:7:::
daemon*:17001:0:99999:7:::
bin*:17001:0:99999:7:::
sys*:17001:0:99999:7:::
sync*:17001:0:99999:7:::
games*:17001:0:99999:7:::
man*:17001:0:99999:7:::
lp*:17001:0:99999:7:::
mail*:17001:0:99999:7:::
news*:17001:0:99999:7:::
uucp*:17001:0:99999:7:::
proxy*:17001:0:99999:7:::
www-data*:17001:0:99999:7:::
backup*:17001:0:99999:7:::
list*:17001:0:99999:7:::
irc*:17001:0:99999:7:::
gnats*:17001:0:99999:7:::
nobody*:17001:0:99999:7:::
systemd-timesync*:17001:0:99999:7:::
systemd-network*:17001:0:99999:7:::
systemd-resolve*:17001:0:99999:7:::
syslog*:17001:0:99999:7:::
_apt*:17001:0:99999:7:::
lxd*:17394:0:99999:7:::
messagebus*:17394:0:99999:7:::

```

(cat shadow)


```

alice@surprise:~$
alice@surprise:~$ su rachel
Password:

/ Are you ever going to do the dishes? Or \
\ will you change your major to biology? /

      ^ _ ^
      (oo)\_____/
      (_____\  )\/\
           ||----w |
           ||     ||

rachel@surprise:/home/alice$ sudo -l
[sudo] password for rachel:
Matching Defaults entries for rachel on surprise:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

```

```

Matching Defaults entries for rachel on surprise:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin

User rachel may run the following commands on surprise:
    (ALL : ALL) ALL
rachel@surprise:/home/alice$ sudo /bin/bash

/ Small things make base men proud. -- \
\ William Shakespeare, "Henry VI" /

      ^ _ ^
      (oo)\_____/
      (_____\  )\/\
           ||----w |
           ||     ||

root@surprise:/home/alice# uname -a
Linux surprise 4.15.0-58-generic #64-Ubuntu SMP Tue Aug 6 11:12:41 UTC 2019 x
86_64 x86_64 x86_64 GNU/Linux
root@surprise:/home/alice# find / -perm -4000 -type f 2>/dev/null
/bin/ping
/bin/su
/bin/umount
/bin/mount
/bin/fusermount

```

73.19.46.175

- 1) I first accessed all the ftp files, passwd, and cracked user credentials. Next, I tried to gain full root access of the system via sudo, then I also accessed the Apache server content in /var/www/html and the potential sensitive app data and MySQL credentials.

- 2) I basically started by trying log in to the system by using anonymous Ftp login, then I basically cracked user passwords using john and later from there i switched to Alice, and then Rachel, where I figured out the users who had the sudo permissions. I also used sudo /bin/bash to gain a root shell over here.
- 3) The system was totally compromised, that is, anyone had the right to read/write and edit capabilities. Secondly, the websites could be manipulated easily and exfiltrated as well. The attack could be pivoted to internal services and databases and I got ownership of all users and processes.
- 4) I revoked Rachel's sudo privileges, removed all unused or legacy users and later I suggested rotating all the passwords and review logs for intrusion.

```
(cpre2310@kali)-[~]
$ ftp 73.19.46.175
Connected to 73.19.46.175.
220 Better Hack Yourself before you Wreck Yourself!
Name (73.19.46.175:cpre2310): anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> ls
229 Entering Extended Passive Mode (|||20581|)
150 Here comes the directory listing.
drwxr-xr-x 102 0      0      12288 Apr 15  2024 fun_files
drwxrwxrwx  3 0      0      4096 Oct 14  2017 hacks_here
drwxrwxrwx  2 0      0      4096 Oct 14  2017 irc_chat_here_too
drwxrwxrwx  2 0      0      4096 Oct 14  2017 vulns_here
drwxr-xr-x 23 0      0      4096 Aug 17  2019 whats_in_here
226 Directory send OK.
ftp> cd 2024 fun_files
usage: cd remote-directory
ftp> ls
229 Entering Extended Passive Mode (|||33547|)
150 Here comes the directory listing.
```

```
(cpre2310@kali)-[~]  
$ rdesktop 73.19.46.152 -u Rachel -p vanilla  
Autoselecting keyboard map 'en-us' from locale
```

ATTENTION! The server uses and invalid security certificate which can not be trusted for the following identified reasons(s);

1. Certificate issuer is not trusted by this system.

Issuer: CN=DESKTOP-T9L6G94

Review the following certificate info before you trust it to be added as an exception.

If you do not trust the certificate the connection attempt will be aborted:

Subject: CN=DESKTOP-T9L6G94
Issuer: CN=DESKTOP-T9L6G94
Valid From: Tue Aug 26 02:37:00 2025
To: Wed Feb 25 01:37:00 2026

Certificate fingerprints:

Name	Date modified	Type	Size
Annie M Gurney	20/03/2021 09:05 ...	Contact file	2 KB
Caroll D Smith	20/03/2021 09:03 ...	Contact file	4 KB
Charles R Schwartz	20/03/2021 09:03 ...	Contact file	3 KB
Erma S Brown	20/03/2021 09:07 ...	Contact file	3 KB
John C Hawkins	20/03/2021 09:04 ...	Contact file	3 KB
Maurice K Gordon	20/03/2021 09:09 ...	Contact file	3 KB
Rachel K Fischer	20/03/2021 09:09 ...	Contact file	3 KB
Richard L McCollough	20/03/2021 09:05 ...	Contact file	2 KB
Rita S Dexter	20/03/2021 09:07 ...	Contact file	3 KB
Robert D Dewees	20/03/2021 09:03 ...	Contact file	4 KB
Sam K Baker	20/03/2021 09:04 AM	Contact file	3 KB
Santiago D. Butcher	20/03/2021 09:05 ...	Contact file	2 KB
Shane U Rye	20/03/2021 09:04 ...	Contact file	3 KB
Shelly D Miller	20/03/2021 09:03 ...	Contact file	3 KB
Susan E Foster	20/03/2021 09:03 ...	Contact file	4 KB
Thomas E Buffer	20/03/2021 09:03 ...	Contact file	3 KB
Tony McClaire	20/03/2021 09:03 ...	Contact file	3 KB
Vega Blanco	20/03/2021 09:07 ...	Contact file	3 KB
Warren G Buffet	20/03/2021 09:04 ...	Contact file	3 KB
Will H Sloane	20/03/2021 09:07 ...	Contact file	3 KB
William H Chang	20/03/2021 09:03 ...	Contact file	3 KB

21 items | State: Shared

Caroll Dean Smith Properties ? X

Summary Name and Email Home Work Family Notes IDs

Name: Caroll Dean Smith

Email: smith.caroll@generalhospital.com

Work

Company: General Hospital

Job Title:

Phone:

Website:

Home

Phone: 949-395-2144

Mobile: 949-395-2144

Website:

Add to my contacts

OK Cancel

