

MAINTENANCE WORK ORDER

WO Number: WO-2026-0142

Date Issued: 2026-06-15

Facility: Riverside Processing Plant - Unit 3

Equipment: Pump P-102

Assigned Technician: S. Iyer

Priority: Routine

1. TASK DESCRIPTION

Pump P-102 is used to transfer sodium hypochlorite between the bulk storage tank and the dosing system. This work order covers the scheduled flush and mechanical seal inspection of P-102. Before beginning, review the sodium hypochlorite Safety Data Sheet and follow all specified handling precautions, including the required personal protective equipment. Drain and flush the pump to remove residual sodium hypochlorite, then inspect the mechanical seal for signs of corrosion consistent with hypochlorite exposure. Record any wear and replace the seal if degradation is found.

2. SAFETY NOTES

Sodium hypochlorite is corrosive and causes severe skin burns and eye damage. Wear protective eyewear and rubber gloves when handling. Ensure adequate ventilation in the work area. Do not mix with acids or ammonia-based cleaners. In case of contact, flush the affected area with water and refer to the Safety Data Sheet first-aid measures.