

FLEXIBLE CONDUIT FITTINGS (BRASS)

PART CODE	F543BRSNOD
DESCRIPTION	CONDUIT FITTINGS FOR FLAME RETARDANT PVC COATED FLEXIBLE
MATERIAL	BRASS
FINISH	NICKEL PLATED
PRODUCT FEATURES	NO HAZARDOUS SHARP EDGES OR BURRS SMOOTH INSIDE FOR EASIER WIRE PULLING CONFORMS TO BS EN 61386-23 GENERAL PURPOSE APPLICATION, IP 54 RATING CORROSION, ABRASION, OIL AND WATER RESISTANT

Ordering Code	Conduit Size (BS) (mm)	Thread Size (mm)	Thread Diameter (mm)	Minimum Bore (mm)	Across Flats (mm)	Thread Length (mm)	Nominal Length (mm)
F543BRSNOD2020	20	20.0	20.0	14.8	24.0	10.0	24.5
F543BRSNOD2525	25	25.0	25.0	18.8	30.0	12.0	28.0
F543BRSNOD3232	32	32.0	32.0	25.8	36.0	13.0	29.0
F543BRSNOD4040	40	40.0	40.0	33.8	46.0	15.0	31.5
F543BRSNOD5050	50	50.0	50.0	41.8	55.0	15.0	33.0



IP RATING WITH RECOMMENDED CONDUIT

IP 54

OPERATING TEMPERATURE

- 25 TO + 90° C.

Our policy is one of continuous product improvement.
We reserve the right to revise designs and specifications without prior notice.

EXCLUSIVELY AVAILABLE AT



Jebel Ali Free Zone, PO BOX 263871
Dubai, UAE

E: sales.lbs@libertyhg.com W: www.libertybuildingsolutions.com
T: +971 4 886 4344

PROVEN PRODUCTS
PREMIUM QUALITY
INDUSTRY STANDARD SPECIFICATION
WORLDWIDE CUSTOMER SUPPORT

