

FLEXIBLE CONDUIT FITTINGS (ZINC)

PART CODE	F543ZNCNOD
DESCRIPTION	CONDUIT FITTINGS FOR FLAME RETARDANT PVC COATED FLEXIBLE
MATERIAL	ZINC
FINISH	NICKEL PLATED
PRODUCT FEATURES	NO HAZARDOUS SHARP EDGES OR BURRS SMOOTH INSIDE FOR EASIER WIRE PULLING CONFORMS TO BS EN 61386-23 PRE-PACKAGED WITH A LOCKNUT GENERAL PURPOSE APPLICATION, IP 54 RATING CORROSION, ABRASION, OIL AND WATER RESISTANT

Ordering Code	Conduit Size (BS) (mm)	Thread Size (mm)	Thread Diameter (mm)	Minimum Bore (mm)	Across Flats (mm)	Thread Length (mm)	Nominal Length (mm)
F543ZNCNOD2020	20	20.0	20.0	14.8	24.0	10.0	24.5
F543ZNCNOD2525	25	25.0	25.0	18.8	30.0	12.0	28.0
F543ZNCNOD3232	32	32.0	32.0	25.8	36.0	13.0	29.0
F543ZNCNOD4040	40	40.0	40.0	33.8	46.0	15.0	31.5
F543ZNCNOD5050	50	50.0	50.0	41.8	55.0	15.0	33.0



IP RATING WITH RECOMMENDED CONDUIT

IP 54

OPERATING TEMPERATURE

- 25 TO + 90° C.

Our policy is one of continuous product improvement.

We reserve the right to revise designs and specifications without prior notice.

EXCLUSIVELY AVAILABLE AT



Jebel Ali Free Zone, PO BOX 263871

Dubai, UAE

E: sales.lbs@libertyhg.com W: www.libertybuildingsolutions.com

T: +971 4 886 4344

PROVEN PRODUCTS

PREMIUM QUALITY

INDUSTRY STANDARD SPECIFICATION

WORLDWIDE CUSTOMER SUPPORT

