```
In [1]: import math
        class LehmerRandomNumberGenerator:
            This class is responsible for generating uniformly distributed random numbers
            on the interval (0, 1)
            def __init__(self, seed: int, modulus: int, multiplier: int):
                The constructor of the class
                :param seed: the seed to start with
                :param modulus: the modulus value
                :param multiplier: the multiplier
                self.last_value = seed
                self.modulus = modulus
                self.multiplier = multiplier
            def next(self) -> float:
                Returns the next random number in the sequence
                :return:
                self.last_value = (self.multiplier * self.last_value) % self.modulus
                return self.last_value / self.modulus
        def find_period_multiplier(modulus: int) -> int:
            Finds a full-period multiplier for the given modulus
            :param modulus: the modulus to check
            :return: a full-period multiplier
            a = 1
            while True:
                p = 1
                x = a
                while x != 1:
                    p += 1
                    x = (a * x) % modulus
                if p == modulus - 1:
                    print("{} is a full period multiplier\n".format(a))
                    return a
                a += 1
        def find_all_multipliers(modulus: int, multiplier: int = None) -> list:
            Finds all full-period multiplier for the given modulus and a multiplier
            :param modulus: the modulus to check
            :param multiplier: the multiplier to start with
            :return: a list of all full-period multipliers
            if multiplier is None:
                multiplier = find_period_multiplier(modulus)
            i = 1
            x = multiplier
            multipliers = []
            while \times != 1:
                if math.gcd(i, modulus - 1) == 1:
                   multipliers.append(x)
                i += 1
                x = (multiplier * x) % modulus
            multipliers.sort()
            return multipliers
        if __name__ == '__main__':
            mod = 251
            multiplier_list = find_all_multipliers(mod)
            print("Found {} Period Multipliers of {}:".format(len(multiplier_list), mod))
            for m in multiplier_list:
                print(m)
```

6 is a full period multiplier

```
Found 100 Period Multipliers of 251:
11
14
18
19
24
26
29
30
33
34
37
42
43
44
46
53
54
55
56
57
59
61
62
70
71
72
76
77
78
82
87
90
95
96
97
98
104
107
109
111
116
120
127
129
130
132
133
134
136
137
139
141
143
145
146
148
150
158
159
162
163
165
166
167
168
170
172
176
177
178
183
184
185
186
```

| | 199 | |
|---------|-----|--|
| | 202 | |
| | 203 | |
| | 206 | |
| | 210 | |
| | 212 | |
| | 213 | |
| | 215 | |
| | 216 | |
| | 220 | |
| | 223 | |
| | 224 | |
| | 228 | |
| | 229 | |
| | 230 | |
| | 234 | |
| | 236 | |
| | 238 | |
| | 239 | |
| | 242 | |
| | 244 | |
| | 248 | |
| In []: | | |
| | | |
| In []: | | |
| | | |
| In []: | | |
| | | |