

A3 — Data and Query Design

Team 16 · Private Wellbeing Intake & Booking (Pod 4, Student Support — University Digital Campus Platform)

Team members

No.	Student ID	Name
1	6731503011	Dechawat Wetprasit
2	6731503014	Thiraphot Punkham
3	6731503015	Teerapat Sukkasem
4	6731503018	Nithanthip Kulmong
5	6731503019	Nithikorn Suttanu

Project

Repository	https://github.com/TEERAPAT-SUKKASEM/wellbeing-intake
Database	Supabase (managed PostgreSQL 17)
Schema source	supabase/migrations/ — two versioned SQL migrations
API contract	openapi.yaml — OpenAPI 3.1, 21 operations under <code>/api/v1</code>
Examples captured	2026-09-20, from the running application against seeded demo data only


All data in this document is fictional seed data. No real student record exists anywhere in the project (PRD C-11, BR-18).

1. What the database has to do

Students privately request a campus health, counselling or wellbeing service, receive safe urgency guidance, and book a confirmed time slot. The data is sensitive, so the database design is driven by four requirements rather than by screens:

1. **Privacy** — request content is visible only to the student who wrote it and to practitioners of the one service it was sent to. Every such view is audited.
2. **Integrity under concurrency** — two students can never hold the same slot, even if they click at the same millisecond.
3. **Immutability** — what a student submitted can never be edited afterwards; history tables are append-only.
4. **Reliable messaging** — reminder events to the Notification Hub (Team 20) must never be lost and must never carry sensitive content.

3. ER diagram



`INBOUND_EVENT` and `AI_CALL_BUDGET` are operational tables with no relationships. `OUTBOUND_EVENT` is deliberately foreign-key-free: it is a transactional outbox whose rows must outlive, and reveal nothing about, the records they refer to.

4. Database schema

Full DDL: [20260920000001_schema.sql](#) (tables, indexes, triggers, RLS) and [20260920000002_functions.sql](#) (13 transactional functions).

4.1 Tables

Table	Purpose	Key constraints
<code>triage_level</code>	The three fixed urgency levels	Sealed: a trigger rejects every <code>INSERT / UPDATE / DELETE</code> after seeding
<code>service</code>	Public service catalogue	<code>slug</code> unique
<code>app_user</code>	Minimal user record (5 fields + FK)	<code>identity_ref</code> unique; <code>role</code> check; <code>CHECK ((role = 'practitioner') = (service_id IS NOT NULL))</code>
<code>request</code>	A student's private request	Length checks; <code>status</code> check; <code>submission_key</code> unique (a double-click creates one request); immutable-content trigger
<code>request_status_change</code>	Who changed status, when	Append-only trigger
<code>slot</code>	A practitioner's offered time	<code>UNIQUE (practitioner_id, start_at)</code> ; "open" is derived, never stored
<code>appointment</code>	A booking	Two partial unique indexes (below)
<code>audit_event</code>	One row per content view	Append-only ; holds no content
<code>outbound_event</code>	Transactional outbox to Team 20	<code>UNIQUE (reference, type)</code> ; <code>CHECK</code> allowlisting payload keys
<code>inbound_event</code>	Delivery receipts from Team 20	Primary key on <code>event_id</code> makes retries idempotent
<code>ai_call_budget</code>	Daily cap for the AI helper	One row per day

All foreign keys are `ON DELETE RESTRICT` — nothing is ever silently cascaded away.

4.2 The three constraints that matter most

No double booking — decided by the storage engine, not by application code:

```
create unique index appointment_one_active_per_slot    on appointment (slot_id)    where status = 'confirmed';
create unique index appointment_one_active_per_request on appointment (request_id) where status = 'confirmed';
```

Because the indexes are *partial*, a cancelled appointment stops occupying the slot immediately, while two concurrent confirmed inserts on one slot can never both commit. Our integration suite fires two parallel bookings at one slot and asserts exactly one 201 and one 409.

Request content is frozen at submission:

```
create trigger request_immutable_content before update on request
  for each row execute function request_content_immutable();
-- raises 'request content is immutable' if any column other than status differs
```

Deny-all Row Level Security — the backstop if the API layer ever has a bug:

```
alter table request enable row level security;          -- ...on all 11 tables, with ZERO policies
revoke all on all tables in schema public from anon, authenticated;
```

4.3 Indexes designed from the queries

Query	Index
Practitioner queue: one service, most urgent first, then oldest first	request_queue_idx (service_id, triage_level_id DESC, submitted_at ASC)
"My requests", newest first	request_student_idx (student_id, submitted_at DESC)
Latest status change for a request	request_status_change_request_idx (request_id, changed_at DESC)
A student's appointments	appointment_student_idx (student_id)
Outbox dispatcher: only rows still pending	outbound_event_pending_idx (next_attempt_at) WHERE delivered_at IS NULL AND failed_at IS NULL

4.4 Query design: multi-step operations are single transactions

Every operation that touches more than one row is a PL/pgSQL function called through Supabase RPC, so it either fully happens or does not happen at all.

Function	What happens atomically
create_request	Insert request + first history row; a repeated submission_key returns the original
read_request_content	Write the audit row , move submitted → in_review on first read, then return content — the only path that returns content to a non-owner
update_request_status	Validate the fixed lifecycle, update, append history
book_appointment	Lock request and slot (FOR UPDATE), check ownership / service / status / urgency / server clock, insert appointment, mark request handled , append history
cancel_appointment	Cancel, free the slot, neutralise any pending reminder and enqueue a retraction
enqueue_due_reminders , claim_outbound_events , mark_outbound_*	Outbox: enqueue once, lease rows to a dispatcher, record delivery or back-off

Function	What happens atomically
<code>remove_slot, record_inbound_event, consume_ai_budget, reset_demo_data</code>	Supporting operations

Example — the core of `book_appointment`:

```
select * into v_req  from request where id = p_request for update;
select * into v_slot from slot    where id = p_slot    for update;
-- ...ownership, same-service, status = 'in_review', not urgent, start_at > now()...
begin
  insert into appointment (request_id, slot_id, student_id) values (v_req.id, v_slot.id, p_student)
  returning id into v_appt;
exception when unique_violation then
  return jsonb_build_object('code', 'slot_taken');    -- the partial unique index decided the race
end;
update request set status = 'handled' where id = v_req.id;
insert into request_status_change (request_id, new_status, actor_id) values (v_req.id, 'handled',
p_student);
```

5. Migration and deployment to the remote database

The schema exists only as versioned migration files; no table was ever created by hand.

```
# Local (Docker) – also what CI does on every push
pnpm db:start                # supabase start: applies supabase/migrations to a fresh Postgres
pnpm seed                    # loads demo fixtures

# Remote (hosted Supabase project)
pnpm exec supabase login
pnpm exec supabase link --project-ref jtwrgfcmfghfklddyatv
pnpm exec supabase db push    # applies the same two migrations to the remote database
pnpm seed                    # with SUPABASE_URL / keys pointing at the remote project
```

The migrations also apply cleanly to a fresh database on every CI run, and the full integration suite (53 tests) passes against the result — [CI run 35502866601](#).

5.1 Remote deployment evidence (captured 2026-09-20)

Item	Value
Supabase project	ref <code>jtwrgfcmfghfklddyatv</code> — Free plan
Region	<code>ap-southeast-1</code> (Southeast Asia, Singapore)
Database	PostgreSQL 17.6 — same major version as local and CI
Project URL	<code>https://jtwrgfcmfghfklddyatv.supabase.co</code>
Migrations pushed	<code>20260920000001_schema, 20260920000002_functions</code>

supabase db push — real output:

```
Connecting to remote database...
Do you want to push these migrations to the remote database?
• 20260920000001_schema.sql
• 20260920000002_functions.sql
[Y/n] y
Applying migration 20260920000001_schema.sql...
Applying migration 20260920000002_functions.sql...
Finished supabase db push.
```

supabase migration list — local and remote are in sync:

Local	Remote
20260920000001	20260920000001
20260920000002	20260920000002

Row counts on the remote database after `pnpm seed` (queried through the REST API with the server-only service-role key):

Table	Rows	Table	Rows
triage_level	3	appointment	0
service	4	audit_event	0
app_user	9	outbound_event	0
slot	15	inbound_event	0
request	0	ai_call_budget	0
request_status_change	0		

All 11 tables exist. The transactional tables are empty because a fresh seed contains only the catalogue, the nine demo users and fifteen open slots.


Deny-all RLS verified on the remote database — the same query with the public (`anon`) key, which is the only key a browser could ever hold:

```
curl "https://jtwrgfcmfghfklddyatv.supabase.co/rest/v1/request?select=*" -H "apikey: <anon key>" -H
"Authorization: Bearer <anon key>"
```

```
{ "code": "42501", "message": "permission denied for table request" }
```

HTTP 401 — and the same for `service`, even though the catalogue is public information: every read must go through our API.

Screenshot — Supabase Table Editor showing the deployed tables:



The address bar shows the project ref `jtwrgfcmfghfklddyatv`; the sidebar lists all 11 tables of the `public` schema, created by `supabase db push` and not by hand.

6. APIs for accessing the data (CRUD)

All routes are under `/api/v1`, are documented in `openapi.yaml`, validate input with Zod, and return an `x-Correlation-Id` header. Roles: **S** student, **P** practitioner, **C** coordinator, **—** public.

CRUD	Method and path	Role	Data touched
Create	POST <code>/requests</code>	S	<code>request</code> , <code>request_status_change</code>
Create	POST <code>/slots</code>	P	<code>slot</code>
Create	POST <code>/appointments</code>	S	<code>appointment</code> , <code>request</code> , <code>request_status_change</code>
Read	GET <code>/services</code>	—	<code>service</code>
Read	GET <code>/me</code>	any	<code>app_user</code>
Read	GET <code>/requests/me</code>	S	<code>request</code> , <code>appointment</code> , <code>slot</code>
Read	GET <code>/queue</code>	P	<code>request</code> — metadata only, no content
Read	POST <code>/requests/{id}/content-views</code>	P	<code>request</code> content + writes <code>audit_event</code> (a POST because every read has a side effect)
Read	GET <code>/coordinator/requests</code>	C	<code>request</code> — metadata only, no content
Read	GET <code>/requests/{id}/slots</code> , GET <code>/slots</code> , GET <code>/practitioners/{id}/slots</code>	S / P	<code>slot</code> , <code>appointment</code>
Update	PATCH <code>/requests/{id}</code>	P	<code>request.status</code> , <code>request_status_change</code>
Update	POST <code>/appointments/{id}/cancel</code>	S	<code>appointment.status</code> , <code>outbound_event</code>
Delete	DELETE <code>/slots/{id}</code>	P	<code>slot</code> (only if it has no confirmed appointment)

Also: POST/DELETE `/session` (demo sign-in/out), POST `/finder/suggest`, GET `/health`, POST `/internal/events/dispatch`, POST `/webhooks/notification-hub`.

What is deliberately *not* offered: there is no "update request content" and no "delete request" endpoint. Content is immutable by design, and records are removed only by the whole-dataset demo reset. This is a privacy decision, not a missing feature.

7. Using the APIs — example requests and responses

These are **real captures** from the running application (local stack, seeded demo data, 2026-09-20). Access tokens are masked; long lists are shortened with

```
BASE=http://localhost:3000/api/v1
```

7.0 Sign in (get a token)

```
curl -X POST $BASE/session -H "Content-Type: application/json" \
  -d '{"email":"student.a@demo.test","password":"demo-password-16"}'
```

```
{ "ok": true, "accessToken": "eyJhbG...(masked)", "expiresAt": 1789902000 }
```

Use it as `-H "Authorization: Bearer $TOKEN"` below.

7.1 READ — public service catalogue • `GET /services` → 200

```
curl $BASE/services
```

```
{
  "services": [
    {
      "id": "908c7343-601a-4a2a-a57a-b3870866f530",
      "slug": "counselling",
      "name": "Counselling",
      "whatFor": "Talking through stress, low mood, anxiety, relationships, grief, or anything that is weighing on you. You do not need a diagnosis or a 'big enough' problem.",
      "firstSession": "A relaxed 50-minute conversation with a counsellor about what is going on and what might help. Nothing is decided for you.",
      "whoWillKnow": "Only the counsellors of this service. Not your lecturers, not your parents, not other students."
    },
    "... 3 more"
  ]
}
```

7.2 CREATE — submit a request (student) • POST /requests → 201

```
curl -X POST $BASE/requests -H "Authorization: Bearer $STUDENT" -H "Content-Type: application/json" -d '{
  "serviceId": "908c7343-601a-4a2a-a57a-b3870866f530",
  "structuredDescription": "Trouble sleeping and feeling stressed before exams",
  "freeText": "It has been going on for about three weeks.",
  "preferredTimes": "Weekday afternoons",
  "triageLevelId": 1,
  "submissionKey": "a5a057b1-f53d-475b-b8ea-ab3f0682dc77"
}'
```

```
{
  "id": "0a7461bf-01ab-4594-a5b2-a49c6a53cbef",
  "status": "submitted",
  "triageLevelId": 1,
  "submittedAt": "2026-09-20T10:00:00.792008+00:00",
  "created": true,
  "acute": false
}
```

Sending the same `submissionKey` again returns `200` and the same request with `"created": false` — a double-click never creates two rows.

7.3 READ — my requests (student) • GET /requests/me → 200

```
{
  "requests": [
    {
      "id": "0a7461bf-01ab-4594-a5b2-a49c6a53cbef",
      "serviceName": "Counselling",
      "triageLevelId": 1,
      "status": "submitted",
      "submittedAt": "2026-09-20T10:00:00.792008+00:00",
      "bookable": false,
      "appointment": null
    },
    "..."
  ]
}
```

7.4 READ — practitioner queue, metadata only • GET /queue → 200

Most urgent first, then oldest first. Note what is **absent**: no description, no free text.

```
{
  "queue": [
    {
      "id": "03be1c83-75e8-4205-a765-ef76a37ee348",
      "triageLevelId": 3,
      "status": "submitted",
      "submittedAt": "2026-09-20T09:35:39.730788+00:00"
    },
    {
      "id": "a8b4da13-1b5f-45db-8285-ed0035886592",
      "triageLevelId": 1,
      "status": "submitted",
      "submittedAt": "2026-09-20T09:35:34.717531+00:00"
    },
    "..."
  ]
}
```

7.5 READ with audit — open one request's content (practitioner) • `POST /requests/{id}/content-views` → 201

```
curl -X POST $BASE/requests/0a7461bf-01ab-4594-a5b2-a49c6a53cbef/content-views -H "Authorization: Bearer $COUNSELLOR"
```

```
{
  "id": "0a7461bf-01ab-4594-a5b2-a49c6a53cbef",
  "structuredDescription": "Trouble sleeping and feeling stressed before exams",
  "freeText": "It has been going on for about three weeks.",
  "preferredTimes": "Weekday afternoons",
  "triageLevelId": 1,
  "status": "in_review",
  "submittedAt": "2026-09-20T10:00:00.792008+00:00"
}
```

In one transaction this wrote an `audit_event` row and moved the request `submitted` → `in_review` (compare `status` with 7.2).

7.6 CREATE — offer a slot (practitioner) • `POST /slots` → 201

```
curl -X POST $BASE/slots -H "Authorization: Bearer $COUNSELLOR" -H "Content-Type: application/json" \
  -d '{"startAt":"2026-09-29T03:00:00.000Z"}'
```

```
{
  "id": "1a8b0b56-0f82-4c55-8f42-adb1d8e706a6",
  "startAt": "2026-09-29T03:00:00+00:00",
  "booked": false
}
```

7.7 CREATE — book an appointment (student) • POST /appointments → 201

```
curl -X POST $BASE/appointments -H "Authorization: Bearer $STUDENT" -H "Content-Type: application/json" \
  -d '{"requestId":"0a7461bf-01ab-4594-a5b2-a49c6a53cbef","slotId":"3c33b594-7baf-4edb-accb-65a74eca1fc4"}'
```

```
{
  "id": "c14b97bf-5de3-4022-b213-e663895fbf60",
  "startAt": "2026-09-20T11:35:55.777+00:00",
  "status": "confirmed"
}
```

Repeating the same call → 409 { "error": "request_not_bookable" } — the request is already handled. A different student racing for the same slot receives 409 slot_taken.

7.8 UPDATE — cancel the appointment (student) • POST /appointments/{id}/cancel → 200

```
{ "id": "c14b97bf-5de3-4022-b213-e663895fbf60", "status": "cancelled" }
```

The slot is bookable again immediately (partial unique index).

7.9 UPDATE — change request status (practitioner) • PATCH /requests/{id} → 200

```
curl -X PATCH $BASE/requests/9e7043e5-778c-4d62-9a81-f67d88184c62 -H "Authorization: Bearer $COUNSELLOR" \
  -H "Content-Type: application/json" -d '{"status":"escalated"}'
```

```
{ "id": "9e7043e5-778c-4d62-9a81-f67d88184c62", "status": "escalated" }
```

7.10 DELETE — remove an unbooked slot (practitioner) • DELETE /slots/{id} → 200

```
curl -X DELETE $BASE/slots/1a8b0b56-0f82-4c55-8f42-adb1d8e706a6 -H "Authorization: Bearer $COUNSELLOR"
```

```
{ "ok": true }
```

7.11 Error responses (all content-free)

Case	Call	Response
No token	GET /requests/me	401 { "error": "unauthenticated" }
Wrong role (student calls the practitioner queue)	GET /queue	404 { "error": "not_found" }
Another student's request	GET /requests/{id}/slots	404 { "error": "not_found" } — identical to a record that does not exist, so existence is never leaked
Invalid urgency level 4	POST /requests	400 { "error": "validation_failed", "fields": ["triageLevelId"] }
Health	GET /health	200 { "status": "ok", "service": "wellbeing", "version": "dev", "database": "up" }

8. How we know it works

Check	Result
Migrations apply to a fresh PostgreSQL	Every CI run
Integration suite against the real database — privacy, role boundaries, concurrent booking, cancellation, escalation, events	53 / 53 passing
Unit tests (payload allowlist, signing, fallback matcher)	24 / 24 passing
openapi.yaml matches implemented routes	21 operations, in sync
No server secret in the browser bundle	Clean (66 files scanned)