西南林业大学 本科毕业(设计)论文 (二〇一七届)

题	目:	一个简单操作系统的实现 —
	_	RongOS
分院系	系部:	计算机与信息科学学院
专	小: -	计算机科学与技术专业
姓	名:	蒲启元
	-	
守帅外	生名:_	
导师耳	识称:	讲师

一个简单操作系统的实现 — RongOS

蒲启元

(西南林业大学计算机与信息科学学院,云南昆明650224)

摘 要:操作系统管理着计算机的硬件和软件资源,它是向上层应用软件提供服务 (接口)的核心系统软件,这些服务包括进程管理,内存管理,文件系统,网络通信,安全机制等。操作系统的设计与实现则是软件工业的基础与内核。为此,在国务院提出的《中国制造 2025》中专门强调了操作系统的开发。但长期以来,操作系统核心开发技术都掌握在外国人手中,技术受制,对于我们的软件工业来说很不利。本文拟从零开始设计开发一个简单的操作系统,包括 boot loader,中断,内存管理,图形接口,多任务,以及在这个系统上的几个小应用等。尽管这个系统很简单,但它为自主开发操作系统做了一个小小的尝试。

关键词:操作系统,开发,自主

The implement of a simple OS — RongOS

Qiyuan Pu

School of Computer and Information Science Southwest Forestry University Kunming 650224, Yunnan, China

Abstract: Operating system manages the sources of hardware and software, it lie in the core of the system software and provide service(interface) to upper application. These service including process management, memory management, file system, network communication, security mechanism etc. The design and implement of operating system is the foundation and core of software industry. Therefore, «Made in China 2025» emphasize the development of operating system that put forward by The State Council. For a long time, however, the kernel development technology grasped in the hand of foreigner, it's bad for our software industry cause of limited technology. So this article will design and develop a simple operating system, including boot loader, interrupt, memory management, graphic interface, multitasking, and some little application depend on this system. In spite of the simple of this system, it's a small trying for autonomous development operating system.

Key words: operating system, development, autonomous

目 录

1	Chapter — Preliminary Works	1
	1.1 Development Environment	1
	1.2 Tools	1
	1.3 Install	1
2	Chapter — Boot Loader	2
	2.1 Chose Disk	2
	2.2 The Structure of Floppy Disk	2
	2.3 The Source Codes and Comments of Boot Loader	2
3	Chapter — 32-bit Mode and Import C Codes	8
4	Chapter — Screen Display and Text	9
5	Chapter — Control Mouse	10
6	Chapter — Memory Management	11
7	Chapter — Making Window	12
8	Chapter — Timer	13
9	Chapter — Multitasking	14
10	Chapter — Command Line Window	15
	Chapter — API	16
	Chapter — OS Protection	17
13	Chapter — Graphics Processing	18

目 录

14 Chapter — Window Operation	19
15 Chapter — Application Protection	20
16 Chapter — File Operation	21
17 Chapter — Some Applications	22
18 Chapter — Prospects and Shortages	23
参考文献	24
指导教师简介	24
致 谢	26

插图目录

2-1	Floppy Disk Structure 1	2
-----	-------------------------	---

表格目录

1 Chapter — Preliminary Works

1.1 Development Environment

Operating System: Debian 4.11.0-1-amd64

Debug System: QEMU emulator version 2.8.1(Debian 1:2.8+dfsg-7)

Emacs version: GNU Emacs 25.2.2

1.2 Tools

Some tools used to develop RongOS, see tools.¹.

1.3 Install

Debian System: there is a small tutorial.²

QEMU, for my x86_64 architecture:

Note that the tools is exe formate, so on Debian system, you need to install wine:

\$ sudo apt-get update

Maybe you also need to add i386 architecture cause of AMD64 on your machine to use these tools:

\$ sudo apt-get update

¹https://github.com/Puqiyuan/RongOS/tree/master/Tools

²http://cs2.swfc.edu.cn/~wx672/lecture_notes/linux/install.html

2 Chapter — Boot Loader

2.1 Chose Disk

There are many ways to boot a operating system, from hard disk, USB, floppy disk etc. I chose floppy disk, although it is out of date. For my purpose is that develop a simple operating system, pay my attention on how to development. The structure of floppy disk is simple and for my simple operating system it's enough.

2.2 The Structure of Floppy Disk

This picture show the inside of floppy disk:




图 2-1 Floppy Disk Structure 1

2.3 The Source Codes and Comments of Boot Loader

```
CYLS equ 10

org 0x7c00; load the program to address 0x7c00.

jmp entry

; The next codes specify the format of standard FAT12 floppy disk.

db 0x90; db is the abbreation of "define byte", it literally places that byte

; right there in the executable.

db "RONGBOOT"; The name of boot sector, must be 8 byte.
```

```
dw 512; the size of every sector, must be 512 byte.
db 1; the size of cluster, must be 1.
dw 1; the start point of FAT, 1 general case.
db 2; the number of FAT, must be 2.
dw 224; the size of root directory, 224 in general.
dw 2880; the size of this floppy disk, must be 2880.
db 0xf0; the kind of disk.
dw 9; the length of FAT.
dw 18; how many sectors in one track, must be 18.
dw 2; the number of head, must be 2.
dd 0; no partion, must be 0.
dd 2880; the size if re-writer one time.
db 0,0,0x29; just fixed, no meaning.
dd Oxffffffff
db "RONGBOOTOS "; the name of disk.
db "FAT12"; the name of disk formate.
resb 18; reserved 18 byte.
        ; end FAT12 formate.
entry:
       mov ax, 0; init the registers.
       mov ss, ax
       mov sp, 0x7c00
       mov ds, ax
       mov si, msg_init
        jmp init
init:
       mov al, [si]
```

```
add si, 1; increment by 1.
40
            cmp al, 0
41
            je load ; if al == 0, jmp to load, the msg_init info displayed.
            mov ah, 0x0e; write a character in TTY mode.
            mov bx, 15 ; specify the color of the character.
44
            int 0x10; call BIOS function, video card is number 10.
            jmp init
46
47
   msg_init:
   db 0x0a ; new line
   db 0x0d
   db "Copyright: GPL"
   db 0x0a
   db 0x0d
   db "Author: Qiyuan Pu"
   db 0x0a
   db 0x0d
   db "https://github.com/Puqiyuan/RongOS"
   db 0x0a
   db 0x0d
60
   db "IPL is loading, please waiting..."
61
   db 0x0a
62
   db 0x0d
    db "...."
64
65
66
67
    load:
68
           mov ax, 0
69
```

```
mov ax, 0x0820
            mov es, ax
            mov ch, 0 ; cylinder 0.
            mov dh, 0; magnetict head 0.
            mov cl, 2; sector 2.
76
    readloop:
            mov si, 0
    retry:
            mov ah, 0x02; parameter 0x02 to ah, read disk.
81
            mov al, 1; parameter 1 to al, read disk.
            mov bx, 0
            mov dl, 0x00; the number of driver number.
            int 0x13; after prepared parameters, call 0x13 interrupted.
85
86
            jnc next
87
            add si, 1
88
            cmp si, 5
89
            jae error
            mov ah, 0x00
            mov dl, 0x00
92
            int 0x13
93
            jmp retry
95
   next:
96
            mov ax, es
97
            add ax, 0x0020
99
            mov es, ax
            add cl, 1
            cmp cl, 18
```

```
jbe readloop
             mov cl, 1
             add dh, 1
             cmp dh, 2
             jb readloop
106
             mov dh, 0
             add ch, 1
             cmp ch, CYLS
             jb readloop
             jmp correct
114
    fin:
             hlt
             jmp fin
116
118
    error:
119
             mov si, msg
    correct:
             mov si, msg_corr
124
126
    putloop:
             mov al, [si]
128
129
             add si, 1
             cmp al, 0
             mov [0x0ff0], ch
             je 0xc200
```

```
mov ah, 0x0e
            mov bx, 15
134
            int 0x10
             jmp putloop
136
    msg_corr:
    db 0x0a
140
    db 0x0d
    db 0x0a
    db 0x0d
    db "OK: IPL loaded"
144
    db 0x0a
    db 0x0d
    db 0
147
148
    msg:
    db 0x0a
    db "IPL load error"
    db 0x0a
    db 0
154
    resb 0x7dfe-$
    \mbox{\bf db} Ox55, Oxaa ; the sector end with Ox55 Oxaa, the sector is
158
            ;boot sector.
159
```

3 Chapter — 32-bit Mode and Import C Codes

4 Chapter — Screen Display and Text

5 Chapter — Control Mouse

6 Chapter — Memory Management

7 Chapter — Making Window

8 Chapter — Timer

9 Chapter — Multitasking

10 Chapter — Command Line Window

11 Chapter — API

12 Chapter — OS Protection

13 Chapter — Graphics Processing

14 Chapter — Window Operation

15 Chapter — Application Protection

16 Chapter — File Operation

17 Chapter — Some Applications

18 Chapter — Prospects and Shortages

参考文献

- [1] 国务院。中国制造 2025, 2015-05。。
- [2] WiKipedia. Operating System, 2017-08..
- [3] 川合秀实. 30 天自制操作系统. 人民邮电出版社, 2012-08.

指导教师简介

指导教师简介(约百余字)

致 谢

首先我想感谢我的老师,王晓林。大学期间,他给了我很多指导,包括专业方面和上大学的意义等。很多时候,他对学生的要求看起来都是不近情理的,但正是通过这个"痛苦"的过程,我锻炼了坚强的意志,和战胜困难的信心。谢谢你,王老师。我最想感谢的是我的女友,她容忍我在完成这个设计时的很多个夜晚不陪她,给我支持,鼓励我,不抱怨。所以我愿意把这个简单操作系统命名为 RongOS,蓉便是她名字的最后一个字。谢谢你,我最亲爱的。