

# Codebook- Team Far Behind

## IIT Delhi, India

Ayush Ranjan, Naman Jain, Manish Tanwar

## Contents

<b>1 Syntax</b>		<b>1 6 Maths</b>	<b>16</b>
1.1 Template . . . . .	1	6.1 Chinese Remainder Theorem . . . . .	16
1.2 C++ Sublime Build . . . . .	3	6.2 Discrete Log . . . . .	16
<b>2 Data Structures</b>	<b>3</b>	6.3 NTT . . . . .	17
2.1 Fenwick . . . . .	3	6.4 Online FFT . . . . .	18
2.2 2D-BIT . . . . .	3	6.5 Lagrange Interpolation . . . . .	19
2.3 Segment Tree . . . . .	3	6.6 Matrix Struct . . . . .	19
2.4 Persistent Segment Tree . . . . .	3	6.7 nCr(Non Prime Modulo) . . . . .	19
2.5 DP Optimization . . . . .	4	6.8 Primitive Root Generator . . . . .	20
<b>3 Flows and Matching</b>	<b>5</b>	<b>7 Strings</b>	<b>20</b>
3.1 General Matching . . . . .	5	7.1 Hashing Theory . . . . .	20
3.2 Global Mincut . . . . .	5	7.2 Manacher . . . . .	21
3.3 Hopcroft Matching . . . . .	6	7.3 Trie . . . . .	21
3.4 Dinic . . . . .	6	7.4 Z-algorithm . . . . .	21
3.5 Ford Fulkerson . . . . .	7	7.5 Aho Corasick . . . . .	22
3.6 MCMF . . . . .	7	7.6 KMP . . . . .	22
3.7 MinCost Matching . . . . .	8	7.7 Palindrome Tree . . . . .	22
<b>4 Geometry</b>	<b>9</b>	7.8 Suffix Array . . . . .	23
4.1 Geometry . . . . .	9	7.9 Suffix Tree . . . . .	24
4.2 Convex Hull . . . . .	12	<b>1 Syntax</b>	
4.3 Convex Hull Trick . . . . .	13	<b>1.1 Template</b>	
<b>5 Trees</b>	<b>13</b>		
5.1 BlockCut Tree . . . . .	13		
5.2 Bridges Online . . . . .	14		
5.3 HLD . . . . .	15		
5.4 LCA . . . . .	15		

```
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
using namespace std;
template<class T> ostream& operator<<(ostream &os, ←
vector<T> V) {
```

```

os << "["; for(auto v : V) os << v << " "; return <←
os << "];}
template<class L, class R> ostream& operator<<(<←
ostream &os, pair<L,R> P) {
return os << "(" << P.first << "," << P.second << "←
)";}
#define TRACE
#ifdef TRACE
#define trace(...) _f(#__VA_ARGS__, __VA_ARGS__)
template <typename Arg1>
void _f(const char* name, Arg1&& arg1){
cout << name << " : " << arg1 << std::endl;
}
template <typename Arg1, typename... Args>
void _f(const char* names, Arg1&& arg1, Args&&... <←
args){
const char* comma = strchr(names + 1, ',');cout.<←
write(names, comma - names) << " : " << arg1<<" <←
| ";_f(comma+1, args...);
}
#else
#define trace(...) 1
#endif
#define ll long long
#define ld long double
#define vll vector<ll>
#define pll pair<ll,ll>
#define vpll vector<pll>
#define I insert
#define pb push_back
#define F first
#define S second
#define all(x) x.begin(),x.end()
#define endl "\n"
// const ll MAX=1e6+5;
// int mod=1e9+7;
inline int mul(int a,int b){return (a*1ll*b)%mod;}
inline int add(int a,int b){a+=b;if(a>=mod)a-=mod;<←
return a;}
inline int sub(int a,int b){a-=b;if(a<0)a+=mod;return<←
a;}
inline int power(int a,int b){int rt=1;while(b>0){if(<←
b&1)rt=mul(rt,a);a=mul(a,a);b>>=1;}return rt;}
inline int inv(int a){return power(a,mod-2);}
inline void modadd(int &a,int b){a+=b;if(a>=mod)a-<←
mod;}
int main(){
ios_base::sync_with_stdio(false);cin.tie(0);cout.<←
tie(0);cout<<setprecision(25);
}
// clock
clock_t clk = clock();
clk = clock() - clk;
((ld)clk)/CLOCKS_PER_SEC
// fastio
inline ll read() {
ll n = 0; char c = getchar_unlocked();
while (!( '0' <= c && c <= '9')) c = <←
getchar_unlocked();

```

```

while ( '0' <= c && c <= '9')
n = n * 10 + c - '0', c = getchar_unlocked();
return n;
}
inline void write(ll a){
register char c; char snum[20]; ll i=0;
do{
snum[i++]=a%10+48;
a=a/10;
}while(a!=0); i--;
while(i>=0)
putchar_unlocked(snum[i--]);
putchar_unlocked('\n');
}
using getline, use cin.ignore()
// gp_hash_table
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
gp_hash_table<int, int> table; //cc_hash_table can <←
also be used
//custom hash function
const int RANDOM = chrono::high_resolution_clock::now<←
().time_since_epoch().count();
struct chash {
int operator()(int x) { return hash<int>{}(x ^ <←
RANDOM); }
};
gp_hash_table<int, int, chash> table;
//custom hash function for pair
struct chash {
int operator()(pair<int,int> x) const { return x.<←
first* 31 + x.second; }
};
// random
mt19937 rng(chrono::steady_clock::now().<←
time_since_epoch().count());
uniform_int_distribution<int> uid(1,r);
int x=uid(rng);
//mt19937_64 rng(chrono::steady_clock::now().<←
time_since_epoch().count());
// - for 64 bit unsigned numbers
vector<int> per(N);
for (int i = 0; i < N; i++)
per[i] = i;
shuffle(per.begin(), per.end(), rng);
// string splitting
// this splitting is better than custom function(w.r.<←
t time)
string line = "Ge";
vector <string> tokens;
stringstream check1(line);
string ele;
// Tokenizing w.r.t. space ' '
while(getline(check1, ele, ' '))
tokens.push_back(ele);

```

## 1.2 C++ Sublime Build

```
{
  "cmd": ["bash", "-c", "g++ -std=c++11 -O3 '${file}' -o '${file_path}/${file_base_name}' && gnome-terminal -- bash -c '\"${file_path}/${file_base_name}\" < input.txt > output.txt'"],
  "file_regex": "^(..[^:]*):([0-9]+):?([0-9]+)??:?(.*)$",
  "working_dir": "${file_path}",
  "selector": "source.c++, source.cpp",
}
```

## 2 Data Structures

### 2.1 Fenwick

```
/*All indices are 1 indexed
*Range update and point query: maintain BIT of prefix sum of updates
-add val in [a,b] -> add val at a, -val at b
-value[a]=BITsum(a)+arr[a]
*Range update ,range query: maintain 2 BITs B1,B2
-add val in [a,b] -> B1:add val at a, -val at b+1 and in B2 -> Add val*(a-1) at a, -val*b at b+1
-sum[1,b]=B1sum(1,b)*b-B2sum(1,b)
-sum[a,b]=sum[1,b]-sum[1,a-1]*/
ll fen[MAX_N];
void update(ll p, ll val){
    for(ll i = p; i <= n; i += i & -i)
        fen[i] += val;
}
ll sum(ll p){
    ll ans = 0;
    for(ll i = p; i >= 1; i -= i & -i) ans += fen[i];
    return ans;
}
```

### 2.2 2D-BIT

```
/*All indices are 1 indexed.Increment value of cell (i,j) by val -> update(x,y,val)
*sum of rectangle [a,b]-[c,d] ->sum of rectangles [1,1]-[c,d],[1,1]-[c,b],[1,1][a,d] and [1,1]-[a,b] and use inclusion exclusion*/
ll bit[MAX][MAX];
void update(ll x, ll y, ll val){
    while( x < MAX ){
        ll y1 = y;
        while( y1 < MAX )
            bit[x][y1] += val, y1 += ( y1 & -y1 );
        x += ( x & -x );
    }
}
```

```
ll sum(ll x, ll y){
    ll ans = 0;
    while( x > 0 ){
        ll y1 = y;
        while( y1 > 0 )
            ans += bit[x][y1], y1 -= ( y1 & -y1 );
        x -= ( x & -x );
    }
    return ans;
}
```

### 2.3 Segment Tree

```
/*All arrays are 0 indexed. call bld(0,n-1,1)
upd(0,n-1,1,x,y,val) -> increase [x,y] by val
sum(0,n-1,1,x,y) -> sum [x,y]
array of size N -> segment tree of size 4*N*/
ll arr[N], st[N<<2], lz[N<<2];
void ppgt(ll l, ll r, ll id){
    if(l==r) return;
    ll m = l+r>>1;
    lz[id*2] += lz[id]; lz[id<<1|1] += lz[id];
    st[id<<1] += (m - l + 1) * lz[id];
    st[id<<1|1] += (r-m)*lz[id]; lz[id] = 0;
}
void bld(ll l, ll r, ll id){
    if(l==r) { st[id] = arr[l]; return; }
    bld(l, l+r>>1, id*2); bld(l+r+1>>1, r, id*2+1);
    st[id] = st[id<<1] + st[id<<1|1];
}
void upd(ll l, ll r, ll id, ll x, ll y, ll val){
    if( l > y || r < x ) return; ppgt(l, r, id);
    if( l >= x && r <= y ) {
        lz[id] += val; st[id] += (r-l+1)*val; return;
    }
    upd(l, l+r>>1, id<<1, x, y, val); upd((l+r>>1)+1, r, id<<1|1, x, y, val);
    st[id] = st[id<<1] + st[id<<1|1];
}
ll sum(ll l, ll r, ll id, ll x, ll y){
    if( l > y || r < x ) return 0; ppgt(l, r, id);
    if( l >= x && r <= y ) return st[id];
    return sum(l, l+r>>1, id<<1, x, y) + sum((l+r>>1)+1, r, id<<1|1, x, y);
}
```

### 2.4 Persistent Segment Tree

```
/*id of first node = 0. call build(0,n-1) first. afterwards call upd(0,n-1,previous id,i,val) to add val in ith number. It returns root of new segment tree after modification
*sum(0,n-1,id of root,l,r) -> sum of values in subarray l to r in tree rooted at id
**size of st,lc,rc >= N*2+(N+Q)*logN*/
const ll N=1e5+10;
ll arr[N], st[20*N], lc[20*N], rc[20*N], ids[N], cnt;
void build(ll l, ll r){
```

```

if(l==r) {st[cnt]=arr[l];++cnt;return;}
ll id = cnt++;lc[id] = cnt;
build( l, l+r >>1);
rc[id] = cnt; build( (l + r >> 1) + 1, r);
st[id] = st[lc[id]] + st[rc[id]];
ll upd(ll l,ll r,ll id,ll x,ll val){
if(l == r)
{st[cnt]=st[id]+val;++cnt;return cnt-1;}
ll myid = cnt++; ll mid = l + r >>1;
if(x <= mid)
rc[myid] = rc[id],lc[myid] = upd(l, mid, lc[id], ←
x, val);
else
lc[myid] = lc[id],rc[myid] = upd(mid+1, r, rc[id]←
], x, val);
st[myid] = st[lc[myid]] + st[rc[myid]];
return myid;}
ll sum(ll l,ll r,ll id,ll x,ll y){
if (l > y || r < x ) return 0;
if (l >= x && r <= y ) return st[id];
return sum(l, l + r >> 1,lc[id], x, y) + sum((l + r←
>> 1) + 1,r ,rc[id],x, y);}
ll gkth(ll l,ll r,ll id1,ll id2,ll k){
if(l==r) return l;ll mid = l+r>>1;
ll a=st[lc[id2]]-(id1>=0?st[lc[id1]]:0);
if(a >= k)
return gkth(l, mid ,(id1>=0?lc[id1]:-1), lc[id2],←
k);
else
return gkth(mid+1, r,(id1>=0?rc[id1]:-1), rc[id2]←
], k-a);}
//kth largest num in range
int main(){
ll n,m;vll finalid(n);vpll v;
loop : v.pb({arr[i],i});sort(all(v));
loop : finalid[v[i].second]=i;
memset(arr,0,sizeof(ll)*N);
arr[finalid[0]]++;build(0,n-1);
loop:ids[i]=upd(0,n-1,ids[i-1],finalid[i],1);
while(m--){
ll i,j,k;cin>>i>>j>>k;--i;--j;
ans=gkth(0,n-1,(i==0?-1:ids[i-1]),ids[j],k);
cout<<v[ans].F<<endl;}
}

```

## 2.5 DP Optimization

/\*Split L size array into G intervals, minimizing the cost ( $G \leq L$ ). The cost func.  $C[i,j]$  satisfies:  $C[a,b]+C[c,d] \leq C[a,d]+C[c,b]$  for  $a \leq c \leq b \leq d$ . (Q.E) & intuitively you can think that the c.f increases at a rate which is more than linear at all intervals. So, if the c.f. satisfies Q.E., the following holds:  
 $F(g,l)$ : min cost of splitting first l into g ival's.  
 $F(g,l)$ :  $\min(F(g-1,k)+C(k+1,l))$  over all valid k.

$P(g,l)$ : lowest position k s.t. it minimizes  $F(g,l)$ .  
 $P(g,0) \leq P(g,1) \leq \dots \leq P(g,l)$ ; DivConq,  $O(G.L.\log(L))$   
 $P(0,l) \leq P(1,l) \leq P(2,l) \dots \leq P(G-1,l) \leq P(G,l)$ .  
Knuth Opti, complexity  $O(L.L)$ .  
For div&conq, we calculate  $P(g,l)$  for each g 1 by 1.  
In each g, we calculate for mid-l and do recursively using the obtained upper and lower bounds. For knuth, we use  $P(g,l-1) \leq P(g,l) \leq P(g+1,l)$ , and fill our table in increasing l and decreasing g. In opt. BST type problems, use  $bk[i][j-1] \leq bk[i][j] \leq bk[i+1][j]$  \*/  
// Code for Divide and Conquer Opti  $O(G.L.\log(L))$ : -  
ll C[8111]; ll sums[8111];  
ll F[811][8111]; // optimal value  
int P[811][8111]; // optimal position.  
// note first val. in arrays is for no. of groups  
ll cost(int i, int j) { // cost function  
return i > j ? 0 : (sums[j]-sums[i-1])\*(j-i+1);  
}  
/\*fill(g,ll,l2,p1,p2) calcs.  $P[g][l]$  and  $F[g][l]$  for  $ll \leq l \leq l2$ , with the knowledge that  $p1 \leq P[g][l] \leq p2$  \*/  
void fill(int g, int l1, int l2, int p1, int p2) {  
if (l1 > l2) return; int lm = (l1 + l2) >> 1;  
ll nv=INF,nv1=-1;  
for (int k = p1; k <= min(lm-1,p2); k++) {  
ll new\_cost = F[g-1][k] + cost[k+1][lm];  
if (nv > new\_cost) { nv=new\_cost; nv1 = k; }  
}  
P[g][lm]=nv1; F[g][lm]=nv;  
fill(g, l1, lm-1, p1, P[g][lm]);  
fill(g, lm+1, l2, P[g][lm], p2);  
}  
int main() { // example call  
for(i=0;i<=n;i++)F[0][i]=INF;  
for(i=0;i<=k;i++)F[i][0]=0;  
F[0][0]=0;  
for(i=1;i<=k;i++)fill(i,1,n,0,n);  
}  
// Code for Knuth Optimization  $O(L.L)$  :-  
ll dp[8002][802];  
int a[8002],s[8002][802];  
ll sum[8002];  
// index strats from 1  
ll run(int n,int m) {  
memset(dp,0xff,sizeof(dp)); dp[0][0] = 0;  
for (int i = 1; i <= n; ++i) {  
sum[i] = sum[i-1] + a[i];  
int maxj = min(i, m), mk; ll mn = INF;  
for (int k = 0; k < i; ++k) {  
if (dp[k][maxj-1] >= 0) {  
ll tmp = dp[k][maxj-1] +  
(sum[i] - sum[k]) \* (i - k);  
if (tmp < mn) {  
mn = tmp; mk = k; }  
}  
}

```

    }
    dp[i][maxj] = mn; s[i][maxj] = mk;
    for (int j = maxj - 1; j >= 1; --j) {
        ll mn = INF; int mk;
        for (ll k=s[i - 1][j]; k<=s[i][j + 1];++k){
            if (dp[k][j - 1] >= 0) {
                ll tmp =dp[k][j - 1]+(sum[i]-sum[k])*(i-k);
                if (tmp < mn) {mn = tmp;mk = k;} }
        }
        dp[i][j] = mn; s[i][j] = mk;
    }
} return dp[n][m];
}
// call -> run(n, min(n,m))

```

## 3 Flows and Matching

### 3.1 General Matching

```

/*Given any directed graph, finds maximal matching
Vertices-0-indexed, O(n^3) per call to edmonds*/
vll adj[MAXN]; int p[MAXN], base[MAXN], match[MAXN];
int lca(int n, int u, int v){
    vector<bool> used(n);
    for (;;) {
        u = base[u]; used[u] = true;
        if (match[u] == -1) break; u = p[match[u]];
    }
    for (;;) {
        v = base[v]; if (used[v]) return v;
        v = p[match[v]];
    }
}
void mark_path(vector<bool> &blo, int u, int b, int ←
child){
    for (; base[u] != b; u = p[match[u]]){
        blo[base[u]] = true; blo[base[match[u]]] = true;
        p[u] = child; child = match[u];
    }
}
int find_path(int n, int root) {
    vector<bool> used(n);
    for (int i = 0; i < n; ++i)
        p[i] = -1, base[i] = i;
    used[root] = true;
    queue<int> q; q.push(root);
    while(!q.empty()) {
        int u = q.front(); q.pop();
        for (int j = 0; j < (int)adj[u].size(); j++) {
            int v = adj[u][j];
            if (base[u]==base[v] || match[u]==v) continue;
            if (v==root || (match[v]!=-1 && p[match[v]]!=-1)){
                int curr_base = lca(n, u, v);
                vector<bool> blossom(n);
                mark_path(blossom, u, curr_base, v);
                mark_path(blossom, v, curr_base, u);
                for (int i = 0; i < n; i++){

```

```

                    if (blossom[base[i]]){
                        base[i] = curr_base;
                        if (!used[i]) used[i] = true, q.push(i);
                    }
                }
            } else if (p[v] == -1){
                p[v] = u;
                if (match[v] == -1) return v;
                v=match[v]; used[v]=true; q.push(v);
            }
        }
    }
    return -1;
}
int edmonds(int n){
    for (int i=0; i<n; i++) match[i] = -1;
    for (int i = 0; i < n; i++){
        if (match[i] == -1) {
            int u, pu, ppu;
            for (u = find_path(n, i); u != -1; u = ppu) {
                pu = p[u]; ppu = match[pu];
                match[u] = pu; match[pu] = u;
            }
        }
    }
    int matches = 0;
    for (int i = 0; i < n; i++)
        if (match[i] != -1) matches++;
    return matches/2;
}
u--; v--; adj[u].pb(v); adj[v].pb(u);
cout << edmonds(n) * 2 << endl;
for (int i = 0; i < n; i++) {
    if (match[i] != -1 && i < match[i]) {
        cout << i + 1 << " " << match[i] + 1 << endl;
    }
}

```

### 3.2 Global Mincut

```

/*finds min weighted cut in undirected graph in
O(n^3), Adj Matrix, 0-indexed vertices
output-(min cut value, nodes in half of min cut)*/
typedef vector<int> VI;
typedef vector<VI> VVI;
const int INF = 1000000000;
pair<int, VI> GetMinCut(VVI &weights) {
    int N = weights.size();
    VI used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N-1; phase >= 0; phase--) {
        VI w = weights[0];
        VI added = used;
        int prev, last = 0;
        for (int i = 0; i < phase; i++) {
            prev = last; last = -1;

```

```

for (int j = 1; j < N; j++)
if (!added[j] && (last == -1 || w[j] > w[last]))
    last = j;
if (i == phase-1) {
    for(int j=0;j<N;j++)
        weights[prev][j] += weights[last][j];
    for(int j=0;j<N;j++)
        weights[j][prev] = weights[prev][j];
    used[last] = true; cut.push_back(last);
    if (best_weight==-1 || w[last]<best_weight)
        best_cut = cut, best_weight = w[last];
}
else {
    for (int j = 0; j < N; j++)
        w[j] += weights[last][j];
    added[last] = true;
}
}
}
return make_pair(best_weight, best_cut);
}
VVI weights(n, VI(n));
pair<int, VI> res = GetMinCut(weights);

```

### 3.3 Hopcroft Matching

```

// O(m * \sqrt{n})
struct graph {
    int L, R; // 0-indexed vertices
    vector<vector<int>> adj;
    graph(int L, int R) : L(L), R(R), adj(L+R) {}
    void add_edge(int u, int v) {
        adj[u].pb(v+L); adj[v+L].pb(u);
    }
    int maximum_matching(){
        vector<int> level(L), mate(L+R, -1);
        function<bool(void)> levelize = [&]() { // BFS
            queue<int> Q;
            for (int u = 0; u < L; ++u) {
                level[u] = -1;
                if (mate[u] < 0) level[u] = 0, Q.push(u);
            }
            while (!Q.empty()) {
                int u = Q.front(); Q.pop();
                for (int w: adj[u]) {
                    int v = mate[w];
                    if (v < 0) return true;
                    if (level[v] < 0)
                        level[v] = level[u] + 1, Q.push(v);
                }
            }
            return false;
        };
        function<bool(int)> augment = [&](int u) { // DFS
            for (int w: adj[u]) {

```

```

                int v = mate[w];
                if (v<0 || (level[v]>level[u] &&augment(v))){
                    mate[u] = w; mate[w] = u; return true;
                }
            }
            return false;
        };
        int match = 0;
        while (levelize())
            for (int u = 0; u < L; ++u)
                if (mate[u] < 0 && augment(u)) ++match;
        return match;
    }
}; // L-left size, R->right size
graph g(L,R); g.add_edge(u,v); g.maximum_matching();

```

### 3.4 Dinic

```

/*O(min(fm,mn^2)), for any unit capacity network
O(m*sqrt(n)), in practice it is pretty fast for any
bipartite network, **vertices are 1-indexed**
e=(u,v), e.flow represent effective flow from u to v
(i.e f(u->v) - f(v->u))
*use int if possible(ll could be slow in dinic)*/
struct edge {ll x, y, cap, flow;};
struct DinicFlow {
    // *** change inf accordingly *****
    const ll inf = (1e18);
    vector<edge> e; vll cur, d;
    vector<vll> adj; ll n, source, sink;
    DinicFlow() {}
    DinicFlow(ll v) {
        n = v; cur = vll(n+1);
        d = vll(n+1); adj = vector<vll>(n+1);
    }
    void addEdge(ll from, ll to, ll cap) {
        edge e1 = {from, to, cap, 0};
        edge e2 = {to, from, 0, 0};
        adj[from].pb(e.size()); e.pb(e1);
        adj[to].pb(e.size()); e.pb(e2);
    }
    ll bfs() {
        queue<ll> q;
        for(ll i = 0; i <= n; ++i) d[i] = -1;
        q.push(source); d[source] = 0;
        while(!q.empty() and d[sink] < 0) {
            ll x = q.front(); q.pop();
            for(ll i = 0; i < (ll)adj[x].size(); ++i){
                ll id = adj[x][i], y = e[id].y;
                if(d[y]<0 and e[id].flow < e[id].cap){
                    q.push(y); d[y] = d[x] + 1;
                }
            }
        }
    }
}

```



```

    return d[sink] >= 0;
}
ll dfs(ll x, ll flow) {
    if(!flow) return 0;
    if(x == sink) return flow;
    for(; cur[x] < (ll)adj[x].size(); ++cur[x]) {
        ll id = adj[x][cur[x]], y = e[id].y;
        if(d[y] != d[x] + 1) continue;
        ll pushe=dfs(y,min(flow,e[id].cap-e[id].flow));
        if(pushed) {
            e[id].flow += pushed; e[id^1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
ll maxFlow(ll src, ll snk) {
    this->source = src; this->sink = snk;
    ll flow = 0;
    while(bfs()) {
        for(ll i = 0; i <= n; ++i) cur[i] = 0;
        while(ll pushed = dfs(source, inf))
            flow += pushed;
    }
    return flow;
}
};

```

### 3.5 Ford Fulkerson

```

/*O(f*m)*/ ll n; // number of vertices
ll cap[N][N]; // adj matrix for cap
vll adj[N]; // *** vertices are 0-indexed ***
// adj list of the corresponding undirected(*imp*)
ll INF = (1e18);
ll snk,cnt; //cnt for vis, no need to initialize vis
vector<ll> par, vis;
ll dfs(ll u,ll curf){
    vis[u] = cnt; if(u == snk) return curf;
    if(adj[u].size() == 0) return 0;
    for(ll j=0;j<5;j++){ // random for good aug.
        ll a = rand()%(adj[u].size()); ll v = adj[u][a];
        if(vis[v]==cnt || cap[u][v] == 0) continue;
        par[v] = u;
        ll f = dfs(v,min(curf, cap[u][v]));
        if(vis[snk] == cnt) return f;
    }
    for(auto v : adj[u]){
        if(vis[v] == cnt || cap[u][v] == 0) continue;
        par[v] = u;
        ll f = dfs(v,min(curf, cap[u][v]));
        if(vis[snk] == cnt) return f;
    }
    return 0;
}

```

```

ll maxflow(ll s, ll t) {
    snk = t; ll flow = 0; cnt++;
    par = vll(n,-1); vis = vll(n,0);
    while(ll new_flow = dfs(s,INF)){
        flow += new_flow; cnt++;
        ll cur = t;
        while(cur != s){
            ll prev = par[cur];
            cap[prev][cur] -= new_flow;
            cap[cur][prev] += new_flow;
            cur = prev;
        }
    }
    return flow;
}

```

### 3.6 MCMF

```

// MCMF Theory:
// 1. If a network with negative costs had no  $\leftarrow$ 
// negative cycle it is possible to transform it into  $\leftarrow$ 
// one with nonnegative
// costs. Using  $C_{ij\_new}(pi) = C_{ij\_old} + pi(i) - \leftarrow$ 
//  $pi(j)$ , where  $pi(x)$  is shortest path from  $s$  to  $x$  in  $\leftarrow$ 
// network with an
// added vertex  $s$ . The objective value remains  $\leftarrow$ 
// the same ( $z\_new = z + constant$ ).  $z(x) = \sum(c_{ij} * \leftarrow$ 
//  $x_{ij})$ 
// ( $x \rightarrow flow, c \rightarrow cost, u \rightarrow cap, r \rightarrow residual\ cap$ ).
// 2. Residual Network:  $c_{ji} = -c_{ij}, r_{ij} = u_{ij} - x_{ij}, \leftarrow$ 
//  $r_{ji} = x_{ij}$ .
// 3. Note: If edge  $(i,j),(j,i)$  both are there then  $\leftarrow$ 
// residual graph will have four edges b/w  $i,j$  (pairs  $\leftarrow$ 
// of parallel edges).
// 4. let  $x^*$  be a feasible soln, its optimal iff  $\leftarrow$ 
// residual network  $G_{x^*}$  contains no negative cost  $\leftarrow$ 
// cycle.
// 5. Cycle Cancelling algo  $\Rightarrow$  Complexity  $O(n*m^2*U*C \leftarrow$ 
// ) ( $C \rightarrow \max$  abs value of cost,  $U \rightarrow \max$  cap) ( $m*U*C \leftarrow$ 
// iterations).
// 6. Successive shortest path algo  $\Rightarrow$  Complexity  $O(n \leftarrow$ 
//  $^3 * B) / O(nm \log n)$  (using heap in Dijkstra) ( $B \rightarrow \leftarrow$ 
// largest supply node).
// Works for negative costs, but does not work for  $\leftarrow$ 
// negative cycles
// Complexity:  $O(\min(E^2 * V \log V, E \log V * flow))$ 
// to use  $\rightarrow$  graph  $G(n), G.add\_edge(u,v,cap,cost), G. \leftarrow$ 
//  $min\_cost\_max\_flow(s,t)$ 
// ***** INF is used in both flow_type and  $\leftarrow$ 
// cost_type so change accordingly
const ll INF = 99999999;
// vertices are 0-indexed
struct graph {
    typedef ll flow_type; // **** flow type ****

```

```

typedef ll cost_type; // **** cost type ****
struct edge {
    int src, dst;
    flow_type cap, flow;
    cost_type cost;
    size_t rev;
};
vector<edge> edges;
void add_edge(int s, int t, flow_type c, cost_type ←
    cost) {
    adj[s].pb({s,t,c,0,cost,adj[t].size()});
    adj[t].pb({t,s,0,0,-cost,adj[s].size()-1});
}
int n;
vector<vector<edge>> adj;
graph(int n) : n(n), adj(n) { }
pair<flow_type, cost_type> min_cost_max_flow(int s, ←
    int t) {
    flow_type flow = 0;
    cost_type cost = 0;
    for (int u = 0; u < n; ++u) // initialize
        for (auto &e: adj[u]) e.flow = 0;
    vector<cost_type> p(n, 0);
    auto rcost = [&](edge e)
    {return e.cost+p[e.src]-p[e.dst];};
    for (int iter = 0; ; ++iter) {
        vector<int> prev(n, -1); prev[s] = 0;
        vector<cost_type> dist(n, INF); dist[s] = 0;
        if (iter == 0) { // use Bellman-Ford to
            // remove negative cost edges
            vector<int> count(n); count[s] = 1;
            queue<int> que;
            for (que.push(s); !que.empty(); ) {
                int u = que.front(); que.pop();
                count[u] = -count[u];
                for (auto &e: adj[u]) {
                    if (e.cap > e.flow && dist[e.dst] > dist[←
                        e.src] + rcost(e)) {
                        dist[e.dst] = dist[e.src] + rcost(e);
                        prev[e.dst] = e.rev;
                        if (count[e.dst] <= 0) {
                            count[e.dst] = -count[e.dst] + 1;
                            que.push(e.dst);
                        }
                    }
                }
            }
        }
        for (int i=0; i<n; i++) p[i] = dist[i]; // added ←
        continue;
    }
    else { // use Dijkstra
        typedef pair<cost_type, int> node;
        priority_queue<node, vector<node>, greater<←
            node>> que;
        que.push({0, s});
        while (!que.empty()) {
            node a = que.top(); que.pop();

```

```

            if (a.S == t) break;
            if (dist[a.S] > a.F) continue;
            for (auto e: adj[a.S]) {
                if (e.cap > e.flow && dist[e.dst] > a.F + ←
                    rcost(e)) {
                    dist[e.dst] = dist[e.src] + rcost(e);
                    prev[e.dst] = e.rev;
                    que.push({dist[e.dst], e.dst});
                }
            }
        }
    }
    if (prev[t] == -1) break;
    for (int u = 0; u < n; ++u)
        if (dist[u] < dist[t]) p[u] += dist[u] - dist[←
            t];
    function<flow_type(int, flow_type)> augment = ←
        [&](int u, flow_type cur) {
            if (u == s) return cur;
            edge &r = adj[u][prev[u]], &e = adj[r.dst][r. ←
                rev];
            flow_type f = augment(e.src, min(e.cap - e. ←
                flow, cur));
            e.flow += f; r.flow -= f;
            return f;
        };
    flow_type f = augment(t, INF);
    flow += f;
    cost += f * (p[t] - p[s]);
}
return {flow, cost};
};

```

### 3.7 MinCost Matching

```

// Min cost bipartite matching via shortest ←
// augmenting paths
//
// This is an  $O(n^3)$  implementation of a shortest ←
// augmenting path
// algorithm for finding min cost perfect matchings ←
// in dense
// graphs. In practice, it solves 1000x1000 problems ←
// in around 1
// second.
//
// cost[i][j] = cost for pairing left node i with ←
// right node j
// Lmate[i] = index of right node that left node i ←
// pairs with
// Rmate[j] = index of left node that right node j ←
// pairs with
//

```



```

// The values in cost[i][j] may be positive or ←
// negative. To perform
// maximization, simply negate the cost[][] matrix.
typedef ll cost_type;
typedef vector<cost_type> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;
cost_type MinCostMatching(const VVD &cost, VI &Lmate, ←
    VI &Rmate) {
    int n = int(cost.size());
    // construct dual feasible solution
    VD u(n);
    VD v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost ←
            [i][j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost ←
            [i][j] - u[i]);
    }
    // construct primal solution satisfying ←
    // complementary slackness
    Lmate = VI(n, -1);
    Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
                //**** change this comparision if double cost ←
                ****
                Lmate[i] = j;
                Rmate[j] = i;
                mated++;
                break;
            }
        }
    }
    VD dist(n); VI dad(n); VI seen(n);
    // repeat until primal solution is feasible
    while (mated < n) {
        // find an unmatched left node
        int s = 0;
        while (Lmate[s] != -1) s++;
        // initialize Dijkstra
        fill(dad.begin(), dad.end(), -1);
        fill(seen.begin(), seen.end(), 0);
        for (int k = 0; k < n; k++)
            dist[k] = cost[s][k] - u[s] - v[k];
        int j = 0;
        while (true) {
            // find closest
            j = -1;
            for (int k = 0; k < n; k++) {

```

```

                if (seen[k]) continue;
                if (j == -1 || dist[k] < dist[j]) j = k;
            }
        }
        seen[j] = 1;
        // termination condition
        if (Rmate[j] == -1) break;
        // relax neighbors
        const int i = Rmate[j];
        for (int k = 0; k < n; k++) {
            if (seen[k]) continue;
            const cost_type new_dist = dist[j] + cost[i][ ←
                k] - u[i] - v[k];
            if (dist[k] > new_dist) {
                dist[k] = new_dist;
                dad[k] = j;
            }
        }
        // update dual variables
        for (int k = 0; k < n; k++) {
            if (k == j || !seen[k]) continue;
            const int i = Rmate[k];
            v[k] += dist[k] - dist[j];
            u[i] -= dist[k] - dist[j];
        }
        u[s] += dist[j];
        // augment along path
        while (dad[j] >= 0) {
            const int d = dad[j];
            Rmate[j] = Rmate[d];
            Lmate[Rmate[j]] = j;
            j = d;
        }
        Rmate[j] = s;
        Lmate[s] = j;
        mated++;
    }
    cost_type value = 0;
    for (int i = 0; i < n; i++)
        value += cost[i][Lmate[i]];
    return value;
}

```

## 4 Geometry

### 4.1 Geometry

```

//small non recursive functions should me made inline
//do not read input in double format if they are ←
integer points
#define ld double
#define PI acos(-1)

```

```

//atan2(y,x) slope of line (0,0)->(x,y) in radian (-<
PI,PI]
// to convert to degree multiply by 180/PI
ld INF = 1e100;
ld EPS = 1e-9;
inline bool eq(ld a,ld b) {return fabs(a-b)<EPS;}
inline bool lt(ld a,ld b) {return a+EPS<b;}
inline bool gt(ld a,ld b) {return a>b+EPS;}
inline bool le(ld a,ld b) {return lt(a,b)||eq(a,b);}
inline bool ge(ld a,ld b) {return gt(a,b)||eq(a,b);}
struct pt {
    ld x, y;
    pt() {}
    pt(ld x, ld y) : x(x), y(y) {}
    pt(const pt &p) : x(p.x), y(p.y) {}
    pt operator + (const pt &p) const { return pt(x+p.x,
    y+p.y); }
    pt operator - (const pt &p) const { return pt(x-p.x,
    y-p.y); }
    pt operator * (ld c) const { return pt(x*c, y<
    *c ); }
    pt operator / (ld c) const { return pt(x/c, y<
    /c ); }
    bool operator < (const pt &p) const{ return lt(y,p.<
    y)|| (eq(y,p.y)&&lt(x,p.x));}
    bool operator > (const pt &p) const{ return p<pt(x,<
    y);}
    bool operator <= (const pt &p) const{ return !(pt(x<
    ,y)>p);}
    bool operator >= (const pt &p) const{ return !(pt(x<
    ,y)<p);}
    bool operator == (const pt &p) const{ return (pt(x,<
    y)<=p)&&(pt(x,y)>=p);}
};
ld dot(pt p,pt q) {return p.x*q.x+p.y*q.y;}
ld dist2(pt p, pt q) {return dot(p-q,p-q);}
ld dist(pt p,pt q) {return sqrt(dist2(p,q));}
ld norm2(pt p) {return dot(p,p);}
ld norm(pt p) {return sqrt(norm2(p));}
ld cross(pt p, pt q) { return p.x*q.y-p.y*q.x;}
ostream &operator<<(ostream &os, const pt &p) {
    return os << "(" << p.x << "," << p.y << ")";}
istream& operator >> (istream &is, pt &p){
    return is >> p.x >> p.y;}
//returns 0 if a,b,c are collinear,1 if a->b->c is cw<
//and -1 if ccw
int orient(pt a,pt b,pt c)
{
    pt p=b-a,q=c-b;double cr=cross(p,q);
    if(eq(cr,0))return 0;if(lt(cr,0))return 1;return <
    -1;}
// rotate a point CCW or CW around the origin
pt RotateCCW90(pt p) { return pt(-p.y,p.x); }
pt RotateCW90(pt p) { return pt(p.y,-p.x); }

```

```

pt RotateCCW(pt p, ld t) { //rotate by angle t <
    degree ccw
    return pt(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos<
    (t)); }
// project point c onto line (not segment) through a <
// and b assuming a != b
pt ProjectPointLine(pt a, pt b, pt c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);}
// project point c onto line segment through a and b <
// (closest point on line segment)
pt ProjectPointSegment(pt a, pt b, pt c) {
    ld r = dot(b-a,b-a); if (eq(r,0)) return a;//a and <
    b are same
    r = dot(c-a, b-a)/r;if (lt(r,0)) return a;//c on <
    left of a
    if (gt(r,1)) return b; return a + (b-a)*r;}
// compute distance from c to segment between a and b
ld DistancePointSegment(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)))<
    ;}
// compute distance from c to line between a and b
ld DistancePointLine(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointLine(a, b, c)));}
// determine if lines from a to b and c to d are <
// parallel or collinear
bool LinesParallel(pt a, pt b, pt c, pt d) {
    return eq(cross(b-a, c-d),0); }
bool LinesCollinear(pt a, pt b, pt c, pt d) {
    return LinesParallel(a, b, c, d) && eq(cross(a-b, a<
    -c),0) && eq(cross(c-d, c-a),0);}
// determine if line segment from a to b intersects <
// with line segment from c to d
bool SegmentsIntersect(pt a, pt b, pt c, pt d) {
    if (LinesCollinear(a, b, c, d)) {
        //a->b and c->d are collinear and have one point <
        common
        if(eq(dist2(a,c),0)||eq(dist2(a,d),0)||eq(dist2(b<
        ,c),0)||eq(dist2(b,d),0)) return true;
        if(gt(dot(c-a,c-b),0)&&gt(dot(d-a,d-b),0)&&gt(dot<
        (c-b,d-b),0)) return false;
        return true;}
    if(gt(cross(d-a,b-a)*cross(c-a,b-a),0)) return <
    false;//c,d on same side of a,b
    if(gt(cross(a-c,d-c)*cross(b-c,d-c),0)) return <
    false;//a,b on same side of c,d
    return true;}
// compute intersection of line passing through a and<
// b
// with line passing through c and d,assuming that *<
// unique** intersection exists;
//*for segment intersection,check if segments <
// intersect first
pt ComputeLineIntersection(pt a,pt b,pt c,pt d){
    b=b-a;d=d-c;c=c-a;//lines must not be collinear
    assert(gt(dot(b, b),0)&&gt(dot(d, d),0));
    return a + b*cross(c, d)/cross(b, d);}

```

```

//returns true if point a,b,c are collinear and b ←
//lies between a and c
bool between(pt a,pt b,pt c){
    if(!eq(cross(b-a,c-b),0))return 0;//not collinear
    return le(dot(b-a,b-c),0);
}
//compute intersection of line segment a-b and c-d
pt ComputeSegmentIntersection(pt a,pt b,pt c,pt d){
    if(!SegmentsIntersect(a,b,c,d))return {INF,INF};//←
    //don't intersect
    //if collinear then infinite intersection points, ←
    //this returns any one
    if(LinesCollinear(a,b,c,d)){if(between(a,c,b))←
        return c;if(between(c,a,d))return a;return b;}
    return ComputeLineIntersection(a,b,c,d);
}
// compute center of circle given three points - *a,b←
//,c shouldn't be collinear
pt ComputeCircleCenter(pt a,pt b,pt c){
    b=(a+b)/2;c=(a+c)/2;
    return ComputeLineIntersection(b,b+RotateCW90(a-b),←
        c,c+RotateCW90(a-c));}
//point in polygon using winding number -> returns 0 ←
//if point is outside
//winding number>0 if point is inside and equal to 0 ←
//if outside
//draw a ray to the right and add 1 if side goes from←
//up to down and -1 otherwise
bool PointInPolygon(const vector<pt> &p,pt q){
    int n=p.size(),windingNumber=0;
    for(int i=0;i<n;++i){
        if(eq(dist2(q,p[i]),0)) return 1;//q is a vertex
        int j=(i+1)%n;
        if(eq(p[i].y,q.y)&&eq(p[j].y,q.y)) {//i,i+1 ←
            //vertex is vertical
            if(le(min(p[i].x,p[j].x),q.x)&&le(q.x,max(p[i].←
                x, p[j].x))) return 1;}//q lies on boundary
        else {
            bool below=lt(p[i].y,q.y);
            if(below!=lt(p[j].y,q.y)) {
                auto orientation=orient(q,p[j],p[i]);
                if(orientation==0) return 1;//q lies on ←
                //boundary i->j
                if(below==(orientation>0)) windingNumber+=←
                    below?1:-1;}}}
    return windingNumber==0?0:1;
}
// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<pt> &p,pt q) {
    for (int i = 0; i < p.size(); i++)
        if (eq(dist2(ProjectPointSegment(p[i],p[(i+1)%p.←
            size()],q),q),0)) return true;
    return false;}
// Compute area or centroid of any polygon (←
//coordinates must be listed in cw/ccw

```

```

//fashion.The centroid is often known as center of ←
//gravity/mass
ld ComputeSignedArea(const vector<pt> &p) {
    ld ans=0;
    for(int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        ans+=cross(p[i],p[j]);
    } return ans / 2.0;}
ld ComputeArea(const vector<pt> &p) {
    return fabs(ComputeSignedArea(p));
}
// compute intersection of line through points a and ←
// b with
// circle centered at c with radius r > 0
vector<pt> CircleLineIntersection(pt a, pt b, pt c, ←
    ld r){
    vector<pt> ret;
    b = b-a;a = a-c;
    ld A = dot(b, b),B = dot(a, b),C = dot(a, a) - r*r,←
    D = B*B - A*C;
    if (lt(D,0)) return ret; //don't intersect
    ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
    if (gt(D,0)) ret.push_back(c+a+b*(-B-sqrt(D))/A);
    return ret;}
// compute intersection of circle centered at a with ←
// radius r
// with circle centered at b with radius R
vector<pt> CircleCircleIntersection(pt a, pt b, ld r,←
    ld R){
    vector<pt> ret;
    ld d = sqrt(dist2(a, b)),d1=dist2(a,b);
    pt inf(INF,INF);
    if(eq(d1,0)&&eq(r,R)){ret.pb(inf);return ret;}//←
    //circles are same return (INF,INF)
    if(gt(d,r+R) || lt(d+min(r, R),max(r, R)) ) return ←
    ret;
    ld x = (d*d-R*R+r*r)/(2*d),y = sqrt(r*r-x*x);
    pt v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if (gt(y,0)) ret.push_back(a+v*x - RotateCCW90(v)*y←
    );
    return ret;}
//compute centroid of simple polygon by dividing it ←
//into disjoint triangles
//and taking weighted mean of their centroids (Jerome←
//)
pt ComputeCentroid(const vector<pt> &p) {
    pt c(0,0),inf(INF,INF);
    ld scale = 6.0 * ComputeSignedArea(p);
    if(p.empty())return inf;//empty vector
    if(eq(scale,0))return inf;//all points on straight ←
    //line
    for (int i = 0; i < p.size(); i++){
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*cross(p[i],p[j]);}
    return c / scale;}

```

```

// tests whether or not a given polygon (in CW or CCW
order) is simple
bool IsSimple(const vector<pt> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == 1 || j == k) continue;
            if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
                return false;
        }
    }
    return true;
}
/*point in convex polygon
****bottom left point must be at index 0 and top is
the index of upper right vertex
****if not call make_hull once*/
bool pointinConvexPolygon(vector<pt> poly, pt point,
int top) {
    if (point < poly[0] || point > poly[top]) return 0;
    //0 for outside and 1 for on/inside
    auto orientation = orient(point, poly[top], poly[0]);
    if (orientation == 0) {
        if (point == poly[0] || point == poly[top])
            return 1;
        return top == 1 || top + 1 == poly.size() ? 1 :
            1; //checks if point lies on boundary when
            //bottom and top points are adjacent
    } else if (orientation < 0) {
        auto itRight = lower_bound(poly.begin() + 1, poly.end(),
            point);
        return orient(itRight[0], point, itRight[-1]) <= 0;
    } else {
        auto itLeft = upper_bound(poly.rbegin(), poly.rend(),
            point);
        return (orient(itLeft == poly.rbegin() ? poly[0] :
            itLeft[-1], point, itLeft[0]) <= 0;
    }
}
/*maximum distance between two points in convex
polygon using rotating calipers
make sure that polygon is convex. if not call
make_hull first
*/
ld maxDist2(vector<pt> poly) {
    int n = poly.size();
    ld res = 0;
    for (int i = 0, j = n < 2 ? 0 : 1; i < j; ++i)
        for (; j = j+1 % n; j++) {
            res = max(res, dist2(poly[i], poly[j]));
            if (gt(cross(poly[j+1 % n] - poly[j], poly[i+1] -
                poly[i]), 0)) break;
        }
    return res;
}
//Line polygon intersection: check if given line
intersects any side of polygon

```

```

//if yes then line intersects. If no, then check if
its midpoint is inside polygon
//if midpoint is inside then line is inside else
outside
// compute distance between point (x,y,z) and plane
ax+by+cz=d
ld DistancePointPlane(ld x,ld y,ld z,ld a,ld b,ld c,ld d)
{ return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c); }

```

## 4.2 Convex Hull

```

pt firstpoint;
//for sorting points in ccw(counter clockwise)
direction w.r.t firstpoint (leftmost and
bottommost)
bool compare(pt x, pt y) {
    ll o = orient(firstpoint, x, y);
    if (o == 0) return lt(x.x+x.y, y.x+y.y);
    return o < 0;
}
/*poi->input points, hull->empty vector
returns hull in ccw order with min points*/
void make_hull(vector<pt> &poi, vector<pt> &hull) {
    pair<ld, ld> bl = {INF, INF};
    ll n = poi.size(); ll ind;
    for (ll i = 0; i < n; i++) {
        pair<ld, ld> pp = {poi[i].y, poi[i].x};
        if (pp < bl) {
            ind = i; bl = {poi[i].y, poi[i].x};
        }
    }
    swap(bl.F, bl.S); firstpoint = pt(bl.F, bl.S);
    vector<pt> cons;
    for (ll i = 0; i < n; i++) {
        if (i == ind) continue; cons.pb(poi[i]);
    }
    sort(cons.begin(), cons.end(), compare);
    hull.pb(firstpoint); ll m;
    for (auto z : cons) {
        if (hull.size() <= 1) { hull.pb(z); continue; }
        pt pr, ppr; bool fl = true;
        while ((m = hull.size()) >= 2) {
            pr = hull[m-1]; ppr = hull[m-2];
            ll ch = orient(ppr, pr, z);
            if (ch == -1) break;
            else if (ch == 1) { hull.pop_back(); continue; }
            else {
                ld d1, d2;
                d1 = dist2(ppr, pr); d2 = dist2(ppr, z);
                if (gt(d1, d2)) { fl = false; break; } else { hull.
                    pop_back(); }
            }
        }
        if (fl) { hull.push_back(z); }
    }
}

```



```

    return;
}

```

## 4.3 Convex Hull Trick

```

/*maintains upper convex hull of lines ax+b and gives←
  minimum value at a given x
to add line ax+b: sameoldcht.addline(a,b), to get min←
  value at x: sameoldcht.getbest(x)
to get maximum value at x add -ax-b as lines instead ←
  of ax+b and use -sameoldcht.getbest(x)*/
const int N = 1e5 + 5;
int n,a[N],b[N];ll dp[N];
struct line{
    ll a , b;double xleft;bool type;
    line(ll _a , ll _b){a = _a;b = _b;type = 0;}
    bool operator < (const line &other) const{
        if(other.type){return xleft < other.xleft;}
        return a > other.a;}
};
double meet(line x , line y){
    return 1.0 * (y.b - x.b) / (x.a - y.a);}
struct cht{
    set <line> hull;
    cht() {hull.clear();}
    typedef set < line > :: iterator ite;
    bool hasleft(ite node){
        return node != hull.begin();}
    bool hasright(ite node){
        return node != prev(hull.end());}
    void updateborder(ite node){
        if(hasright(node)){line temp = *next(node);
            hull.erase(temp);
            temp.xleft=meet(*node,temp);
            hull.insert(temp);}
        if(hasleft(node)){line temp = *node;
            temp.xleft = meet(*prev(node) , temp);
            hull.erase(node);hull.insert(temp);}
        else{
            line temp = *node;hull.erase(node);
            temp.xleft = -1e18;hull.insert(temp);}
    }
    bool useless(line left,line middle,line right){
        double x = meet(left,right);
        double y = x * middle.a + middle.b;
        double ly = left.a * x + left.b;
        return y > ly;}
    bool useless(ite node){
        if(hasleft(node) && hasright(node)){return
            useless(*prev(node)*node,*next(node));}
        return 0;}
    void addline(ll a , ll b){
        line temp = line(a , b);
        auto it = hull.lower_bound(temp);

```

```

        if(it != hull.end() && it -> a == a){
            if(it -> b > b){hull.erase(it);}
            else return;}
        hull.insert(temp);it = hull.find(temp);
        if(useless(it)){hull.erase(it);return;}
        while(hasleft(it) && useless(prev(it))){
            hull.erase(prev(it));}
        while(hasright(it) && useless(next(it))){
            hull.erase(next(it));}
        updateborder(it);}
ll getbest(ll x){
    if(hull.empty())return 1e18;
    line query(0 , 0);
    query.xleft = x;query.type = 1;
    auto it = hull.lower_bound(query);
    it = prev(it);
    return it -> a * x + it -> b;}
};
cht sameoldcht;
int main(){
    sameoldcht.addline(b[1] , 0);
    dp[i] = sameoldcht.getbest(a[i]);
    sameoldcht.addline(b[i] , dp[i]);}

```

## 5 Trees

### 5.1 BlockCut Tree

```

// Take care it is 0 indexed --
struct BiconnectedComponents {
    struct Edge {
        int from, to;
    };
    struct To {
        int to; int edge;
    };
    vector<Edge> edges; vector<vector<To> > g;
    vector<int> low, ord, depth;
    vector<bool> isArtic;vll edgeColor;
    vector<int> edgeStack;
    int colors; int dfsCounter;
    void init(int n) {
        edges.clear();
        g.assign(n, vector<To>());
    }
    void addEdge(int u, int v) {
        if(u > v) swap(u, v); Edge e = { u, v };
        int ei = edges.size(); edges.push_back(e);
        To tu = { v, ei }, tv = { u, ei };
        g[u].push_back(tu); g[v].push_back(tv);
    }
    void run() {

```



```

int n = g.size(), m = edges.size();
low.assign(n, -2); ord.assign(n, -1);
depth.assign(n, -2); isArtic.assign(n, false);
edgeColor.assign(m, -1); edgeStack.clear();
colors = 0;
for(int i = 0; i < n; ++ i) if(ord[i] == -1) {
    dfsCounter = 0;
    dfs(i);
}
}
private:
void dfs(int i) {
    low[i] = ord[i] = dfsCounter ++;
    for(int j = 0; j < (int)g[i].size(); ++ j) {
        int to = g[i][j].to, ei = g[i][j].edge;
        if(ord[to] == -1) {
            depth[to] = depth[i] + 1;
            edgeStack.push_back(ei);
            dfs(to);
            low[i] = min(low[i], low[to]);
            if(low[to] >= ord[i]) {
                if(ord[i] != 0 || j >= 1)
                    isArtic[i] = true;
                while(!edgeStack.empty()) {
                    int fi = edgeStack.back();
                    edgeStack.pop_back();
                    edgeColor[fi] = colors;
                    if(fi == ei) break;
                } ++colors;
            }
        } else if(depth[to] < depth[i] - 1) {
            low[i] = min(low[i], ord[to]);
            edgeStack.push_back(ei);
        }
    }
}
};

```

## 5.2 Bridges Online

```

vector<int> par, dsu_2ecc, dsu_cc, dsu_cc_size;
int bridges; int lca_iteration;
vector<int> last_visit;
void init(int n) {
    par.resize(n); dsu_2ecc.resize(n);
    dsu_cc.resize(n); dsu_cc_size.resize(n);
    lca_iteration = 0; last_visit.assign(n, 0);
    for(int i=0; i<n; ++i) {
        dsu_2ecc[i] = i; dsu_cc[i] = i;
        dsu_cc_size[i] = 1; par[i] = -1;
    } bridges = 0;
}
int find_2ecc(int v) { // 2-edge connected comp.
    if (v == -1) return -1;

```

```

    return dsu_2ecc[v] == v ? v : dsu_2ecc[v] = ←
        find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) { // connected comp.
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v : dsu_cc[v] = find_cc(←
        dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v);
    int root = v; int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]);
        par[v] = child; dsu_cc[v] = root;
        child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
void merge_path (int a, int b) {
    ++lca_iteration;
    vector<int> path_a, path_b;
    int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a); path_a.push_back(a);
            if (last_visit[a] == lca_iteration)
                lca = a;
            last_visit[a] = lca_iteration; a=par[a];
        }
        if (b != -1) {
            path_b.push_back(b);
            b = find_2ecc(b);
            if (last_visit[b] == lca_iteration) lca = b;
            last_visit[b] = lca_iteration; b = par[b];
        }
    }
    for (int v : path_a) {
        dsu_2ecc[v] = lca; if (v == lca) break;
        --bridges;
    }
    for (int v : path_b) {
        dsu_2ecc[v] = lca; if (v == lca) break;
        --bridges;
    }
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;
    int ca = find_cc(a); int cb = find_cc(b);
    if (ca != cb) { ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b); swap(ca, cb);}
        make_root(a); par[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else { merge_path(a, b);}
}

```

## 5.3 HLD

```

/*
v is adjacency matrix of tree. clear v[i],hdc[i]=0,i←
=-1 before every run
clear ord and curc=0
*/
const ll MAX=250005;
vll v[MAX],ord;
ll par[MAX],noc[MAX],hdc[MAX],curc,posinch[MAX],len[←
MAX],ti=-1;
ll sta[MAX],en[MAX],subs[MAX],level[MAX];
ll st[4*MAX],lazy[4*MAX];
ll n;
void dfs(ll x){
    subs[x]=1;
    for(auto z:v[x]){
        if(z!=par[x]){par[z]=x;level[z]=level[x]+1;
            dfs(z);subs[x]+=subs[z];
        }
    }
}
void makehld(ll x){
    if(hdc[curc]==0){hdc[curc]=x;len[curc]=0;}
    noc[x]=curc;posinch[x]=++len[curc];
    ll a,b,c;a=b=0;ord.pb(x);sta[x]=++ti;
    for(auto z:v[x]){if(z==par[x]) continue;
        if(subs[z]>b){b=subs[z];a=z;}
    }
    if(a!=0)makehld(a);
    for(auto z:v[x]){if(z==par[x]||z==a) continue;curc←
        ++;makehld(z);}
    en[x]=ti;
}
inline void upd(ll x,ll y)//to update on path from a ←
to b
{
    ll a,b,c,d;
    while(x!=y){
        a=hdc[noc[x]],b=hdc[noc[y]];
        if(a==b){
            if(level[x]>level[y])swap(x,y);c=sta[x],d=sta[y]←
            ;
            //lca=a;
            update(1,0,n-1,c+1,d);return;}
        if(level[a]>level[b])swap(a,b),swap(x,y);
        update(1,0,n-1,sta[b],sta[y]);y=par[b];}}//update←
on segment tree
int main() {
    //v is adjacency matrix
    for(i=1;i<=n;i++) v[i].clear(),hdc[i]=0,ti=-1;
    ord.clear(),curc=0;
    level[1]=0;par[1]=0;curc=1;dfs(1);makehld(1);
    cin>>m;
    while(m--){cin>>a>>b;upd(a,b);ll ans=sumq(1,0,n←
        -1,0,n-1);}
}

```

## 5.4 LCA

```

const int N = int(1e5)+10;
const int LOGN = 20;
set<int> g[N];
int level[N];
int DP[LOGN][N];
int n,m;
/*----- Pre-Processing -----*/
/* Code Cridits : Tanuj Khattar codeforces submission←
*/
void dfs0(int u)
{
    for(auto it=g[u].begin();it!=g[u].end();it++)
        if(*it!=DP[0][u])
        {
            DP[0][*it]=u;
            level[*it]=level[u]+1;
            dfs0(*it);
        }
}
void preprocess()
{
    level[0]=0;
    DP[0][0]=0;
    dfs0(0);
    for(int i=1;i<LOGN;i++)
        for(int j=0;j<n;j++)
            DP[i][j] = DP[i-1][DP[i-1][j]];
}
int lca(int a,int b)
{
    if(level[a]>level[b])swap(a,b);
    int d = level[b]-level[a];
    for(int i=0;i<LOGN;i++)
        if(d&(1<<i))
            b=DP[i][b];
    if(a==b)return a;
    for(int i=LOGN-1;i>=0;i--)
        if(DP[i][a]!=DP[i][b])
            a=DP[i][a],b=DP[i][b];
    return DP[0][a];
}
int dist(int u,int v)
{
    return level[u] + level[v] - 2*level[lca(u,v)];
}

```

## 5.5 Centroid Decomposition

```

/*nx:max nodes,par:parents of nodes in centroid tree,←
timestep: timestamps of nodes when they became ←
centroids,ssize,vis: subtree size and visit times ←
in dfs,tim: timestamp iterator
dist[nx]: dist[i][0][j]=no. of nodes at dist k in ←
subtree of i in centroid tree

```

```

dist[i][j][k]=no. of nodes at distance k in jth child←
  of i in centroid tree *(use adj while doing dfs←
  instead of adj1)***
preprocess: stores all values in dist array*/
const int nx=1e5;
vector<int> adj[nx],adj1[nx];
int par[nx],timestmp[nx],ssize[nx],vis[nx];
int tim=1;
vector<int> cntnorder;//centroids in order
vector<vector<int>> > dist[nx];
int dfs(int root){
  vis[root]=tim;
  int t=0;
  for(auto i:adj[root]){
    if(!timestmp[i]&&vis[i]<tim)t+=dfs(i);}
  ssize[root]=t+1;return t+1;}
int dfs1(int root,int n){
  vis[root]=tim;pair<int,int> mxc={0,-1};
  bool poss=true;
  for(auto i:adj[root]){
    if(!timestmp[i]&&vis[i]<tim)
      poss&=((ssize[i]<=n/2),mx=max(mxc,{ssize[i],i})←
      );}
  if(poss&&(n-ssize[root])<=n/2)return root;
  return dfs1(mxc.second,n);}
int findc(int root){
  dfs(root);
  int n=ssize[root];tim++;
  return dfs1(root,n);}
void cntnorder(int root,int p){
  int cnt=findc(root);
  cntnorder.pb(cnt);
  timestmp[cnt]=tim++;par[cnt]=p;
  if(p>=0)adj1[p].pb(cnt);
  for(auto i:adj[cnt])
    if(!timestmp[i])
      cntnorder(i,cnt);}
void dfs2(int root,int nod,int j,int dst){
  if(dist[root][j].size()==dst)dist[root][j].pb(0);
  vis[nod]=tim;dist[root][j][dst]+=1;
  for(auto i:adj[nod]){
    if((timestmp[i]<=timestmp[root])||(vis[i]==vis[nod]←
    ))continue;
    vis[i]=tim;dfs2(root,i,j,dst+1);}
}
void preprocess(){
  for(int i=0;i<cntnorder.size();i++){
    int root=cntnorder[i];
    vector<int> temp;
    dist[root].pb(temp);temp.pb(0);++tim;
    dfs2(root,root,0,0);
    int cnt=0;
    for(int j=0;j<adj[root].size();j++){
      int nod=adj[root][j];
      if(timestmp[nod]<timestmp[root])
        continue;

```

```

    dist[root].pb(temp);++tim;
    dfs2(root,nod,++cnt,1);}
  }
}

```

## 6 Maths

### 6.1 Chinese Remainder Theorem

```

/*solves system of equations x=rem[i]%mods[i] for any←
  mod (need not be coprime)
input:vector of remainders and moduli
output: pair of answer(x%lcm of modulo) and lcm of ←
  all the modulo (returns -1 if it is inconsistent)←
  */
ll GCD(ll a, ll b) { return (b == 0) ? a : GCD(b, a %←
  b); }
inline ll LCM(ll a, ll b) { return a / GCD(a, b) * b;←
  }
inline ll normalize(ll x, ll mod) { x %= mod; if (x <←
  0) x += mod; return x; }
struct GCD_type { ll x, y, d; };
GCD_type ex_GCD(ll a, ll b)
{
  if (b == 0) return {1, 0, a};
  GCD_type pom = ex_GCD(b, a % b);
  return {pom.y, pom.x - a / b * pom.y, pom.d};
}
pair<ll,ll> CRT(vector<ll> &rem,vector<ll> &mods)
{
  ll n=rem.size();
  ll ans=rem[0];
  ll lcm=mods[0];
  for(ll i=1;i<n;i++)
  {
    auto pom=ex_GCD(lcm,mods[i]);
    ll x1=pom.x;
    ll d=pom.d;
    if((rem[i]-ans)%d!=0)return {-1,0};
    ans=normalize(ans+x1*(rem[i]-ans)/d%(mods[i]/←
    d)*lcm,lcm*mods[i]/d);
    lcm=LCM(lcm,mods[i]); // you can save time by←
    replacing above lcm * n[i] /d by lcm = ←
    lcm * n[i] / d
  }
  return {ans,lcm};
}

```

### 6.2 Discrete Log



```

inline int sub(int a,int b){a-=b;if(a<0)a+=mod;return a;}
inline int power(int a,int b){int rt=1;while(b>0){if(b&1)rt=mul(rt,a);a=mul(a,a);b>>=1;}return rt;}
inline int inv(int a){return power(a,mod-2);}
inline void modadd(int &a,int &b){a+=b;if(a>=mod)a-=mod;}
int base = 1;
vector<int> roots = {0, 1};
vector<int> rev = {0, 1};
int max_base=18; //x such that 2^x|(mod-1) and 2^x<=
max_answer_size(=2*n)
int root=202376916; //primitive root^((mod-1)/(2^
max_base))
void ensure_base(int nbase) {
    if (nbase <= base) {
        return;
    }
    assert(nbase <= max_base);
    rev.resize(1 << nbase);
    for (int i = 0; i < (1 << nbase); i++) {
        rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (nbase <
        - 1));
    }
    roots.resize(1 << nbase);
    while (base < nbase) {
        int z = power(root, 1 << (max_base - 1 - base));
        for (int i = 1 << (base - 1); i < (1 << base); i<
        ++)) {
            roots[i << 1] = roots[i];
            roots[(i << 1) + 1] = mul(roots[i], z);
        }
        base++;
    }
}
void fft(vector<int> &a) {
    int n = (int) a.size();
    assert((n & (n - 1)) == 0);
    int zeros = __builtin_ctz(n);
    ensure_base(zeros);
    int shift = base - zeros;
    for (int i = 0; i < n; i++) {
        if (i < (rev[i] >> shift)) {
            swap(a[i], a[rev[i] >> shift]);
        }
    }
    for (int k = 1; k < n; k <= 1) {
        for (int i = 0; i < n; i += 2 * k) {
            for (int j = 0; j < k; j++) {
                int x = a[i + j];
                int y = mul(a[i + j + k], roots[j + k]);
                a[i + j] = x + y - mod;
                if (a[i + j] < 0) a[i + j] += mod;
                a[i + j + k] = x - y + mod;
                if (a[i + j + k] >= mod) a[i + j + k] -= mod;
            }
        }
    }
}

```

```

}
vector<int> multiply(vector<int> a, vector<int> b, <
    int eq = 0) {
    int need = (int) (a.size() + b.size() - 1);
    int nbase = 0;
    while ((1 << nbase) < need) nbase++;
    ensure_base(nbase);
    int sz = 1 << nbase;
    a.resize(sz);
    b.resize(sz);
    fft(a);
    if (eq) b = a; else fft(b);
    int inv_sz = inv(sz);
    for (int i = 0; i < sz; i++) {
        a[i] = mul(mul(a[i], b[i]), inv_sz);
    }
    reverse(a.begin() + 1, a.end());
    fft(a);
    a.resize(need);
    return a;
}
vector<int> square(vector<int> a) {
    return multiply(a, a, 1);
}

```

## 6.4 Online FFT

```

//f[i]=sum over j from 0 to i-1 f[j]*g[i-1-j]
//handle f[0] and g[0] separately
const int nx=131072;int f[nx],g[nx];
void onlinefft(int a,int b,int c,int d)
{
    vector<int> v1,v2;
    v1.pb(f+a,f+b+1);v2.pb(g+c,g+d+1); vector<int> res=<
    multiply(v1,v2);
    for(int i=0;i<res.size();i++)
        if(a+c+i+1<nx) f[a+c+i+1]=add(f[a+c+i+1],res[i]);
}
void precal()
{
    g[0]=1;
    for(int i=1;i<nx;i++)
        g[i]=power(i,i-1);
    f[1]=1;
    for(int i=1;i<=100000;i++)
    {
        f[i+1]=add(f[i+1],g[i]);f[i+1]=add(f[i+1],f[i]);
        f[i+2]=add(f[i+2],mul(f[i],g[1]));f[i+3]=add(f[i<
        +3],mul(f[i],g[2]));
        for(int j=2;i%j==0&&j<nx;j=j*2) onlinefft(i-j,i<
        -1,j+1,2*j);
    }
}

```



## 6.5 Lagrange Interpolation

```
/* Input :
Degree of polynomial: k
Polynomial values at x=0,1,2,3,...,k
Output :
Polynomial value at x
Complexity: O(degree of polynomial)
Works only if the points are equally spaced
*/
ll lagrange(vll& v , int k, ll x,int mod){
    if(x <= k) return v[x];
    ll inn = 1; ll den = 1;
    for(int i = 1; i<=k; i++){
        inn = (inn*(x - i))%mod;
        den = (den*(mod - i))%mod;
    }
    inn = (inn*inv(den % mod))%mod;
    ll ret = 0;
    for(int i = 0; i<=k; i++){
        ret = (ret + v[i]*inn)%mod;
        ll md1 = mod - ((x-i)*(k-i))%mod;
        ll md2 = ((i+1)*(x-i-1))%mod;
        if(i!=k)
            inn = (((inn*md1)%mod)*inv(md2 % mod))%mod;
    } return ret;
}
```

## 6.6 Matrix Struct

```
struct matrix{
    ld B[N][N], n;
    matrix(){n = N; memset(B,0,sizeof B);}
    matrix(int _n){
        n = _n; memset(B, 0, sizeof B);
    }
    void iden(){
        for(int i = 0; i < n; i++)
            B[i][i] = 1;
    }
    void operator += (matrix M){
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                B[i][j] = add(B[i][j], M.B[i][j]);
    }
    void operator -= (matrix M){}
    void operator *= (ld b){}
    matrix operator - (matrix M){}
    matrix operator + (matrix M){
        matrix ret = (*this);
        ret += M; return ret;
    }
    matrix operator * (matrix M){
        matrix ret = matrix(n); memset(ret.B, 0, sizeof ←
        ret.B);
```

```
        for(int i = 0; i < n; i++){
            for(int j = 0; j < n; j++){
                for(int k = 0; k < n; k++){
                    ret.B[i][j] = add(ret.B[i][j], mul(B[i][k], ←
                    M.B[k][j]));
                }
            }
        }
        return ret;
    }
    matrix operator *= (matrix M){ *this = ((*this) * M) ←
    );}
    matrix operator * (int b){
        matrix ret = (*this); ret *= b; return ret;
    }
    vector<double> multiply(const vector<double> & v) ←
    const{
        vector<double> ret(n);
        for(int i = 0; i < n; i++){
            for(int j = 0; j < n; j++){
                ret[i] += B[i][j] * v[j];
            }
        }
        return ret;
    }
};
```

## 6.7 nCr(Non Prime Modulo)

```
// calculates nCr, for small
// non-prime modulo, and (very) big n,r.
ll phimod;
vll pr,prn;vll fact;
ll power(ll a,ll x,ll mod){
    ll ans=1;
    while(x){
        if((1LL)&(x))ans=(ans*a)%mod;
        a=(a*a)%mod;x>=1LL;
    }
    return ans;
}
// prime factorization of x.
// pr-> prime ; prn -> it's exponent
void getprime(ll x){
    pr.clear();prn.clear();
    ll i,j,k;
    for(i=2;(i*i)<=x;i++){
        k=0;while((x%i)==0){k++;x/=i;}
        if(k>0){pr.pb(i);prn.pb(k);}
    }
    if(x!=1){pr.pb(x);prn.pb(1);}
    return;
}
// factorials are calculated ignoring
// multiples of p.
void primeproc(ll p,ll pe){ // p , p^e
    ll i,d;
    fact.clear();fact.pb(1);d=1;
```

```

    for(i=1;i<pe;i++){
        if(i%p){fact.pb((fact[i-1]*i)%pe);}
        else {fact.pb(fact[i-1]);}
    }
    return;
}
// again note this has ignored multiples of p
ll Bigfact(ll n,ll mod){
    ll a,b,c,d,i,j,k;
    a=n/mod;a%=phimod;a=power(fact[mod-1],a,mod);
    b=n%mod;a=(a*fact[b])%mod;
    return a;
}
// Chinese Remainder Thm.
vll crtval,crtmod;
ll crt(vll &val,vll &mod){
    ll a,b,c,d,i,j,k;b=1;
    for(ll z:mod)b*=z;
    ll ans=0;
    for(i=0;i<mod.size();i++){
        a=mod[i];c=b/a;
        d=power(c,(((a/pr[i])*(pr[i]-1))-1),a);
        c=(c*d)%b;c=(c*val[i])%b;ans=(ans+c)%b;
    }
    return ans;
}
// calculate for prime powers and
// take crt. For each prime power,
// first ignore multiples of p,
// and then do recursively, calculating
// the powers of p separately.
ll Bigncr(ll n,ll r,ll mod){
    ll a,b,c,d,i,j,k;ll p,pe;
    getprime(mod);ll Fnum=1;ll Fden;
    crtval.clear();crtmod.clear();
    for(i=0;i<pr.size();i++){
        Fnum=1;Fden=1;
        p=pr[i];pe=power(p,prn[i],1e17);
        primeproc(p,pe);
        a=1;d=0;
        phimod=(pe*(p-1LL))/p;
        ll n1=n,r1=r,nr=n-r;
        while(n1){
            Fnum=(Fnum*(Bigfact(n1,pe)))%pe;
            Fden=(Fden*(Bigfact(r1,pe)))%pe;
            Fden=(Fden*(Bigfact(nr,pe)))%pe;
            d+=n1-(r1+nr);
            n1/=p;r1/=p;nr/=p;
        }
        Fnum=(Fnum*(power(Fden,(phimod-1LL),pe)))%pe;
        if(d>=prn[i])Fnum=0;
        else Fnum=(Fnum*(power(p,d,pe)))%pe;
        crtmod.pb(pe);crtval.pb(Fnum);
    }
}
// you can just iterate instead of crt
// for(i=0;i<mod;i++){
//     bool cg=true;

```

```

//     for(j=0;j<crtmod.size();j++){
//         if(i%crtmod[j]!=crtval[j])cg=false;
//     }
//     if(cg)return i;
// }
return crt(crtval,crtmod);
}

```

## 6.8 Primitive Root Generator

```

/*To find generator of U(p),we check for all
g in [1,p]. But only for powers of the
form phi(p)/p_j, where p_j is a prime factor of
phi(p). Note that p is not prime here.
Existence, if one of these : 1. p = 1,2,4
2. p = q^k, where q -> odd prime.
3. p = 2.(q^k), where q-> odd prime
Note that a.g^(phi(p)) = 1 (mod p)
b.there are phi(phi(p)) generators if exists.
Finds "a" generator of U(p), multiplicative group
of integers mod p. Here calc_phi returns the totient
function for p. O(Ans.log(phi(p)).log(p)) +
time for factorizing phi(p). By some theorem,
Ans = O((log(p))^6). Should be fast generally.*/
int generator(int p) {
    vector<int> fact;
    int phi = calc_phi(p), n = phi;
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1)fact.push_back(n);
    for (int res=2; res<=p; ++res) {
        if(gcd(res,p)!=1)continue;
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod(res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}

```

## 7 Strings

### 7.1 Hashing Theory

If order not imp. and count/frequency imp. use [this](#) ←  
as hash fn:-

```

((a_1+h)^k + (a_2+h)^k + (a_3+h)^k + (a_4+h)^k ) % p ←
. Select : h,k,p
Alternate:
((x)^(a_1)+(x)^(a_2)+...+(x)^(a_k))%mod where x and ←
mod are fixed and a_1...a_k is an unordered set

```

## 7.2 Manacher

```

// Same idea as Z_algo, Time : O(n)
// [l,r] represents : boundaries of rightmost ←
// detected subpalindrom (with max r)
// takes string s and returns a vector of lengths of ←
// odd length palindrom
// centered around that char (e.g abac for 'b' returns ←
// 2(not 3))
vll manacher_odd(string s){
    ll n = s.length(); vll d1(n);
    for(ll i = 0, l = 0, r = -1; i<n; i++){
        d1[i] = 1;
        if(i <= r){
            d1[i] = min(r-i+1, d1[l+r-i]); // use prev ←
            val
        }
        while(i+d1[i] < n && i-d1[i] >= 0 && s[i+d1[i] ←
            ] == s[i-d1[i]]) d1[i]++; // trivial ←
            matching
        if(r < i+d1[i]-1) l=i-d1[i]+1, r=i+d1[i]-1; ←
        // update r
    }
    return d1;
}
// takes string s and returns vector of lengths of ←
// even length ...
// (it's centered around the right middle char, bb is ←
// centered around the later 'b')
vll manacher_even(string s){
    ll n = s.length(); vll d2(n);
    for(ll i = 0, l = 0, r = -1; i<n; i++){
        d2[i] = 0;
        if(i <= r){
            d2[i] = min(r-i+1, d2[l+r+1-i]);
        }
        while(i+d2[i] < n && i-d2[i]-1 >= 0 && s[i+d2[ ←
            i]] == s[i-d2[i]-1]) d2[i]++;
        if(d2[i] > 0 && r < i+d2[i]-1) l=i-d2[i], r=i ←
            +d2[i]-1;
    }
    return d2;
}
// Other mtd : To do both things in one pass, add ←
// special char e.g string "abc" => "$a$b$c$"

```

## 7.3 Trie

```

const ll AS = 26; // alphabet size
ll go[MAX][AS]; ll cnt[MAX]; ll cn=0;
// cn -> index of next new node
// convert all strings to vll
ll newNode() {
    for(ll i=0; i<AS; i++){
        go[cn][i] = -1;
    }
    return cn++;
}
// call newNode once **** before adding anything **
void addTrie(vll &x) {
    ll v = 0;
    cnt[v]++;
    for(ll i=0; i<x.size(); i++){
        ll y=x[i];
        if(go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
        cnt[v]++;
    }
}
// returns count of substrings with prefix x
ll getcount(vll &x){
    ll v=0;
    for(i=0; i<x.size(); i++){
        ll y=x[i];
        if(go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
    }
    return cnt[v];
}

```

## 7.4 Z-algorithm

```

// [l,r] -> indices of the rightmost segment match
// (the detected segment that ends rightmost (with max ←
// r))
// 2 cases -> 1st. i <= r : z[i] is atleast min(r-i ←
// +1, z[i-1]), then match trivially
// 2nd. o.w compute z[i] with trivial matching
// update l,r
// Time : O(n) (asy. behavior), Proof : each iteration ←
// of inner while loop make r pointer advance to ←
// right,
// Applications: 1) Search substring(text t, ←
// pattern p) s = p + '$' + t.
// 3) String compression(s = t+t+...+t, then find |t ←
// |)
// 2) Number of distinct substrings (in O(n^2))
// (useful when appending or deleting characters ←
// online from the end or beginning)
vector<ll> z_function(string s) {

```

```

11 n = (ll) s.length();
vector<ll> z(n);
for (ll i = 1, l = 0, r = 0; i < n; ++i) {
    if (i <= r)
        z[i] = min (r - i + 1, z[i - 1]); // use ←
        previous z val
    while (i + z[i] < n && s[z[i]] == s[i + z[i]←
    ]) // trivial matching
        ++z[i];
    if (i + z[i] - 1 > r)
        l = i, r = i + z[i] - 1; // update ←
        rightmost segment matched
}
return z;
}

```

## 7.5 Aho Corasick

```

const int K = 26;
// remember to set K
struct Vertex {
    int next[K]; bool leaf = false;
    int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};
vector<Vertex> aho(1);
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (aho[v].next[c] == -1) {
            aho[v].next[c] = aho.size();
            aho.emplace_back(v, ch);
        }
        v = aho[v].next[c];
    }
    aho[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (aho[v].link == -1) {
        if (v==0 || aho[v].p==0) aho[v].link = 0;
        else aho[v].link =
            go(get_link(aho[v].p), aho[v].pch);
    }
    return aho[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (aho[v].go[c] == -1) {
        if (aho[v].next[c] != -1)
            aho[v].go[c] = aho[v].next[c];
        else

```

```

        aho[v].go[c] = v == 0 ? 0 : go(get_link(v), ch)←
    }
    return aho[v].go[c];
}

```

## 7.6 KMP

```

/*Time:O(n)(j increases n times(& j>=0) only so asy. ←
0(n))
pi[i] = length of longest prefix of s ending at i
applications: search substring, # of different ←
substrings(O(n^2)),
3) String compression(s = t+t+...+t, then find |t|, k←
=n-pi[n-1],if k|n)
4) Building Automaton(Gray Code Example)*/
vector<ll> prefix_function(string s) {
    ll n = (ll)s.length();
    vector<ll> pi(n);
    for (ll i = 1; i < n; i++) {
        ll j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j]) j++;
        pi[i] = j;
    }
    return pi;
}
// searching s in t, returns all occurrences(indices)
vector<ll> search(string s, string t) {
    vll pi = prefix_function(s);
    ll m = s.length(); vll ans; ll j = 0;
    for (ll i=0; i<t.length(); i++) {
        while (j > 0 && t[i] != s[j])
            j = pi[j-1];
        if (t[i] == s[j]) j++;
        if (j == m) ans.pb(i-m+1);
    }
    return ans; // if ans empty then no occurrence
}

```

## 7.7 Palindrome Tree

```

const ll MAX=1e5+15;
ll par[MAX]; // stores index of parent node
ll sul[1][MAX]; // stores index of suffix link
ll len[MAX]; // stores len of largest
pallindrome ending at that node */
ll child[MAX][30]; // stores the children of the node
/*-----
index 0 - root "-1"

```

```

index 1 - root "0"
therefore node of s[i] is i+2
initialize all child[i][j] to -1
-----*/
void eer_tree(string s){
    ll a,b,c,d,i,j,k,e,f;
    sul1[1]=0;sul1[0]=0;len[1]=0;len[0]=-1;
    ll n=s.length();
    for(i=0;i<n+10;i++){
        for(j=0;j<30;j++) child[i][j]=-1;
    }
    ll cur=1;d=1;
    for(i=0;i<s.size();i++){
        ++d;
        while(true){
            a=i-1-len[cur];
            if(a>=0){
                if(s[a]==s[i]){
                    if(child[cur][(ll)(s[i]-'a')]==-1){
                        par[d]=cur;child[cur][(ll)(s[i]-'a')]=d;
                        len[d]=len[cur]+2;cur=d;
                    }
                    else{
                        par[d]=cur;len[d]=len[cur]+2;
                        cur=child[cur][(ll)(s[i]-'a')]];
                    }
                }
                break;
            }
        }
        if(cur==0)break;
        cur=sul1[cur];
    }
    if(cur!=d)continue;
    if(len[d]==1)sul1[d]=1;
    else{
        c=sul1[par[d]];
        while(child[c][(ll)(s[i]-'a')]==-1){
            if(c==0)break;
            c=sul1[c];
        }
        sul1[d]=child[c][(ll)(s[i]-'a')]];
    }
}
}
}

```

## 7.8 Suffix Array

/\*Sorted array of suffixes = sorted array of cyclic shifts of string+\$. We consider a prefix of len.  $2^k$  of the cyclic, in the kth iteration. String of len.  $2^k$  → combination of 2 strings of len.  $2^{(k-1)}$ , whose order we know, from previous iteration. Just radix sort on pair for next iteration.  
Time :-  $O(n \log(n) + \text{alphabet})$ . Applications :-  
Finding the smallest cyclic shift; Finding a substring in a string; Comparing two substrings of a string; Longest common prefix of two substrings; Number of

```

different substrings. */
//returns permutation of indices in sorted order ***
vector<ll> sort_cyclic_shifts(string const& s) {
    ll n = s.size();
    const ll alphabet = 256;
    //change the alphabet size accordingly and indexing
    vector<ll> p(n), c(n), cnt(max(alphabet, n), 0);
    // p:sorted ord. of 1-len prefix of each cyclic
    // shift index. c:class of a index
    // pn:same as p for kth iteration . ||ly cn.
    for (ll i = 0; i < n; i++)
        cnt[s[i]]++;
    for (ll i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (ll i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    ll classes = 1;
    for (ll i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
        c[p[i]] = classes - 1;
    }
    vector<ll> pn(n), cn(n);
    for (ll h = 0; (1 << h) < n; ++h) {
        for (ll i = 0; i < n; i++) { //sorting w.r.t
            pn[i] = p[i] - (1 << h); //second part.
            if (pn[i] < 0)
                pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (ll i = 0; i < n; i++)
            cnt[c[pn[i]]]++;
        for (ll i = 1; i < classes; i++)
            cnt[i] += cnt[i-1];
        // sorting w.r.t. 1st(more significant) part
        for (ll i = n-1; i >= 0; i--)
            p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0; classes = 1;
        // determining new classes in sorted array.
        for (ll i = 1; i < n; i++) {
            pll cur={c[p[i]],c[(p[i]+(1<<h))%n]};
            pll prev={c[p[i-1]],c[(p[i-1]+(1<<h))%n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}
vector<ll> suffix_array_construction(string s) {
    s += "$";
    vector<ll> sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}
// For comp. two substr. of len. l starting at i,j.

```



```

// k - 2^k > l/2. check the first 2^k part, if equal,
// check last 2^k part. c[k] is the c in kth iter
//of S.A construction.
int compare(int i, int j, int l, int k) {
    pll a = {c[k][i], c[k][(i+l-(1 << k))%n]};
    pll b = {c[k][j], c[k][(j+l-(1 << k))%n]};
    return a == b ? 0 : a < b ? -1 : 1; }
/*lcp[i]=len. of lcp of ith & (i+1)th suffix in the ←
SA
1.Consider suffixes in decreasing order of length.
2.Let p = s[i...n]. It will be somewhere in the S.A.
We determine its lcp = k. 3.Then lcp of q=s[(i+1)..n]
will be atleast k-1 coz 4.remove the first char of p
and its successor in the S.A. These are suffixes with
lcp k-1. 5.But note that these 2 may not be ←
consecutive
in S.A.But lcp of str. in b/w have to be also >= k-1.←
*/
vll lcp_cons(string const& s, vector<ll> const& p) {
    ll n = s.size();
    vector<ll> rank(n, 0);
    for (ll i = 0; i < n; i++)
        rank[p[i]] = i;
    ll k = 0; vector<ll> lcp(n-1, 0);
    for (ll i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0; continue; }
        ll j = p[rank[i] + 1];
        while(i+k<n && j+k<n && s[i+k]==s[j+k]) k++;
        lcp[rank[i]] = k; if (k) k--; }
    return lcp;
}

```

## 7.9 Suffix Tree

```

const int N=1000000, // set it more than 2*(len. of ←
string)
string str; // input string for which the suffix tree←
is being built
int chi[N][26],
lef[N], // left...
rig[N], // ...and right boundaries of the substring ←
of a which correspond to incoming edge
par[N], // parent of the node
sfli[N], // suffix link
tv, tp, la,
ts; // the number of nodes
void ukkadd(int c) {
    suff++;
    if (rig[tp]<tp){
        if (chi[tp][c]==-1){chi[tp][c]=ts;lef[ts]=la;
            par[ts++]=tv;tv=sfli[tp];tp=rig[tp]+1;goto suff;}
        tv=chi[tp][c];tp=lef[tp];
    }
    if (tp==-1 || c==str[tp]-'a')tp++;
}

```

```

else {
    lef[ts]=lef[tp]; rig[ts]=tp-1; par[ts]=par[tp];
    chi[ts][str[tp]-'a']=tv; chi[ts][c]=ts+1;
    lef[ts+1]=la; par[ts+1]=ts; lef[tp]=tp; par[tp]=←
    ts;
    chi[par[ts]][str[lef[ts]]-'a']=ts; ts+=2;
    tv=sfli[par[ts-2]]; tp=lef[ts-2];
    while (tp <= rig[ts-2]) {
        tv=chi[tp][str[tp]-'a']; tp+=rig[tp]-lef[tp]←
        +1;}
    if (tp == rig[ts-2]+1) sfli[ts-2]=tv; else sfli[←
    ts-2]=ts;
    tp=rig[tp]-(tp-rig[ts-2])+2;goto suff;
}
}
void build() {
    ts=2; tv=0; tp=0;
    ll ss = str.size();ss*=2;ss+=15;
    fill(rig,rig+ss,(int)str.size()-1);
    // initialize data for the root of the tree
    sfli[0]=1; lef[0]=-1; rig[0]=-1;
    lef[1]=-1; rig[1]=-1; for (ll i=0;i<ss;i++)
        fill (chi[i], chi[i]+27,-1);
    fill(chi[1],chi[1]+26,0);
    // add the text to the tree, letter by letter
    for (la=0; la<(int)str.size(); ++la)
        ukkadd (str[la]-'a');
}

```