

Codebook- Team Far Behind

IIT Delhi, India

Ayush Ranjan, Naman Jain, Manish Tanwar

Contents		
1 Syntax		
1.1 Template		
1.2 C++ Sublime Build		
2 Data Structures		
2.1 Fenwick		
2.2 2D-BIT		
2.3 Segment Tree		
2.4 Persistent Segment Tree		
2.5 DP Optimization		
3 Flows and Matching		
3.1 General Matching		
3.2 Global Mincut		
3.3 Hopcroft Matching		
3.4 Dinic		
3.5 Ford Fulkerson		
3.6 MCMF		
3.7 MinCost Matching		
4 Geometry		
4.1 Geometry		
4.2 Convex Hull		
4.3 Convex Hull Trick		
5 Trees		
5.1 BlockCut Tree		
5.2 Bridges Online		
5.3 HLD		
5.4 LCA		
5.5 Centroid Decompostion		16
6 Maths		16
6.1 Chinese Remainder Theorem		16
6.2 Discrete Log		17
6.3 NTT		17
6.4 Online FFT		19
6.5 Langrange Interpolation		19
6.6 Matrix Struct		19
6.7 nCr(Non Prime Modulo)		20
6.8 Primitive Root Generator		20
7 Strings		21
7.1 Hashing Theory		21
7.2 Manacher		21
7.3 Trie		21
7.4 Z-algorithm		22
7.5 Aho Corasick		22
7.6 KMP		22
7.7 Palindrome Tree		23
7.8 Suffix Array		23
7.9 Suffix Tree		24
1 Syntax		
1.1 Template		
<pre>#include <bits/stdc++.h> #include <ext/pb_ds/assoc_container.hpp> using namespace __gnu_pbds; using namespace std; template<class T> ostream& operator<<(ostream &os, ← vector<T> V) {</pre>		

```

os << "["; for(auto v : V) os << v << " "; return <←
os << "];}
template<class L, class R> ostream& operator<<(<←
ostream &os, pair<L,R> P) {
return os << "(" << P.first << "," << P.second << "←
)";}
#define TRACE
#ifdef TRACE
#define trace(...) _f(#__VA_ARGS__, __VA_ARGS__)
template <typename Arg1>
void _f(const char* name, Arg1&& arg1){
cout << name << " : " << arg1 << std::endl;
}
template <typename Arg1, typename... Args>
void _f(const char* names, Arg1&& arg1, Args&&... <←
args){
const char* comma = strchr(names + 1, ',');cout.<←
write(names, comma - names) << " : " << arg1<<" <←
| ";_f(comma+1, args...);
}
#else
#define trace(...) 1
#endif
#define ll long long
#define ld long double
#define vll vector<ll>
#define pll pair<ll,ll>
#define vpll vector<pll>
#define I insert
#define pb push_back
#define F first
#define S second
#define all(x) x.begin(),x.end()
#define endl "\n"
// const ll MAX=1e6+5;
// int mod=1e9+7;
inline int mul(int a,int b){return (a*1ll*b)%mod;}
inline int add(int a,int b){a+=b;if(a>=mod)a-=mod;<←
return a;}
inline int sub(int a,int b){a-=b;if(a<0)a+=mod;return<←
a;}
inline int power(int a,int b){int rt=1;while(b>0){if(<←
b&1)rt=mul(rt,a);a=mul(a,a);b>>=1;}return rt;}
inline int inv(int a){return power(a,mod-2);}
inline void modadd(int &a,int b){a+=b;if(a>=mod)a-<←
mod;}
int main(){
ios_base::sync_with_stdio(false);cin.tie(0);cout.<←
tie(0);cout<<setprecision(25);
}
// clock
clock_t clk = clock();
clk = clock() - clk;
((ld)clk)/CLOCKS_PER_SEC
// fastio
inline ll read() {
ll n = 0; char c = getchar_unlocked();
while (!('0' <= c && c <= '9')) c = <←
getchar_unlocked();

```

```

while ('0' <= c && c <= '9')
n = n * 10 + c - '0', c = getchar_unlocked();
return n;
}
inline void write(ll a){
register char c; char snum[20]; ll i=0;
do{
snum[i++]=a%10+48;
a=a/10;
}while(a!=0); i--;
while(i>=0)
putchar_unlocked(snum[i--]);
putchar_unlocked('\n');
}
using getline, use cin.ignore()
// gp_hash_table
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
gp_hash_table<int, int> table; //cc_hash_table can <←
also be used
//custom hash function
const int RANDOM = chrono::high_resolution_clock::now<←
().time_since_epoch().count();
struct chash {
int operator()(int x) { return hash<int>{}(x ^ <←
RANDOM); }
};
gp_hash_table<int, int, chash> table;
//custom hash function for pair
struct chash {
int operator()(pair<int,int> x) const { return x.<←
first* 31 + x.second; }
};
// random
mt19937 rng(chrono::steady_clock::now().<←
time_since_epoch().count());
uniform_int_distribution<int> uid(1,r);
int x=uid(rng);
//mt19937_64 rng(chrono::steady_clock::now().<←
time_since_epoch().count());
// - for 64 bit unsigned numbers
vector<int> per(N);
for (int i = 0; i < N; i++)
per[i] = i;
shuffle(per.begin(), per.end(), rng);
// string splitting
// this splitting is better than custom function(w.r.<←
t time)
string line = "Ge";
vector <string> tokens;
stringstream check1(line);
string ele;
// Tokenizing w.r.t. space ' '
while(getline(check1, ele, ' '))
tokens.push_back(ele);

```

1.2 C++ Sublime Build

```
{
  "cmd": ["bash", "-c", "g++ -std=c++11 -O3 '${file}' -o '${file_path}/${file_base_name}' && gnome-terminal -- bash -c '\"${file_path}/${file_base_name}\" < input.txt > output.txt' "],
  "file_regex": "^(..[^:]*):([0-9]+):?([0-9]+)??:? (.*)$",
  "working_dir": "${file_path}",
  "selector": "source.c++, source.cpp",
}
```

2 Data Structures

2.1 Fenwick

```
/*All indices are 1 indexed
*Range update and point query: maintain BIT of prefix sum of updates
-add val in [a,b] -> add val at a, -val at b
-value[a]=BITsum(a)+arr[a]
*Range update ,range query: maintain 2 BITs B1,B2
-add val in [a,b] -> B1:add val at a, -val at b+1 and in B2 -> Add val*(a-1) at a, -val*b at b+1
-sum[1,b]=B1sum(1,b)*b-B2sum(1,b)
-sum[a,b]=sum[1,b]-sum[1,a-1]*/
ll fen[MAX_N];
void update(ll p,ll val){
    for(ll i = p;i <= n;i += i & -i)
        fen[i] += val;
}
ll sum(ll p){
    ll ans = 0;
    for(ll i = p;i >= 1;i -= i & -i) ans += fen[i];
    return ans;
}
```

2.2 2D-BIT

```
/*All indices are 1 indexed.Increment value of cell (i,j) by val -> update(x,y,val)
*sum of rectangle [a,b]-[c,d] ->sum of rectangles [1,1]-[c,d],[1,1]-[c,b],[1,1][a,d] and [1,1]-[a,b] and use inclusion exclusion*/
ll bit[MAX][MAX];
void update(ll x , ll y, ll val){
    while( x < MAX ){
        ll y1 = y;
        while( y1 < MAX )
            bit[x][y1] += val , y1 += ( y1 & -y1 );
        x += ( x & -x );
    }
}
```

```
ll sum(ll x , ll y){
    ll ans = 0;
    while( x > 0 ){
        ll y1 = y;
        while( y1 > 0 )
            ans += bit[x][y1] , y1 -= ( y1 & -y1 );
        x -= ( x & -x );
    }
    return ans;
}
```

2.3 Segment Tree

```
/*All arrays are 0 indexed. call bld(0,n-1,1)
upd(0,n-1,1,x,y,val) -> increase [x,y] by val
sum(0,n-1,1,x,y) -> sum [x,y]
array of size N -> segment tree of size 4*N*/
ll arr[N],st[N<<2],lz[N<<2];
void ppgt(ll l, ll r,ll id){
    if(l==r) return;
    ll m=l+r>>1;
    lz[id*2] += lz[id];lz[id<<1|1] += lz[id];
    st[id << 1] += (m - l + 1) * lz[id];
    st[id<<1|1] += (r-m)*lz[id];lz[id] = 0;
}
void bld(ll l,ll r,ll id){
    if(l==r) { st[id] = arr[l]; return; }
    bld(l,l+r>>1,id*2);bld(l+r+1>>1,r,id*2+1);
    st[id] = st[id << 1] + st[id << 1 | 1];
}
void upd(ll l,ll r,ll id,ll x,ll y,ll val){
    if (l > y || r < x) return;ppgt(l, r, id);
    if (l >= x && r <= y) {
        lz[id] += val;st[id] += (r-l+1)*val; return;
    }
    upd(l,l + r >> 1,id << 1, x, y, val);upd((l + r >> 1) + 1,r ,id << 1 | 1,x, y, val);
    st[id] = st[id << 1] + st[id << 1 | 1];
}
ll sum(ll l,ll r,ll id,ll x,ll y){
    if (l > y || r < x) return 0;ppgt(l, r, id);
    if (l >= x && r <= y) return st[id];
    return sum(l, l + r >> 1,id << 1, x, y) + sum((l + r >> 1) + 1,r ,id << 1 | 1,x, y);
}
```

2.4 Persistent Segment Tree

```
/*id of first node = 0. call build(0,n-1) first. afterwards call upd(0,n-1,previous id,i,val) to add val in ith number. It returns root of new segment tree after modification
*sum(0,n-1,id of root,l,r) -> sum of values in subarray l to r in tree rooted at id
**size of st,lc,rc >= N*2+(N+Q)*logN*/
const ll N=1e5+10;
ll arr[N],st[20*N],lc[20*N],rc[20*N],ids[N],cnt;
void build(ll l,ll r){
```

```

if(l==r) {st[cnt]=arr[l];++cnt;return;}
ll id = cnt++;lc[id] = cnt;
build( l, l+r >>1);
rc[id] = cnt; build( (l + r >> 1) + 1, r);
st[id] = st[lc[id]] + st[rc[id]];}
ll upd(ll l,ll r,ll id,ll x,ll val){
if(l == r)
{st[cnt]=st[id]+val;++cnt;return cnt-1;}
ll myid = cnt++; ll mid = l + r >>1;
if(x <= mid)
rc[myid] = rc[id],lc[myid] = upd(l, mid, lc[id], ←
x, val);
else
lc[myid] = lc[id],rc[myid] = upd(mid+1, r, rc[id]←
l, x, val);
st[myid] = st[lc[myid]] + st[rc[myid]];
return myid;}
ll sum(ll l,ll r,ll id,ll x,ll y){
if (l > y || r < x ) return 0;
if (l >= x && r <= y ) return st[id];
return sum(l, l + r >> 1,lc[id], x, y) + sum((l + r←
>> 1) + 1,r ,rc[id],x, y);}
ll gkth(ll l,ll r,ll id1,ll id2,ll k){
if(l==r) return l;ll mid = l+r>>1;
ll a=st[lc[id2]]-(id1>=0?st[lc[id1]]:0);
if(a >= k)
return gkth(l, mid ,(id1>=0?lc[id1]:-1), lc[id2],←
k);
else
return gkth(mid+1, r,(id1>=0?rc[id1]:-1), rc[id2]←
l, k-a);}
//kth largest num in range
int main(){
ll n,m;vll finalid(n);vp11 v;
loop : v.pb({arr[i],i});sort(all(v));
loop : finalid[v[i].second]=i;
memset(arr,0,sizeof(ll)*N);
arr[finalid[0]]++;build(0,n-1);
loop:ids[i]=upd(0,n-1,ids[i-1],finalid[i],1);
while(m--){
ll i,j,k;cin>>i>>j>>k;--i;--j;
ans=gkth(0,n-1,(i==0?-1:ids[i-1]),ids[j],k);
cout<<v[ans].F<<endl;}
}

```

2.5 DP Optimization

/*You have an array of size L.You need to split it into G intervals, minimizing the cost. (G<=L otherwise we can just split in 1-intervals). There is a cost function C[i,j] of taking an interval. The cost function satisfies : $C[a,b]+C[c,d] \leq C[a,d]+C[c,b]$ for all $a \leq c \leq b \leq d$.

This is the quadrangle inequality and intuitively you can think that the cost function increases at a rate which is more than linear at all intervals (may not be strictly true). So , if the cost function satisfies this inequality, the following property holds :
 $F(g,l)$: min cost of splitting first l elements into g intervals
Basic recurrence : $F(g,l) = \min(F(g-1,k)+C(k+1,l))$ over all valid k.
 $P(g,l)$: lowest position k s.t. it minimizes $F(g,l)$.
 $P(g,0) \leq P(g,1) \leq P(g,2) \dots \leq P(g,l-1) \leq P(g,l)$. (DivConqOpti, $O(G.L \log(L))$)
Also, $P(0,l) \leq P(1,l) \leq P(2,l) \dots \leq P(G-1,l) \leq P(G,l)$. This with previous inequality leads to Knuth Opti, complexity $O(L.L)$.
For div&conq, we calculate $P(g,l)$ for each g 1 by 1. In each g, we calculate for mid-l and solve recursively using the obtained upper and lower bounds. For knuth, we use $P(g,l-1) \leq P(g,l) \leq P(g+1,l)$, and fill our table in increasing l and decreasing g. In opt. BST type problems, use $bk[i][j-1] \leq bk[i][j] \leq bk[i+1][j]$. */
// Code for Divide and Conquer Opti $O(G.L \log(L))$: -
ll C[8111];
ll sums[8111];
ll F[8111][8111]; // optimal value
int P[8111][8111]; // optimal position.
// note first val. in arrays is for no. of groups
ll cost(int i, int j) { // cost function
return i > j ? 0 : (sums[j] - sums[i-1]) * (j - i + 1);
}
// fill(g,l1,l2,p1,p2) calculates all $P[g][l]$ and $F[g][l]$
// for $l1 \leq l \leq l2$, with the knowledge that $p1 \leq P[g][l1] \leq p2$
void fill(int g, int l1, int l2, int p1, int p2) {
if (l1 > l2) return;
int lm = (l1 + l2) >> 1;
ll nv=INF,nv1=-1;
for (int k = p1; k <= min(lm-1,p2); k++) {
ll new_cost = F[g-1][k] + cost[k+1][lm];
if (nv > new_cost) {
nv = new_cost;
nv1 = k;
}
}
P[g][lm]=nv1; F[g][lm]=nv;
fill(g, l1, lm-1, p1, P[g][lm]);
fill(g, lm+1, l2, P[g][lm], p2);
}
int main() { // example call

```

for(i=0;i<=n;i++)F[0][i]=INF;
for(i=0;i<=k;i++)F[i][0]=0;
F[0][0]=0;
for(i=1;i<=k;i++)fill(i,1,n,0,n);
}
// Code for Knuth Optimization O(L.L) :-
ll dp[8002][802];
int a[8002],s[8002][802];
ll sum[8002];
// index strats from 1
ll run(int n,int m) {
    memset(dp,0xff,sizeof(dp));
    dp[0][0] = 0;
    for (int i = 1; i <= n; ++i) {
        sum[i] = sum[i - 1] + a[i];
        int maxj = min(i, m), mk;
        ll mn = INF;
        for (int k = 0; k < i; ++k) {
            if (dp[k][maxj - 1] >= 0) {
                ll tmp = dp[k][maxj - 1] +
                    (sum[i] - sum[k]) * (i - k); ←
                //k + 1..i
                if (tmp < mn) {
                    mn = tmp;
                    mk = k;
                }
            }
        }
        dp[i][maxj] = mn;
        s[i][maxj] = mk;
        for (int j = maxj - 1; j >= 1; --j) {
            ll mn = INF;
            int mk;
            for (int k = s[i - 1][j]; k <= s[i][j] + ←
                1; ++k) {
                if (dp[k][j - 1] >= 0) {
                    ll tmp = dp[k][j - 1] +
                        (sum[i] - sum[k]) * (i - k);
                    if (tmp < mn) {
                        mn = tmp;
                        mk = k;
                    }
                }
            }
            dp[i][j] = mn;
            s[i][j] = mk;
        }
    }
    return dp[n][m];
}
// call -> run(n, min(n,m))

```

3 Flows and Matching

3.1 General Matching

```

/*Given any directed graph, finds maximal matching
Vertices-0-indexed, 0(n^3) per call to edmonds*/
vll adj[MAXN]; int p[MAXN], base[MAXN], match[MAXN];
int lca(int n, int u, int v){
    vector<bool> used(n);
    for (;;) {
        u = base[u]; used[u] = true;
        if (match[u] == -1) break; u = p[match[u]];
    }
    for (;;) {
        v = base[v]; if (used[v]) return v;
        v = p[match[v]];
    }
}
void mark_path(vector<bool> &blo,int u,int b,int ←
    child){
    for (; base[u] != b; u = p[match[u]]){
        blo[base[u]] = true; blo[base[match[u]]] = true;
        p[u] = child; child = match[u];
    }
}
int find_path(int n, int root) {
    vector<bool> used(n);
    for (int i = 0; i < n; ++i)
        p[i] = -1, base[i] = i;
    used[root] = true;
    queue<int> q; q.push(root);
    while(!q.empty()) {
        int u = q.front(); q.pop();
        for (int j = 0; j < (int)adj[u].size(); j++) {
            int v = adj[u][j];
            if(base[u]==base[v] || match[u]==v)continue;
            if(v==root||(match[v]!=-1 && p[match[v]]!=-1)){
                int curr_base = lca(n, u, v);
                vector<bool> blossom(n);
                mark_path(blossom, u, curr_base, v);
                mark_path(blossom, v, curr_base, u);
                for(int i = 0; i < n; i++){
                    if(blossom[base[i]]){
                        base[i] = curr_base;
                        if(!used[i]) used[i] = true, q.push(i);
                    }
                }
            }
            }else if (p[v] == -1){
                p[v] = u;
                if (match[v] == -1) return v;
                v=match[v]; used[v]=true; q.push(v);
            }
        }
    }
    return -1;
}
int edmonds(int n){
    for(int i=0;i<n;i++) match[i] = -1;
    for(int i = 0; i < n; i++){
        if (match[i] == -1) {
            int u, pu, ppu;

```

```

        for (u = find_path(n, i); u != -1; u = ppu) {
            pu = p[u]; ppu = match[pu];
            match[u] = pu; match[pu] = u;
        }
    }
}
int matches = 0;
for (int i = 0; i < n; i++)
    if (match[i] != -1) matches++;
return matches/2;
}
u--; v--; adj[u].pb(v); adj[v].pb(u);
cout << edmonds(n) * 2 << endl;
for (int i = 0; i < n; i++) {
    if (match[i] != -1 && i < match[i]) {
        cout << i + 1 << " " << match[i] + 1 << endl;
    }
}
}

```

3.2 Global Mincut

```

/*finds min weighted cut in undirected graph in
O(n^3), Adj Matrix, 0-indexed vertices
output-(min cut value, nodes in half of min cut)*/
typedef vector<int> VI;
typedef vector<VI> VVI;
const int INF = 1000000000;
pair<int, VI> GetMinCut(VVI &weights) {
    int N = weights.size();
    VI used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N-1; phase >= 0; phase--) {
        VI w = weights[0];
        VI added = used;
        int prev, last = 0;
        for (int i = 0; i < phase; i++) {
            prev = last; last = -1;
            for (int j = 1; j < N; j++)
                if (!added[j] && (last == -1 || w[j] > w[last]))
                    last = j;
            if (i == phase-1) {
                for (int j=0; j<N; j++)
                    weights[prev][j] += weights[last][j];
                for (int j=0; j<N; j++)
                    weights[j][prev] = weights[prev][j];
                used[last] = true; cut.push_back(last);
                if (best_weight==-1 || w[last]<best_weight)
                    best_cut = cut, best_weight = w[last];
            }
            else {
                for (int j = 0; j < N; j++)
                    w[j] += weights[last][j];
                added[last] = true;
            }
        }
    }
}

```

```

    }
}
return make_pair(best_weight, best_cut);
}
VVI weights(n, VI(n));
pair<int, VI> res = GetMinCut(weights);

```

3.3 Hopcroft Matching

```

// O(m * \sqrt{n})
struct graph {
    int L, R; // 0-indexed vertices
    vector<vector<int>> adj;
    graph(int L, int R) : L(L), R(R), adj(L+R) {}
    void add_edge(int u, int v) {
        adj[u].pb(v+L); adj[v+L].pb(u);
    }
    int maximum_matching() {
        vector<int> level(L), mate(L+R, -1);
        function<bool(void)> levelize = [&]() { // BFS
            queue<int> Q;
            for (int u = 0; u < L; ++u) {
                level[u] = -1;
                if (mate[u] < 0) level[u] = 0, Q.push(u);
            }
            while (!Q.empty()) {
                int u = Q.front(); Q.pop();
                for (int w: adj[u]) {
                    int v = mate[w];
                    if (v < 0) return true;
                    if (level[v] < 0)
                        level[v] = level[u] + 1, Q.push(v);
                }
            }
            return false;
        };
        function<bool(int)> augment = [&](int u) { // DFS
            for (int w: adj[u]) {
                int v = mate[w];
                if (v<0 || (level[v]>level[u] && augment(v))) {
                    mate[u] = w; mate[w] = u; return true;
                }
            }
            return false;
        };
        int match = 0;
        while (levelize())
            for (int u = 0; u < L; ++u)
                if (mate[u] < 0 && augment(u)) ++match;
        return match;
    };
}; // L-left size, R->right size
graph g(L,R); g.add_edge(u,v); g.maximum_matching();

```


3.4 Dinic

```
/*0(min(fm,mn^2)), for any unit capacity network
0(m*sqrt(n)), in practice it is pretty fast for any
bipartite network, **vertices are 1-indexed**
e=(u,v), e.flow represent effective flow from u to v
(i.e f(u->v) - f(v->u))
*use int if possible(ll could be slow in dinic)*/
struct edge {ll x, y, cap, flow;};
struct DinicFlow {
    // *** change inf accordingly *****
    const ll inf = (1e18);
    vector<edge> e; vll cur, d;
    vector<vll> adj; ll n, source, sink;
    DinicFlow() {}
    DinicFlow(ll v) {
        n = v; cur = vll(n+1);
        d = vll(n+1); adj = vector<vll>(n+1);}
    void addEdge(ll from, ll to, ll cap) {
        edge e1 = {from, to, cap, 0};
        edge e2 = {to, from, 0, 0};
        adj[from].pb(e1.size()); e.pb(e1);
        adj[to].pb(e2.size()); e.pb(e2);
    }
    ll bfs() {
        queue<ll> q;
        for(ll i = 0; i <= n; ++i) d[i] = -1;
        q.push(source); d[source] = 0;
        while(!q.empty() and d[sink] < 0) {
            ll x = q.front(); q.pop();
            for(ll i = 0; i < (ll)adj[x].size(); ++i){
                ll id = adj[x][i], y = e[id].y;
                if(d[y]<0 and e[id].flow < e[id].cap){
                    q.push(y); d[y] = d[x] + 1;
                }
            }
        }
        return d[sink] >= 0;
    }
    ll dfs(ll x, ll flow) {
        if(!flow) return 0;
        if(x == sink) return flow;
        for(;cur[x] < (ll)adj[x].size(); ++cur[x]) {
            ll id = adj[x][cur[x]], y = e[id].y;
            if(d[y] != d[x] + 1) continue;
            ll pushe=dfs(y,min(flow,e[id].cap-e[id].flow));
            if(pushed) {
                e[id].flow += pushed; e[id^1].flow -= pushed;
                return pushed;
            }
        }
        return 0;
    }
    ll maxFlow(ll src, ll snk) {
        this->source = src; this->sink = snk;
        ll flow = 0;
```

```
        while(bfs()) {
            for(ll i = 0; i <= n; ++i) cur[i] = 0;
            while(ll pushed = dfs(source, inf))
                flow += pushed;
        }
        return flow;
    }
};
```

3.5 Ford Fulkerson

```
/*0(f*m)*/ ll n; // number of vertices
ll cap[N][N]; // adj matrix for cap
vll adj[N]; // *** vertices are 0-indexed ***
// adj list of the corresponding undirected(*imp*)
ll INF = (1e18);
ll snk,cnt;//cnt for vis, no need to initialize vis
vector<ll> par, vis;
ll dfs(ll u,ll curf){
    vis[u] = cnt; if(u == snk) return curf;
    if(adj[u].size() == 0) return 0;
    for(ll j=0;j<5;j++){ // random for good aug.
        ll a = rand()%(adj[u].size()); ll v = adj[u][a];
        if(vis[v]==cnt || cap[u][v] == 0) continue;
        par[v] = u;
        ll f = dfs(v,min(curf, cap[u][v]));
        if(vis[snk] == cnt) return f;
    }
    for(auto v : adj[u]){
        if(vis[v] == cnt || cap[u][v] == 0) continue;
        par[v] = u;
        ll f = dfs(v,min(curf, cap[u][v]));
        if(vis[snk] == cnt) return f;
    }
    return 0;
}
ll maxflow(ll s, ll t) {
    snk = t; ll flow = 0; cnt++;
    par = vll(n,-1); vis = vll(n,0);
    while(ll new_flow = dfs(s,INF)){
        flow += new_flow; cnt++;
        ll cur = t;
        while(cur != s){
            ll prev = par[cur];
            cap[prev][cur] -= new_flow;
            cap[cur][prev] += new_flow;
            cur = prev;
        }
    }
    return flow;
}
```

3.6 MCMF

```

// MCMF Theory:
// 1. If a network with negative costs had no negative cycle it is possible to transform it into one with nonnegative costs. Using  $C_{ij\_new}(pi) = C_{ij\_old} + pi(i) - pi(j)$ , where  $pi(x)$  is shortest path from  $s$  to  $x$  in network with an added vertex  $s$ . The objective value remains the same ( $z\_new = z + constant$ ).  $z(x) = \sum(c_{ij} * x_{ij})$ 
// (x->flow, c->cost, u->cap, r->residual cap).
// 2. Residual Network:  $c_{ji} = -c_{ij}$ ,  $r_{ij} = u_{ij} - x_{ij}$ ,  $r_{ji} = x_{ij}$ .
// 3. Note: If edge  $(i,j), (j,i)$  both are there then residual graph will have four edges b/w  $i,j$  (pairs of parallel edges).
// 4. let  $x^*$  be a feasible soln, its optimal iff residual network  $Gx^*$  contains no negative cost cycle.
// 5. Cycle Cancelling algo => Complexity  $O(n*m^2*U*C)$  ( $C$ ->max abs value of cost,  $U$ ->max cap) ( $m*U*C$  iterations).
// 6. Successive shortest path algo => Complexity  $O(n^3 * B) / O(nm \log n)$  (using heap in Dijkstra) ( $B$  -> largest supply node).
// Works for negative costs, but does not work for negative cycles
// Complexity:  $O(\min(E^2 * V \log V, E \log V * flow))$ 
// to use -> graph  $G(n)$ ,  $G.add\_edge(u,v, cap, cost)$ ,  $G.min\_cost\_max\_flow(s,t)$ 
// ***** INF is used in both flow_type and cost_type so change accordingly
const ll INF = 99999999;
// vertices are 0-indexed
struct graph {
    typedef ll flow_type; // **** flow type ****
    typedef ll cost_type; // **** cost type ****
    struct edge {
        int src, dst;
        flow_type capacity, flow;
        cost_type cost;
        size_t rev;
    };
    vector<edge> edges;
    void add_edge(int src, int dst, flow_type cap, cost_type cost) {
        adj[src].push_back({src, dst, cap, 0, cost, adj[dst].size()});
        adj[dst].push_back({dst, src, 0, 0, -cost, adj[src].size()-1});
    }
    int n;
    vector<vector<edge>> adj;
    graph(int n) : n(n), adj(n) { }

```

```

pair<flow_type, cost_type> min_cost_max_flow(int s, int t) {
    flow_type flow = 0;
    cost_type cost = 0;
    for (int u = 0; u < n; ++u) // initialize
        for (auto &e: adj[u]) e.flow = 0;
    vector<cost_type> p(n, 0);
    auto rcost = [&](edge e) { return e.cost + p[e.src] - p[e.dst]; };
    for (int iter = 0; ; ++iter) {
        vector<int> prev(n, -1); prev[s] = 0;
        vector<cost_type> dist(n, INF); dist[s] = 0;
        if (iter == 0) { // use Bellman-Ford to remove negative cost edges
            vector<int> count(n); count[s] = 1;
            queue<int> que;
            for (que.push(s); !que.empty(); ) {
                int u = que.front(); que.pop();
                count[u] = -count[u];
                for (auto &e: adj[u]) {
                    if (e.capacity > e.flow && dist[e.dst] > dist[e.src] + rcost(e)) {
                        dist[e.dst] = dist[e.src] + rcost(e);
                        prev[e.dst] = e.rev;
                        if (count[e.dst] <= 0) {
                            count[e.dst] = -count[e.dst] + 1;
                            que.push(e.dst);
                        }
                    }
                }
            }
        }
        for (int i=0; i<n; i++) p[i] = dist[i]; // added it
        continue;
    } else { // use Dijkstra
        typedef pair<cost_type, int> node;
        priority_queue<node, vector<node>, greater<node>> que;
        que.push({0, s});
        while (!que.empty()) {
            node a = que.top(); que.pop();
            if (a.S == t) break;
            if (dist[a.S] > a.F) continue;
            for (auto e: adj[a.S]) {
                if (e.capacity > e.flow && dist[e.dst] > a.F + rcost(e)) {
                    dist[e.dst] = dist[e.src] + rcost(e);
                    prev[e.dst] = e.rev;
                    que.push({dist[e.dst], e.dst});
                }
            }
        }
    }
    if (prev[t] == -1) break;
    for (int u = 0; u < n; ++u)
        if (dist[u] < dist[t]) p[u] += dist[u] - dist[t];
}

```



```

function<flow_type(int,flow_type)> augment = ←
    [&](int u, flow_type cur) {
        if (u == s) return cur;
        edge &r = adj[u][prev[u]], &e = adj[r.dst][r.←
            rev];
        flow_type f = augment(e.src, min(e.capacity -←
            e.flow, cur));
        e.flow += f; r.flow -= f;
        return f;
    };
    flow_type f = augment(t, INF);
    flow += f;
    cost += f * (p[t] - p[s]);
}
return {flow, cost};
};

```

3.7 MinCost Matching

```

// Min cost bipartite matching via shortest ←
// augmenting paths
//
// This is an O(n^3) implementation of a shortest ←
// augmenting path
// algorithm for finding min cost perfect matchings ←
// in dense
// graphs. In practice, it solves 1000x1000 problems←
// in around 1
// second.
//
// cost[i][j] = cost for pairing left node i with ←
// right node j
// Lmate[i] = index of right node that left node i ←
// pairs with
// Rmate[j] = index of left node that right node j ←
// pairs with
//
// The values in cost[i][j] may be positive or ←
// negative. To perform
// maximization, simply negate the cost[][] matrix.
typedef ll cost_type;
typedef vector<cost_type> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;
cost_type MinCostMatching(const VVD &cost, VI &Lmate,←
    VI &Rmate) {
    int n = int(cost.size());
    // construct dual feasible solution
    VD u(n);
    VD v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost←
            [i][j]);
    }
}

```

```

}
for (int j = 0; j < n; j++) {
    v[j] = cost[0][j] - u[0];
    for (int i = 1; i < n; i++) v[j] = min(v[j], cost←
        [i][j] - u[i]);
}
// construct primal solution satisfying ←
// complementary slackness
Lmate = VI(n, -1);
Rmate = VI(n, -1);
int mated = 0;
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        if (Rmate[j] != -1) continue;
        if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
            //**** change this comparison if double cost ←
            ****
            Lmate[i] = j;
            Rmate[j] = i;
            mated++;
            break;
        }
    }
}
}
VD dist(n); VI dad(n); VI seen(n);
// repeat until primal solution is feasible
while (mated < n) {
    // find an unmatched left node
    int s = 0;
    while (Lmate[s] != -1) s++;
    // initialize Dijkstra
    fill(dad.begin(), dad.end(), -1);
    fill(seen.begin(), seen.end(), 0);
    for (int k = 0; k < n; k++)
        dist[k] = cost[s][k] - u[s] - v[k];
    int j = 0;
    while (true) {
        // find closest
        j = -1;
        for (int k = 0; k < n; k++) {
            if (seen[k]) continue;
            if (j == -1 || dist[k] < dist[j]) j = k;
        }
        seen[j] = 1;
        // termination condition
        if (Rmate[j] == -1) break;
        // relax neighbors
        const int i = Rmate[j];
        for (int k = 0; k < n; k++) {
            if (seen[k]) continue;
            const cost_type new_dist = dist[j] + cost[i][←
                k] - u[i] - v[k];
            if (dist[k] > new_dist) {
                dist[k] = new_dist;
                dad[k] = j;
            }
        }
    }
}
}

```

```

}
// update dual variables
for (int k = 0; k < n; k++) {
    if (k == j || !seen[k]) continue;
    const int i = Rmate[k];
    v[k] += dist[k] - dist[j];
    u[i] -= dist[k] - dist[j];
}
u[s] += dist[j];
// augment along path
while (dad[j] >= 0) {
    const int d = dad[j];
    Rmate[j] = Rmate[d];
    Lmate[Rmate[j]] = j;
    j = d;
}
Rmate[j] = s;
Lmate[s] = j;
mated++;
}
cost_type value = 0;
for (int i = 0; i < n; i++)
    value += cost[i][Lmate[i]];
return value;
}

```

4 Geometry

4.1 Geometry

```

//small non recursive functions should be made inline
//do not read input in double format if they are ←
integer points
#define ld double
#define PI acos(-1)
//atan2(y,x) slope of line (0,0)->(x,y) in radian (←
PI,PI]
// to convert to degree multiply by 180/PI
ld INF = 1e100;
ld EPS = 1e-9;
inline bool eq(ld a,ld b) {return fabs(a-b)<EPS;}
inline bool lt(ld a,ld b) {return a+EPS<b;}
inline bool gt(ld a,ld b) {return a>b+EPS;}
inline bool le(ld a,ld b) {return lt(a,b)||eq(a,b);}
inline bool ge(ld a,ld b) {return gt(a,b)||eq(a,b);}
struct pt {
    ld x, y;
    pt() {}
    pt(ld x, ld y) : x(x), y(y) {}
    pt(const pt &p) : x(p.x), y(p.y) {}
    pt operator + (const pt &p) const { return pt(x+p.x, ←
    y+p.y); }
}

```

```

pt operator - (const pt &p) const { return pt(x-p.x, ←
x, y-p.y); }
pt operator * (ld c) const { return pt(x*c, y←
*c); }
pt operator / (ld c) const { return pt(x/c, y←
/c); }
bool operator < (const pt &p) const { return lt(y,p.←
y)||((eq(y,p.y)&&lt;(x,p.x)));}
bool operator > (const pt &p) const { return p<pt(x, ←
y);}
bool operator <= (const pt &p) const { return !(pt(x←
,y)>p);}
bool operator >= (const pt &p) const { return !(pt(x←
,y)<p);}
bool operator == (const pt &p) const { return (pt(x, ←
y)<=p)&&(pt(x,y)>=p);}
};
ld dot(pt p,pt q) {return p.x*q.x+p.y*q.y;}
ld dist2(pt p, pt q) {return dot(p-q,p-q);}
ld dist(pt p,pt q) {return sqrt(dist2(p,q));}
ld norm2(pt p) {return dot(p,p);}
ld norm(pt p) {return sqrt(norm2(p));}
ld cross(pt p, pt q) { return p.x*q.y-p.y*q.x;}
ostream &operator<<(ostream &os, const pt &p) {
    return os << "(" << p.x << "," << p.y << ")";}
istream& operator >> (istream &is, pt &p){
    return is >> p.x >> p.y;}
//returns 0 if a,b,c are collinear,1 if a->b->c is cw←
and -1 if ccw
int orient(pt a,pt b,pt c)
{
    pt p=b-a,q=c-b;double cr=cross(p,q);
    if(eq(cr,0))return 0;if(lt(cr,0))return 1;return ←
-1;}
// rotate a point CCW or CW around the origin
pt RotateCCW90(pt p) { return pt(-p.y,p.x); }
pt RotateCW90(pt p) { return pt(p.y,-p.x); }
pt RotateCCW(pt p, ld t) { //rotate by angle t ←
degree ccw
return pt(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*cos←
(t)); }
// project point c onto line (not segment) through a ←
and b assuming a != b
pt ProjectPointLine(pt a, pt b, pt c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);}
// project point c onto line segment through a and b ←
(closest point on line segment)
pt ProjectPointSegment(pt a, pt b, pt c) {
    ld r = dot(b-a,b-a); if (eq(r,0)) return a;//a and ←
b are same
r = dot(c-a, b-a)/r;if (lt(r,0)) return a;//c on ←
left of a
if (gt(r,1)) return b; return a + (b-a)*r;}
// compute distance from c to segment between a and b
ld DistancePointSegment(pt a, pt b, pt c) {

```

```

return sqrt(dist2(c, ProjectPointSegment(a, b, c)))←
; }
// compute distance from c to line between a and b
ld DistancePointLine(pt a, pt b, pt c) {
return sqrt(dist2(c, ProjectPointLine(a, b, c)));}
// determine if lines from a to b and c to d are ←
parallel or collinear
bool LinesParallel(pt a, pt b, pt c, pt d) {
return eq(cross(b-a, c-d),0); }
bool LinesCollinear(pt a, pt b, pt c, pt d) {
return LinesParallel(a, b, c, d) && eq(cross(a-b, a←
-c),0) && eq(cross(c-d, c-a),0);}
// determine if line segment from a to b intersects ←
with line segment from c to d
bool SegmentsIntersect(pt a, pt b, pt c, pt d) {
if (LinesCollinear(a, b, c, d)) {
//a->b and c->d are collinear and have one point ←
common
if(eq(dist2(a,c),0)||eq(dist2(a,d),0)||eq(dist2(b←
,c),0)||eq(dist2(b,d),0)) return true;
if(gt(dot(c-a,c-b),0)&&gt(dot(d-a,d-b),0)&&gt(dot←
(c-b,d-b),0)) return false;
return true;}
if(gt(cross(d-a,b-a)*cross(c-a,b-a),0)) return ←
false;//c,d on same side of a,b
if(gt(cross(a-c,d-c)*cross(b-c,d-c),0)) return ←
false;//a,b on same side of c,d
return true;}
// compute intersection of line passing through a and←
b
// with line passing through c and d,assuming that **←
unique** intersection exists;
//for segment intersection,check if segments ←
intersect first
pt ComputeLineIntersection(pt a,pt b,pt c,pt d){
b=b-a;d=c-d;c=c-a;//lines must not be collinear
assert(gt(dot(b, b),0)&&gt(dot(d, d),0));
return a + b*cross(c, d)/cross(b, d);}
//returns true if point a,b,c are collinear and b ←
lies between a and c
bool between(pt a,pt b,pt c){
if(!eq(cross(b-a,c-b),0))return 0;//not collinear
return le(dot(b-a,b-c),0);
}
//compute intersection of line segment a-b and c-d
pt ComputeSegmentIntersection(pt a,pt b,pt c,pt d){
if(!SegmentsIntersect(a,b,c,d))return {INF,INF};//←
don't intersect
//if collinear then infinite intersection points, ←
this returns any one
if(LinesCollinear(a,b,c,d)){if(between(a,c,b))←
return c;if(between(c,a,d))return a;return b;}
return ComputeLineIntersection(a,b,c,d);
}
// compute center of circle given three points - *a,b←
,c shouldn't be collinear
pt ComputeCircleCenter(pt a,pt b,pt c){

```

```

b=(a+b)/2;c=(a+c)/2;
return ComputeLineIntersection(b,b+RotateCW90(a-b),←
c,c+RotateCW90(a-c));}
//point in polygon using winding number -> returns 0 ←
if point is outside
//winding number>0 if point is inside and equal to 0 ←
if outside
//draw a ray to the right and add 1 if side goes from←
up to down and -1 otherwise
bool PointInPolygon(const vector<pt> &p,pt q){
int n=p.size(),windingNumber=0;
for(int i=0;i<n;++i){
if(eq(dist2(q,p[i]),0)) return 1;//q is a vertex
int j=(i+1)%n;
if(eq(p[i].y,q.y)&&eq(p[j].y,q.y)) {//i,i+1 ←
vertex is vertical
if(le(min(p[i].x,p[j].x),q.x)&&le(q.x,max(p[i].←
x, p[j].x))) return 1;}//q lies on boundary
else {
bool below=lt(p[i].y,q.y);
if(below!=lt(p[j].y,q.y)) {
auto orientation=orient(q,p[j],p[i]);
if(orientation==0) return 1;//q lies on ←
boundary i->j
if(below==(orientation>0)) windingNumber+=←
below?1:-1;}}}
return windingNumber==0?0:1;
}
// determine if point is on the boundary of a polygon
bool PointOnPolygon(const vector<pt> &p,pt q) {
for (int i = 0; i < p.size(); i++)
if (eq(dist2(ProjectPointSegment(p[i],p[(i+1)%p.←
size()],q),q),0)) return true;
return false;}
// Compute area or centroid of any polygon (←
coordinates must be listed in cw/ccw
//fashion.The centroid is often known as center of ←
gravity/mass
ld ComputeSignedArea(const vector<pt> &p) {
ld ans=0;
for(int i = 0; i < p.size(); i++) {
int j = (i+1) % p.size();
ans+=cross(p[i],p[j]);
} return ans / 2.0;}
ld ComputeArea(const vector<pt> &p) {
return fabs(ComputeSignedArea(p));
}
// compute intersection of line through points a and ←
b with
// circle centered at c with radius r > 0
vector<pt> CircleLineIntersection(pt a, pt b, pt c, ←
ld r) {
vector<pt> ret;
b = b-a;a = a-c;
ld A = dot(b, b),B = dot(a, b),C = dot(a, a) - r*r,←
D = B*B - A*C;

```

```

if (lt(D,0)) return ret; //don't intersect
ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
if (gt(D,0)) ret.push_back(c+a+b*(-B-sqrt(D))/A);
return ret;}
// compute intersection of circle centered at a with ←
radius r
// with circle centered at b with radius R
vector<pt> CircleCircleIntersection(pt a, pt b, ld r, ←
ld R) {
vector<pt> ret;
ld d = sqrt(dist2(a, b)),d1=dist2(a,b);
pt inf(INF,INF);
if(eq(d1,0)&&eq(r,R)){ret.pb(inf);return ret;}//←
circles are same return (INF,INF)
if(gt(d,r+R) || lt(d+min(r, R),max(r, R)) ) return ←
ret;
ld x = (d*d-R*R+r*r)/(2*d),y = sqrt(r*r-x*x);
pt v = (b-a)/d;
ret.push_back(a+v*x + RotateCCW90(v)*y);
if (gt(y,0)) ret.push_back(a+v*x - RotateCCW90(v)*y←
);
return ret;}
//compute centroid of simple polygon by dividing it ←
into disjoint triangles
//and taking weighted mean of their centroids (Jerome←
)
pt ComputeCentroid(const vector<pt> &p) {
pt c(0,0),inf(INF,INF);
ld scale = 6.0 * ComputeSignedArea(p);
if(p.empty())return inf;//empty vector
if(eq(scale,0))return inf;//all points on straight ←
line
for (int i = 0; i < p.size(); i++){
int j = (i+1) % p.size();
c = c + (p[i]+p[j])*cross(p[i],p[j]);}
return c / scale;}
// tests whether or not a given polygon (in CW or CCW←
order) is simple
bool IsSimple(const vector<pt> &p) {
for (int i = 0; i < p.size(); i++) {
for (int k = i+1; k < p.size(); k++) {
int j = (i+1) % p.size();
int l = (k+1) % p.size();
if (i == 1 || j == k) continue;
if (SegmentsIntersect(p[i], p[j], p[k], p[l]))
return false;}}
return true;}
/*point in convex polygon
****bottom left point must be at index 0 and top is ←
the index of upper right vertex
****if not call make_hull once*/
bool pointinConvexPolygon(vector<pt> poly,pt point, ←
int top) {
if (point < poly[0] || point > poly[top]) return 0;←
//0 for outside and 1 for on/inside

```

```

auto orientation = orient(point, poly[top], poly←
[0]);
if (orientation == 0) {
if (point == poly[0] || point == poly[top]) ←
return 1;
return top == 1 || top + 1 == poly.size() ? 1 : ←
1;//checks if point lies on boundary when
//bottom and top points are adjacent
} else if (orientation < 0) {
auto itRight = lower_bound(poly.begin() + 1, poly←
.begin() + top, point);
return orient(itRight[0], point, itRight[-1])<=0;
} else {
auto itLeft = upper_bound(poly.rbegin(), poly.←
rend() - top-1, point);
return (orient(itLeft == poly.rbegin() ? poly[0] ←
: itLeft[-1], point, itLeft[0]))<=0;
}
}
/*maximum distance between two points in convex ←
polygon using rotating calipers
make sure that polygon is convex. if not call ←
make_hull first
*/
ld maxDist2(vector<pt> poly) {
int n = poly.size();
ld res=0;
for (int i = 0, j = n < 2 ? 0 : 1; i < j; ++i)
for (; j = j+1 % n) {
res = max(res, dist2(poly[i], poly[j]));
if (gt(cross(poly[j+1 % n] - poly[j],poly[i+1] ←
- poly[i]),0)) break;
}
return res;
}
//Line polygon intersection: check if given line ←
intersects any side of polygon
//if yes then line intersects. If no, then check if ←
its midpoint is inside polygon
//if midpoint is inside then line is inside else ←
outside
// compute distance between point (x,y,z) and plane ←
ax+by+cz=d
ld DistancePointPlane(ld x,ld y,ld z,ld a,ld b,ld c,←
ld d)
{ return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);}

```

4.2 Convex Hull

```

pt firstpoint;
//for sorting points in ccw(counter clockwise) ←
direction w.r.t firstpoint (leftmost and ←
bottommost)
bool compare(pt x,pt y){

```



```

ll o=orient(firstpoint,x,y);
if(o==0)return lt(x.x+x.y,y.x+y.y);
return o<0;}
/*poi->input points, hull->empty vector
returns hull in ccw order with min points*/
void make_hull(vector<pt>& poi,vector<pt>& hull){
    pair<ld,ld> bl={INF,INF};
    ll n=poi.size();ll ind;
    for(ll i=0;i<n;i++){
        pair<ld,ld> pp={poi[i].y,poi[i].x};
        if(pp<bl){
            ind=i;bl={poi[i].y,poi[i].x};}
    }
    swap(bl.F,bl.S);firstpoint=pt(bl.F,bl.S);
    vector<pt> cons;
    for(ll i=0;i<n;i++){
        if(i==ind)continue;cons.pb(poi[i]);}
    sort(cons.begin(),cons.end(),compare);
    hull.pb(firstpoint);ll m;
    for(auto z:cons){
        if(hull.size()<=1){hull.pb(z);continue;}
        pt pr,ppr;bool fl=true;
        while((m=hull.size())>=2){
            pr=hull[m-1];ppr=hull[m-2];
            ll ch=orient(ppr,pr,z);
            if(ch==-1){break;}
            else if(ch==1){hull.pop_back();continue;}
            else {
                ld d1,d2;
                d1=dist2(ppr,pr);d2=dist2(ppr,z);
                if(gt(d1,d2)){fl=false;break;}else {hull.←
                    pop_back();}
            }
        }
        if(fl){hull.push_back(z);}
    }
    return;
}

```

4.3 Convex Hull Trick

```

/*maintains upper convex hull of lines ax+b and gives←
    minimum value at a given x
to add line ax+b: sameoldcht.addline(a,b), to get min←
    value at x: sameoldcht.getbest(x)
to get maximum value at x add -ax-b as lines instead ←
    of ax+b and use -sameoldcht.getbest(x)*/
const int N = 1e5 + 5;
int n,a[N],b[N];ll dp[N];
struct line{
    ll a , b;double xleft;bool type;
    line(ll _a , ll _b){a = _a;b = _b;type = 0;}
    bool operator < (const line &other) const{
        if(other.type){return xleft < other.xleft;}

```

```

        return a > other.a;}
};
double meet(line x , line y){
    return 1.0 * (y.b - x.b) / (x.a - y.a);}
struct cht{
    set <line> hull;
    cht() {hull.clear();}
    typedef set < line > :: iterator ite;
    bool hasleft(ite node){
        return node != hull.begin();}
    bool hasright(ite node){
        return node != prev(hull.end());}
    void updateborder(ite node){
        if(hasright(node)){line temp = *next(node);
            hull.erase(temp);
            temp.xleft=meet(*node,temp);
            hull.insert(temp);}
        if(hasleft(node)){line temp = *node;
            temp.xleft = meet(*prev(node) , temp);
            hull.erase(node);hull.insert(temp);}
        else{
            line temp = *node;hull.erase(node);
            temp.xleft = -1e18;hull.insert(temp);}
    }
    bool useless(line left,line middle,line right){
        double x = meet(left,right);
        double y = x * middle.a + middle.b;
        double ly = left.a * x + left.b;
        return y > ly;}
    bool useless(ite node){
        if(hasleft(node) && hasright(node)){return
            useless(*prev(node)*node,*next(node));}
        return 0;}
    void addline(ll a , ll b){
        line temp = line(a , b);
        auto it = hull.lower_bound(temp);
        if(it != hull.end() && it -> a == a){
            if(it -> b > b){hull.erase(it);}
            else return;}
        hull.insert(temp);it = hull.find(temp);
        if(useless(it)){hull.erase(it);return;}
        while(hasleft(it) && useless(prev(it))){
            hull.erase(prev(it));}
        while(hasright(it) && useless(next(it))){
            hull.erase(next(it));}
        updateborder(it);}
    ll getbest(ll x){
        if(hull.empty())return 1e18;
        line query(0 , 0);
        query.xleft = x;query.type = 1;
        auto it = hull.lower_bound(query);
        it = prev(it);
        return it -> a * x + it -> b;}
};
cht sameoldcht;

```



```
int main(){
    sameoldcht.addline(b[1], 0);
    dp[i] = sameoldcht.getbest(a[i]);
    sameoldcht.addline(b[i], dp[i]);}
}
```

5 Trees

5.1 BlockCut Tree

```
// Take care it is 0 indexed --
struct BiconnectedComponents {
    struct Edge {
        int from, to;
    };
    struct To {
        int to; int edge;
    };
    vector<Edge> edges; vector<vector<To> > g;
    vector<int> low, ord, depth;
    vector<bool> isArtic; vll edgeColor;
    vector<int> edgeStack;
    int colors; int dfsCounter;
    void init(int n) {
        edges.clear();
        g.assign(n, vector<To>());
    }
    void addEdge(int u, int v) {
        if(u > v) swap(u, v); Edge e = { u, v };
        int ei = edges.size(); edges.push_back(e);
        To tu = { v, ei }, tv = { u, ei };
        g[u].push_back(tu); g[v].push_back(tv);
    }
    void run() {
        int n = g.size(), m = edges.size();
        low.assign(n, -2); ord.assign(n, -1);
        depth.assign(n, -2); isArtic.assign(n, false);
        edgeColor.assign(m, -1); edgeStack.clear();
        colors = 0;
        for(int i = 0; i < n; ++ i) if(ord[i] == -1) {
            dfsCounter = 0;
            dfs(i);
        }
    }
private:
    void dfs(int i) {
        low[i] = ord[i] = dfsCounter ++;
        for(int j = 0; j < (int)g[i].size(); ++ j) {
            int to = g[i][j].to, ei = g[i][j].edge;
            if(ord[to] == -1) {
                depth[to] = depth[i] + 1;
                edgeStack.push_back(ei);
                dfs(to);
                low[i] = min(low[i], low[to]);
            }
        }
    }
}
```

```
if(low[to] >= ord[i]) {
    if(ord[i] != 0 || j >= 1)
        isArtic[i] = true;
    while(!edgeStack.empty()) {
        int fi = edgeStack.back();
        edgeStack.pop_back();
        edgeColor[fi] = colors;
        if(fi == ei) break;
    } ++colors;
}
} else if(depth[to] < depth[i] - 1) {
    low[i] = min(low[i], ord[to]);
    edgeStack.push_back(ei);
}
}
};
```

5.2 Bridges Online

```
vector<int> par, dsu_2ecc, dsu_cc, dsu_cc_size;
int bridges; int lca_iteration;
vector<int> last_visit;
void init(int n) {
    par.resize(n); dsu_2ecc.resize(n);
    dsu_cc.resize(n); dsu_cc_size.resize(n);
    lca_iteration = 0; last_visit.assign(n, 0);
    for (int i=0; i<n; ++i) {
        dsu_2ecc[i] = i; dsu_cc[i] = i;
        dsu_cc_size[i] = 1; par[i] = -1;
    } bridges = 0;
}
int find_2ecc(int v) { // 2-edge connected comp.
    if (v == -1) return -1;
    return dsu_2ecc[v] == v ? v : dsu_2ecc[v] = find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) { // connected comp.
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v : dsu_cc[v] = find_cc(dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v);
    int root = v; int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]);
        par[v] = child; dsu_cc[v] = root;
        child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
void merge_path (int a, int b) {
    ++lca_iteration;
    vector<int> path_a, path_b;
```

```

int lca = -1;
while (lca == -1) {
    if (a != -1) {
        a = find_2ecc(a); path_a.push_back(a);
        if (last_visit[a] == lca_iteration)
            lca = a;
        last_visit[a] = lca_iteration; a=par[a];
    }
    if (b != -1) {
        path_b.push_back(b);
        b = find_2ecc(b);
        if (last_visit[b] == lca_iteration) lca = b;
        last_visit[b] = lca_iteration; b = par[b];
    }
}
for (int v : path_a) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
for (int v : path_b) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;
    int ca = find_cc(a); int cb = find_cc(b);
    if (ca != cb) { ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b); swap(ca, cb); }
        make_root(a); par[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else { merge_path(a, b); }
}

```

```

noc[x]=curc; posinch[x]=++len[curc];
ll a,b,c; a=b=0; ord.pb(x); sta[x]=++ti;
for(auto z:v[x]){ if(z==par[x]) continue;
    if(subs[z]>b){b=subs[z]; a=z;}
}
if(a!=0) makehld(a);
for(auto z:v[x]){ if(z==par[x] || z==a) continue; curc←
    ++; makehld(z); }
en[x]=ti;
}
inline void upd(ll x, ll y) //to update on path from a ←
    to b
{
    ll a,b,c,d;
    while(x!=y){
        a=hdc[noc[x]], b=hdc[noc[y]];
        if(a==b){
            if(level[x]>level[y]) swap(x,y); c=sta[x], d=sta[y]←
                ];
            //lca=a;
            update(1,0,n-1,c+1,d); return; }
        if(level[a]>level[b]) swap(a,b), swap(x,y);
        update(1,0,n-1,sta[b],sta[y]); y=par[b]; } } //update←
    on segment tree
int main() {
    //v is adjacency matrix
    for(i=1; i<=n; i++) v[i].clear(), hdc[i]=0, ti=-1;
    ord.clear(), curc=0;
    level[1]=0; par[1]=0; curc=1; dfs(1); makehld(1);
    cin>>m;
    while(m--){ cin>>a>>b; upd(a,b); ll ans=sumq(1,0,n←
        -1,0,n-1); }
}

```

5.3 HLD

```

/*
v is adjacency matrix of tree. clear v[i],hdc[i]=0,i←
    =-1 before every run
clear ord and curc=0
*/
const ll MAX=250005;
vll v[MAX], ord;
ll par[MAX], noc[MAX], hdc[MAX], curc, posinch[MAX], len[←
    MAX], ti=-1;
ll sta[MAX], en[MAX], subs[MAX], level[MAX];
ll st[4*MAX], lazy[4*MAX];
ll n;
void dfs(ll x){
    subs[x]=1;
    for(auto z:v[x]){
        if(z!=par[x]){ par[z]=x; level[z]=level[x]+1;
            dfs(z); subs[x]+=subs[z]; }
    }
}
void makehld(ll x){
    if(hdc[curc]==0){ hdc[curc]=x; len[curc]=0; }
}

```

5.4 LCA

```

const int N = int(1e5)+10;
const int LOGN = 20;
set<int> g[N];
int level[N];
int DP[LOGN][N];
int n,m;
/*----- Pre-Processing -----*/
/* Code Cridits : Tanuj Khattar codeforces submission←
    */
void dfs0(int u)
{
    for(auto it=g[u].begin(); it!=g[u].end(); it++)
        if(*it!=DP[0][u])
        {
            DP[0][*it]=u;
            level[*it]=level[u]+1;
            dfs0(*it);
        }
}

```

```

}
void preprocess()
{
    level[0]=0;
    DP[0][0]=0;
    dfs0(0);
    for(int i=1;i<LOGN;i++)
        for(int j=0;j<n;j++)
            DP[i][j] = DP[i-1][DP[i-1][j]];
}
int lca(int a,int b)
{
    if(level[a]>level[b])swap(a,b);
    int d = level[b]-level[a];
    for(int i=0;i<LOGN;i++)
        if(d&(1<<i))
            b=DP[i][b];
    if(a==b)return a;
    for(int i=LOGN-1;i>=0;i--)
        if(DP[i][a]!=DP[i][b])
            a=DP[i][a],b=DP[i][b];
    return DP[0][a];
}
int dist(int u,int v)
{
    return level[u] + level[v] - 2*level[lca(u,v)];
}

```

5.5 Centroid Decompostion

```

/*nx:max nodes,par:parents of nodes in centroid tree,←
   timstamp: timestamps of nodes when they became ←
   centroids,ssize,vis: subtree size and visit times ←
   in dfs,tim: timestamp iterator
dist[nx]: dist[i][0][j]=no. of nodes at dist k in ←
   subtree of i in centroid tree
dist[i][j][k]=no. of nodes at distance k in jth child←
   of i in centroid tree *(use adj while doing dfs←
   instead of adj1)***
preprocess: stores all values in dist array*/
const int nx=1e5;
vector<int> adj[nx],adj1[nx];
int par[nx],timstamp[nx],ssize[nx],vis[nx];
int tim=1;
vector<int> cntorder;//centroids in order
vector<vector<int>>> dist[nx];
int dfs(int root){
    vis[root]=tim;
    int t=0;
    for(auto i:adj[root]){
        if(!timstamp[i]&&vis[i]<tim)t+=dfs(i);}
    ssize[root]=t+1;return t+1;}
int dfs1(int root,int n){
    vis[root]=tim;pair<int,int> mxc={0,-1};
    bool poss=true;

```

```

    for(auto i:adj[root]){
        if(!timstamp[i]&&vis[i]<tim)
            poss&=(ssize[i]<=n/2),mxc=max(mxc,{ssize[i],i})←
            ;}
    if(poss&&(n-ssize[root])<=n/2)return root;
    return dfs1(mxc.second,n);}
int findc(int root){
    dfs(root);
    int n=ssize[root];tim++;
    return dfs1(root,n);}
void cntorder(int root,int p){
    int cnt=findc(root);
    cntorder.pb(cnt);
    timstamp[cnt]=tim++;par[cnt]=p;
    if(p>=0)adj1[p].pb(cnt);
    for(auto i:adj[cnt])
        if(!timstamp[i])
            cntorder(i,cnt);}
void dfs2(int root,int nod,int j,int dst){
    if(dist[root][j].size()==dst)dist[root][j].pb(0);
    vis[nod]=tim;dist[root][j][dst]+=1;
    for(auto i:adj[nod]){
        if((timstamp[i]<=timstamp[root])||(vis[i]==vis[nod]←
            ))continue;
        vis[i]=tim;dfs2(root,i,j,dst+1);}
}
void preprocess(){
    for(int i=0;i<cntorder.size();i++){
        int root=cntorder[i];
        vector<int> temp;
        dist[root].pb(temp);temp.pb(0);++tim;
        dfs2(root,root,0,0);
        int cnt=0;
        for(int j=0;j<adj[root].size();j++){
            int nod=adj[root][j];
            if(timstamp[nod]<timstamp[root])
                continue;
            dist[root].pb(temp);++tim;
            dfs2(root,nod,++cnt,1);}
    }
}

```

6 Maths

6.1 Chinese Remainder Theorem

```

/*solves system of equations x=rem[i]%mods[i] for any←
   mod (need not be coprime)
input:vector of remainders and moduli
output: pair of answer(x%lcm of modulo) and lcm of ←
   all the modulo (returns -1 if it is inconsistent)←
   */

```

```

ll GCD(ll a, ll b) { return (b == 0) ? a : GCD(b, a % b); }
inline ll LCM(ll a, ll b) { return a / GCD(a, b) * b; }
inline ll normalize(ll x, ll mod) { x %= mod; if (x < 0) x += mod; return x; }
struct GCD_type { ll x, y, d; };
GCD_type ex_GCD(ll a, ll b)
{
    if (b == 0) return {1, 0, a};
    GCD_type pom = ex_GCD(b, a % b);
    return {pom.y, pom.x - a / b * pom.y, pom.d};
}
pair<ll, ll> CRT(vector<ll> &rem, vector<ll> &mods)
{
    ll n = rem.size();
    ll ans = rem[0];
    ll lcm = mods[0];
    for (ll i = 1; i < n; i++)
    {
        auto pom = ex_GCD(lcm, mods[i]);
        ll x1 = pom.x;
        ll d = pom.d;
        if ((rem[i] - ans) % d != 0) return {-1, 0};
        ans = normalize(ans + x1 * (rem[i] - ans) / d % (mods[i] / d) * lcm, lcm * mods[i] / d);
        lcm = LCM(lcm, mods[i]); // you can save time by replacing above lcm * n[i] / d by lcm = lcm * n[i] / d
    }
    return {ans, lcm};
}

```

6.2 Discrete Log

/*Discrete Log , Baby-Step Giant-Step , e-maxx
The idea is to make two functions, $f_1(p)$, $f_2(q)$ and find p, q s.t. $f_1(p) = f_2(q)$ by storing all possible values of f_1 , and checking for q . In this case $a^x = b \pmod m$ is solved by subst. x by $p \cdot n - q$, where n is chosen optimally.*/
/*returns a soln. for $a^x = b \pmod m$ for given a, b, m ; -1 if no. soln; $O(\sqrt{m} \cdot \log(m))$ use unordered_map to remove log factor.
IMP : works only if a, m are co-prime.
But can be modified.*/
int solve (int a, int b, int m) {
 int n = (int) sqrt (m + .0) + 1;
 int an = 1;
 for (int i = 0; i < n; ++i)
 an = (an * a) % m;
 map<int, int> vals;
 for (int i = 1, cur = an; i <= n; ++i) {
 if (!vals.count(cur))
 vals[cur] = i;

```

        cur = (cur * an) % m;
    }
    for (int i = 0, cur = b; i <= n; ++i) {
        if (vals.count(cur)) {
            int ans = vals[cur] * n - i;
            if (ans < m) return ans;
        }
        cur = (cur * a) % m;
    }
    return -1;
}

```

6.3 NTT

/*
Kevin's different Code: https://s3.amazonaws.com/codechef_shared/download/Solutions/JUNE15/tester/MOREFB.cpp
****There is no problem that FFT can solve while this NTT cannot
Case1: If the answer would be small choose a small enough NTT prime modulus
Case2: If the answer is large ($> \sim 1e9$) FFT would not work anyway due to precision issues
In Case2 use NTT. If max_answer_size = $n * (\text{largest_coefficient}^2)$
So use two or three modulus to solve it
****Compute $a * b \% \text{mod}$ if $a \% \text{mod} * b \% \text{mod}$ would result in overflow in $O(\log(a))$ time:
ll mulmod (ll a, ll b, ll mod) {
 ll res = 0;
 while (a != 0) {
 if (a & 1) res = (res + b) % m;
 a >>= 1;
 b = (b << 1) % m;
 }
 return res;
}
Fastest NTT (can also do polynomial multiplication if max coefficients are upto $1e18$ using 2 modulus and CRT)
How to use:
 $P = A * B$
Polynomial1 = $A[0] + A[1] * x^1 + A[2] * x^2 + \dots + A[n-1] * x^{n-1}$
Polynomial2 = $B[0] + B[1] * x^1 + B[2] * x^2 + \dots + B[n-1] * x^{n-1}$
 $P = \text{multiply}(A, B)$
 A and B are not passed by reference because they are changed in multiply function
For CRT after obtaining answer modulo two primes p_1 and p_2 :
 $x = a_1 \pmod{p_1}$, $x = a_2 \pmod{p_2} \Rightarrow x = ((a_1 * (m_2^{-1} \% m_1) * m_2 + (a_2 * (m_1^{-1} \% m_2) * m_1) \% m_1 m_2$
*** Before each call to multiply:
 set base=1, roots={0,1}, rev={0,1}, max_base=x (such that if $\text{mod} = c * (2^k) + 1$ then $x \leq k$ and 2^x is greater than equal to nearest power of 2 of $2 * n$)
 root = primitive_root^((mod-1)/(2^max_base))


```
vector<int> square(vector<int> a) {
    return multiply(a, a, 1);
}
```

6.4 Online FFT

```
//f[i]=sum over j from 0 to i-1 f[j]*g[i-1-j]
//handle f[0] and g[0] separately
const int nx=131072;int f[nx],g[nx];
void onlinefft(int a,int b,int c,int d)
{
    vector<int> v1,v2;
    v1.pb(f+a,f+b+1);v2.pb(g+c,g+d+1); vector<int> res=↵
        multiply(v1,v2);
    for(int i=0;i<res.size();i++)
        if(a+c+i+1<nx) f[a+c+i+1]=add(f[a+c+i+1],res[i]);
}
void precal()
{
    g[0]=1;
    for(int i=1;i<nx;i++)
        g[i]=power(i,i-1);
    f[1]=1;
    for(int i=1;i<=100000;i++)
    {
        f[i+1]=add(f[i+1],g[i]);f[i+1]=add(f[i+1],f[i]);
        f[i+2]=add(f[i+2],mul(f[i],g[1]));f[i+3]=add(f[i↵
            +3],mul(f[i],g[2]));
        for(int j=2;i%j==0&&j<nx;j=j*2) onlinefft(i-j,i↵
            -1,j+1,2*j);
    }
}
```

6.5 Langrange Interpolation

```
/* Input :
Degree of polynomial: k
Polynomial values at x=0,1,2,3,...,k
Output :
Polynomial value at x
Complexity: O(degree of polynomial)
Works only if the points are equally spaced
*/
ll lagrange(vll& v , int k, ll x,int mod){
    if(x <= k) return v[x];
    ll inn = 1; ll den = 1;
    for(int i = 1;i<=k;i++){
        inn = (inn*(x - i))%mod;
        den = (den*(mod - i))%mod;
    }
    inn = (inn*inv(den % mod))%mod;
    ll ret = 0;
```

```
for(int i = 0;i<=k;i++){
    ret = (ret + v[i]*inn)%mod;
    ll md1 = mod - ((x-i)*(k-i))%mod;
    ll md2 = ((i+1)*(x-i-1))%mod;
    if(i!=k)
        inn = (((inn*md1)%mod)*inv(md2 % mod))%mod;
    } return ret;
}
```

6.6 Matrix Struct

```
struct matrix{
    ld B[N][N], n;
    matrix(){n = N; memset(B,0,sizeof B);}
    matrix(int _n){
        n = _n; memset(B, 0, sizeof B);
    }
    void iden(){
        for(int i = 0; i < n; i++)
            B[i][i] = 1;
    }
    void operator += (matrix M){
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                B[i][j] = add(B[i][j], M.B[i][j]);
    }
    void operator -= (matrix M){}
    void operator *= (ld b){}
    matrix operator - (matrix M){}
    matrix operator + (matrix M){
        matrix ret = (*this);
        ret += M; return ret;
    }
    matrix operator * (matrix M){
        matrix ret = matrix(n); memset(ret.B, 0, sizeof ↵
            ret.B);
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++){
                for(int k = 0; k < n; k++){
                    ret.B[i][j] = add(ret.B[i][j], mul(B[i][k],↵
                        M.B[k][j]));
                }
            }
        return ret;
    }
    matrix operator *= (matrix M){ *this = ((*this) * M)↵
        );}
    matrix operator * (int b){
        matrix ret = (*this); ret *= b; return ret;
    }
    vector<double> multiply(const vector<double> & v) ↵
        const{
        vector<double> ret(n);
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++){
                ret[i] += B[i][j] * v[j];
            }
    }
```

```

    }
    return ret;
};
}

```

6.7 nCr(Non Prime Modulo)

```

// calculates nCr, for small
// non-prime modulo, and (very) big n,r.
ll phimod;
vll pr,prn;vll fact;
ll power(ll a,ll x,ll mod){
    ll ans=1;
    while(x){
        if((1LL)&(x))ans=(ans*a)%mod;
        a=(a*a)%mod;x>>=1LL;
    }
    return ans;
}
// prime factorization of x.
// pr-> prime ; prn -> it's exponent
void getprime(ll x){
    pr.clear();prn.clear();
    ll i,j,k;
    for(i=2;(i*i)<=x;i++){
        k=0;while((x%i)==0){k++;x/=i;}
        if(k>0){pr.pb(i);prn.pb(k);}
    }
    if(x!=1){pr.pb(x);prn.pb(1);}
    return;
}
// factorials are calculated ignoring
// multiples of p.
void primeproc(ll p,ll pe){    // p , p^e
    ll i,d;
    fact.clear();fact.pb(1);d=1;
    for(i=1;i<pe;i++){
        if(i%p){fact.pb((fact[i-1]*i)%pe);}
        else {fact.pb(fact[i-1]);}
    }
    return;
}
// again note this has ignored multiples of p
ll Bigfact(ll n,ll mod){
    ll a,b,c,d,i,j,k;
    a=n/mod;a%=phimod;a=power(fact[mod-1],a,mod);
    b=n%mod;a=(a*fact[b])%mod;
    return a;
}
// Chinese Remainder Thm.
vll crtval,crtmod;
ll crt(vll &val,vll &mod){
    ll a,b,c,d,i,j,k;b=1;
    for(ll z:mod)b*=z;
    ll ans=0;
    for(i=0;i<mod.size();i++){

```

```

        a=mod[i];c=b/a;
        d=power(c,(((a/pr[i])*(pr[i]-1))-1),a);
        c=(c*d)%b;c=(c*val[i])%b;ans=(ans+c)%b;
    }
    return ans;
}
// calculate for prime powers and
// take crt. For each prime power,
// first ignore multiples of p,
// and then do recursively, calculating
// the powers of p separately.
ll Bigncr(ll n,ll r,ll mod){
    ll a,b,c,d,i,j,k;ll p,pe;
    getprime(mod);ll Fnum=1;ll Fden;
    crtval.clear();crtmod.clear();
    for(i=0;i<pr.size();i++){
        Fnum=1;Fden=1;
        p=pr[i];pe=power(p,prn[i],1e17);
        primeproc(p,pe);
        a=1;d=0;
        phimod=(pe*(p-1LL))/p;
        ll n1=n,r1=r,nr=n-r;
        while(n1){
            Fnum=(Fnum*(Bigfact(n1,pe)))%pe;
            Fden=(Fden*(Bigfact(r1,pe)))%pe;
            Fden=(Fden*(Bigfact(nr,pe)))%pe;
            d+=n1-(r1+nr);
            n1/=p;r1/=p;nr/=p;
        }
        Fnum=(Fnum*(power(Fden,(phimod-1LL),pe)))%pe;
        if(d>=prn[i])Fnum=0;
        else Fnum=(Fnum*(power(p,d,pe)))%pe;
        crtmod.pb(pe);crtval.pb(Fnum);
    }
    // you can just iterate instead of crt
    // for(i=0;i<mod;i++){
    //     bool cg=true;
    //     for(j=0;j<crtmod.size();j++){
    //         if(i%crtmod[j]!=crtval[j])cg=false;
    //     }
    //     if(cg)return i;
    // }
    return crt(crtval,crtmod);
}

```

6.8 Primitive Root Generator

```

/*To find generator of U(p),we check for all
g in [1,p]. But only for powers of the
form phi(p)/p_j, where p_j is a prime factor of
phi(p). Note that p is not prime here.
Existence , if one of these : 1. p = 1,2,4
2. p = q^k , where q -> odd prime.

```

3. $p = 2 \cdot (q^k)$, where $q \rightarrow$ odd prime
 Note that $a \cdot g^{(\phi(p))} = 1 \pmod{p}$
 b. there are $\phi(\phi(p))$ generators if exists.
 Finds "a" generator of $U(p)$, multiplicative group of integers mod p . Here `calc_phi` returns the totient function for p . $O(\text{Ans} \cdot \log(\phi(p)) \cdot \log(p))$ + time for factorizing $\phi(p)$. By some theorem, $\text{Ans} = O((\log(p))^6)$. Should be fast generally.*/

```
int generator (int p) {
    vector<int> fact;
    int phi = calc_phi(p), n = phi;
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back (i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1) fact.push_back (n);
    for (int res=2; res<=p; ++res) {
        if (gcd(res,p)!=1) continue;
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod (res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}
```

7 Strings

7.1 Hashing Theory

If order **not** imp. and count/frequency imp. use **this** \leftarrow
 as hash fn:-
 $((a_1+h)^k + (a_2+h)^k + (a_3+h)^k + (a_4+h)^k) \% p \leftarrow$
 . Select : h, k, p
 Alternate:
 $((x)^{(a_1)} + (x)^{(a_2)} + \dots + (x)^{(a_k)}) \% \text{mod}$ where x and \leftarrow
 mod are fixed and $a_1 \dots a_k$ is an unordered set

7.2 Manacher

```
// Same idea as Z_algo, Time : O(n)
// [l,r] represents : boundaries of rightmost  $\leftarrow$ 
// detected subpalindrom (with max r)
// takes string s and returns a vector of lengths of  $\leftarrow$ 
// odd length palindrom
// centered around that char (e.g abac for 'b' returns  $\leftarrow$ 
// 2(not 3))
vll manacher_odd(string s){
    ll n = s.length(); vll d1(n);
    for (ll i = 0, l = 0, r = -1; i<n; i++){
```

```
        d1[i] = 1;
        if (i <= r){
            d1[i] = min(r-i+1, d1[l+r-i]); // use prev  $\leftarrow$ 
            val
        }
        while (i+d1[i] < n && i-d1[i] >= 0 && s[i+d1[i]  $\leftarrow$ 
            ] == s[i-d1[i]]) d1[i]++; // trivial  $\leftarrow$ 
            matching
        if (r < i+d1[i]-1) l=i-d1[i]+1, r=i+d1[i]-1;  $\leftarrow$ 
            // update r
    }
    return d1;
}
// takes string s and returns vector of lengths of  $\leftarrow$ 
// even length ...
// (it's centered around the right middle char, bb is  $\leftarrow$ 
// centered around the later 'b')
vll manacher_even(string s){
    ll n = s.length(); vll d2(n);
    for (ll i = 0, l = 0, r = -1; i<n; i++){
        d2[i] = 0;
        if (i <= r){
            d2[i] = min(r-i+1, d2[l+r+1-i]);
        }
        while (i+d2[i] < n && i-d2[i]-1 >= 0 && s[i+d2[i]  $\leftarrow$ 
            [i]] == s[i-d2[i]-1]) d2[i]++;
        if (d2[i] > 0 && r < i+d2[i]-1) l=i-d2[i], r=i  $\leftarrow$ 
            +d2[i]-1;
    }
    return d2;
}
// Other mtd : To do both things in one pass, add  $\leftarrow$ 
// special char e.g string "abc" => "$a$b$c$"
```

7.3 Trie

```
const ll AS = 26; // alphabet size
ll go[MAX][AS]; ll cnt[MAX]; ll cn=0;
// cn -> index of next new node
// convert all strings to vll
ll newNode() {
    for (ll i=0; i<AS; i++)
        go[cn][i] = -1;
    return cn++;
}
// call newNode once **** before adding anything **
void addTrie(vll &x) {
    ll v = 0;
    cnt[v]++;
    for (ll i=0; i<x.size(); i++){
        ll y=x[i];
        if (go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
        cnt[v]++;
    }
```

```

}
// returns count of substrings with prefix x
ll getcount(vll &x){
    ll v=0;
    for(i=0;i<x.size();i++){
        ll y=x[i];
        if(go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
    }
    return cnt[v];
}

```

7.4 Z-algorithm

```

// [l,r] -> indices of the rightmost segment match
// (the detected segment that ends rightmost(with max ←
// r))
// 2 cases -> 1st. i ≤ r : z[i] is atleast min(r-i ←
// +1,z[i-1]), then match trivially
// 2nd. o.w compute z[i] with trivial matching
// update l,r
// Time : O(n)(asy. behavior), Proof : each iteration ←
// of inner while loop make r pointer advance to ←
// right,
// Applications: 1) Search substring(text t, ←
// pattern p) s = p + '$' + t.
// 3) String compression(s = t+t+...+t, then find |t ←
// |)
// 2) Number of distinct substrings (in O(n^2))
// (useful when appending or deleting characters ←
// online from the end or beginning)
vector<ll> z_function(string s) {
    ll n = (ll) s.length();
    vector<ll> z(n);
    for (ll i = 1, l = 0, r = 0; i < n; ++i) {
        if (i ≤ r)
            z[i] = min (r - i + 1, z[i - 1]); // use ←
            previous z val
        while (i + z[i] < n && s[z[i]] == s[i + z[i] ←
        ])) // trivial matching
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1; // update ←
            rightmost segment matched
    }
    return z;
}

```

7.5 Aho Corasick

```

const int K = 26;
// remember to set K
struct Vertex {
    int next[K]; bool leaf = false;
    int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};
vector<Vertex> aho(1);
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (aho[v].next[c] == -1) {
            aho[v].next[c] = aho.size();
            aho.emplace_back(v, ch);
        }
        v = aho[v].next[c];
    } aho[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (aho[v].link == -1) {
        if (v==0 || aho[v].p==0) aho[v].link = 0;
        else aho[v].link =
            go(get_link(aho[v].p), aho[v].pch);
    }
    return aho[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (aho[v].go[c] == -1) {
        if (aho[v].next[c] != -1)
            aho[v].go[c] = aho[v].next[c];
        else
            aho[v].go[c] = v == 0 ? 0 : go(get_link(v), ch) ←
            ;
    }
    return aho[v].go[c];
}

```

7.6 KMP

```

/*Time:O(n)(j increases n times(& j>=0) only so asy. ←
O(n))
pi[i] = length of longest prefix of s ending at i
applications: search substring, # of different ←
substrings(O(n^2)),
3) String compression(s = t+t+...+t, then find |t|, k ←
=n-pi[n-1],if k|n)
4) Building Automaton(Gray Code Example)*/
vector<ll> prefix_function(string s) {

```

```

    ll n = (ll)s.length();
    vector<ll> pi(n);
    for (ll i = 1; i < n; i++) {
        ll j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j]) j++;
        pi[i] = j;
    }
    return pi;
}
// searching s in t, returns all occurrences (indices)
vector<ll> search(string s, string t) {
    vll pi = prefix_function(s);
    ll m = s.length(); vll ans; ll j = 0;
    for (ll i = 0; i < t.length(); i++) {
        while (j > 0 && t[i] != s[j])
            j = pi[j-1];
        if (t[i] == s[j]) j++;
        if (j == m) ans.pb(i-m+1);
    }
    return ans; // if ans empty then no occurrence
}

```

7.7 Palindrome Tree

```

const ll MAX=1e5+15;
ll par[MAX]; // stores index of parent node
ll sul_i[MAX]; // stores index of suffix link
ll len[MAX]; // stores len of largest
                palindrome ending at that node */
ll child[MAX][30]; // stores the children of the node
/*-----
index 0 - root "-1"
index 1 - root "0"
therefore node of s[i] is i+2
initialize all child[i][j] to -1
-----*/
void eer_tree(string s) {
    ll a,b,c,d,i,j,k,e,f;
    sul_i[1]=0; sul_i[0]=0; len[1]=0; len[0]=-1;
    ll n=s.length();
    for (i=0; i<n+10; i++)
        for (j=0; j<30; j++) child[i][j]=-1;
    ll cur=1; d=1;
    for (i=0; i<s.size(); i++) {
        ++d;
        while (true) {
            a=i-1-len[cur];
            if (a>=0) {
                if (s[a]==s[i]) {
                    if (child[cur][(ll)(s[i]-'a')]==-1) {
                        par[d]=cur; child[cur][(ll)(s[i]-'a')]=d;
                        len[d]=len[cur]+2; cur=d;
                    }
                }
            }
        }
    }
}

```

```

        else {
            par[d]=cur; len[d]=len[cur]+2;
            cur=child[cur][(ll)(s[i]-'a')];
        }
        break;
    }
}
if (cur==0) break;
cur=sul_i[cur];
}
if (cur!=d) continue;
if (len[d]==1) sul_i[d]=1;
else {
    c=sul_i[par[d]];
    while (child[c][(ll)(s[i]-'a')]==-1) {
        if (c==0) break;
        c=sul_i[c];
    }
    sul_i[d]=child[c][(ll)(s[i]-'a')];
}
}
}
}

```

7.8 Suffix Array

/*Sorted array of suffixes = sorted array of cyclic shifts of string+\$. We consider a prefix of len. 2^k of the cyclic, in the kth iteration. String of len. 2^k → combination of 2 strings of len. $2^{(k-1)}$, whose order we know, from previous iteration. Just radix sort on pair for next iteration.
Time :- $O(n \log(n) + \text{alphabet})$. Applications :-
Finding the smallest cyclic shift; Finding a substring in a string; Comparing two substrings of a string; Longest common prefix of two substrings; Number of different substrings. */
//returns permutation of indices in sorted order ***
vector<ll> sort_cyclic_shifts(string const& s) {
 ll n = s.size();
 const ll alphabet = 256;
 //change the alphabet size accordingly and indexing
 vector<ll> p(n), c(n), cnt(max(alphabet, n), 0);
 // p: sorted ord. of 1-len prefix of each cyclic
 // shift index. c: class of a index
 // pn: same as p for kth iteration. ||ly cn.
 for (ll i = 0; i < n; i++)
 cnt[s[i]]++;
 for (ll i = 1; i < alphabet; i++)
 cnt[i] += cnt[i-1];
 for (ll i = 0; i < n; i++)
 p[--cnt[s[i]]] = i;
 c[p[0]] = 0;
 ll classes = 1;
 for (ll i = 1; i < n; i++) {


```

    if (s[p[i]] != s[p[i-1]])
        classes++;
    c[p[i]] = classes - 1;
}
vector<ll> pn(n), cn(n);
for (ll h = 0; (1 << h) < n; ++h) {
    for (ll i = 0; i < n; i++) { //sorting w.r.t
        pn[i] = p[i] - (1 << h); //second part.
        if (pn[i] < 0)
            pn[i] += n;
    }
    fill(cnt.begin(), cnt.begin() + classes, 0);
    for (ll i = 0; i < n; i++)
        cnt[c[pn[i]]]++;
    for (ll i = 1; i < classes; i++)
        cnt[i] += cnt[i-1];
// sorting w.r.t. 1st(more significant) part
    for (ll i = n-1; i >= 0; i--)
        p[--cnt[c[pn[i]]]] = pn[i];
    cn[p[0]] = 0; classes = 1;
// determining new classes in sorted array.
    for (ll i = 1; i < n; i++) {
        pll cur={c[p[i]],c[(p[i]+(1<<h))%n]};
        pll prev={c[p[i-1]],c[(p[i-1]+(1<<h))%n]};
        if (cur != prev) ++classes;
        cn[p[i]] = classes - 1;
    }
    c.swap(cn); }
return p;
}
vector<ll> suffix_array_construction(string s) {
    s += "$";
    vector<ll> sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts; }
// For comp. two substr. of len. l starting at i,j.
// k - 2^k > l/2. check the first 2^k part, if equal,
// check last 2^k part. c[k] is the c in kth iter
//of S.A construction.
int compare(int i, int j, int l, int k) {
    pll a = {c[k][i],c[k][(i+l-(1 << k))%n]};
    pll b = {c[k][j],c[k][(j+l-(1 << k))%n]};
    return a == b ? 0 : a < b ? -1 : 1; }
/*lcp[i]=len. of lcp of ith & (i+1)th suffix in the ←
SA
1.Consider suffixes in decreasing order of length.
2.Let p = s[i....n]. It will be somewhere in the S.A.
We determine its lcp = k. 3.Then lcp of q=s[(i+1)..n]
will be atleast k-1 coz 4.remove the first char of p
and its successor in the S.A. These are suffixes with
lcp k-1. 5.But note that these 2 may not be ←
consecutive
in S.A.But lcp of str. in b/w have to be also >= k-1.←
*/
vll lcp_cons(string const& s, vector<ll> const& p) {
    ll n = s.size();

```

```

    vector<ll> rank(n, 0);
    for (ll i = 0; i < n; i++)
        rank[p[i]] = i;
    ll k = 0; vector<ll> lcp(n-1, 0);
    for (ll i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0; continue; }
        ll j = p[rank[i] + 1];
        while(i+k<n && j+k<n && s[i+k]==s[j+k]) k++;
        lcp[rank[i]] = k; if (k) k--; }
    return lcp;
}

```

7.9 Suffix Tree

```

const int N=1000000, // set it more than 2*(len. of ←
string)
string str; // input string for which the suffix tree←
is being built
int chi[N][26],
lef[N], // left...
rig[N], // ...and right boundaries of the substring ←
of a which correspond to incoming edge
par[N], // parent of the node
sfli[N], // suffix link
tv,tp,la,
ts; // the number of nodes
void ukkadd(int c) {
    suff++;
    if (rig[tp]<tp){
        if (chi[tp][c]==-1){chi[tp][c]=ts;lef[ts]=la;
            par[ts++]=tp;tv=sfli[tp];tp=rig[tp]+1;goto suff;}
        tv=chi[tp][c];tp=lef[tp];
    }
    if (tp==-1 || c==str[tp]-'a')tp++;
    else {
        lef[ts]=lef[tp]; rig[ts]=tp-1; par[ts]=par[tp];
        chi[ts][str[tp]-'a']=tv; chi[ts][c]=ts+1;
        lef[ts+1]=la; par[ts+1]=ts; lef[tp]=tp; par[tp]=←
        ts;
        chi[par[ts]][str[lef[ts]]-'a']=ts; ts+=2;
        tv=sfli[par[ts-2]]; tp=lef[ts-2];
        while (tp <= rig[ts-2]) {
            tv=chi[tp][str[tp]-'a']; tp+=rig[tp]-lef[tp]←
            +1;}
        if (tp == rig[ts-2]+1) sfli[ts-2]=tv; else sfli[←
        ts-2]=ts;
        tp=rig[tp]-(tp-rig[ts-2])+2;goto suff;
    }
}
void build() {
    ts=2; tv=0; tp=0;
    ll ss = str.size();ss*=2;ss+=15;
    fill(rig,rig+ss,(int)str.size()-1);

```

```
// initialize data for the root of the tree
sfli[0]=1; lef[0]=-1; rig[0]=-1;
lef[1]=-1; rig[1]=-1; for(ll i=0;i<ss;i++)
fill (chi[i], chi[i]+27,-1);
fill(chi[1],chi[1]+26,0);
// add the text to the tree, letter by letter
for (la=0; la<(int)str.size(); ++la)
ukkadd (str[la]-'a');
}
```