

# Codebook- Team Far\_Behind IIT Delhi, India

Ayush Ranjan, Naman Jain, Manish Tanwar

## 2. Data Structures :

2.1 - Fenwick, 2.2 - 2D-BIT, 2.3 - Segment Tree, 2.4 - Persistent Segment Tree, 2.5 - DP Optimization

## 3. Flows and Matching :

3.1 - General Matching, 3.2 - Global Mincut, 3.3 - Hopcroft Matching, 3.4 - Dinic, 3.5 - Ford Fulkerson, 3.6 - MCMF, 3.7 - MinCost Matching

## 4. Geometry :

4.1 - Geometry, 4.2 - Convex Hull, 4.3 - Li Chao Tree, 4.4 - Convex Hull Trick

## 5. Trees :

5.1 - BlockCut Tree, 5.2 - Bridge Tree, 5.3 - Dominator Tree, 5.4 - Bridges Online, 5.5 - HLD, 5.6 - LCA, 5.7 - Centroid Decomposition

## 6. Maths :

6.1 - Chinese Remainder Theorem, 6.2 - Discrete Log, 6.3 - NTT, 6.4 - Online FFT, 6.5 - Lagrange Interpolation, 6.6 - Matrix Struct, 6.7 - nCr(Non Prime Modulo), 6.8 - Primitive Root Generator, 6.9 - Math Miscellaneous, 6.10 - Group Theory

## 7. Strings

7.1 - Hashing Theory, 7.2 - Manacher, 7.3 - Trie, 7.4 - Z-algorithm, 7.5 - Aho Corasick, 7.6 - KMP, 7.7 - Palindrome Tree, 7.8 - Suffix Array, 7.9 - Suffix Tree, 7.10 - Suffix Automaton

## 1 Syntax

### 1.1 Template

```
#include<bits/stdc++.h>
#include<ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
using namespace std;
#define ll long long
ll mxm() {return LLONG_MIN;}
template<typename... Args>
ll mxm(ll a, Args... args) { return max(a,mxm(args...)); }
ll mnm() {return LLONG_MAX;}
template<typename... Args>
ll mnm(ll a, Args... args) { return min(a,mnm(args...)); }
template<class T> ostream& operator<<(ostream& os, vector<T> V){
```

```
os<<"[ ";for(auto v:V)os<<v<<" ";return os<<"]"<<endl;
};
template<class L,class R> ostream& operator<<(<<ostream& os,pair<L,R> P){
return os<<"("<<P.first<<" "<<P.second<<")";}
#define TRACE
#ifdef TRACE
#define trace(...) __f(#__VA_ARGS__ ,__VA_ARGS__)
template<typename Arg1>
void __f(const char* name,Arg1&& arg1){
cout<<name<<" : "<<arg1<<endl;}
template<typename Arg1,typename... Args>
void __f(const char* names,Arg1&& arg1,Args&&... args){
const char* comma=strchr(names+1,',');cout.write<<
(names,comma-names)<<" : "<<arg1<<" | ";__f(
comma+1,args...);}
#else
#define trace(...) 1
#endif
#define ld long double
#define pll pair<ll,ll>
#define pii pair<int,int>
#define vll vector<ll>
#define vi vector<int>
#define vpll vector<pll>
#define I insert
#define F first
#define S second
#define pb push_back
#define endl "\n"
#define all(x) x.begin(),x.end()
// const int mod=1e9+7;
// 128 bit: __int128
inline int add(int a,int b){a+=b;if(a>=mod)a-=mod;return a;}
inline int sub(int a,int b){a-=b;if(a<0)a+=mod;return a;}
inline int mul(int a,int b){return (a*1ll*b)%mod;}
inline int power(int a,int b){int rt=1;while(b>0){if(b&1)rt=mul(rt,a);a=mul(a,a);b>>=1;}return rt;}
inline int inv(int a){return power(a,mod-2);}
int main()
{
```

```

ios_base::sync_with_stdio(false);cin.tie(0);cout<<
    .tie(0);cout<<setprecision(25);
}
// clock
clock_t clk = clock();
clk = clock() - clk;
((ld)clk)/CLOCKS_PER_SEC
// fastio
inline ll read() {
    ll n = 0; char c = getchar_unlocked();
    while (!('0' <= c && c <= '9')) c = getchar_unlocked();
    while ('0' <= c && c <= '9')
        n = n * 10 + c - '0', c = getchar_unlocked();
    return n;
}
inline void write(ll a){
    register char c; char snum[20]; ll i=0;
    do{
        snum[i++] = a%10+48;
        a = a/10;
    }
    while(a!=0); i--;
    while(i>=0)
        putchar_unlocked(snum[i--]);
    putchar_unlocked('\n');
}
// gp_hash_table
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
gp_hash_table<int, int> table; //cc_hash_table can also be used
//custom hash function
const int RANDOM = chrono::high_resolution_clock::now().time_since_epoch().count();
struct chash {
    int operator()(int x) { return hash<int>{}(x ^ RANDOM); }
};
gp_hash_table<int, int, chash> table;
//custom hash function for pair
struct chash {
    int operator()(pair<int,int> x) const { return x.first* 31 + x.second; }
};
// random
mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());
uniform_int_distribution<int> uid(1,r);
int x=uid(rng);
//mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
// - for 64 bit unsigned numbers
vector<int> per(N);

```

```

for (int i = 0; i < N; i++)
    per[i] = i;
shuffle(per.begin(), per.end(), rng);
// string splitting
// this splitting is better than custom function(w.r.t time)
using getline, use cin.ignore()
string line = "Ge";
vector<string> tokens;
stringstream check1(line);
string ele;
// Tokenizing w.r.t. space ' '
while(getline(check1, ele, ' '))
    tokens.push_back(ele);
//Ordered Sets
typedef tree<ll,null_type,less<ll>,rb_tree_tag,tree_order_statistics_node_update> ordered_set;
ordered_set X;X.insert(1);X.insert(2);
*X.find_by_order(0)-> 1
*X.find_by_order(1)-> 2
(end(X)==X.find_by_order(2) -> true
//order_of_key(x) -> # of elements < x
//For multiset use less_equal operator but
//it does support erase operations for multiset

```

## 1.2 C++ Sublime Build

```

{
    "cmd": ["bash", "-c", "g++ -std=c++11 -O3 '${file}' -o '${file_path}/${file_base_name}' && gnome-terminal -- bash -c '\"${file_path}/${file_base_name}\" < input.txt >output.txt'"],
    "file_regex": "^(..[^:]*):([0-9]+):?([0-9]+)?(?:.*)$",
    "working_dir": "${file_path}",
    "selector": "source.c++, source.cpp",
}

```

## 2 Data Structures

### 2.1 Fenwick

```

/*All indices are 1 indexed
*Range update and point query: maintain BIT of prefix sum of updates
-add val in [a,b] -> add val at a,-val at b+1
-value[a]=BITsum(a)+arr[a]
*Range update ,range query: maintain 2 BITs B1,B2
-add val in [a,b] -> B1:add val at a,-val at b+1 and in B2 -> Add val*(a-1) at a, -val*b at b+1
-sum[1,b]=B1sum(1,b)*b-B2sum(1,b)
-sum[a,b]=sum[1,b]-sum[1,a-1]*/
ll fen[MAX_N];
void update(ll p,ll val){

```

```

for(ll i = p; i <= n; i += i & -i)
    fen[i] += val;}
ll sum(ll p){
    ll ans = 0;
    for(ll i = p; i; i -= i & -i) ans += fen[i];
    return ans;}

```

## 2.2 2D-BIT

```

/*All indices are 1 indexed. Increment value of ←
cell (i,j) by val -> update(x,y,val)
*sum of rectangle [a,b]-[c,d] -> sum of rectangles ←
[1,1]-[c,d], [1,1]-[c,b], [1,1][a,d] and [1,1]-[a,←
b] and use inclusion exclusion*/
ll bit[MAX][MAX];
void update(ll x, ll y, ll val){
    while( x < MAX ){
        ll y1 = y;
        while( y1 < MAX )
            bit[x][y1] += val, y1 += ( y1 & -y1 );
        x += ( x & -x );
    }
}
ll sum(ll x, ll y){
    ll ans = 0;
    while( x > 0 ){
        ll y1 = y;
        while( y1 > 0 )
            ans += bit[x][y1], y1 -= ( y1 & -y1 );
        x -= ( x & -x );
    }
    return ans;}

```

## 2.3 Segment Tree

```

/*All arrays are 0 indexed. call bld(0,n-1,1)
upd(0,n-1,1,x,y,val) -> increase [x,y] by val
sum(0,n-1,1,x,y) -> sum [x,y]
array of size N -> segment tree of size 4*N*/
ll arr[N], st[N<<2], lz[N<<2];
void ppgt(ll l, ll r, ll id){
    if(l==r) return;
    ll m = l+r>>1;
    lz[id*2] += lz[id]; lz[id<<1|1] += lz[id];
    st[id<<1] += (m - l + 1) * lz[id];
    st[id<<1|1] += (r-m)*lz[id]; lz[id] = 0;}
void bld(ll l, ll r, ll id){
    if(l==r) { st[id] = arr[l]; return; }
    bld(l, l+r>>1, id*2); bld(l+r+1>>1, r, id*2+1);
    st[id] = st[id<<1] + st[id<<1|1];}
void upd(ll l, ll r, ll id, ll x, ll y, ll val){
    if (l > y || r < x) return; ppgt(l, r, id);
    if (l >= x && r <= y) {
        lz[id] += val; st[id] += (r-l+1)*val; return;}
    upd(l, l+r>>1, id<<1, x, y, val); upd((l+r<←
>>1) + 1, r, id<<1|1, x, y, val);
    st[id] = st[id<<1] + st[id<<1|1];}
ll sum(ll l, ll r, ll id, ll x, ll y){

```

```

if (l > y || r < x) return 0; ppgt(l, r, id);
if (l >= x && r <= y) return st[id];
return sum(l, l+r>>1, id<<1, x, y) + sum((l<←
+r>>1) + 1, r, id<<1|1, x, y);}

```

## 2.4 Persistent Segment Tree

```

/*id of first node = 0. call build(0,n-1) first. ←
afterwards call upd(0,n-1,previous id,i,val) to ←
add val in ith number. It returns root of new ←
segment tree after modification
*sum(0,n-1,id of root,l,r) -> sum of values in ←
subarray l to r in tree rooted at id
**size of st,lc,rc >= N*2+(N+Q)*logN*/
const ll N=1e5+10;
ll arr[N], st[20*N], lc[20*N], rc[20*N], ids[N], cnt;
void build(ll l, ll r){
    if(l==r) {st[cnt]=arr[l]; ++cnt; return;}
    ll id = cnt++; lc[id] = cnt;
    build(l, l+r>>1);
    rc[id] = cnt; build((l+r>>1) + 1, r);
    st[id] = st[lc[id]] + st[rc[id]];
}
ll upd(ll l, ll r, ll id, ll x, ll val){
    if(l==r)
        {st[cnt]=st[id]+val; ++cnt; return cnt-1;}
    ll myid = cnt++; ll mid = l+r>>1;
    if(x <= mid)
        rc[myid] = rc[id], lc[myid] = upd(l, mid, lc[id]<←
], x, val);
    else
        lc[myid] = lc[id], rc[myid] = upd(mid+1, r, rc[id]<←
id], x, val);
    st[myid] = st[lc[myid]] + st[rc[myid]];
    return myid;}
ll sum(ll l, ll r, ll id, ll x, ll y){
    if (l > y || r < x) return 0;
    if (l >= x && r <= y) return st[id];
    return sum(l, l+r>>1, lc[id], x, y) + sum((l<←
+r>>1) + 1, r, rc[id], x, y);}
ll gkth(ll l, ll r, ll id1, ll id2, ll k){
    if(l==r) return l; ll mid = l+r>>1;
    ll a = st[lc[id2]] - (id1>=0?st[lc[id1]]:0);
    if(a >= k)
        return gkth(l, mid, (id1>=0?lc[id1]:-1), lc[←
id2], k);
    else
        return gkth(mid+1, r, (id1>=0?rc[id1]:-1), rc[←
id2], k-a);}
//kth largest num in range
int main(){
    ll n,m; vll finalid(n); vpll v;
    loop : v.pb({arr[i],i}); sort(all(v));
    loop : finalid[v[i].second]=i;
    memset(arr,0,sizeof(ll)*N);
    arr[finalid[0]]++; build(0,n-1);
    loop:ids[i]=upd(0,n-1,ids[i-1],finalid[i],1);
}

```

```

while(m--){
    ll i,j,k;cin>>i>>j>>k;--i;--j;
    ans=gkth(0,n-1,(i==0?-1:ids[i-1]),ids[j],k);
    cout<<v[ans].F<<endl;}
}

```

## 2.5 DP Optimization

/\*Split L size array into G intervals, minimizing the cost ( $G \leq L$ ). The cost func.  $C[i,j]$  satisfies:  $C[a,b]+C[c,d] \leq C[a,d]+C[c,b]$  for  $a \leq c \leq b \leq d$ . (Q.E) & intuitively you can think that the c.f increases at a rate which is more than linear at all intervals.

So, if the c.f. satisfies Q.E., the following holds:

$F(g,1)$ : min cost of splitting first l into g ival's.

$F(g,1)$ :  $\min(F(g-1,k)+C(k+1,1))$  over all valid k.

$P(g,1)$ : lowest position k s.t. it minimizes  $F(g,1)$

$P(g,0) \leq P(g,1) \leq \dots \leq P(g,l)$ ; DivConq,  $O(G.L.\log(L))$

$P(0,1) \leq P(1,1) \leq P(2,1) \dots \leq P(G-1,1) \leq P(G,1)$ .

Knuth Opti, complexity  $O(L.L)$ .

For div&conq, we calculate  $P(g,1)$  for each g 1 by 1.

In each g, we calculate for mid-1 and do recursively using the obtained upper and lower bounds. For knuth, we use  $P(g,1-1) \leq P(g,1) \leq P(g+1,1)$ , and fill our table in increasing l and decreasing g. In opt. BST type problems, use  $bk[i][j-1] \leq bk[i][j] \leq bk[i+1][j]$

\*/

// Code for Divide and Conquer Opti  $O(G.L.\log(L))$ :

```

ll C[8111]; ll sums[8111];
ll F[811][8111]; // optimal value
int P[811][8111]; // optimal position.
// note first val. in arrays is for no. of groups
ll cost(int i, int j) { // cost function
    return i > j ? 0 : (sums[j]-sums[i-1])*(j-i+1);
}
/*fill(g,l1,l2,p1,p2) calcs. P[g][l] and F[g][l]
for
ll<=l<= l2, with the knowledge that p1<=P[g][l]<=p2
*/
void fill(int g, int l1, int l2, int p1, int p2) {
    if (l1 > l2) return; int lm = (l1 + l2) >> 1;
    ll nv=INF, nv1=-1;
    for (int k = p1; k <= min(lm-1,p2); k++) {
        ll new_cost = F[g-1][k] + cost[k+1][lm];
        if (nv > new_cost) { nv=new_cost; nv1 = k; }
    }
    P[g][lm]=nv1; F[g][lm]=nv;
    fill(g, l1, lm-1, p1, P[g][lm]);
}

```

```

fill(g, lm+1, l2, P[g][lm], p2);
}
int main() { // example call
    for(i=0;i<=n;i++)F[0][i]=INF;
    for(i=0;i<=k;i++)F[i][0]=0;
    F[0][0]=0;
    for(i=1;i<=k;i++)fill(i,1,n,0,n);
}
// Code for Knuth Optimization  $O(L.L)$  :-
ll dp[8002][802];
int a[8002],s[8002][802];
ll sum[8002];
// index strats from 1
ll run(int n,int m) {
    memset(dp,0xff,sizeof(dp)); dp[0][0] = 0;
    for (int i = 1; i <= n; ++i) {
        sum[i] = sum[i-1] + a[i];
        int maxj = min(i, m), mk; ll mn = INF;
        for (int k = 0; k < i; ++k) {
            if (dp[k][maxj-1] >= 0) {
                ll tmp = dp[k][maxj-1] +
                    (sum[i] - sum[k]) * (i - k);
                if (tmp < mn) {
                    mn = tmp; mk = k; }
            }
        }
        dp[i][maxj] = mn; s[i][maxj] = mk;
        for (int j = maxj-1; j >= 1; --j) {
            ll mn = INF; int mk;
            for (ll k=s[i-1][j]; k<=s[i][j+1];++k){
                if (dp[k][j-1] >= 0) {
                    ll tmp = dp[k][j-1] + (sum[i]-sum[k])*(i-
                        k);
                    if (tmp < mn) {mn = tmp;mk = k;} }
            }
            dp[i][j] = mn; s[i][j] = mk;
        }
    }
    return dp[n][m];
}
// call -> run(n, min(n,m))

```

## 3 Flows and Matching

### 3.1 General Matching

/\*Given any directed graph, finds maximal matching Vertices-0-indexed,  $O(n^3)$  per call to edmonds\*/

```

vll adj[MAXN]; int p[MAXN], base[MAXN], match[MAXN];
int lca(int n, int u, int v){
    vector<bool> used(n);
    for (;;) {
        u = base[u]; used[u] = true;
        if (match[u] == -1) break; u = p[match[u]];
    }
    for (;;) {

```

```

    v = base[v]; if (used[v]) return v;
    v = p[match[v]];}}
void mark_path(vector<bool> &blo, int u, int b, int ←
    child){
    for (; base[u] != b; u = p[match[u]]){
        blo[base[u]] = true; blo[base[match[u]]] = ←
            true;
        p[u] = child; child = match[u];}}
int find_path(int n, int root) {
    vector<bool> used(n);
    for (int i = 0; i < n; ++i)
        p[i] = -1, base[i] = i;
    used[root] = true;
    queue<int> q; q.push(root);
    while(!q.empty()) {
        int u = q.front(); q.pop();
        for (int j = 0; j < (int)adj[u].size(); j++) {
            int v = adj[u][j];
            if(base[u]==base[v] || match[u]==v)continue;
            if(v==root||(match[v]!=-1 && p[match[v]←
                ]!=-1)){
                int curr_base = lca(n, u, v);
                vector<bool> blossom(n);
                mark_path(blossom, u, curr_base, v);
                mark_path(blossom, v, curr_base, u);
                for(int i = 0; i < n; i++){
                    if(blossom[base[i]]){
                        base[i] = curr_base;
                        if(!used[i]) used[i] = true, q.push(i)←
                            ;
                    }
                }
            }else if (p[v] == -1){
                p[v] = u;
                if (match[v] == -1) return v;
                v=match[v]; used[v]=true; q.push(v);
            }
        }
    }
    return -1;}
int edmonds(int n){
    for(int i=0;i<n;i++) match[i] = -1;
    for(int i = 0; i < n; i++){
        if (match[i] == -1) {
            int u, pu, ppu;
            for (u = find_path(n, i); u != -1; u = ppu) ←
                {
                    pu = p[u]; ppu = match[pu];
                    match[u] = pu; match[pu] = u;
                }
        }
    }
    int matches = 0;
    for (int i = 0; i < n; i++)
        if (match[i] != -1) matches++;

```

```

        return matches/2;
    }
    u--; v--; adj[u].pb(v); adj[v].pb(u);
    cout << edmonds(n) * 2 << endl;
    for (int i = 0; i < n; i++) {
        if (match[i] != -1 && i < match[i]) {
            cout << i + 1 << " " << match[i] + 1 << ←
                endl;
        }
    }
}

```

### 3.2 Global Mincut

```

/*finds min weighted cut in undirected graph in
O(n^3), Adj Matrix, 0-indexed vertices
output-(min cut value, nodes in half of min cut)*/
typedef vector<int> VI;
typedef vector<VI> VVI;
const int INF = 1000000000;
pair<int, VI> GetMinCut(VVI &weights) {
    int N = weights.size();
    VI used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N-1; phase >= 0; phase--) {
        VI w = weights[0];
        VI added = used;
        int prev, last = 0;
        for (int i = 0; i < phase; i++) {
            prev = last; last = -1;
            for (int j = 1; j < N; j++)
                if(!added[j] && (last == -1 || w[j] > w[last]←
                    ))
                    last = j;
            if (i == phase-1) {
                for(int j=0;j<N;j++)
                    weights[prev][j] += weights[last][j];
                for(int j=0;j<N;j++)
                    weights[j][prev] = weights[prev][j];
                used[last] = true; cut.push_back(last);
                if (best_weight==-1 || w[last]<best_weight←
                    )
                    best_cut = cut, best_weight = w[last];
            }
            else {
                for (int j = 0; j < N; j++)
                    w[j] += weights[last][j];
                added[last] = true;
            }
        }
    }
    return make_pair(best_weight, best_cut);
}
VVI weights(n, VI(n));
pair<int, VI> res = GetMinCut(weights);

```



### 3.3 Hopcroft Matching

```
// O(m * \sqrt{n})
struct graph {
    int L, R; // 0-indexed vertices
    vector<vector<int>>> adj;
    graph(int L, int R) : L(L), R(R), adj(L+R) {}
    void add_edge(int u, int v) {
        adj[u].pb(v+L); adj[v+L].pb(u);
    }
    int maximum_matching() {
        vector<int> level(L), mate(L+R, -1);
        function<bool(void)> levelize = [&]() { // BFS
            queue<int> Q;
            for (int u = 0; u < L; ++u) {
                level[u] = -1;
                if (mate[u] < 0) level[u] = 0, Q.push(u);
            }
            while (!Q.empty()) {
                int u = Q.front(); Q.pop();
                for (int w: adj[u]) {
                    int v = mate[w];
                    if (v < 0) return true;
                    if (level[v] < 0)
                        level[v] = level[u] + 1, Q.push(v);
                }
            }
            return false;
        };
        function<bool(int)> augment = [&](int u) { // ←
            DFS
            for (int w: adj[u]) {
                int v = mate[w];
                if (v < 0 || (level[v] > level[u] && augment(v) ←
                    )) {
                    mate[u] = w; mate[w] = u; return true;
                }
            }
            return false;
        };
        int match = 0;
        while (levelize())
            for (int u = 0; u < L; ++u)
                if (mate[u] < 0 && augment(u)) ++match;
        return match;
    }; // L-left size, R-right size
    graph g(L,R); g.add_edge(u,v); g.maximum_matching←
    ();
```

### 3.4 Dinic

*/\*O(min(fm,mn<sup>2</sup>)), for any unit capacity network  
O(m\*sqrt(n)), in practice it is pretty fast for ←  
any  
bipartite network, \*\*vertices are 1-indexed\*\*  
e=(u,v), e.flow represent effective flow from u to←  
v*

```
(i.e f(u->v) - f(v->u))
*use int if possible(1l could be slow in dinic)
To put lower bound on edge capacities form a new
graph G' with source s' and t' for each edge u->v
in G with cap (low, high), replace it with
s'->v with low, v->t' with low
u->v with high - low*/
struct edge {ll x, y, cap, flow;};
struct DinicFlow {
    // *** change inf accordingly *****
    const ll inf = (1e18);
    vector<edge> e; vll cur, d;
    vector<vll> adj; ll n, source, sink;
    DinicFlow() {}
    DinicFlow(ll v) {
        n = v; cur = vll(n+1);
        d = vll(n+1); adj = vector<vll>(n+1);
    }
    void addEdge(ll from, ll to, ll cap) {
        edge e1 = {from, to, cap, 0};
        edge e2 = {to, from, 0, 0};
        adj[from].pb(e.size()); e.pb(e1);
        adj[to].pb(e.size()); e.pb(e2);
    }
    ll bfs() {
        queue<ll> q;
        for(ll i = 0; i <= n; ++i) d[i] = -1;
        q.push(source); d[source] = 0;
        while(!q.empty() and d[sink] < 0) {
            ll x = q.front(); q.pop();
            for(ll i = 0; i < (ll)adj[x].size(); ++i){
                ll id = adj[x][i], y = e[id].y;
                if(d[y]<0 and e[id].flow < e[id].cap){
                    q.push(y); d[y] = d[x] + 1;
                }
            }
        }
        return d[sink] >= 0;
    }
    ll dfs(ll x, ll flow) {
        if(!flow) return 0;
        if(x == sink) return flow;
        for(; cur[x] < (ll)adj[x].size(); ++cur[x]) {
            ll id = adj[x][cur[x]], y = e[id].y;
            if(d[y] != d[x] + 1) continue;
            ll pushe=dfs(y,min(flow,e[id].cap-e[id].flow←
                ));
            if(pushed) {
                e[id].flow += pushed; e[id^1].flow -= ←
                pushed;
                return pushed;
            }
        }
        return 0;
    }
    ll maxFlow(ll src, ll snk) {
```

```

this->source = src; this->sink = snk;
ll flow = 0;
while(bfs()) {
    for(ll i = 0; i <= n; ++i) cur[i] = 0;
    while(ll pushed = dfs(source, inf))
        flow += pushed;
}
return flow;
};

```

### 3.5 Ford Fulkerson

```

/*O(f*m)*/ ll n; // number of vertices
ll cap[N][N]; // adj matrix for cap
vll adj[N]; // *** vertices are 0-indexed ***
// adj list of the corresponding undirected(*imp*)
ll INF = (1e18);
ll snk, cnt; // cnt for vis, no need to initialize ← vis
vector<ll> par, vis;
ll dfs(ll u, ll curf) {
    vis[u] = cnt; if(u == snk) return curf;
    if(adj[u].size() == 0) return 0;
    for(ll j = 0; j < adj[u].size(); ++j) { // random for good aug.
        ll a = rand() % (adj[u].size()); ll v = adj[u][a] ←
    };
    if(vis[v] == cnt || cap[u][v] == 0) continue;
    par[v] = u;
    ll f = dfs(v, min(curf, cap[u][v]));
    if(vis[snk] == cnt) return f;
}
for(auto v : adj[u]) {
    if(vis[v] == cnt || cap[u][v] == 0) continue;
    par[v] = u;
    ll f = dfs(v, min(curf, cap[u][v]));
    if(vis[snk] == cnt) return f;
}
return 0;
}
ll maxflow(ll s, ll t) {
    snk = t; ll flow = 0; cnt++;
    par = vll(n, -1); vis = vll(n, 0);
    while(ll new_flow = dfs(s, INF)) {
        flow += new_flow; cnt++;
        ll cur = t;
        while(cur != s) {
            ll prev = par[cur];
            cap[prev][cur] -= new_flow;
            cap[cur][prev] += new_flow;
            cur = prev;
        }
    }
    return flow;
}

```

### 3.6 MCMF

```

/*Works for -ve costs, doesn't work for -ve cycles
O(min(E^2 * V log V, E log V * flow))
**INF is used in both flow_type and cost_type*/
const ll INF = 1e9; // vertices are 0-indexed
struct graph {
    typedef ll flow_type; // **** flow type ****
    typedef ll cost_type; // **** cost type ****
    struct edge {
        int src, dst;
        flow_type cap, flow;
        cost_type cost;
        size_t rev;
    };
    vector<edge> edges;
    void add_edge(int s, int t, flow_type cap, ←
        cost_type cost) {
        adj[s].pb({s, t, cap, 0, cost, adj[t].size()});
        adj[t].pb({t, s, 0, 0, -cost, adj[s].size()-1});
    }
    int n; vector<vector<edge>> adj;
    graph(int n) : n(n), adj(n) {}
    pair<flow_type, cost_type> min_cost_max_flow(int ←
        s, int t) {
        flow_type flow = 0;
        cost_type cost = 0;
        for (int u = 0; u < n; ++u) // initialize
            for (auto &e: adj[u]) e.flow = 0;
        vector<cost_type> p(n, 0);
        auto rcost = [&](edge e)
        {return e.cost + p[e.src] - p[e.dst];};
        for (int iter = 0; ; ++iter) {
            vector<int> prev(n, -1); prev[s] = 0;
            vector<cost_type> dist(n, INF); dist[s] = 0;
            if (iter == 0) { // use Bellman-Ford to
                // remove negative cost edges
                vector<int> count(n); count[s] = 1;
                queue<int> que;
                for (que.push(s); !que.empty(); ) {
                    int u = que.front(); que.pop();
                    count[u] = -count[u];
                    for (auto &e: adj[u]) {
                        if (e.cap > e.flow && dist[e.dst] > ←
                            dist[e.src] + rcost(e)) {
                            dist[e.dst] = dist[e.src] + rcost(e);
                            prev[e.dst] = e.rev;
                            if (count[e.dst] <= 0) {
                                count[e.dst] = -count[e.dst] + 1;
                                que.push(e.dst);
                            }
                        }
                    }
                }
            }
            for (int i = 0; i < n; i++) p[i] = dist[i];
        }
    }
}

```

```

    continue; // added last 2 lines
} else { // use Dijkstra
typedef pair<cost_type, int> node;
priority_queue<node, vector<node>, greater<
    <node>> > que;
que.push({0, s});
while (!que.empty()) {
    node a = que.top(); que.pop();
    if (a.S == t) break;
    if (dist[a.S] > a.F) continue;
    for (auto e: adj[a.S]) {
        if (e.cap > e.flow && dist[e.dst] > a.F + rcost(e)) {
            dist[e.dst] = dist[e.src] + rcost(e);
            prev[e.dst] = e.rev;
            que.push({dist[e.dst], e.dst});
        }
    }
}
if (prev[t] == -1) break;
for (int u = 0; u < n; ++u)
    if (dist[u] < dist[t]) p[u] += dist[u] - dist[t];
function<flow_type(int, flow_type)> augment =
    [&](int u, flow_type cur) {
        if (u == s) return cur;
        edge &r = adj[u][prev[u]], &e = adj[r.dst][r.rev];
        flow_type f = augment(e.src, min(e.cap - e.flow, cur));
        e.flow += f; r.flow -= f;
        return f;
    };
flow_type f = augment(t, INF);
flow += f;
cost += f * (p[t] - p[s]);
}
return {flow, cost};
};

```

### 3.7 MinCost Matching

```

/*O(n^3) solves 1000x1000 problems in around 1s
cost[i][j] = cost for pairing Li with Rj
Lmate[i]=index of R node that L node i pairs with
Rmate[j]=index of L node that R node j pairs with
cost[i][j] may be +ve or -ve. To perform
maximization, simply negate the cost[][] matrix.*/
typedef ll cost_type;
typedef vector<cost_type> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;

```

```

cost_type MCM(const VVD &cost, VI &Lmate, VI &Rmate) {
    int n = int(cost.size()); VD u(n), v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost[i][j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost[i][j] - u[i]);
    }
    Lmate = VI(n, -1); Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
                //**** change this comparision if double cost ****
                Lmate[i] = j; Rmate[j] = i; mated++; break;
            }
        }
    }
    VD dist(n); VI dad(n); VI seen(n);
    while (mated < n) {
        int s = 0;
        while (Lmate[s] != -1) s++;
        fill(dad.begin(), dad.end(), -1);
        fill(seen.begin(), seen.end(), 0);
        for (int k = 0; k < n; k++)
            dist[k] = cost[s][k] - u[s] - v[k];
        int j = 0;
        while (true) {
            j = -1;
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                if (j == -1 || dist[k] < dist[j]) j = k;
            }
            seen[j] = 1;
            if (Rmate[j] == -1) break;
            const int i = Rmate[j];
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                const cost_type new_dist = dist[j] + cost[i][k] - u[i] - v[k];
                if (dist[k] > new_dist) {
                    dist[k] = new_dist;
                    dad[k] = j;
                }
            }
        }
        for (int k = 0; k < n; k++) {
            if (k == j || !seen[k]) continue;
            const int i = Rmate[k];
            v[k] += dist[k] - dist[j];
        }
    }
}

```



```

    u[i] -= dist[k]-dist[j];}
    u[s] += dist[j];
    while (dad[j] >= 0) {
        const int d = dad[j];
        Rmate[j]=Rmate[d]; Lmate[Rmate[j]]=j; j=d;}
    Rmate[j] = s; Lmate[s] = j; mated++;
}
cost_type value = 0;
for (int i = 0; i < n; i++)
    value += cost[i][Lmate[i]];
return value;
}

```

## 4 Geometry

### 4.1 Geometry

```

//do not read input in double format
#define PI acos(-1)
//atan2(y,x) slope of line (0,0)->(x,y) in radian ←
    (-PI,PI]
// to convert to degree multiply by 180/PI
ld INF = 1e100;
ld EPS = 1e-9;
inline bool eq(ld a,ld b) {return fabs(a-b)<EPS;}
inline bool lt(ld a,ld b) {return a+EPS<b;}
inline bool gt(ld a,ld b) {return a>b+EPS;}
inline bool le(ld a,ld b) {return lt(a,b)||eq(a,b)←
};
inline bool ge(ld a,ld b) {return gt(a,b)||eq(a,b)←
};
struct pt {
    ld x, y;
    pt() {}
    pt(ld x, ld y) : x(x), y(y) {}
    pt(const pt &p) : x(p.x), y(p.y) {}
    pt operator + (const pt &p)
    const { return pt(x+p.x, y+p.y); }
    pt operator - (const pt &p)
    const { return pt(x-p.x, y-p.y); }
    pt operator * (ld c)
    const { return pt(x*c, y*c); }
    pt operator / (ld c)
    const { return pt(x/c, y/c); }
    bool operator < (const pt &p)
    const {return lt(y,p.y)|| (eq(y,p.y)&&ltlt(x,p.x))←
};
    bool operator > (const pt &p)
    const{ return p<pt(x,y);}
    bool operator <= (const pt &p)
    const{ return !(pt(x,y)>p);}
    bool operator >= (const pt &p)
    const{ return !(pt(x,y)<p);}
    bool operator == (const pt &p)

```

```

    const{ return (pt(x,y)<=p)&&(pt(x,y)>=p);}
};
ld dot(pt p,pt q) {return p.x*q.x+p.y*q.y;}
ld dist2(pt p, pt q) {return dot(p-q,p-q);}
ld dist(pt p,pt q) {return sqrt(dist2(p,q));}
ld norm2(pt p) {return dot(p,p);}
ld norm(pt p) {return sqrt(norm2(p));}
ld cross(pt p, pt q) { return p.x*q.y-p.y*q.x;}
ostream &operator<<(ostream &os, const pt &p) {
    return os << "(" << p.x << ", " << p.y << ")";}
istream& operator >> (istream &is, pt &p){
    return is >> p.x >> p.y;}
//returns 0 if a,b,c are collinear,1 if a->b->c is←
    cw and -1 if ccw
int orient(pt a,pt b,pt c)
{
    pt p=b-a,q=c-b;double cr=cross(p,q);
    if(eq(cr,0))return 0;if(lt(cr,0))return 1;return←
        -1;}
// rotate a point CCW or CW around the origin
pt RotateCCW90(pt p) { return pt(-p.y,p.x); }
pt RotateCW90(pt p) { return pt(p.y,-p.x); }
pt RotateCCW(pt p, ld t) {//rotate by t degree ccw
return pt(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*←
    cos(t)); }
// project point c onto line (not segment) through←
    a and b assuming a != b
pt ProjectPointLine(pt a, pt b, pt c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);}
// project point c onto line segment through a and←
    b (closest point on line segment)
pt ProjectPointSegment(pt a, pt b, pt c) {
    ld r = dot(b-a,b-a); if (eq(r,0)) return a;//a ←
        and b are same
    r = dot(c-a, b-a)/r;if (lt(r,0)) return a;//c on←
        left of a
    if (gt(r,1)) return b; return a + (b-a)*r;}
// compute dist from c to segment between a and b
ld DistancePointSegment(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c←
        )));}
// compute dist from c to line between a and b
ld DistancePointLine(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointLine(a, b, c))←
        );}
// determine if lines from a to b and c to d are ←
    parallel or collinear
bool LinesParallel(pt a, pt b, pt c, pt d) {
    return eq(cross(b-a, c-d),0);}
bool LinesCollinear(pt a, pt b, pt c, pt d) {
    return LinesParallel(a, b, c, d) && eq(cross(a-b←
        , a-c),0) && eq(cross(c-d, c-a),0);}
// determine if line segment from a to b ←
    intersects with line segment from c to d

```

```

bool SegmentsIntersect(pt a, pt b, pt c, pt d) {
    if (LinesCollinear(a, b, c, d)) {
        //a->b and c->d are collinear and have one ←
        point common
        if (eq(dist2(a, c), 0) || eq(dist2(a, d), 0) || eq(←
            dist2(b, c), 0) || eq(dist2(b, d), 0))
            return true;
        if (gt(dot(c-a, c-b), 0) && gt(dot(d-a, d-b), 0) && gt(←
            dot(c-b, d-b), 0)) return false;
        return true;
    }
    if (gt(cross(d-a, b-a) * cross(c-a, b-a), 0)) return ←
        false; //c, d on same side of a, b
    if (gt(cross(a-c, d-c) * cross(b-c, d-c), 0))
        return false; //a, b on same side of c, d
    return true;
}
// compute intersection of line passing through a ←
// and b
// with line passing through c and d, assuming that ←
// **unique** intersection exists;
// *for segment intersection, check if segments ←
// intersect first
pt ComputeLineIntersection(pt a, pt b, pt c, pt d) {
    b = b - a; d = d - c; c = c - a; //lines must not be collinear
    assert(gt(dot(b, b), 0) && gt(dot(d, d), 0));
    return a + b * cross(c, d) / cross(b, d);
}
// returns true if point a, b, c are collinear and b ←
// lies between a and c
bool between(pt a, pt b, pt c) {
    if (!eq(cross(b-a, c-b), 0)) return 0; //not ←
    collinear
    return le(dot(b-a, b-c), 0);
}
// compute intersection of line segment a-b and c-d
pt ComputeSegmentIntersection(pt a, pt b, pt c, pt d) ←
{
    if (!SegmentsIntersect(a, b, c, d)) return {INF, INF}; ←
    //don't intersect
    //if collinear then infinite intersection points ←
    //this returns any one
    if (LinesCollinear(a, b, c, d)) { if (between(a, c, b)) ←
        return c; if (between(c, a, d)) return a; return b; }
    return ComputeLineIntersection(a, b, c, d);
}
// compute center of circle given three points - * ←
// a, b, c shouldn't be collinear
pt ComputeCircleCenter(pt a, pt b, pt c) {
    b = (a+b)/2; c = (a+c)/2;
    return ComputeLineIntersection(b, b+RotateCW90(a-←
        b), c, c+RotateCW90(a-c));
}
// point in polygon using winding number -> returns ←
// 0 if point is outside
// winding number > 0 if point is inside and equal to ←
// 0 if outside
// draw a ray to the right and add 1 if side goes ←
// from up to down and -1 otherwise
bool PointInPolygon(const vector<pt> &p, pt q) {

```

```

    int n = p.size(), windingNumber = 0;
    for (int i = 0; i < n; ++i) {
        if (eq(dist2(q, p[i]), 0)) return 1; //q is a ←
        vertex
        int j = (i+1) % n;
        if (eq(p[i].y, q.y) && eq(p[j].y, q.y)) { //i, i+1 ←
            vertex is vertical
            if (le(min(p[i].x, p[j].x), q.x) && le(q.x, max(p[←
                i].x, p[j].x))) return 1; } //q lies on ←
            boundary
        else {
            bool below = lt(p[i].y, q.y);
            if (below != lt(p[j].y, q.y)) {
                auto orientation = orient(q, p[j], p[i]);
                if (orientation == 0) return 1; //q lies on ←
                boundary i->j
                if (below == (orientation > 0)) windingNumber += ←
                    below ? 1 : -1; } }
            return windingNumber == 0 ? 0 : 1;
        }
    }
    // determine if point is on the boundary of a ←
    polygon
    bool PointOnPolygon(const vector<pt> &p, pt q) {
        for (int i = 0; i < p.size(); i++)
            if (eq(dist2(ProjectPointSegment(p[i], p[(i+1)%←
                p.size()], q), q), 0)) return true;
        return false;
    }
    // Compute area or centroid of any polygon (←
    // coordinates must be listed in cw/ccw
    // fashion. The centroid is often known as center of ←
    // gravity/mass
    ld ComputeSignedArea(const vector<pt> &p) {
        ld ans = 0;
        for (int i = 0; i < p.size(); i++) {
            int j = (i+1) % p.size();
            ans += cross(p[i], p[j]);
        } return ans / 2.0;
    }
    ld ComputeArea(const vector<pt> &p) {
        return fabs(ComputeSignedArea(p));
    }
    // compute intersection of line through points a ←
    // and b with
    // circle centered at c with radius r > 0
    vector<pt> CircleLineIntersection(pt a, pt b, pt c ←
        , ld r) {
        vector<pt> ret;
        b = b - a; a = a - c;
        ld A = dot(b, b), B = dot(a, b), C = dot(a, a) - r ←
            *r, D = B*B - A*C;
        if (lt(D, 0)) return ret; //don't intersect
        ret.push_back(c + a + b * (-B + sqrt(D + EPS)) / A);
        if (gt(D, 0)) ret.push_back(c + a + b * (-B - sqrt(D)) / A) ←
            ;
        return ret;
    }

```

```

// compute intersection of circle centered at a ←
// with radius r
// with circle centered at b with radius R
vector<pt> CircleCircleIntersection(pt a, pt b, ld←
    r, ld R) {
    vector<pt> ret;
    ld d = sqrt(dist2(a, b)), d1=dist2(a,b);
    pt inf(INF,INF);
    if(eq(d1,0)&&eq(r,R)){ret.pb(inf);return ret;}//←
    // circles are same return (INF,INF)
    if(gt(d,r+R) || lt(d+min(r, R),max(r, R)) ) ←
        return ret;
    ld x = (d*d-R*R+r*r)/(2*d), y = sqrt(r*r-x*x);
    pt v = (b-a)/d;
    ret.push_back(a+v*x + RotateCCW90(v)*y);
    if (gt(y,0)) ret.push_back(a+v*x - RotateCCW90(v←
        )*y);
    return ret;}
//compute centroid of simple polygon by dividing ←
// it into disjoint triangles
//and taking weighted mean of their centroids (←
//Jerome)
pt ComputeCentroid(const vector<pt> &p) {
    pt c(0,0),inf(INF,INF);
    ld scale = 6.0 * ComputeSignedArea(p);
    if(p.empty())return inf;//empty vector
    if(eq(scale,0))return inf;//all points on ←
    //straight line
    for (int i = 0; i < p.size(); i++){
        int j = (i+1) % p.size();
        c = c + (p[i]+p[j])*cross(p[i],p[j]);}
    return c / scale;}
// tests whether or not a given polygon (in CW or ←
// CCW order) is simple
bool IsSimple(const vector<pt> &p) {
    for (int i = 0; i < p.size(); i++) {
        for (int k = i+1; k < p.size(); k++) {
            int j = (i+1) % p.size();
            int l = (k+1) % p.size();
            if (i == 1 || j == k) continue;
            if (SegmentsIntersect(p[i], p[j], p[k], p[l]←
                ))
                return false;}}
    return true;}
/*point in convex polygon
****bottom left point must be at index 0 and top ←
is the index of upper right vertex
****if not call make_hull once*/
bool pointinConvexPolygon(vector<pt> poly,pt point←
    , int top) {
    if (point < poly[0] || point > poly[top]) return←
        0;//0 for outside and 1 for on/inside
    auto orientation = orient(point, poly[top], poly←
        [0]);

```

```

    if (orientation == 0) {
        if (point == poly[0] || point == poly[top]) ←
            return 1;
        return top == 1 || top + 1 == poly.size() ? 1 ←
            : 1;//checks if point lies on boundary when
        //bottom and top points are adjacent
    } else if (orientation < 0) {
        auto itRight = lower_bound(poly.begin() + 1, ←
            poly.begin() + top, point);
        return orient(itRight[0], point, itRight[-1])←
            <=0;
    } else {
        auto itLeft = upper_bound(poly.rbegin(), poly.←
            rend() - top-1, point);
        return (orient(itLeft == poly.rbegin() ? poly←
            [0] : itLeft[-1], point, itLeft[0]))<=0;
    }
}
/*maximum distance between two points in convex ←
polygon using rotating calipers
make sure that polygon is convex. if not call ←
make_hull first*/
ld maxDist2(vector<pt> poly) {
    int n = poly.size();
    ld res=0;
    for (int i = 0, j = n < 2 ? 0 : 1; i < j; ++i)
        for (; j = j+1 % n) {
            res = max(res, dist2(poly[i], poly[j]));
            if (gt(cross(poly[j+1 % n] - poly[j],poly[i]←
                +1] - poly[i]),0)) break;
        }
    return res;
}
//Line polygon intersection: check if given line ←
intersects any side of polygon
//if yes then line intersects. If no, then check ←
if its midpoint is inside polygon
//if midpoint is inside then line is inside else ←
outside
// compute distance between point (x,y,z) and ←
plane ax+by+cz=d
ld DistancePointPlane(ld x,ld y,ld z,ld a,ld b,ld ←
    c,ld d)
{ return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);}

```

## 4.2 Convex Hull

```

pt firstpoint;
//for sorting points in ccw(counter clockwise) ←
direction w.r.t firstpoint (leftmost and ←
bottommost)
bool compare(pt x,pt y){
    ll o=orient(firstpoint,x,y);
    if(o==0)return lt(x.x+x.y,y.x+y.y);
    return o<0;}

```

```

/*poi->input points, hull->empty vector
returns hull in ccw order with min points*/
void make_hull(vector<pt>& poi,vector<pt>& hull){
    pair<ld,ld> bl={INF,INF};
    ll n=poi.size();ll ind;
    for(ll i=0;i<n;i++){
        pair<ld,ld> pp={poi[i].y,poi[i].x};
        if(pp<bl){
            ind=i;bl={poi[i].y,poi[i].x};
        }
    }
    swap(bl.F,bl.S);firstpoint=pt(bl.F,bl.S);
    vector<pt> cons;
    for(ll i=0;i<n;i++){
        if(i==ind)continue;cons.pb(poi[i]);
    }
    sort(cons.begin(),cons.end(),compare);
    hull.pb(firstpoint);ll m;
    for(auto z:cons){
        if(hull.size()<=1){hull.pb(z);continue;}
        pt pr,ppr;bool fl=true;
        while((m=hull.size())>=2){
            pr=hull[m-1];ppr=hull[m-2];
            ll ch=orient(ppr,pr,z);
            if(ch==-1){break;}
            else if(ch==1){hull.pop_back();continue;}
            else {
                ld d1,d2;
                d1=dist2(ppr,pr);d2=dist2(ppr,z);
                if(gt(d1,d2)){fl=false;break;}else {hull.←
                    pop_back();}
            }
        }
        if(fl){hull.push_back(z);}
    }
    return;
}

```

### 4.3 Li Chao Tree

```

/*All pair of lines must not intersect at more
than 1 points*/
void add_l(pt nw,int v=1,int l=0,int r=maxn) {
    int m = (l + r) / 2;
    bool lef = f(nw, l) < f(line[v], l);
    bool mid = f(nw, m) < f(line[v], m);
    if(mid) swap(line[v], nw);
    if(r - l == 1) return;
    else if(lef != mid) add_line(nw, 2 * v, l, m);
    else add_line(nw, 2 * v + 1, m, r);
}
int get(int x,int v=1,int l=0,int r=maxn) {
    int m=(l+r)/2;
    if(r - l == 1) return f(line[v], x);
    else if(x < m)
        return min(f(line[v],x),get(x,2*v,l,m));
    else
        return min(f(line[v],x),get(x,2*v+1,m,r));
}

```

### 4.4 Convex Hull Trick

```

/*maintains upper convex hull of lines ax+b and ←
gives minimum value at a given x
to add line ax+b: sameoldcht.addline(a,b), to get ←
min value at x: sameoldcht.getbest(x)
to get maximum value at x add -ax-b as lines ←
instead of ax+b and use -sameoldcht.getbest(x)*/
const int N = 1e5 + 5;
int n,a[N],b[N];ll dp[N];
struct line{
    ll a , b;double xleft;bool type;
    line(ll _a , ll _b){a = _a;b = _b;type = 0;}
    bool operator < (const line &other) const{
        if(other.type){return xleft < other.xleft;}
        return a > other.a;}
};
double meet(line x , line y){
    return 1.0 * (y.b - x.b) / (x.a - y.a);}
struct cht{
    set <line> hull;
    cht() {hull.clear();}
    typedef set < line > :: iterator ite;
    bool hasleft(ite node){
        return node != hull.begin();}
    bool hasright(ite node){
        return node != prev(hull.end());}
    void updateborder(ite node){
        if(hasright(node)){line temp = *next(node);
            hull.erase(temp);
            temp.xleft=meet(*node,temp);
            hull.insert(temp);}
        if(hasleft(node)){line temp = *node;
            temp.xleft = meet(*prev(node) , temp);
            hull.erase(node);hull.insert(temp);}
        else{
            line temp = *node;hull.erase(node);
            temp.xleft = -1e18;hull.insert(temp);}
    }
    bool useless(line left,line middle,line right){
        double x = meet(left,right);
        double y = x * middle.a + middle.b;
        double ly = left.a * x + left.b;
        return y > ly;}
    bool useless(ite node){
        if(hasleft(node) && hasright(node)){return
            useless(*prev(node),*node,*next(node));}
        return 0;}
    void addline(ll a , ll b){
        line temp = line(a , b);
        auto it = hull.lower_bound(temp);
        if(it != hull.end() && it -> a == a){
            if(it -> b > b){hull.erase(it);}
            else return;}
        hull.insert(temp);it = hull.find(temp);
    }
}

```



```

    if(useless(it)){hull.erase(it);return;}
    while(hasleft(it) && useless(prev(it))){
        hull.erase(prev(it));
    }
    while(hasright(it) && useless(next(it))){
        hull.erase(next(it));
    }
    updateborder(it);}
11 getbest(11 x){
    if(hull.empty())return 1e18;
    line query(0 , 0);
    query.xleft = x;query.type = 1;
    auto it = hull.lower_bound(query);
    it = prev(it);
    return it -> a * x + it -> b;}
};
cht sameoldcht;
int main(){
    sameoldcht.addline(b[1] , 0);
    dp[i] = sameoldcht.getbest(a[i]);
    sameoldcht.addline(b[i] , dp[i]);}

```

## 5 Trees

### 5.1 BlockCut Tree

```

// Take care it is 0 indexed --
struct BiconnectedComponents {
    struct Edge {
        int from, to;
    };
    struct To {
        int to; int edge;
    };
    vector<Edge> edges; vector<vector<To> > g;
    vector<int> low, ord, depth;
    vector<bool> isArtic; vll edgeColor;
    vector<int> edgeStack;
    int colors; int dfsCounter;
    void init(int n) {
        edges.clear();
        g.assign(n, vector<To>());
    }
    void addEdge(int u, int v) {
        if(u > v) swap(u, v); Edge e = { u, v };
        int ei = edges.size(); edges.push_back(e);
        To tu = { v, ei }, tv = { u, ei };
        g[u].push_back(tu); g[v].push_back(tv);
    }
    void run() {
        int n = g.size(), m = edges.size();
        low.assign(n, -2); ord.assign(n, -1);
        depth.assign(n, -2); isArtic.assign(n, false);
        edgeColor.assign(m, -1); edgeStack.clear();
        colors = 0;
        for(int i = 0; i < n; ++ i) if(ord[i] == -1) {
            dfsCounter = 0;
            dfs(i);
        }
    }
};

```

```

    }
}
private:
void dfs(int i) {
    low[i] = ord[i] = dfsCounter ++;
    for(int j=0; j<(int)g[i].size(); ++j) {
        int to = g[i][j].to, ei = g[i][j].edge;
        if(ord[to] == -1) {
            depth[to] = depth[i] + 1;
            edgeStack.push_back(ei);
            dfs(to);
            low[i] = min(low[i], low[to]);
            if(low[to] >= ord[i]) {
                if(ord[i] != 0 || j >= 1)
                    isArtic[i] = true;
                while(!edgeStack.empty()) {
                    int fi=edgeStack.back();
                    edgeStack.pop_back();
                    edgeColor[fi] = colors;
                    if(fi == ei) break;
                } ++colors;
            }
        }
        else if(depth[to] < depth[i] - 1) {
            low[i] = min(low[i], ord[to]);
            edgeStack.push_back(ei);
        }
    }
}
};

```

### 5.2 Bridge Tree

```

vll tree[N], g[N]; //edge list rep. of graph
11 U[M], V[M], vis[N], arr[N], T, dsu[N];
bool isbridge[M]; // if i'th edge is a bridge edge
11 adj(11 u, 11 e) {
    return U[e]^V[e]^u;
}
11 f(11 x) {
    return dsu[x]=(dsu[x]==x?f(dsu[x]));
}
void merge(11 a, 11 b) {
    dsu[f(a)]=f(b);
}
11 dfs0(11 u, 11 edge) { //mark bridges
    vis[u]=1;
    arr[u]=T++;
    11 dbe = arr[u];
    for(auto e : g[u]) {
        11 w = adj(u, e);
        if(!vis[w]) dbe = min(dbe, dfs0(w, e));
        else if(e!=edge) dbe = min(dbe, arr[w]);
    }
    if(dbe==arr[u] && edge!=-1) isbridge[edge]=true;
    else if(edge!=-1) merge(U[edge], V[edge]);
    return dbe;
}

```



```

}
void buildBridgeTree(ll n,ll m) {
    for(ll i=1; i<=n; i++) dsu[i]=i;
    for(ll i=1; i<=n; i++) if(!vis[i]) dfs0(i,-1);
    for(ll i=1; i<=m; i++)
        if(f(U[i])!=f(V[i])) {
            tree[f(U[i])].pb(f(V[i]));
            tree[f(V[i])].pb(f(U[i]));
        }
}
ll n,m;
for(i=1;i<=m;i++)
    cin>>U[i]>>V[i]; g[U[i]].pb(i); g[V[i]].pb(i);
buildBridgeTree(n,m);

```

### 5.3 Dominator Tree

```

/*g:adjacency matrix (directed graph).
tree rooted at node 1. call dominator().
tree: undirected graph of dominators rooted
at node 1 (use visit times while doing dfs)*/
const int N = int(2e5)+10;
vi g[N],tree[N],rg[N],bucket[N];
int sdом[N],par[N],dom[N],dsu[N],label[N];
int arr[N],rev[N],T;
int Find(int u,int x=0){
    if(u==dsu[u])return x?-1:u;
    int v = Find(dsu[u],x+1);
    if(v<0)return u;
    if(sdom[label[dsu[u]]] < sdom[label[u]])
        label[u] = label[dsu[u]];
    dsu[u] = v;
    return x?v:label[u];
}
void Union(int u,int v) {dsu[v]=u;}
void dfs0(int u){
    T++;arr[u]=T;rev[T]=u;
    label[T]=T;sdom[T]=T;dsu[T]=T;
    for(int i=0;i<g[u].size();i++){
        int w = g[u][i];
        if(!arr[w])dfs0(w),par[arr[w]]=arr[u];
        rg[arr[w]].pb(arr[u]);
    }
}
void dominator(){
    dfs0(1);int n=T;
    for(int i=n;i>=1;i--){
        for(int j=0;j<rg[i].size();j++)
            sdom[i] = min(sdom[i],sdom[Find(rg[i][j])]);
        if(i>1)bucket[sdom[i]].pb(i);
        for(int j=0;j<bucket[i].size();j++){
            int w = bucket[i][j];
            int v = Find(w);
            if(sdom[v]==sdom[w])dom[w]=sdom[w];
            else dom[w] = v;
        }
        if(i>1)Union(par[i],i);
    }
}

```

```

for(int i=2;i<=n;i++){
    if(dom[i]!=sdom[i]) dom[i]=dom[dom[i]];
    tree[rev[i]].pb(rev[dom[i]]);
    tree[rev[dom[i]]].pb(rev[i]);
}
}

```

### 5.4 Bridges Online

```

vector<int> par(MAX), dsu_2ecc(MAX), dsu_cc(MAX), ←
    dsu_cc_size(MAX);
int bridges,lca_iteration;
vector<int> last_visit(MAX);
void init(int n) {
    lca_iteration = 0;
    for (int i=0; i<n; ++i) {
        dsu_2ecc[i] = i; dsu_cc[i] = i;
        dsu_cc_size[i] = 1; par[i] = -1;
        last_visit[i]=0;
    } bridges = 0;
}
int find_2ecc(int v) { // 2-edge connected comp.
    if (v == -1) return -1;
    return dsu_2ecc[v] == v ? v : dsu_2ecc[v] = ←
        find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) { // connected comp.
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v : dsu_cc[v] = find_cc(←
        dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v);
    int root = v;int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]);
        par[v] = child; dsu_cc[v] = root;
        child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
vector<int> path_a, path_b;
void merge_path (int a, int b) {
    ++lca_iteration;
    int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a); path_a.push_back(a);
            if (last_visit[a] == lca_iteration) lca = a;
            last_visit[a] = lca_iteration; a=par[a];
        }
        if (b != -1) {
            b = find_2ecc(b); path_b.push_back(b);
            if (last_visit[b] == lca_iteration) lca = b;
            last_visit[b] = lca_iteration; b = par[b];
        }
    }
}

```

```

for (int v : path_a) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
for (int v : path_b) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
path_a.clear(); path_b.clear();
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;
    int ca = find_cc(a); int cb = find_cc(b);
    if (ca != cb) { ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b); swap(ca, cb); }
        make_root(a); par[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else { merge_path(a, b); }
}

```

## 5.5 HLD

```

/*v : adj matrix of tree.clear v[i],hdc[i]=0,i=-1 ←
before every run,clear ord and curc=0*/
vll v[MAX],ord;
ll par[MAX],noc[MAX],hdc[MAX],curc,posinch[MAX],←
len[MAX],ti=-1,sta[MAX],en[MAX],subs[MAX],level[←
MAX];
ll st[4*MAX],lazy[4*MAX],n;
void dfs(ll x){
    subs[x]=1;
    for(auto z:v[x]){
        if(z!=par[x]){par[z]=x;level[z]=level[x]+1;
            dfs(z);subs[x]+=subs[z];
        }}
void makehld(ll x){
    if(hdc[curc]==0){hdc[curc]=x;len[curc]=0;}
    noc[x]=curc;posinch[x]=++len[curc];
    ll a,b,c;a=b=0;ord.pb(x);sta[x]=++ti;
    for(auto z:v[x]){ if(z==par[x]) continue;
        if(subs[z]>b){b=subs[z];a=z;}
    }
    if(a!=0) makehld(a);
    for(auto z:v[x]){if(z==par[x]||z==a) continue;←
        curc++;makehld(z);}
    en[x]=ti;}
inline void upd(ll x,ll y){//update path a->b
    ll a,b,c,d;
    while(x!=y){a=hdc[noc[x]],b=hdc[noc[y]];
        if(a==b){
            if(level[x]>level[y]) swap(x,y);c=sta[x],d=←
            sta[y];
            //lca=a;
            update(1,0,n-1,c+1,d);return;}
        if(level[a]>level[b]) swap(a,b),swap(x,y);

```

```

//update on seg tree
update(1,0,n-1,sta[b],sta[y]);y=par[b];}}
int main(){
    loop: v[i].clear(),hdc[i]=0,ti=-1;
    ord.clear(),curc=0;
    level[1]=0;par[1]=0;curc=1;dfs(1);makehld(1);
    while(q--){cin>>a>>b;upd(a,b);ll ans=sumq(1,0,←
        n-1,0,n-1);}
}

```

## 5.6 LCA

```

int lca(int a,int b){
    if(level[a]>level[b]) swap(a,b);
    int d=level[b]-level[a];
    for(int i=0;i<LOGN;i++) if(d&(1<<i))
        b=DP[i][b];
    if(a==b) return a;
    for(int i=LOGN-1;i>=0;i--)
        if(DP[i][a]!=DP[i][b])
            a=DP[i][a],b=DP[i][b];
    return DP[0][a];}

```

## 5.7 Centroid Decomposition

```

/*nx:max nodes,par:parents of nodes in centroid ←
tree,timstamp: timestamps of nodes when they ←
became centroids,ssize,vis: subtree size and ←
visit times in dfs,tim: timestamp iterator
dist[nx]: dist[i][0][j]=no. of nodes at dist k in ←
subtree of i in centroid tree
dist[i][j][k]=no. of nodes at distance k in jth ←
child of i in centroid tree **(use adj while ←
doing dfs instead of adj1)**
preprocess: stores all values in dist array*/
const int nx=1e5;
vector<int> adj[nx],adj1[nx];
int par[nx],timstamp[nx],ssize[nx],vis[nx];
int tim=1;
vector<int> cntnorder;//centroids in order
vector<vector<int>> > dist[nx];
int dfs(int root){
    vis[root]=tim;
    int t=0;
    for(auto i:adj[root]){
        if(!timstamp[i]&&vis[i]<tim)t+=dfs(i);
        ssize[root]=t+1;return t+1;}
int dfs1(int root,int n){
    vis[root]=tim;pair<int,int> mxc={0,-1};
    bool poss=true;
    for(auto i:adj[root]){
        if(!timstamp[i]&&vis[i]<tim)
            poss&=(ssize[i]<=n/2),mxc=max(mxc,{ssize[i],←
            i});}
    if(poss&&(n-ssize[root])<=n/2) return root;
    return dfs1(mxc.second,n);}

```

```

int findc(int root){
    dfs(root);
    int n=ssize[root];tim++;
    return dfs1(root,n);}
void cntrdecom(int root,int p){
    int cntr=findc(root);
    cntrorder.pb(cntr);
    timstamp[cntr]=tim++;par[cntr]=p;
    if(p>=0)adj1[p].pb(cntr);
    for(auto i:adj[cntr])
        if(!timstamp[i])
            cntrdecom(i,cntr);}
void dfs2(int root,int nod,int j,int dst){
    if(dist[root][j].size()==dst)dist[root][j].pb(0)←;
    vis[nod]=tim;dist[root][j][dst]+=1;
    for(auto i:adj[nod]){
        if((timstamp[i]<=timstamp[root])||(vis[i]==vis[←
            nod]))continue;
        vis[i]=tim;dfs2(root,i,j,dst+1);}
}
void preprocess(){
    for(int i=0;i<cntrorder.size();i++){
        int root=cntrorder[i];
        vector<int> temp;
        dist[root].pb(temp);temp.pb(0);++tim;
        dfs2(root,root,0,0);
        int cnt=0;
        for(int j=0;j<adj[root].size();j++){
            int nod=adj[root][j];
            if(timstamp[nod]<timstamp[root])
                continue;
            dist[root].pb(temp);++tim;
            dfs2(root,nod,++cnt,1);}
    }
}

```

## 6 Maths

### 6.1 Inclusion-Exclusion

```

//inclusion exclusion on primes without ←
    calculating mobius
//pr is current product, sign is mobius value, i ←
    is index in list of primes
//p is list of primes under consideration
void rec(int i,int pr,int sign)
{
    int m=n/pr;
    ans+=sign*m;
    for(int j=i;j<L && p[j]<=m;j++)
        rec(j+1,pr*p[j],-sign);
}

```

### 6.2 Gaussian Elimination

```

// (1) solving systems of linear equations (AX=B←
// )
// (2) inverting matrices (AX=I)
// (3) computing determinants of square matrices
//
// O(n^3)
// INPUT:      a[][] = an nxn matrix
//              b[][] = an nxm matrix
//              A MUST BE INVERTIBLE!
//
// OUTPUT: X ← = an nxm matrix (stored in b[][][])
//           A^{-1} ← = an nxn matrix (stored in a[][][])
//           returns determinant of a[][]
const double EPS = 1e-10;
#define vld vector<ld>
#define vvld vector<vld>
ll GaussJordan(vvll &a, vvll &b) {
    const int n = a.size(), m = b[0].size();
    int n1 = a[0].size();
    vvll irow(n),icol(n),ipiv(n,0);ll det = 1;
    for(int i=0;i<n1;i++){
        int pj=-1,pk=-1;
        for(int j=0;j<n;j++){
            if(!ipiv[j])
                for(int k=0;k<n1;k++){
                    if(!ipiv[k])
                        if(pj==-1||fabs(a[j][k])>fabs(a[pj][pk]←
                            )){pj=j;pk=k;}
                }
        // if(fabs(a[pj][pk])<EPS){return 0;} // ←
        // uncomment in double version
        ipiv[pk]++;
        swap(a[pj],a[pk]);swap(b[pj],b[pk]);
        if(a[pk][pk]==0)return 0; // comment in ←
        // double version
        if(pj!=pk)det = mul(det,mod-1); // det*=-1;
        irow[i]=pj;icol[i]=pk;
        ll c=inv(a[pk][pk]);det = mul(det,a[pk][pk]);
        a[pk][pk]=1;
        for(int p=0;p<n1;p++) a[pk][p] = mul(a[pk][p],←
            c);
        for(int p=0;p<m;p++) b[pk][p] = mul(b[pk][p], ←
            c);
        for(int p=0;p<n;p++){
            if(p!=pk){
                c=a[p][pk];
                a[p][pk]=0;
                for(int q=0;q<n1;q++) a[p][q] = sub(a[p][q]←
                    ], mul(a[pk][q],c));
                for(int q=0;q<m;q++) b[p][q] = sub(b[p][q]←
                    ], mul(b[pk][q],c));
            }
        }
    }
}

```

```
// comment below if not square matrix .
for (int p=n-1;p>=0;p--)
    if(irow[p]!=icol[p]){
        for(int k=0;k<n;k++)
            swap(a[k][irow[p]],a[k][icol[p]]);
    }
return det;
}
```

### 6.3 Chinese Remainder Theorem

```
/*x=rem[i]%mods[i] for any mods
input: rem->remainder,mods->moduli
output: (x%lcm of mods,lcm),-1 if infeasible*/
ll LCM(ll a, ll b) { return a / __gcd(a, b) * b; }
ll normalize(ll x, ll mod)
{x %= mod; if (x < 0) x += mod; return x; }
struct GCD_type { ll x, y, d; };
GCD_type ex_GCD(ll a, ll b){
    if (b == 0) return {1, 0, a};
    GCD_type pom = ex_GCD(b, a % b);
    return {pom.y, pom.x - a / b * pom.y, pom.d};
}
pll CRT(vll &rem, vll &mods){
    ll n=rem.size(),ans=rem[0],lcm=mods[0];
    for(ll i=1;i<n;i++){
        auto pom=ex_GCD(lcm,mods[i]);
        ll x1=pom.x,d=pom.d;
        if((rem[i]-ans)%d!=0) return {-1,0};
        ans=normalize(ans+x1*(rem[i]-ans)/d%(mods[i]
            /d)*lcm,lcm*mods[i]/d);
        lcm=LCM(lcm,mods[i]); // you can save time
        by replacing above lcm * n[i] /d by lcm
        = lcm * n[i] / d}
    return {ans,lcm};
}
```

### 6.4 Discrete Log

```
/*Discrete Log , Baby-Step Giant-Step , e-maxx
The idea is to make two functions, f1(p) ,f2(q)
and find p,q s.t. f1(p) = f2(q) by storing all
possible values of f1, and checking for q. In
this case  $a^x = b \pmod m$  is solved by subst.
x by p.n-q , where n is choosen optimally.*/
/*returns a soln. for  $a^x = b \pmod m$  for
given a,b,m; -1 if no. soln; 0(sqrt(m).log(m))
use unordered_map to remove log factor.
IMP : works only if a,m are co-prime.
But can be modified.*/
int solve (int a, int b, int m) {
    int n = (int) sqrt (m + .0) + 1;
    int an = 1;
    for (int i=0; i<n; ++i)
        an = (an * a) % m;
    map<int,int> vals;
```

```
for (int i=1, cur=an; i<=n; ++i) {
    if (!vals.count(cur))
        vals[cur] = i;
    cur = (cur * an) % m;
}
for (int i=0, cur=b; i<=n; ++i) {
    if (vals.count(cur)) {
        int ans = vals[cur] * n - i;
        if (ans < m) return ans;
    }
    cur = (cur * a) % m;
}
return -1;
}
```

### 6.5 NTT

```
/*a*b%mod if a%mod*b%mod results in overflow:
ll mulmod(ll a, ll b, ll mod) {ll res = 0;
while (a!=0){if(a&1)(res+=b)%=mod;a>>=1;(b<=
    <=1)%=mod;}
return res;}
P=A*B A[0]=coeff of  $x^0$ 
x = a1 mod p1, x = a2 mod p2 => x=((a1*(m2^-1)%m1)
    *m2+(a2*(m1^-1)%m2)*m1)%m1m2
***max_base=x (s.t. if mod=c*(2^k)+1 then x<=k and
    2^x >= nearest power of 2 of 2*n)
root=primitive_root^((mod-1)/(2^max_base))
For P=A*A use square function
635437057,11|639631361,6|985661441&998244353,3*/
#define chinese(a1,m1,inv2m1,a2,m2,inv1m2) ((a1
    *1ll* inv2m1 % m1 * 1ll*m2 + a2 *1ll* inv1m2 %
    m2 * 1ll*m1) % (m1 *1ll* m2))
int mod;//reset mod everytime
int base = 1;
vll roots = {0, 1},rev = {0, 1};
int max_base=18,root=202376916;
void ensure_base(int nbase) {
    if (nbase <= base) return;
    rev.resize(1 << nbase);
    for (int i = 0; i < (1 << nbase); i++) {
        rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (
            nbase - 1));
    }
    roots.resize(1 << nbase);
    while (base < nbase) {
        int z = power(root, 1 << (max_base - 1 - base)
            );
        for (int i = 1 << (base - 1); i < (1 << base);
            i++) {
            roots[i << 1] = roots[i];
            roots[(i << 1) + 1] = mul(roots[i], z);
        }
        base++;
    }
}
void fft(vll &a) {
    int n = (int) a.size();
    int zeros = __builtin_ctz(n);
```

```

ensure_base(zeros);
int shift = base - zeros;
for (int i = 0; i < n; i++) {
    if (i < (rev[i] >> shift)) {
        swap(a[i], a[rev[i] >> shift]);
    }
}
for (int k = 1; k < n; k <= 1) {
    for (int i = 0; i < n; i += 2 * k) {
        for (int j = 0; j < k; j++) {
            int x = a[i + j];
            int y = mul(a[i + j + k], roots[j+k]);
            a[i + j] = x + y - mod;
            if (a[i + j] < 0) a[i + j] += mod;
            a[i + j + k] = x - y + mod;
            if (a[i+j+k]>=mod) a[i + j + k] -= mod;}
        }
}
vll multiply(vll a, vll b, int eq = 0) {
    int need = (int) (a.size() + b.size() - 1);
    int nbase = 0;
    while ((1 << nbase) < need) nbase++;
    ensure_base(nbase);
    int sz = 1 << nbase;
    a.resize(sz); b.resize(sz); fft(a);
    if (eq) b = a; else fft(b);
    int inv_sz = inv(sz);
    for (int i = 0; i < sz; i++)
        a[i] = mul(mul(a[i], b[i]), inv_sz);
    reverse(a.begin() + 1, a.end());
    fft(a); a.resize(need); return a;
}
vll square(vll a) {return multiply(a, a, 1);}

```

## 6.6 Online FFT

```

//f[i]=sum over j from 0 to i-1 f[j]*g[i-1-j]
//handle f[0] and g[0] separately
const int nx=131072; int f[nx], g[nx];
void onlinefft(int a, int b, int c, int d){
    vector<int> v1, v2;
    v1.pb(f+a, f+b+1); v2.pb(g+c, g+d+1); vector<int> ←
    res=multiply(v1, v2);
    for(int i=0; i<res.size(); i++)
        if(a+c+i+1<nx) f[a+c+i+1]=add(f[a+c+i+1], res[i←
        ]);
}
void precal(){
    g[0]=1;
    for(int i=1; i<nx; i++)
        g[i]=power(i, i-1);
    f[1]=1;
    for(int i=1; i<=100000; i++){
        f[i+1]=add(f[i+1], g[i]); f[i+1]=add(f[i+1], f[i←
        ]);
        f[i+2]=add(f[i+2], mul(f[i], g[1])); f[i+3]=add(f←
        [i+3], mul(f[i], g[2]));
    }
}

```

```

for(int j=2; i%j==0&&j<nx; j=j*2)
    onlinefft(i-j, i-1, j+1, 2*j);}
}

```

## 6.7 Lagrange Interpolation

```

/* Input :
Degree of polynomial: k
Polynomial values at x=0,1,2,3,...,k
Output :
Polynomial value at x
Complexity: O(degree of polynomial)
Works only if the points are equally spaced
*/
ll lagrange(vll& v, int k, ll x, int mod){
    if(x <= k) return v[x];
    ll inn = 1; ll den = 1;
    for(int i = 1; i <= k; i++){
        inn = (inn*(x - i))%mod;
        den = (den*(mod - i))%mod;
    }
    inn = (inn*inv(den % mod))%mod;
    ll ret = 0;
    for(int i = 0; i <= k; i++){
        ret = (ret + v[i]*inn)%mod;
        ll md1 = mod - ((x-i)*(k-i))%mod;
        ll md2 = ((i+1)*(x-i-1))%mod;
        if(i!=k)
            inn = (((inn*md1)%mod)*inv(md2 % mod))%mod←
    } return ret;
}

```

## 6.8 Matrix Struct

```

struct matrix{
    ld B[N][N], n;
    matrix(){n = N; memset(B, 0, sizeof B);}
    matrix(int _n)
        {n = _n; memset(B, 0, sizeof B);}
    void iden(){
        for(int i = 0; i < n; i++) B[i][i] = 1;}
    void operator += (matrix M){
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                B[i][j]=add(B[i][j], M.B[i][j]);}
    void operator -= (matrix M){}
    void operator *= (ld b){}
    matrix operator - (matrix M){}
    matrix operator + (matrix M){
        matrix ret = (*this); ret += M; return ret;}
    matrix operator * (matrix M){
        matrix ret = matrix(n); memset(ret.B, 0, ←
        sizeof ret.B);
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                for(int k = 0; k < n; k++)

```



```

        ret.B[i][j] = add(ret.B[i][j], mul(B[i][←
            k], M.B[k][j]));
    return ret;}
matrix operator *=(matrix M){*this=((*this)*M)←
};
matrix operator *(int b){
    matrix ret =(*this);ret *= b; return ret;}
vector<double> multiply(const vector<double> & v←
) const{
    vector<double> ret(n);
    for(int i = 0; i < n; i++)
        for(int j = 0; j < n; j++)
            ret[i] += B[i][j] * v[j];
    return ret;
}
};

```

## 6.9 nCr(Non Prime Modulo)

```

// calculates nCr, for small
// non-prime modulo, and (very) big n,r.
ll phimod;
vll pr,prn;vll fact;
ll power(ll a,ll x,ll mod){
    ll ans=1;
    while(x){
        if((1LL)&(x))ans=(ans*a)%mod;
        a=(a*a)%mod;x>>=1LL;
    }
    return ans;
}
// prime factorization of x.
// pr-> prime ; prn -> it's exponent
void getprime(ll x){
    pr.clear();prn.clear();
    ll i,j,k;
    for(i=2;(i*i)<=x;i++){
        k=0;while((x%i)==0){k++;x/=i;}
        if(k>0){pr.pb(i);prn.pb(k);}
    }
    if(x!=1){pr.pb(x);prn.pb(1);}
    return;
}
// factorials are calculated ignoring
// multiples of p.
void primeproc(ll p,ll pe){ // p , p^e
    ll i,d;
    fact.clear();fact.pb(1);d=1;
    for(i=1;i<pe;i++){
        if(i%p){fact.pb((fact[i-1]*i)%pe);}
        else {fact.pb(fact[i-1]);}
    }
    return;
}
// again note this has ignored multiples of p
ll Bigfact(ll n,ll mod){

```

```

    ll a,b,c,d,i,j,k;
    a=n/mod;a%=phimod;a=power(fact[mod-1],a,mod);
    b=n%mod;a=(a*fact[b])%mod;
    return a;
}
// Chinese Remainder Thm.
vll crtval,crtmod;
ll crt(vll &val,vll &mod){
    ll a,b,c,d,i,j,k;b=1;
    for(ll z:mod)b*=z;
    ll ans=0;
    for(i=0;i<mod.size();i++){
        a=mod[i];c=b/a;
        d=power(c,(((a/pr[i])*(pr[i]-1))-1),a);
        c=(c*d)%b;c=(c*val[i])%b;ans=(ans+c)%b;
    }
    return ans;
}
// calculate for prime powers and
// take crt. For each prime power,
// first ignore multiples of p,
// and then do recursively, calculating
// the powers of p separately.
ll Bigncr(ll n,ll r,ll mod){
    ll a,b,c,d,i,j,k;ll p,pe;
    getprime(mod);ll Fnum=1;ll Fden;
    crtval.clear();crtmod.clear();
    for(i=0;i<pr.size();i++){
        Fnum=1;Fden=1;
        p=pr[i];pe=power(p,prn[i],1e17);
        primeproc(p,pe);
        a=1;d=0;
        phimod=(pe*(p-1LL))/p;
        ll n1=n,r1=r,nr=n-r;
        while(n1){
            Fnum=(Fnum*(Bigfact(n1,pe)))%pe;
            Fden=(Fden*(Bigfact(r1,pe)))%pe;
            Fden=(Fden*(Bigfact(nr,pe)))%pe;
            d+=n1-(r1+nr);
            n1/=p;r1/=p;nr/=p;
        }
        Fnum=(Fnum*(power(Fden,(phimod-1LL),pe)))%pe;
        if(d>=prn[i])Fnum=0;
        else Fnum=(Fnum*(power(p,d,pe)))%pe;
        crtmod.pb(pe);crtval.pb(Fnum);
    }
    // you can just iterate instead of crt
    // for(i=0;i<mod;i++){
    //     bool cg=true;
    //     for(j=0;j<crtmod.size();j++){
    //         if(i%crtmod[j]!=crtval[j])cg=false;
    //     }
    //     if(cg)return i;
    // }
    return crt(crtval,crtmod);
}

```

```
}
```

## 6.10 Primitive Root Generator

```
/*To find generator of U(p), we check for all
g in [1,p]. But only for powers of the
form phi(p)/p_j, where p_j is a prime factor of
phi(p). Note that p is not prime here.
Existence, if one of these: 1. p = 1,2,4
2. p = q^k, where q -> odd prime.
3. p = 2.(q^k), where q -> odd prime
Note that a.g^(phi(p)) = 1 (mod p)
b. there are phi(phi(p)) generators if exists.
Finds "a" generator of U(p), multiplicative group
of integers mod p. Here calc_phi returns the
toitent
function for p. O(Ans.log(phi(p)).log(p)) +
time for factorizing phi(p). By some theorem,
Ans = O((log(p))^6). Should be fast generally.*/
int generator(int p) {
    vector<int> fact;
    int phi = calc_phi(p), n = phi;
    for (int i=2; i*i<=n; ++i)
        if (n % i == 0) {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }
    if (n > 1) fact.push_back(n);
    for (int res=2; res<=p; ++res) {
        if (gcd(res, p) != 1) continue;
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod(res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}
```

## 6.11 Math Miscellaneous

```
int gcd(int a, int b, int &x, int &y) {
    if (a == 0) {x = 0; y = 1; return b;}
    int x1, y1, d = gcd(b%a, a, x1, y1);
    x = y1 - (b / a) * x1; y = x1; return d;
}
int g(int n) {return n^(n >> 1);} //nth Gray code
int rev_g(int g) {//index of gray code g
    int n = 0; for (; g; g >= 1) n ^= g; return n;}
}
```

## 6.12 Group Theory

$x^2 = n \pmod{p}$ . Existence -  $n^{((p-1)/2)} == 1 \rightarrow$  there is a soln.,  
else == -1, no solution.  
Finding sqrt. in some  $\mathbb{Z} \pmod{p}$ :  
Cipollas Algorithm.

Find an 'a' (randomly), s.t.  $a^2 \pmod{p}$  doesn't have a sqrt.  
Adjoin it to the field. Take  $(a + \sqrt{a^2 - n})^{((p+1)/2)}$ .  
Do all operations mod p, ans will be integer.  
Cipollas Algo works only when mod is prime.  
[Remember  $(a+b)^p = a^p + b^p \pmod{p} = a + b \pmod{p}$ ]  
For non-prime:  
 $x^2 = n \pmod{m}$ .  
Soln.  $\rightarrow$  Compute it modulo prime powers and take CRT.  
For prime powers:  
We have a solution  $x_0 \pmod{p}$ . We use it to find a solution  $\pmod{p^2}$ ,  
then  $\pmod{p^3}$  and so on. For  $p^2$ :  $x^2 = n \pmod{p^2}$ ;  
We want x to reduce to  $x_0 \pmod{p}$ . So  $x = x_0 + p \cdot x_1$ . Square it.  $x_0^2 + 2 \cdot x_0 \cdot x_1 = n \pmod{p^2}$ .  
Calculate  $x_1$ . This can be extended to find greater powers of p.  
But the inverse may not exist always which may give a problem.  
But then no solution or all solutions. This is called Hensel's Lifting.  
This can also be extended to find  $f(x) = 0 \pmod{p^2}$ , if we have a soln. for  $f(x) = 0 \pmod{p}$ . Get something in  $f'(x)$

## 7 Strings

### 7.1 Hashing Theory

If order not imp. and count/frequency imp. use this as hash fn:-  
 $((a_1+h)^k + (a_2+h)^k + (a_3+h)^k + (a_4+h)^k) \% p$ . Select: h, k, p  
Alternate:  
 $((x)^{(a_1)} + (x)^{(a_2)} + \dots + (x)^{(a_k)}) \% \text{mod}$  where x and mod are fixed and  $a_1 \dots a_k$  is an unordered set

### 7.2 Manacher

```
/*Same idea as Z_fn, O(n)
[l,r]: rightmost detected subpalindrom (with max r)
len of odd length palindrom centered around that
char (e.g abac for 'b' returns 2(not 3))*/
vll manacher_odd(string s) {
    ll n = s.length(); vll d1(n);
    for (ll i = 0, l = 0, r = -1; i < n; i++) {
        d1[i] = 1;
        if (i <= r) { // use prev val
            d1[i] = min(r-i+1, d1[l+r-i]);
        }
        while (i+d1[i] < n && i-d1[i] >= 0 && s[i+d1[i]] == s[i-d1[i]])
            d1[i]++; // trivial matching
    }
}
```

```

    if(r < i+d1[i]-1) l=i-d1[i]+1, r=i+d1[i]-1;
}
return d1;}
//even lens centered around (bb is centered around←
the later 'b')
vll manacher_even(string s){
    ll n = s.length(); vll d2(n);
    for(ll i = 0, l = 0, r = -1; i<n; i++){
        d2[i] = 0;
        if(i <= r){
            d2[i] = min(r-i+1, d2[l+r+1-i]);}
        while(i+d2[i] < n && i-d2[i]-1 >= 0 && s[i+d2[i]←
            i]] == s[i-d2[i]-1]) d2[i]++;
        if(d2[i] > 0 && r < i+d2[i]-1)
            l=i-d2[i], r=i+d2[i]-1;
    }
    return d2;
}
// Other mtd : To do both things in one pass,
// add special char e.g string "abc" => "$a$b$c$"

```

### 7.3 Trie

```

const ll AS = 26; // alphabet size
ll go[MAX][AS]; ll cnt[MAX]; ll cn=0;
// cn -> index of next new node
// convert all strings to vll
ll newNode() {
    for(ll i=0; i<AS; i++)
        go[cn][i]=-1;
    return cn++;
}
// call newNode once **** before adding anything ←
**
void addTrie(vll &x) {
    ll v = 0;
    cnt[v]++;
    for(ll i=0; i<x.size(); i++){
        ll y=x[i];
        if(go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
        cnt[v]++;
    }
}
// returns count of substrings with prefix x
ll getcount(vll &x){
    ll v=0;
    for(i=0; i<x.size(); i++){
        ll y=x[i];
        if(go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
    }
    return cnt[v];
}

```

### 7.4 Z-algorithm

```

/*[l,r]->rightmost segment match(with max r)
Time : O(n)(asy. behavior), Proof:each itr of
inner while loop make r pointer advance to right,
App:1)Search substring(text t,pat p)s=p+ '$' + t.
3) String compression(s=t+t+...+t, then find |t|)
2) Number of distinct substrings (in O(n^2))
(useful when appending or deleting characters
online from the end or beginning)*/
vector<ll> z_function(string s) {
    ll n = (ll) s.length();
    vector<ll> z(n);
    for (ll i=1, L=0, R=0; i<n; ++i) {
        if (i <= R) // use previous z val
            z[i] = min (R - i + 1, z[i - L]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            ++z[i]; // trivial matching
        if (i + z[i] - 1 > R) L = i, R = i + z[i] - 1;
        // update rightmost segment matched
    }
    return z;
}

```

### 7.5 Aho Corasick

```

const int K = 26;
// remember to set K
struct Vertex {
    int next[K]; bool leaf = false;
    int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};
vector<Vertex> aho(1);
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (aho[v].next[c] == -1) {
            aho[v].next[c] = aho.size();
            aho.emplace_back(v, ch);
        }
        v = aho[v].next[c];
    }
    aho[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (aho[v].link == -1) {
        if (v==0 || aho[v].p==0) aho[v].link = 0;
        else aho[v].link =
            go(get_link(aho[v].p), aho[v].pch);
    }
}

```

```

    return aho[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (aho[v].go[c] == -1) {
        if (aho[v].next[c] != -1)
            aho[v].go[c] = aho[v].next[c];
        else
            aho[v].go[c] = v == 0 ? 0 : go(get_link(v), ←
                ch);
    }
    return aho[v].go[c];
}

```

## 7.6 KMP

```

/*Time:O(n)(j increases n times(& j>=0) only so
asy. O(n)), pi[i] = length of longest prefix of
s ending at i
app.: search substring,
# of different substrings(O(n^2)),
3) String compression(s = t+t+...+t,
then find |t|, k=n-pi[n-1],if k|n)
4) Building Automaton(Gray Code Example)*/
vector<ll> prefix_function(string s) {
    ll n = (ll)s.length(); vll pi(n);
    for (ll i = 1; i < n; i++) {
        ll j = pi[i-1];
        while (j > 0 && s[i] != s[j]) j = pi[j-1];
        if (s[i] == s[j]) j++;
        pi[i] = j;
    }
    return pi;
}
//searching s in t, returns all occurrences(indices
vector<ll> search(string s,string t){
    vll pi = prefix_function(s);
    ll m = s.length(); vll ans; ll j = 0;
    for(ll i=0;i<t.length();i++){
        while(j > 0 && t[i] != s[j])
            j = pi[j-1];
        if(t[i] == s[j]) j++;
        if(j == m) ans.pb(i-m+1);
    } // if ans empty then no occurrence
    return ans;
}

```

## 7.7 Palindrome Tree

```

const ll MAX=1e5+15;
ll par[MAX]; // stores index of parent node
ll sul_i[MAX]; // stores index of suffix link
ll len[MAX]; /* stores len of largest
pallindrome ending at that node */
ll child[MAX][30]; // stores the children of the ←
node
/*-----

```

```

index 0 - root "-1"
index 1 - root "0"
therefore node of s[i] is i+2
initialize all child[i][j] to -1
-----<
*/
void eer_tree(string s){
    ll a,b,c,d,i,j,k,e,f;
    sul_i[1]=0;sul_i[0]=0;len[1]=0;len[0]=-1;
    ll n=s.length();
    for(i=0;i<n+10;i++){
        for(j=0;j<30;j++) child[i][j]=-1;
        ll cur=1;d=1;
        for(i=0;i<s.size();i++){
            ++d;
            while(true){
                a=i-1-len[cur];
                if(a>=0){
                    if(s[a]==s[i]){
                        if(child[cur][(ll)(s[i]-'a')]==-1){
                            par[d]=cur;child[cur][(ll)(s[i]-'a')]=←
                                d;
                            len[d]=len[cur]+2;cur=d;
                        }
                        else{
                            par[d]=cur;len[d]=len[cur]+2;
                            cur=child[cur][(ll)(s[i]-'a')]];
                        }
                        break;
                    }
                }
                if(cur==0) break;
                cur=sul_i[cur];
            }
            if(cur!=d) continue;
            if(len[d]==1) sul_i[d]=1;
            else{
                c=sul_i[par[d]];
                while(child[c][(ll)(s[i]-'a')]==-1){
                    if(c==0) break;
                    c=sul_i[c];
                }
                sul_i[d]=child[c][(ll)(s[i]-'a')]];
            }
        }
    }
}

```

## 7.8 Suffix Array

```

/*Sorted array of suffixes = sorted array of ←
cyclic
shifts of string+$. We consider a prefix of len. 2^←
k
of the cyclic, in the kth iteration.String of len.
2^k->combination of 2 strings of len. 2^(k-1), ←
whose
order we know, from previous iteration. Just radix
sort on pair for next iteration.

```

```

Time :- O(nlog(n) + alphabet). Applications :-
Finding the smallest cyclic shift; Finding a ←
substring
in a string; Comparing two substrings of a string;
Longest common prefix of two substrings; Number of
different substrings. */
//returns permutation of indices in sorted order ←
***
vector<ll> sort_cyclic_shifts(string const& s) {
    ll n = s.size();
    const ll alphabet = 256;
    //change the alphabet size accordingly and ←
    indexing
    vector<ll> p(n), c(n), cnt(max(alphabet, n), 0);
    // p:sorted ord. of 1-len prefix of each cyclic
    // shift index. c:class of a index
    // pn:same as p for kth iteration . ||ly cn.
    for (ll i = 0; i < n; i++)
        cnt[s[i]]++;
    for (ll i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (ll i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    ll classes = 1;
    for (ll i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
        c[p[i]] = classes - 1;
    }
    vector<ll> pn(n), cn(n);
    for (ll h = 0; (1 << h) < n; ++h) {
        for (ll i = 0; i < n; i++) { //sorting w.r.t
            pn[i] = p[i] - (1 << h); //second part.
            if (pn[i] < 0)
                pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (ll i = 0; i < n; i++)
            cnt[c[pn[i]]]++;
        for (ll i = 1; i < classes; i++)
            cnt[i] += cnt[i-1];
        // sorting w.r.t. 1st(more significant) part
        for (ll i = n-1; i >= 0; i--)
            p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0; classes = 1;
        // determining new classes in sorted array.
        for (ll i = 1; i < n; i++) {
            pll cur={c[p[i]],c[(p[i]+(1<<h))%n]};
            pll prev={c[p[i-1]],c[(p[i-1]+(1<<h))%n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}

```

```

}
vector<ll> suffix_array_construction(string s) {
    s += "$";
    vector<ll> sorted_shifts = sort_cyclic_shifts(s)←
    ;
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts; }
// For comp. two substr. of len. l starting at i,j←
// k - 2^k > 1/2. check the first 2^k part, if ←
equal,
// check last 2^k part. c[k] is the c in kth iter
//of S.A construction.
int compare(int i, int j, int l, int k) {
    pll a = {c[k][i],c[k][(i+1-(1 << k))%n]};
    pll b = {c[k][j],c[k][(j+1-(1 << k))%n]};
    return a == b ? 0 : a < b ? -1 : 1; }
/*lcp[i]=len. of lcp of ith & (i+1)th suffix in ←
the SA
1. Consider suffixes in decreasing order of length.
2. Let p = s[i....n]. It will be somewhere in the S←
.A.
We determine its lcp = k. 3. Then lcp of q=s[(i+1)←
.n]
will be atleast k-1 coz 4.remove the first char of←
p
and its successor in the S.A. These are suffixes ←
with
lcp k-1. 5. But note that these 2 may not be ←
consecutive
in S.A. But lcp of str. in b/w have to be also >= k←
-1.*/
vll lcp_cons(string const& s, vector<ll> const& p)←
{
    ll n = s.size();
    vector<ll> rank(n, 0);
    for (ll i = 0; i < n; i++)
        rank[p[i]] = i;
    ll k = 0; vector<ll> lcp(n-1, 0);
    for (ll i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0; continue; }
        ll j = p[rank[i] + 1];
        while(i+k < n && j+k < n && s[i+k] == s[j+k]) k++;
        lcp[rank[i]] = k; if (k) k--; }
    return lcp;
}

```

## 7.9 Suffix Tree

```

const int N=1000000, // set it more than 2*(len. ←
of string)
string str; // input string for which the suffix ←
tree is being built
int chi[N][26],
lef[N], // left...

```



```

rig[N], // ...and right boundaries of the ←
        substring of a which correspond to incoming edge
par[N], // parent of the node
sfli[N], // suffix link
tv, tp, la,
ts; // the number of nodes
void ukkadd(int c) {
    suff++;
    if (rig[tp] < tv) {
        if (chi[tp][c] == -1) { chi[tp][c] = ts; lef[ts] = la;
            par[ts++] = tv; tv = sfli[tp]; tp = rig[tp] + 1; goto ←
            suff; }
        tv = chi[tp][c]; tp = lef[tp];
    }
    if (tp == -1 || c == str[tp] - 'a') tp++;
    else {
        lef[ts] = lef[tp]; rig[ts] = tp - 1; par[ts] = par[tp] ←
        ];
        chi[ts][str[tp] - 'a'] = tv; chi[ts][c] = ts + 1;
        lef[ts + 1] = la; par[ts + 1] = ts; lef[tp] = tp; par[tp] ←
        ] = ts;
        chi[par[ts]][str[lef[ts]] - 'a'] = ts; ts += 2;
        tv = sfli[par[ts - 2]]; tp = lef[ts - 2];
        while (tp <= rig[ts - 2]) {
            tv = chi[tp][str[tp] - 'a']; tp += rig[tp] - lef[tp] ←
            ] + 1; }
        if (tp == rig[ts - 2] + 1) sfli[ts - 2] = tv; else ←
            sfli[ts - 2] = ts;
        tp = rig[tp] - (tp - rig[ts - 2]) + 2; goto suff;
    }
}
void build() {
    ts = 2; tv = 0; tp = 0;
    ll ss = str.size(); ss *= 2; ss += 15;
    fill(rig, rig + ss, (int)str.size() - 1);
    // initialize data for the root of the tree
    sfli[0] = 1; lef[0] = -1; rig[0] = -1;
    lef[1] = -1; rig[1] = -1; for (ll i = 0; i < ss; i++)
    fill(chi[i], chi[i] + 27, -1);
    fill(chi[1], chi[1] + 26, 0);
    // add the text to the tree, letter by letter
    for (la = 0; la < (int)str.size(); ++la)
    ukkadd(str[la] - 'a');
}

```

## 7.10 Suffix Automaton

```

struct state {
    int len, link;
    map<char, int> next;
};
const int MAXLEN = 200005;
state st[MAXLEN];
int sz, last;
void sa_init() {

```

```

    st[0].len = 0;
    st[0].link = -1;
    sz++;
    last = 0;
}
void sa_extend(char c) {
    int cur = sz++;
    st[cur].len = st[last].len + 1;
    int p = last;
    while (p != -1 && !st[p].next.count(c)) {
        st[p].next[c] = cur;
        p = st[p].link;
    }
    if (p == -1) {
        st[cur].link = 0;
    } else {
        int q = st[p].next[c];
        if (st[p].len + 1 == st[q].len) {
            st[cur].link = q;
        } else {
            int clone = sz++;
            st[clone].len = st[p].len + 1;
            st[clone].next = st[q].next;
            st[clone].link = st[q].link;
            while (p != -1 && st[p].next[c] == q) {
                st[p].next[c] = clone;
                p = st[p].link;
            }
            st[q].link = st[cur].link = clone;
        }
    }
    last = cur;
}
void build(string &x) {
    sz = 0;
    for (ll i = 0; i < 3 * x.length() + 15; i++)
    {
        st[i].next.clear();
        st[i].len = 0; st[i].link = 0;
    }
    sa_init();
    for (ll i = 0; i < x.size(); i++) sa_extend(x[i]);
}

```

## Möbius Function

$$\mu(n) = \begin{cases} 0 & n \text{ not squarefree} \\ 1 & n \text{ squarefree w/ even no. of prime factors} \\ -1 & n \text{ squarefree w/ odd no. of prime factors} \end{cases}$$

Note that  $\mu(a)\mu(b) = \mu(ab)$  for  $a, b$  relatively prime

$$\text{Also } \sum_{d|n} \mu(d) = \begin{cases} 1 & \text{if } n = 1 \\ 0 & \text{otherwise} \end{cases}$$

**Möbius Inversion** If  $g(n) = \sum_{d|n} f(d)$  for all  $n \geq 1$ , then  $f(n) = \sum_{d|n} \mu(d)g(n/d)$  for all  $n \geq 1$ .

### Burnside's Lemma (Text)

The number of orbits of a set  $X$  under the group action  $G$  equals the average number of elements of  $X$  fixed by the elements of  $G$ .

Here's an example. Consider a square of  $2n$  times  $2n$  cells. How many ways are there to color it into  $X$  colors, up to rotations and/or reflections? Here, the group has only 8 elements (rotations by 0, 90, 180 and 270 degrees, reflections over two diagonals, over a vertical line and over a horizontal line). Every coloring stays itself after rotating by 0 degrees, so that rotation has  $X^{4n^2}$  fixed points. Rotation by 180 degrees and reflections over a horizontal/vertical line split all cells in pairs that must be of the same color for a coloring to be unaffected by such rotation/reflection, thus there exist  $X^{2n^2}$  such colorings for each of them. Rotations by 90 and 270 degrees split cells in groups of four, thus yielding  $X^{n^2}$  fixed colorings. Reflections over diagonals split cells into  $2n$  groups of 1 (the diagonal itself) and  $2n^2 - n$  groups of 2 (all remaining cells), thus yielding  $X^{2n^2 - n + 2n} = X^{2n^2 + n}$  unaffected colorings. So, the answer is  $(X^{4n^2} + 3X^{2n^2} + 2X^{n^2} + 2X^{2n^2 + n})/8$ . Every tree with  $n$  vertices has  $n - 1$  edges.

### Trees-Kraft inequality:

If the depths of the leaves of a binary tree are  $d_1 \dots d_n$ :  $\sum_{i=1}^n 2^{-d_i} \leq 1$ , and equality holds only if every internal node has 2 sons.

### Euler Tour:

- Undirected graph iff All vertices have even degree, all non-zero degree vertices are in a single connected component.(Can be decomposed into edge-disjoint cycles)
- Directed graph iff For each vertex in-degree=out-degree, all non-zero degree vertices are in a single strongly connected component.(Decomposable into directed-edge disjoint cycles)

### Euler Trail:

- Undirected graph iff exactly 0 or 2 vertices have odd degree, single connected component(consider zero degree vertices only).
- Directed graph iff at most one vertex has (out-degree)-(in-degree) = 1, at most one vertex has (in-degree)-(out-degree) = 1, every other vertex has equal in-degree and out-degree, and all of its vertices with nonzero degree belong to a single connected component of the underlying undirected graph.

### Master method:

$$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$$

If  $\exists \epsilon > 0$  such that  $f(n) = O(n^{\log_b a - \epsilon})$  then  $T(n) = \Theta(n^{\log_b a})$ .

If  $f(n) = \Theta(n^{\log_b a})$  then  $T(n) = \Theta(n^{\log_b a} \log_2 n)$ .

If  $\exists \epsilon > 0$  such that  $f(n) = \Omega(n^{\log_b a + \epsilon})$ , and  $\exists c < 1$  such that  $af(n/b) \leq cf(n)$  for large  $n$ , then  $T(n) = \Theta(f(n))$ .

### Probability:

Variance, standard deviation:  $Var[X] = E[X^2] - E[X]^2$

Poisson distribution:

Normal (Gaussian) distribution:

$$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda \quad \left| \quad p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$$

The "coupon collector": We are given a random coupon each day, and there are  $n$  different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all  $n$  types is  $nH_n$ .

### Miscellaneous:

1. Radius of inscribed circle for Right Angle Triangle:  $\frac{AB}{A+B+C}$
2. Law of cosine:  $c^2 = a^2 + b^2 - 2ab \cos C$
3. Area of a triangle: Area:  $A = \frac{1}{2}hc = \frac{1}{2}ab \sin C = \frac{c^2 \sin A \sin B}{2 \sin C}$ .
4.  $\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i, \pi(i)}$ , for Permanents remove sign.
5. Perfect Numbers:  $x$  is an even perfect number iff  $x = 2^{n-1}(2^n - 1)$  and  $2^n - 1$  is prime.
6. Wilson's theorem:  $n$  is a prime iff  $(n-1)! \equiv -1 \pmod n$ .
7. If graph  $G$  is planar then  $n - m + f = 2$ , so  $f \leq 2n - 4$ ,  $m \leq 3n - 6$ . Any planar graph has a vertex with degree  $\leq 5$ .
8. Dirichlet power series:  $A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}$
9. Coefficient of  $x^r$  in  $(1-x)^{-n}$  is  $\binom{n+r-1}{r}$ .

### For Bipartite Graphs

1. Min-edge cover( $me$ ) = Max-independent set( $mi$ ) ( $G$  has no isolated vertex).
2. Min-vertex cover( $mv$ ) = Max matching( $mm$ )  $mi + mv = |V|$ ,  $mi \geq \frac{|V|}{2}$
3. Min-edge cover subgraph is a combination of star graphs.
4. Min Vertex cover : In residual graph of max flow pick all the vertices in L(left bipartite) not reachable from  $s$ (whose edges are cut) and lly in R reachable from  $s$ .
5. Min-edge cover(no isolated vertex) : Find max matching, take all those edges, for vertices not covered take any edge.

$$\frac{x}{(1-x)^2} = \sum_{i=0}^{\infty} ix^i, \quad \ln(1+x) = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, \quad \frac{x}{1-x-x^2} = \sum_{i=0}^{\infty} F_i x^i$$

$$(x_1 + x_2 + \dots + x_k)^n = \sum_{c_1 + c_2 + \dots + c_k = n} \frac{n!}{c_1! c_2! \dots c_k!} x_1^{c_1} x_2^{c_2} \dots x_k^{c_k}$$

$$\int \tanh x dx = \ln |\cosh x|, \quad \int \coth x dx = \ln |\sinh x|, \quad \int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln \left| \frac{a+x}{a-x} \right|,$$

$$\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln \left( x + \sqrt{a^2 + x^2} \right) \quad (a > 0), \quad \int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a} \quad (a > 0),$$

$$\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a} \quad (a > 0)$$

$$\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a} \quad (a > 0)$$

### Fibonacci:

1.  $F_{-i} = (-1)^{i-1} F_i$ ,  $F_i = \frac{1}{\sqrt{5}} (\phi^i - \hat{\phi}^i)$
2. Cassini's identity:  $F_{i+1} F_{i-1} - F_i^2 = (-1)^i$  for  $i > 0$ ,
3. Additive Rule:  $F_{n+k} = F_k F_{n+1} + F_{k-1} F_n$ ,  $F_{2n} = F_n F_{n+1} + F_{n-1} F_n$
4. Every integer  $n$  has a unique representation  $n = F_{k_1} + F_{k_2} + \dots + F_{k_m}$ , where  $k_i \geq k_{i+1} + 2$  for  $1 \leq i < m$  and  $k_m \geq 2$ .

### Primes

$\forall(a, b)$ , The largest prime smaller than  $10^a$  is  $p = 10^a - b$

(1,3), (2,3), (3,3), (4,27), (5,9), (6,17), (7,9), (8,11), (9,63), (10,33),

(11,23), (12,11), (13,29), (14,27), (15,11), (16,63), (17,3), (18,11)

### Ideas

Div and Conq, Brute force and observe, (+1,-1), Dominator Tree for Directed Graph, use fenwick, Monte Carlo, Summation Interchange, Clever Optimization of brute force(binary search/ignore)

### C++ Sublime Build Extra

```
{
"cmd" : ["g++ -std=c++11 $file_name -o ↵
    $file_base_name && timeout 4s ./$file_base_name<↵
    input.txt>output.txt"],
"selector" : "source.c",
"shell" : true,
"working_dir" : "$file_path"
}
```