

Codebook- Team Far Behind

IIT Delhi, India

Ayush Ranjan, Naman Jain, Manish Tanwar

Contents

1 Syntax

- 1.1 Template 1
- 1.2 C++ Sublime Build 2

2 Data Structures

- 2.1 Fenwick 3
- 2.2 2D-BIT 3
- 2.3 Segment Tree 3
- 2.4 Persistent Segment Tree 3
- 2.5 DP Optimization 4

3 Flows and Matching

- 3.1 General Matching 5
- 3.2 Global Mincut 5
- 3.3 Hopcroft Matching 6
- 3.4 Dinic 6
- 3.5 Ford Fulkerson 7
- 3.6 MCMF 8
- 3.7 MinCost Matching 8

4 Geometry

- 4.1 Geometry 9
- 4.2 Convex Hull 11
- 4.3 Convex Hull Trick 12

5 Trees

- 5.1 BlockCut Tree 13
- 5.2 Dominator Tree 13
- 5.3 Bridges Online 14
- 5.4 HLD 14
- 5.5 LCA 15
- 5.6 Centroid Decomposition 15

6 Maths

- 6.1 Chinese Remainder Theorem 15
- 6.2 Discrete Log 16
- 6.3 NTT 16
- 6.4 Online FFT 17
- 6.5 Langrange Interpolation 17

- 6.6 Matrix Struct 17
- 6.7 nCr(Non Prime Modulo) 17
- 6.8 Primitive Root Generator 18
- 6.9 Group Theory 19

7 Strings

- 7.1 Hashing Theory 19
- 7.2 Manacher 19
- 7.3 Trie 19
- 7.4 Z-algorithm 20
- 7.5 Aho Corasick 20
- 7.6 KMP 20
- 7.7 Palindrome Tree 21
- 7.8 Suffix Array 21
- 7.9 Suffix Tree 22

1 Syntax

1.1 Template

```
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
using namespace std;
template<class T> ostream& operator<<(ostream &os, const
vector<T> &V) {
os << "["; for(auto v : V) os << v << " ";
return os << "];"}
template<class L, class R> ostream& operator<<(ostream &os, pair<L,R> P) {
return os << "(" << P.first << "," << P.second <<
"<< ")]";}
#define TRACE
#ifdef TRACE
#define trace(...) _f(#__VA_ARGS__, __VA_ARGS__)
template<typename Arg1>
void _f(const char* name, Arg1&& arg1){
cout << name << " : " << arg1 << endl;
}
template<typename Arg1, typename... Args>
void _f(const char* names, Arg1&& arg1, Args&&... args){
const char* comma = strchr(names + 1, ',');cout <<
write(names, comma - names) << " : " << arg1<<
" | ";_f(comma+1, args...);
}
```

```

#else
#define trace(...) 1
#endif
#define ll long long
#define ld long double
#define vll vector<ll>
#define pll pair<ll,ll>
#define vpll vector<pll>
#define I insert
#define pb push_back
#define F first
#define S second
#define all(x) x.begin(),x.end()
#define endl "\n"
// const ll MAX=1e6+5;
// int mod=1e9+7;
inline int mul(int a,int b){return (a*1ll*b)%mod;}
inline int add(int a,int b){a+=b;if(a>=mod)a-=mod;
return a;}
inline int sub(int a,int b){a-=b;if(a<0)a+=mod;
return a;}
inline int power(int a,int b){int rt=1;while(b>0){
if(b&1)rt=mul(rt,a);a=mul(a,a);b>>=1;}return rt}
inline int inv(int a){return power(a,mod-2);}
inline void modadd(int &a,int b){a+=b;if(a>=mod)a
-=mod;}
int main(){
ios_base::sync_with_stdio(false);cin.tie(0);cout
.tie(0);cout<<setprecision(25);
}
// clock
clock_t clk = clock();
clk = clock() - clk;
((ld)clk)/CLOCKS_PER_SEC
// fastio
inline ll read() {
ll n = 0; char c = getchar_unlocked();
while (!( '0' <= c && c <= '9' )) c =
getchar_unlocked();
while ( '0' <= c && c <= '9' )
n = n * 10 + c - '0', c = getchar_unlocked
();
return n;
}
inline void write(ll a){
register char c; char snum[20]; ll i=0;
do{
snum[i++]=a%10+48;
a=a/10;
}while(a!=0); i--;
while(i>=0)
putchar_unlocked(snum[i--]);
putchar_unlocked('\n');
}
using getline, use cin.ignore()
// gp_hash_table

```

```

#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
gp_hash_table<int, int> table; //cc_hash_table ←
can also be used
//custom hash function
const int RANDOM = chrono::high_resolution_clock::
now().time_since_epoch().count();
struct chash {
int operator()(int x) { return hash<int>{}(x ^
RANDOM); }
};
gp_hash_table<int, int, chash> table;
//custom hash function for pair
struct chash {
int operator()(pair<int,int> x) const { return
x.first* 31 + x.second; }
};
// random
mt19937 rng(chrono::steady_clock::now().
time_since_epoch().count());
uniform_int_distribution<int> uid(1,r);
int x=uid(rng);
//mt19937_64 rng(chrono::steady_clock::now().
time_since_epoch().count());
// - for 64 bit unsigned numbers
vector<int> per(N);
for (int i = 0; i < N; i++)
per[i] = i;
shuffle(per.begin(), per.end(), rng);
// string splitting
// this splitting is better than custom function(w
.r.t time)
string line = "Ge";
vector <string> tokens;
stringstream check1(line);
string ele;
// Tokenizing w.r.t. space ' '
while(getline(check1, ele, ' '))
tokens.push_back(ele);

```

1.2 C++ Sublime Build

```

{
"cmd": ["bash", "-c", "g++ -std=c++11 -O3 '${
file}' -o '${file_path}/${file_base_name}' &&
gnome-terminal -- bash -c '\"${file_path}/${
file_base_name}\" < input.txt >output.txt' "
],
"file_regex": "^(...[^:]*):([0-9]+):?([0-9]+)??:?
(.*?)$",
"working_dir": "${file_path}",
"selector": "source.c++, source.cpp",
}

```

2 Data Structures

2.1 Fenwick

```
/*All indices are 1 indexed
*Range update and point query: maintain BIT of ←
prefix sum of updates
-add val in [a,b] -> add val at a,-val at b
-value[a]=BITsum(a)+arr[a]
*Range update ,range query: maintain 2 BITs B1,B2
-add val in [a,b] -> B1:add val at a,-val at b+1 ←
and in B2 -> Add val*(a-1) at a, -val*b at b+1
-sum[1,b]=B1sum(1,b)*b-B2sum(1,b)
-sum[a,b]=sum[1,b]-sum[1,a-1]*/
ll fen[MAX_N];
void update(ll p,ll val){
    for(ll i = p;i <= n;i += i & -i)
        fen[i] += val;}
ll sum(ll p){
    ll ans = 0;
    for(ll i = p;i; i -= i & -i) ans += fen[i];
    return ans;}
```

2.2 2D-BIT

```
/*All indices are 1 indexed.Increment value of ←
cell (i,j) by val -> update(x,y,val)
*sum of rectangle [a,b]-[c,d] ->sum of rectangles ←
[1,1]-[c,d],[1,1]-[c,b],[1,1][a,d] and [1,1]-[a,←
b] and use inclusion exclusion*/
ll bit[MAX][MAX];
void update(ll x , ll y, ll val){
    while( x < MAX ){
        ll y1 = y;
        while( y1 < MAX )
            bit[x][y1]+=val , y1 += ( y1 & -y1 );
        x += ( x & -x);}
}
ll sum(ll x , ll y){
    ll ans = 0;
    while( x > 0 ){
        ll y1 = y;
        while( y1 > 0 )
            ans+=bit[x][y1] , y1 -= ( y1 & -y1 );
        x -= ( x & -x);}
    return ans;}
```

2.3 Segment Tree

```
/*All arrays are 0 indexed. call bld(0,n-1,1)
upd(0,n-1,1,x,y,val) -> increase [x,y] by val
sum(0,n-1,1,x,y) -> sum [x,y]
array of size N -> segment tree of size 4*N*/
ll arr[N],st[N<<2], lz[N<<2];
void ppgt(ll l, ll r,ll id){
    if(l==r) return;
    ll m=l+r>>1;
```

```
lz[id*2]+=lz[id];lz[id<<1|1]+=lz[id];
st[id << 1] += (m - l + 1) * lz[id];
st[id<<1|1]+=(r-m)*lz[id];lz[id] = 0;}
void bld(ll l,ll r,ll id){
    if(l==r) { st[id] = arr[l]; return; }
    bld(l,l+r>>1,id*2);bld(l+r+1>>1,r,id*2+1);
    st[id] = st[id << 1] + st[id << 1 | 1];}
void upd(ll l,ll r,ll id,ll x,ll y,ll val){
    if (l > y || r < x ) return;ppgt(l, r, id);
    if (l >= x && r <= y ) {
        lz[id]+=val;st[id]+=(r-l+1)*val; return;}
    upd(l,l + r >> 1,id << 1, x, y, val);upd((l + r <←
        >> 1) + 1,r ,id << 1 | 1,x, y, val);
    st[id] = st[id << 1] + st[id << 1 | 1];}
ll sum(ll l,ll r,ll id,ll x,ll y){
    if (l > y || r < x ) return 0;ppgt(l, r, id);
    if (l >= x && r <= y ) return st[id];
    return sum(l, l + r >> 1,id << 1, x, y) + sum((l <←
        + r >> 1) + 1,r ,id << 1 | 1,x, y);}
```

2.4 Persistent Segment Tree

```
/*id of first node = 0. call build(0,n-1) first. ←
afterwards call upd(0,n-1,previous id,i,val) to ←
add val in ith number. It returns root of new ←
segment tree after modification
*sum(0,n-1,id of root,l,r) -> sum of values in ←
subarray l to r in tree rooted at id
**size of st,lc,rc >= N*2+(N+Q)*logN*/
const ll N=1e5+10;
ll arr[N],st[20*N],lc[20*N],rc[20*N],ids[N],cnt;
void build(ll l,ll r){
    if(l==r) {st[cnt]=arr[l];++cnt;return;}
    ll id = cnt++;lc[id] = cnt;
    build( l, l+r >>1);
    rc[id] = cnt; build( (l + r >> 1) + 1, r);
    st[id] = st[lc[id]] + st[rc[id]];}
ll upd(ll l,ll r,ll id,ll x,ll val){
    if(l == r)
        {st[cnt]=st[id]+val;++cnt;return cnt-1;}
    ll myid = cnt++; ll mid = l + r >>1;
    if(x <= mid)
        rc[myid] = rc[id],lc[myid] = upd(l, mid, lc[id]←
            , x, val);
    else
        lc[myid] = lc[id],rc[myid] = upd(mid+1, r, rc[←
            id], x, val);
    st[myid] = st[lc[myid]] + st[rc[myid]];
    return myid;}
ll sum(ll l,ll r,ll id,ll x,ll y){
    if (l > y || r < x ) return 0;
    if (l >= x && r <= y ) return st[id];
    return sum(l, l + r >> 1,lc[id], x, y) + sum((l <←
        + r >> 1) + 1,r ,rc[id],x, y);}
ll gkth(ll l,ll r,ll id1,ll id2,ll k){
    if(l==r) return l;ll mid = l+r>>1;
```

```

11 a=st[lc[id2]]-(id1>=0?st[lc[id1]]:0);
if(a >= k)
    return gkth(1, mid, (id1>=0?lc[id1]:-1), lc[id2], k);
else
    return gkth(mid+1, r, (id1>=0?rc[id1]:-1), rc[id2], k-a);}
//kth largest num in range
int main(){
    ll n,m;vll finalid(n);vpll v;
    loop : v.pb({arr[i],i});sort(all(v));
    loop : finalid[v[i].second]=i;
    memset(arr,0,sizeof(ll)*N);
    arr[finalid[0]]++;build(0,n-1);
    loop:ids[i]=upd(0,n-1,ids[i-1],finalid[i],1);
    while(m--){
        ll i,j,k;cin>>i>>j>>k;--i;--j;
        ans=gkth(0,n-1,(i==0?-1:ids[i-1]),ids[j],k);
        cout<<v[ans].F<<endl;}
}

```

2.5 DP Optimization

/*Split L size array into G intervals, minimizing the cost ($G \leq L$). The cost func. $C[i,j]$ satisfies: $C[a,b]+C[c,d] \leq C[a,d]+C[c,b]$ for $a \leq c \leq b \leq d$. (Q.E) & intuitively you can think that the c.f increases at a rate which is more than linear at all intervals. So, if the c.f. satisfies Q.E., the following holds:

$F(g,l)$: min cost of splitting first l into g ivalds.
 $F(g,l)$: $\min(F(g-1,k)+C(k+1,l))$ over all valid k.
 $P(g,l)$: lowest position k s.t. it minimizes $F(g,l)$
 $P(g,0) \leq P(g,1) \leq \dots \leq P(g,l)$; DivConq, $O(G.L.\log(L))$
 $P(0,1) \leq P(1,1) \leq P(2,1) \dots \leq P(G-1,1) \leq P(G,1)$.
 Knuth Opti, complexity $O(L.L)$.
 For div&conq, we calculate $P(g,l)$ for each g 1 by 1.
 In each g, we calculate for mid-l and do recursively using the obtained upper and lower bounds. For knuth, we use $P(g,l-1) \leq P(g,l) \leq P(g+1,l)$, and fill our table in increasing l and decreasing g. In opt. BST type problems, use $bk[i][j-1] \leq bk[i][j] \leq bk[i+1][j]$ */

// Code for Divide and Conquer Opti $O(G.L.\log(L))$:

```

11 C[8111]; ll sums[8111];
11 F[811][8111]; // optimal value
int P[811][8111]; // optimal position.
// note first val. in arrays is for no. of groups
11 cost(int i, int j) { // cost function
    return i > j ? 0 : (sums[j]-sums[i-1])*(j-i+1);
}

```

```

}
/*fill(g,l1,l2,p1,p2) calcs. P[g][l1] and F[g][l1]
for
11 l1<=l2, with the knowledge that p1<=P[g][l1]<=p2
*/
void fill(int g, int l1, int l2, int p1, int p2) {
    if (l1 > l2) return; int lm = (l1 + l2) >> 1;
    ll nv=INF, nv1=-1;
    for (int k = p1; k <= min(lm-1,p2); k++) {
        ll new_cost = F[g-1][k] + cost[k+1][lm];
        if (nv > new_cost) { nv=new_cost; nv1 = k; }
    }
    P[g][lm]=nv1; F[g][lm]=nv;
    fill(g, l1, lm-1, p1, P[g][lm]);
    fill(g, lm+1, l2, P[g][lm], p2);
}
int main() { // example call
    for(i=0;i<=n;i++)F[0][i]=INF;
    for(i=0;i<=k;i++)F[i][0]=0;
    F[0][0]=0;
    for(i=1;i<=k;i++)fill(i,1,n,0,n);
}
// Code for Knuth Optimization  $O(L.L)$  :-
11 dp[8002][802];
int a[8002],s[8002][802];
11 sum[8002];
// index strats from 1
11 run(int n,int m) {
    memset(dp,0xff,sizeof(dp)); dp[0][0] = 0;
    for (int i = 1; i <= n; ++i) {
        sum[i] = sum[i-1] + a[i];
        int maxj = min(i, m), mk; ll mn = INF;
        for (int k = 0; k < i; ++k) {
            if (dp[k][maxj-1] >= 0) {
                ll tmp = dp[k][maxj-1] +
                    (sum[i] - sum[k]) * (i - k);
                if (tmp < mn) {
                    mn = tmp; mk = k; }
            }
        }
        dp[i][maxj] = mn; s[i][maxj] = mk;
        for (int j = maxj-1; j >= 1; --j) {
            ll mn = INF; int mk;
            for (ll k=s[i-1][j]; k<=s[i][j+1];++k){
                if (dp[k][j-1] >= 0) {
                    ll tmp = dp[k][j-1] + (sum[i]-sum[k])*(i-
                        k);
                    if (tmp < mn) {mn = tmp;mk = k;} }
                }
            dp[i][j] = mn; s[i][j] = mk;
        }
    } return dp[n][m];
}
// call -> run(n, min(n,m))

```

3 Flows and Matching

3.1 General Matching

```
/*Given any directed graph, finds maximal matching
Vertices-0-indexed, O(n^3) per call to edmonds*/
vll adj[MAXN]; int p[MAXN], base[MAXN], match[MAXN];
int lca(int n, int u, int v){
    vector<bool> used(n);
    for (;;){
        u = base[u]; used[u] = true;
        if (match[u] == -1) break; u = p[match[u]];
    }
    for (;;){
        v = base[v]; if (used[v]) return v;
        v = p[match[v]];
    }
}
void mark_path(vector<bool> &blo, int u, int b, int child){
    for (; base[u] != b; u = p[match[u]]){
        blo[base[u]] = true; blo[base[match[u]]] = true;
        p[u] = child; child = match[u];
    }
}
int find_path(int n, int root) {
    vector<bool> used(n);
    for (int i = 0; i < n; ++i)
        p[i] = -1, base[i] = i;
    used[root] = true;
    queue<int> q; q.push(root);
    while(!q.empty()) {
        int u = q.front(); q.pop();
        for (int j = 0; j < (int)adj[u].size(); j++) {
            int v = adj[u][j];
            if (base[u] == base[v] || match[u] == v) continue;
            if (v == root || (match[v] != -1 && p[match[v]] != -1)){
                int curr_base = lca(n, u, v);
                vector<bool> blossom(n);
                mark_path(blossom, u, curr_base, v);
                mark_path(blossom, v, curr_base, u);
                for (int i = 0; i < n; i++){
                    if (blossom[base[i]]){
                        base[i] = curr_base;
                        if (!used[i]) used[i] = true, q.push(i);
                    }
                }
            }
            else if (p[v] == -1){
                p[v] = u;
                if (match[v] == -1) return v;
                v = match[v]; used[v] = true; q.push(v);
            }
        }
    }
    return -1;
}
int edmonds(int n){
    for (int i = 0; i < n; i++) match[i] = -1;
```

```
for (int i = 0; i < n; i++){
    if (match[i] == -1) {
        int u, pu, ppu;
        for (u = find_path(n, i); u != -1; u = ppu) {
            pu = p[u]; ppu = match[pu];
            match[u] = pu; match[pu] = u;
        }
    }
}
int matches = 0;
for (int i = 0; i < n; i++)
    if (match[i] != -1) matches++;
return matches/2;
}
u--; v--; adj[u].pb(v); adj[v].pb(u);
cout << edmonds(n) * 2 << endl;
for (int i = 0; i < n; i++) {
    if (match[i] != -1 && i < match[i]) {
        cout << i + 1 << " " << match[i] + 1 << " ";
    }
}
}
```

3.2 Global Mincut

```
/*finds min weighted cut in undirected graph in
O(n^3), Adj Matrix, 0-indexed vertices
output-(min cut value, nodes in half of min cut)*/
typedef vector<int> VI;
typedef vector<VI> VVI;
const int INF = 1000000000;
pair<int, VI> GetMinCut(VVI &weights) {
    int N = weights.size();
    VI used(N), cut, best_cut;
    int best_weight = -1;
    for (int phase = N-1; phase >= 0; phase--) {
        VI w = weights[0];
        VI added = used;
        int prev, last = 0;
        for (int i = 0; i < phase; i++) {
            prev = last; last = -1;
            for (int j = 1; j < N; j++)
                if (!added[j] && (last == -1 || w[j] > w[last]))
                    last = j;
            if (i == phase-1) {
                for (int j = 0; j < N; j++)
                    weights[prev][j] += weights[last][j];
                for (int j = 0; j < N; j++)
                    weights[j][prev] = weights[prev][j];
                used[last] = true; cut.push_back(last);
                if (best_weight == -1 || w[last] < best_weight)
                    best_cut = cut, best_weight = w[last];
            }
        }
    }
}
```



```

    else {
        for (int j = 0; j < N; j++)
            w[j] += weights[last][j];
        added[last] = true;
    }
}
return make_pair(best_weight, best_cut);
}
VVI weights(n, VI(n));
pair<int, VI> res = GetMinCut(weights);

```

3.3 Hopcroft Matching

```

// O(m * \sqrt{n})
struct graph {
    int L, R; // 0-indexed vertices
    vector<vector<int>> adj;
    graph(int L, int R) : L(L), R(R), adj(L+R) {}
    void add_edge(int u, int v) {
        adj[u].pb(v+L); adj[v+L].pb(u);
    }
    int maximum_matching() {
        vector<int> level(L), mate(L+R, -1);
        function<bool(void)> levelize = [&]() { // BFS
            queue<int> Q;
            for (int u = 0; u < L; ++u) {
                level[u] = -1;
                if (mate[u] < 0) level[u] = 0, Q.push(u);
            }
            while (!Q.empty()) {
                int u = Q.front(); Q.pop();
                for (int w: adj[u]) {
                    int v = mate[w];
                    if (v < 0) return true;
                    if (level[v] < 0)
                        level[v] = level[u] + 1, Q.push(v);
                }
            }
            return false;
        };
        function<bool(int)> augment = [&](int u) { // ←
            DFS
            for (int w: adj[u]) {
                int v = mate[w];
                if (v < 0 || (level[v] > level[u] && augment(v) ←
                )) {
                    mate[u] = w; mate[w] = u; return true;
                }
            }
            return false;
        };
        int match = 0;
        while (levelize())
            for (int u = 0; u < L; ++u)
                if (mate[u] < 0 && augment(u)) ++match;
        return match;
    }
}

```

```

}; // L-left size, R->right size
graph g(L,R); g.add_edge(u,v); g.maximum_matching←
();

```

3.4 Dinic

```

/*O(min(fm,mn^2)), for any unit capacity network
O(m*sqrt(n)), in practice it is pretty fast for ←
any
bipartite network, **vertices are 1-indexed**
e=(u,v), e.flow represent effective flow from u to←
v
(i.e f(u->v) - f(v->u))
*use int if possible(ll could be slow in dinic)*/
struct edge {ll x, y, cap, flow;};
struct DinicFlow {
    // *** change inf accordingly *****
    const ll inf = (1e18);
    vector<edge> e; vll cur, d;
    vector<vll> adj; ll n, source, sink;
    DinicFlow() {}
    DinicFlow(ll v) {
        n = v; cur = vll(n+1);
        d = vll(n+1); adj = vector<vll>(n+1);
    }
    void addEdge(ll from, ll to, ll cap) {
        edge e1 = {from, to, cap, 0};
        edge e2 = {to, from, 0, 0};
        adj[from].pb(e1.size()); e.pb(e1);
        adj[to].pb(e2.size()); e.pb(e2);
    }
    ll bfs() {
        queue<ll> q;
        for(ll i = 0; i <= n; ++i) d[i] = -1;
        q.push(source); d[source] = 0;
        while(!q.empty() and d[sink] < 0) {
            ll x = q.front(); q.pop();
            for(ll i = 0; i < (ll)adj[x].size(); ++i){
                ll id = adj[x][i], y = e[id].y;
                if(d[y]<0 and e[id].flow < e[id].cap){
                    q.push(y); d[y] = d[x] + 1;
                }
            }
        }
        return d[sink] >= 0;
    }
    ll dfs(ll x, ll flow) {
        if(!flow) return 0;
        if(x == sink) return flow;
        for(; cur[x] < (ll)adj[x].size(); ++cur[x]) {
            ll id = adj[x][cur[x]], y = e[id].y;
            if(d[y] != d[x] + 1) continue;
            ll pushe=dfs(y,min(flow,e[id].cap-e[id].flow←
            ));
            if(pushed) {

```



```

        que.push(e.dst);
    }
}
}
for(int i=0;i<n;i++) p[i] = dist[i];
continue; // added last 2 lines
} else { // use Dijkstra
typedef pair<cost_type, int> node;
priority_queue<node, vector<node>, greater<node>> > que;
que.push({0, s});
while (!que.empty()) {
    node a = que.top(); que.pop();
    if (a.S == t) break;
    if (dist[a.S] > a.F) continue;
    for (auto e: adj[a.S]) {
        if (e.cap > e.flow && dist[e.dst] > a.F + rcost(e)) {
            dist[e.dst] = dist[e.src] + rcost(e);
            prev[e.dst] = e.rev;
            que.push({dist[e.dst], e.dst});
        }
    }
}
if (prev[t] == -1) break;
for (int u = 0; u < n; ++u)
    if (dist[u] < dist[t]) p[u] += dist[u] - dist[t];
function<flow_type(int, flow_type)> augment = [&](int u, flow_type cur) {
    if (u == s) return cur;
    edge &r = adj[u][prev[u]], &e = adj[r.dst][r.rev];
    flow_type f = augment(e.src, min(e.cap - e.flow, cur));
    e.flow += f; r.flow -= f;
    return f;
};
flow_type f = augment(t, INF);
flow += f;
cost += f * (p[t] - p[s]);
}
return {flow, cost};
};

```

3.7 MinCost Matching

/*O(n³) solves 1000x1000 problems in around 1s
cost[i][j] = cost for pairing Li with Rj
Lmate[i]=index of R node that L node i pairs with
Rmate[j]=index of L node that R node j pairs with
cost[i][j] may be +ve or -ve. To perform
maximization, simply negate the cost[][] matrix.*/

```

typedef ll cost_type;
typedef vector<cost_type> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;
cost_type MCM(const VVD &cost, VI &Lmate, VI &Rmate) {
    int n = cost.size(); VD u(n), v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost[i][j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost[i][j] - u[i]);
    }
    Lmate = VI(n, -1); Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
                //**** change this comparision if double cost ****
                Lmate[i]=j; Rmate[j]=i; mated++; break;
            }
        }
    }
    VD dist(n); VI dad(n); VI seen(n);
    while (mated < n) {
        int s = 0;
        while (Lmate[s] != -1) s++;
        fill(dad.begin(), dad.end(), -1);
        fill(seen.begin(), seen.end(), 0);
        for (int k = 0; k < n; k++)
            dist[k] = cost[s][k] - u[s] - v[k];
        int j = 0;
        while (true) {
            j = -1;
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                if (j == -1 || dist[k] < dist[j]) j = k;
            }
            seen[j] = 1;
            if (Rmate[j] == -1) break;
            const int i = Rmate[j];
            for (int k = 0; k < n; k++) {
                if (seen[k]) continue;
                const cost_type new_dist = dist[j] + cost[i][k] - u[i] - v[k];
                if (dist[k] > new_dist) {
                    dist[k] = new_dist;
                    dad[k] = j;
                }
            }
        }
    }
}

```



```

}
for (int k = 0; k < n; k++) {
    if (k == j || !seen[k]) continue;
    const int i = Rmate[k];
    v[k] += dist[k]-dist[j];
    u[i] -= dist[k]-dist[j];
    u[s] += dist[j];
    while (dad[j] >= 0) {
        const int d = dad[j];
        Rmate[j]=Rmate[d]; Lmate[Rmate[j]]=j; j=d;
        Rmate[j] = s; Lmate[s] = j; mated++;
    }
    cost_type value = 0;
    for (int i = 0; i < n; i++)
        value += cost[i][Lmate[i]];
    return value;
}

```

4 Geometry

4.1 Geometry

```

//do not read input in double format
#define PI acos(-1)
//atan2(y,x) slope of line (0,0)->(x,y) in radian ←
(-PI,PI]
// to convert to degree multiply by 180/PI
ld INF = 1e100;
ld EPS = 1e-9;
inline bool eq(ld a,ld b) {return fabs(a-b)<EPS;}
inline bool lt(ld a,ld b) {return a+EPS<b;}
inline bool gt(ld a,ld b) {return a>b+EPS;}
inline bool le(ld a,ld b) {return lt(a,b)||eq(a,b)←
;}
inline bool ge(ld a,ld b) {return gt(a,b)||eq(a,b)←
;}
struct pt {
    ld x, y;
    pt() {}
    pt(ld x, ld y) : x(x), y(y) {}
    pt(const pt &p) : x(p.x), y(p.y) {}
    pt operator + (const pt &p)
    const { return pt(x+p.x, y+p.y); }
    pt operator - (const pt &p)
    const { return pt(x-p.x, y-p.y); }
    pt operator * (ld c)
    const { return pt(x*c, y*c ); }
    pt operator / (ld c)
    const { return pt(x/c, y/c ); }
    bool operator < (const pt &p)
    const {return lt(y,p.y)|| (eq(y,p.y)&&ltlt(x,p.x))←
;}
    bool operator > (const pt &p)
    const{ return p<pt(x,y);}
    bool operator <= (const pt &p)

```

```

const{ return !(pt(x,y)>p);}
bool operator >= (const pt &p)
const{ return !(pt(x,y)<p);}
bool operator == (const pt &p)
const{ return (pt(x,y)<=p)&&(pt(x,y)>=p);}
};
ld dot(pt p,pt q) {return p.x*q.x+p.y*q.y;}
ld dist2(pt p, pt q) {return dot(p-q,p-q);}
ld dist(pt p,pt q) {return sqrt(dist2(p,q));}
ld norm2(pt p) {return dot(p,p);}
ld norm(pt p) {return sqrt(norm2(p));}
ld cross(pt p, pt q) { return p.x*q.y-p.y*q.x;}
ostream &operator<<(ostream &os, const pt &p) {
    return os << "(" << p.x << "," << p.y << ")"; }
istream& operator >> (istream &is, pt &p){
    return is >> p.x >> p.y;}
//returns 0 if a,b,c are collinear,1 if a->b->c is←
cw and -1 if ccw
int orient(pt a,pt b,pt c)
{
    pt p=b-a,q=c-b;double cr=cross(p,q);
    if(eq(cr,0))return 0;if(lt(cr,0))return 1;return←
-1;}
// rotate a point CCW or CW around the origin
pt RotateCCW90(pt p) { return pt(-p.y,p.x); }
pt RotateCW90(pt p) { return pt(p.y,-p.x); }
pt RotateCCW(pt p, ld t) { //rotate by t degree ccw
return pt(p.x*cos(t)-p.y*sin(t), p.x*sin(t)+p.y*←
cos(t)); }
// project point c onto line (not segment) through←
a and b assuming a != b
pt ProjectPointLine(pt a, pt b, pt c) {
    return a + (b-a)*dot(c-a, b-a)/dot(b-a, b-a);}
// project point c onto line segment through a and←
b (closest point on line segment)
pt ProjectPointSegment(pt a, pt b, pt c) {
    ld r = dot(b-a,b-a); if (eq(r,0)) return a; //a ←
and b are same
    r = dot(c-a, b-a)/r;if (lt(r,0)) return a; //c on←
left of a
    if (gt(r,1)) return b; return a + (b-a)*r;}
// compute dist from c to segment between a and b
ld DistancePointSegment(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointSegment(a, b, c)←
));}
// compute dist from c to line between a and b
ld DistancePointLine(pt a, pt b, pt c) {
    return sqrt(dist2(c, ProjectPointLine(a, b, c)))←
;}
// determine if lines from a to b and c to d are ←
parallel or collinear
bool LinesParallel(pt a, pt b, pt c, pt d) {
    return eq(cross(b-a, c-d),0); }

```

```

bool LinesCollinear(pt a, pt b, pt c, pt d) {
    return LinesParallel(a, b, c, d) && eq(cross(a-b,
    , a-c),0) && eq(cross(c-d, c-a),0);}
// determine if line segment from a to b
// intersects with line segment from c to d
bool SegmentsIntersect(pt a, pt b, pt c, pt d) {
    if (LinesCollinear(a, b, c, d)) {
        //a->b and c->d are collinear and have one
        // point common
        if(eq(dist2(a,c),0)||eq(dist2(a,d),0)||eq(
        dist2(b,c),0)||eq(dist2(b,d),0))
            return true;
        if(gt(dot(c-a,c-b),0)&&gt;(dot(d-a,d-b),0)&&gt;(
        dot(c-b,d-b),0)) return false;
        return true;
    }
    if(gt(cross(d-a,b-a)*cross(c-a,b-a),0)) return
    false; //c,d on same side of a,b
    if(gt(cross(a-c,d-c)*cross(b-c,d-c),0))
        return false; //a,b on same side of c,d
    return true;
}
// compute intersection of line passing through a
// and b
// with line passing through c and d, assuming that
// **unique** intersection exists;
// *for segment intersection, check if segments
// intersect first
pt ComputeLineIntersection(pt a,pt b,pt c,pt d){
    b=b-a;d=c-d;c=c-a; //lines must not be collinear
    assert(gt(dot(b, b),0)&&gt;(dot(d, d),0));
    return a + b*cross(c, d)/cross(b, d);}
//returns true if point a,b,c are collinear and b
// lies between a and c
bool between(pt a,pt b,pt c){
    if(!eq(cross(b-a,c-b),0))return 0; //not
    // collinear
    return le(dot(b-a,b-c),0);
}
//compute intersection of line segment a-b and c-d
pt ComputeSegmentIntersection(pt a,pt b,pt c,pt d){
    {
        if(!SegmentsIntersect(a,b,c,d))return {INF,INF};
        //don't intersect
        //if collinear then infinite intersection points
        // , this returns any one
        if(LinesCollinear(a,b,c,d)){if(between(a,c,b))
            return c;if(between(c,a,d))return a;return b;}
        return ComputeLineIntersection(a,b,c,d);
    }
}
// compute center of circle given three points - *
// a,b,c shouldn't be collinear
pt ComputeCircleCenter(pt a,pt b,pt c){
    b=(a+b)/2;c=(a+c)/2;
    return ComputeLineIntersection(b,b+RotateCW90(a-
    b),c,c+RotateCW90(a-c));}
//point in polygon using winding number -> returns
// 0 if point is outside

```

```

//winding number>0 if point is inside and equal to
// 0 if outside
//draw a ray to the right and add 1 if side goes
// from up to down and -1 otherwise
bool PointInPolygon(const vector<pt> &p,pt q){
    int n=p.size(),windingNumber=0;
    for(int i=0;i<n;++i){
        if(eq(dist2(q,p[i]),0)) return 1; //q is a
        // vertex
        int j=(i+1)%n;
        if(eq(p[i].y,q.y)&&eq(p[j].y,q.y)) { //i,i+1
        // vertex is vertical
        if(le(min(p[i].x,p[j].x),q.x)&&le(q.x,max(p[
        i].x, p[j].x))) return 1; } //q lies on
        // boundary
        else {
            bool below=lt(p[i].y,q.y);
            if(below!=lt(p[j].y,q.y)) {
                auto orientation=orient(q,p[j],p[i]);
                if(orientation==0) return 1; //q lies on
                // boundary i->j
                if(below==(orientation>0)) windingNumber+=
                below?1:-1; } } }
    return windingNumber==0?0:1;
}
// determine if point is on the boundary of a
// polygon
bool PointOnPolygon(const vector<pt> &p,pt q) {
    for (int i = 0; i < p.size(); i++)
        if (eq(dist2(ProjectPointSegment(p[i],p[(i+1)%
        p.size()],q),q),0)) return true;
    return false;
}
// Compute area or centroid of any polygon (
// coordinates must be listed in cw/ccw
// fashion.The centroid is often known as center of
// gravity/mass
ld ComputeSignedArea(const vector<pt> &p) {
    ld ans=0;
    for(int i = 0; i < p.size(); i++) {
        int j = (i+1) % p.size();
        ans+=cross(p[i],p[j]);
    } return ans / 2.0;}
ld ComputeArea(const vector<pt> &p) {
    return fabs(ComputeSignedArea(p));
}
// compute intersection of line through points a
// and b with
// circle centered at c with radius r > 0
vector<pt> CircleLineIntersection(pt a, pt b, pt c
    , ld r) {
    vector<pt> ret;
    b = b-a;a = a-c;
    ld A = dot(b, b),B = dot(a, b),C = dot(a, a) - r
    *r,D = B*B - A*C;
    if (lt(D,0)) return ret; //don't intersect

```

```

ret.push_back(c+a+b*(-B+sqrt(D+EPS))/A);
if (gt(D,0)) ret.push_back(c+a+b*(-B-sqrt(D))/A)←
;
return ret;}
// compute intersection of circle centered at a ←
// with radius r
// with circle centered at b with radius R
vector<pt> CircleCircleIntersection(pt a, pt b, ld←
r, ld R) {
vector<pt> ret;
ld d = sqrt(dist2(a, b)),d1=dist2(a,b);
pt inf(INF,INF);
if(eq(d1,0)&&eq(r,R)){ret.pb(inf);return ret;}//←
// circles are same return (INF,INF)
if(gt(d,r+R) || lt(d+min(r, R),max(r, R)) ) ←
return ret;
ld x = (d*d-R*R+r*r)/(2*d),y = sqrt(r*r-x*x);
pt v = (b-a)/d;
ret.push_back(a+v*x + RotateCCW90(v)*y);
if (gt(y,0)) ret.push_back(a+v*x - RotateCCW90(v←
)*y);
return ret;}
//compute centroid of simple polygon by dividing ←
// it into disjoint triangles
//and taking weighted mean of their centroids (←
//Jerome)
pt ComputeCentroid(const vector<pt> &p) {
pt c(0,0),inf(INF,INF);
ld scale = 6.0 * ComputeSignedArea(p);
if(p.empty())return inf;//empty vector
if(eq(scale,0))return inf;//all points on ←
//straight line
for (int i = 0; i < p.size(); i++){
int j = (i+1) % p.size();
c = c + (p[i]+p[j])*cross(p[i],p[j]);}
return c / scale;}
// tests whether or not a given polygon (in CW or ←
// CCW order) is simple
bool IsSimple(const vector<pt> &p) {
for (int i = 0; i < p.size(); i++) {
for (int k = i+1; k < p.size(); k++) {
int j = (i+1) % p.size();
int l = (k+1) % p.size();
if (i == 1 || j == k) continue;
if (SegmentsIntersect(p[i], p[j], p[k], p[l]←
))
return false;}}
return true;}
/*point in convex polygon
****bottom left point must be at index 0 and top ←
// is the index of upper right vertex
****if not call make_hull once*/
bool pointinConvexPolygon(vector<pt> poly,pt point←
, int top) {

```

```

if (point < poly[0] || point > poly[top]) return←
0;//0 for outside and 1 for on/inside
auto orientation = orient(point, poly[top], poly←
[0]);
if (orientation == 0) {
if (point == poly[0] || point == poly[top]) ←
return 1;
return top == 1 || top + 1 == poly.size() ? 1 ←
: 1;//checks if point lies on boundary when
//bottom and top points are adjacent
} else if (orientation < 0) {
auto itRight = lower_bound(poly.begin() + 1, ←
poly.begin() + top, point);
return orient(itRight[0], point, itRight[-1])←
<=0;
} else {
auto itLeft = upper_bound(poly.rbegin(), poly.←
rend() - top-1, point);
return (orient(itLeft == poly.rbegin() ? poly←
[0] : itLeft[-1], point, itLeft[0]))<=0;
}
}
/*maximum distance between two points in convexy ←
// polygon using rotating calipers
// make sure that polygon is convex. if not call ←
// make_hull first*/
ld maxDist2(vector<pt> poly) {
int n = poly.size();
ld res=0;
for (int i = 0, j = n < 2 ? 0 : 1; i < j; ++i)
for (; j = j+1 % n) {
res = max(res, dist2(poly[i], poly[j]));
if (gt(cross(poly[j+1 % n] - poly[j],poly[i]←
+1 - poly[i]),0)) break;
}
return res;
}
//Line polygon intersection: check if given line ←
// intersects any side of polygon
//if yes then line intersects. If no, then check ←
// if its midpoint is inside polygon
//if midpoint is inside then line is inside else ←
// outside
// compute distance between point (x,y,z) and ←
// plane ax+by+cz=d
ld DistancePointPlane(ld x,ld y,ld z,ld a,ld b,ld ←
c,ld d)
{ return fabs(a*x+b*y+c*z-d)/sqrt(a*a+b*b+c*c);}

```

4.2 Convex Hull

```

pt firstpoint;
//for sorting points in ccw(counter clockwise) ←
// direction w.r.t firstpoint (leftmost and ←
// bottommost)

```

```

bool compare(pt x,pt y){
    ll o=orient(firstpoint,x,y);
    if(o==0)return lt(x.x+x.y,y.x+y.y);
    return o<0;}
/*poi->input points, hull->empty vector
returns hull in ccw order with min points*/
void make_hull(vector<pt>& poi,vector<pt>& hull){
    pair<ld,ld> bl={INF,INF};
    ll n=poi.size();ll ind;
    for(ll i=0;i<n;i++){
        pair<ld,ld> pp={poi[i].y,poi[i].x};
        if(pp<bl){
            ind=i;bl={poi[i].y,poi[i].x};}
    }
    swap(bl.F,bl.S);firstpoint=pt(bl.F,bl.S);
    vector<pt> cons;
    for(ll i=0;i<n;i++){
        if(i==ind)continue;cons.pb(poi[i]);}
    sort(cons.begin(),cons.end(),compare);
    hull.pb(firstpoint);ll m;
    for(auto z:cons){
        if(hull.size()<=1){hull.pb(z);continue;}
        pt pr,ppr;bool fl=true;
        while((m=hull.size())>=2){
            pr=hull[m-1];ppr=hull[m-2];
            ll ch=orient(ppr,pr,z);
            if(ch==-1){break;}
            else if(ch==1){hull.pop_back();continue;}
            else {
                ld d1,d2;
                d1=dist2(ppr,pr);d2=dist2(ppr,z);
                if(gt(d1,d2)){fl=false;break;}else {hull.←
                    pop_back();}
            }
        }
        if(fl){hull.push_back(z);}
    }
    return;
}

```

4.3 Convex Hull Trick

```

/*maintains upper convex hull of lines ax+b and ←
gives minimum value at a given x
to add line ax+b: sameoldcht.addline(a,b), to get ←
min value at x: sameoldcht.getbest(x)
to get maximum value at x add -ax-b as lines ←
instead of ax+b and use -sameoldcht.getbest(x)*/
const int N = 1e5 + 5;
int n,a[N],b[N];ll dp[N];
struct line{
    ll a , b;double xleft;bool type;
    line(ll _a , ll _b){a = _a;b = _b;type = 0;}
    bool operator < (const line &other) const{
        if(other.type){return xleft < other.xleft;}

```

```

        return a > other.a;}
};
double meet(line x , line y){
    return 1.0 * (y.b - x.b) / (x.a - y.a);}
struct cht{
    set <line> hull;
    cht() {hull.clear();}
    typedef set < line > :: iterator ite;
    bool hasleft(ite node){
        return node != hull.begin();}
    bool hasright(ite node){
        return node != prev(hull.end());}
    void updateborder(ite node){
        if(hasright(node)){line temp = *next(node);
            hull.erase(temp);
            temp.xleft=meet(*node,temp);
            hull.insert(temp);}
        if(hasleft(node)){line temp = *node;
            temp.xleft = meet(*prev(node) , temp);
            hull.erase(node);hull.insert(temp);}
        else{
            line temp = *node;hull.erase(node);
            temp.xleft = -1e18;hull.insert(temp);}
    }
    bool useless(line left,line middle,line right){
        double x = meet(left,right);
        double y = x * middle.a + middle.b;
        double ly = left.a * x + left.b;
        return y > ly;}
    bool useless(ite node){
        if(hasleft(node) && hasright(node)){return
            useless(*prev(node),*node,*next(node));}
        return 0;}
    void addline(ll a , ll b){
        line temp = line(a , b);
        auto it = hull.lower_bound(temp);
        if(it != hull.end() && it -> a == a){
            if(it -> b > b){hull.erase(it);}
            else return;}
        hull.insert(temp);it = hull.find(temp);
        if(useless(it)){hull.erase(it);return;}
        while(hasleft(it) && useless(prev(it))){
            hull.erase(prev(it));}
        while(hasright(it) && useless(next(it))){
            hull.erase(next(it));}
        updateborder(it);}
    ll getbest(ll x){
        if(hull.empty())return 1e18;
        line query(0 , 0);
        query.xleft = x;query.type = 1;
        auto it = hull.lower_bound(query);
        it = prev(it);
        return it -> a * x + it -> b;}
};

```



```

cht sameoldcht;
int main(){
    sameoldcht.addline(b[1], 0);
    dp[i] = sameoldcht.getbest(a[i]);
    sameoldcht.addline(b[i], dp[i]);}

```

5 Trees

5.1 BlockCut Tree

```

// Take care it is 0 indexed --
struct BiconnectedComponents {
    struct Edge {
        int from, to;
    };
    struct To {
        int to; int edge;
    };
    vector<Edge> edges; vector<vector<To> > g;
    vector<int> low, ord, depth;
    vector<bool> isArtic; vll edgeColor;
    vector<int> edgeStack;
    int colors; int dfsCounter;
    void init(int n) {
        edges.clear();
        g.assign(n, vector<To>());
    }
    void addEdge(int u, int v) {
        if(u > v) swap(u, v); Edge e = { u, v };
        int ei = edges.size(); edges.push_back(e);
        To tu = { v, ei }, tv = { u, ei };
        g[u].push_back(tu); g[v].push_back(tv);
    }
    void run() {
        int n = g.size(), m = edges.size();
        low.assign(n, -2); ord.assign(n, -1);
        depth.assign(n, -2); isArtic.assign(n, false);
        edgeColor.assign(m, -1); edgeStack.clear();
        colors = 0;
        for(int i = 0; i < n; ++ i) if(ord[i] == -1) {
            dfsCounter = 0;
            dfs(i);
        }
    }
private:
    void dfs(int i) {
        low[i] = ord[i] = dfsCounter ++;
        for(int j=0; j<(int)g[i].size(); ++j) {
            int to = g[i][j].to, ei = g[i][j].edge;
            if(ord[to] == -1) {
                depth[to] = depth[i] + 1;
                edgeStack.push_back(ei);
                dfs(to);
                low[i] = min(low[i], low[to]);
                if(low[to] >= ord[i]) {
                    if(ord[i] != 0 || j >= 1)
                        isArtic[i] = true;

```

```

                while(!edgeStack.empty()) {
                    int fi=edgeStack.back();
                    edgeStack.pop_back();
                    edgeColor[fi] = colors;
                    if(fi == ei) break;
                } ++colors;
            }
        } else if(depth[to] < depth[i] - 1) {
            low[i] = min(low[i], ord[to]);
            edgeStack.push_back(ei);
        }
    }
};

```

5.2 Dominator Tree

```

/*g:adjacency matrix (directed graph).
tree rooted at node 1. call dominator().
tree: undirected graph of dominators rooted
at node 1 (use visit times while doing dfs)*/
const int N = int(2e5)+10;
vi g[N], tree[N], rg[N], bucket[N];
int sdom[N], par[N], dom[N], dsu[N], label[N];
int arr[N], rev[N], T;
int Find(int u, int x=0){
    if(u==dsu[u])return x?-1:u;
    int v = Find(dsu[u], x+1);
    if(v<0)return u;
    if(sdom[label[dsu[u]]] < sdom[label[u]])
        label[u] = label[dsu[u]];
    dsu[u] = v;
    return x?v:label[u];}
void Union(int u, int v) {dsu[v]=u;}
void dfs0(int u){
    T++; arr[u]=T; rev[T]=u;
    label[T]=T; sdom[T]=T; dsu[T]=T;
    for(int i=0; i<g[u].size(); i++){
        int w = g[u][i];
        if(!arr[w])dfs0(w), par[arr[w]]=arr[u];
        rg[arr[w]].pb(arr[u]);
    }
}
void dominator(){
    dfs0(1); int n=T;
    for(int i=n; i>=1; i--){
        for(int j=0; j<rg[i].size(); j++){
            sdom[i] = min(sdom[i], sdom[Find(rg[i][j])]);
            if(i>1)bucket[sdom[i]].pb(i);
            for(int j=0; j<bucket[i].size(); j++){
                int w = bucket[i][j];
                int v = Find(w);
                if(sdom[v]==sdom[w])dom[w]=sdom[w];
                else dom[w] = v;}
            if(i>1)Union(par[i], i);
        }
    }
}

```



```

}
for(int i=2;i<=n;i++){
    if(dom[i]!=sdom[i]) dom[i]=dom[dom[i]];
    tree[rev[i]].pb(rev[dom[i]]);
    tree[rev[dom[i]]].pb(rev[i]);
}
}

```

5.3 Bridges Online

```

vector<int> par(MAX), dsu_2ecc(MAX), dsu_cc(MAX), ←
    dsu_cc_size(MAX);
int bridges,lca_iteration;
vector<int> last_visit(MAX);
void init(int n) {
    lca_iteration = 0;
    for (int i=0; i<n; ++i) {
        dsu_2ecc[i] = i; dsu_cc[i] = i;
        dsu_cc_size[i] = 1; par[i] = -1;
        last_visit[i]=0;
    } bridges = 0;
}
int find_2ecc(int v) { // 2-edge connected comp.
    if (v == -1) return -1;
    return dsu_2ecc[v] == v ? v : dsu_2ecc[v] = ←
        find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) { // connected comp.
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v : dsu_cc[v] = find_cc(←
        dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v);
    int root = v; int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]);
        par[v] = child; dsu_cc[v] = root;
        child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
vector<int> path_a, path_b;
void merge_path (int a, int b) {
    ++lca_iteration;
    int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a); path_a.push_back(a);
            if (last_visit[a] == lca_iteration) lca = a;
            last_visit[a] = lca_iteration; a=par[a];
        }
        if (b != -1) {
            b = find_2ecc(b); path_b.push_back(b);
            if (last_visit[b] == lca_iteration) lca = b;
            last_visit[b] = lca_iteration; b = par[b];
        }
    }
}

```

```

}
for (int v : path_a) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
for (int v : path_b) {
    dsu_2ecc[v] = lca; if (v == lca) break;
    --bridges; }
path_a.clear(); path_b.clear();
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;
    int ca = find_cc(a); int cb = find_cc(b);
    if (ca != cb) { ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b); swap(ca, cb); }
        make_root(a); par[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else { merge_path(a, b); }
}

```

5.4 HLD

```

/*v : adj matrix of tree.clear v[i],hdc[i]=0,i=-1 ←
before every run,clear ord and curc=0*/
vll v[MAX],ord;
ll par[MAX],noc[MAX],hdc[MAX],curc,posinch[MAX],←
len[MAX],ti=-1,sta[MAX],en[MAX],subs[MAX],level[←
MAX];
ll st[4*MAX],lazy[4*MAX],n;
void dfs(ll x){
    subs[x]=1;
    for(auto z:v[x]){
        if(z!=par[x]){par[z]=x;level[z]=level[x]+1;
            dfs(z);subs[x]+=subs[z];
        }}
}
void makehld(ll x){
    if(hdc[curc]==0){hdc[curc]=x;len[curc]=0;}
    noc[x]=curc;posinch[x]=++len[curc];
    ll a,b,c;a=b=0;ord.pb(x);sta[x]=++ti;
    for(auto z:v[x]){ if(z==par[x]) continue;
        if(subs[z]>b){b=subs[z];a=z;}
    }
    if(a!=0)makehld(a);
    for(auto z:v[x]){if(z==par[x]||z==a) continue;←
        curc++;makehld(z);}
    en[x]=ti;}
inline void upd(ll x,ll y){//update path a->b
    ll a,b,c,d;
    while(x!=y){a=hdc[noc[x]],b=hdc[noc[y]];
        if(a==b){
            if(level[x]>level[y])swap(x,y);c=sta[x],d=←
                sta[y];
            //lca=a;
            update(1,0,n-1,c+1,d);return;}
    }
}

```

```

    if(level[a]>level[b])swap(a,b),swap(x,y);
    //update on seg tree
    update(1,0,n-1,sta[b],sta[y]);y=par[b];}}
int main(){
    loop: v[i].clear(),hdc[i]=0,ti=-1;
    ord.clear(),curc=0;
    level[1]=0;par[1]=0;curc=1;dfs(1);makehld(1);
    while(q--){cin>>a>>b;upd(a,b);ll ans=sumq(1,0,←
        n-1,0,n-1);}
}

```

5.5 LCA

```

int lca(int a,int b){
    if(level[a]>level[b])swap(a,b);
    int d=level[b]-level[a];
    for(int i=0;i<LOGN;i++)if(d&(1<<i))
        b=DP[i][b];
    if(a==b)return a;
    for(int i=LOGN-1;i>=0;i--)
        if(DP[i][a]!=DP[i][b])
            a=DP[i][a],b=DP[i][b];
    return DP[0][a];}

```

5.6 Centroid Decomposition

```

/*nx:max nodes,par:parents of nodes in centroid tree,
  timestmp: timestamps of nodes when they became centroids,
  ssize,vis: subtree size and visit times in dfs,tim: timestamp iterator
dist[nx]: dist[i][0][j]=no. of nodes at dist k in subtree of i
in centroid tree
dist[i][j][k]=no. of nodes at distance k in jth child of i
in centroid tree *** (use adj while doing dfs instead of adj1)***
preprocess: stores all values in dist array*/
const int nx=1e5;
vector<int> adj[nx],adj1[nx];
int par[nx],timestmp[nx],ssize[nx],vis[nx];
int tim=1;
vector<int> cntorder;//centroids in order
vector<vector<int>>> dist[nx];
int dfs(int root){
    vis[root]=tim;
    int t=0;
    for(auto i:adj[root]){
        if(!timestmp[i]&&vis[i]<tim)t+=dfs(i);}
    ssize[root]=t+1;return t+1;}
int dfs1(int root,int n){
    vis[root]=tim;pair<int,int> mxc={0,-1};
    bool poss=true;
    for(auto i:adj[root]){
        if(!timestmp[i]&&vis[i]<tim)
            poss&=(ssize[i]<=n/2),mxc=max(mxc,{ssize[i],←
                i});}
    if(poss&&(n-ssize[root])<=n/2)return root;
}

```

```

return dfs1(mxc.second,n);}
int findc(int root){
    dfs(root);
    int n=ssize[root];tim++;
    return dfs1(root,n);}
void cntdecom(int root,int p){
    int cntr=findc(root);
    cntorder.pb(cntr);
    timestmp[cntr]=tim++;par[cntr]=p;
    if(p>=0)adj1[p].pb(cntr);
    for(auto i:adj[cntr])
        if(!timestmp[i])
            cntdecom(i,cntr);}
void dfs2(int root,int nod,int j,int dst){
    if(dist[root][j].size()==dst)dist[root][j].pb(0)←
        ;
    vis[nod]=tim;dist[root][j][dst]+=1;
    for(auto i:adj[nod]){
        if((timestmp[i]<=timestmp[root])||
            (vis[i]==vis[←
                nod]))continue;
        vis[i]=tim;dfs2(root,i,j,dst+1);}
}
void preprocess(){
    for(int i=0;i<cntorder.size();i++){
        int root=cntorder[i];
        vector<int> temp;
        dist[root].pb(temp);temp.pb(0);++tim;
        dfs2(root,root,0,0);
        int cnt=0;
        for(int j=0;j<adj[root].size();j++){
            int nod=adj[root][j];
            if(timestmp[nod]<timestmp[root])
                continue;
            dist[root].pb(temp);++tim;
            dfs2(root,nod,++cnt,1);}
    }
}

```

6 Maths

6.1 Chinese Remainder Theorem

```

/*x=rem[i]%mods[i] for any mods
input: rem->remainder,mods->moduli
output: (x%lcm of mods,lcm),-1 if infeasible*/
ll LCM(ll a, ll b) { return a / __gcd(a, b) * b; }
ll normalize(ll x,ll mod)
{x %= mod; if (x < 0) x += mod; return x; }
struct GCD_type { ll x, y, d; };
GCD_type ex_GCD(ll a, ll b){
    if (b == 0) return {1, 0, a};
    GCD_type pom = ex_GCD(b, a % b);
    return {pom.y, pom.x - a / b * pom.y, pom.d};
}
pll CRT(vll &rem,vll &mods){

```

```

11 n=rem.size(),ans=rem[0],lcm=mods[0];
for(11 i=1;i<n;i++){
    auto pom=ex_GCD(lcm,mods[i]);
    11 x1=pom.x,d=pom.d;
    if((rem[i]-ans)%d!=0) return {-1,0};
    ans=normalize(ans+x1*(rem[i]-ans)/d%(mods[i]
    i]/d)*lcm,lcm*mods[i]/d);
    lcm=LCM(lcm,mods[i]); // you can save time
    by replacing above lcm * n[i] /d by lcm
    = lcm * n[i] / d}
return {ans,lcm};
}

```

6.2 Discrete Log

/*Discrete Log , Baby-Step Giant-Step , e-maxx
The idea is to make two functions, $f_1(p)$, $f_2(q)$
and find p, q s.t. $f_1(p) = f_2(q)$ by storing all
possible values of f_1 , and checking for q . In
this case $a^x = b \pmod m$ is solved by subst.
 x by $p \cdot n - q$, where n is chosen optimally.*/
/*returns a soln. for $a^x = b \pmod m$ for
given a, b, m ; -1 if no. soln; 0(sqrt(m).log(m))
use unordered_map to remove log factor.
IMP : works only if a, m are co-prime.

```

But can be modified.*/
int solve(int a, int b, int m) {
    int n = (int) sqrt(m + .0) + 1;
    int an = 1;
    for (int i=0; i<n; ++i)
        an = (an * a) % m;
    map<int,int> vals;
    for (int i=1, cur=an; i<=n; ++i) {
        if (!vals.count(cur))
            vals[cur] = i;
        cur = (cur * an) % m;
    }
    for (int i=0, cur=b; i<=n; ++i) {
        if (vals.count(cur)) {
            int ans = vals[cur] * n - i;
            if (ans < m) return ans;
        }
        cur = (cur * a) % m;
    }
    return -1;
}

```

6.3 NTT

```

/*a*b%mod if a%mod*b%mod results in overflow:
11 mulmod(11 a, 11 b, 11 mod) {11 res = 0;
    while (a!=0){if(a&1)(res+=b)%=mod;a>>=1;(b<=1)%=mod;}
    return res;}
P=A*B A[0]=coeff of x^0
x = a1 mod p1, x = a2 mod p2 => x=((a1*(m2^-1)%m1)<-
    *m2+(a2*(m1^-1)%m2)*m1)%m1m2

```

```

***max_base=x (s.t. if mod=c*(2^k)+1 then x<=k and
    2^x >= nearest power of 2 of 2*n)
root=primitive_root^((mod-1)/(2^max_base))
For P=A*A use square function
635437057,11|639631361,6|985661441&998244353,3*/
#define chinese(a1,m1,inv2m1,a2,m2,inv1m2) ((a1 <-
    *11l* inv2m1 % m1 * 11l*m2 + a2 *11l* inv1m2 %<-
    m2 * 11l*m1) % (m1 *11l* m2))
int mod;//reset mod everytime
int base = 1;
v11 roots = {0, 1},rev = {0, 1};
int max_base=18,root=202376916;
void ensure_base(int nbase) {
    if (nbase <= base) return;
    rev.resize(1 << nbase);
    for (int i = 0; i < (1 << nbase); i++) {
        rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (<-
            nbase - 1));}
    roots.resize(1 << nbase);
    while (base < nbase) {
        int z = power(root, 1 << (max_base - 1 - base)<-
            );
        for (int i = 1 << (base - 1); i < (1 << base);<-
            i++) {
            roots[i << 1] = roots[i];
            roots[(i << 1) + 1] = mul(roots[i], z);
        }
        base++;
    }
}
void fft(v11 &a) {
    int n = (int) a.size();
    int zeros = __builtin_ctz(n);
    ensure_base(zeros);
    int shift = base - zeros;
    for (int i = 0; i < n; i++) {
        if (i < (rev[i] >> shift)) {
            swap(a[i], a[rev[i] >> shift]);}
    }
    for (int k = 1; k < n; k <= 1) {
        for (int i = 0; i < n; i += 2 * k) {
            for (int j = 0; j < k; j++) {
                int x = a[i + j];
                int y = mul(a[i + j + k], roots[j+k]);
                a[i + j] = x + y - mod;
                if (a[i + j] < 0) a[i + j] += mod;
                a[i + j + k] = x - y + mod;
                if (a[i+j+k]>=mod) a[i + j + k] -= mod;}
            }
    }
}
v11 multiply(v11 a, v11 b,int eq = 0) {
    int need = (int) (a.size() + b.size() - 1);
    int nbase = 0;
    while ((1 << nbase) < need) nbase++;
    ensure_base(nbase);
    int sz = 1 << nbase;

```

```

a.resize(sz);b.resize(sz);fft(a);
if (eq) b = a; else fft(b);
int inv_sz = inv(sz);
for (int i = 0; i < sz; i++)
    a[i] = mul(mul(a[i], b[i]), inv_sz);
reverse(a.begin() + 1, a.end());
fft(a);a.resize(need);return a;
}
vll square(vll a) {return multiply(a, a, 1);}

```

6.4 Online FFT

```

//f[i]=sum over j from 0 to i-1 f[j]*g[i-1-j]
//handle f[0] and g[0] separately
const int nx=131072;int f[nx],g[nx];
void onlinefft(int a,int b,int c,int d){
    vector<int> v1,v2;
    v1.pb(f+a,f+b+1);v2.pb(g+c,g+d+1); vector<int> ←
    res=multiply(v1,v2);
    for(int i=0;i<res.size();i++)
        if(a+c+i+1<nx) f[a+c+i+1]=add(f[a+c+i+1],res[i←
        ]);}
void precal(){
    g[0]=1;
    for(int i=1;i<nx;i++)
        g[i]=power(i,i-1);
    f[1]=1;
    for(int i=1;i<=100000;i++){
        f[i+1]=add(f[i+1],g[i]);f[i+1]=add(f[i+1],f[i←
        ]);
        f[i+2]=add(f[i+2],mul(f[i],g[1]));f[i+3]=add(f←
        [i+3],mul(f[i],g[2]));
        for(int j=2;i%j==0&&j<nx;j=j*2)
            onlinefft(i-j,i-1,j+1,2*j);}
}

```

6.5 Langrange Interpolation

```

/* Input :
Degree of polynomial: k
Polynomial values at x=0,1,2,3,...,k
Output :
Polynomial value at x
Complexity: O(degree of polynomial)
Works only if the points are equally spaced
*/
ll lagrange(vll& v , int k, ll x,int mod){
    if(x <= k) return v[x];
    ll inn = 1; ll den = 1;
    for(int i = 1;i<=k;i++){
        inn = (inn*(x - i))%mod;
        den = (den*(mod - i))%mod;
    }
    inn = (inn*inv(den % mod))%mod;
    ll ret = 0;
    for(int i = 0;i<=k;i++){

```

```

        ret = (ret + v[i]*inn)%mod;
        ll md1 = mod - ((x-i)*(k-i))%mod;
        ll md2 = ((i+1)*(x-i-1))%mod;
        if(i!=k)
            inn = (((inn*md1)%mod)*inv(md2 % mod))%mod←
    } return ret;
}

```

6.6 Matrix Struct

```

struct matrix{
    ld B[N][N], n;
    matrix(){n = N; memset(B,0,sizeof B);}
    matrix(int _n)
        {n = _n; memset(B, 0, sizeof B);}
    void iden(){
        for(int i = 0; i < n; i++) B[i][i] = 1;}
    void operator += (matrix M){
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                B[i][j]=add(B[i][j],M.B[i][j]);}
    void operator -= (matrix M){}
    void operator *= (ld b){}
    matrix operator - (matrix M){}
    matrix operator + (matrix M){
        matrix ret = (*this); ret += M; return ret;}
    matrix operator * (matrix M){
        matrix ret = matrix(n); memset(ret.B, 0, ←
        sizeof ret.B);
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n;j++)
                for(int k = 0; k < n; k++)
                    ret.B[i][j] = add(ret.B[i][j], mul(B[i][←
                    k], M.B[k][j]));
        return ret;}
    matrix operator *= (matrix M){*this=((*this)*M)←
    ;}
    matrix operator * (int b){
        matrix ret =(*this);ret *= b; return ret;}
    vector<double> multiply(const vector<double> & v←
    ) const{
        vector<double> ret(n);
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++)
                ret[i] += B[i][j] * v[j];
        return ret;
    }
};

```

6.7 nCr(Non Prime Modulo)

```

// calculates nCr, for small
// non-prime modulo, and (very) big n,r.
ll phimod;
vll pr,prn;vll fact;

```

```

11 power(11 a,11 x,11 mod){
    11 ans=1;
    while(x){
        if((1LL)&(x))ans=(ans*a)%mod;
        a=(a*a)%mod;x>>=1LL;
    }
    return ans;
}
// prime factorization of x.
// pr-> prime ; prn -> it's exponent
void getprime(11 x){
    pr.clear();prn.clear();
    11 i,j,k;
    for(i=2;(i*i)<=x;i++){
        k=0;while((x%i)==0){k++;x/=i;}
        if(k>0){pr.pb(i);prn.pb(k);}
    }
    if(x!=1){pr.pb(x);prn.pb(1);}
    return;
}
// factorials are calculated ignoring
// multiples of p.
void primeproc(11 p,11 pe){ // p , p^e
    11 i,d;
    fact.clear();fact.pb(1);d=1;
    for(i=1;i<pe;i++){
        if(i%p){fact.pb((fact[i-1]*i)%pe);}
        else {fact.pb(fact[i-1]);}
    }
    return;
}
// again note this has ignored multiples of p
11 Bigfact(11 n,11 mod){
    11 a,b,c,d,i,j,k;
    a=n/mod;a%=phimod;a=power(fact[mod-1],a,mod);
    b=n%mod;a=(a*fact[b])%mod;
    return a;
}
// Chinese Remainder Thm.
v11 crtval,crtmod;
11 crt(v11 &val,v11 &mod){
    11 a,b,c,d,i,j,k;b=1;
    for(11 z:mod)b*=z;
    11 ans=0;
    for(i=0;i<mod.size();i++){
        a=mod[i];c=b/a;
        d=power(c,(((a/pr[i])*(pr[i]-1))-1),a);
        c=(c*d)%b;c=(c*val[i])%b;ans=(ans+c)%b;
    }
    return ans;
}
// calculate for prime powers and
// take crt. For each prime power,
// first ignore multiples of p,
// and then do recursively, calculating
// the powers of p separately.

```

```

11 Bigncr(11 n,11 r,11 mod){
    11 a,b,c,d,i,j,k;11 p,pe;
    getprime(mod);11 Fnum=1;11 Fden;
    crtval.clear();crtmod.clear();
    for(i=0;i<pr.size();i++){
        Fnum=1;Fden=1;
        p=pr[i];pe=power(p,prn[i],1e17);
        primeproc(p,pe);
        a=1;d=0;
        phimod=(pe*(p-1LL))/p;
        11 n1=n,r1=r,nr=n-r;
        while(n1){
            Fnum=(Fnum*(Bigfact(n1,pe)))%pe;
            Fden=(Fden*(Bigfact(r1,pe)))%pe;
            Fden=(Fden*(Bigfact(nr,pe)))%pe;
            d+=n1-(r1+nr);
            n1/=p;r1/=p;nr/=p;
        }
        Fnum=(Fnum*(power(Fden,(phimod-1LL),pe)))%pe;
        if(d>=prn[i])Fnum=0;
        else Fnum=(Fnum*(power(p,d,pe)))%pe;
        crtmod.pb(pe);crtval.pb(Fnum);
    }
    // you can just iterate instead of crt
    // for(i=0;i<mod;i++){
    //     bool cg=true;
    //     for(j=0;j<crtmod.size();j++){
    //         if(i%crtmod[j]!=crtval[j])cg=false;
    //     }
    //     if(cg)return i;
    // }
    return crt(crtval,crtmod);
}

```

6.8 Primitive Root Generator

/*To find generator of $U(p)$, we check for all g in $[1, p]$. But only for powers of the form $\phi(p)/p_j$, where p_j is a prime factor of $\phi(p)$. Note that p is not prime here. Existence, if one of these: 1. $p = 1, 2, 4$ 2. $p = q^k$, where $q \rightarrow$ odd prime. 3. $p = 2 \cdot (q^k)$, where $q \rightarrow$ odd prime. Note that $a \cdot g^{\phi(p)} = 1 \pmod{p}$ b. there are $\phi(\phi(p))$ generators if exists. Finds "a" generator of $U(p)$, multiplicative group of integers mod p . Here `calc_phi` returns the \leftarrow toitent function for p . $O(\text{Ans} \cdot \log(\phi(p)) \cdot \log(p)) +$ time for factorizing $\phi(p)$. By some theorem, $\text{Ans} = O((\log(p))^6)$. Should be fast generally.*/

```

int generator(int p){
    vector<int> fact;
    int phi = calc_phi(p), n = phi;
    for(int i=2; i*i<=n; ++i)

```



```

    if (n % i == 0) {
        fact.push_back(i);
        while (n % i == 0)
            n /= i;
    }
    if (n > 1) fact.push_back(n);
    for (int res=2; res<=p; ++res) {
        if (gcd(res,p)!=1) continue;
        bool ok = true;
        for (size_t i=0; i<fact.size() && ok; ++i)
            ok &= powmod(res, phi / fact[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}

```

6.9 Group Theory

$x^2 = n \pmod{p}$. Existence - $n^{((p-1)/2)} == 1 \rightarrow$ there is a soln.,
 $\text{else} == -1$, no solution.
 Finding sqrt. in some $\mathbb{Z} \pmod{p}$:
 Cipollas Algorithm.
 Find an 'a' (randomly), s.t. $a^2 - n$ doesn't have a sqrt.
 Adjoin it to the field. Take $(a + \sqrt{a^2 - n})^{((p+1)/2)}$.
 Do all operations mod p, ans will be integer.
 Cipollas Algo works only when mod is prime.
 [Remember $(a+b)^p = a^p + b^p \pmod{p} = a + b \pmod{p}$]
 For non-prime:
 $x^2 = n \pmod{m}$.
 Soln. \rightarrow Compute it modulo prime powers and take CRT.
 For prime powers:
 We have a solution $x_0 \pmod{p}$. We use it to find a solution $\pmod{p^2}$,
 then $\pmod{p^3}$ and so on. For p^2 : $x^2 = n \pmod{p^2}$; We want x to
 reduce to $x_0 \pmod{p}$. So $x = x_0 + p \cdot x_1$. Square it. $x_0^2 + 2 \cdot x_0 \cdot x_1 = n \pmod{p^2}$.
 Calculate x_1 . This can be extended to find greater powers of p.
 But the inverse may not exist always which may give a problem.
 But then no solution or all solutions. This is called Hensel's Lifting.
 This can also be extended to find $f(x) = 0 \pmod{p^2}$, if we have a soln. for $f(x) = 0 \pmod{p}$. Get something in $f'(x)$

7 Strings

7.1 Hashing Theory

If order not imp. and count/frequency imp. use this as hash fn:-

$((a_{-1+h})^k + (a_{-2+h})^k + (a_{-3+h})^k + (a_{-4+h})^k) \leftarrow \% p$. Select : h,k,p
 Alternate:
 $((x)^{(a_{-1}}) + (x)^{(a_{-2}}) + \dots + (x)^{(a_{-k})}) \% \text{mod}$ where x and mod are fixed and $a_{-1} \dots a_{-k}$ is an unordered set

7.2 Manacher

/*Same idea as Z_fn, 0(n)
 [l,r]: rightmost detected subpalindrom (with max r)
 len of odd length palindrom centered around that char (e.g abac for 'b' returns 2(not 3))*/
 vll manacher_odd(string s){
 ll n = s.length(); vll d1(n);
 for(ll i = 0, l = 0, r = -1; i < n; i++){
 d1[i] = 1;
 if(i <= r){ // use prev val
 d1[i] = min(r-i+1, d1[l+r-i]);
 while(i+d1[i] < n && i-d1[i] >= 0 && s[i+d1[i]] == s[i-d1[i]])
 d1[i]++; // trivial matching
 if(r < i+d1[i]-1) l=i-d1[i]+1, r=i+d1[i]-1;
 }
 return d1;
 }
 //even lens centered around (bb is centered around the later 'b')
 vll manacher_even(string s){
 ll n = s.length(); vll d2(n);
 for(ll i = 0, l = 0, r = -1; i < n; i++){
 d2[i] = 0;
 if(i <= r){
 d2[i] = min(r-i+1, d2[l+r+1-i]);
 while(i+d2[i] < n && i-d2[i]-1 >= 0 && s[i+d2[i]] == s[i-d2[i]-1]) d2[i]++;
 if(d2[i] > 0 && r < i+d2[i]-1)
 l=i-d2[i], r=i+d2[i]-1;
 }
 return d2;
 }
 }
 // Other mtd : To do both things in one pass,
 // add special char e.g string "abc" => "\$a\$b\$c\$"

7.3 Trie

```

const ll AS = 26; // alphabet size
ll go[MAX][AS]; ll cnt[MAX]; ll cn=0;
// cn -> index of next new node
// convert all strings to vll
ll newNode() {
    for(ll i=0; i<AS; i++)
        go[cn][i] = -1;
    return cn++;
}
// call newNode once **** before adding anything
void addTrie(vll &x) {
    ll v = 0;

```

```

cnt[v]++;
for (ll i=0; i<x.size(); i++){
    ll y=x[i];
    if (go[v][y]==-1)
        go[v][y]=newNode();
    v=go[v][y];
    cnt[v]++;
}
// returns count of substrings with prefix x
ll getcount(vll &x){
    ll v=0;
    for (i=0; i<x.size(); i++){
        ll y=x[i];
        if (go[v][y]==-1)
            go[v][y]=newNode();
        v=go[v][y];
    }
    return cnt[v];
}

```

7.4 Z-algorithm

/*[l,r]->rightmost segment match(with max r)
Time : $O(n)$ (asy. behavior), Proof: each itr of
inner while loop make r pointer advance to right,
App:1) Search substring(text t, pat p) s=p+ '\$' + t.
3) String compression(s=t+t+...+t, then find |t|)
2) Number of distinct substrings (in $O(n^2)$)
(useful when appending or deleting characters
online from the end or beginning)*/
vector<ll> z_function(string s) {
 ll n = (ll) s.length();
 vector<ll> z(n);
 for (ll i=1, L=0, R=0; i<n; ++i) {
 if (i <= R) // use previous z val
 z[i] = min(R - i + 1, z[i - L]);
 while (i + z[i] < n && s[z[i]] == s[i + z[i]])
 ++z[i]; // trivial matching
 if (i + z[i] - 1 > R) L = i, R = i + z[i] - 1;
 // update rightmost segment matched
 }
 return z;
}

7.5 Aho Corasick

```

const int K = 26;
// remember to set K
struct Vertex {
    int next[K]; bool leaf = false;
    int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};

```

```

};
vector<Vertex> aho(1);
void add_string(string const& s) {
    int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (aho[v].next[c] == -1) {
            aho[v].next[c] = aho.size();
            aho.emplace_back(v, ch);
        }
        v = aho[v].next[c];
    } aho[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (aho[v].link == -1) {
        if (v==0 || aho[v].p==0) aho[v].link = 0;
        else aho[v].link =
            go(get_link(aho[v].p), aho[v].pch);
    }
    return aho[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (aho[v].go[c] == -1) {
        if (aho[v].next[c] != -1)
            aho[v].go[c] = aho[v].next[c];
        else
            aho[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    }
    return aho[v].go[c];
}

```

7.6 KMP

/*Time: $O(n)$ (j increases n times (& $j \geq 0$) only so
asy. $O(n)$), pi[i] = length of longest prefix of
s ending at i
app.: search substring,
of different substrings ($O(n^2)$),
3) String compression(s = t+t+...+t,
then find |t|, k=n-pi[n-1], if k|n)
4) Building Automaton(Gray Code Example)*/
vector<ll> prefix_function(string s) {
 ll n = (ll) s.length(); vll pi(n);
 for (ll i = 1; i < n; i++) {
 ll j = pi[i-1];
 while (j > 0 && s[i] != s[j]) j = pi[j-1];
 if (s[i] == s[j]) j++;
 pi[i] = j;
 }
 return pi;
}
//searching s in t, returns all occurrences(indices

```
vector<ll> search(string s,string t){
    vll pi = prefix_function(s);
    ll m = s.length(); vll ans; ll j = 0;
    for(ll i=0;i<t.length();i++){
        while(j > 0 && t[i] != s[j])
            j = pi[j-1];
        if(t[i] == s[j]) j++;
        if(j == m) ans.pb(i-m+1);
    } // if ans empty then no occurrence
    return ans;}

```

7.7 Palindrome Tree

```
const ll MAX=1e5+15;
ll par[MAX]; // stores index of parent node
ll sul[1][MAX]; // stores index of suffix link
ll len[MAX]; // stores len of largest
// palindrome ending at that node */
ll child[MAX][30]; // stores the children of the node
/*-----
index 0 - root "-1"
index 1 - root "0"
therefore node of s[i] is i+2
initialize all child[i][j] to -1
-----*/
void eer_tree(string s){
    ll a,b,c,d,i,j,k,e,f;
    sul[1][1]=0; sul[0][0]=0; len[1]=0; len[0]=-1;
    ll n=s.length();
    for(i=0;i<n+10;i++){
        for(j=0;j<30;j++) child[i][j]=-1;
    }
    ll cur=1; d=1;
    for(i=0;i<s.size();i++){
        ++d;
        while(true){
            a=i-1-len[cur];
            if(a>=0){
                if(s[a]==s[i]){
                    if(child[cur][(ll)(s[i]-'a')]==-1){
                        par[d]=cur; child[cur][(ll)(s[i]-'a')]=d;
                        len[d]=len[cur]+2; cur=d;
                    }
                    else{
                        par[d]=cur; len[d]=len[cur]+2;
                        cur=child[cur][(ll)(s[i]-'a')];
                    }
                }
                break;
            }
        }
        if(cur==0) break;
        cur=sul[cur][1];
    }
    if(cur!=d) continue;
    if(len[d]==1) sul[d]=1;
    else{

```

```

        c=sul[par[d]];
        while(child[c][(ll)(s[i]-'a')]==-1){
            if(c==0) break;
            c=sul[c];
        }
        sul[d]=child[c][(ll)(s[i]-'a')];
    }
}
}

```

7.8 Suffix Array

```

/*Sorted array of suffixes = sorted array of cyclic
shifts of string+$. We consider a prefix of len.  $2^k$  of the cyclic, in the kth iteration. String of len.  $2^k$  → combination of 2 strings of len.  $2^{(k-1)}$ , whose order we know, from previous iteration. Just radix sort on pair for next iteration.
Time :-  $O(n \log(n) + \text{alphabet})$ . Applications :-
Finding the smallest cyclic shift; Finding a substring
in a string; Comparing two substrings of a string;
Longest common prefix of two substrings; Number of
different substrings. */
//returns permutation of indices in sorted order
***
vector<ll> sort_cyclic_shifts(string const& s) {
    ll n = s.size();
    const ll alphabet = 256;
    //change the alphabet size accordingly and indexing
    vector<ll> p(n), c(n), cnt(max(alphabet, n), 0);
    // p:sorted ord. of 1-len prefix of each cyclic
    // shift index. c:class of a index
    // pn:same as p for kth iteration. ||ly cn.
    for (ll i = 0; i < n; i++)
        cnt[s[i]]++;
    for (ll i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (ll i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    ll classes = 1;
    for (ll i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
        c[p[i]] = classes - 1;
    }
    vector<ll> pn(n), cn(n);
    for (ll h = 0; (1 << h) < n; ++h) {
        for (ll i = 0; i < n; i++) { //sorting w.r.t
            pn[i] = p[i] - (1 << h); //second part.
            if (pn[i] < 0)

```

```

        pn[i] += n;
    }
    fill(cnt.begin(), cnt.begin() + classes, 0);
    for (ll i = 0; i < n; i++)
        cnt[c[pn[i]]]++;
    for (ll i = 1; i < classes; i++)
        cnt[i] += cnt[i-1];
    // sorting w.r.t. 1st(more significant) part
    for (ll i = n-1; i >= 0; i--)
        p[--cnt[c[pn[i]]]] = pn[i];
    cn[p[0]] = 0; classes = 1;
    // determining new classes in sorted array.
    for (ll i = 1; i < n; i++) {
        pll cur={c[p[i]],c[(p[i]+(1<<h))%n]};
        pll prev={c[p[i-1]],c[(p[i-1]+(1<<h))%n]};
        if (cur != prev) ++classes;
        cn[p[i]] = classes - 1;
    }
    c.swap(cn);
    return p;
}
vector<ll> suffix_array_construction(string s) {
    s += "$";
    vector<ll> sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}
// For comp. two substr. of len. l starting at i,j
// k - 2^k > l/2. check the first 2^k part, if
// equal,
// check last 2^k part. c[k] is the c in kth iter
//of S.A construction.
int compare(int i, int j, int l, int k) {
    pll a = {c[k][i],c[k][(i+l-(1 << k))%n]};
    pll b = {c[k][j],c[k][(j+l-(1 << k))%n]};
    return a == b ? 0 : a < b ? -1 : 1;
}
/*lcp[i]=len. of lcp of ith & (i+1)th suffix in
the SA
1.Consider suffixes in decreasing order of length.
2.Let p = s[i....n]. It will be somewhere in the S.A.
We determine its lcp = k. 3.Then lcp of q=s[(i+1)....n]
will be atleast k-1 coz 4.remove the first char of p
and its successor in the S.A. These are suffixes
with lcp k-1. 5.But note that these 2 may not be
consecutive in S.A.But lcp of str. in b/w have to be also >= k-1.*/
vll lcp_cons(string const& s, vector<ll> const& p)
{
    ll n = s.size();
    vector<ll> rank(n, 0);
    for (ll i = 0; i < n; i++)
        rank[p[i]] = i;

```

```

    ll k = 0; vector<ll> lcp(n-1, 0);
    for (ll i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0; continue;
        }
        ll j = p[rank[i] + 1];
        while (i+k < n && j+k < n && s[i+k]==s[j+k]) k++;
        lcp[rank[i]] = k; if (k) k--;
    }
    return lcp;
}

```

7.9 Suffix Tree

```

const int N=1000000, // set it more than 2*(len. of string)
string str; // input string for which the suffix tree is being built
int chi[N][26],
lef[N], // left...
rig[N], // ...and right boundaries of the substring of a which correspond to incoming edge
par[N], // parent of the node
sfli[N], // suffix link
tv,tp,la,
ts; // the number of nodes
void ukkadd(int c) {
    suff++;
    if (rig[tp]<tv){
        if (chi[tp][c]==-1){chi[tp][c]=ts;lef[ts]=la;
            par[ts++]=tv;tv=sfli[tp];tp=rig[tp]+1;goto suff;}
        tv=chi[tp][c];tp=lef[tp];
    }
    if (tp==-1 || c==str[tp]-'a')tp++;
    else {
        lef[ts]=lef[tp]; rig[ts]=tp-1; par[ts]=par[tp];
        chi[ts][str[tp]-'a']=tv; chi[ts][c]=ts+1;
        lef[ts+1]=la; par[ts+1]=ts; lef[tp]=tp; par[tp]=ts;
        chi[par[ts]][str[lef[ts]]-'a']=ts; ts+=2;
        tv=sfli[par[ts-2]]; tp=lef[ts-2];
        while (tp <= rig[ts-2]) {
            tv=chi[tp][str[tp]-'a']; tp+=rig[tp]-lef[tp]+1;}
        if (tp == rig[ts-2]+1) sfli[ts-2]=tv; else sfli[ts-2]=ts;
        tp=rig[tp]-(tp-rig[ts-2])+2;goto suff;
    }
}
void build() {
    ts=2; tv=0; tp=0;
    ll ss = str.size();ss*=2;ss+=15;
    fill(rig,rig+ss,(int)str.size()-1);
    // initialize data for the root of the tree
    sfli[0]=1; lef[0]=-1; rig[0]=-1;
}

```

```

lef[1]=-1; rig[1]=-1; for(ll i=0;i<ss;i++)
fill(chi[i], chi[i]+27,-1);
fill(chi[1], chi[1]+26,0);
// add the text to the tree, letter by letter
for(la=0; la<(int)str.size(); ++la)
ukkadd(str[la]-'a');
}

```

Möbius Function

$$\mu(n) = \begin{cases} 0 & n \text{ not squarefree} \\ 1 & n \text{ squarefree w/ even no. of prime factors} \\ -1 & n \text{ squarefree w/ odd no. of prime factors} \end{cases}$$

Note that $\mu(a)\mu(b) = \mu(ab)$ for a, b relatively prime

$$\text{Also } \sum_{d|n} \mu(d) = \begin{cases} 1 & \text{if } n = 1 \\ 0 & \text{otherwise} \end{cases}$$

Möbius Inversion If $g(n) = \sum_{d|n} f(d)$ for all $n \geq 1$, then $f(n) = \sum_{d|n} \mu(d)g(n/d)$ for all $n \geq 1$.

Burnside's Lemma (Text)

The number of orbits of a set X under the group action G equals the average number of elements of X fixed by the elements of G .

Here's an example. Consider a square of $2n$ times $2n$ cells. How many ways are there to color it into X colors, up to rotations and/or reflections? Here, the group has only 8 elements (rotations by 0, 90, 180 and 270 degrees, reflections over two diagonals, over a vertical line and over a horizontal line). Every coloring stays itself after rotating by 0 degrees, so that rotation has X^{4n^2} fixed points. Rotation by 180 degrees and reflections over a horizontal/vertical line split all cells in pairs that must be of the same color for a coloring to be unaffected by such rotation/reflection, thus there exist X^{2n^2} such colorings for each of them. Rotations by 90 and 270 degrees split cells in groups of four, thus yielding X^{n^2} fixed colorings. Reflections over diagonals split cells into $2n$ groups of 1 (the diagonal itself) and $2n^2 - n$ groups of 2 (all remaining cells), thus yielding $X^{2n^2 - n + 2n} = X^{2n^2 + n}$ unaffected colorings. So, the answer is $(X^{4n^2} + 3X^{2n^2} + 2X^{n^2} + 2X^{2n^2 + n})/8$. Every tree with n vertices has $n - 1$ edges.

Trees-Kraft inequality:

If the depths of the leaves of a binary tree are $d_1 \dots d_n$: $\sum_{i=1}^n 2^{-d_i} \leq 1$, and equality holds only if every internal node has 2 sons.

Master method:

$$T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$$

If $\exists \varepsilon > 0$ such that $f(n) = O(n^{\log_b a - \varepsilon})$ then $T(n) = \Theta(n^{\log_b a})$.

If $f(n) = \Theta(n^{\log_b a})$ then $T(n) = \Theta(n^{\log_b a} \log_2 n)$.

If $\exists \varepsilon > 0$ such that $f(n) = \Omega(n^{\log_b a + \varepsilon})$, and $\exists c < 1$ such that $af(n/b) \leq cf(n)$ for large n , then $T(n) = \Theta(f(n))$.

Probability:

Variance, standard deviation: $\text{Var}[X] = E[X^2] - E[X]^2$

Poisson distribution:

Normal (Gaussian) distribution:

$$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda \quad \left| \quad p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$$

The "coupon collector": We are given a random coupon each day, and there are n different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all n types is nH_n .

Miscellaneous:

1. Radius of inscribed circle for Right Angle Triangle: $\frac{AB}{A+B+C}$
2. Law of cosine: $c^2 = a^2 + b^2 - 2ab \cos C$
3. Area of a triangle: Area: $A = \frac{1}{2}hc = \frac{1}{2}ab \sin C = \frac{c^2 \sin A \sin B}{2 \sin C}$.
4. $\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i, \pi(i)}$, for Permanents remove sign.
5. Perfect Numbers: x is an even perfect number iff $x = 2^{n-1}(2^n - 1)$ and $2^n - 1$ is prime.
6. Wilson's theorem: n is a prime iff $(n-1)! \equiv -1 \pmod n$.
7. If graph G is planar then $n - m + f = 2$, so $f \leq 2n - 4$, $m \leq 3n - 6$. Any planar graph has a vertex with degree ≤ 5 .
8. Dirichlet power series: $A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}$
9. Coefficient of x^r in $(1-x)^{-n}$ is $\binom{n+r-1}{r}$.

For Bipartite Graphs

1. Min-edge cover(me) = Max-independent set(mi) (G has no isolated vertex).
2. Min-vertex cover(mv) = Max matching(mm) $mi + mv = |V|$, $mi \geq \frac{|V|}{2}$
3. Min-edge cover subgraph is a combination of star graphs.
4. Min Vertex cover : In residual graph of max flow pick all the vertices in L(left bipartite) not reachable from s (whose edges are cut) and lly in R reachable from s .
5. Min-edge cover(no isolated vertex) : Find max matching, take all those edges, for vertices not covered take any edge.

$$\frac{x}{(1-x)^2} = \sum_{i=0}^{\infty} ix^i, \quad \ln(1+x) = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, \quad \frac{x}{1-x-x^2} = \sum_{i=0}^{\infty} F_i x^i$$

$$(x_1 + x_2 + \dots + x_k)^n = \sum_{c_1+c_2+\dots+c_k=n} \frac{n!}{c_1!c_2!\dots c_k!} x_1^{c_1} x_2^{c_2} \dots x_k^{c_k}$$

$$\int \tanh x dx = \ln |\cosh x|, \quad \int \coth x dx = \ln |\sinh x|, \quad \int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln \left| \frac{a+x}{a-x} \right|,$$

$$\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln \left(x + \sqrt{a^2 + x^2} \right) \quad (a > 0), \quad \int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a} \quad (a > 0),$$

$$\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a} \quad (a > 0)$$

$$\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a} \quad (a > 0)$$

Fibonacci:

1. $F_{-i} = (-1)^{i-1} F_i, \quad F_i = \frac{1}{\sqrt{5}} (\phi^i - \hat{\phi}^i)$
2. Cassini's identity: $F_{i+1} F_{i-1} - F_i^2 = (-1)^i \quad \text{for } i > 0,$
3. Addictive Rule: $F_{n+k} = F_k F_{n+1} + F_{k-1} F_n, \quad F_{2n} = F_n F_{n+1} + F_{n-1} F_n$
4. Every integer n has a unique representation $n = F_{k_1} + F_{k_2} + \cdots + F_{k_m}$, where $k_i \geq k_{i+1} + 2$ for $1 \leq i < m$ and $k_m \geq 2$.

Primes

$\forall(a, b)$, The largest prime smaller than 10^a is $p = 10^a - b$

(1,3), (2,3), (3,3), (4,27), (5,9), (6,17), (7,9), (8,11), (9,63), (10,33),

(11,23), (12,11), (13,29), (14,27), (15,11), (16,63), (17,3), (18,11)