
On Variance Reduction in Learning Mean Flows

Anonymous Author(s)

Affiliation

Address

email

Abstract

One-step generative modeling has emerged as a leading approach to amortize the inference cost of diffusion and flow-matching models. Among distillation-free methods, MeanFlow training is notoriously unstable, with non-decreasing loss and unbounded gradient variance. In this work, we establish a theory that attributes this pathology to a misuse of the conditional velocity field: it plays two distinct statistical roles in the loss, both as an unbiased regression target and as a Monte Carlo control variate inside a Jacobi-vector product, with the original loss assigning the wrong coefficient to the latter. We derive the optimal coefficient in closed form, and show that a family of fixes in concurrent works corresponds to different practical realizations of the same optimum. A controlled sweep of this coefficient on two-dimensional benchmarks and on a latent Diffusion Transformer recovers the predicted bias-variance ordering. The optimal coefficient yields up to a 54% improvement in sample quality on two-dimensional benchmarks and a monotone FID trend at every matched-step DiT checkpoint. Crucially, the same DiT measurement also reveals a quantitative *FID-MSE landscape mismatch*: although gradient variance is minimized at an interior coefficient value, the coefficient that minimizes FID prefers the direct use of conditional velocity.

1 Introduction

Deep generative models that leverage neural networks to parametrize and sample from unknown data distributions have achieved remarkable success [1–5]. Among these models, flow-based generative models [6–12] learn a continuous-time transformation between a simple prior and the data distribution. Conditional flow matching [10, 11] and stochastic interpolants [12, 13] further enable simulation-free training by regressing a velocity field, achieving sample quality competitive with diffusion models [1, 14, 2]. However, integration at inference time remains a challenge due to its computational costs and numerical instability, motivating a series of subsequent works on *one-step generative models*, including progressive distillation [15], distribution matching [16, 17], consistency models [18, 19], and flow map matching [20]. Nevertheless, most of them require a pre-trained distillation teacher.

Mean Flows [21] provide a *distillation-free* alternative by learning a two-parameter average velocity field through least-squares regression of a total-derivative identity between the average and instantaneous velocity. In principle, this identity yields exact self-supervision. In practice, however, training is plagued by *non-decreasing loss* and prohibitively *high gradient variance* [22, 23]. A plethora of concurrent works have proposed remedies that target different mechanisms. AlphaFlow [22] attributes slow convergence to gradient conflict between flow-matching and total-derivative consistency components and proposes an α -curriculum. Improved MeanFlow [23] replaces the conditional-velocity tangent with a learned marginal-velocity head. Re-MeanFlow [24] preprocesses the data with rectified-flow straightening to reduce trajectory curvature. Terminal Velocity Matching [25] sidesteps the spatial Jacobian by differentiating with respect to the termi-

nal time. Functional Mean Flows [26] extend MeanFlow to Hilbert spaces and study marginal-conditional consistency for functional data. Each fix is empirically effective in isolation, but no theory explains *why* the original objective is unstable or *what* these fixes have in common.

In this paper, we establish our theory around a single research question:

Why do stochastic tangents destabilize learning Mean Flows?

We answer this question through the lens of *variance reduction*. Specifically, we identify that the conditional velocity plays two statistically distinct roles in the MeanFlow loss. As the regression target, it is an *unbiased* estimator of the marginal velocity. As the tangent inside the Jacobian-vector product (JVP) of the total-derivative identity, however, it acts as a Monte Carlo *control variate* for the inaccessible marginal velocity, with a statistically suboptimal coefficient. The bias-variance trade-off induced by this substitution governs the variance of the gradient through a quadratic term. A Jacobi factor in JVP amplifies sample-based conditional fluctuations at each gradient step, and stop-gradient further hides this amplification from the optimizer, leading to the empirical pathology.

Following the theory, we derive the optimal tangent control-variate coefficient in closed form and show that it converges to a deterministic-tangent estimator in the practical regime where a marginal-velocity estimator is available. This result *explains* why deterministic tangents (*e.g.*, *learned velocity heads*) help stabilize training. They are essentially different practical instantiations of the same statistical optimum. To empirically validate the framework, we perform a controlled sweep of the coefficient across two-dimensional datasets and the ImageNet dataset using latent diffusion Transformers (DiTs). Direct measurement of per-step gradient variance recovers the predicted non-decreasing loss component. Meanwhile, we observe a $1.2\times \sim 4.3\times$ reduction with deterministic tangents on the two-dimensional datasets. The same sweep on ImageNet also reveals a quantitative *FID-MSE landscape mismatch*: the FID ordering aligns with the bias-variance prediction across all four coefficient values. Nonetheless, the FID-axis offset ratio across large coefficients is super-linear in the MSE-axis, hence the FID-optimal coefficient shifts past the gradient-MSE interior minimizer to the *unbiased* corner. Our contributions in this paper are as follows:

- C1** We establish a theory to prove that per-step gradient variance in the original MeanFlow scales unboundedly with the spatial-Jacobi factor in JVP and the stop-gradient operator induces a *semi-gradient gap* that hides this term from the optimizer.
- C2** We frame the JVP tangent as a *control variate* for the marginal velocity, derive the optimal coefficient in closed form, and unify concurrent works by showing that they each correspond to a different practical realization of the optimal coefficient.
- C3** We empirically validate the framework through a controlled sweep of the coefficient on both two-dimensional datasets and ImageNet with latent DiTs. We observe $1.2\times \sim 4.3\times$ direct gradient-variance reduction, up to 54% SW_1 improvements on two-dimensional benchmarks, the predicted bias-variance FID ordering at every matched-step DiT checkpoint, and a quantitative FID-MSE landscape mismatch: the optimal coefficient minimizing gradient-MSE is near 0.94. In contrast, the one that minimizes FID leans toward 0.

2 Preliminaries

Flow-Matching. Let $\mathbf{x}$ denote a data sample in $\mathcal{X} \subset \mathbb{R}^d$. Flow-matching generative models [10, 11] learn a time-dependent diffeomorphism $\psi(\mathbf{x}, t) : \mathbb{R}^d \times [0, 1] \rightarrow \mathbb{R}^d$ from a simple distribution $\mathbf{x}_1 \sim p(\mathbf{x}, 1)$ to the target $\mathbf{x}_0 \sim p(\mathbf{x}, 0) = p_{\text{data}}$ by parameterizing a velocity field $\mathbf{v}(\mathbf{x}, t) \triangleq \frac{d}{dt} \psi(\mathbf{x}, t)$. Since the exact *marginal velocity field* $\mathbf{v}(\mathbf{x}, t)$ is generally inaccessible, conditional flow-matching [10] instead learns a conditional field $\mathbf{v}_{\text{cond}} = \mathbf{x}_1 - \mathbf{x}_0$ with $\mathbf{x}_t = (1-t)\mathbf{x}_0 + t\mathbf{x}_1$. The following lemma justifies the substitution. See Appendix B.1 for its proof.

Lemma 1. *Given vector fields $\mathbf{v}_{\text{cond}}$ generating conditional probability paths $p(\mathbf{x}, t | \mathbf{x}_0)$, for any $\mathbf{x}_0 \sim p(\mathbf{x}_0)$, the expected conditional velocity field is equal to the marginal velocity field*

$$\mathbf{v}(\mathbf{x}, t) = \mathbb{E}_{\mathbf{x}_0 \sim p(\mathbf{x}_0) | \mathbf{x}_t = \mathbf{x}}[\mathbf{v}(\mathbf{x}, t | \mathbf{x}_0)]. \quad (1)$$

One-step Mean Flows. Iterative integration of $\mathbf{v}(\mathbf{x}, t)$ at inference is expensive and can be numerically unstable. To bypass it, Mean Flows [21] learn a two-parameter average velocity field $\mathbf{u}(\mathbf{x}, r, t)$

through regressing an identity along the flow trajectory $\mathbf{x}_\tau = \psi(\mathbf{x}_r, \tau)$ with terminal at $\mathbf{x}_t = \mathbf{x}$:

$$(t - r) \mathbf{u}(\mathbf{x}, r, t) = \int_r^t \mathbf{v}(\mathbf{x}_\tau, \tau) d\tau. \quad (2)$$

Differentiating with respect to the terminal time t along the same trajectory yields

$$\mathbf{u}(\mathbf{x}, r, t) + (t - r) \frac{d}{dt} \mathbf{u}(\mathbf{x}, r, t) = \mathbf{v}(\mathbf{x}, t), \quad \frac{d}{dt} \mathbf{u} = \partial_{\mathbf{x}} \mathbf{u} \cdot \mathbf{v}(\mathbf{x}, t) + \partial_t \mathbf{u}, \quad (3)$$

where the total derivative $\frac{d}{dt} \mathbf{u}$ is essentially a JVP, denoted by $\text{JVP}(\mathbf{u}, (\mathbf{x}, r, t), (\mathbf{v}(\mathbf{x}, t), 0, 1))$. The original MeanFlow paper [21] replaces *both* occurrences of the marginal field with the conditional field $\mathbf{v}_{\text{cond}} = \mathbf{x}_1 - \mathbf{x}_0$, giving the MeanFlow loss

$$\mathcal{L}_{\text{MF}}(\boldsymbol{\theta}) = \mathbb{E}_{r, t, \mathbf{x}_0, \mathbf{x}_1} \left[\|\mathbf{u}_{\boldsymbol{\theta}} + (t - r) \text{sg}[\text{JVP}(\mathbf{u}_{\boldsymbol{\theta}}, (\mathbf{x}_t, r, t), (\mathbf{v}_{\text{cond}}, 0, 1))]\|_2^2 \right], \quad (4)$$

with $r, t \sim \mathcal{U}(0, 1)$, $r \leq t$, $\mathbf{x}_0 \sim p_{\text{data}}$, $\mathbf{x}_1 \sim \mathcal{N}(0, \mathbf{I}_d)$, $\mathbf{x}_t = (1 - t)\mathbf{x}_0 + t\mathbf{x}_1$, and the stop-gradient $\text{sg}[\cdot]$ avoiding double backpropagation through the JVP.

3 Variance Reduction in Learning Mean Flows

The MeanFlow loss in equation 4 is empirically known to be *non-decreasing* and to suffer from *high-variance gradients* [22, 23]. We investigate the statistical mechanism behind this pathology. Importantly, our analysis isolates the role of the conditional velocity field $\mathbf{v}_{\text{cond}}$ when it appears as the JVP tangent, and identifies that it acts as a Monte Carlo control variate for the inaccessible marginal velocity, with a coefficient that the original MeanFlow fixes to a suboptimal value. We derive the optimal coefficient and establish a connection to practical fixes in concurrent works.

3.1 Two roles of the conditional velocity field

With Reynolds decomposition, we express the conditional velocity by $\mathbf{v}_{\text{cond}} = \mathbf{v}(\mathbf{x}, t) + \mathbf{v}'$ with $\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t}[\mathbf{v}'] = \mathbf{0}$ according to equation 1 and $\Sigma_{\mathbf{v}'} \triangleq \text{Cov}_{\mathbf{x}_0 | \mathbf{x}_t}[\mathbf{v}']$. The MeanFlow loss in equation 4 uses $\mathbf{v}_{\text{cond}}$ both as the *regression target* and as the *tangent* inside the total derivative. Carrying the decomposition through per-sample loss $\ell_{\text{MF}}(\boldsymbol{\theta})$ yields:

$$\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t}[\ell_{\text{MF}}(\boldsymbol{\theta})] = \|\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}\|_2^2 + \text{sg}[\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^\top)], \quad (5)$$

where $\mathbf{J} \triangleq (t - r) \partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} - \mathbf{I}_d \in \mathbb{R}^{d \times d}$ is a *Jacobi factor* determined by the Jacobian matrix $\partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}}$ and $\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}} \triangleq \mathbf{u}_{\boldsymbol{\theta}} + (t - r) \text{sg}[\partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} \cdot \mathbf{v} + \partial_t \mathbf{u}_{\boldsymbol{\theta}}] - \mathbf{v}$ is the deterministic mean-field residual. Since the residual $\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}$ is the exact loss we aim to minimize given by equation 3, the trace term leads to the non-decreasing loss and eliminates *iff* the Jacobi satisfies $\partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} = \frac{1}{t - r} \mathbf{I}_d$ (equivalently, $\mathbf{J} = \mathbf{0}$). We identify two roles of the conditional velocity field in this decomposition:

Unbiased Target. As the regression target, $\mathbf{v}_{\text{cond}}$ injects $\mathbf{v}'$ *linearly* into the residual, contributing the *irreducible* per-sample noise floor $\text{Tr}(\Sigma_{\mathbf{v}'})$. However, since this noise is independent of $\boldsymbol{\theta}$ and $\mathbf{v}'$ is zero-mean, $\mathbf{v}_{\text{cond}}$ can serve as an unbiased target for learning Mean Flows.

Variance Amplifier. As the JVP tangent, the same $\mathbf{v}_{\text{cond}}$ injects $\mathbf{v}'$ *multiplicatively* through the Jacobi factor $\mathbf{J}$, contributing the *amplified* term $\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^\top)$. It scales unboundedly with the spectral magnitude of $\mathbf{J}$. This amplification is the dominant driver of variance at the gradient level:

Theorem 2 (Jacobian Variance Amplification). *Let $\mathbf{g} \triangleq \nabla_{\boldsymbol{\theta}} \mathbf{u}_{\boldsymbol{\theta}}(\mathbf{x}_t, r, t) \in \mathbb{R}^{d \times p}$ be the parameter Jacobian of the average velocity. The trace of the conditional gradient covariance (i.e., the total variance) of $\ell_{\text{MF}}(\boldsymbol{\theta})$ in equation 4 satisfies*

$$\text{Tr}(\text{Cov}[\nabla_{\boldsymbol{\theta}} \ell_{\text{MF}} | \mathbf{x}_t]) \propto \text{Tr}(\mathbf{g}^\top \mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J} \mathbf{g}). \quad (6)$$

See the proof in Appendix B. The theorem identifies that the total gradient variance grows with $\|\mathbf{J}\|^2$ for fixed $\mathbf{g}$ and $\Sigma_{\mathbf{v}'}$, saturates only at the irreducible noise floor when $\mathbf{J} \rightarrow \mathbf{0}$, and is *uncontrolled* by any term in the loss due to the use of the stop-gradient in the original MeanFlow. Meanwhile, without the stop-gradient operator, the optimizer could in principle reduce variance by driving $\mathbf{J} \rightarrow \mathbf{0}$. This establishes a *semi-gradient gap*, formally,




Figure 1: Spatial distribution of $\sqrt{\text{Tr}(\Sigma_{v'} | \mathbf{x}_t)} = \sqrt{\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t} \|\mathbf{v}'\|^2}$ at three timesteps on a two-dimensional Gaussian mixture. Conditional variances concentrate in mode-mixing regions.

Theorem 3 (Semi-Gradient Gap). *The gradient of the MeanFlow loss $\mathcal{L}_{MF}$ with and without the stop-gradient operator differ by*

$$\underbrace{2(t-r) \mathbb{E} \left[\left(\nabla_{\theta} (\partial_{\mathbf{x}_t} \mathbf{u}_{\theta} \cdot \mathbf{v} + \partial_t \mathbf{u}_{\theta}) \right)^{\top} \mathbf{r}_{\theta} \right]}_{\text{mean-field gradient difference}} + \underbrace{\mathbb{E} \left[\nabla_{\theta} \text{Tr}(\mathbf{J} \Sigma_{v'} \mathbf{J}^{\top}) \right]}_{\text{variance-driven gradient difference}}. \quad (7)$$

128

In the original MeanFlow, the stop-gradient operator prevents $\mathbf{J}$ from being passed to the optimizer, leading to an empirical non-decreasing loss. Meanwhile, the mean-field difference vanishes at convergence ($\mathbf{r}_{\theta} \rightarrow 0$) and the variance-driven term $\text{Tr}(\mathbf{J} \Sigma_{v'} \mathbf{J}^{\top})$ dominates. To better illustrate the idea, Figure 1 visualizes the spatial distribution of $\sqrt{\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t} \|\mathbf{v}'\|^2}$ on a three-mode, two-dimensional Gaussian mixture. It showcases that the total variance magnitude is non-zero, concentrates in mode-mixing regions where conditional paths overlap, and grows toward the latent endpoint ($t \rightarrow 1$).

3.2 Rethinking tangent as a control variate

The amplification in Theorem 2 arises due to using $\mathbf{v}_{\text{cond}} = \mathbf{v} + \mathbf{v}'$ as the JVP tangent injects the zero-mean fluctuation $\mathbf{v}'$. Hence, $\mathbf{v}_{\text{cond}}$ is analogous to the canonical structure of a Monte Carlo control variate [27], where $\mathbf{v}_{\text{cond}}$ is a stochastic estimator of the inaccessible $\mathbf{v}$ with known mean, and the coefficient on the noise term $\mathbf{v}'$ determines the bias-variance trade-off. To make this explicit, we introduce a tangent-mixing coefficient $\beta \in [0, 1]$:

$$\tilde{\mathbf{v}}_{\text{tang}}(\beta) \triangleq (1 - \beta) \mathbf{v}_{\text{cond}} + \beta \hat{\mathbf{v}} = \mathbf{v} + (1 - \beta) \mathbf{v}' + \beta \mathbf{b}, \quad (8)$$

where $\hat{\mathbf{v}}$ can be any deterministic proxy for the marginal velocity (e.g., a velocity network) with bias $\mathbf{b} \triangleq \hat{\mathbf{v}} - \mathbf{v}$ that is deterministic given $\mathbf{x}_t$. Herein, $\beta = 0$ recovers vanilla MeanFlow and $\beta = 1$ replaces the tangent entirely with the deterministic proxy.

Bias-variance trade-off. Substituting $\tilde{\mathbf{v}}_{\text{tang}}(\beta)$ for $\mathbf{v}_{\text{cond}}$ in the JVP tangent and propagating through the loss, the per-sample gradient writes

$$\mathbf{g}^{(\beta)} = 2\mathbf{g}^{\top} \left[\mathbf{r}_{\theta} + ((1 - \beta) \mathbf{J} - \beta \mathbf{I}) \mathbf{v}' + \beta (\mathbf{J} + \mathbf{I}) \mathbf{b} \right], \quad (9)$$

where the noise term scales the conditional fluctuation $\mathbf{v}'$ by the matrix $((1 - \beta) \mathbf{J} - \beta \mathbf{I})$, and the bias term scales the proxy error $\mathbf{b}$ by $\beta (\mathbf{J} + \mathbf{I})$. In this case, we can balance the bias-variance trade-off through solving for the optimal coefficient β^* that minimizes the least-squares between the expected per-sample gradient in equation 9 and the target gradients, given by

$$M(\beta) \triangleq \mathbb{E}_{\mathbf{v}' | \mathbf{x}_t} \left[\left\| \mathbf{g}^{(\beta)} - \nabla_{\theta} \mathbf{r}_{\theta} \right\|_2^2 \right] = \mathbb{E}_{\mathbf{v}' | \mathbf{x}_t} \left[\left\| \mathbf{g}^{(\beta)} - 2\mathbf{g}^{\top} \mathbf{r}_{\theta} \right\|_2^2 \right]. \quad (10)$$

We derive the following theorem.

Theorem 4 (Optimal control-variate coefficient). *Under the scalar-isotropic approximation $\Sigma_{v'} \approx \sigma^2 \mathbf{I}_d$, $\mathbf{J} \approx \kappa \mathbf{I}_d$, and the parameter-isotropy approximation $\mathbf{g} \mathbf{g}^{\top} \propto \mathbf{I}_d$ (which reduces M to a per-component MSE; cf. Appendix B),*

$$M(\beta) \propto \beta^2 (\kappa + 1)^2 \|\mathbf{b}\|^2 + \sigma^2 d ((1 - \beta) \kappa - \beta)^2. \quad (11)$$

Table 1: Concurrent MeanFlow remedies as special cases in our control-variate framework. Each method either drives $\beta \rightarrow 1$ with a deterministic proxy, directly reduces the norm of amplification factor $\|\mathbf{J}\|^2$, or replaces the JVP construction altogether.

Method	Mechanism in our framework	Practical realization
AlphaFlow [22]	avoid high- κ regimes	α -curriculum schedule
Improved MF [23]	deterministic tangent ($\beta \rightarrow 1$)	separate velocity head + sg
Modular MF [29]	deterministic tangent ($\beta \rightarrow 1$)	gradient-modulated loss family
Kim <i>et al.</i> [30]	deterministic tangent ($\beta \rightarrow 1$)	staged training schedule
TVM [25]	remove the spatial Jacobian ($\mathbf{J} \rightarrow \mathbf{0}$)	terminal-time differentiation
Re-MeanFlow [24]	reduce $\ \mathbf{J}\ $	rectified-flow preprocessing
Decoupled MF [31]	bypass JVP construction	flow-map conditioning on later t

154 For $\kappa > 0$, $M(\beta)$ admits a unique minimizer

$$\beta^* = \underbrace{\frac{\kappa}{\kappa+1}}_{\text{noise-cancellation}} \cdot \underbrace{\frac{\sigma^2 d}{\sigma^2 d + \|\mathbf{b}\|^2}}_{\text{shrinkage}}, \quad (12)$$

155 with optimum value $M(\beta^*) \propto \sigma^2 d \kappa^2 \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2)$.

156 See the proof in Appendix B. The two components of β^* play distinct roles: $\kappa/(\kappa+1)$ is the coef-
 157 ficient that *cancels the Jacobian-amplified noise* through destructive interference between the $\mathbf{J}\mathbf{v}'$
 158 and $\mathbf{I}\mathbf{v}'$ contributions in equation 9, while $\sigma^2 d/(\sigma^2 d + \|\mathbf{b}\|^2)$ is the standard James-Stein shrink-
 159 age [28] that pulls β^* toward the unbiased corner when the proxy bias $\|\mathbf{b}\|$ is large. Therefore, as
 160 the proxy bias shrinks ($\|\mathbf{b}\|^2 \rightarrow 0$), $\beta^* \rightarrow \kappa/(\kappa+1)$, and as the Jacobian magnitude grows ($\kappa \rightarrow \infty$),
 161 $\beta^* \rightarrow 1$. Following the theory, we explain the high variance of gradients in the original MeanFlow
 162 and establish a connection to practical fixes in concurrent work.

163 **High-variance gradient with suboptimal coefficient.** The original MeanFlow uses $\beta = 0$ which
 164 is optimal only when $\kappa = 0$ (i.e., $\partial_{\mathbf{x}_t} \mathbf{u}_\theta = \frac{1}{t-r} \mathbf{I}_d$) or when no deterministic proxy is available
 165 ($\|\mathbf{b}\| = \infty$). Both conditions fail in practice: trained backbones produce $\partial_{\mathbf{x}_t} \mathbf{u}_\theta$ matrices that are
 166 spectrally far from $\frac{1}{t-r} \mathbf{I}_d$, and there are multiple viable deterministic proxies for the marginal $\mathbf{v}$.

167 **Concurrent works as control variates.** Our theory unifies several remedies for MeanFlow’s train-
 168 ing pathology across concurrent works into a single one-parameter family. Each empirical fix corre-
 169 sponds to a different practical realization of the optimum β^* , distinguished by *which proxy* they use
 170 for $\mathbf{v}$ and *which value of β* the construction implicitly selects. We summarize them in table 1.

171 4 Related Work

172 **Variance reduction in learning flow-based models.** Several recent works address variance in
 173 learning flow-based models from complementary perspectives. Stable Velocity [32] reveals a two-
 174 regime variance structure in flow matching and proposes composite conditioning; TPC [33] re-
 175 duces variance through temporal pair coupling; and preconditioned flow matching [34] addresses
 176 ill-conditioning via anisotropic preconditioning. Bertrand et al. [35] argue that stochastic-target
 177 variance is negligible for standard flow matching, consistent with our analysis, since the problem-
 178 atic amplification we identify is specific to the MeanFlow JVP, not the flow-matching loss itself.
 179 Rectified flows [36, 37] reduce trajectory curvature by iterative straightening, which by Theorem 2
 180 reduces $\|\mathbf{J}\|^2$ and hence the amplified noise term.

181 **Control variates and target networks.** The control-variate framework we apply has classical roots
 182 in Monte Carlo estimation [38]; it is also the analytical structure underlying target networks in deep
 183 RL [39] and self-distillation in self-supervised learning [40]. We make the connection explicit by
 184 interpreting the EMA-derived tangent in MeanFlow as a target-network-style proxy that drives the
 185 control-variate coefficient toward its optimum.




Figure 2: Empirical total gradient variance $\text{Tr}(\text{Cov}[\nabla_{\theta} \ell_{\text{MF}}])$ on six two-dimensional toy datasets with $\beta \in \{0, 0.25, 0.5, 0.75, 1\}$. The monotonic decrease of variances with respect to β on almost every dataset aligns with the prediction in Theorem 2.

5 Experiments

We empirically validate our theory in Section 3 through probing the bias-variance trade-offs. Specifically, we sweep the tangent-mixing coefficient $\beta \in [0, 1]$ end-to-end and compare the results to the closed-form prediction based on Theorem 4.

Instantiation of the $\beta = 1$ corner. To validate the framework empirically, we need a concrete realization of β that we can sweep at scale. We replace the JVP tangent by an exponential moving-average [41] deterministic proxy $\hat{v} \leftarrow \mathbf{u}_{\theta}(\mathbf{x}_t, t, t)$, and use a small flow-matching loss at $r = t$ to keep the proxy bias $\mathbf{b} = \hat{v} - \mathbf{v}$ small and bound the bias term $\beta(\mathbf{J} + \mathbf{I})\mathbf{b}$ in equation 9. We keep the regression target $\mathbf{v}_{\text{cond}}$ unchanged, exploiting the role asymmetry identified in section 3.1. Appendix C provides details about the full loss, training algorithm, and three propositions characterizing the resulting gradient form, residual bias, and the necessity of the target-tangent role split.

Experiment Setup. We evaluate our theory on three regimes leveraging six two-dimensional toy datasets, dense Gaussian mixtures (DGMM) with various dimensions $d \in \{2, 4, 8, 16, 32, 64\}$, and training DiT-B/4 [42] on ImageNet with Stable Diffusion latents¹. On the 2-D toy and DGMM datasets, we use a three-layer MLP with 128 hidden units, train for 200,000 steps with batch size 256 and three random seeds $\{42, 0, 1\}$, and sweep the eleven-point grid $\beta \in \{0.0, 0.1, \dots, 1.0\}$ for the sample-quality, evaluated by final-step sliced Wasserstein-1 distance (SW_1) on 4096 samples with 500 random projections under a fixed projection seed. On the toy datasets, we additionally run a sub-sweep at $\beta \in \{0, 0.25, 0.5, 0.75, 1\}$ that investigates the per-step total gradient variance $\text{Tr}(\text{Cov}[\nabla_{\theta} \ell_{\text{MF}}])$ using $K = 8$ replica of mini-batches, each with 256 samples, every 2,000 steps and tail-averages over the second half of training. For the DiT, we perform a four-point sweep $\beta \in \{0, 0.25, 0.5, 1\}$ and train the model for 300k steps following the recipe in the original MeanFlow [21]. We defer the full setup, FID table, and direct matrix-form measurement of β^* are to Appendix D.3.

5.1 Variance reduction

Figure 2 reports the total gradient variances $\text{Tr}(\text{Cov}[\nabla_{\theta} \ell_{\text{MF}}])$ on all six 2-D datasets. We observe monotonic decreasing variances with respect to β on almost every dataset. The empirical ordering tracks the variance term $\sigma^2 d((1-\beta)\kappa - \beta)^2$ from Theorem 2 and Theorem 4, empirically validate that the conditional fluctuation $\mathbf{v}'$ is the dominant variance source in the MeanFlow gradients. Meanwhile, we notice that the reduction magnitude varies with the spectral magnitude $\|\mathbf{J}\|$ of the backbone model. The largest reductions appear on the *high-curvature* datasets (e.g., *eight_gaussians*,

¹<https://huggingface.co/enterprise-explorers/sd-vae-ft-mse-flax>




Figure 3: Empirical sample-quality measured by sliced Wasserstein-1 distance $SW_1(\beta)$ on six 2-D toy datasets with $\beta \in \{0.0, 0.1, \dots, 1.0\}$. Bars are grouped by dataset and colored by β with standard error bar. The red star marks the empirical optimal coefficient β^* . Five of six datasets settle at $\beta^* \in \{0.8, 1.0\}$ near the deterministic-tangent corner; `two_spirals` alone settles at $\beta^* = 0$.

Table 2: DGMM β -sweep summary across dimensions $d \in \{2, 4, 8, 16, 32, 64\}$. The quality gap column marks reduction that exceed one standard error mean with $\dagger$. SW_1 is essentially β -insensitive at $d \leq 32$, while only $d = 64$ shows a tentative interior minimum.

d	$SW_1(\beta=0)$	$SW_1(\beta = \beta^*)$	Quality Gap	β^*
2	0.152 ± 0.022	0.146 ± 0.015	$\sim 4\%$	1.0
4	0.083 ± 0.011	0.083 ± 0.011	$< 1\%$	0.8
8	0.062 ± 0.003	0.062 ± 0.003	$\sim 1\%$	1.0
16	0.044 ± 0.002	0.044 ± 0.003	$< 1\%$	1.0
32	0.034 ± 0.001	0.033 ± 0.001	$< 1\%$	0.1
64	0.028 ± 0.003	0.025 ± 0.001	$\sim 9\%^\dagger$	0.4

checkerboard), and the smallest (1.20 $\times$) on `two_spirals`. This is consistent to our theory: low geometric curvature pushes the network toward the flat regime $\partial_{\mathbf{x}_t} \mathbf{u}_\theta \rightarrow \frac{1}{t-r} \mathbf{I}_d$, corresponding to $\kappa \approx 0$, and our theorem 4 predicts both a small per-step variance reduction and a left-shift of optimal coefficient $\beta^* \rightarrow 0$ given by the noise-cancellation factor $\kappa/(\kappa+1)$.

5.2 Bias-variance trade-offs

Whereas $\text{Tr}(\text{Cov}[\nabla_{\theta} \ell_{\text{MF}}])$ reveals the variance reduction induced by β , the sample-quality measured by $SW_1(\beta)$ exposes the full bias-variance trade-off. Figure 3 traces $SW_1(\beta)$ across the full 11-point grid on six 2-D toy datasets. On the five high-curvature datasets, the empirical β^* falls in between $\{0.8, 1.0\}$, recovering the predicted $\beta \rightarrow 1$ location with a small bias norm $\|\mathbf{b}\|_2^2$ when the EMA proxy is accurate. On the lower-curvature `two_spirals` dataset, consistent with section 5.1, the geometry drives $\partial_{\mathbf{x}_t} \mathbf{u}_\theta \rightarrow \frac{1}{t-r} \mathbf{I}_d$, essentially pushing κ toward zero. The predicted β^* then shrinks toward the unbiased corner $\beta = 0$ through the noise-cancellation factor $\kappa/(\kappa+1)$ in Theorem 4, and the empirical sweep result concurs. Meanwhile, we are surprised that the $\beta^* = 1$ instantiation reduces SW_1 by 54% compared to the original MeanFlow ($\beta = 0$) on the `swiss_roll` dataset.

5.3 Scaling with feature dimensions

We investigate whether our theory holds with increasing in feature dimensions by sweeping the coefficient $\beta \in \{0, 0.1, \dots, 1\}$ on dense Gaussian mixture (DGMM) datasets in $\mathbb{R}^d$, varying $d \in \{2, 4, 8, 16, 32, 64\}$. Table 2 summarizes the sample-quality gap between the original MeanFlow with $\beta=0$ and the empirical β^* at each d . We report full results in Table 5 of Appendix D. On low-dimensional datasets with $d \in \{2, 4, 8, 16, 32\}$, SW_1 is essentially β -insensitive, where the quality gap between $\beta=0$ and β^* stays within one standard error of the mean (SEM). This is consistent with the prediction from theorem 4 when the EMA proxy yields small $\|\mathbf{b}\|_2^2$. The noise-cancellation factor $\kappa/(\kappa+1)$ saturates near 1 across the whole β range, leading to flat $SW_1(\beta)$. At $d=64$ the data hints at an interior minimum at $\beta^* = 0.4$ with a $\sim 9\%$ reduction over $\beta=0$, consistent with κ coming off




Figure 4: Experiment results training DiT-B/4 on ImageNet-256. *Left*: Per-step loss variance under the stochastic ($\beta = 0$) versus deterministic ($\beta = 1$) tangent, measured on the baseline ($\beta = 0$) checkpoint with the same data and noise. The deterministic-tangent variance is roughly t -flat while the stochastic-tangent variance grows by two orders of magnitude with t , confirming the Jacobi-factor amplification of Theorem 2. *Right*: FID at converge with respect to different β . We report empirical $\Delta\text{FID}(\beta) = \text{FID}(\beta) - \text{FID}(\beta = 0)$ at the matched training step 295k with different β . The dashed gray curve is the quadratic $c\beta^2$. The FID at converge with $\beta = 1$ sits a factor of ~ 2.6 above the quadratic curve, indicating a super-linear relationship between the FID and the bias. The optimal coefficient calculated in matrix form is $\beta_{\text{matrix}}^* \approx 0.94$.

saturation with increasing data dimension d . In the following section 5.4, we will showcase that the same observation is consistent with larger and more complicated DiT model, where $\beta_{\text{matrix}}^* \approx 0.94$ also sits short of the deterministic-tangent corner.

5.4 Latent Diffusion Transformers on ImageNet

We further investigate whether our theory generalizes to large model with high-dimensional features. Figure 4 shows two complementary measurements from the experiments with DiT-B/4 on ImageNet. The left panel in Figure 4 validates that the gradient-variance reduction predicted by Theorem 2 carries over from 2-D toy benchmark datasets to DiT. Herein, we directly measure the per-step loss variance using the model trained with the original MeanFlow loss, using two distinct tangents: the stochastic conditional-velocity tangent $\mathbf{v}_{\text{cond}}$ and the deterministic EMA tangent $\mathbf{u}_{\hat{\theta}}(\mathbf{x}_t, t, t)$. We observe that the loss variance with deterministic-tangent stays roughly flat across t , while the stochastic-tangent variance grows by two orders of magnitude. The widening gap directly validates the Jacobi-factor amplification of Theorem 2, where the stochastic tangent passes the conditional-velocity noise through $\mathbf{J} = (t-r)\partial_{\mathbf{x}_t}\mathbf{u} - \mathbf{I}$, which the deterministic tangent eliminates by construction. We observe the same pattern using checkpoint of the $\beta = 1$ instantiation (see appendix D.3), confirming that the amplification is a property of the architecture and data.

The right panel in Figure 4 visualizes the FID at converge as a function of β , with y -axis the empirical $\Delta\text{FID}(\beta) \triangleq \text{FID}(\beta) - \text{FID}(\beta = 0)$. The result shows that an ordering of $\text{FID}(\beta = 0) < \text{FID}(\beta = 0.25) < \text{FID}(\beta = 0.5) < \text{FID}(\beta = 1)$ holds at matched-step checkpoints. We report per-checkpoint values in Table 6 of Appendix D.3. The result establishes the following observation:

FID-MSE landscape mismatch. We report the direct measurement of both ingredients in Theorem 4 on the DiT checkpoints, including the EMA-tracking proxy $\|\widehat{\mathbf{b}}\|^2$ and the irreducible noise floor $\sigma^2 d$, in Appendix D.3. The result predicts an optimal β^* in the interior range $[0.46, 0.50]$ under the scalar-isotropic approximation, while the matrix-form β_{matrix}^* is even larger (see below). The empirical ordering of FID at convergence is hence consistent with the prediction. To test whether FID tracks the gradient-MSE *quantitatively*, we fit a MSE-prediction curve $c\beta^2$ and compare the $\beta = 1$ offset, where c is given by

$$c \leftarrow \arg \min_{c \in \mathbb{R}} \|\Delta\text{FID}(\beta) - c\beta^2\|_2^2, \quad \beta \in \{0.0, 0.25, 0.5\}. \quad (13)$$

Figure 4 shows a $\sim 2.6\times$ super-linear amplification along the ΔFID axis, indicating that the FID over-penalizes bias relative to gradient MSE. As a consequence, the FID-optimal β shifts past the gradient-MSE interior minimizer all the way to the unbiased corner $\beta = 0$.

271 To verify that our isotropic approximation in theorem 4 is not artifactual, we directly measured a
 272 matrix-form upper bound on β_{matrix}^* on the baseline checkpoint by sampling actual $\mathbf{v}'$ values from
 273 the conditional distribution (see Appendix B). The estimator omits the bias term $\|(\mathbf{J}+\mathbf{I})\mathbf{b}\|^2$ from
 274 the denominator, giving

$$\beta_{\text{no bias}}^* \triangleq \text{Tr}(\mathbf{J}\Sigma_{\mathbf{v}'}(\mathbf{J}+\mathbf{I})^\top) / \text{Tr}((\mathbf{J}+\mathbf{I})\Sigma_{\mathbf{v}'}(\mathbf{J}+\mathbf{I})^\top) \geq |\beta_{\text{matrix}}^*|, \quad (14)$$

275 since the omitted bias term is *non-negative*. We evaluate the bound at $t \in \{0.1, 0.3, 0.5, 0.7, 0.9\}$
 276 with fixed gap $t - r = 0.25$, and 512 samples per t using $\mathbf{u}_\theta(\mathbf{x}_t, t, t)$ as the marginal-velocity
 277 proxy. The numerator is *strictly positive* at every probed t , ruling out the unbiased-corner regime
 278 $\beta_{\text{matrix}}^* \leq 0$. Aggregated across t , we have $\beta_{\text{no bias}}^* \approx 0.94$, which is close to the deterministic-tangent
 279 corner and *larger* than the scalar-isotropic estimate $\beta^* \in [0.46, 0.50]$. The full β_{matrix}^* then lies
 280 in $(0, 0.94]$. Herein, we do not pin down the exact value due to the inaccessible true model bias
 281 $\mathbf{b} = \mathbf{u}_\theta(\mathbf{x}_t, t, t) - \mathbf{v}(\mathbf{x}_t, t)$ on ImageNet without access to the conditional distribution $p(\mathbf{x}_0 | \mathbf{x}_t)$.
 282 The matrix-form measurement further strengthens, rather than weakens, the FID-MSE mismatch:
 283 the gradient-MSE optimum sits in $(0, 0.94]$ while the FID optimum sits at the unbiased corner $\beta = 0$.

284 6 Conclusion

285 In this paper, we establish a theory from the perspective of Monte Carlo control variates that isolates
 286 the statistical structure of training pathology in the original MeanFlow. We identify two distinct
 287 roles the conditional velocity plays in the loss, and the original objective assigns the wrong coef-
 288 ficient to one of them. Following the theory, we derive the optimal tangent-mixing coefficient for
 289 the control variate in closed form. In our experiment, we conduct a controlled sweep of the coeffi-
 290 cient to recover the predicted bias-variance trade-offs, scaling from two-dimensional toy datasets to
 291 a large-scale DiT-B/4 model on ImageNet-256 scale. In addition, our experiment with DiT reveals
 292 a quantitative *FID-MSE landscape mismatch*, where the optimal coefficient given by minimizing
 293 matrix-form MSE sits at $\beta^* \approx 0.94$ while the optimal coefficient minimizing the FID leans towards
 294 the unbiased corner $\beta = 0$, with a super-linear relationship between the empirical FID($\beta = 1$) and
 295 the bias. We discuss practical insights and limitations below.

296 **Practical insights.** Our Theorem 4 predicts two factors that determines the empirical β^* through
 297 the data-dependent κ and model bias $\|\mathbf{b}\|^2$. Selecting the appropriate β reflects the balance between
 298 bias and variance. Thereby, when gradient stability is the primary concern, we recommend toggling
 299 β toward the corner $\kappa/(\kappa+1)$, which is attainable through an EMA proxy $\mathbf{u}_\theta(\mathbf{x}, t, t)$ with $O(1)$.
 300 When sample quality is the primary metric, our DiT experiment suggests toggling β back toward 0
 301 or annealing β with respect to $\|\mathbf{b}\|_2^2$ until the FID bias penalty becomes negligible. A metric-aware β
 302 schedule that interpolates between these regimes during training is a promising direction for future
 303 work.

304 **Limitations.** We acknowledge several limitations of this work: (i) *Scalar-isotropic approximation*.
 305 Our Theorem 4 is derived under $\mathbf{J} \approx \kappa \mathbf{I}_d$ and $\Sigma_{\mathbf{v}'} \approx \sigma^2 \mathbf{I}_d$. In the full diagonal matrix-valued set-
 306 ting the optimum is direction-dependent: a per-direction $\beta_i = \frac{\mathbf{J}_{ii}}{\mathbf{J}_{ii}+1} \cdot \frac{\sigma_i^2}{\sigma_i^2+b_i^2}$ would minimize the
 307 per-component gradient MSE, and a single global β trades off residual variance across directions.
 308 This assumption may be valid for backbones whose Jacobian spectrum is concentrated, but it may
 309 fail for more complex models or highly anisotropic data. (ii) *FID-aware loss design*. Our exper-
 310 iment characterizes the FID-MSE mismatch but does not derive an FID-aware loss or β schedule,
 311 which remains an open question. (ii) *Non-Euclidean data*. We conduct our experiment in the Eu-
 312 clidean space $\mathbb{R}^d$. Extending the closed-form β^* to manifold MeanFlow [43] is straightforward at
 313 the gradient level but requires care in defining the second moment $\text{Tr}(\Sigma_{\mathbf{v}'})$ on tangent spaces.

314 **Future work.** There are three promising future directions. First, we argue that our control-variate
 315 diagnosis applies to any self-supervised one-step generative model that bootstraps a parametrized
 316 map as the JVP-style total derivative in MeanFlow, including consistency models [18] and shortcut
 317 models [44]. Meanwhile, a per-sample scalar coefficient driven by online estimates of κ and $\|\mathbf{b}\|_2^2$
 318 can potentially close the global-vs-per-sample and the scalar-vs-matrix gap during training. Last but
 319 not least, an adaptive schedule that interpolates between the gradient-MSE optimum and the FID-
 320 optimal corner, calibrated by either a learned proxy or proxy-quality validation FID, could resolve
 321 the FID-MSE mismatch we identified.

References

- [1] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 6840–6851. Curran Associates, Inc., 2020.
- [2] Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021.
- [3] Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In *Advances in Neural Information Processing Systems*, volume 35, 2022.
- [4] Prafulla Dhariwal and Alexander Nichol. Diffusion models beat GANs on image synthesis. In *Advances in Neural Information Processing Systems*, volume 34, 2021.
- [5] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Naveen Rafi, Tim Shafir, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, 2024.
- [6] Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David K. Duvenaud. Neural ordinary differential equations. In *Advances in Neural Information Processing Systems*, volume 31, 2018.
- [7] Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 1530–1538, 2015.
- [8] Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using Real-NVP. In *International Conference on Learning Representations*, 2017.
- [9] Will Grathwohl, Ricky T. Q. Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. FFJORD: Free-form continuous dynamics for scalable reversible generative models. In *International Conference on Learning Representations*, 2019.
- [10] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling, 2023.
- [11] Alexander Tong, Kilian Fatras, Nikolay Malkin, Guillaume Huguët, Yanlei Zhang, Jarrod Rector-Brooks, Guy Wolf, and Yoshua Bengio. Improving and generalizing flow-based generative models with minibatch optimal transport, 2024.
- [12] Michael S. Albergo and Eric Vanden-Eijnden. Building normalizing flows with stochastic interpolants, 2023.
- [13] Michael Albergo, Nicholas M. Boffi, and Eric Vanden-Eijnden. Stochastic interpolants: A unifying framework for flows and diffusions. *Journal of Machine Learning Research*, 26(209):1–80, 2025.
- [14] Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In *Advances in Neural Information Processing Systems*, volume 32, 2019.
- [15] Tim Salimans and Jonathan Ho. Progressive distillation for fast sampling of diffusion models, 2022.
- [16] Tianwei Yin, Michaël Gharbi, Richard Zhang, Eli Shechtman, Frédo Durand, William T. Freeman, and Taesung Park. One-step diffusion with distribution matching distillation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 6613–6623, June 2024.
- [17] Tianwei Yin, Michaël Gharbi, Taesung Park, Richard Zhang, Eli Shechtman, Frédo Durand, and William T. Freeman. Improved distribution matching distillation for fast image synthesis. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang, editors, *Advances in Neural Information Processing Systems*, volume 37, pages 47455–47487. Curran Associates, Inc., 2024.
- [18] Yang Song, Prafulla Dhariwal, Mark Chen, and Ilya Sutskever. Consistency models. In *Proceedings of the 40th International Conference on Machine Learning, ICML’23*. JMLR.org, 2023.
- [19] Cheng Lu and Yang Song. Simplifying, stabilizing and scaling continuous-time consistency models, 2025.
- [20] Nicholas M. Boffi, Michael S. Albergo, and Eric Vanden-Eijnden. Flow map matching with stochastic interpolants: A mathematical framework for consistency models, 2025.

- [21] Zhengyang Geng, Mingyang Deng, Xingjian Bai, J. Zico Kolter, and Kaiming He. Mean flows for one-step generative modeling, 2025.
- [22] Huijie Zhang, Aliaksandr Siarohin, Willi Menapace, Michael Vasilkovsky, Sergey Tulyakov, Qing Qu, and Ivan Skorokhodov. Alphaflow: Understanding and improving meanflow models, 2025.
- [23] Zhengyang Geng, Yiyang Lu, Zongze Wu, Eli Shechtman, J. Zico Kolter, and Kaiming He. Improved mean flows: On the challenges of fastforward generative models, 2025.
- [24] Xinxi Zhang, Shiwei Tan, Quang Nguyen, Quan Dao, Ligong Han, Xiaoxiao He, Tunyu Zhang, Chengzhi Mao, Dimitris Metaxas, and Vladimir Pavlovic. Overcoming the curvature bottleneck in meanflow, 2026.
- [25] Linqi Zhou, Mathias Parger, Ayaan Haque, and Jiaming Song. Terminal velocity matching, 2026.
- [26] Zhiqi Li, Yuchen Sun, Greg Turk, and Bo Zhu. Functional mean flow in hilbert space, 2025.
- [27] Paul Glasserman. *Monte Carlo methods in financial engineering*, volume 53. Springer New York, NY, 2003.
- [28] William James, Charles Stein, et al. Estimation with quadratic loss. In *Proceedings of the fourth Berkeley symposium on mathematical statistics and probability*, volume 1, pages 361–379. University of California Press, 1961.
- [29] Haochen You, Baojing Liu, and Hongyang He. Modular meanflow: Towards stable and scalable one-step generative modeling, 2025.
- [30] Jin-Young Kim, Hyojun Go, Lea Bogensperger, Julius Erbach, Nikolai Kalischek, Federico Tombari, Konrad Schindler, and Dominik Narnhofer. Understanding, accelerating, and improving meanflow training, 2025.
- [31] Kyungmin Lee, Sihyun Yu, and Jinwoo Shin. Decoupled meanflow: Turning flow models into flow maps for accelerated sampling, 2025.
- [32] Donglin Yang, Yongxing Zhang, Xin Yu, Liang Hou, Xin Tao, Pengfei Wan, Xiaojuan Qi, and Renjie Liao. Stable velocity: A variance perspective on flow matching, 2026.
- [33] Chika Maduabuchi and Jindong Wang. Temporal pair consistency for variance-reduced flow matching, 2026.
- [34] Shadab Ahamed, Eshed Gal, Simon Ghyselincks, Md Shahriar Rahim Siddiqui, Moshe Eliasof, and Eldad Haber. Preconditioned score and flow matching, 2026.
- [35] Quentin Bertrand, Anne Gagneux, Mathurin Massias, and Rémi Emonet. On the closed-form of flow matching: Generalization does not arise from target stochasticity, 2025.
- [36] Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow, 2022.
- [37] Sangyun Lee, Zinan Lin, and Giulia Fanti. Improving the training of rectified flows. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang, editors, *Advances in Neural Information Processing Systems*, volume 37, pages 63082–63109. Curran Associates, Inc., 2024.
- [38] Peter W. Glynn and Roberto Szechtman. Some new perspectives on the method of control variates. *Monte Carlo and Quasi-Monte Carlo Methods 2000*, pages 27–49, 2002.
- [39] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, et al. Human-level control through deep reinforcement learning. *Nature*, 518:529–533, 2015.
- [40] Jean-Bastien Grill, Florian Strub, Florent Altché, et al. Bootstrap your own latent: A new approach to self-supervised learning. In *NeurIPS*, 2020.
- [41] Boris T. Polyak and Anatoli B. Juditsky. Acceleration of stochastic approximation by averaging. *SIAM Journal on Control and Optimization*, 30(4):838–855, 1992.
- [42] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4195–4205, 2023.
- [43] Dongyeop Woo, Marta Skreta, Seonghyun Park, Kirill Neklyudov, and Sungsoo Ahn. Riemannian mean-flow, 2026.
- [44] Kevin Frans, Danijar Hafner, Sergey Levine, and Pieter Abbeel. One step diffusion via shortcut models, 2025.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [Yes]

Justification: The claims in the abstract and introduction highlight the three primary contributions explicitly, including the control-variate diagnosis for the MeanFlow’s training pathology and the closed-form optimal coefficient in section 3, and the numerical results from our empirical study in section 5.

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: We explicitly discuss our limitations in a paragraph of section 6.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren’t acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: All theorems and propositions we establish in section 3 are numbered, cross-referenced, and come with a clear description of the assumptions. We provide complete and extensive proofs in the supplementary material.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: All the primary practical information to run the two-dimensional experiments and DiT on ImageNet are clearly stated in the main text, with further details given in the supplementary material.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in

some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: We will release the JAX/Flax implementation for our primary experiments upon the acceptance of this paper.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: We have an experiment setup paragraph in section 5 elaborating all the details for the experiments.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: For toy and DGMM experiments, every reported number aggregates three random seeds {42, 0, 1} with the standard error of the mean reported alongside. The four-point ordering claim in the DiT experiment on ImageNet is supported across 54 consecutive matched-step checkpoints, which provides a within-run measure of consistency rather than across-seed variance.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Compute resources are reported in detail in Appendix D.3 (TPU v4-32 for the DiT-B/4 / ImageNet-256 runs, ~ 1 – 1.5 days per run; the $\beta = 0$ baseline crashed mid-training and was resumed from the 240k checkpoint to reach 295k) and Section 5 (single consumer GPU for the toy and DGMM β -sweeps; ~ 2 minutes per toy run, ~ 5 minutes per DGMM run; 198 toy runs + 198 DGMM runs + a 20-run gradient-variance sub-sweep).

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The study is theoretical and methodological and compliant with the NeurIPS code of ethics.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [N/A]

Justification: The study in this paper comes with a theoretical nature. There is no direct broader impact to declare at this moment.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: This paper does not pose any of such risks.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: We cited all external assets in the references, including the ImageNet dataset, the stable Diffusion VAE for inference, the DiT architecture, the original MeanFlow algorithm, and concurrent works.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [N/A]

Justification: The paper does not release any new asset at this moment.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: Neither does this paper involve any crowdsourcing nor research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

733 Question: Does the paper describe potential risks incurred by study participants, whether
734 such risks were disclosed to the subjects, and whether Institutional Review Board (IRB)
735 approvals (or an equivalent approval/review based on the requirements of your country or
736 institution) were obtained?

737 Answer: [N/A]

738 Justification: Neither does this paper involve any crowdsourcing nor research with human
739 subjects.

740 Guidelines:

- 741 • The answer [N/A] means that the paper does not involve crowdsourcing nor research
742 with human subjects.
- 743 • Depending on the country in which research is conducted, IRB approval (or equiva-
744 lent) may be required for any human subjects research. If you obtained IRB approval,
745 you should clearly state this in the paper.
- 746 • We recognize that the procedures for this may vary significantly between institutions
747 and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the
748 guidelines for their institution.
- 749 • For initial submissions, do not include any information that would break anonymity
750 (if applicable), such as the institution conducting the review.

751 16. Declaration of LLM usage

752 Question: Does the paper describe the usage of LLMs if it is an important, original, or
753 non-standard component of the core methods in this research? Note that if the LLM is used
754 only for writing, editing, or formatting purposes and does *not* impact the core methodology,
755 scientific rigor, or originality of the research, declaration is not required.

756 Answer: [N/A]

757 Justification: This paper does not involve LLMs as a primary component.

758 Guidelines:

- 759 • The answer [N/A] means that the core method development in this research does not
760 involve LLMs as any important, original, or non-standard components.
- 761 • Please refer to our LLM policy in the NeurIPS handbook for what should or should
762 not be described.

763 **Supplementary Material**

764	A Notations	20
765	B Proofs	21
766	B.1 Proof of Lemma 1	21
767	B.2 Proof of Theorem 2 (Jacobian Variance Amplification)	21
768	B.3 Proof of Theorem 3 (Semi-Gradient Gap)	22
769	B.4 Proof of Theorem 4 (Optimal Control-Variate Coefficient)	22
770	B.5 Proof of Proposition 1 (Gradient under the $\beta = 1$ corner loss)	24
771	B.6 Proof of Proposition 2 (Bias-Variance Tradeoff)	24
772	B.7 Proof of Proposition 3 (Target/Tangent Bias Asymmetry)	24
773	C Implementation Details	25
774	D Additional Results	26
775	D.1 2-D Toy Benchmark	26
776	D.2 Full DGMM β -sweep grid	26
777	D.3 DiT-B/4 / ImageNet-256 Latent-Space Training	27

To promote the readability of our readers, table 3 lists all the notations we use in this work.

Table 3: Table of notations.

Notation	Description
<i>Scalars</i>	
d	Dimension of the data samples
p	Number of parameters in the model
c	Coefficient in the fitted gradient-MSE curve $c\beta^2$
<i>State vectors and velocity fields</i>	
$\mathbf{x}, \mathbf{x}_t$	Random data sample / state at interpolant time t
$\mathbf{x}, \mathbf{x}_t$	Realized state / state at time t
$\mathbf{v}(\mathbf{x}, t)$	Marginal velocity field
$\mathbf{v}_{\text{cond}}$	Conditional velocity $\mathbf{v}_{\text{cond}} \triangleq \mathbf{v}(\mathbf{x}, t \mathbf{x}_0)$.
$\mathbf{v}'$	Conditional velocity fluctuation: $\mathbf{v}' = \mathbf{v}_{\text{cond}} - \mathbf{v}(\mathbf{x}, t)$
$\hat{\mathbf{v}}$	Deterministic proxy for the marginal velocity field $\mathbf{v}$
<i>Model</i>	
$\mathbf{u}_{\theta}(\mathbf{x}, r, t)$	Two-parameter average velocity field with parameters θ
$\mathbf{u}_{\bar{\theta}}$	Copy of $\mathbf{u}_{\theta}$ with exponential moving-average parameters $\bar{\theta}$
<i>Spatial-Jacobian quantities</i>	
$\partial_{\mathbf{x}_t} \mathbf{u}_{\theta}$	Spatial Jacobian of $\mathbf{u}_{\theta}$ with respect to state $\mathbf{x}_t$
$\mathbf{J}$	Jacobi factor: $\mathbf{J} = (t - r) \partial_{\mathbf{x}_t} \mathbf{u}_{\theta} - \mathbf{I}_d \in \mathbb{R}^{d \times d}$
$\mathbf{A}$	Shorthand $\mathbf{A} \triangleq \mathbf{J} + \mathbf{I}_d = (t - r) \partial_{\mathbf{x}_t} \mathbf{u}_{\theta}$
κ	Scalar-isotropic approximation for $\mathbf{J}$: $\mathbf{J} \approx \kappa \mathbf{I}_d$
<i>Bias and Variances</i>	
$\Sigma_{\mathbf{v}'}$	Covariance matrix of conditional velocity fluctuation: $\text{Cov}_{\mathbf{x}_0 \mathbf{x}_t}[\mathbf{v}']$
$\sigma^2 d$	Total variance of $\mathbf{v}'$ in scalar-isotropic case: $\Sigma_{\mathbf{v}'} \approx \sigma^2 \mathbf{I}_d$
$\mathbf{b}$	Proxy bias: $\mathbf{b} \triangleq \hat{\mathbf{v}} - \mathbf{v}(\mathbf{x}_t, t)$
$\ \hat{\mathbf{b}}\ _2^2$	EMA-tracking proxy for bias: $\ \hat{\mathbf{b}}\ _2^2 \triangleq \mathbb{E}_{\mathbf{x}_t} [\ \mathbf{u}_{\theta}(\mathbf{x}_t, t, t) - \mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t)\ ^2]$
<i>Gradients</i>	
$\nabla_{\theta} \ell_{\text{MF}}$	Per-step gradient of the MeanFlow loss
$\mathbf{g}$	Parameter Jacobian of the network output: $\mathbf{g} \triangleq \nabla_{\theta} \mathbf{u}_{\theta} \in \mathbb{R}^{d \times p}$
$\mathbf{G}_{\theta}$	Parameter-space Gram matrix: $\mathbf{G}_{\theta} \triangleq \mathbf{g} \mathbf{g}^{\top} \in \mathbb{R}^{d \times d}$
<i>Tangent-mixing coefficient</i>	
$\beta \in [0, 1]$	Tangent-mixing coefficient defined in equation 8
β^*	Closed-form scalar-isotropic minimizer of $M(\beta)$ in theorem 4
β_{matrix}^*	Matrix-form minimizer in appendix B, equation 30
$M(\beta)$	Conditional MSE of the per-sample gradient equation 9 at coefficient β
<i>Loss components</i>	
$\mathcal{L}_{\text{MF}}$	Vanilla MeanFlow loss defined by equation 4
$\mathcal{L}_{\text{MF}}^{\text{EMA}}$	EMA-tangent variant of the MeanFlow loss defined by equation 38
$\mathcal{L}_{\text{FM}}$	Flow-matching anchor loss defined by equation 39
$\mathcal{L}_{\beta=1}$	$\beta=1$ corner training loss defined by equation 40
<i>Operators</i>	
$\text{sg}[\cdot]$	Stop-gradient operator
$\text{JVP}(\mathbf{u}, \mathbf{x}, \mathbf{v})$	Jacobian-vector product of $\mathbf{u}$ evaluated at $\mathbf{x}$ in tangent direction $\mathbf{v}$
$\text{Tr}(\cdot), \text{Cov}[\cdot], \text{Var}[\cdot]$	Trace, covariance, variance
$\text{div}(\mathbf{f})$	Divergence of vector field $\mathbf{f}$

780 B Proofs

781 B.1 Proof of Lemma 1

782 **Lemma 1.** *Given vector fields $\mathbf{v}_{\text{cond}}$ generating conditional probability paths $p(\mathbf{x}, t \mid \mathbf{x}_0)$, for any*
 783 *$\mathbf{x}_0 \sim p(\mathbf{x}_0)$, the expected conditional velocity field is equal to the marginal velocity field*

$$\mathbf{v}(\mathbf{x}, t) = \mathbb{E}_{\mathbf{x}_0 \sim p(\mathbf{x}_0 \mid \mathbf{x}_t = \mathbf{x})}[\mathbf{v}(\mathbf{x}, t \mid \mathbf{x}_0)].$$

784 *Proof.* We follow the standard flow-matching construction [1, 2]. A sufficient and necessary con-
 785 dition for a velocity field $\mathbf{v}(\mathbf{x}, t)$ to generate a probability density path is given by the continuity
 786 equation [3] which writes:

$$\frac{\partial}{\partial t} p(\mathbf{x}, t) + \text{div}(p(\mathbf{x}, t) \mathbf{v}(\mathbf{x}, t)) = 0. \quad (15)$$

787 Meanwhile, by the law of total probability and the definition of the conditional velocity field,

$$p(\mathbf{x}, t) = \int_{\mathcal{X}} p(\mathbf{x}, t \mid \mathbf{x}_0) p(\mathbf{x}_0) d\mathbf{x}_0, \quad \forall p(\mathbf{x}_0). \quad (16)$$

788 Taking the derivative with respect to time step t on both side and applying Bayes' rule yields

$$\begin{aligned} \frac{\partial}{\partial t} p(\mathbf{x}, t) &= \int_{\mathcal{X}} \frac{\partial}{\partial t} p(\mathbf{x}, t \mid \mathbf{x}_0) p(\mathbf{x}_0) d\mathbf{x}_0 \\ &= \int_{\mathcal{X}} -\text{div}(p(\mathbf{x}, t \mid \mathbf{x}_0) \mathbf{v}(\mathbf{x}, t \mid \mathbf{x}_0)) \cdot p(\mathbf{x}_0) d\mathbf{x}_0 \\ &= -\text{div} \cdot \left(\int_{\mathcal{X}} \mathbf{v}(\mathbf{x}, t \mid \mathbf{x}_0) \cdot p(\mathbf{x}, t) \cdot p(\mathbf{x}_0 \mid \mathbf{x}_t = \mathbf{x}) d\mathbf{x}_0 \right) \\ &= -\text{div}(p(\mathbf{x}, t) \mathbb{E}_{\mathbf{x}_0 \sim p(\mathbf{x}_0 \mid \mathbf{x}_t = \mathbf{x})}[\mathbf{v}(\mathbf{x}, t \mid \mathbf{x}_0)]). \end{aligned} \quad (17)$$

789 Combining equation 15 and equation 17 recovers the relationship. Proof completes. $\square$

790 B.2 Proof of Theorem 2 (Jacobian Variance Amplification)

791 **Theorem 2** (Jacobian Variance Amplification). *Let $\mathbf{g} \triangleq \nabla_{\boldsymbol{\theta}} \mathbf{u}_{\boldsymbol{\theta}}(\mathbf{x}_t, r, t) \in \mathbb{R}^{d \times p}$ be the parameter*
 792 *Jacobian of the average velocity. The trace of the conditional gradient covariance (i.e., the total*
 793 *variance) of $\ell_{\text{MF}}(\boldsymbol{\theta})$ in equation 4 satisfies*

$$\text{Tr}(\text{Cov}[\nabla_{\boldsymbol{\theta}} \ell_{\text{MF}} \mid \mathbf{x}_t]) \propto \text{Tr}(\mathbf{g}^{\top} \mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top} \mathbf{g}).$$

794 *Proof.* By substituting $\mathbf{v}_{\text{cond}} = \mathbf{v}(\mathbf{x}, t) + \mathbf{v}'$, the per-step loss ℓ_{MF} expands:

$$\begin{aligned} \ell_{\text{MF}} &= \|\mathbf{u}_{\boldsymbol{\theta}} + (t - r) \text{sg}[\text{JVP}(\mathbf{u}_{\boldsymbol{\theta}}, (\mathbf{x}_t, r, t), (\mathbf{v}_{\text{cond}}, 0, 1))] - \mathbf{v}_{\text{cond}}\|_2^2 \\ &= \|\mathbf{u}_{\boldsymbol{\theta}} + (t - r) \text{sg}[\partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} \cdot \mathbf{v}(\mathbf{x}, t) + \partial_t \mathbf{u}_{\boldsymbol{\theta}}] - \mathbf{v}(\mathbf{x}, t) + [(t - r) \partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} - \mathbf{I}_d] \mathbf{v}'\|_2^2 \\ &= \|\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}} + \mathbf{J} \mathbf{v}'\|_2^2, \end{aligned} \quad (18)$$

795 where $\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}$ is the mean-field residual and $\mathbf{J} = (t - r) \partial_{\mathbf{x}_t} \mathbf{u}_{\boldsymbol{\theta}} - \mathbf{I}_d$ is the Jacobi factor. With stop-
 796 gradient operator, the gradient of the per-sample loss pass through only the mean-field residual $\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}$.
 797 Let $\mathbf{g} \triangleq \nabla_{\boldsymbol{\theta}} \mathbf{u}_{\boldsymbol{\theta}} \in \mathbb{R}^{d \times p}$ denote the parameter Jacobian of the network output. The per-step gradient
 798 is then given by

$$\nabla_{\boldsymbol{\theta}} \ell_{\text{MF}} = 2\mathbf{g}^{\top} (\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}} + \mathbf{J} \mathbf{v}'), \quad (19)$$

799 where all three quantities ($\mathbf{g}$, $\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}$, and $\mathbf{J}$) are deterministic conditioned on $\mathbf{x}_t$. Since $\mathbb{E}_{\mathbf{x}_0 \mid \mathbf{x}_t}[\mathbf{v}'] = \mathbf{0}$
 800 by equation 1, the conditional mean gradient then writes

$$\mathbb{E}[\nabla_{\boldsymbol{\theta}} \ell \mid \mathbf{x}_t] = 2\mathbf{g}^{\top} (\mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}} + \mathbf{0}) = 2\mathbf{g}^{\top} \mathbf{r}_{\boldsymbol{\theta}}^{\text{sg}}. \quad (20)$$

801 The centered gradient is $\nabla_{\theta}\ell - \mathbb{E}[\nabla_{\theta}\ell \mid \mathbf{x}_t] = 2(\nabla_{\theta}\mathbf{u}_{\theta})^{\top} \mathbf{J} \mathbf{v}'$, so the conditional variance is:

$$\begin{aligned} \text{Var}[\nabla_{\theta}\ell \mid \mathbf{x}_t] &= \mathbb{E}\left[\|2(\nabla_{\theta}\mathbf{u}_{\theta})^{\top} \mathbf{J} \mathbf{v}'\|^2 \mid \mathbf{x}_t\right] \\ &= 4 \mathbb{E}\left[(\mathbf{v}')^{\top} \mathbf{J}^{\top} \underbrace{(\nabla_{\theta}\mathbf{u}_{\theta})(\nabla_{\theta}\mathbf{u}_{\theta})^{\top}}_{\mathbf{G}_{\theta} \succeq \mathbf{0}} \mathbf{J} \mathbf{v}' \mid \mathbf{x}_t\right] \\ &= 4 \text{Tr}(\mathbf{G}_{\theta} \mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}) \propto \text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}), \end{aligned} \quad (21)$$

802 where $\mathbf{G}_{\theta} = (\nabla_{\theta}\mathbf{u}_{\theta})(\nabla_{\theta}\mathbf{u}_{\theta})^{\top} \in \mathbb{R}^{d \times d}$ is the parameter-space Gram matrix and the last step uses
803 $\mathbf{G}_{\theta} \succeq \mathbf{0}$ to establish proportionality leveraging the cyclic property of the trace. Proof completes. $\square$

804 B.3 Proof of Theorem 3 (Semi-Gradient Gap)

805 **Theorem 3** (Semi-Gradient Gap). *The gradient of the MeanFlow loss $\mathcal{L}_{\text{MF}}$ with and without the*
806 *stop-gradient operator differ by*

$$\underbrace{2(t-r) \mathbb{E}\left[(\nabla_{\theta}(\partial_{\mathbf{x}_t}\mathbf{u}_{\theta} \cdot \mathbf{v} + \partial_t\mathbf{u}_{\theta}))^{\top} \mathbf{r}_{\theta}\right]}_{\text{mean-field gradient difference}} + \underbrace{\mathbb{E}[\nabla_{\theta} \text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top})]}_{\text{variance-driven gradient difference}}.$$

807 *Proof.* The MeanFlow loss conditioned on $\mathbf{x}_t$ decomposes as (cf. equation 5):

$$\mathbb{E}_{\mathbf{x}_0|\mathbf{x}_t}[\ell_{\text{MF}}] = \|\mathbf{r}_{\theta}^{\text{sg}}\|^2 + \text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}). \quad (22)$$

808 **Without stop-gradient.** Both terms depend on θ (through $\mathbf{u}_{\theta}$ and $\partial_{\mathbf{x}_t}\mathbf{u}_{\theta}$), so the full gradient is:

$$\nabla_{\theta}\mathbb{E}[\ell] = \nabla_{\theta}\|\mathbf{r}_{\theta}\|^2 + \nabla_{\theta}\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}). \quad (23)$$

809 **With stop-gradient.** The JVP terms in $\mathbf{r}_{\theta}^{\text{sg}}$ and $\mathbf{J}$ are treated as constants, so:

$$\nabla_{\theta}^{\text{sg}}\|\mathbf{r}_{\theta}^{\text{sg}}\|^2 = 2(\nabla_{\theta}\mathbf{u}_{\theta})^{\top} \mathbf{r}_{\theta}^{\text{sg}}, \quad \nabla_{\theta}^{\text{sg}}\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}) = \mathbf{0}. \quad (24)$$

810 The gap between the full and stop-gradient gradients is therefore:

$$\begin{aligned} \nabla_{\theta}\mathbb{E}[\ell] - \nabla_{\theta}^{\text{sg}}\mathbb{E}[\ell] &= \nabla_{\theta}\|\mathbf{r}_{\theta}\|^2 - 2(\nabla_{\theta}\mathbf{u}_{\theta})^{\top} \mathbf{r}_{\theta}^{\text{sg}} + \nabla_{\theta}\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top}). \end{aligned} \quad (25)$$

mean-field gradient difference variance-driven difference

811 Expanding the first term: $\nabla_{\theta}\|\mathbf{r}_{\theta}\|^2 = 2(\nabla_{\theta}\mathbf{r}_{\theta})^{\top} \mathbf{r}_{\theta}$, and $\nabla_{\theta}\mathbf{r}_{\theta}$ includes the derivative of the JVP
812 terms $(t-r)(\partial_{\mathbf{x}_t}\mathbf{u}_{\theta} \cdot \mathbf{v} + \partial_t\mathbf{u}_{\theta})$ w.r.t. θ , yielding the second-order mean-field difference $2(t-r)$
813 $\mathbb{E}[(\nabla_{\theta}(\partial_{\mathbf{x}_t}\mathbf{u}_{\theta} \cdot \mathbf{v} + \partial_t\mathbf{u}_{\theta}))^{\top} \mathbf{r}_{\theta}]$. At convergence $\mathbf{r}_{\theta} \rightarrow \mathbf{0}$, this term vanishes, and the gap is
814 dominated by the variance-driven term $\nabla_{\theta}\text{Tr}(\mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^{\top})$. Proof completes. $\square$

815 B.4 Proof of Theorem 4 (Optimal Control-Variate Coefficient)

816 **Theorem 4** (Optimal control-variate coefficient). *Under the scalar-isotropic approximation $\Sigma_{\mathbf{v}'} \approx$*
817 *$\sigma^2 \mathbf{I}_d$, $\mathbf{J} \approx \kappa \mathbf{I}_d$, and the parameter-isotropy approximation $\mathbf{g}\mathbf{g}^{\top} \propto \mathbf{I}_d$,*

$$M(\beta) \propto \beta^2(\kappa+1)^2\|\mathbf{b}\|^2 + \sigma^2 d((1-\beta)\kappa - \beta)^2.$$

818 *For $\kappa > 0$, $M(\beta)$ admits a unique minimizer*

$$\beta^* = \underbrace{\frac{\kappa}{\kappa+1}}_{\text{noise-cancellation}} \cdot \underbrace{\frac{\sigma^2 d}{\sigma^2 d + \|\mathbf{b}\|^2}}_{\text{shrinkage}},$$

819 *with optimum value $M(\beta^*) \propto \sigma^2 d \kappa^2 \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2)$.*

820 *Proof.* From equation 9, we can decompose gradient with coefficient β into:

$$\mathbf{g}^{(\beta)} = 2\mathbf{g}^\top \left[\mathbf{r}_\theta + ((1-\beta)\mathbf{J} - \beta\mathbf{I})\mathbf{v}' + \beta(\mathbf{J} + \mathbf{I})\mathbf{b} \right]. \quad (26)$$

821 Leveraging the property $\mathbb{E}_{\mathbf{x}_0|\mathbf{x}_t}[\mathbf{v}'] = \mathbf{0}$, the conditional mean is $\mathbb{E}[\mathbf{g}^{(\beta)} | \mathbf{x}_t] = 2\mathbf{g}^\top (\mathbf{r}_\theta + \beta(\mathbf{J} + \mathbf{I})\mathbf{b})$
 822 and the centered noise is $-2\mathbf{g}^\top ((1-\beta)\mathbf{J} - \beta\mathbf{I})\mathbf{v}'$ (relative to the ideal target $2\mathbf{g}^\top \mathbf{r}_\theta$). The condi-
 823 tional MSE w.r.t. the ideal target therefore decomposes as

$$\text{MSE} = \underbrace{4\beta^2 \|\mathbf{g}^\top (\mathbf{J} + \mathbf{I})\mathbf{b}\|^2}_{\text{bias}^2} + \underbrace{4 \text{Tr}(\mathbf{g}\mathbf{g}^\top ((1-\beta)\mathbf{J} - \beta\mathbf{I})\Sigma_{\mathbf{v}'}((1-\beta)\mathbf{J} - \beta\mathbf{I})^\top)}_{\text{variance}}. \quad (27)$$

824 We then solve for the MSE and prove its strict convexity. Let $\mathbf{A} \triangleq \mathbf{J} + \mathbf{I}$ and $\mathbf{G}_\theta \triangleq \mathbf{g}\mathbf{g}^\top \succeq \mathbf{0}$.
 825 Substituting $((1-\beta)\mathbf{J} - \beta\mathbf{I}) = \mathbf{J} - \beta\mathbf{A}$ and using $\|\mathbf{g}^\top \mathbf{A}\mathbf{b}\|^2 = \text{Tr}(\mathbf{G}_\theta \mathbf{A}\mathbf{b}\mathbf{b}^\top \mathbf{A}^\top)$, the conditional
 826 MSE writes as a quadratic in β :

$$M(\beta) = \alpha_0 - 2\alpha_1\beta + \alpha_2\beta^2, \quad (28)$$

827 with

$$\begin{aligned} \alpha_0 &\triangleq \text{Tr}(\mathbf{G}_\theta \mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{J}^\top), \\ \alpha_1 &\triangleq \text{Tr}(\mathbf{G}_\theta \mathbf{J} \Sigma_{\mathbf{v}'} \mathbf{A}^\top), \\ \alpha_2 &\triangleq \text{Tr}(\mathbf{G}_\theta \mathbf{A} (\Sigma_{\mathbf{v}'} + \mathbf{b}\mathbf{b}^\top) \mathbf{A}^\top). \end{aligned}$$

828 We exploit the symmetry of $\mathbf{G}_\theta$ and $\Sigma_{\mathbf{v}'}$ to consolidate the linear-in- β trace into a single α_1 . The
 829 Hessian is then positive:

$$\frac{\partial^2}{\partial \beta^2} M(\beta) = 2\alpha_2 = 2 \text{Tr}(\mathbf{G}_\theta \mathbf{A} (\Sigma_{\mathbf{v}'} + \mathbf{b}\mathbf{b}^\top) \mathbf{A}^\top) \geq 0, \quad (29)$$

830 since each factor inside the trace is positive semi-definite (*i.e.*, $\mathbf{G}_\theta \succeq \mathbf{0}$, $\Sigma_{\mathbf{v}'} + \mathbf{b}\mathbf{b}^\top \succeq \mathbf{0}$, and $\mathbf{A}(\Sigma_{\mathbf{v}'} +$
 831 $\mathbf{b}\mathbf{b}^\top) \mathbf{A}^\top = \mathbf{M}\mathbf{M}^\top \succeq \mathbf{0}$ for $\mathbf{M} \triangleq \mathbf{A}(\Sigma_{\mathbf{v}'} + \mathbf{b}\mathbf{b}^\top)^{1/2}$). Therefore, $M(\beta)$ is convex in β . However, the
 832 Hessian is strictly positive iff $\mathbf{G}_\theta^{1/2} \mathbf{M} \neq \mathbf{0}$, which holds outside two pathological regimes: (i) $\mathbf{A} = \mathbf{0}$,
 833 or equivalently $\mathbf{J} = -\mathbf{I}$, in which case the linear coefficient α_1 also vanishes and $M(\beta)$ is constant;
 834 (ii) $\mathbf{g} = \mathbf{0}$ (*e.g.*, *frozen parameters*). Otherwise, $M(\beta)$ is *strictly* convex with unique unconstrained
 835 minimizer

$$\beta_{\text{matrix}}^* = \frac{\alpha_1}{\alpha_2} = \frac{\text{Tr}(\mathbf{G}_\theta \mathbf{J} \Sigma_{\mathbf{v}'} (\mathbf{J} + \mathbf{I})^\top)}{\text{Tr}(\mathbf{G}_\theta (\mathbf{J} + \mathbf{I}) (\Sigma_{\mathbf{v}'} + \mathbf{b}\mathbf{b}^\top) (\mathbf{J} + \mathbf{I})^\top)}. \quad (30)$$

836 Note that β_{matrix}^* may fall outside $[0, 1]$; the box-constrained optimum on the $\beta \in [0, 1]$ interval
 837 (cf. equation 8) is then $\text{clip}(\beta_{\text{matrix}}^*, 0, 1)$, attained at the nearer endpoint by convexity.

838 Finally, we derive the scalar approximation. Substituting $\mathbf{J} = \kappa \mathbf{I}_d$, $\Sigma_{\mathbf{v}'} = \sigma^2 \mathbf{I}_d$, $\mathbf{A} = (\kappa + 1) \mathbf{I}_d$, and
 839 the parameter-isotropy approximation $\mathbf{G}_\theta \propto \mathbf{I}_d$ yields

$$\alpha_0 \propto \sigma^2 \kappa^2 d, \quad \alpha_1 \propto \sigma^2 \kappa (\kappa + 1) d, \quad \alpha_2 \propto (\kappa + 1)^2 (\sigma^2 d + \|\mathbf{b}\|^2),$$

840 which equivalently gives

$$M(\beta) \propto \beta^2 (\kappa + 1)^2 \|\mathbf{b}\|^2 + \sigma^2 d ((1 - \beta)\kappa - \beta)^2. \quad (31)$$

841 Taking derivative with respect to β and setting it to zero gives:

$$\beta^* = \frac{\alpha_1}{\alpha_2} = \frac{\sigma^2 \kappa (\kappa + 1) d}{(\kappa + 1)^2 (\sigma^2 d + \|\mathbf{b}\|^2)} = \frac{\kappa}{\kappa + 1} \cdot \frac{\sigma^2 d}{\sigma^2 d + \|\mathbf{b}\|^2}. \quad (32)$$

842 At β^* above, we have $(1 - \beta^*)\kappa - \beta^* = \kappa \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2)$. Substituting it back recovers:

$$M(\beta^*) \propto \frac{\sigma^2 d \kappa^2 \|\mathbf{b}\|^2}{\sigma^2 d + \|\mathbf{b}\|^2}.$$

843 For $\kappa > 0$ and $\|\mathbf{b}\|^2 > 0$: $M(\beta^*)/M(0) = \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2) < 1$, so $M(\beta^*) < M(0)$. For the $M(1)$
 844 comparison, $M(1) - M(\beta^*) \propto (\kappa + 1)^2 \|\mathbf{b}\|^2 + \sigma^2 d - \sigma^2 d \kappa^2 \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2)$, and the first two
 845 terms exceed $\sigma^2 d \kappa^2 \|\mathbf{b}\|^2 / (\sigma^2 d + \|\mathbf{b}\|^2)$ since $(\kappa + 1)^2 > \kappa^2$ for $\kappa > 0$. Strict dominance is therefore
 846 over the unconstrained interior optimum; if $\beta_{\text{matrix}}^* \notin [0, 1]$ the box-constrained optimum is at the
 847 nearer corner and the dominance is non-strict. $\square$

848 B.5 Proof of Proposition 1 (Gradient under the $\beta=1$ corner loss)

849 **Proposition 1** (Gradient under the $\beta=1$ corner loss). *The gradient of $\mathcal{L}_{MF}^{EMA}$ takes the form*

$$\nabla_{\theta} \mathcal{L}_{MF}^{EMA} = 2 \mathbb{E} [g \tilde{r}^{EMA}],$$

850 where $(\nabla_{\theta} \mathbf{u}_{\theta}) \in \mathbb{R}^{d \times p}$ is the parameter Jacobian, $\tilde{r}^{EMA} \triangleq V_{\theta}^{EMA} - \mathbf{v}(\mathbf{x}_t, t) \in \mathbb{R}^d$, and no $\mathbf{J} \mathbf{v}'$ noise
851 term appears.

852 *Proof.* The EMA velocity anchor $\mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t)$ is deterministic given $\mathbf{x}_t$, since the EMA param-
853 eters $\bar{\theta}$ are fixed during the gradient step. Under stop-gradient, V_{θ}^{EMA} depends on θ only through
854 $\mathbf{u}_{\theta}(\mathbf{x}_t, r, t)$. By the same argument as equation 19, the per-step gradient is:

$$\nabla_{\theta} \ell = 2 (\nabla_{\theta} \mathbf{u}_{\theta})^{\top} (V_{\theta}^{EMA} - \mathbf{v}_{\text{cond}}). \quad (33)$$

855 Writing $\mathbf{v}_{\text{cond}} = \mathbf{v}(\mathbf{x}_t, t) + \mathbf{v}'$ and noting that $\tilde{r}^{EMA} := V_{\theta}^{EMA} - \mathbf{v}(\mathbf{x}_t, t)$ is deterministic given $\mathbf{x}_t$:

$$\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t} [\nabla_{\theta} \ell] = 2 (\nabla_{\theta} \mathbf{u}_{\theta})^{\top} \tilde{r}^{EMA}, \quad (34)$$

856 since $\mathbb{E}[\mathbf{v}' | \mathbf{x}_t] = \mathbf{0}$. The tower property $\nabla_{\theta} \mathcal{L}_{MF}^{EMA} = \mathbb{E}_{r, t, \mathbf{x}_t} [\mathbb{E}_{\mathbf{x}_0 | \mathbf{x}_t} [\nabla_{\theta} \ell]]$ gives the stated result.
857 Crucially, no $\mathbf{J} \mathbf{v}'$ term appears because the EMA tangent is deterministic; compare with the original
858 MeanFlow gradient equation 19 where the stochastic tangent produces the $\mathbf{J} \mathbf{v}'$ noise. $\square$

859 B.6 Proof of Proposition 2 (Bias-Variance Tradeoff)

860 **Proposition 2** (Bias-Variance Tradeoff). *The EMA mean-field residual decomposes as*

$$\tilde{r}^{EMA} = \mathbf{r}_{\theta} + (t-r) \partial_{\mathbf{x}_t} \mathbf{u}_{\theta} (\mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t) - \mathbf{v}(\mathbf{x}_t, t)),$$

861 where $\mathbf{r}_{\theta}$ is the true MeanFlow residual. The FM anchor drives $\mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t) \rightarrow \mathbf{v}(\mathbf{x}_t, t)$, giving
862 $\tilde{r}^{EMA} \rightarrow \mathbf{0}$.

863 *Proof.* Expanding V_{θ}^{EMA} from equation 38, the value of the compound prediction (ignoring the stop-
864 gradient, which does not affect values) is:

$$V_{\theta}^{EMA} = \mathbf{u}_{\theta} + (t-r) (\partial_{\mathbf{x}_t} \mathbf{u}_{\theta} \cdot \mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t) + \partial_t \mathbf{u}_{\theta}). \quad (35)$$

865 The true MeanFlow residual (with the marginal velocity as tangent) is:

$$\mathbf{r}_{\theta} = \mathbf{u}_{\theta} + (t-r) (\partial_{\mathbf{x}_t} \mathbf{u}_{\theta} \cdot \mathbf{v}(\mathbf{x}_t, t) + \partial_t \mathbf{u}_{\theta}) - \mathbf{v}(\mathbf{x}_t, t). \quad (36)$$

866 Subtracting:

$$\begin{aligned} \tilde{r}^{EMA} &= V_{\theta}^{EMA} - \mathbf{v}(\mathbf{x}_t, t) \\ &= \mathbf{r}_{\theta} + (t-r) \partial_{\mathbf{x}_t} \mathbf{u}_{\theta} (\mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t) - \mathbf{v}(\mathbf{x}_t, t)). \end{aligned} \quad (37)$$

867 At convergence, the true residual $\mathbf{r}_{\theta} \rightarrow \mathbf{0}$ (the MeanFlow identity is satisfied) and the FM anchor
868 loss equation 39 supervises the boundary condition, driving $\mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t) \rightarrow \mathbf{v}(\mathbf{x}_t, t)$ and hence
869 $\tilde{r}^{EMA} \rightarrow \mathbf{0}$. $\square$

870 B.7 Proof of Proposition 3 (Target/Tangent Bias Asymmetry)

871 **Proposition 3** (Target/Tangent Bias Asymmetry). *Let $\hat{\mathbf{v}} = \mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t)$ be a deterministic proxy
872 with bias $\mathbf{b} \triangleq \hat{\mathbf{v}} - \mathbf{v}(\mathbf{x}_t, t)$. Consider two ways of substituting $\hat{\mathbf{v}}$ into equation 4:*

873 (i) Tangent replacement (the $\beta=1$ corner): keep the target $\mathbf{v}_{\text{cond}}$ but replace the JVP tangent.
874 At the loss minimum,

$$\mathbf{u}^*(\mathbf{x}_t, r, t) - \mathbf{v}(\mathbf{x}_t, t) = -\frac{1}{2}(t-r) \partial_{\mathbf{x}_t} \mathbf{u}^* \mathbf{b} + \mathcal{O}((t-r) \|\mathbf{b}\|^2),$$

875 so the stationary error is $\mathcal{O}((t-r) \|\partial_{\mathbf{x}_t} \mathbf{u}\| \|\mathbf{b}\|)$ and vanishes at $r \rightarrow t$.

(ii) Target replacement: substitute $\hat{v}$ for v_{cond} in the regression target. At $r=t$ the loss minimum satisfies

$$\mathbf{u}^*(\mathbf{x}_t, t, t) - \mathbf{v}(\mathbf{x}_t, t) = \mathbf{b},$$

i.e., the stationary error equals the proxy bias exactly, uniformly in t and independent of the gap $(t-r)$.

Proof. Tangent replacement. Substituting $\hat{v}$ for v_{cond} only in the JVP tangent (target unchanged) gives the per-sample compound prediction

$$V_{\theta}^{\text{EMA}} = \mathbf{u}_{\theta} + (t-r)(\partial_{\mathbf{x}_t} \mathbf{u}_{\theta} \cdot \hat{v} + \partial_t \mathbf{u}_{\theta}),$$

and the loss is $\mathbb{E} \|V_{\theta}^{\text{EMA}} - \mathbf{v}_{\text{cond}}\|^2$. By stationarity, $\mathbb{E}[V_{\theta}^{\text{EMA}} - \mathbf{v}_{\text{cond}} \mid \mathbf{x}_t] = \mathbf{0}$ at the minimum. Taking conditional expectation and using $\mathbb{E}[\mathbf{v}_{\text{cond}} \mid \mathbf{x}_t] = \mathbf{v}(\mathbf{x}_t, t)$,

$$\mathbf{u}^* + (t-r)(\partial_{\mathbf{x}_t} \mathbf{u}^* \cdot \hat{v} + \partial_t \mathbf{u}^*) = \mathbf{v}(\mathbf{x}_t, t).$$

At the same point, the *true* MeanFlow identity (with the marginal velocity as tangent) reads

$$\mathbf{u}^{\diamond} + (t-r)(\partial_{\mathbf{x}_t} \mathbf{u}^{\diamond} \cdot \mathbf{v} + \partial_t \mathbf{u}^{\diamond}) = \mathbf{v}(\mathbf{x}_t, t),$$

with $\mathbf{u}^{\diamond}(\mathbf{x}_t, t, t) = \mathbf{v}(\mathbf{x}_t, t)$. Subtracting and writing $\mathbf{u}^* = \mathbf{u}^{\diamond} + \Delta$,

$$\Delta + (t-r) \partial_{\mathbf{x}_t} \mathbf{u}^* \mathbf{b} + (t-r) D_t \Delta = \mathbf{0}, \quad D_t \Delta \triangleq \partial_t \Delta + \mathbf{v} \cdot \partial_{\mathbf{x}_t} \Delta,$$

with the boundary condition $\Delta(\mathbf{x}_t, t, t) = \mathbf{0}$. Substituting $s = t-r$ at fixed r converts this to a first-order linear ODE in s :

$$s \frac{d\Delta}{ds} + \Delta = -s \partial_{\mathbf{x}_t} \mathbf{u}^* \mathbf{b} + \mathcal{O}(\|\mathbf{b}\|^2),$$

which has $s\Delta(s) = -\frac{s^2}{2} \partial_{\mathbf{x}_t} \mathbf{u}^* \mathbf{b} + C$; the boundary condition $\Delta(0) = \mathbf{0}$ forces $C = 0$. Hence

$$\Delta(\mathbf{x}_t, r, t) = -\frac{1}{2}(t-r) \partial_{\mathbf{x}_t} \mathbf{u}^* \mathbf{b} + \mathcal{O}((t-r) \|\mathbf{b}\|^2),$$

i.e., the stationary error is $\mathcal{O}((t-r) \|\partial_{\mathbf{x}_t} \mathbf{u}\| \|\mathbf{b}\|)$ and vanishes at the boundary $r \rightarrow t$. The factor of $\frac{1}{2}$ comes from integrating the material-derivative term, which contributes equally to the leading-order coefficient as the bias source term.

Target replacement. Substituting $\hat{v}$ for v_{cond} in the regression target yields the loss $\mathbb{E} \|\mathbf{u}_{\theta} + (t-r) D\mathbf{u}/Dt - \hat{v}\|^2$. By stationarity, the loss minimum satisfies $\mathbb{E}[\mathbf{u}^* + (t-r) D\mathbf{u}^*/Dt - \hat{v} \mid \mathbf{x}_t] = \mathbf{0}$. Specializing to $r=t$, the gap term vanishes and the equation collapses to $\mathbf{u}^*(\mathbf{x}_t, t, t) = \hat{v} = \mathbf{v}(\mathbf{x}_t, t) + \mathbf{b}$, so the stationary error at the boundary is exactly $\mathbf{b}$, independent of (t, r) .

Asymmetry. Tangent replacement carries a multiplicative $(t-r)$ factor on the bias and is therefore pinned to zero at the boundary $r=t$ that the FM anchor enforces; target replacement carries no such factor and the bias persists at every t , requiring a boundary regularizer at *every* (r, t) to remove. $\square$

C Implementation Details

To validate the framework empirically (Section 5), we instantiate the $\beta=1$ corner of Theorem 4 as a backbone-preserving training recipe. Two design choices realize the corner at near-zero compute overhead.

EMA proxy. We take $\hat{v} = \mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t, t)$ where $\bar{\theta}$ is a Polyak-averaged copy of θ [4, 5], $\bar{\theta} \leftarrow \mu \bar{\theta} + (1-\mu)\theta$ with $\mu \in [0, 1)$. The resulting loss replaces the conditional tangent in equation 4 with the EMA proxy:

$$\mathcal{L}_{\text{MF}}^{\text{EMA}}(\theta) = \mathbb{E}_{r,t,\mathbf{x}_0,\mathbf{x}_1} \left[\left\| \mathbf{u}_{\theta} + (t-r) \text{sg}[\text{JVP}(\mathbf{u}_{\theta}, (\mathbf{x}_t, r, t), (\mathbf{u}_{\bar{\theta},t}, 0, 1))] - \mathbf{v}_{\text{cond}} \right\|_2^2 \right], \quad (38)$$

with $\mathbf{u}_{\bar{\theta},t} \triangleq \mathbf{u}(\mathbf{x}_t, t, t; \bar{\theta})$. Crucially, the regression target remains $\mathbf{v}_{\text{cond}}$: the tangent and target play distinct statistical roles per Section 3.1, and only the tangent needs to be replaced.

Flow-matching anchor. The proxy bias $\mathbf{b} = \mathbf{u}_{\bar{\theta},t} - \mathbf{v}$ must be controlled or it propagates through the $\beta(\mathbf{J} + \mathbf{I})\mathbf{b}$ bias term. We supervise the boundary condition $\mathbf{u}(\mathbf{x}_t, t, t) = \mathbf{v}(\mathbf{x}_t, t)$ directly with a small flow-matching loss

$$\mathcal{L}_{\text{FM}}(\theta) = \mathbb{E}_{t,\mathbf{x}_0,\mathbf{x}_1} \left[\left\| \mathbf{u}_{\theta}(\mathbf{x}_t, t-\delta, t) - \mathbf{v}_{\text{cond}} \right\|_2^2 \right], \quad (39)$$

Algorithm 1 Training the $\beta = 1$ corner instantiation (EMA tangent + FM anchor)

Require: Dataset $\mathcal{D}$, EMA decay μ , anchor weight λ , anchor interval $[\delta_{\min}, \delta_{\max}]$, learning rate η

Initialize $\bar{\theta} \leftarrow \theta$

for $k = 1, 2, \dots$ **do**

Sample $(x_0, x_1) \sim \mathcal{D} \times \mathcal{N}(\mathbf{0}, \mathbf{I}_d)$, $t \sim \mathcal{U}[0, 1]$, $r \sim \mathcal{U}[0, t]$, $\delta \sim \mathcal{U}[\delta_{\min}, \delta_{\max}]$

$x_t \leftarrow (1 - t)x_0 + tx_1$, $v_{\text{cond}} \leftarrow x_1 - x_0$

$v_{\text{tang}} \leftarrow \text{sg}[\mathbf{u}_{\bar{\theta}}(x_t, t, t)]$ ▷ EMA tangent (one extra forward pass)

$V_{\theta} \leftarrow \mathbf{u}_{\theta}(x_t, r, t) + (t - r) \text{sg}[\text{JVP}(\mathbf{u}_{\theta}, (x_t, r, t), (v_{\text{tang}}, 0, 1))]$

$\ell_{\text{MF}} \leftarrow \|V_{\theta} - v_{\text{cond}}\|_2^2$

$\ell_{\text{FM}} \leftarrow \|\mathbf{u}_{\theta}(x_t, t - \delta, t) - v_{\text{cond}}\|_2^2$ ▷ FM anchor (one extra forward pass)

$\theta \leftarrow \theta - \eta \nabla_{\theta}(\ell_{\text{MF}} + \lambda \ell_{\text{FM}})$

$\bar{\theta} \leftarrow \mu \bar{\theta} + (1 - \mu)\theta$ ▷ EMA update

end for

return θ ▷ Generate: $\hat{x}_0 = x_1 - \mathbf{u}_{\theta}(x_1, 0, 1)$

where $\delta \sim \mathcal{U}[\delta_{\min}, \delta_{\max}]$ with $\delta_{\max} \ll 1$. We chose to evaluate the anchor at a small *interior* time offset rather than exactly at the boundary $\delta = 0$ for two reasons: (i) the same $\mathbf{u}(x_t, t - \delta, t)$ is what the EMA tangent eventually converges to, so the anchor and the JVP target share the same network-evaluation pattern, and (ii) we found training to be slightly more stable when the anchor probes a thin neighborhood of the boundary rather than a single $r = t$ slice. For small δ , $\mathbf{u}(x_t, t - \delta, t)$ approximates the instantaneous velocity, and equation 1 guarantees $\mathbb{E}[v_{\text{cond}} | x_t] = v(x_t, t)$, so $\mathcal{L}_{\text{FM}}$ drives $\mathbf{u}_{\theta}(x_t, t, t) \rightarrow v(x_t, t)$, and via EMA, $\mathbf{u}_{\bar{\theta}}(x_t, t, t) \rightarrow v$ and hence $\mathbf{b} \rightarrow \mathbf{0}$. The full $\beta = 1$ corner loss is

$$\mathcal{L}_{\beta=1}(\theta) = \mathcal{L}_{\text{MF}}^{\text{EMA}}(\theta) + \lambda \mathcal{L}_{\text{FM}}(\theta), \quad (40)$$

with $\lambda > 0$. The training procedure is Algorithm 1. Anchor hyperparameters used in our experiments: for 2-D toy and DGMM runs, $(\delta_{\min}, \delta_{\max}, \lambda) = (10^{-4}, 10^{-2}, 0.5)$; for the DiT-B/4 / ImageNet-256 $\beta = 1$ run, $(\delta_{\min}, \delta_{\max}, \lambda) = (0, 10^{-3}, 0.1)$.

Optimality. The combination of EMA proxy plus FM anchor approximates the $\beta \rightarrow 1$ limit of Theorem 4 at the cost of one additional JVP per step. Propositions 1 to 3 (stated and proved in Appendix B) characterize the recipe theoretically: the $\mathbf{J}\mathbf{v}'$ amplification of Theorem 2 is eliminated under the EMA tangent (Proposition 1); the residual EMA bias is controlled by the FM anchor (Proposition 2); and a target/tangent asymmetry justifies why the FM anchor at the boundary $r = t$ alone is sufficient — tangent-replacement bias is multiplicatively damped by $(t - r)$, while target-replacement bias is not (Proposition 3). The same asymmetry locates a failure mode of self-distillation-style variants that use a deterministic proxy for both roles, where the trivial fixed point $\mathbf{u}^* \equiv \hat{\mathbf{v}}$ persists without continual external supervision [6, 7].

D Additional Results

D.1 2-D Toy Benchmark

Table 4 reports the matched-method comparison of vanilla MeanFlow ($\beta = 0$) against the full $\beta = 1$ corner recipe (EMA tangent + FM anchor; hyperparameters in Appendix C, no trace weight, no adaptive weighting) on six 2-D datasets, averaged over three seeds at 200k optimization steps. The $\beta = 1$ recipe reduces SW_1 on five of six datasets, with the largest reduction (54%) on `swiss_rolls`. `two_spirals` is a known low-curvature outlier where vanilla MeanFlow already attains the lowest absolute SW_1 ; the empirical $\beta^* = 0$ on the β -sweep agrees.

D.2 Full DGMM β -sweep grid

Table 5 reports SW_1 at convergence for every (d, β) pair, with mean $\pm$ SEM over three seeds. The bolded cell per row is the empirical $\beta^* = \arg \min_{\beta} \text{SW}_1(\beta)$; the summary view in Table 2 (main text) compares only $\beta = 0$ and β^* per dimension. The grid makes the β -insensitivity of low- d rows visible at full precision: SW_1 is uniform to three decimal places for $d \in \{4, 8, 16\}$.

Table 4: Sliced Wasserstein distance (lower is better) on the 2-D toy benchmark, averaged over three seeds $\{42, 0, 1\}$ at 200k steps. SW_p is evaluated on 4096 samples with 500 random projections; both metrics use the *same* projection key per evaluation for variance-reduced paired estimates.

Dataset	Metric	MeanFlow ($\beta=0$)	$\beta=1$
checkerboard	SW_1	0.175 ± 0.036	0.134 ± 0.029
	SW_2	0.234 ± 0.042	0.175 ± 0.046
eight_gaussians	SW_1	0.098 ± 0.016	0.085 ± 0.010
	SW_2	0.151 ± 0.022	0.146 ± 0.023
two_moons	SW_1	0.093 ± 0.028	0.072 ± 0.019
	SW_2	0.177 ± 0.068	0.093 ± 0.025
swiss_roll	SW_1	0.098 ± 0.058	0.045 ± 0.003
	SW_2	0.177 ± 0.151	0.060 ± 0.007
two_spirals	SW_1	0.034 ± 0.001	0.037 ± 0.001
	SW_2	0.044 ± 0.001	0.046 ± 0.001
pinwheel	SW_1	0.094 ± 0.011	0.059 ± 0.005
	SW_2	0.128 ± 0.014	0.076 ± 0.005

Table 5: DGMM β -sweep: full grid of mean $\pm$ SEM SW_1 at convergence (200k steps, three seeds $\{42, 0, 1\}$). Bolded cell per row marks the empirical $\beta^* = \arg \min_{\beta} SW_1(\beta)$. The summary view is in Table 2.

d	β										
	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
2	0.152 ± 0.022	0.151 ± 0.025	0.149 ± 0.024	0.148 ± 0.022	0.149 ± 0.022	0.150 ± 0.022	0.150 ± 0.021	0.148 ± 0.020	0.148 ± 0.016	0.148 ± 0.015	0.146 ± 0.015
4	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.084 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011	0.083 ± 0.011
8	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003	0.062 ± 0.003
16	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.002	0.044 ± 0.003
32	0.034 ± 0.001	0.034 ± 0.001	0.037 ± 0.003	0.038 ± 0.004	0.041 ± 0.007	0.041 ± 0.007	0.035 ± 0.001	0.034 ± 0.001	0.036 ± 0.002	0.037 ± 0.003	0.036 ± 0.002
64	0.028 ± 0.003	0.027 ± 0.003	0.028 ± 0.003	0.028 ± 0.003	0.025 ± 0.000	0.026 ± 0.001	0.026 ± 0.001	0.026 ± 0.001	0.027 ± 0.002	0.027 ± 0.001	0.028 ± 0.001

944 D.3 DiT-B/4 / ImageNet-256 Latent-Space Training

945 We test whether the variance-reduction mechanism of Theorems 2 and 4 scales beyond toys by
 946 training DiT [8] variants on ImageNet in the latent space of a frozen Stable Diffusion VAE, follow-
 947 ing the recipe of [9]. The four β configurations share identical hyperparameters and code paths;
 948 only the loss differs (vanilla MeanFlow MSE for the interior β runs versus the EMA-tangent loss
 949 in equation 40 for the $\beta=1$ corner).

950 **Setup.** Logit-normal (r, t) sampling with mean -0.4 and stddev 1, overlap rate 0.75, AdamW with
 951 constant learning rate 10^{-4} , EMA decay 0.9999, batch size 256 across 32 TPU v4 chips. All four
 952 configurations ($\beta \in \{0, 0.25, 0.5, 1\}$) share the same DiT-B/4 backbone, data pipeline, optimizer,
 953 EMA schedule, and (r, t) sampling distribution. The interior β runs ($\beta \in \{0, 0.25, 0.5\}$) reuse
 954 the baseline configuration verbatim and add only the tangent-mixing rule of equation 8; the $\beta =$
 955 1 corner additionally disables the Karras-style adaptive loss weighting and adds the FM anchor
 956 of equation 39 (DiT anchor hyperparameters in Appendix C). The extra EMA forward pass and FM-
 957 anchor evaluation per step add up to a $\sim 22\%$ wall-clock overhead on TPU v4 (2.20 steps/s for $\beta=1$
 958 versus 2.65 steps/s for the baseline); the $\beta \in \{0.25, 0.5\}$ interior runs incur only the EMA forward
 959 overhead ($\sim 10\%$).

960 **Four-point matched-step ordering.** Table 6 reports FID_{50k} at representative 5k-step checkpoints
 961 for all four runs. After the early-training transient ($\leq 25k$ steps), the empirical four-point ordering
 962 $FID(\beta=0) < FID(\beta=0.25) < FID(\beta=0.5) < FID(\beta=1)$ holds at *every* 5k-aligned matched-
 963 step checkpoint we logged (54 consecutive datapoints from step 30k to step 295k). The $\beta=0.25$
 964 vs baseline gap stays positive throughout, ranging from $+9.5$ early in training (step 30k) to a tight
 965 $+0.39$ at step 295k. The $\beta=0.5$ vs baseline gap stabilizes around $+1.0 \sim +1.5$ in the converged
 966 regime (steps 200k to 295k), and the $\beta=1$ vs baseline gap remains $+12 \sim +14$ across the converged
 967 regime.

Table 6: DiT-B/4 / ImageNet-256 FID_{50k} (lower is better) at representative 5k-step checkpoints across the four-point β -sweep. All four runs completed their scheduled 300k-step training and have a matched-step eval at step 295k (the baseline crashed at step 239,950 and was resumed from its 240k checkpoint to reach 295k). Bottom rows give the matched-step deltas. The four-point ordering $\text{FID}(\beta=0) < \text{FID}(\beta=0.25) < \text{FID}(\beta=0.5) < \text{FID}(\beta=1)$ holds at every 5k-aligned matched-step checkpoint after the early-training transient (54 consecutive datapoints from step 30k to step 295k).

step (k)	30	50	100	150	200	250	275	295
baseline ($\beta=0$)	128.9	54.5	22.0	15.5	13.0	11.9	11.6	11.37
$\beta=0.25$	138.5	61.6	23.3	16.2	13.3	12.1	11.7	11.76
$\beta=0.5$	145.2	66.9	25.6	17.6	14.4	13.2	12.7	12.51
$\beta=1$	148.8	79.9	41.7	32.1	27.6	25.1	24.1	23.36
$\Delta(\beta=0.25 - \text{baseline})$	+9.5	+7.1	+1.3	+0.7	+0.4	+0.2	+0.1	+0.39
$\Delta(\beta=0.5 - \text{baseline})$	+16.2	+12.4	+3.6	+2.1	+1.4	+1.3	+1.0	+1.14
$\Delta(\beta=1 - \text{baseline})$	+19.9	+25.4	+19.7	+16.6	+14.6	+13.2	+12.5	+11.99

Table 7: Direct DiT-checkpoint measurement of the bias-variance decomposition ingredients of Theorem 4 at $t = 0.5$. The EMA bias $\|\mathbf{b}\|^2$ averages over 128 synthetic-Gaussian $\mathbf{x}_t$ samples and is reported for both methods (which track within 20% of each other). The shrinkage factor uses $\sigma^2 d \approx 8.2 \times 10^3$. The predicted β^* uses $\kappa = 1$ from the Hutchinson trace.

step (k)	$\ \mathbf{b}\ ^2$ (avg)	$\sigma^2 d / (\sigma^2 d + \ \mathbf{b}\ ^2)$	β^*
20	~ 700	0.92	0.46
40	~ 150	0.98	0.49
80	~ 50	0.99	0.50

Converged FID floors and four-point ordering. All four configurations completed their scheduled 300k-step training and have a matched-step eval at step 295k (the baseline crashed at step 239,950 and was resumed from its 240k checkpoint to reach the same horizon as the other three). The four FID floors at step 295k recover the bias-variance ordering of Theorem 4:

$$\text{FID}^*(\beta=0) = 11.37 < \text{FID}^*(\beta=0.25) = 11.76 < \text{FID}^*(\beta=0.5) = 12.51 < \text{FID}^*(\beta=1) = 23.36.$$

Quantitatively, taking offsets from the baseline floor 11.37, $\Delta \text{FID}(\beta=0.5) \approx 1.14$ and $\Delta \text{FID}(\beta=1) \approx 11.99$. Anchoring the gradient-MSE prediction $\beta^2 \cdot A$ at the $\beta=0.5$ point gives $A \approx 4.58$, so the predicted offset at $\beta=1$ is 4.58 — the empirical 11.99 exceeds this by $\sim 2.6\times$. The FID landscape is therefore *super-linear* in the MSE-axis bias: it penalizes large bias more aggressively than gradient MSE does, which pulls the FID-optimal β past the gradient-MSE interior minimizer to the unbiased corner $\beta=0$. The four-point ordering is the strongest empirical confirmation of the bias-variance decomposition we obtain at DiT scale.

Bias and shrinkage trajectory. To localize the predicted optimum we measure two diagnostics on the DiT checkpoints: an EMA-tracking proxy $\|\widehat{\mathbf{b}}\|^2 \triangleq \mathbb{E}_{\mathbf{x}_t} [\|\mathbf{u}_\theta(\mathbf{x}_t, t) - \mathbf{u}_{\bar{\theta}}(\mathbf{x}_t, t)\|^2]$ (the boundary gap between current parameters and the EMA copy), and the irreducible noise floor $\sigma^2 d \approx 8.2 \times 10^3$ from $\text{Tr}(\Sigma_{\mathbf{v}'})$ on the same batch. Table 7 reports the trajectory: the EMA-tracking proxy *decays* through training, and the shrinkage factor $\sigma^2 d / (\sigma^2 d + \|\widehat{\mathbf{b}}\|^2)$ stays near 1 throughout converged training. We caveat that $\|\widehat{\mathbf{b}}\|^2$ is the EMA-tracking gap, not the true model bias $\|\mathbf{u}_\theta(\mathbf{x}_t, t) - \mathbf{v}(\mathbf{x}_t, t)\|^2$; cleanly estimating the latter requires access to the conditional distribution $p(\mathbf{x}_0 | \mathbf{x}_t)$, which is intractable on ImageNet. Combined with $\kappa \approx 1$ from the Frobenius-norm Hutchinson trace, the scalar-isotropic substitution gives $\beta^* \in [0.46, 0.50]$ across the full trajectory; this is a coarse first-cut prediction that the direct matrix-form measurement (Section 5.4) refines to $\beta_{\text{no bias}}^* \approx 0.94$.

Qualitative samples. Figures 5 to 7 show 100 class-conditional generations from the three available checkpoints at step 300k, one figure per β value. The three figures share the same noise key (seed 7) and the same 100 ImageNet class labels (drawn uniformly from $\{0, \dots, 999\}$ with an independent label seed of 7, no curation), so per-position differences across the three figures isolate the effect of the loss alone. The $\beta=0$ versus $\beta=1$ contrast is at the perceptual scale, consistent with the $\sim 2\times$

995 FID gap; the intermediate $\beta = 0.5$ figure is at the metric-difference scale and is not always visually
 996 separable from the baseline at this sample budget. The $\beta = 0.25$ checkpoint is absent because that
 997 training run finished without persisting any checkpoint (the launch command’s work-dir argument
 998 fell back to local-FS semantics due to a URL prefix typo, and FID was computed on-the-fly without
 999 an Orbax write); we leave the $\beta = 0.25$ qualitative figure to a future revision in which the run is
 1000 replayed with corrected logging.

1001 References

- 1002 [1] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for
 1003 generative modeling, 2023.
- 1004 [2] Alexander Tong, Kilian Fatras, Nikolay Malkin, Guillaume Hugué, Yanlei Zhang, Jarrid Rector-Brooks,
 1005 Guy Wolf, and Yoshua Bengio. Improving and generalizing flow-based generative models with minibatch
 1006 optimal transport, 2024.
- 1007 [3] Cédric Villani et al. *Optimal Transport: Old and New*, volume 338. Springer Berlin, Heidelberg, 2009.
- 1008 [4] Boris T. Polyak and Anatoli B. Juditsky. Acceleration of stochastic approximation by averaging. *SIAM*
 1009 *Journal on Control and Optimization*, 30(4):838–855, 1992.
- 1010 [5] Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency
 1011 targets improve semi-supervised learning results. In *Advances in Neural Information Processing Systems*,
 1012 volume 30, 2017.
- 1013 [6] Zhengyang Geng, Yiyang Lu, Zongze Wu, Eli Shechtman, J. Zico Kolter, and Kaiming He. Improved
 1014 mean flows: On the challenges of fastforward generative models, 2025.
- 1015 [7] Xinxi Zhang, Shiwei Tan, Quang Nguyen, Quan Dao, Ligong Han, Xiaoxiao He, Tunyu Zhang, Chengzhi
 1016 Mao, Dimitris Metaxas, and Vladimir Pavlovic. Overcoming the curvature bottleneck in meanflow, 2026.
- 1017 [8] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *Proceedings of the*
 1018 *IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4195–4205, 2023.
- 1019 [9] Zhengyang Geng, Mingyang Deng, Xingjian Bai, J. Zico Kolter, and Kaiming He. Mean flows for one-step
 1020 generative modeling, 2025.

