

# Aquamacs User Help

David Reitter and Kevin Walzer

August 2, 2005

## Contents

<b>1</b>	<b>Emacs: The Aquamacs Distribution</b>	<b>2</b>
<b>2</b>	<b>What's New in This Release</b>	<b>4</b>
2.1	Changes: 0.9.5b1 . . . . .	4
2.2	Bug Fixes—0.9.4 . . . . .	5
2.3	Bug Fixes—0.9.3a and 0.9.3b . . . . .	6
2.4	Bug Fixes—0.9.3 . . . . .	7
2.5	Features and Changes: 0.9.3 . . . . .	9
2.5.1	New Address . . . . .	9
2.5.2	Running Aquamacs . . . . .	9
2.5.3	Frame and Window Operations . . . . .	10
2.5.4	Fonts . . . . .	10
2.5.5	Interface . . . . .	10
2.5.6	Configuration . . . . .	12
2.5.7	External Tools Support . . . . .	13
2.5.8	User Documentation . . . . .	13
<b>3</b>	<b>Tutorial: Aquamacs for Beginners</b>	<b>13</b>
3.1	What Makes Aquamacs Like Other Text Editors . . . . .	13
3.2	What Makes Aquamacs (Emacs) Different from Other Text Editors . . . . .	14
<b>4</b>	<b>In Depth: The Aquamacs Interface</b>	<b>15</b>
4.1	File . . . . .	15
4.2	Edit . . . . .	16
4.3	Options . . . . .	16
4.4	Buffers . . . . .	16

4.5	Tools . . . . .	17
4.6	Help . . . . .	18
<b>5</b>	<b>Aquamacs for Emacs Veterans</b>	<b>18</b>
5.1	Keyboard Shortcuts . . . . .	18
5.2	Customizing Aquamacs . . . . .	18
5.3	L <sup>A</sup> T <sub>E</sub> X Support . . . . .	22
5.3.1	Enhanced Carbon Emacs Plugin Under Development	24
5.3.2	T <sub>E</sub> Xniscopes: A Superb L <sup>A</sup> T <sub>E</sub> X Previewer . . . . .	25
<b>6</b>	<b>Getting Help</b>	<b>25</b>
<b>7</b>	<b>Acknowledgments</b>	<b>26</b>
<b>8</b>	<b>Licenses</b>	<b>26</b>

# 1 Emacs: The Aquamacs Distribution

Aquamacs is an freely-available Aqua-native build of the powerful Emacs text editor (<http://www.gnu.org/software/emacs/emacs.html>). By “Aqua-native,” we mean more than just the fact that this version of Emacs runs as a standard OS X application. Aquamacs features extensive customization that enables it to conform better with Apple’s standard Human Interface Guidelines (HIG) than standard versions of the editor do.

Emacs is a text editor of legendary power and configurability, but it also has an enormously complex interface that, while consistent across platforms, is usually at odds with the specific interface conventions of the particular platform on which it is being used. The official OS X version of Emacs, called Carbon Emacs, is no different.

The Aquamacs distribution implements the standard OS X keyboard shortcuts and other interface conventions, integrating Emacs into the Aqua environment to a far greater degree than other versions of Emacs. This allows Mac users who might be unfamiliar with Emacs’ complex standard interface to harness its amazing editing power in a familiar way.

You can always download the latest version of Aquamacs from the project home page, <http://www.aquamacs.org>. The direct download link is <http://aquamacs.org/cgi-bin/download.cgi>. Just download the disk image (DMG), move the Aquamacs application bundle to your hard drive, and launch.

This documentation aims to introduce Aquamacs to novice users of Emacs, to help them get started with this powerful text editor. The documentation also aims to introduce Aquamacs to experienced users of Emacs, who may find aspects of its interface inconsistent with their experience.

The Aquamacs documentation will focus on the following areas:

- What’s New in this Release
- Tutorial: Aquamacs for Beginners
- In-Depth: The Aquamacs Interface
- Aquamacs for Emacs Veterans

Our hope is that using Aquamacs will be a rewarding experience both for new users, who come to appreciate the power of Emacs without the steep learning curve, and for experienced Emacs users, who may find Emacs’ integration into the Aqua environment an unexpectedly pleasant surprise.




Figure 1: Aquamacs combines the legendary power of Emacs with user-friendly customizations to provide a more Aqua-specific user experience.

## 2 What's New in This Release

This is version 0.9.5b1 of Aquamacs, released July 20, 2005. Aquamacs 0.9.5b1 includes a number of bug fixes and optimizations that should improve performance and stability.

### 2.1 Changes: 0.9.5b1

- The customization variable `aquamacs-auto-frame-parameters` allows you to turn off mode-specific themes—your frames stay the same, no matter what major mode you switch to.
- Frame Appearance Themes have a better menu structure now in the Options menu. Also, there is a new function “Delete all mode-specific themes”.
- Many menu items are now greyed out (cannot be selected) when no frame is visible.
- Font “Bitstream Vera Sans” works again.
- Every Aquamacs frame has a toolbar-button now. Use it to turn the toolbar in the given frame on and off.
- Tool-bar can be turned off (per frame) again. Different defaults for major modes are allowed.
- Improvement when working with multiple frames: when no frame is visible, Aquamacs no longer raises some other frame as soon as a file is loaded.
- Speedbar works when one-buffer-one-frame (“Open Buffers in Separate Frames”) is turned off.
- Ispell did not work when one-buffer-one-frame was turned on. (Reported by Robert Sloan)
- Startup with arguments `-nw` (tty / in terminal) revised.
- In particular in TeX mode, Aquamacs tended to give audio signals all the time when there were internal exceptions (internal errors signaled) with parsing the TeX code. Therefore, we do not ring the bell any more, i.e. `aquamacs-ring-bell-on-error-flag` is nil by default. (Reported by Ken Bloom and Andreas Hess)

- You can now redefine Aquamacs keys like this:  

```
(define-key osx-key-mode-map [end] 'end-of-line)
```

(Thanks for reporting: Andreas Hess.)
- If the user changes `mac-command-modifier`, it may be advisable to call  

```
(osx-key-reset-mode-map)
```

This will ensure that the keymap is updated and Aquamacs installs its Mac-like keyboard commands (provided you want this).
- New frames will not open behind the Dock any more.
- Manual updated to 0.9.4 with changelog.
- Startup is faster now due to an optimization in loading fonts (thanks: Yamamoto M.) and precompiling some `.el` files.
- Error message during version check on startup removed (occurred in certain cases where users had upgraded their system.)
- Exiting view mode (e.g. `help`) with `'q'` deletes the frame instead of iconifying it.
- An error message (harmless) when clicking on "Finish" in customize is gone.

## 2.2 Bug Fixes—0.9.4

- Bug reports contain the subject line that the user entered.
- No more (delay due to) tramp mode on startup in cases where tramp mode had been used before (`recentf`).
- Files on externally mounted volumes are not checked for readability any more for exclusion from recent files list. (Reported by Bill Clementson)
- No more warnings when fonts are missing (on startup).
- Drag and Drop while in minibuffer works again.
- Mouse-2 works again.

- default-major-mode and initial-major-mode are respected now. initial-frame-alist is not modified any more. Note that other than in any standard Emacs, mode-specific settings always take precedence over default-frame-alist (but not over initial-frame-alist). (Reported by Rick Zaccone, Joe Davison and Peter Dyballa)
- No more warnings in customization buffers that the values have been changed outside customize (for certain variables).
- Gnus articles (newsreader) open in same frame now.
- Gnus has a useful (free) nntp server set so you can start right away.
- Send Email with Sendmail is gone from menu (doesn't usually work on OS X).
- Fonts corrected: Some glyphs in some fonts turned out wrong when in bold or italic. Also, font sizes are correct again (Lucida 14 is Lucida Grande 14, not 12 or so). The default font size for text-mode (and similar ones) is set to Lucida 13 to make up for the change. Apologies for any inconvenience this may cause with your default settings. (Reported by William Henney)
- Better customization for aquamacs-mode-specific-default-themes
- The customizations file (customizations.el) doesn't grow any more. (Reported by Alastair Rankine.)
- Various corrections in the Aquamacs Manual.
- Plugin support: All files named site-start.el anywhere in the load-path are loaded at startup, before the user's init files are loaded. For example, such a file may be placed in /Library/Application Support/Aquamacs Emacs/myPlugin. This feature enables support for easily installable plugins.
- We anticipate shorter startup times in the next release. Stay tuned.

## 2.3 Bug Fixes—0.9.3a and 0.9.3b

- Fixed “wrong argument type” problem (version check), which could occur in new installations or those updated from 0.9.1.
- Monaco 18 font present (suggestion: David M. Cook).

- Emacs Manual available again.
- Save mac-pass-option-to-system when saving options.

## 2.4 Bug Fixes—0.9.3

- Initial-frame-alist is respected. (Reported by Alastair Rankine)
- When saving a buffer and the Finder is not running, the Finder is not opened any more. (Reported by George W. Gilchrist.)
- Using dead-keys (like Option-u or Option-n on most keyboards) works again. (Reported by Howard Melman and Pierre Albarede)
- When modified files existed, but no frame was visible and one tried to quit Aquamacs, the application seemed to hang while prompting for keyboard input (Save file? y/n) in an invisible window. This has been fixed.
- If no frame is visible and you input text, the frame is made visible so you can see what you are doing.
- Closing windows consistently with the mouse now works properly.
- Clicking on links to source files in help buffers properly opens a new frame (if “open buffers in separate frames” is on).
- When the buffer shown in a frame changes, sometimes the color theme and font were not set correctly; this has been addressed. This could happen when “Show Buffers in Separate Frames” was off, and one killed a buffer. (Reported by Peter Dyballa.)
- When “Show Buffers in Separate Frames” was off, and one killed a buffer (kill-buffer, C-x k), the frame was deleted.
- You have the option to save newly created buffers (Command-N) that have not been saved yet when you quit Aquamacs.
- Less frame-dancing (resizing) on startup.
- AUCT<sub>E</sub>X uses the standard commands again. The menu is unstructured for this reason. (Reported by Robert Sloan.)



- No frames could be opened when using a two-screen setup with the menu bar on the right screen, and a currently selected frame on the left screen. This has been addressed. (Reported by George W. Gilchrist.)
- Customizing a theme for a special display frame (e.g. help or customization) works now.
- Recent Files/Clear Menu works again.
- Paths and other environment variables are now derived from the shell when you start Aquamacs.
- Your settings for highlight parens, “Blinking Cursor,” etc. are now persistent. The function Options/Save Options (menu-bar-option-save) now correctly saves such settings. This should include most customization settings except some that Aquamacs relies on for proper clipboard copy/paste functionality.
- The font menu (Options) no longer includes non-existent fonts.
- Option/Show-Hide/Menu Bar is gone because you cannot turn off the menu bar on OS X.
- “Send Emacs Bug Report” now uses the OS X default mail program to compose a message. This ensures that bug reports actually go through. Before, they did not, unless you were running a local SMTP server (sendmail/postfix), which is not enabled by default.
- Fixed loading of files when file names contain certain Kanji characters, due to a bug in AppleScript.
- The menu shortcut entries were corrected.
- Characters that require the use of the option key work again. For example, Alt-3 produces the pound sign (£) on a US keyboard, Alt-L the ‘at’ sign @ and Alt-Shift-7 the backslash on a German one. Inputting the Euro sign works, too. *However, that means that the option key is not used to emulate the ‘meta’ modifier; you will have to use Esc to do that.* Alternatively, you can map the option key to meta in your .emacs file:  

```
(setq mac-option-modifier 'meta)
```
- Improvements in the fontset selection allow you to display the Euro sign with the default font.

## 2.5 Features and Changes: 0.9.3

### 2.5.1 New Address

- We have moved Aquamacs to <http://www.aquamacs.org>.
- The Aquamacs wiki is now at <http://www.emacswiki.org/cgi-bin/wiki/AquamacsEmacs/>.
- The Aquamacs bug reporting address is now `mailto:aquamacs-bugs@aquamacs.org`. This can be accessed from directly within the Aquamacs Help menu.
- The general Aquamacs mailing list is still `mailto:macosx-emacs@email.esm.psu.edu`; e-mail `mailto:macosx-emacs-on@email.esm.psu.edu` to subscribe.

### 2.5.2 Running Aquamacs

- Slightly faster startup.
- Runs on OS X 10.3.9, 10.4.0 and 10.4.—tested.
- Aquamacs automatically checks for updates and notifies the user if there is something new. This function communicates with an internet server; it does not transmit any information identifying the user. If you would like to know more about what is transmitted, use `M-x aquamacs-check-version-information`. If you like to turn this check off, add this to your file `/Users/ yourname / Library / Preferences / Aquamacs Emacs/ Preferences.el`:  

```
(setq aquamacs-version-check-url nil)
```
- Adding Emacs packages is easier now: Emacs automatically finds packages in subdirectories within the `/Library/Preferences— Application Support/Emacs—Aquamacs Emacs/` paths.
- Aquamacs now sets the file creator information of files it writes. This helps to open the file from Finder with Aquamacs when you double-click it. Feature can be turned off via customization option “`aquamacs-set-creator-codes-after-writing-files`.” Also, Emacs will appear in the Finder’s context menu under “Open With” for a lot of files that it is commonly used to edit.

- You can start Aquamacs in a terminal (by running `/Applications/Emacs.app/Contents/MacOS/Emacs`) with parameter `-nw` and will show up in the terminal rather than as a Carbon application. Basic file editing and all traditional commands work. However, Aquamacs-specific keyboard commands (with the Command key) will not work and other functionality may be limited, too. *Warning:* This mode of use, which may break in future versions, is not supported by the Aquamacs team.

### 2.5.3 Frame and Window Operations

We make sure that the `*Completions*` buffer (and similar things) open as a window inside the frame directly above the Minibuffer, and not in a new frame.

All newly opened frames open in a somewhat useful position, so they are not in the way. (If you do not like this, we suggest you set your own static frame positions via “set current theme as default” and also add this to your file `/Users/yourname/Library/Preferences/Aquamacs Emacs/Preferences.el`:

```
(setq smart-frame-positioning-enforce nil)
```

Or, if you would like to go with the default position all the time, turn the global minor mode off:

```
(smart-frame-positioning-mode nil)
```

### 2.5.4 Fonts

- Aquamacs should not complain about missing fonts any more when you have upgraded from earlier versions and set scalable fonts as default fonts for modes or all frames. They get filtered automatically.
- Users with certain setups (cyrillic Lucida Grande) should not get a “default font not found” error any more.

### 2.5.5 Interface

- “Recursive Minibuffers” are enabled.
- “Subscribe to mailing list” in Help menu.
- PHP-Mode included (`M-x php-mode`).
- Ruby-Mode included (`M-x ruby-mode`)

- yes-or-no-p is customizable now. Use the new customization variable `aquamacs-quick-yes-or-no-prompt`. (Thanks: Pavel Hlavnicka.)
- Soft word wrap (`longlines-mode`) is available from the Options menu. To make it the default, add this to your preferences file: `(set-default 'longlines-mode t)`
- Case-insensitive search option has gone into “search” submenu (in “Edit”).
- If you are in an empty frame (i.e. a frame with an empty buffer) and you load (find) a file, Aquamacs will not open an additional frame. This is useful also for drag and drops, when a scratch frame is open.
- The secondary selection is back: use the Command (Apple) key together with clicking/dragging the mouse cursor over text in order to select text that is not related to the point (cursor). This way, you can select text and then scroll somewhere else. Extend your selection with `shift-command-mouse1`. To copy/cut the text in the secondary selection to the clipboard, use `Shift-Command-C/X`, respectively.
- Some key-bindings are more like the original Emacs ones—in particular `M-w`, which does `kill-ring-save` again. (Idea: Joe Davison) Also, Home and End keys work as expected.
- No more annoying system “ding” (bell ringing) all the time. The bell is turned off completely, until Emacs developers eliminate the use of the bell on user-initiated abort actions (such as `ESC ESC ESC` when in minibuffer, or pressing Cancel in the file selection dialog).
- The toolbar is only displayed in normal frames, but not in frames that show help/info buffers. (`tool-bar+` and `aquamacs-tool-bar` packages). Turn such toolbars on/off in Options/Show/Hide menu.
- The “About Emacs” dialogue has been improved.
- Key combinations with the option key that involve another modifier (that is, `ctrl` or `command`) will now work, even though simple option combinations are handled by the system to produce special characters.
- The Speedbar is back. Activate in Options/ Show/Hide.
- The redo function is in the Edit menu now.

- New buffers (File / New) open in Text Adapt Fill mode now.
- .save-places and customizations.el do not show up in the recent files list any more.
- auto-save-files (in / Users / yourname / .emacs.d) are now saved to / Users / yourname/Library/Preferences.
- “Save Place in Files in between sessions” will not generate files in the user’s home folder any more. Instead, the file goes into / Users / yourname/Library/Preferences/Aquamacs Emacs/ where it belongs.
- Command-’ now cycles between different windows (suggested by Joseph Kiniry.)
- Option is mapped to Meta by default, allowing you to enter key combinations such as C-M- easily. If you’d like to map it to alt instead, just add this to your .emacs:  

```
(setq mac-option-modifier 'alt)
```

### 2.5.6 Configuration

- Color Themes: The color-themes package has been integrated in Aquamacs. Use the Option/Color Theme... menu command to choose a set of predefined colors for editing source code or writing texts. This applies to the current frame only, but you can make it the default for all new frames or for all frames in a specific mode with the according menu commands.
- There is a new customization group called “Aquamacs” that allows you to modify the customizations introduced by Aquamacs. This is fairly untested - unexpected results may occur. If so, try to locate and fix the bug and send us a patch. If you couldn’t find the problem, please report via Help/Send Bug Report... PLEASE NOTE that a lot of customization variables have changed their names—usually, you just need to prepend 1on1 to them.
- Aquamacs will load YOUR configuration files not just from / Users / yourname/.emacs, but also from the location that is appropriate for a Mac OS X installation:

```
/ Library/ Preferences /Aquamacs Emacs / Preferences.el  
/ Users / yourname/Library/Preferences/Aquamacs Emacs/Preferences.el  
/Library/Preferences / Emacs / Preferences.el  
/ Users / yourname / Library/Preferences/Emacs/Preferences.el
```

It is recommended to use these instead of `/ Users / yourname/.emacs` on OS X-only installations. The first two files should be used for the host-wide and user-specific Aquamacs configs, the latter two for general Emacs configurations.

- There is a new configuration option that gives you more fine-grained control over how the option modifier key is handled.
- If `mac-pass-option-to-system` is nil, your Aquamacs will get all key combinations. If you press option-3, Aquamacs will see “M-3” (or, depending on `mac-option-modifier` “A-3”). If it is non-nil, you will simply get the pound sign (£) on a US keyboard.

### 2.5.7 External Tools Support

- TeXniScope support in LaTeX mode (if installed in `/ Applications`).

### 2.5.8 User Documentation

- We have two great manuals available comfortably via Apple Help now, directly from within Aquamacs Emacs (Help menu). There is a brand-new Aquamacs manual, and there is Richard Stallman’s original Emacs manual. They can be searched (e.g. via Spotlight on OS X 10.4). We also provide direct access to the online configuration Wiki, which has been filling up with content nicely. Please contribute; everybody has write access!

## 3 Tutorial: Aquamacs for Beginners

### 3.1 What Makes Aquamacs Like Other Text Editors

When you first launch Aquamacs, you will see that it is like many other text editors such as Bare Bones Edit, Dreamweaver, or similar programs: you can type text, cut and paste text, and save and close a file using the menubar or standard OS X keyboard shortcuts (Apple-S for save, Apple-X

for cut, Apple-V for paste, and so on). If you are writing one of the many text formats that is supported by Aquamacs, such as HTML, you will also note Aquamacs' use of *syntax coloring*, which sets certain parts of the text—such as HTML markup—in a different color than the text content. This makes editing the text and adjusting the markup easier.

### 3.2 What Makes Aquamacs (Emacs) Different from Other Text Editors

If you look at some of the menu items and keyboard shortcuts, you will see some of the features that make Emacs different from other text editors. Although Aquamacs has been designed to present many of these features in an Aqua-friendly way, it does not hide these features. Aquamacs is a complete editing environment.

- **Sophisticated text processing.** Aquamacs features text editing capabilities that go far beyond the average text editor. For instance, Aquamacs features several kinds of search and replace: it can replace text incrementally, it can search and replace text by complex patterns of characters (regular expressions) and not just by word matching, and so on. Aquamacs also features support for virtually every kind of text file imaginable: computer code such as C/C++, HTML,  $\text{\LaTeX}$ , XML, and other formats.
- **The buffer.** One of the features that makes Emacs such a productive editing environment for experienced users is the *buffer*. The buffer includes any window in which text is being edited, similar to a standard Aqua “Document” window, but also includes windows that display messages from the program, a window that you can use to actually send commands that Aquamacs executes, and other functions. The buffer feature of Aquamacs allows you to switch quickly between windows, to send execute or preview the code you are writing with a couple of keystrokes, and to monitor logs of commands you are executing. You can also split a single window into multiple buffer displays if you choose.
- **Integration with additional tools.** Aquamacs' “Tools” menu provides access to file comparison and version control, compiling and debugging of program code, the ability to read e-mail and newsgroups, and more.

OS X Term	Emacs Term
Window	Frame
Tab/pane	Window
Document	Buffer
Keyboard shortcut	Key

Table 1: Key Emacs terms and their Apple counterparts.

In addition to its large number of features, Aquamacs also defines some interface terms differently than other OS X applications. See Table 1 for more information.

This list provides just a small sampling of the functionality available in Emacs. Aquamacs’ customizations make Emacs much easier to learn; it is possible to get started and become productive quickly. However, harnessing all of Emacs’ power, even with assistance from the Aqua shortcuts, will take time.

## 4 In Depth: The Aquamacs Interface

In this section, we will walk through the Aquamacs interface step by step, and will introduce relevant points about how Emacs solves particular editing problems in a distinctive way. Here our discussion will focus on how Aquamacs is configured, as opposed to Emacs in general.

### 4.1 File

The File menu includes basic operations for opening, closing, and printing files. Opening and saving files uses standard Mac keyboard shortcuts (Apple-O, Apple-S), and uses standard Aqua dialog boxes. You can also open a directory; from the menubar this brings up a standard Aqua dialog box, through the keyboard shortcuts are the traditional Emacs one (control-x d), and it brings up a directory name in the “minibuffer” (small space for commands at the bottom of the main window, or frame).

Printing is supported, though only from the menu, and it will not present a traditional Mac print dialog. Instead the text in your file will print to your default printer using the command-line `lpr` program.

From the File menu, you can also open a new “frame,” or window, or split the open window into two separate buffers. The keyboard shortcuts



for these commands are the traditional Emacs ones (see the menubar).

## 4.2 Edit

The Edit menu is the heart of Emacs' textual wizardry. Emacs supports all customary editing functions, such as cut, copy, paste, and simple search and replace. In Aquamacs these basic functions are supported by standard Aqua keyboard shortcuts. There is a great deal more functionality, however, than the average text editor. For instance, Emacs allows you to go to a specific line number in the file you are editing, to the top or bottom of the buffer, and so on. It also supports searches with *regular expressions*, which are sophisticated text patterns that go beyond simply matching a specific set of characters (or "string"). Emacs also stores more than twenty of the most recently-copied items on the clipboard, and these are accessible from the menu in case you need to paste these items again. The Edit menu also supports "bookmarks," a feature that allows you to save your place in a specific file.

## 4.3 Options

The Options menu is where you can easily customize your settings. The options that you can configure include syntax coloring, matching of parentheses (useful for text markup that depends on open and close brackets), how to display buffers and frames, color theme, fonts, and other settings. If you change a setting, such as the color theme or fonts, be sure to select the "Save Options" item in the menu. The changes will not be saved by default.

## 4.4 Buffers

The Buffers menu allows you to navigate through the windows/frames that you may have open. Note that a "buffer" is not synonymous with a window or frame, in that you can split a frame and have more than one buffer contained within. (Multiple windows/frames is a feature of Aquamacs; standard Emacs does not support this.) In addition to standard frames that display open files, there are a few other important buffer types. One is the "scratch" buffer, which is simply a buffer to type notes into; this can also be the starting point for a file to save, and a buffer to type configuration commands for Aquamacs (an advanced feature). Another is the "message" buffer, which displays a log of output from Aqua-




Figure 2: The “buffer” feature of Emacs, which Aquamacs preserves, is a powerful tool for enhancing productivity.

macs commands and operations. Finally, there is the “info” buffer, in which Aquamacs displays built-in user help, tutorials and other documentation in Emacs’ “info” format.

## 4.5 Tools

The Tools menu provides access to a variety of functions, including integration with version control systems, running shell commands, searching external files for text, and compiling and debugging software code. The Tools menu also provides access to newsgroups and e-mail in a command-line capacity.<sup>1</sup>

<sup>1</sup>The functionality provided in the Tools menu is, to say the least, diverse, and is part of the attraction of Emacs for a large number of users—particularly advanced users. It is not necessary to use Aquamacs as an e-mail client to appreciate its considerable power and utility, however.

## 4.6 Help

The Help menu contains a wealth of information about Aquamacs/Emacs. Except for the help provided in this document, Aquamacs' Help menu provides no documentation of the Mac-specific customizations that you will find in Emacs. However, the general Emacs user help is comprehensive and detailed to the point of possibly overwhelming the inexperienced user. The beginner should definitely start with the Emacs tutorial contained in the Help menu. While geared toward the traditional Emacs interface instead of the OS X Aquamacs version, the tutorial is a good introduction to Emacs' unique capabilities. And, as you gain more experience, you will appreciate the depth of the Emacs documentation.

## 5 Aquamacs for Emacs Veterans

While experienced users of Emacs on other platforms can continue to use all the key combinations to which they are accustomed, we recommend that they use the Aquamacs-specific conventions to get the most benefit from the applications. Many of the standard Emacs behaviors and interface conventions have been modified in Aquamacs in the interest of providing a more Aqua-native experience. In this section, we discuss some of the ways that Emacs conventions are mapped to Aqua conventions, and outline some advanced ways that users can modify Aquamacs to their specific preferences.

### 5.1 Keyboard Shortcuts

Emacs has a well-defined set of keyboard shortcuts, which Aquamacs revises to accomodate OS X conventions. See Table 2 and Table 3 for details.

### 5.2 Customizing Aquamacs

One of the distinguishing features of Emacs is the degree to which it can be customized by the end user. Emacs includes its own internal scripting language, *elisp*, which allows the user to customize such things as keyboard shortcuts, window settings, fonts, and more. The Aquamacs customizations themselves are implemented in *elisp*.<sup>2</sup>

---

<sup>2</sup>The Aquamacs customizations are stored in *elisp* files in the application bundle. It is possible to modify these files directly, but we discourage this practice and provide no support for it.

Shortcut	Elisp Command	Function
Apple-N	new-frame-with-new-scratch	Open a new empty window/frame
Apple-O	mac-find-file-other-frame	Open a new window/frame with a file
Apple-shift-s	mac-save-file-as	Save as
Apple-shift-O	find-file-other-frame	Find file in another frame
Apple-A	mark-whole-buffer	Select all text
Apple-V	yank	Paste text
Apple-C	kill-ring-save	Copy text
Apple-X	kill-region	Cut text
Apple-S	save-buffer	Save file
Apple-L	goto-line	Go to specified line
Apple-F	isearch-forward	Search
Apple-G	isearch-repeat-forward	Repeat search
Apple-W	'intelligent-close)	Close window
Apple-M	iconify-or-deiconify-frame	Minimize window to the Dock
Apple-.	keyboard-quit)	Keyboard quit
Apple-Q	'save-buffers-kill-emacs)	Save file, exit program
Apple-Z	undo	Undo
Apple-shift-Z	redo	Redo

Table 2: Aqua-specific keyboard shortcuts implemented in Aquamacs.

We recommend that user customizations be placed in specific locations:

- /Library/Preferences/Emacs/Preferences: Preferences for all Carbon Emacs installations
- /Library/Preferences/Aquamacs Emacs/Preferences: Preferences for Aquamacs and for all users
- /Users/username/Library/Emacs/Preferences: User-specific preferences for all Carbon Emacs installations
- /Users/username/Library/Aquamacs Emacs/Preferences: User-specific preferences for Aquamacs

It is also possible to define and store user customizations in the traditional .emacs file, which is placed in the user's home directory. This option is deprecated in Aquamacs, however.

Below are some specific customization items that may be of interest:

Emacs Command Key	Aqua Command Key
C-*	Control-*
H-*	Apple-*
A-*	Option-*
C-M-*	ESC Control-*

Table 3: Aqua-specific command keys implemented in Aquamacs.


- **Frame.** Aquamacs opens new files (and other buffers) in new frames. That is usually more convenient and allows you to use the graphical user interface of today’s computers, which did not exist when Emacs was conceived almost three decades ago. If you do not like this behavior, perhaps because you are used to traditional Emacs, just deselect “Display Buffers in Separate Frames” in the Options menu and save your choice with “Save Options.”
- **Colors and fonts for frames and modes.** Aquamacs allows you to alter specific features of the current frame via functions in the Options menu. “Set Color Theme...” will let you choose a pre-defined combination of colors and fonts. “Set Font...” gives you a choice of pre-defined fonts to use.

These settings only apply to the current frame. To make them “stick,” use the function “Set current theme as default.” Then, all future frames will open with the new colors and fonts chosen. This applies to all frame-settings that a mode or you as a user have chosen using Emacs’ configuration system. The choice of a default theme will stick until you restart Aquamacs Emacs.

Aquamacs Emacs also offers you to pick a theme specific to the current mode. For example, you can use different settings when you are editing C or LaTeX, then when you are editing a text file. That is what the function “Set current theme for current mode” is for. Again, the setting will stick for newly opened frames or or whenever you newly use a given mode, until you restart Aquamacs Emacs.

Finally, you may want to save your settings so they will stick even when you restart Aquamacs Emacs. To do so, use the function “Save Options.”

- **mac-pass-option-to-system is nil.** If this variable is set in your .emacs or Preferences.el file to non-nil, the Mac “Option” key can be used to



```
#!/usr/bin/python

import re
import sys

# coherence reordering

def summary_sentences(file):
    for line in open(file, 'r'): #
        m = re.match('^(.*?)__(.*?)__(.*?)\s(.*?)$', line)

        if m:
            yield (m.group(1), m.group(2), m.group(3), m.group(4))
        #else:
        #    if line:
        #        print "unreadable line: ", line

sents = summary_sentences(sys.argv[1])

# identify lead sentences:

for s in sents:
```

-u:-- coherence-reordering.py Top (12,13) (Python)-----

Figure 3: Aquamacs with a custom theme applied.

compose characters as handled by the system and depending on the keyboard layout chosen. Only if the Mac “Command” or “Ctrl” key is depressed at the same time, Emacs evaluates the combination using whatever modifier is set in `mac-option-modifier`.

- **mac-option-modifier’s value is meta.** This is the modifier to use for the Mac alt/option key. The value can be `alt`, `hyper`, or `super` for the respective modifier. If the value is `nil` then the key will act as the normal Mac option modifier, and the option key can be used to compose characters depending on the chosen Mac keyboard setting. Note that `mac-pass-option-to-system` takes precedence over this setting. If `mac-pass-option-to-system` is non-`nil`, simple key combinations with Option will be handled by the system in order to produce characters, and only combinations in conjunction with Command or Control will let Emacs see the modifier that is assigned to the Option key.
- **Additional customization.** Of course, Aquamacs Emacs offers you almost all the customization possibilities that Emacs has. Under “Customize Emacs,” you will find a sub-menu that allows you to browse the vast space of customization settings. Beware: some of them are complex and not easy to understand. If you would like to tinker with some Aquamacs-specific behavior, you can customize the group “Aquamacs.” See Table 4 for a complete list of the items that can be configured here.

The range of possible customizations—including restoring some of Emacs’ traditional interface conventions—is beyond the scope of this help document. However, we provide a wiki for users to share their modifications. See <http://www.emacswiki.org/cgi-bin/wiki/AquamacsEmacs/> for more details.

### 5.3 L<sup>A</sup>T<sub>E</sub>X Support

One special feature of Aquamacs is its extensive support for the editing of L<sup>A</sup>T<sub>E</sub>X documents, especially Emacs’ AucT<sub>E</sub>X mode.

The following is necessary to fully access the enhanced L<sup>A</sup>T<sub>E</sub>X functionality that Aquamacs offers:

Install Gerben Wierda’s T<sub>E</sub>X package for Mac OS X. This package is the most complete and user-friendly T<sub>E</sub>X distribution for the Mac. You can download the installer package at <http://www.rna.nl/tex.html>.




Figure 4: Aquamacs offers extensive support for  $\text{\LaTeX}$  documents.



Variable
Aquamacs Set Creator Codes After Writing Files
Aquamacs Quick Yes Or No Prompt
Aquamacs Ring Bell On Error
Aquamacs Mode Specific Default Themes
Aquamacs Auto Frame Parameters
One Buffer One Frame; Smart Frame Positioning Enforce
Smart Frame Positioning Mode
1on1 *Completions* Frame
1on1 *Help* Frame
Mac Option Modifier
Mac Pass Option To System
Mac Control Modifier
Mac Pass Control To System
Mac Command Modifier
Mac Pass Command To System

Table 4: Aquamacs-specific variables that can be customized in the Options menu.

While you can obtain T<sub>E</sub>X from other sources, only the Gerben Wierda distribution is supported in Aquamacs at this time.

Install the AucT<sub>E</sub>X package maintained by Norm Gall. This package can be downloaded from <http://yaced.sourceforge.net>. The installer will give you the option to select the installation directory; do not choose the default location, but instead pick /Library/Application Support/Emacs. (Other locations are not supported in Aquamacs.)<sup>3</sup>

### 5.3.1 Enhanced Carbon Emacs Plugin Under Development

Enrico Franconi, developer of the old Enhanced Carbon Emacs distribution that had special support for L<sup>A</sup>T<sub>E</sub>X editing via its customizations for

---

<sup>3</sup>Norm Gall maintains a full distribution of Emacs called Yet Another Carbon Emacs Distribution (Yaced) that is a standard build of Emacs on the Mac, which can be downloaded at <http://yaced.sourceforge.net>. Another distribution, with some differences, is maintained by Seiji Zenitani at <http://home.att.ne.jp/alpha/z123/emacs-mac-e.html>. If you are accustomed to the Emacs interface and prefer not to have that interface mapped to OS X conventions, you may want to consider using either of these distributions.

AucT<sub>E</sub>X mode, has revived ECE as an external plugin that can be installed on any Carbon Emacs, including Aquamacs. At this time, the ECE plugin is undergoing beta testing. The beta version can be downloaded from this location:

<http://www.inf.unibz.it/~franconi/enhanced-carbon-emacs/ec-emacs-plugin-beta.dmg>

### 5.3.2 T<sub>E</sub>Xniscopes: A Superb L<sup>A</sup>T<sub>E</sub>X Previewer

One special feature of the Enhanced Carbon Emacs plugin is its support for T<sub>E</sub>Xniscopes, a Cocoa-based L<sup>A</sup>T<sub>E</sub>X previewer that can display both PDF and DVI formats. We recommend T<sub>E</sub>Xniscopes as a superb L<sup>A</sup>T<sub>E</sub>X previewer and complement to Aquamacs/Enhanced Carbon Emacs. T<sub>E</sub>Xniscopes can be downloaded from <http://www.ing.unipi.it/~d9615/homepage/texniscopes.html>.<sup>4</sup>

## 6 Getting Help

There are many options for getting help with Aquamacs.

From within Aquamacs, you can access user documentation from the menu or from specific key combinations: c-h k (key/menu entry) brings up help for some input items; C-h f (function) gives help for an elisp function; autocompletion support is available with (tab); and c-h a brings up apropos, a search function.

For help from other Aquamacs/Emacs users, the best place to begin is the OS X Emacs mailing list. The searchable list archives are located at <http://www.esm.psu.edu/mac-tex/MacOSX-Emacs-Digests/>. For more information on subscribing to the list, see <http://www.aquamacs.org>.

Another option for general Emacs help is the [gnu.emacs.help](mailto:gnu.emacs.help) newsgroup.

In addition to requesting help, you can also offer it. Apart from answering questions at the OS X Emacs mailing list, you can also file bug reports on Aquamacs. Use the “Send Bug Report” function in the Help menu (general Emacs bugs, too), and also our Aquamacs-specific bug report system at <http://sourceforge.net/projects/aquamacs>.

---

<sup>4</sup>The developer of T<sub>E</sub>Xniscopes, Massimiliano Gubinelli, is also the creator of the Aquamacs icon.

## 7 Acknowledgments

We would also like to acknowledge the contributions of these authors, whose source code and hints on public forums have already been integrated into the build: Andrew Choi (main Emacs-to-Mac port); Drew Adams; Lawrence Akka; Emil Astrom; Stefan Bruda; Steve Dodd; Massimiliano Gubinelli (Emacs icon); Kyle E. Jones; Pekka Marjola; Yamamoto Mitsuharu; Gerd Neugebauer; Ovidiu Predesc; Steven Tamm; Bob Weiner; Milan Zamazal; and Seiji Zenitani.

Emacs is the work of Richard Stallman and many other developers.

## 8 Licenses

Aquamacs: the Emacs distribution, (c) 2005 by David Reitter, Kevin Walzer and individual contributors. Aquamacs is licensed under the terms of the GNU General Public License. For details of this license, please see <http://www.gnu.org/copyleft/gpl.html>. The Aquamacs documentation is licensed under the terms of the GNU Free Documentation License. For details of this license, please see <http://www.gnu.org/copyleft/fdl.html#SEC1>.