

Lab 5

Aim: To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

Q1. Insert new player Michale Clark with player ID 300311 in the table player

```
MySQL localhost:3306 ssl d6_10 SQL > INSERT INTO Player
-> (PlayerID, FName, LName, Country, YBorn, FTest)
-> VALUES
-> (300311, 'Michale', 'Clark', 'Australia', NULL, NULL);
Query OK, 1 row affected (0.0102 sec)
```

Q2. Insert new player Sam from India , Ahemdabad with player ID 406317 in the table player.

```
MySQL localhost:3306 ssl d6_10 SQL > INSERT INTO Player
-> (PlayerID, FName, LName, Country, YBorn, FTest)
-> VALUES
-> (406317, 'Sam', NULL, 'India', NULL, NULL);
Query OK, 1 row affected (0.0073 sec)
```

Q3. Creating View for Batsman.

```
MySQL localhost:3306 ssl d6_10 SQL > CREATE VIEW Batsman
-> (PID, FName, LName, Country, MID, Score)
-> AS
-> SELECT PlayerID, FName, LName, Country, MatchID, NRuns
-> FROM Player, Batting
-> WHERE PlayerID = PID;
Query OK, 0 rows affected (0.0080 sec)
```

```
MySQL localhost:3306 ssl d6_10 SQL > SELECT * FROM Batsman;
```

PID	FName	LName	Country	MID	Score
23001	Yuvraj	Singh	India	2755	0
25001	MS	Dhoni	India	2755	71
91001	Sanath	Jayasuriya	Sri Lanka	2755	60
94002	Chaminda	Vaas	Sri Lanka	2755	17
92002	Muthiah	Murlitharan	Sri Lanka	2755	1
89001	Sachin	Tendulkar	India	2689	91
23001	Yuvraj	Singh	India	2689	38
25001	MS	Dhoni	India	2689	36
99002	Adam	Gilchrist	Australia	2689	2
95001	Ricky	Ponting	Australia	2689	1
24001	Andrew	Symonds	Australia	2689	42
99001	Breet	Lee	Australia	2689	7
27001	Praveen	Kumar	India	2689	7
27001	Praveen	Kumar	India	2755	2
98002	Harbhajan	Singh	India	2689	3
98002	Harbhajan	Singh	India	2755	2

```
16 rows in set (0.0008 sec)
```

Q4. Creating a View for Bowling.

```
MySQL localhost:3306 ssl d6_10 SQL > CREATE VIEW Bowling2689
-> (PID, FName, LName, Country, NOvers, NWickets)
-> AS
-> SELECT PlayerID, FName, LName, Country, NOvers, NWickets
-> FROM Player, Bowling
-> WHERE PlayerID = PID
-> AND MatchID = 2689;
Query OK, 0 rows affected (0.0092 sec)
MySQL localhost:3306 ssl d6_10 SQL > SELECT * FROM Bowling2689;
+-----+-----+-----+-----+-----+-----+
| PID | FName | LName | Country | NOvers | NWickets |
+-----+-----+-----+-----+-----+-----+
| 99001 | Breet | Lee | Australia | 10 | 1 |
| 24001 | Andrew | Symonds | Australia | 3 | 1 |
| 23001 | Yuvraj | Singh | India | 3 | 0 |
| 98002 | Harbhajan | Singh | India | 10 | 1 |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.0007 sec)
```

Q5. Find the name of all players who have scored 60 or more runs.

```
MySQL localhost:3306 ssl d6_10 SQL > SELECT DISTINCT Player.FName, Player.LName
-> FROM Player, Batting
-> WHERE Player.PlayerID = Batting.PID
-> AND Batting.NRuns >= 60;
+-----+-----+
| FName | LName |
+-----+-----+
| MS | Dhoni |
| Sanath | Jayasuriya |
| Sachin | Tendulkar |
+-----+-----+
3 rows in set (0.0053 sec)
```

Q6. Find the names of bowlers that have not taken any wickets in ODI matches 2689.

```
MySQL localhost:3306 ssl d6_10 SQL > SELECT Player.FName, Player.LName
-> FROM Player, Bowling
-> WHERE Player.PlayerID = Bowling.PID
-> AND Bowling.MatchID = 2689
-> AND Bowling.Nwickets = 0;
+-----+-----+
| FName | LName |
+-----+-----+
| Yuvraj | Singh |
+-----+-----+
1 row in set (0.0005 sec)
```

Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.

```
MySQL localhost:3306 ssl d6_10 SQL > CREATE VIEW NPlayer
-> AS
-> SELECT Country, COUNT(*) AS NumberOfPlayers
-> FROM Player
-> GROUP BY Country;
```

Query OK, 0 rows affected (0.0143 sec)

```
MySQL localhost:3306 ssl d6_10 SQL > SELECT * FROM NPlayer;
```

Country	NumberOfPlayers
India	11
Australia	5
West Indies	1
Sri Lanka	3
Pakistan	2
Zimbabwe	1
South Africa	4
New Zealand	2
England	1
NULL	1

10 rows in set (0.0046 sec)