Dominio de la API de Simulación (tipos de simulator-api/src)

Cuerpo de POST /v1/sim/webhooks/trigger. Cualquier otra clave, como targetUrl, se rechaza con INVALID_REQUEST.

«Interfaz» TriggerRequest
+gateway: Gateway
+transactionId: string

«Almacén» TransactionStore <TRecord>
+save(id: string, record: TRecord): void
+findById(id: string): TRecord | undefined
+clear(): void
+size(): number

findById() da el record

«Tipo» WebhookSubject
+gateway: Gateway
+kind: "transaction" | "payment" | "order" | "charge" | "transfer" | "checkout"
+record: registro nativo (WompiTransaction, RapydPayment, ...)

«Interfaz» ResolvedScenario
+scenario: string
+source: ScenarioSource
+queryFailure?: QueryFailure

source

queryFailure

gateway

usa

gateway

«Tipo» ScenarioSource
header
gateway_data
amount
default

scenario

«Tipo» QueryFailure
QUERY_FLAPPING
QUERY_SERVER_ERROR
QUERY_SLOW

«Servicio» SignatureGenerator
+generate(subject: WebhookSubject): OutgoingWebhook
+generateSequence(subject: WebhookSubject): OutgoingWebhook[]

genera

«Enumeración» SimulatorScenario
APPROVED
APPROVAL
PENDING
DECLINED
REJECTED
EXPIRED
TIMEOUT
GATEWAY_TIMEOUT
NETWORK_ERROR
CONNECTION_ERROR
RATE_LIMIT
TOO_MANY_REQUESTS
SERVER_ERROR
INTERNAL_ERROR
BAD_GATEWAY
SERVICE_UNAVAILABLE
FLAPPING
DUPLICATE_PAYMENT
SLOW
MALFORMED_JSON
MALFORMED_BODY
HTML_ERROR
PENDING_THEN_DECLINED

resolveScenario() toma la cabecera x-simulator-scenario o x-simulate-scenario, el dato de prueba de la pasarela o un monto de RESERVED_AMOUNTS, en ese orden; si no hay ninguno, APPROVED.

«Interfaz» OutgoingWebhook
+gateway: Gateway
+query: string | null
+headers: Record<string, string>
+body: string

gateway

«Compartido» Gateway
WOMPI
RAPYD
MERCADOPAGO
KUSHKI

entrega

«Servicio» WebhookDispatcher
+deliver(webhook: OutgoingWebhook): Promise< { receiverStatus: number }>

Viene de kit-pagos-colombia, el SDK; no se redefine aquí.

config

Sale de SIMULATOR_WEBHOOK_TARGET_URL, SIMULATOR_WEBHOOK_AUTO y SIMULATOR_WEBHOOK_TIMEOUT_MS.

«Interfaz» WebhookDispatchConfig
+targetUrl?: string
+auto: boolean
+timeoutMs: number