

ColourPaletteExtractor

Release 0.5.4

Tim Churchfield

Jul 31, 2021

1	colourpaletteextractor	1
1.1	colourpaletteextractor package	1
	Python Module Index	21
	Index	23

colourpaletteextractor

1.1 colourpaletteextractor package

1.1.1 Subpackages

colourpaletteextractor.controller package

Submodules

colourpaletteextractor.controller.controller module

class

`colourpaletteextractor.controller.controller.ColourPaletteExtractorController`
(*model*: `colourpaletteextractor.model.model.ColourPaletteExtractorModel`, *view*: `colourpaletteextractor.view-mainview.MainView`)

Bases: `PySide2.QtCore.QRunnable`

ColourPaletteExtractor Controller.

Used to connect the ColourPaletteExtractor GUI signals with the appropriate slot to be able to manipulate the associated model.

Parameters

- **model** (`ColourPaletteExtractorModel`) – The main model of ColourPaletteExtractor.
- **view** (`MainView`) – The main window of ColourPaletteExtractor.

current_tab_changed (*i*: `int`)

Update the current tab index and update the view with the tab's properties.

In most cases, $i \geq 0$, however a value of $i = -2$ or -3 is also valid for performing a 'dummy' tab change to update the current view shown to the user. A value of -1 will lead to the creation of the default tab (the quick start guide).

Parameters **i** (`int`) – Index of the current tab.

Raises **ValueError** – If the value of *i* is less than -3 .

colourpaletteextractor.controller.worker module

class `colourpaletteextractor.controller.worker.Worker` (*fn*, *function_type*: `str`, *tab*: `colourpaletteextractor.view.tabview.NewTab`, **args*, ***kwargs*)

Bases: `PySide2.QtCore.QRunnable`

Worker thread used to generate the colour palette or report for an image.

Inherits from `QRunnable` to handler worker thread setup, signals and wrap-up.

Adapted from: [ref](#)

Accessed: 01/08/21

Parameters

- **fn** – The function or method to be run as a new thread (generating an image's

colour palette or its colour palette report.

- **tab** (*NewTab*) – `tabview.NewTab` object associated with the image to be processed.
- **function_type** (*str*) – The action to be run. This can either be 'colour palette' or 'report'.
- ***args** – Arguments to pass to the callback function
- ***kwargs** – Keywords to pass to the callback function

Attributes:

Parameters **progress_callback** – The function callback to run on this worker thread. Supplied args and kwargs will be passed through to the runner.

Raises **ValueError** – If the provided `function_type` is invalid.

run ()

Initialise the runner function with passed args, kwargs.

class `colourpaletteextractor.controller.worker.WorkerSignals`

Bases: `PySide2.QtCore.QObject`

Specify the signals available from a running `Worker` thread.

Adapted from: [ref](#)

Accessed: 01/08/21

Supported signals are:

error

Tuple (`exc_type`, `value`, `traceback.format_exc()`).

finished

Integer emitted upon finishing.

When generating a colour palette, the value is -2. When generating a report, the value is -3. This is used to reload the tab displaying the image with the correct settings and colour palette.

progress

`NewTab` object for which the GUI is to be updated for and the percentage complete for the current task.

The current task is either generating the colour palette for an image or generating the colour palette report for the image.

result

Object data returned from processing, anything - NOT IN USE.

staticMetaObject = `<PySide2.QtCore.QMetaObject object>`

Module contents

colourpaletteextractor.examples package

Submodules

colourpaletteextractor.examples.generatecolourpaletteexample module

Contains an example script demonstrating how to generate the colour palette of a sample image.

Module contents

colourpaletteextractor.model package

Subpackages

colourpaletteextractor.model.algorithms package

Submodules

colourpaletteextractor.model.algorithms.cielabcube module

class colourpaletteextractor.model.algorithms.cielabcube.CielabCube (
 l_star_coord: int, a_star_coord: int, b_star_coord: int)

Bases: object

A cube representing a fixed region in the CIELAB colour space.

The cube is used to hold pixels in an image that exist within the cube's region of the CIELAB colour space. The input parameters do not refer to the actual L*, a* and b* values, but depend on the *CUBE_SIZE* specified by the colour palette algorithm (in particular, any variant on the [Nieves 2020](#) algorithm).

In the case of the `nieves2020.Nieves2020CentredCubes` algorithm, the coordinates refer to the centre of the cube. For the `nieves2020.Nieves2020OffsetCubes` algorithm, the coordinates refer to the corner of the cube closest to the origin.

Parameters

- **l_star_coord** (*int*) – Perceptual lightness cube coordinate
- **a_star_coord** (*int*) – Green-red cube coordinate
- **b_star_coord** (*int*) – Blue-yellow cube coordinate

add_pixel_to_cube (*pixel: numpy.array, c_star: numpy.float64*) → None

Assign a pixel to the cube.

Parameters

- **pixel** (*np.array*) – The pixel as a [L*,a*,b*] triplet.
- **c_star** (*np.float64*) – The C* (chroma, relative saturation) value for the pixel.

property c_stars: list

The C* (chroma, relative saturation) values for all of the pixels in the cube.

$C^{\{*\}} = \sqrt{\{a^{\{*\}}\}^2 + \{b^{\{*\}}\}^2}$

Returns (*list[`np.float64`]*) – The list of C* values for all pixels in the cube.

calculate_mean_colour () → None

Calculate the mean colour of the pixels in the cube.

Nothing is calculated if the number of pixels in the cube is equal to 0.

property coordinates: numpy.array

The coordinates of the cube ([L*, a*, b*]).

In the case of the `nieves2020.Nieves2020CentredCubes` algorithm, the coordinates refer to the centre of the cube. For the `nieves2020.Nieves2020OffsetCubes` algorithm, the coordinates refer to the corner of the cube closest to the origin.

Returns (*np.array*) – The cube's coordinates.

get_c_star_percentile_value (*percentile: float*) → Union[int, numpy.percentile]

Returns the C* value for the given percentile based on the pixels in the cube.

Parameters **percentile** (*float*) – The percentile to calculate the C* value for.

Returns (Union[int, *np.percentile*]) – The C* value for the chosen percentile. If no pixels are found, the return value is 0.

get_l_star_percentile_value (*percentile: float*) → Union[int, numpy.percentile]

Returns the L* value for the given percentile based on the pixels in the cube.

Parameters **percentile** (*float*) – The percentile to calculate the L* value for.

Returns (Union[int, *np.percentile*]) – The L* value for the chosen percentile. If no pixels are found, the return value is 0.

increment_pixel_count_after_reassignment () → None
 Increase the number of pixels with this cube's mean colour by one.

property l_stars: numpy.array
 The L* values for all pixels in the cube.
Returns (np.array) – Array of L* values for all pixels in the cube.

property mean_colour: numpy.array
 The mean colour of the pixels in the cube.
Returns (np.array) – The mean colour of the cube as a [L*,a*,b*] triplet.

property pixel_count_after_reassignment: int
 The number of pixels in the recoloured image with this cube's mean colour.
Returns (int) – The number of pixels with the cube's mean colour.

property pixels: list
 The list of pixels ([L*, a*, b*] triplets) in the cube.
Returns (list[np.array]) – The list of pixels in the cube.

property relevant: bool
 The relevancy status of the cube.
Returns (bool) – True if the cube is a relevant cube. Otherwise False.

`colourpaletteextractor.model.algorithms.cielabcube.get_relative_frequencies`
 (*relevant_cubes: list, total_pixels: int*) → list

Calculate the relative frequency of each colour (relevant colour) in the recoloured image.

Parameters

- **relevant_cubes** (*list[CielabCube]*) – List of relevant `CielabCube` objects.
- **total_pixels** (*int*) – The total number of pixels in the image.

Returns (*list[float]*) – The list of relative frequencies for each relevant cube.

colourpaletteextractor.model.algorithms.dummyalgorithm module

class `colourpaletteextractor.model.algorithms.dummyalgorithm.TestAlgorithm`

Bases:

`colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm`

generate_colour_palette (*image*)

Generate the colour palette for the given image.

Analyses the given image to obtain its colour palette. Returns the recoloured image using only the colours found in the colour palette, the colour palette of the image and finally the relative frequencies of each of those colours in the recoloured image.

Parameters **image** (*np.array*) – A 3D array representing an image. It is assumed that the input image is

Returns

- **recoloured_image** (*np.array*) – The recoloured image using only the colours found in the colour palette
- **colour_palette** (*list*) – The list of colours (sRGB 8-bit values) in the colour palette
- **relative_frequencies** (*list*) – The relative frequencies of each colour in the colour palette in the recoloured image

Note It is assumed that the input image has been encoded in the sRGB colour space.

colourpaletteextractor.model.algorithms.grogan2018 module

class colourpaletteextractor.model.algorithms.grogan2018.**Grogan2018**

Bases:

colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm

generate_colour_palette (*image*)

Generate the colour palette for the given image.

Analyses the given image to obtain its colour palette. Returns the recoloured image using only the colours found in the colour palette, the colour palette of the image and finally the relative frequencies of each of those colours in the recoloured image.

Parameters **image** (*np.array*) – A 3D array representing an image. It is assumed that the input image is

Returns

- **recoloured_image** (*np.array*) – The recoloured image using only the colours found in the colour palette
- **colour_palette** (*list*) – The list of colours (sRGB 8-bit values) in the colour palette
- **relative_frequencies** (*list*) – The relative frequencies of each colour in the colour palette in the recoloured image

Note It is assumed that the input image has been encoded in the sRGB colour space.

name = 'Grogan, Hudon, McCormack and Smolic (2018) [NOT IMPLEMENTED!]'

url = 'https://v-sense.scss.tcd.ie/research/vfx-animation/automatic-palette-extraction-for-image-editing/'

colourpaletteextractor.model.algorithms.nieves2020 module

class colourpaletteextractor.model.algorithms.nieves2020.**Nieves2020** (*name, url*)

Bases:

colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm,
abc.ABC

COLOUR_CHANNELS = 3

CUBE_SIZE = 20

C_STAR_PERCENTILE = 50

L_STAR_PERCENTILE_THRESHOLD = 0.00375

MIN_L_STAR = 80

SECONDARY_THRESHOLD = 0.00375

THRESHOLD = 0.03

generate_colour_palette (*image*) → tuple

Generate the colour palette for the given image.

Analyses the given image to obtain its colour palette. Returns the recoloured image using only the colours found in the colour palette, the colour palette of the image and finally the relative frequencies of each of those colours in the recoloured image.

Parameters **image** (*np.array*) – A 3D array representing an image. It is assumed that the input image is

Returns

- **recoloured_image** (*np.array*) – The recoloured image using only the colours found in the colour palette
- **colour_palette** (*list*) – The list of colours (sRGB 8-bit values) in the colour palette
- **relative_frequencies** (*list*) – The relative frequencies of each colour in the colour palette in the recoloured image

Note It is assumed that the input image has been encoded in the sRGB colour space.

class

`colourpaletteextractor.model.algorithms.nieves2020.Nieves2020CentredCubes`

Bases: `colourpaletteextractor.model.algorithms.nieves2020.Nieves2020`

name = 'Nieves, Gomez-Robledo, Chen and Romero (2020) - Cube centred on CIELAB origin'

url = 'https://doi.org/10.1364/AO.378659'

class

`colourpaletteextractor.model.algorithms.nieves2020.Nieves2020OffsetCubes`

Bases: `colourpaletteextractor.model.algorithms.nieves2020.Nieves2020`

name = 'Nieves, Gomez-Robledo, Chen and Romero (2020) - Cube corners at CIELAB origin'

url = 'https://doi.org/10.1364/AO.378659'

`colourpaletteextractor.model.algorithms.nieves2020.convert_lab_2_rgb (image)`

Convert an image in the CIELAB colour space into the sRGB colour space.

`colourpaletteextractor.model.algorithms.nieves2020.convert_rgb_2_lab (image)`

Convert an sRGB image into the CIELAB colour space.

`colourpaletteextractor.model.algorithms.nieves2020.get_c_stars (lab)`

Return the matrix of C* (chroma) values for each pixel in the image.

`colourpaletteextractor.model.algorithms.nieves2020cython module`

`colourpaletteextractor.model.algorithms.palettealgorithm module`

class

`colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm (`

`name: str, url: str)`

Bases: `abc.ABC`

Abstract class representing an algorithm used to obtain a colour palette from an image.

Parameters

- **name** (*str*) – Name of the algorithm
- **url** (*str*) – Link to a description of the algorithm

property `continue_thread: bool`

Get the execution status of the algorithm.

A value of *false* would indicate that the algorithm should return without generation a colour palette when it next checks its execution status.

Returns **bool** – The execution status of the algorithm

abstract generate_colour_palette (*image: numpy.array*) → tuple

Generate the colour palette for the given image.

Analyses the given image to obtain its colour palette. Returns the recoloured image using only the colours found in the colour palette, the colour palette of the image and finally the relative frequencies of each of those colours in the recoloured image.

Parameters **image** (*np.array*) – A 3D array representing an image. It is assumed that the input image is

Returns

- **recoloured_image** (*np.array*) – The recoloured image using only the colours found in the colour palette
- **colour_palette** (*list*) – The list of colours (sRGB 8-bit values) in the colour palette
- **relative_frequencies** (*list*) – The relative frequencies of each colour in the colour palette in the recoloured image

Note It is assumed that the input image has been encoded in the sRGB colour space.

property name: str

Get the name of the algorithm.

Returns (str) – The name of the algorithm

set_progress_callback (*progress_callback: PySide2.QtCore.SignalInstance, tab: colourpaletteextractor.view.tabview.NewTab, image_data*) → None

Set the signal function called by the algorithm at regular intervals to update the GUI thread.

Parameters

- **progress_callback** (*QtCore.SignalInstance*) – Signal that when emitted, is used to update the GUI.
- **tab** (*NewTab*) – The tab associated with the image being analysed (see `generate_colour_palette()`).
- **image_data** (*ImageData*) – *ImageData* object that holds the image being analysed.

property url: str

Get the link to the description of the algorithm.

Returns (str) – The link to the description of the algorithm

`colourpaletteextractor.model.algorithms.palettealgorithm.get_implemented_algorithms()`

Recursively finds all subclasses of the `PaletteAlgorithm` class.

Like Python's `__class__.__subclasses__()`, but recursive. Returns a list containing all subclasses of `PaletteAlgorithm`.

Adapted from: [ref](#)

Accessed: 15/07/2021

Returns:

[object]: List of all non-abstract subclasses of `PaletteAlgorithm`

[Module contents](#)

[Submodules](#)

colourpaletteextractor.model.generatereport module

class `colourpaletteextractor.model.generatereport.ColourPaletteReport` (
image_data: colourpaletteextractor.model.imagedata.ImageData)

Bases: `fpdf.fpdf.FPDF`, `fpdf.html.HTMLMixin`

A modified FPDF object to fit the requirements for generating a PDF colour palette report.

Parameters *image_data* (*ImageData*) – The ImageData object holding the image’s data (the original image, the recoloured image, and the colour palette).

A4_HEIGHT = 297

The height of an A4 sheet of paper (mm).

A4_WIDTH = 210

The width of an A4 sheet of paper (mm).

IMAGE_START_POSITION = 30

The standard left indentation when placing an image in the PDF report (mm).

IMAGE_WIDTH = 150

The standard width of images in the PDF report (mm).

MARGIN = 10

The size of the margins to be used in the PDF report (mm).

MAX_IMAGE_HEIGHT = 257

The standard maximum height of images in the report (mm).

footer () → None

Set the footer used in the PDF report.

header () → None

Set the header used in the PDF report.

class `colourpaletteextractor.model.generatereport.ReportGenerator` (*tab:*
colourpaletteextractor.view.tabview.NewTab, *image_data:* *colourpaletteextractor.model.imagedata.ImageData*,
progress_callback: *PySide2.QtCore.SignalInstance*)

Bases: `object`

Class used to create, populate a `ColourPaletteReport` object and save the resulting PDF to disk.

Parameters

- **tab** (*NewTab*) – The tab associated with the image to be analysed.
- **image_data** (*ImageData*) – The ImageData object holding the image’s data (the original image, the recoloured image, and the colour palette).
- **progress_callback** (*QtCore.SignalInstance*) – Signal that when emitted, is used to update the GUI.

create_report () → `Optional[colourpaletteextractor.model.generatereport.ColourPaletteReport]`

Create a `ColourPaletteReport` object representing the PDF colour palette report.

Returns (`Union[ColourPaletteReport, None]`) – None if the `ColourPaletteReport` object was not properly generated, otherwise returns the populated `ColourPaletteReport` object.

save_report (*pdf:* *colourpaletteextractor.model.generatereport.ColourPaletteReport*) → None

save the `ColourPaletteReport` object representing the PDF colour palette report to disk.

Parameters *pdf* (*ColourPaletteReport*) – The `ColourPaletteReport` object to be

saved as a PDF to disk..

`colourpaletteextractor.model.generatereport.generate_report (tab: colourpaletteextractor.view.tabview.NewTab, image_data: colourpaletteextractor.model.imagedata.ImageData, progress_callback: PySide2.QtCore.SignalInstance) → None`

Generate a colour palette report for an image.

- Parameters**
- **tab** (*NewTab*) – The tab associated with the image to be analysed.
 - **image_data** (*ImageData*) – The ImageData object holding the image's data (the original image, the recoloured image, and the colour palette).
 - **progress_callback** (*QtCore.SignalInstance*) – Signal that when emitted, is used to update the GUI.

Raises **ValueError** – If the provided ImageData object does not have a recoloured image or has no colours in its colour palette.

colourpaletteextractor.model.imagedata module

class `colourpaletteextractor.model.imagedata.ImageData (file_name_and_path: str)`

Bases: object

Object to hold the data associated with an image to be analysed.

Stores the original image, its colour palette, the recoloured image, the relative frequency of each colour in the recoloured image, the algorithm used to generate the colour palette and the execution status of the thread used to generate the colour palette.

Parameters **file_name_and_path** (*str*) – Path to the image to be added.

Raises **ValueError** – If the file_name_and_path argument is None.

property **algorithm_used**

property **colour_palette**

property **colour_palette_relative_frequency**

property **continue_thread**

property **extension**

property **file_name_and_path**

static **get_image_as_q_image** (*image*)

property **image**

property **name**

property **recoloured_image**

sort_colour_palette (*reverse=True*)

colourpaletteextractor.model.model module

class `colourpaletteextractor.model.model.ColourPaletteExtractorModel (algorithm_class_name=None)`

Bases: object

DEFAULT_ALGORITHM

alias

of `colourpaletteextractor.model.algorithms.nieves2020.Nieves2020CentredCubes`

DEFAULT_HEIGHT: int = 894

DEFAULT_USER_DIRECTORY: str = 'C:/Users/timch/OneDrive/Documents/ColourPaletteExtractor/Output'

DEFAULT_USE_USER_DIRECTORY: bool = False

DEFAULT_WIDTH: int = 1523

ERROR_MSG: str = "Error! :!("

SUPPORTED_IMAGE_TYPES: set = {'jpeg', 'jpg', 'png'}

property active_thread_counter: int

add_image (*file_name_and_path*: str)

From the path to an image, create a new image_data object and add it to the dictionary of image_data objects with a new ID number.

change_output_directory (*use_user_dir*: bool, *new_user_directory*: str)

close_temporary_directory () → None

evaluate_expression (*expression*)

slot function. :param expression: :return:

generate_palette (*image_data_id*, *tab*, *progress_callback*=None, *temp_algorithm*=None)

get_image_data (*image_data_id*)

property image_data_id_dictionary

remove_image_data (*image_data_id*)

Remove image from list of images by its index.

set_algorithm (*algorithm_class_name*=<class 'colourpaletteextractor.model.algorithm-s.nieves2020.Nieves2020CentredCubes'>)

Set the algorithm use to extract the colour palette of an image.

write_default_settings ()

colourpaletteextractor.model.model.generate_colour_palette_from_image (*path_to_file*: str, *algorithm*: Optional[type] = None) → tuple

colourpaletteextractor.model.model.get_settings () → PySide2.QtCore.QSettings

Module contents

colourpaletteextractor.tests package

Subpackages

colourpaletteextractor.tests.helpers package

Submodules

colourpaletteextractor.tests.helpers.helperfunctions module

colourpaletteextractor.tests.helpers.helperfunctions.get_image (*path_to_image*: str)

Returns the image found at the given path.

Parameters *path_to_image* (str) – Path to the image to be imported.

Returns (np.array) – Image represented as a 3D array

Module contents

Submodules

colourpaletteextractor.tests.nieves2020_test module

```

colourpaletteextractor.tests.nieves2020_test.test_closest_relevant_colour_used_to_recol
( )

colourpaletteextractor.tests.nieves2020_test.test_cube_colour_must_occur_more_than_thre
( )

colourpaletteextractor.tests.nieves2020_test.test_cube_colour_must_occur_more_than_thre
( )

colourpaletteextractor.tests.nieves2020_test.test_low_a_b_colour_does_not_meet_secondar
( )

colourpaletteextractor.tests.nieves2020_test.test_low_a_b_colour_does_not_meet_secondar
( )

colourpaletteextractor.tests.nieves2020_test.test_nieves2020_centred_cubes_constructor
( )

colourpaletteextractor.tests.nieves2020_test.test_nieves2020_offset_cubes_constructor
( )

colourpaletteextractor.tests.nieves2020_test.test_primary_requirements_1( )

colourpaletteextractor.tests.nieves2020_test.test_primary_requirements_2( )

colourpaletteextractor.tests.nieves2020_test.test_primary_requirements_3( )

colourpaletteextractor.tests.nieves2020_test.test_recoloured_image_of_same_size_1
( )

colourpaletteextractor.tests.nieves2020_test.test_recoloured_image_two_colours_1
( )

colourpaletteextractor.tests.nieves2020_test.test_recoloured_image_two_colours_2
( )

colourpaletteextractor.tests.nieves2020_test.test_two_colours_in_same_cube_can_meet_sec
( )

```

Module contents

colourpaletteextractor.view package

Submodules

colourpaletteextractor.view.mainview module

class colourpaletteextractor.view.mainview.**MainView** (parent=None)

Bases: PySide2.QtWidgets.QMainWindow

The main window of the ColourPaletteExtractor application.

Parameters **parent** – Parent object of the MainWindow. Defaults to None.

tabs

tabbed widget for displaying and managing imported images.

Type `QTabWidget`

colour_palette_dock

Type `tabview.ColourPaletteDock`

_close_request_action

Action for closing the application

Type QAction

open_action

Action for opening a new image

Type QAction

generate_report_action

Action for generating a report for an image

Type QAction

generate_all_report_action

Action for generating a report for all images with a colour palette

Type QAction

generate_palette_action

Action for generating the colour palette for an image

Type QAction

generate_all_palette_action

Action for generating the colour palette for all images

Type QAction

stop_action

Action for stopping the report or colour palette being generated for an image

Type QAction

preferences_menu_action

Action for opening the preferences menu

Type QAction

show_help_action

Action for showing the quick start guide

Type QAction

toggle_recoloured_image_action

Action for toggling between the original and the recoloured image

Type QAction

zoom_in_action

Action for zooming into an image

Type QAction

zoom_out_action

Action for zooming out of an image

Type QAction

about_menu_action

Action for showing the about information widget

Type QAction

show_palette_dock_action
 Action for showing the colour palette dock
 Type QAction

show_toolbar_action
 Action for showing the toolbar
 Type QAction

tools
 (QToolBar): Toolbar for holding QToolButtons used in the GUI

status
 Status bar for holding hints, the progress bar and the current version of the application
 Type `otherviews.StatusBar`

RESOURCES_DIR = 'resources'
 The name of the directory containing the icons and images used for the GUI.
 Type str

app_icon = 'app_icon'
 The name of the file used as the application's icon.
 Type str

closeEvent (*event: PySide2.QtGui.QCloseEvent*) → None
 Intercept GUI close event to check if the user wishes to close the GUI.
 Parameters **event** (*QtGui.QCloseEvent*) – Close event

close_current_tab (*tab_index: int*) → int
 Close the tab with the given index.
 Parameters **tab_index** (*int*) – The index of the tab to close
 Returns (int) – The index of the tab that is now visible after closing the selected tab

create_new_tab (*image_id, image_data*) → None
 Create a new image tab for the main window.
 Parameters

- **image_id** (*str*) – ID of the image to be used for the new tab (e.g., 'Tab_1')
- **image_data** (*model.imagedata.ImageData*) – Object containing tab and image properties and state

default_new_tab_image = 'images:how-to-dark-mode.png'
 The name of the file used as the default new tab (the quick start guide).
 Type str

resources_path = 'C:\\\\Users\\timch\\PycharmProjects\\MSc-CS-Project---ColourPaletteExtractor\\colourpaletteextractor\\view\\resources'
 The path to the resources used for the GUI.
 This will vary depending on whether the code has been compiled into an application or is been run from the command line.
 Type str

show_file_dialog_box (*supported_file_types: set*) → tuple
 Show the dialog box for importing images.
 Parameters **supported_file_types** (*set[str]*) – The supported file types (e.g., '.png')

- Returns**
- **list** (*str*) – The list of the absolute paths to the images to be loaded into the application
 - **str** – The filter used when selecting the images to import

staticMetaObject = <PySide2.QtCore.QMetaObject object>

colourpaletteextractor.view.otherviews module

class colourpaletteextractor.view.otherviews.**AboutBox** (*parent=None*)

Bases: PySide2.QtWidgets.QMessageBox

Message box to show the basic information about the application.

Parameters **parent** – The parent object of the AboutBox. The default is None.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

class colourpaletteextractor.view.otherviews.**BatchGenerationProgressWidget**

Bases: PySide2.QtWidgets.QDialog

Custom dialog box shown when multiple colour palette or reports are being generated.

Shows the number of threads to be run and the number of threads completed. Is also has a simple animation attached to it so the user knows that the application has not frozen and is still processing their images.

label

Label used to show the number of threads to be run and the number completed.

Type QLabel

cancel_batch_button

The button used to notify the controller object that the user wishes to cancel the current batch processing.

Type QPushButton

set_cancel_text () → None

Set the text shown to cancelling to let the user know that any incomplete threads are to be cancelled.

show_widget (*total_count: int, batch_type: str*) → None

Reset and show the widget.

- Parameters**
- **total_count** (*int*) – The total number of threads to be processed.
 - **batch_type** (*str*) – The text clarifying what task is being carried out as a batch process.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

update_progress () → None

Update the batch progress bar by increasing the number of completed threads by one.

class colourpaletteextractor.view.otherviews.**ElidedLabel** (*text='', width=40, parent=None*)

Bases: PySide2.QtWidgets.QLabel

Status bar message label that will become elided if there is not enough space to display the entire message.

Adapted from: [ref1](#) and [ref2](#)

Accessed: 18/07/2021

Args:

text (str): The text to be shown in the label. The default is an empty string
width (int): The minimum width of the label. The default is 40.
parent: The parent object of the ElidedLabel. The default is None.

elided_text () → str

Get the elided text shown by the label.

Returns (str) – The elided text

paintEvent (event: PySide2.QtCore.QEvent.Type.Paint) → None

Update the text shown by the label on receiving a paint event.

Parameters event (QEvent.Type.Paint) – A paint event

staticMetaObject = <PySide2.QtCore.QMetaObject object>

class colourpaletteextractor.view.otherviews.**ErrorBox** (box_type: Optional[str] = None, parent=None)

Bases: PySide2.QtWidgets.QMessageBox

Message box to show warnings and errors.

Parameters • **box_type** (str) – The error box type. Used to customise the icon and main text show.

• **parent** – Parent object of the ErrorBox. Defaults to None.

header

The heading of the ErrorBox.

Type str

append_title (error: Exception) → None

Append the title with additional information from an exception.

Parameters error (Exception) – Exception whose error summary message is appended to the title text.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

class colourpaletteextractor.view.otherviews.**PreferencesWidget** (parent=None)

Bases: PySide2.QtWidgets.QDialog

The dialog box for setting a user's preferences.

Currently, the user can change the algorithm used to generate the colour palette, as well as the output directory for any reports that are generated.

Parameters parent – The parent object of the PreferencesWidget. The default is None.

browse_button

Button used to open the operating system's file explorer to select a valid output directory.

Type QPushButton

user_path_selector

Text window used to show the user's currently selected output directory.

Type QLineEdit

default_path_button

Button used to select the default output directory.

Type QRadioButton

user_path_button

Button used to select the user's output directory.

Type `QRadioButton`

output_tab

The output directory settings tab of the preferences dialog box.

Type `QWidget`

algorithm_tab

The algorithm settings tab of the preferences dialog box.

Type `QWidget`

get_algorithms_and_buttons () → tuple

Get the list of algorithm classes and their associated buttons.

Returns

- (list[palettealgorithm.PaletteAlgorithm]) – List of algorithm classes.
- (list[QRadioButton]) – List of buttons associated with the algorithm classes.

show_output_directory_dialog_box (current_path: str)

Show the dialog box for selecting output directory for reports.

Parameters **current_path** (str) – The path to open the system's file explorer to.

Returns (str) – Path to the new output directory.

show_preferences () → None

Show the preferences widget.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

update_preferences () → None

Update the preferences dialog box with the correct settings.

class colourpaletteextractor.view.otherviews.StatusBar (parent=None)

Bases: `PySide2.QtWidgets.QStatusBar`

The status bar at the bottom of the main window.

This holds the current shortcut tip for the given tab, as well as the progress bar for showing the current progress towards generating a report or the image's colour palette.

Parameters **parent** – Parent object of the StatusBar. Defaults to None.

_status_label

Primary status label.

Type `ElidedLabel`

_progress_bar

Progress bar used to track the progress of generating a colour palette or a report.

Type `QProgressBar`

_max_progress

Maximum value for the progress bar.

Type `int`

_min_progress

Minimum value for the progress bar.

Type `int`

set_status_bar (*state: int*) → None

Set the state of the status bar elements.

Depending on the state, the primary status label will change to reflect what the application is currently processing.

Parameters *state* (*int*) – The new state of the status bar.

Raises **ValueError** – If state is not a valid state.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

update_progress_bar (*n: float*) → None

Update the current level of progress for the status bar.

Parameters *n* (*float*) – New level of progress for the progress bar.

Raises **ValueError** – If the new progress value exceeds the predefined limits of the progress bar.

colourpaletteextractor.view.tabview module

class colourpaletteextractor.view.tabview.ColourBox (*parent=None*)

Bases: PySide2.QtWidgets.QLabel

Modified QLabel to hold an individual colour in the colour palette.

Parameters *parent* – The parent object of the ColourBox. The default is None.

enterEvent (*event: PySide2.QtCore.QEvent*) → None

Intercept an enter event.

In the future, this could be used to trigger the highlighting regions of the image that use this colour in the recoloured image.

Parameters *event* (*QEvent*) – Enter event.

leaveEvent (*event: PySide2.QtCore.QEvent*)

Intercept a leave event.

In the future, this could be used to cancel the highlighting of regions of the image that use this colour in the recoloured image.

Parameters *event* (*QEvent*) – Leave event.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

class colourpaletteextractor.view.tabview.ColourPaletteDock (*parent=None*)

Bases: PySide2.QtWidgets.QDockWidget

A modified QDockWidget to hold small images of each colour in an image's colour palette.

Parameters *parent* – Parent object of the ColourPaletteDock. Defaults to None.

add_colour_palette (*colour_palette: list, image_id: str, relative_frequencies: Optional[list] = None*) → None

Clear the colour palette dock and add a new image's colour palette to the dock.

Parameters • **colour_palette** (*list[np.array]*) – List of colours in the colour palette.

• **image_id** (*str*) – The ID ('Tab_xx') associated with a tab and image.

• **relative_frequencies** (*list[float]*) – The relative frequencies of each colour in the colour palette in the recoloured image.

remove_colour_palette () → None

Remove all of the ColourBox labels from the colour palette dock.

Adapted from: [ref](#)

Accessed: 27/07/2021

staticMetaObject = <PySide2.QtCore.QMetaObject object>

class colourpaletteextractor.view.tabview.**ImageDisplay** (*image_data:*
colourpaletteextractor.model.imagedata.ImageData, parent=None)

Bases: PySide2.QtWidgets.QLabel

A modified QLabel to display and manipulate the current image.

Parameters

- **image_data** (*imagedata.ImageData*) – The ImageData object that hold the information associated with an image.
- **parent** – Parent object of the ImageDisplay. Defaults to None.

event (*event: PySide2.QtCore.QEvent*) → bool

Intercept the QLabel's event if it is a gesture to allow for zooming into and out of the current image.

Also calls the super class' event handler at the end.

Parameters event (*QEvent*) – An event.

Returns (bool) – The result from the super class' event handler.

image_zoom (*mouse_pos: PySide2.QtCore.QPoint*, *value: float*) → None

Zoom into or out of an image at the mouse pointer's current location.

Parameters

- **mouse_pos** (*QtCore.QPoint*) – Current position of the mouse cursor.
- **value** (*float*) – The degree of magnification of the image.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

update_image (*image: numpy.array*) → None

Update the image shown by the ImageDisplay.

Parameters image (*np.array*) – Numpy array representing an image.

zoom_factor = 1.25

The zoom-in factor used when the user zoom's into the image via the zoom-in button.

zoom_in (*zoom_factor: float = 1.25*) → None

Zoom into the current image.

Parameters zoom_factor (*float*) – The new magnification factor for the image.

zoom_out (*zoom_factor: float = 0.8*) → None

Zoom out of the current image.

Parameters zoom_factor (*float*) – The new magnification factor for the image.

zoom_out_factor = 0.8

The zoom-out factor used when the user zoom's out of the image via the zoom-out button.

class colourpaletteextractor.view.tabview.**NewTab** (*image_id: Optional[str] = None*,
image_data: Optional[colourpaletteextractor.model.imagedata.ImageData] = None, parent=None)

Bases: PySide2.QtWidgets.QScrollArea

Modified QScrollArea to display and manipulate an image (via the *ImageDisplay* class).

Parameters

- **image_id** (*str*) – The ID ('Tab_xx') associated with a tab and image.
- **image_data** (*imagedata.ImageData*) – The ImageData object that hold the information associated with an image.

- **parent** – Parent object of the NewTab Defaults to None.

image_display

ImageDisplay used to show the QPixmap representation of the current image.

Type [ImageDisplay](#)

change_toggle_recoloured_image_pressed () → None

Toggle the _toggle_recoloured_image_pressed attribute between true and false (its opposite).

property generate_palette_available: bool

The ability to generate the colour palette for the current NewTab object.

Returns (bool) – Returns true if the colour palette can be generated. Otherwise false.

property generate_report_available: bool

The ability to generate the colour palette report for the current NewTab object.

Returns (bool) – Returns true if the colour palette report can be generated. Otherwise false.

get_slider_positions () → PySide2.QtCore.QPointF

Get the grip positions of the horizontal and vertical scrollbars.

Returns (QPointF) – The position of the grip for the horizontal and vertical scrollbars.

property image_id: str

The image ID of the images and its data that is linked to the current NewTab object

Returns (str) – The ID ('Tab_xx') associated with a tab and image.

property progress_bar_value: float

The current level of progress shown by the status bar for the associated NewTab object.

Returns (float) – The current level of progress shown by the status bar.

set_slider_positions (x_position: float, y_position: float) → None

Set the position of the horizontal and vertical scrollbar's grip.

Parameters • **x_position (float)** – Position of the grip for the horizontal scrollbar.

 • **y_position (float)** – Position of the grip for the vertical scrollbar.

staticMetaObject = <PySide2.QtCore.QMetaObject object>

property status_bar_state: int

The current status bar state, represented by an integer.

See the `otherviews.StatusBar.set_status_bar ()` method for more information.

Returns (int) – The current status bar state.

property toggle_recoloured_image_available: bool

Stores the availability of the recoloured image (if it available to be displayed or not).

Returns (bool) – True if the recoloured image is available. Otherwise false.

property toggle_recoloured_image_pressed: bool

The status of the toggle button used to switch between the original image and the recoloured image.

Returns (bool) – True if the recoloured image is displayed by the GUI. Otherwise false.

wheelEvent (event: PySide2.QtGui.QWheelEvent) → None

Intercepts the super class' wheelEvent to allow zooming into and out of an image using the mousewheel.

Also calls the super class' wheelEvent handler at the end.

Parameters **event** (*QWheelEvent*) – Mousewheel event

property **zoom_level**: float

The degree of magnification for the currently displayed image.

Returns (float) – The degree of magnification for the current image.

Module contents

1.1.2 Submodules

1.1.3 colourpaletteextractor.test_script module

1.1.4 Module contents

- genindex
- modindex
- search

C

- [colourpaletteextractor](#), 20
 - [colourpaletteextractor.controller](#), 2
 - [colourpaletteextractor.controller.controller](#), 1
 - [colourpaletteextractor.controller.worker](#), 1
 - [colourpaletteextractor.examples](#), 2
 - [colourpaletteextractor.examples.generatecolourpaletteexample](#), 2
 - [colourpaletteextractor.model](#), 10
 - [colourpaletteextractor.model.algorithms](#), 7
 - [colourpaletteextractor.model.algorithms.cielabcube](#), 3
 - [colourpaletteextractor.model.algorithms.dummyalgorithm](#), 4
 - [colourpaletteextractor.model.algorithms.grogan2018](#), 5
 - [colourpaletteextractor.model.algorithms.nieves2020](#), 5
 - [colourpaletteextractor.model.algorithms.palettealgorithm](#), 6
 - [colourpaletteextractor.model.generatereport](#), 8
 - [colourpaletteextractor.model.imagedata](#), 9
 - [colourpaletteextractor.model.model](#), 9
 - [colourpaletteextractor.test_script](#), 20
 - [colourpaletteextractor.tests](#), 11
 - [colourpaletteextractor.tests.helpers](#), 10
 - [colourpaletteextractor.tests.helpers.helperfunctions](#), 10
 - [colourpaletteextractor.tests.nieves2020_test](#), 11
 - [colourpaletteextractor.view](#), 20
 - [colourpaletteextractor.view.mainview](#), 11
 - [colourpaletteextractor.view.otherviews](#), 14
 - [colourpaletteextractor.view.tabview](#), 17

Symbols

`_close_request_action` (colourpaletteextractor.view.mainview.MainView attribute), 12

`_max_progress` (colourpaletteextractor.view.otherviews.StatusBar attribute), 16

`_min_progress` (colourpaletteextractor.view.otherviews.StatusBar attribute), 16

`_progress_bar` (colourpaletteextractor.view.otherviews.StatusBar attribute), 16

`_status_label` (colourpaletteextractor.view.otherviews.StatusBar attribute), 16

A

`A4_HEIGHT` (colourpaletteextractor.model.generatorreport.ColourPaletteReport attribute), 8

`A4_WIDTH` (colourpaletteextractor.model.generatorreport.ColourPaletteReport attribute), 8

`about_menu_action` (colourpaletteextractor.view.mainview.MainView attribute), 12

`AboutBox` (class in colourpaletteextractor.view.otherviews), 14

`active_thread_counter` (colourpaletteextractor.model.model.ColourPaletteExtractorModel property), 10

`add_colour_palette()` (colourpaletteextractor.view.tabview.ColourPaletteDock method), 17

`add_image()` (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), 10

`add_pixel_to_cube()` (colourpaletteextractor.model.algorithms.cielabcube.CielabCube method), 3

`algorithm_tab` (colourpaletteextractor.view.otherviews.PreferencesWidget attribute),

16

`algorithm_used` (colourpaletteextractor.model.imagedata.ImageData property), 9

`app_icon` (colourpaletteextractor.view.mainview.MainView attribute), 13

`append_title()` (colourpaletteextractor.view.otherviews.ErrorBox method), 15

B

`BatchGenerationProgressWidget` (class in colourpaletteextractor.view.otherviews), 14

`browse_button` (colourpaletteextractor.view.otherviews.PreferencesWidget attribute), 15

C

`C_STAR_PERCENTILE` (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5

`c_stars` (colourpaletteextractor.model.algorithms.cielabcube.CielabCube property), 3

`calculate_mean_colour()` (colourpaletteextractor.model.algorithms.cielabcube.CielabCube method), 3

`cancel_batch_button` (colourpaletteextractor.view.otherviews.BatchGenerationProgressWidget attribute), 14

`change_output_directory()` (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), 10

`change_toggle_recoloured_image_pressed()` (colourpaletteextractor.view.tabview.NewTab method), 19

`CielabCube` (class in colourpaletteextractor.model.algorithms.cielabcube), 3

`close_current_tab()` (colourpaletteextractor.view.mainview.MainView method), 13

`close_temporary_directory()` (colourpaletteextractor.model.model.ColourPaletteExtractorModel

- method), 10
 - closeEvent() (colourpaletteextractor.view.main-view.MainView method), 13
 - COLOUR_CHANNELS (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5
 - colour_palette (colourpaletteextractor.model.imagedata.ImageData property), 9
 - colour_palette_dock (colourpaletteextractor.view.mainview.MainView attribute), 11
 - colour_palette_relative_frequency (colourpaletteextractor.model.imagedata.ImageData property), 9
 - ColourBox (class in colourpaletteextractor.view.tabview), 17
 - ColourPaletteDock (class in colourpaletteextractor.view.tabview), 17
 - colourpaletteextractor
 - module, 20
 - colourpaletteextractor.controller
 - module, 2
 - colourpaletteextractor.controller.controller
 - module, 1
 - colourpaletteextractor.controller.worker
 - module, 1
 - colourpaletteextractor.examples
 - module, 2
 - colourpaletteextractor.examples.generatecolourpaletteextractor
 - module, 2
 - colourpaletteextractor.model
 - module, 10
 - colourpaletteextractor.model.algorithms
 - module, 7
 - colourpaletteextractor.model.algorithms.cielabcube
 - module, 3
 - colourpaletteextractor.model.algorithms.dummyalgorithm
 - module, 4
 - colourpaletteextractor.model.algorithms.grogan2018
 - module, 5
 - colourpaletteextractor.model.algorithms.nieves2020
 - module, 5
 - colourpaletteextractor.model.algorithms.palettealgorithm
 - module, 6
 - colourpaletteextractor.model.generatereport
 - module, 8
 - colourpaletteextractor.model.imagedata
 - module, 9
 - colourpaletteextractor.model.model
 - module, 9
 - colourpaletteextractor.test_script
 - module, 20
 - colourpaletteextractor.tests
 - module, 11
 - colourpaletteextractor.tests.helpers
 - module, 10
 - colourpaletteextractor.tests.helpers.helperfunctions
 - module, 10
 - colourpaletteextractor.tests.nieves2020_test
 - module, 11
 - colourpaletteextractor.view
 - module, 20
 - colourpaletteextractor.view.mainview
 - module, 11
 - colourpaletteextractor.view.otherviews
 - module, 14
 - colourpaletteextractor.view.tabview
 - module, 17
 - ColourPaletteExtractorController (class in colourpaletteextractor.controller.controller), 1
 - ColourPaletteExtractorModel (class in colourpaletteextractor.model.model), 9
 - ColourPaletteReport (class in colourpaletteextractor.model.generatereport), 8
 - continue_thread (colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm property), 6
 - continue_thread (colourpaletteextractor.model.imagedata.ImageData property), 9
 - convert_lab_2_rgb() (in module colourpaletteextractor.model.algorithms.nieves2020), 6
 - convert_rgb_2_lab() (in module colourpaletteextractor.model.algorithms.nieves2020), 6
 - convert_rgb_2_lab() (in module colourpaletteextractor.model.algorithms.nieves2020), 6
 - create_new_tab() (colourpaletteextractor.view.mainview.MainView method), 13
 - create_report() (colourpaletteextractor.model.generatereport.ReportGenerator method), 8
 - CUBE_SIZE (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5
 - current_tab_changed() (colourpaletteextractor.controller.controller.ColourPaletteExtractorController method), 1
- ## D
- DEFAULT_ALGORITHM (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 9
 - DEFAULT_HEIGHT (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 9
 - default_new_tab_image (colourpaletteextractor.view.mainview.MainView attribute), 13
 - default_path_button (colourpaletteextractor.view.otherviews.PreferencesWidget attribute), 15
 - DEFAULT_USE_USER_DIRECTORY (colour-

paletteextractor.model.model.ColourPaletteExtractorModel.generate_palette() (colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm method), 7

DEFAULT_USER_DIRECTORY (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 10

DEFAULT_WIDTH (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 10

E

elided_text() (colourpaletteextractor.view.otherviews.ElidedLabel method), 15

ElidedLabel (class in colourpaletteextractor.view.otherviews), 14

enterEvent() (colourpaletteextractor.view.tabview.ColourBox method), 17

error (colourpaletteextractor.controller.worker.WorkerSignals attribute), 2

ERROR_MSG (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 10

ErrorMessage (class in colourpaletteextractor.view.otherviews), 15

evaluate_expression() (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), 10

event() (colourpaletteextractor.view.tabview.ImageDisplay method), 18

extension (colourpaletteextractor.model.image_data.ImageData property), 9

F

file_name_and_path (colourpaletteextractor.model.imagedata.ImageData property), 9

finished (colourpaletteextractor.controller.worker.WorkerSignals attribute), 2

footer() (colourpaletteextractor.model.generatorreport.ColourPaletteReport method), 8

G

generate_all_palette_action (colourpaletteextractor.view.mainview.MainView attribute), 12

generate_all_report_action (colourpaletteextractor.view.mainview.MainView attribute), 12

generate_colour_palette() (colourpaletteextractor.model.algorithms.dummyalgorithm.TestAlgorithm method), 4

generate_colour_palette() (colourpaletteextractor.model.algorithms.grogan2018.Grogan2018 method), 5

generate_colour_palette() (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 method), 5

generate_palette() (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), 10

generate_palette_action (colourpaletteextractor.view.mainview.MainView attribute), 12

generate_palette_available (colourpaletteextractor.view.tabview.NewTab property), 19

generate_report() (in module colourpaletteextractor.model.generatorreport), 9

generate_report_action (colourpaletteextractor.view.mainview.MainView attribute), 12

generate_report_available (colourpaletteextractor.view.tabview.NewTab property), 19

get_algorithms_and_buttons() (colourpaletteextractor.view.otherviews.PreferencesWidget method), 16

get_c_star_percentile_value() (colourpaletteextractor.model.algorithms.cielabcube.CielabCube method), 3

get_c_stars() (in module colourpaletteextractor.model.algorithms.nieves2020), 6

get_image() (in module colourpaletteextractor.tests.helpers.helperfunctions), 10

get_image_as_q_image() (colourpaletteextractor.model.imagedata.ImageData static method), 9

get_image_data() (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), 10

get_implemented_algorithms() (in module colourpaletteextractor.model.algorithms.palettealgorithm), 7

get_l_star_percentile_value() (colourpaletteextractor.model.algorithms.cielabcube.CielabCube method), 3

get_relative_frequencies() (in module colourpaletteextractor.model.algorithms.cielabcube), 4

get_settings() (in module colourpaletteextractor.model.model), 10

get_slider_positions() (colourpaletteextractor.view.tabview.NewTab method), 19

Grogan2018 (class in colourpaletteextractor.model.algorithms.grogan2018), 5

H

header (colourpaletteextractor.view.otherviews.ErrorMessage attribute), 15

header() (colourpaletteextractor.model.generatorreport.ColourPaletteReport method), 8

- atereport.ColourPaletteReport method), 8
- I
- image (colourpaletteextractor.model.imagedata.ImageData property), 9
- image_data_id_dictionary (colourpaletteextractor.model.model.ColourPaletteExtractorModel property), 10
- image_display (colourpaletteextractor.view.tabview.NewTab attribute), 19
- image_id (colourpaletteextractor.view.tabview.NewTab property), 19
- IMAGE_START_POSITION (colourpaletteextractor.model.generatereport.ColourPaletteReport attribute), 8
- IMAGE_WIDTH (colourpaletteextractor.model.generatereport.ColourPaletteReport attribute), 8
- image_zoom() (colourpaletteextractor.view.tabview.ImageDisplay method), 18
- ImageData (class in colourpaletteextractor.model.imagedata), 9
- ImageDisplay (class in colourpaletteextractor.view.tabview), 18
- increment_pixel_count_after_reassignment() (colourpaletteextractor.model.algorithms.cielabcube.CielabCube method), 4
- L
- L_STAR_PERCENTILE_THRESHOLD (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5
- l_stars (colourpaletteextractor.model.algorithms.cielabcube.CielabCube property), 4
- label (colourpaletteextractor.view.otherviews.BatchGenerationProgressWidget attribute), 14
- leaveEvent() (colourpaletteextractor.view.tabview.ColourBox method), 17
- M
- MainView (class in colourpaletteextractor.view.mainview), 11
- MARGIN (colourpaletteextractor.model.generatereport.ColourPaletteReport attribute), 8
- MAX_IMAGE_HEIGHT (colourpaletteextractor.model.generatereport.ColourPaletteReport attribute), 8
- mean_colour (colourpaletteextractor.model.algorithms.cielabcube.CielabCube property), 4
- MIN_L_STAR (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5
- module
 - colourpaletteextractor, 20
 - colourpaletteextractor.controller, 2
 - colourpaletteextractor.controller.controller, 1
 - colourpaletteextractor.controller.worker, 1
 - colourpaletteextractor.examples, 2
 - colourpaletteextractor.examples.generatecolourpaletteexamples, 2
 - colourpaletteextractor.model, 10
 - colourpaletteextractor.model.algorithms, 7
 - colourpaletteextractor.model.algorithms.cielabcube, 3
 - colourpaletteextractor.model.algorithms.dummyalgorithm, 4
 - colourpaletteextractor.model.algorithms.grogan2018, 5
 - colourpaletteextractor.model.algorithms.nieves2020, 5
 - colourpaletteextractor.model.algorithms.palettealgorithm, 6
 - colourpaletteextractor.model.generatereport, 8
 - colourpaletteextractor.model.imagedata, 9
 - colourpaletteextractor.model.model, 9
 - colourpaletteextractor.test_script, 20
 - colourpaletteextractor.tests, 11
 - colourpaletteextractor.tests.helpers, 10
 - colourpaletteextractor.tests.helpers.helperfunctions, 10
 - colourpaletteextractor.tests.nieves2020_test, 11
 - colourpaletteextractor.view, 20
 - colourpaletteextractor.view.mainview, 11
 - colourpaletteextractor.view.otherviews, 14
 - colourpaletteextractor.view.tabview, 17
- N
- name (colourpaletteextractor.model.algorithms.grogan2018.Grogan2018 attribute), 5
- name (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020CentredCubes attribute), 6
- name (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020OffsetCubes attribute), 6
- name (colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm property), 7
- name (colourpaletteextractor.model.imagedata.ImageData property), 9
- NewTab (class in colourpaletteextractor.view.tabview), 18
- Nieves2020 (class in colourpaletteextractor.model.algorithms.nieves2020), 5
- Nieves2020CentredCubes (class in colourpaletteextractor.model.algorithms.nieves2020), 6

Nieves2020OffsetCubes (class in colourpalette-extractor.model.algorithms.nieves2020),
6

O

open_action (colourpaletteextractor.view.main-view.MainView attribute), 12

output_tab (colourpaletteextractor.view.other-views.PreferencesWidget attribute),
16

P

paintEvent() (colourpaletteextractor.view.other-views.ElidedLabel method), 15

PaletteAlgorithm (class in colourpaletteextrac-tor.model.algorithms.palettealgorithm),
6

pixel_count_after_reassignment (colourpalette-extractor.model.algorithms.cielabcube.CielabCube property), 4

pixels (colourpaletteextractor.model.algorith-m-s.cielabcube.CielabCube property), 4

preferences_menu_action (colourpaletteextrac-tor.view.mainview.MainView attribute), 12

PreferencesWidget (class in colourpaletteex-tractor.view.otherviews), 15

progress (colourpaletteextractor.controller.-worker.WorkerSignals attribute), 2

progress_bar_value (colourpaletteextrac-tor.view.tabview.NewTab property), 19

R

recoloured_image (colourpaletteextractor.mod-el.imagedata.ImageData property), 9

relevant (colourpaletteextractor.model.algo-rithms.cielabcube.CielabCube proper-ty), 4

remove_colour_palette() (colourpaletteextrac-tor.view.tabview.ColourPaletteDock method), 17

remove_image_data() (colourpaletteextractor.-model.model.ColourPaletteExtractorModel method), 10

ReportGenerator (class in colourpaletteextrac-tor.model.generatereport), 8

RESOURCES_DIR (colourpaletteextrac-tor.view.mainview.MainView attribute), 13

resources_path (colourpaletteextractor.view.-mainview.MainView attribute), 13

result (colourpaletteextractor.controller.work-er.WorkerSignals attribute), 2

run() (colourpaletteextractor.controller.worker.-Worker method), 2

S

save_report() (colourpaletteextractor.model.-generatereport.ReportGenerator method), 8

SECONDARY_THRESHOLD (colourpaletteex-tractor.model.algorithms.nieves2020.Nieves2020 attribute), 5

set_algorithm() (colourpaletteextractor.model.-model.ColourPaletteExtractorModel method), 10

set_cancel_text() (colourpaletteextrac-tor.view.otherviews.BatchGenerationProgressWidget method), 14

set_progress_callback() (colourpaletteextrac-tor.model.algorithms.palettealgorithm.PaletteAlgorithm method), 7

set_slider_positions() (colourpaletteextrac-tor.view.tabview.NewTab method), 19

set_status_bar() (colourpaletteextrac-tor.view.otherviews.StatusBar method), 17

show_file_dialog_box() (colourpaletteextrac-tor.view.mainview.MainView method), 13

show_help_action (colourpaletteextrac-tor.view.mainview.MainView attribute), 12

show_output_directory_dialog_box() (colour-paletteextractor.view.otherviews.PreferencesWidget method), 16

show_palette_dock_action (colourpaletteextrac-tor.view.mainview.MainView attribute), 13

show_preferences() (colourpaletteextrac-tor.view.otherviews.PreferencesWidget method), 16

show_toolbar_action (colourpaletteextrac-tor.view.mainview.MainView attribute), 13

show_widget() (colourpaletteextrac-tor.view.otherviews.BatchGenerationProgressWidget method), 14

sort_colour_palette() (colourpaletteextractor.-model.imagedata.ImageData method),
9

staticMetaObject (colourpaletteextractor.con-troller.worker.WorkerSignals attribute), 2

staticMetaObject (colourpaletteextractor.view.-mainview.MainView attribute), 14

staticMetaObject (colourpaletteextrac-tor.view.otherviews.AboutBox attribute), 14

staticMetaObject (colourpaletteextrac-tor.view.otherviews.BatchGenerationProgressWidget attribute), 14

staticMetaObject (colourpaletteextrac-

tor.view.otherviews.ElidedLabel attribute), 15

staticMetaObject (colourpaletteextractor.view.otherviews.ErrorBox attribute), 15

staticMetaObject (colourpaletteextractor.view.otherviews.PreferencesWidget attribute), 16

staticMetaObject (colourpaletteextractor.view.otherviews.StatusBar attribute), 17

staticMetaObject (colourpaletteextractor.view.tabview.ColourBox attribute), 17

staticMetaObject (colourpaletteextractor.view.tabview.ColourPaletteDock attribute), 18

staticMetaObject (colourpaletteextractor.view.tabview.ImageDisplay attribute), 18

staticMetaObject (colourpaletteextractor.view.tabview.NewTab attribute), 19

status (colourpaletteextractor.view.mainview.-MainView attribute), 13

status_bar_state (colourpaletteextractor.view.tabview.NewTab property), 19

StatusBar (class in colourpaletteextractor.view.otherviews), 16

stop_action (colourpaletteextractor.view.mainview.MainView attribute), 12

SUPPORTED_IMAGE_TYPES (colourpaletteextractor.model.model.ColourPaletteExtractorModel attribute), 10

T

tabs (colourpaletteextractor.view.mainview.-MainView attribute), 11

test_closest_relevant_colour_used_to_recolour_pixel() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_cube_colour_must_occur_more_than_three_percent_threshold_1() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_cube_colour_must_occur_more_than_three_percent_threshold_2() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_low_a_b_colour_does_not_meet_secondary_requirements_1() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_low_a_b_colour_does_not_meet_secondary_requirements_2() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_nieves2020_centred_cubes_constructor() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_nieves2020_offset_cubes_constructor() (in module colourpaletteextractor.test-

s.nieves2020_test), 11

test_primary_requirements_1() (in module colourpaletteextractor.tests.nieves2020_test), 11

test_primary_requirements_2() (in module colourpaletteextractor.tests.nieves2020_test), 11

test_primary_requirements_3() (in module colourpaletteextractor.tests.nieves2020_test), 11

test_recoloured_image_of_same_size_1() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_recoloured_image_two_colours_1() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_recoloured_image_two_colours_2() (in module colourpaletteextractor.test-s.nieves2020_test), 11

test_two_colours_in_same_cube_can_meet_secondary_threshold_1() (in module colourpaletteextractor.test-s.nieves2020_test), 11

TestAlgorithm (class in colourpaletteextractor.model.algorithms.dummyalgorithm), 4

THRESHOLD (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020 attribute), 5

toggle_recoloured_image_action (colourpaletteextractor.view.mainview.MainView attribute), 12

toggle_recoloured_image_available (colourpaletteextractor.view.tabview.NewTab property), 19

toggle_recoloured_image_pressed (colourpaletteextractor.view.tabview.NewTab property), 19

tools (colourpaletteextractor.view.mainview.-MainView attribute), 13

U

update_image() (colourpaletteextractor.view.tabview.ImageDisplay method), 18

update_image() (in module colourpaletteextractor.view.tabview.ImageDisplay), 18

update_preferences() (colourpaletteextractor.view.otherviews.PreferencesWidget method), 16

update_progress() (colourpaletteextractor.view.otherviews.BatchGenerationProgressWidget method), 14

update_progress_bar() (colourpaletteextractor.view.otherviews.StatusBar method), 17

url (colourpaletteextractor.model.algorithms.-grogan2018.Grogan2018 attribute), 5

url (colourpaletteextractor.model.algorithm-s.nieves2020.Nieves2020CentredCubes

attribute), [6](#)
url (colourpaletteextractor.model.algorithms.nieves2020.Nieves2020OffsetCubes attribute), [6](#)
url (colourpaletteextractor.model.algorithms.palettealgorithm.PaletteAlgorithm property), [7](#)
user_path_button (colourpaletteextractor.view.otherviews.PreferencesWidget attribute), [16](#)
user_path_selector (colourpaletteextractor.view.otherviews.PreferencesWidget attribute), [15](#)

W

wheelEvent() (colourpaletteextractor.view.tabview.NewTab method), [19](#)
Worker (class in colourpaletteextractor.controller.worker), [1](#)
WorkerSignals (class in colourpaletteextractor.controller.worker), [2](#)
write_default_settings() (colourpaletteextractor.model.model.ColourPaletteExtractorModel method), [10](#)

Z

zoom_factor (colourpaletteextractor.view.tabview.ImageDisplay attribute), [18](#)
zoom_in() (colourpaletteextractor.view.tabview.ImageDisplay method), [18](#)
zoom_in_action (colourpaletteextractor.view.mainview.MainView attribute), [12](#)
zoom_level (colourpaletteextractor.view.tabview.NewTab property), [20](#)
zoom_out() (colourpaletteextractor.view.tabview.ImageDisplay method), [18](#)
zoom_out_action (colourpaletteextractor.view.mainview.MainView attribute), [12](#)
zoom_out_factor (colourpaletteextractor.view.tabview.ImageDisplay attribute), [18](#)

