

1	<pre> #include <stdio.h> int main() { int i, j, n = 5; for(i = 1; i <= n; i++) { for(j = 1; j <= n; j++) { if(i == 1 i == n j == 1 j == n) printf("* "); else printf(" "); } printf("\n"); } return 0; } </pre>
2	<pre> #include <stdio.h> int main() { int i, j; for(i = 1; i <= 5; i++) { for(j = 1; j <= 5; j++) { printf("%d ", i * j); } printf("\n"); } return 0; } </pre>
3	<pre> #include <stdio.h> int main() { int i, j; for(i = 1; i <= 5; i++) { for(j = 1; j <= i; j++) { printf("%d ", j); } printf("\n"); } printf("Pattern complete\n"); return 0; } </pre>
4	<pre> #include <stdio.h> int main() { for(i=1;i<=8;i++){ for(j=1;j<=8;j++){ if((i+j)%2==0) printf("W "); else printf("B "); } printf("\n"); } return 0; } </pre>

5	<pre> #include <stdio.h> int main() { int i, j; for(i = 1; i <= 5; i++) { for(j = 1; j <= i; j++) { printf("* "); } printf("\n"); } return 0; } </pre>
6	<pre> for(i = 0; i < n; i++) { for(j = 1; j < n - i; j++) printf(" "); coef = 1; for(j = 0; j <= i; j++) { printf("%d ", coef); coef = coef * (i - j) / (j + 1); } printf("\n"); } </pre>
7	<pre> for(i = 1; i <= n; i++) { for(j = 1; j <= n - i; j++) printf(" "); for(j = 1; j <= 2*i - 1; j++) printf("*"); printf("\n"); } </pre>

8	<pre> #include <stdio.h> int main() { int num = 121, temp, rev = 0, digit; temp = num; while(num != 0) { digit = num % 10; rev = rev * 10 + digit; num = num / 10; } if(temp == rev) printf("Palindrome\n"); else printf("Not Palindrome\n"); return 0; } </pre>
9	<pre> #include <stdio.h> int main() { int i = 1; while(i <= 5) { printf("Value: %d\n", i); i++; } printf("Loop ended\n"); return 0; } </pre>
10	<pre> #include <stdio.h> int main() { int num = 1234, sum = 0, digit; while(num != 0) { digit = num % 10; sum = sum + digit; num = num / 10; } printf("Sum of digits = %d\n", sum); return 0; } </pre>
11	<pre> #include <stdio.h> int main() { int num = 1234, rev = 0, rem; while(num != 0) { rem = num % 10; rev = rev * 10 + rem; num /= 10; } printf("Reverse = %d", rev); return 0; } </pre>

12	<pre>#include <stdio.h> int main() { int i = 1; while(i <= 5) { printf("Number: %d\n", i); i++; } printf("Loop Ended"); return 0; }</pre>
----	--

13	<pre> #include <stdio.h> int main() { char ch = 'A'; if((ch >= 'a' && ch <= 'z') (ch >= 'A' && ch <= 'Z')) { if(ch=='a' ch=='e' ch=='i' ch=='o' ch=='u' ch=='A' ch=='E' ch=='I' ch=='O' ch=='U') printf("Vowel\n"); else printf("Consonant\n"); } else if(ch >= '0' && ch <= '9') { printf("Digit\n"); } else { printf("Special Character\n"); } return 0; } </pre>
14	<pre> #include <stdio.h> int main() { int a = 10, b = 25, c = 15; if(a > b && a > c) { printf("Largest is a = %d\n", a); } else if(b > c) { printf("Largest is b = %d\n", b); } else { printf("Largest is c = %d\n", c); } return 0; } </pre>
15	<pre> #include <stdio.h> int main() { int marks = 75; if(marks >= 90) printf("Grade A"); else if(marks >= 75) printf("Grade B"); else if(marks >= 50) printf("Grade C"); else printf("Fail"); return 0; } </pre>
16	<pre> #include <stdio.h> int main() { if(income<=250000) tax=0; else if(income<=500000) tax=income*0.05; else if(income<=1000000) tax=income*0.2; else tax=income*0.3; printf("Tax = %.2f", tax); return 0; } </pre>

17	<pre> #include <stdio.h> int main() { int year = 2024; if(year % 4 == 0) { if(year % 100 == 0) { if(year % 400 == 0) printf("Leap Year\n"); else printf("Not Leap Year\n"); } else { printf("Leap Year\n"); } } else { printf("Not Leap Year\n"); } return 0; } </pre>
18	<pre> #include <stdio.h> int main() { int num = -4; if(num > 0) { if(num % 2 == 0) printf("Positive Even\n"); else printf("Positive Odd\n"); } else if(num < 0) { if(num % 2 == 0) printf("Negative Even\n"); else printf("Negative Odd\n"); } else { printf("Number is Zero\n"); } return 0; } </pre>
19	<pre> #include <stdio.h> int main() { int a = 10, b = 20; if(a > 0) { if(b > 0) { printf("Both numbers are positive\n"); } else { printf("a is positive, b is not\n"); } } else { printf("a is not positive\n"); } return 0; } </pre>

20	<pre> #include <stdio.h> int main() { int a = 10, b = 20; if(a > 0) { if(b > 0) printf("Both are positive"); else printf("a positive, b negative"); } else { printf("a is negative"); } return 0; } </pre>
21	<pre> #include <stdio.h> int main() { if(input==password){ if(time<21){ printf("Access Granted\n"); } else { printf("Late Night - Access Limited\n"); } } else { printf("Wrong Password\n"); } return 0; } </pre>