

Show understanding that the DBMS carries out all creation/modification of the database structure using its Data Definition Language (DDL)

9608_s21_qp_11_sc_5.c

QUESTION

(c) A Data Definition Language (DDL) is used to create the structure of the database. One item that can be created is the database.

Identify **three other** items that can be created in the database using the DDL.

1

2

3.....

[3]

MARK SCHEME

5(c)	1 mark each (max 3) e.g. • Tables • Fields/attributes • Indexes • Users • Primary Key • Foreign Key • Relationships • Views	3
------	---	----------

QUESTION

(c) The following table has four SQL scripts.

Tick (✓) **one** box in each row to identify whether the script is an example of a Data Definition Language (DDL) statement or a Data Manipulation Language (DML) statement.

Script	DDL	DML
CREATE TABLE FILMS		
SELECT FilmID FROM FILMS		
ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)		
CREATE DATABASE MYDATA		

[2]

MARK SCHEME

3c	1 mark for at least two correct rows, 2 marks for all four correct rows			2
	Script	DDL	DML	
	CREATE TABLE FILMS	✓		
	SELECT FilmID FROM FILMS		✓	
	ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)	✓		
	CREATE DATABASE MYDATA	✓		

QUESTION

(ii) Anushka first needs to create the database that she has designed.

Write a Data Definition Language (DDL) statement to create the SPORTS_CLUB database.

.....
 [1]

MARK SCHEME

4(b)(ii)	CREATE DATABASE SPORTS_CLUB;	1
----------	------------------------------	----------

Show understanding that the DBMS carries out all queries and maintenance of data using its DML

9608_w19_qp_13_sc_3.c

QUESTION

(c) The following table has four SQL scripts.

Tick (✓) **one** box in each row to identify whether the script is an example of a Data Definition Language (DDL) statement or a Data Manipulation Language (DML) statement.

Script	DDL	DML
CREATE TABLE FILMS		
SELECT FilmID FROM FILMS		
ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)		
CREATE DATABASE MYDATA		

[2]

MARK SCHEME

3c	1 mark for at least two correct rows, 2 marks for all four correct rows			2
	Script	DDL	DML	
	CREATE TABLE FILMS	✓		
	SELECT FilmID FROM FILMS		✓	
	ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)	✓		
	CREATE DATABASE MYDATA	✓		

Show understanding that the industry standard for both DDL and DML is Structured Query Language (SQL)

9608_w19_qp_13_sc_3.c

QUESTION

(c) The following table has four SQL scripts.

Tick (✓) **one** box in each row to identify whether the script is an example of a Data Definition Language (DDL) statement or a Data Manipulation Language (DML) statement.

Script	DDL	DML
CREATE TABLE FILMS		
SELECT FilmID FROM FILMS		
ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)		
CREATE DATABASE MYDATA		

[2]

MARK SCHEME

3c	1 mark for at least two correct rows, 2 marks for all four correct rows			2
	Script	DDL	DML	
	CREATE TABLE FILMS	✓		
	SELECT FilmID FROM FILMS		✓	
	ALTER TABLE FILMS ADD PRIMARY KEY (FilmID)	✓		
	CREATE DATABASE MYDATA	✓		

Understand given SQL (DDL) statements and be able to write simple SQL (DDL) statements using a sub-set of statements

9608_w21_qp_11_sc_9.b

QUESTION

(b) The following is example data for the table `FLIGHT`:

FlightID	FlightDate	FlightTime
MO126	05/05/21	09:00
GK6708	06/09/21	00:30
BA0897	08/12/21	15:30

Write Data Definition Language (DDL) statements to define the table `FLIGHT`.

.....

.....

.....

.....

.....

.....

..... [5]

MARK SCHEME

9(b)	One mark per bullet point • Create table <code>FLIGHT</code> with open and close brackets (and ;) • <code>FlightID</code> as <code>VARCHAR</code> restricted to max 6 • <code>FlightDate</code> as <code>DATE</code> • <code>FlightTime</code> as <code>TIME</code> • Declaring <code>FlightID</code> as Primary Key Example <pre>CREATE TABLE FLIGHT (FlightID VARCHAR(6), FlightDate DATE, FlightTime TIME, PRIMARY KEY (FlightID));</pre>	5
------	---	---

QUESTION

(c) The database needs to store the gender of each employee (either **M** for Male or **F** for Female).

Write a Data Definition Language (DDL) statement to add the attribute `Gender` to the `EMPLOYEE` table.

.....

.....

.....

.....

.....

..... [2]

MARK SCHEME

8(c)	1 mark per bullet point • <code>ALTER TABLE EMPLOYEE</code> • <code>ADD Gender CHAR(1)</code> Example: <code>ALTER TABLE EMPLOYEE</code> <code>ADD Gender CHAR(1);</code>	2
------	---	----------

QUESTION

(c) The table, `GUIDE_TABLE`, is created.

Each guide has a unique guide ID.

Part of the table `GUIDE_TABLE` is shown:

GuideID	Guide	DateOfBirth	Gender
1	Artem	07/03/1992	M
2	Kenton	08/04/1984	M
3	Safia	10/10/1999	F

Write a Data Definition Language (DDL) statement to define the table `GUIDE_TABLE`.

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [5]

MARK SCHEME

4(c)	1 mark per bullet point • Create table <code>GUIDE_TABLE</code> with brackets and semi-colon • <code>GuideID</code> of suitable data type • <code>Guide</code> and <code>Gender</code> of suitable data type(s) • <code>DateOfBirth</code> of correct data type • Declaring <code>GuideID</code> as Primary Key Example answer: <pre>CREATE TABLE GUIDE_TABLE (GuideID INT, Guide VARCHAR(25), DateOfBirth DATE, Gender CHAR(1), PRIMARY KEY (GuideID));</pre>	5
------	--	---

QUESTION

- (c) Sheila creates the database `HOTEL` with the following table structure:

`ROOM(RoomNumber, RoomType)`

`BOOKING(BookingID, RoomNumber, CustomerID, StartDate)`

`CUSTOMER(CustomerID, FirstName, LastName, Address, Tel_Num)`

- (i) The following table shows some sample data for the table `ROOM`.

RoomNumber	RoomType
1	Standard
2	Double
3	Executive
4	Standard

Complete the Data Definition Language (DDL) statement to create the table `ROOM`.

```
..... TABLE ROOM (

    RoomNumber Integer,

    RoomType .....,

    ..... (RoomNumber)

);
```

[3]

MARK SCHEME

6(c)(i)	1 mark for each completed line <pre>CREATE TABLE ROOM (RoomNumber Integer, RoomType Varchar, PRIMARY KEY (RoomNumber));</pre>	3
---------	---	----------

QUESTION

- (iii) The table `BOOKING` needs an additional field to store the number of nights (for example, 3) a customer is staying.

Write a Data Definition Language (DDL) statement to add the new field to the table `BOOKING`.

.....
.....
.....
.....
..... [2]

MARK SCHEME

6(c)(iii)	1 mark per bullet point • Alter table booking • Add number of nights with appropriate field name and data type <code>ALTER TABLE BOOKING</code> <code>ADD NumberNights Integer;</code>	2
-----------	---	----------

QUESTION

- (c) The company also develops computer games. They extend the relational database SOFTWARE_MANAGEMENT by adding a new table. The new table, GAME_DEVELOPMENT, stores details about the games and the software development teams creating them.

The table shows example data in GAME_DEVELOPMENT.

GameName	Genre	TeamNumber	DevelopmentStage	ManagerID
Bunny Hop	Platform	4	Analysis	23KP
Fried Eggs	Retro	2	Programming stage 1	9RTU
Create-a-game	Action	1	Acceptance testing	11TF

- (i) Complete the Data Definition Language (DDL) statement to create the table GAME_DEVELOPMENT.

```
CREATE ..... (
    GameName VarChar,
    Genre VarChar,
    ..... ,
    DevelopmentStage VarChar,
    ManagerID VarChar,
    ..... (GameName)
);
```

[5]

MARK SCHEME

6(c)(i)	1 mark for each correct entry (in bold) <pre>CREATE TABLE GAME_DEVELOPMENT (GameName VarChar, Genre VarChar, TeamNumber Integer, DevelopmentStage VarChar, ManagerID VarChar, PRIMARY KEY (GameName));</pre>	5
---------	--	----------

QUESTION

(c) The table shows some sample data for the table `INSTRUCTOR`.

InstructorID	FirstName	LastName	DateOfBirth	Level
Ins01	Jayden	Han	05/06/1974	1
Ins02	Freda	Choi	06/02/1978	2
Ins03	Kelly	Kim	01/12/1966	1
Ins04	Santana	Thompson	09/09/1985	3

Complete the Data Definition Language (DDL) statement to create the table `INSTRUCTOR`.

```
..... TABLE INSTRUCTOR (

    InstructorID VARCHAR(5),

    FirstName VARCHAR(15),

    LastName VARCHAR(15),

    DateOfBirth DATE,

    Level ..... ,

    ..... (InstructorID)

);
```

[3]

MARK SCHEME

7(c)	1 mark for each correctly completed statement • <code>CREATE</code> (line 1) • <code>INTEGER</code> (line 6) • <code>PRIMARY KEY</code> (line 7) <pre>CREATE TABLE INSTRUCTOR (InstructorID VARCHAR(5), FirstName VARCHAR(15), LastName VARCHAR(15), DateOfBirth DATE, Level INTEGER, PRIMARY KEY (InstructorID));</pre>	3
------	--	----------

QUESTION

- (d) The table `STUDENT` needs an additional field to store the student's telephone number, for example 012-3456.

Write a Data Definition Language (DDL) statement to add the new field to the table `STUDENT`.

.....

 [2]

MARK SCHEME

7(d)	1 mark per bullet point - Alter table student - Add an appropriate identifier with suitable data type <pre>ALTER TABLE STUDENT ADD TelNum VARCHAR;</pre>	2
------	--	----------

QUESTION

- (ii) Anushka first needs to create the database that she has designed.

Write a Data Definition Language (DDL) statement to create the `SPORTS_CLUB` database.

.....
 [1]

MARK SCHEME

4(b)(ii)	<code>CREATE DATABASE SPORTS_CLUB;</code>	1
----------	---	----------

QUESTION

(iii) The table shows some sample data for the table `SESSION`.

<code>SessionID</code>	<code>Description</code>	<code>SessionDate</code>	<code>SessionTime</code>	<code>NumberMembers</code>
21PL	Pilates junior	04/04/2020	18:00	15
13AE	Aerobics senior	04/04/2020	19:00	20
33WG	Weightlifting advanced	04/04/2020	10:00	10

Write a DDL script to create the table `SESSION`.

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [5]

MARK SCHEME

4(b)(iii)	1 mark per bullet point <pre>CREATE TABLE SESSION and (); SessionID as char(4) / varchar / varchar(4) / text and Description as varchar / varchar(x) / char(x) / text SessionDate as date and SessionTime as time NumberMembers as integer / integer(2) / int / int(2) SessionID set as a Primary Key</pre> Example 1: <pre>CREATE TABLE SESSION(SessionID Char(4), Description Varchar, SessionDate Date, SessionTime Time, NumberMembers Integer, PRIMARY KEY (SessionID));</pre> Example 2: <pre>CREATE TABLE SESSION(SessionID Char(4) NOT NULL PRIMARY KEY, Description Varchar, SessionDate Date, SessionTime Time, NumberMembers Integer);</pre>	5
-----------	---	----------

9608_s19_qp_13_sc_3.e.i

QUESTION

(e) Part of the EMPLOYEE_DATA table is shown.

EmployeeID	FirstName	LastName	DateOfBirth	Gender	DepartmentNumber
156FJEK	Harvey	Kim	12/05/1984	Male	S1
558RRKL	Catriona	Moore	03/03/1978	Female	F2
388LMDV	Oscar	Ciao	01/01/1987	Male	F2

(i) Write a Data Definition Language (DDL) statement to create the EMPLOYEES database.

.....
 [1]

MARK SCHEME

3(e)(i)	1 mark for correct answer <pre>CREATE DATABASE EMPLOYEES;</pre>	1
---------	---	----------

QUESTION

- (ii) Write a DDL statement to define the table `EMPLOYEE_DATA`, and declare `EmployeeID` as the primary key.

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [5]

MARK SCHEME

3(e)(ii)	1 mark per bullet Create table <code>EMPLOYEE_DATA</code> with open and close brackets <code>EmployeeID</code> as <code>VarChar</code> restricted to max 7, Gender as a <code>VarChar</code> restricted to max 6, <code>DepartmentNumber</code> as a <code>VarChar</code> restricted to max 2 <code>FirstName</code> and <code>LastName</code> as <code>VarChar</code> (any max lengths must be reasonable) <code>Date of birth</code> as <code>Date</code> Declaring <code>EmployeeID</code> as PK <pre>CREATE TABLE EMPLOYEE_DATA (EmployeeID VarChar(7), FirstName VarChar, LastName VarChar, DateOfBirth Date, Gender VarChar(6), DepartmentNumber VarChar(2), PRIMARY KEY (EmployeeID));</pre>	5
----------	---	---

QUESTION

- (c) The database needs to store the name of the company that produced each movie, for example, *Rocking Movies*.

Write an SQL script to add the attribute `ProductionCompany` to the `MOVIE` table.

.....
.....
.....
.....
.....[2]

MARK SCHEME

7(c)	1 mark per bullet point <code>ALTER TABLE MOVIE ADD (COLUMN) ProductionCompany VARCHAR(25);</code>	2
------	--	----------

QUESTION

(d) (i) The following table shows some sample data for the `PLAYER` table.

PlayerID	PlayerName	SkillLevel
fly918	Kylie	3
elephant11	Mehrdad	9
candy22	Suzi	15
greenGrass	Jason	22

Write an SQL script to create the `PLAYER` table.

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....[5]

MARK SCHEME

2(d)(i)	1 mark per bullet CREATE TABLE <code>PLAYER</code> and (); <code>PlayerID</code> and <code>PlayerName</code> as <code>VARCHAR</code> and commas <code>SkillLevel</code> as <code>INT</code> and comma PRIMARY KEY(<code>PlayerID</code>) An appropriate NOT NULL CREATE TABLE <code>PLAYER</code>(<code>PlayerID</code>: varchar NOT NULL, <code>PlayerName</code>: varchar, <code>SkillLevel</code>: int, PRIMARY KEY(<code>PlayerID</code>),);	5
---------	---	---

QUESTION

(ii) The table, `PLAYER`, needs to be altered. A new field, `DateOfBirth`, needs to be added.

Write an SQL script to add the `DateOfBirth` field to the `PLAYER` table.

.....

.....

.....

.....[2]

MARK SCHEME

2(d)(ii)	1 mark per bullet <code>ALTER TABLE PLAYER</code> <code>ADD DateOfBirth Date;</code>	2
----------	---	----------

QUESTION

- (ii) The database administrator needs to alter the `USER` table. A new field, `Country`, needs to be added.

Write an SQL script to add the field `Country` to the `USER` table.

.....
.....
.....
.....[2]

MARK SCHEME

7(d)(ii)	1 mark per bullet <code>ALTER TABLE USER</code> <code>ADD COUNTRY varchar;</code> <code>ALTER TABLE USER</code> <code>ADD Country varchar;</code>	2
----------	--	----------

QUESTION

(c) The `CLASS` table has primary key `ClassID` and stores the following data:

<code>ClassID</code>	<code>Description</code>	<code>StartDate</code>	<code>ClassTime</code>	<code>NoOfSessions</code>	<code>AdultsOnly</code>
DAY01	Yoga beginners	12/01/2016	11:00	5	TRUE
EVE02	Yoga beginners	12/01/2016	19:00	5	FALSE
DAY16	Circuits	30/06/2016	10:30	4	FALSE

Write an SQL script to create the `CLASS` table.

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....[6]

MARK SCHEME

(c) An example of a script is shown, but different syntax may be used.

```
CREATE TABLE CLASS (  
    ClassID VARCHAR(5),  
    Description VARCHAR(30),  
    StartDate DATE,  
    ClassTime TIME,  
    NoOfSessions INT,  
    AdultsOnly BIT,  
    PRIMARY KEY(ClassID)  
);
```

Mark as follows:

1 mark for `CREATE TABLE CLASS` and `()`;

1 mark for `PRIMARY KEY(ClassID)`

1 mark for both `ClassID VARCHAR(5)`, and `Description VARCHAR(30)`,

1 mark for both `StartDate DATE`, and `ClassTime TIME`,

1 mark for `NoOfSessions INT`,

1 mark for `AdultsOnly BIT`,

[6]

9608_s16_qp_13_sc_5.d.i

QUESTION

(d) (i) The database will store each student's date of birth.

Write an SQL script to add a date of birth attribute to the appropriate table.

.....
.....
.....
.....[2]

MARK SCHEME

(d) (i) **One mark** per statement. Several statements may be on one line.

[2]

```
ALTER TABLE STUDENT  
ADD DateOfBirth DATE;
```

Write an SQL script to query or modify data (DML) which are stored in (at most two) database tables

9608_s21_qp_13_sc_8.d

QUESTION

(d) Part of the `EMPLOYEE` table is shown:

EmployeeID	FirstName	LastName	Salary	DOB	Gender
001	Jasmine	Chen	25 000	25/12/2000	F
002	Kenton	Archer	20 000	01/04/1993	M
003	Michael	Roux	10 000	10/03/1990	M
004	Conrad	Slavorski	15 000	30/03/1989	M

Each employee is paid a salary in dollars (\$).

Write a Data Manipulation Language (DML) statement to return the first name, last name and salary of all employees that are paid more than \$17 500.

.....
.....
.....
.....
.....
..... [3]

MARK SCHEME

8(d)	1 mark per bullet point • <code>SELECT FirstName, LastName, Salary</code> • <code>FROM EMPLOYEE</code> • <code>WHERE Salary > 17 500</code> Example: <code>SELECT FirstName, LastName, Salary</code> <code>FROM EMPLOYEE</code> <code>WHERE Salary > 17 500;</code>	3
------	---	----------

QUESTION

(d) Part of the `EMPLOYEE` table is shown.

EmployeeID	FirstName	LastName	Role	Language
001	Jasmine	Chen	Leader	French
002	Kenton	Archer	Leader	English
003	Michael	Roux	Cook	French
004	Conrad	Slavorski	Leader	Russian

Write a Data Manipulation Language (DML) statement to return the first name and last name of all employees, who are leaders, and speak either French or English.

.....

.....

.....

.....

.....

..... [4]

MARK SCHEME

5(d)	1 mark per syntactically correct bullet point: • Select correct fields • From correct table • Correct criteria for Role • Correct criteria for Language Example: SELECT FirstName, LastName FROM EMPLOYEE WHERE Role = "Leader" AND (Language = "French" OR Language = "English");	4
------	---	----------

9608_s20_qp_13_sc_6.c.ii

QUESTION

- (ii) Room number 5 is a **Double** room.

Complete the Data Manipulation Language (DML) statement to add the details for room number 5 to the table ROOM.

INSERT ROOM

VALUES (.....) ;

[2]

MARK SCHEME

6(c)(ii)	1 mark for each completed line INSERT INTO ROOM VALUES (5, "Double") ;	2
----------	--	----------

9608_s20_qp_12_sc_6.c.ii

QUESTION

- (ii) Another table, PRODUCT_MANAGER, is created.

PRODUCT_MANAGER (ManagerID, FirstName, LastName)

Complete the Data Manipulation Language (DML) statement to return the game name, genre and team number of all games managed by the product manager with the first name 'James' and the last name 'Fitz'.

..... GameName, Genre, TeamNumber

FROM GAME_DEVELOPMENT, PRODUCT_MANAGER

WHERE PRODUCT_MANAGER.FirstName = "James"

AND PRODUCT_MANAGER.LastName = "Fitz"

AND

= ;

[3]

MARK SCHEME

6(c)(ii)	1 mark for each correct entry (shown in brackets) SELECT (1) GameName, Genre, TeamNumber FROM GAME_DEVELOPMENT, PRODUCT_MANAGER WHERE PRODUCT_MANAGER.FirstName = "James" AND PRODUCT_MANAGER.SecondName = "Fitz" AND PRODUCT_MANAGER.ManagerID (1) = GAME_DEVELOPMENT.ManagerID (1) ;	3
----------	--	----------

9608_s20_qp_11_sc_7.e

QUESTION

- (e) Write a Data Manipulation Language (DML) statement to return the date and time of all future lessons booked with the instructor whose `InstructorID` is `Ins01`.

.....

.....

.....

.....

.....

.....

..... [4]

MARK SCHEME

7(e)	1 mark per bullet point • Select lesson date and lesson time • From table LESSON • Where <code>InstructorID = "Ins01"</code> • And lesson date is greater than today's date SELECT LessonDate, LessonTime FROM LESSON WHERE <code>InstructorID = "Ins01"</code> AND LessonDate > #####;	4
------	---	----------

QUESTION

- (iv) Write a Data Manipulation Language (DML) script to return the first name and last name of all members who have *Peak* membership type.

.....

 [3]

MARK SCHEME

4(b)(iv)	1 mark per bullet point Select FirstName and comma and LastName From MEMBER Where MembershipType = "Peak" SELECT FirstName, LastName FROM MEMBER WHERE MembershipType = "Peak";	3
----------	--	----------

QUESTION

- (iii) Write a Data Manipulation Language (DML) statement to return the first name and last name of all female employees in the department named Finance.

.....

 [5]

MARK SCHEME

3(e)(iii)	1 mark per bullet Select FirstName and LastName only From both tables Where DepartmentName = "Finance" AND Gender = "Female" Joining tables (either AND, or inner join) <pre>SELECT FirstName, LastName FROM EMPLOYEE_DATA, DEPARTMENT WHERE DepartmentName = "Finance" AND Gender = "Female" AND DEPARTMENT.DepartmentNumber = EMPLOYEE_DATA.DepartmentNumber;</pre>	5
-----------	--	----------

9608_s19_qp_11_sc_2.c.iii

QUESTION

- (iii) The company needs a list of all software licences that have an expiry date on or before 31/12/2019.

Write an SQL query to return the fields CustomerID, SoftwareID, LicenceType, Cost and ExpiryDate for all licences that expire on, or before 31/12/2019. Group the output by CustomerID, and in ascending order of cost.

.....

.....

.....

.....

.....

.....

.....

.....

.....

..... [5]

MARK SCHEME

2(c)(iii)	1 mark per bullet point Select with correct 5 fields From LICENCE Where ExpiryDate <= '31/12/2019' (any appropriate date type) Group by CustomerID Order by Cost (with or without ASC, but not DESC) SELECT CustomerID, SoftwareID, LicenceType, Cost, ExpiryDate FROM LICENCE WHERE ExpiryDate <= '31/12/2019' GROUP BY CustomerID ORDER BY Cost;	5
-----------	--	----------

9608_w18_qp_11_sc_7.d

QUESTION

- (d) Write an SQL script to display the title and rating of all movies scheduled to play on screen number 3.

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....[4]

MARK SCHEME

7(d)	1 mark per bullet point Answer 1: <pre>SELECT Title, Rating FROM MOVIE, MOVIESCHEDULE WHERE MOVIE.MovieID = MOVIESCHEDULE.MovieID AND MOVIESCHEDULE.ScreenNumber = 3;</pre> Or Answer 2: <pre>SELECT Title, Rating FROM MOVIE INNER JOIN MOVIESCHEDULE ON MOVIE.MovieID = MOVIESCHEDULE.MovieID WHERE MOVIESCHEDULE.ScreenNumber = 3;</pre>	4
------	---	----------

9608_w17_qp_13_sc_7.d.i

QUESTION

(d) The doctor with the ID of 117 has recently been allocated a new `DoctorID` of 017.

(i) Write an SQL script to update this doctor's record in the database.

UPDATE

SET.....

WHERE

[3]

MARK SCHEME

7(d)(i)	One mark per line <pre>UPDATE DOCTOR SET DoctorID = '017' WHERE DoctorID = '117';</pre>	3
---------	---	----------

9608_w17_qp_13_sc_7.e

QUESTION

- (e) Write an SQL script to display the date and time of all appointments made by the patient with the PatientID of 556.

.....
.....
.....[3]

MARK SCHEME

7(e)	One mark per line SELECT AppointmentDate, AppointmentTime FROM APPOINTMENT WHERE PatientID = '556';	3
------	---	----------

9608_w17_qp_12_sc_7.c.i

QUESTION

- (c) Client ABC Holdings are now trading under the name of Albright Holdings.

- (i) Write an SQL script to update this client's record in the database.

UPDATE
SET
WHERE
[3]

- (ii) Describe why this update could cause problems with the existing data stored

MARK SCHEME

7(c)(i)	1 Mark for each correct line UPDATE CLIENT SET ClientName = 'Albright Holdings' WHERE ClientName = 'ABC Holdings';	3
---------	--	----------

QUESTION

- (d) Write an SQL script to display the Staff ID of each member of staff who performed an interview when they visited New Age Toys on 13/10/2016.

.....

[3]

MARK SCHEME

7(d)	1 Mark for each correct line	3
	SELECT StaffID FROM INTERVIEW WHERE ClientName = 'New Age Toys' AND VisitDate = '13/10/2016'; (Accept clauses other way round)	

QUESTION

- (d) Use the table designs in **part (c)(ii)**.

- (i) Write an SQL query to display the Nurse ID and family name for all Area B nurses with a specialism of 'THEATRE'.

.....

[3]

MARK SCHEME

1(d)(i)	SELECT NurseID, FamilyName FROM B-NURSE WHERE Specialism = 'THEATRE';	1 1 1	3
---------	---	-------------	----------

QUESTION

(ii) Fatima Woo is an Area B nurse with the nurse ID of 076. She has recently married, and her new family name is Chi.

Write an SQL command to update her record.

UPDATE
SET
WHERE
[3]

MARK SCHEME

1(d)(ii)	UPDATE B-NURSE SET FamilyName = 'Chi' WHERE NurseID = '076';	1 1 1	3
----------	---	-------------	----------

QUESTION

(c) (i) Write an SQL query to display the shop ID and location of all shops with a 'GROCERY' specialism.

.....
.....
.....[3]

MARK SCHEME

1(c)(i)	SELECT ShopID, Location FROM SHOP WHERE RetailSpecialism = 'GROCERY';	1 1 1	3
---------	---	-------------	----------

9608_s17_qp_12_sc_1.c.ii

QUESTION

(ii) The existing shop with ID 8765 has just used the existing supplier SUP89 for the first time.

Write an SQL script to add this data to the database.

.....

.....

.....[3]

MARK SCHEME

1(c)(ii)	INSERT INTO SHOP-SUPPLIER (ShopID, SupplierID) VALUES (8765, 'SUP89');	1 1 1	3
----------	--	-------------	---

9608_s17_qp_11_sc_1.d.i

QUESTION

(d) Use the table designs in **part (c)(ii)**.

(i) Write an SQL query to display the Nurse ID and family name for all Area B nurses with a specialism of 'THEATRE'.

.....

.....

.....[3]

MARK SCHEME

1(d)(i)	SELECT NurseID, FamilyName FROM B-NURSE WHERE Specialism = 'THEATRE';	1 1 1	3
---------	---	-------------	---

QUESTION

(ii) Fatima Woo is an Area B nurse with the nurse ID of 076. She has recently married, and her new family name is Chi.

Write an SQL command to update her record.

UPDATE
SET
WHERE
[3]

MARK SCHEME

1(d)(ii)	UPDATE B-NURSE SET FamilyName = 'Chi' WHERE NurseID = '076';	1 1 1	3
----------	---	-------------	----------

QUESTION

(ii) Write an SQL script to display the StudentID, Grade and DateOfAward for the QualCode value of SC12.

.....
.....
.....
.....
.....
.....
.....[3]

MARK SCHEME

(ii) **One mark** per statement. Several statements may be on one line. **[3]**

SELECT StudentID, Grade, DateOfAward
FROM STUDENT-QUALIFICATION
WHERE QualCode = 'SC12';

QUESTION

- (iii) Write an SQL script to display the `FirstName` and `LastName` and `QualCode` for all `STUDENT-QUALIFICATIONS` for which the `Grade` value is `A`.

.....

[4]

MARK SCHEME

- (iii) **One mark** per statement. Several statements may be on one line.

[4]

```
SELECT STUDENT.FirstName, STUDENT.LastName, STUDENT-
    QUALIFICATION.QualCode
FROM STUDENT, STUDENT-QUALIFICATION
WHERE STUDENT-QUALIFICATION.Grade = 'A'
AND STUDENT.StudentID = STUDENT-QUALIFICATION.StudentID;
```

Alternative answer:

```
SELECT FirstName, LastName, STUDENT-QUALIFICATION.QualCode
FROM STUDENT, INNER JOIN STUDENT-QUALIFICATION
ON STUDENT.StudentID = STUDENT-QUALIFICATION.StudentID
WHERE Grade = 'A';
```

QUESTION

- (iii) Write an SQL script to display the `StudentID` and `FirstName` of all students who are in the tutor group 10B. Display the list in alphabetical order of `LastName`.

.....

[4]

MARK SCHEME

(iii) One mark per statement. Several statements may be on the same line.

[4]

```
SELECT StudentID, FirstName
FROM STUDENT
WHERE TutorGroup = "10B" // WHERE (TutorGroup = "10B")
ORDER BY LastName ASC;
```

9608_s16_qp_12_sc_8.b.iv

QUESTION

(iv) Write an SQL script to display the `LastName` of all students who attend the class whose `ClassID` is `CS1`.

.....
.....
.....
.....
.....
.....
.....
.....[4]

MARK SCHEME

(iv) One mark per statement. Several statements may be on the same line.

[4]

```
SELECT STUDENT.LastName
FROM STUDENT, CLASS-GROUP
WHERE ClassID = "CS1" // WHERE (ClassID = "CS1")
AND CLASS-GROUP.StudentID = STUDENT.StudentID;
```

One mark per statement. Several statements may be on the same line.

```
SELECT STUDENT.LastName
FROM STUDENT INNER JOIN CLASS-GROUP
ON CLASS-GROUP.StudentID = STUDENT.StudentID
WHERE ClassID = "CS1" // WHERE (ClassID = "CS1");
```

9608_s16_qp_11_sc_8.b.iii

QUESTION

- (iii) Write an SQL script to display the `StudentID` and `FirstName` of all students who are in the tutor group 10B. Display the list in alphabetical order of `LastName`.

.....
.....
.....
.....[4]

MARK SCHEME

- (iii) **One mark** per statement. Several statements may be on the same line.

[4]

```
SELECT StudentID, FirstName  
FROM STUDENT  
WHERE TutorGroup = "10B" // WHERE (TutorGroup = "10B")  
ORDER BY LastName ASC;
```

9608_s16_qp_11_sc_8.b.iv

QUESTION

- (iv) Write an SQL script to display the `LastName` of all students who attend the class whose `ClassID` is CS1.

.....
.....
.....
.....
.....
.....
.....
.....[4]

MARK SCHEME

(iv) **One mark** per statement. Several statements may be on the same line.

[4]

```
SELECT STUDENT.LastName  
FROM STUDENT, CLASS-GROUP  
WHERE ClassID = "CS1" // WHERE (ClassID = "CS1")  
AND CLASS-GROUP.StudentID = STUDENT.StudentID;
```

One mark per statement. Several statements may be on the same line.

```
SELECT STUDENT.LastName  
FROM STUDENT INNER JOIN CLASS-GROUP  
ON CLASS-GROUP.StudentID = STUDENT.StudentID  
WHERE ClassID = "CS1" // WHERE (ClassID = "CS1");
```