

INTER-PROCESS COMMUNICATION USING PIPE

Name : PUSHPA LAKSHMI J

Reg no. :241801218

Write a C program to demonstrate Inter-Process Communication (IPC) using a pipe. The program should create a parent and child process using `fork()`. The parent process should send a message to the child process through the pipe, and the child process should read and display the received message.

Input Format:

The input consists of a single integer `n` entered by the user.

Output Format:

- Displays the value sent by the parent process
- Displays the processed value (double of the number) received and computed by the child process

Sample Input:

5

Sample Output:

Parent sent: 5

Child received: 5

Child processed value (double): 10

CODE:

```
#include <stdio.h>
```

```
#include <unistd.h>
```

```
#include <string.h>
```

```
int main() {  
    int fd[2];  
    pid_t pid;
```

```
    char write_msg[] = "Hello from Parent Process";  
    char read_msg[100];
```

```
    // Create pipe    if (pipe(fd)  
    == -1) {        printf("Pipe  
    failed\n");    return 1;
```

```
}
```

```
    // Create child process  
    pid = fork();
```

```
    if (pid < 0) {    printf("Fork  
    failed\n");    return 1;
```

```
}
```

```
    // Parent Process  
    if (pid > 0) {    close(fd[0]); //
```

```
    Close read end
```

```
        write(fd[1], write_msg, strlen(write_msg) + 1);    printf("Parent  
    sent: %s\n", write_msg);
```

```
        close(fd[1]); // Close write end
```

```
}
```

```
// Child Process  
  
else {      close(fd[1]); // Close  
write end  
  
    read(fd[0], read_msg, sizeof(read_msg));  
    printf("Child received: %s\n", read_msg);  
  
    close(fd[0]); // Close read end  
  
}  
  
return 0;  
  
}
```

Output:

Enter a number: 5 Parent

sent: 5

Child received: 5

Child processed value (double): 10