DaemonThreadExample:->

```
DaemonThreadExample.java:->
```

```java
package com.example.demo;

import java.util.Random;

public class DaemonThreadExample {
    public static void main(String[] args) {

        Thread userThread=new Thread(()->{
            for(int i=1;i<=5;i++) {

                System.out.println("User Thread: " + i);
                try {
                    Thread.sleep(1000L);
                } catch (InterruptedException e) {
                    throw new RuntimeException(e);
                }
            }
        },"UserThread");

        Thread daemonThread=new Thread(()->{
            while (true) {
                System.out.println("Daemon Thread is running ...");
                try {
                    Thread.sleep(1000L);
                } catch (InterruptedException e) {
                    throw new RuntimeException(e);
                }
            }
        },"DaemonThread");

        daemonThread.setDaemon(true);
        userThread.start();
        daemonThread.start();
}
    }
```

```
CustomTask.java:->
```

```java
package com.example.demo;

public class CustomTask implements Runnable{
    @Override
    public void run() {
        System.out.println("Thread Name:
"+Thread.currentThread().getName()+", State
"+Thread.currentThread().getState());
    }
}
```

JVMThreadManagementExample.java:->

```
package com.example.demo;

public class JVMThreadManagementExample {
    public static void main(String[] args) {
        Thread thread1=new Thread(new CustomTask(),"Thread-1");
        Thread thread2=new Thread(new CustomTask(),"Thread-2");
        Thread thread3=new Thread(new CustomTask(),"Thread-3");

        System.out.println("Thread-1 state before start:
"+thread1.getState());
        System.out.println("Thread-2 state before start:
"+thread2.getState());
        System.out.println("Thread-3 state before start:
"+thread3.getState());

        thread1.start();
        thread2.start();
        thread3.start();

        try{
            Thread.sleep(500L);
        } catch (InterruptedException e) {
            throw new RuntimeException(e);
        }

        System.out.println("Thread-1 state after start:
"+thread1.getState());
        System.out.println("Thread-2 state after start:
"+thread2.getState());
        System.out.println("Thread-3 state after start:
"+thread3.getState());

    }
}
```

ThreadPriorityExample.java:->

```java
package com.example.demo;

public class ThreadPriorityExample {
    public static void main(String[] args) {
        Thread highPriorityThread=new Thread(()->{
            for (int i=1;i<=5;i++)
            {
                System.out.println("High priority thread: "+i);
            }
        },"High priority thread");

        Thread mediumPriorityThread=new Thread(()->{
            for(int i=1;i<=5;i++)
            {
                System.out.println("Medium priority thread: "+i);
            }
        },"Medium priority thread");

        Thread lowPriorityThread=new Thread(()->{
            for(int i=1;i<=5;i++)
            {
                System.out.println("Low priority thread: "+i);
            }
        },"Low Priority Thread");

        highPriorityThread.setPriority(Thread.MAX_PRIORITY);
        mediumPriorityThread.setPriority(Thread.NORM_PRIORITY);
        lowPriorityThread.setPriority(Thread.MIN_PRIORITY);

        highPriorityThread.start();
        mediumPriorityThread.start();
        lowPriorityThread.start();
    }
}
```