ThreadPoolExample.java:->

```
package com.example.demo;

import java.util.concurrent.*;

public class ThreadPoolExample {
    public static void main(String[] args) {
        ExecutorService executor= Executors.newFixedThreadPool(3);
        Callable<Integer>task1=()->{
            System.out.println(Thread.currentThread().getName()+" is
calculating the square of 5");
            return 5*5;
        };

        Callable<Integer>task2=()->{
            System.out.println(Thread.currentThread().getName()+" is
calculating square of 7");
            return 7*7;
        };

        Callable<Integer>task3=()->{
            System.out.println(Thread.currentThread().getName()+" is
cauculating square of 10");
            return 10*10;
        };

try{
            Future<Integer>result1=executor.submit(task1);
            Future<Integer>result2=executor.submit(task2);
            Future<Integer>result3=executor.submit(task3);

            System.out.println("square of 5: "+result1.get());
            System.out.println("square of 7: "+result2.get());
            System.out.println("square of 10: "+result3.get());

        } catch (ExecutionException  | InterruptedException e) {
   e.printStackTrace();
}
finally {
    executor.shutdown();
}

    }
}
```

ThreadPoolExecutorExample.java:->

```
package com.example.demo;

import java.util.concurrent.*;

public class ThreadPoolExecutorExample {
    public static void main(String[] args) {
        ThreadPoolExecutor executor = (ThreadPoolExecutor)
                Executors.newFixedThreadPool(2);

        for (int i = 1; i <= 5; i++) {
            int task = i;
            executor.execute(() -> {
                System.out.println(
                        Thread.currentThread().getName() + " executing task "
+ task
                );
            });
        }

        executor.shutdown();
    }
}
```