



# **CS 228 : Logic in Computer Science**

Krishna. S

# First-Order Logic : Semantics

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a **fixed element**  $c_{\mathcal{A}}$  is assigned from the universe  $A$

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a fixed element  $c_{\mathcal{A}}$  is assigned from the universe  $A$
  - ▶ For each  $k$ -ary relation  $R^k$  in the signature  $\tau$ , a set of  $k$ -tuples from  $A^k$  is assigned to  $R^{\mathcal{A}}$

# Structures

---

- ▶ A structure  $\mathcal{A}$  of signature  $\tau$  consists of
  - ▶ A non-empty set  $A$  or  $u(\mathcal{A})$  called the **universe**
  - ▶ For each constant  $c$  in the signature  $\tau$ , a fixed element  $c_{\mathcal{A}}$  is assigned from the universe  $A$
  - ▶ For each  $k$ -ary relation  $R^k$  in the signature  $\tau$ , a set of  $k$ -tuples from  $A^k$  is assigned to  $R^{\mathcal{A}}$
  - ▶ The structure  $\mathcal{A}$  is finite if  $A$  (or  $u(\mathcal{A})$ ) is finite

# Examples of Structures : A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.



# Examples of Structures : A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.
  - ▶ A graph structure over  $\tau$  is  $\mathcal{G} = (V, E^{\mathcal{G}})$ ,
  - ▶ The **universe**  $u(\mathcal{G})$  is the set of vertices  $V$
  - ▶ The relation  $E$  is the edge relation

# Examples of Structures : A Graph

---

- ▶  $\tau = \{E\}$ , with  $E$  binary.
  - ▶ A graph structure over  $\tau$  is  $\mathcal{G} = (V, E^{\mathcal{G}})$ ,
  - ▶ The **universe**  $u(\mathcal{G})$  is the set of vertices  $V$
  - ▶ The relation  $E$  is the edge relation
  - ▶  $\mathcal{G} = (V = \{1, 2, 3, 4\}, E^{\mathcal{G}} = \{(1, 2), (2, 3), (3, 4), (1, 1)\})$ . We could just as well draw the graph for convenience.

# Examples of Structures : An Order

---

- ▶  $\tau = \{<, S\}$  with  $<, S$  binary.

# Examples of Structures : An Order

---

- ▶  $\tau = \{<, S\}$  with  $<, S$  binary.
  - ▶ A finite order structure over  $\tau$  is  $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
  - ▶ The universe  $u(\mathcal{O})$  is the finite ordered set  $O$
  - ▶  $<^{\mathcal{O}}$  is the ordering on  $O$  and  $S^{\mathcal{O}}$  is the successor on  $O$

# Examples of Structures : An Order

---

- ▶  $\tau = \{<, S\}$  with  $<, S$  binary.
  - ▶ A finite order structure over  $\tau$  is  $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
  - ▶ The universe  $u(\mathcal{O})$  is the finite ordered set  $O$
  - ▶  $<^{\mathcal{O}}$  is the ordering on  $O$  and  $S^{\mathcal{O}}$  is the successor on  $O$
  - ▶  $\mathcal{O} = (O = \{1, 2, 4\}, <^{\mathcal{O}} = \{(1, 2), (1, 4), (2, 4)\}, S^{\mathcal{O}} = \{(1, 2)\})$

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$



# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$

# Examples of Structures : A Word

---

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$
  - ▶  $Q_b^{\mathcal{W}}$  is the set of positions labeled  $b$  in  $W$

# Examples of Structures : A Word

- ▶  $\tau = \{<, S, Q_a, Q_b\}$ , where  $<, S$  are binary,  $Q_a, Q_b$  are unary relations.
  - ▶ A word structure  $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
  - ▶ The universe  $u(\mathcal{W})$  consists of the positions in a word  $W$  over symbols  $a, b$
  - ▶  $<^{\mathcal{W}}$  is the ordering relation on the positions of  $W$
  - ▶  $S^{\mathcal{W}}$  is the successor relation on the positions of  $W$
  - ▶  $Q_a^{\mathcal{W}}$  is the set of positions labeled  $a$  in  $W$
  - ▶  $Q_b^{\mathcal{W}}$  is the set of positions labeled  $b$  in  $W$
  - ▶ The structure with  $u(\mathcal{W}) = \{0, 1, 2, \dots, 8\}$ ,  
 $Q_a^{\mathcal{W}} = \{0, 1, 4, 6, 8\}$ ,  $Q_b^{\mathcal{W}} = \{2, 3, 5, 7\}$ ,
  - ▶  $<^{\mathcal{W}} = \{(0, 1), (0, 2), \dots, (7, 8)\}$ ,  $S^{\mathcal{W}} = \{(0, 1), (1, 2), \dots, (7, 8)\}$  uniquely defines the word  $W = aabbababa$ .
  - ▶ For convenience, we can just write the word instead of the structure.

# Free and Bound Variables

---

- ▶ For a wff  $\varphi = \forall x\psi$  or  $\exists x\psi$ ,  $\psi$  is said to be the **scope** of the quantifier  $x$

# Free and Bound Variables

---

- ▶ For a wff  $\varphi = \forall x\psi$  or  $\exists x\psi$ ,  $\psi$  is said to be the **scope** of the quantifier  $x$
- ▶ Every occurrence of  $x$  in  $\forall x\psi$  or  $\exists x\psi$  is **bound**
- ▶ Any occurrence of  $x$  which is not bound is called **free**  
X captured by quantifiers are bound and which are not captured by any quantifier are unbound.

# Free and Bound Variables

---

- ▶ For a wff  $\varphi = \forall x\psi$  or  $\exists x\psi$ ,  $\psi$  is said to be the **scope** of the quantifier  $x$
- ▶ Every occurrence of  $x$  in  $\forall x\psi$  or  $\exists x\psi$  is **bound**
- ▶ Any occurrence of  $x$  which is not bound is called **free**
- ▶  $\varphi = P(x, y) \rightarrow \forall x((\forall yR(x, y)) \rightarrow Q(x, y))$ 
  - ▶  $y$  is free in  $Q(x, y)$  and bound in  $R(x, y)$ ,
  - ▶  $x$  is free in  $P(x, y)$ , and bound in  $Q(x, y)$ ,  $R(x, y)$




# Free and Bound Variables

---

- ▶ For a wff  $\varphi = \forall x\psi$  or  $\exists x\psi$ ,  $\psi$  is said to be the **scope** of the quantifier  $x$
- ▶ Every occurrence of  $x$  in  $\forall x\psi$  or  $\exists x\psi$  is **bound**
- ▶ Any occurrence of  $x$  which is not bound is called **free**
- ▶  $\varphi = P(x, y) \rightarrow \forall x((\forall yR(x, y)) \rightarrow Q(x, y))$ 
  - ▶  $y$  is free in  $Q(x, y)$  and bound in  $R(x, y)$ ,
  - ▶  $x$  is free in  $P(x, y)$ , and bound in  $Q(x, y)$ ,  $R(x, y)$
- ▶ Given  $\varphi$ , denote by  $\varphi(x_1, \dots, x_n)$ , that  $x_1, \dots, x_n$  are the free variables of  $\varphi$ , also  $\text{free}(\varphi)$
- ▶ A sentence is a formula  $\varphi$  **none** of whose variables are **free**

$$P(x, y) \rightarrow \forall x((\forall y R(x, y)) \rightarrow Q(x, y))$$


---



$$P(x, y) \rightarrow \forall x((\forall y R(x, y)) \rightarrow Q(x, y))$$


See no quantifier in front of P, thus variables of P are free.

$$\varphi(s, t) = P(s, t) \rightarrow \forall x((\forall y R(x, y)) \rightarrow Q(x, t))$$




$$\forall x(R(x, y) \rightarrow \forall yP(y))$$

---



$$\forall x(R(x, y) \rightarrow \forall yP(y))$$

---



$$\varphi(t) = \forall x(R(x, t) \rightarrow \forall yP(y))$$

Rename the free var if it is same as bound one.

# Assignments on $\tau$ -structures

---

## Assignments

For a  $\tau$ -structure  $\mathcal{A}$ , an assignment over  $\mathcal{A}$  is a function  $\alpha : \mathcal{V} \rightarrow u(\mathcal{A})$  that assigns every variable  $x \in \mathcal{V}$  a value  $\alpha(x) \in u(\mathcal{A})$ . If  $t$  is a constant symbol  $c$ , then  $\alpha(t)$  is  $c^{\mathcal{A}}$

# Assignments on $\tau$ -structures

---

## Assignments

For a  $\tau$ -structure  $\mathcal{A}$ , an assignment over  $\mathcal{A}$  is a function  $\alpha : \mathcal{V} \rightarrow u(\mathcal{A})$  that assigns every variable  $x \in \mathcal{V}$  a value  $\alpha(x) \in u(\mathcal{A})$ . If  $t$  is a constant symbol  $c$ , then  $\alpha(t)$  is  $c^{\mathcal{A}}$

## Binding on a Variable

For an assignment  $\alpha$  over  $\mathcal{A}$ ,  $\alpha[x \mapsto a]$  is the assignment

$$\alpha[x \mapsto a](y) = \begin{cases} \alpha(y), & y \neq x, \\ a, & y = x \end{cases}$$

It is just put "a" at position x.

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:



# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha(t_1) = \alpha(t_2)$

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha(t_1) = \alpha(t_2)$
- ▶  $\mathcal{A} \models_{\alpha} R(t_1, \dots, t_k)$  iff  $(\alpha(t_1), \dots, \alpha(t_k)) \in R^{\mathcal{A}}$

If the assignment's are in domain then R is true in A under assignment alpha

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha(t_1) = \alpha(t_2)$
- ▶  $\mathcal{A} \models_{\alpha} R(t_1, \dots, t_k)$  iff  $(\alpha(t_1), \dots, \alpha(t_k)) \in R^{\mathcal{A}}$
- ▶  $\mathcal{A} \models_{\alpha} (\varphi \rightarrow \psi)$  iff  $\mathcal{A} \not\models_{\alpha} \varphi$  or  $\mathcal{A} \models_{\alpha} \psi$

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha(t_1) = \alpha(t_2)$
- ▶  $\mathcal{A} \models_{\alpha} R(t_1, \dots, t_k)$  iff  $(\alpha(t_1), \dots, \alpha(t_k)) \in R^{\mathcal{A}}$
- ▶  $\mathcal{A} \models_{\alpha} (\varphi \rightarrow \psi)$  iff  $\mathcal{A} \not\models_{\alpha} \varphi$  or  $\mathcal{A} \models_{\alpha} \psi$
- ▶  $\mathcal{A} \models_{\alpha} (\forall x)\varphi$  iff for every  $a \in u(\mathcal{A})$ ,  $\mathcal{A} \models_{\alpha[x \mapsto a]} \varphi$

# Satisfaction

---

We define the relation  $\mathcal{A} \models_{\alpha} \varphi$  (read as  $\varphi$  is true in  $\mathcal{A}$  under the assignment  $\alpha$ ) inductively:

- ▶  $\mathcal{A} \not\models_{\alpha} \perp$
- ▶  $\mathcal{A} \models_{\alpha} t_1 = t_2$  iff  $\alpha(t_1) = \alpha(t_2)$
- ▶  $\mathcal{A} \models_{\alpha} R(t_1, \dots, t_k)$  iff  $(\alpha(t_1), \dots, \alpha(t_k)) \in R^{\mathcal{A}}$
- ▶  $\mathcal{A} \models_{\alpha} (\varphi \rightarrow \psi)$  iff  $\mathcal{A} \not\models_{\alpha} \varphi$  or  $\mathcal{A} \models_{\alpha} \psi$
- ▶  $\mathcal{A} \models_{\alpha} (\forall x)\varphi$  iff for every  $a \in u(\mathcal{A})$ ,  $\mathcal{A} \models_{\alpha[x \mapsto a]} \varphi$
- ▶  $\mathcal{A} \models_{\alpha} (\exists x)\varphi$  iff there is some  $a \in u(\mathcal{A})$ ,  $\mathcal{A} \models_{\alpha[x \mapsto a]} \varphi$

Last two cases,  $\alpha$  has no effect on the value of  $x$ . Thus, assignments **matter only** to free variables.