


# CS 473: Algorithms

Chandra Chekuri  
chekuri@cs.illinois.edu  
3228 Siebel Center

University of Illinois, Urbana-Champaign

Fall 2010

# Strong Connected Components (SCCs)



## Algorithmic Problem

Find all SCCs of a given directed graph.

Previous lecture: saw an  $O(n \cdot (n + m))$  time algorithm.

This lecture:  $O(n + m)$  time algorithm.

# Graph of SCCs




Figure: Graph  $G$




Figure: Graph of SCCs  $G^{\text{SCC}}$

## Meta-graph of SCCs

Let  $S_1, S_2, \dots, S_k$  be the SCCs of  $G$ . The graph of SCCs is  $G^{\text{SCC}}$

- Vertices are  $S_1, S_2, \dots, S_k$
- There is an edge  $(S_i, S_j)$  if there is some  $u \in S_i$  and  $v \in S_j$  such that  $(u, v)$  is an edge in  $G$ .

# Reversal and SCCs

## Proposition

*For any graph  $G$ , the graph of SCCs of  $G^{\text{rev}}$  is the same as the reversal of  $G^{\text{SCC}}$ .*

## Proof.

Exercise. □

# SCCs and DAGs

## Proposition

*For any graph  $G$ , the graph  $G^{\text{SCC}}$  has no directed cycle.*

# SCCs and DAGs

## Proposition

*For any graph  $G$ , the graph  $G^{\text{SCC}}$  has no directed cycle.*

## Proof.

If  $G^{\text{SCC}}$  has a cycle  $S_1, S_2, \dots, S_k$  then  $S_1 \cup S_2 \cup \dots \cup S_k$  is an SCC in  $G$ . Formal details: exercise. □


# Part I

## Directed Acyclic Graphs

# Directed Acyclic Graphs


## Definition

A directed graph  $G$  is a directed acyclic graph (DAG) if there is no directed cycle in  $G$ .





# Sources and Sinks



## Definition

- A vertex  $u$  is a **source** if it has no in-coming edges.
- A vertex  $u$  is a **sink** if it has no out-going edges.

# Simple DAG Properties

- Every DAG  $G$  has at least one source and at least one sink.

# Simple DAG Properties

- Every DAG  $G$  has at least one source and at least one sink.
- If  $G$  is a DAG if and only if  $G^{rev}$  is a DAG.

# Simple DAG Properties

- Every DAG  $G$  has at least one source and at least one sink.
- If  $G$  is a DAG if and only if  $G^{rev}$  is a DAG.
- $G$  is a DAG if and only if each node is in its own strong connected component.

# Simple DAG Properties

- Every DAG  $G$  has at least one source and at least one sink.
- If  $G$  is a DAG if and only if  $G^{rev}$  is a DAG.
- $G$  is a DAG if and only if each node is in its own strong connected component.

# Simple DAG Properties

- Every DAG  $G$  has at least one source and at least one sink.
- If  $G$  is a DAG if and only if  $G^{rev}$  is a DAG.
- $G$  is a DAG if and only if each node is in its own strong connected component.

Formal proofs: exercise.

# Topological Ordering/Sorting




Figure: Graph  $G$




Figure: Topological Ordering of  $G$

## Definition

A **topological ordering/sorting** of  $G = (V, E)$  is an ordering  $<$  on  $V$  such that if  $(u, v) \in E$  then  $u < v$ .

# DAGs and Topological Sort

## Lemma

*A directed graph  $G$  can be topologically ordered iff it is a DAG.*



# DAGs and Topological Sort

## Lemma

*A directed graph  $G$  can be topologically ordered iff it is a DAG.*

## Proof.

Only if: Suppose  $G$  is not a DAG and has a topological ordering  $<$ .  
 $G$  has a cycle  $C = u_1, u_2, \dots, u_k, u_1$ .

Then  $u_1 < u_2 < \dots < u_k < u_1$ ! A contradiction. □

# DAGs and Topological Sort

## Lemma

*A directed graph  $G$  can be topologically ordered iff it is a DAG.*

## Proof.


If: Consider the following algorithm:

- Pick a source  $u$ , output it.
- Remove  $u$  and all edges out of  $u$ .
- Repeat until graph is empty.
- Exercise: prove this gives an ordering.




Exercise: show above algorithm can be implemented in  $O(m + n)$  time.

# Topological Sort: An Example




Output:

# Topological Sort: An Example




Output: 1

# Topological Sort: An Example




Output: 1 2

# Topological Sort: An Example




Output: 1 2 3

# Topological Sort: An Example



Output: 1 2 3 4

## Topological Sort: Another Example



*a d b c e g f h*



# DAGs and Topological Sort

**Note:** A DAG  $G$  may have many different topological sorts.

**Question:** What is a DAG with the most number of distinct topological sorts for a given number  $n$  of vertices?

**Question:** What is a DAG with the least number of distinct topological sorts for a given number  $n$  of vertices?

# DFS to check for Acyclicity and Topological Ordering

## Question

Given  $G$ , is it a DAG? If it is, generate a topological sort.

# DFS to check for Acyclicity and Topological Ordering

## Question

Given  $G$ , is it a DAG? If it is, generate a topological sort.

DFS based algorithm:

- Compute DFS( $G$ )
- If there is a back edge then  $G$  is not a DAG.
- Otherwise output nodes in decreasing post-visit order.

# DFS to check for Acyclicity and Topological Ordering

## Question

Given  $G$ , is it a DAG? If it is, generate a topological sort.

DFS based algorithm:

- Compute DFS( $G$ )
- If there is a back edge then  $G$  is not a DAG.
- Otherwise output nodes in decreasing post-visit order.

Correctness relies on the following:

## Proposition



$G$  is a DAG iff there is no back-edge in DFS( $G$ ).



## Proposition

If  $G$  is a DAG and  $post(v) > post(u)$ , then  $(u, v)$  is not in  $G$ .

# Example



# Back edge and Cycles

## Proposition

*$G$  has a cycle iff there is a back-edge in  $DFS(G)$ .*

## Proof.

If:  $(u, v)$  is a back edge implies there is a cycle  $C$  consisting of the path from  $v$  to  $u$  in DFS search tree and the edge  $(u, v)$ .

# Back edge and Cycles

## Proposition

*$G$  has a cycle iff there is a back-edge in DFS( $G$ ).*

## Proof.

If:  $(u, v)$  is a back edge implies there is a cycle  $C$  consisting of the path from  $v$  to  $u$  in DFS search tree and the edge  $(u, v)$ .

Only if: Suppose there is a cycle  $C = v_1 \rightarrow v_2 \rightarrow \dots \rightarrow v_k \rightarrow v_1$ .

Let  $v_i$  be first node in  $C$  visited in DFS.

All other nodes in  $C$  are descendants of  $v_i$  since they are reachable from  $v_i$ .

Therefore,  $(v_{i-1}, v_i)$  (or  $(v_k, v_1)$  if  $i = 1$ ) is a back edge. □

## Proposition

If  $G$  is a DAG and  $\text{post}(v) > \text{post}(u)$ , then  $(u, v)$  is not in  $G$ .

## Proof.

Assume  $\text{post}(v) > \text{post}(u)$  and  $(u, v)$  is an edge in  $G$ . We derive a contradiction. One of two cases holds from DFS property.

- **Case 1:**  $[\text{pre}(u), \text{post}(u)]$  is contained in  $[\text{pre}(v), \text{post}(v)]$ .  
Implies that  $(u, v)$  is a back edge but a DAG has no back edges!
- **Case 2:**  $[\text{pre}(u), \text{post}(u)]$  is disjoint from  $[\text{pre}(v), \text{post}(v)]$ .  
This cannot happen since  $v$  would be explored from  $u$ .



$$[\text{pre}(v) \text{ } [u \text{ } ] \text{ } \text{post}(v)] \quad [u] \quad [v]$$



# DAGs and Partial Orders

## Definition

A partially ordered set is a set  $S$  along with a binary relation  $\preceq$  such that  $\preceq$  is (i) reflexive ( $a \preceq a$  for all  $a \in V$ ), (ii) anti-symmetric ( $a \preceq b$  implies  $b \not\preceq a$ ) and (iii) transitive ( $a \preceq b$  and  $b \preceq c$  implies  $a \preceq c$ ).

# DAGs and Partial Orders

## Definition

A partially ordered set is a set  $S$  along with a binary relation  $\preceq$  such that  $\preceq$  is (i) reflexive ( $a \preceq a$  for all  $a \in V$ ), (ii) anti-symmetric ( $a \preceq b$  implies  $b \not\preceq a$ ) and (iii) transitive ( $a \preceq b$  and  $b \preceq c$  implies  $a \preceq c$ ).

**Example:** For numbers in the plane define  $(x, y) \preceq (x', y')$  iff  $x \leq x'$  and  $y \leq y'$ .

# DAGs and Partial Orders

Total order, all the elements of set are comparable with each other.

Partial order, some elements might not be comparable (Not all the elements need to have a relation).

## Definition

A partially ordered set is a set  $S$  along with a binary relation  $\preceq$  such that  $\preceq$  is (i) reflexive ( $a \preceq a$  for all  $a \in V$ ), (ii) anti-symmetric ( $a \preceq b$  implies  $b \not\preceq a$ ) and (iii) transitive ( $a \preceq b$  and  $b \preceq c$  implies  $a \preceq c$ ).

**Example:** For numbers in the plane define  $(x, y) \preceq (x', y')$  iff  $x \leq x'$  and  $y \leq y'$ .

**Observation:** A *finite* partially ordered set is equivalent to a DAG.

**Observation:** A topological sort of a DAG corresponds to a complete (or total) ordering of the underlying partial order.

## Part II

Linear time algorithm for finding all strong connected components of a directed graph

# Finding all SCCs of a Directed Graph

## Problem

Given a directed graph  $G = (V, E)$ , output *all* its strong connected components.

# Finding all SCCs of a Directed Graph

## Problem

Given a directed graph  $G = (V, E)$ , output *all* its strong connected components.

Straightforward algorithm:

```
For each vertex  $u \in V$  do
    find  $SCC(G, u)$  the strong component containing  $u$  as follows:
        Obtain  $rch(G, u)$  using  $DFS(G, u)$ 
        Obtain  $rch(G^{rev}, u)$  using  $DFS(G^{rev}, u)$ 
        Output  $SCC(G, u) = rch(G, u) \cap rch(G^{rev}, u)$ 
```

Running time:  $O(n(n + m))$

# Finding all SCCs of a Directed Graph

## Problem

Given a directed graph  $G = (V, E)$ , output *all* its strong connected components.

Straightforward algorithm:

```
For each vertex  $u \in V$  do
    find  $SCC(G, u)$  the strong component containing  $u$  as follows:
        Obtain  $rch(G, u)$  using  $DFS(G, u)$ 
        Obtain  $rch(G^{rev}, u)$  using  $DFS(G^{rev}, u)$ 
        Output  $SCC(G, u) = rch(G, u) \cap rch(G^{rev}, u)$ 
```

Running time:  $O(n(n + m))$

Is there an  $O(n + m)$  time algorithm?

# Structure of a Directed Graph




Figure: Graph  $G$




Figure: Graph of SCCs  $G^{\text{SCC}}$

## Proposition

*For a directed graph  $G$ , its meta-graph  $G^{\text{SCC}}$  is a DAG.*



# Linear-time Algorithm for SCCs: Ideas

Exploit structure of meta-graph.

## Algorithm

- Let  $u$  be a vertex in a sink SCC of  $G^{\text{SCC}}$
- Do  $\text{DFS}(u)$  to compute  $\text{SCC}(u)$
- Remove  $\text{SCC}(u)$  and repeat

## Justification

- $\text{DFS}(u)$  only visits vertices (and edges) in  $\text{SCC}(u)$
- $\text{DFS}(u)$  takes time proportional to size of  $\text{SCC}(u)$
- Therefore, total time  $O(n + m)$ !

# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

Can we obtain an *implicit* topological sort of  $G^{\text{SCC}}$  without computing  $G^{\text{SCC}}$ ?

# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

Can we obtain an *implicit* topological sort of  $G^{\text{SCC}}$  without computing  $G^{\text{SCC}}$ ?

**Answer:** DFS( $G$ ) gives some information!

# Post-visit times of SCCs

## Definition

Given  $G$  and a SCC  $S$  of  $G$ , define  $\text{post}(S) = \max_{u \in S} \text{post}(u)$  where post numbers are with respect to some  $\text{DFS}(G)$ .

# An Example




Figure: Graph  $G$




Figure: Graph with pre-post times for DFS(A); black edges in tree




Figure:  $G^{\text{SCC}}$  with post times

# $G^{\text{SCC}}$ and post-visit times

## Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

## $G^{\text{SCC}}$ and post-visit times

### Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

### Proof.

Let  $u$  be first vertex in  $S \cup S'$  that is visited.





## $G^{\text{SCC}}$ and post-visit times

### Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

### Proof.

Let  $u$  be first vertex in  $S \cup S'$  that is visited.

- If  $u \in S$  then all of  $S'$  will be explored before  $\text{DFS}(u)$  completes.



## $G^{\text{SCC}}$ and post-visit times

### Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

### Proof.

Let  $u$  be first vertex in  $S \cup S'$  that is visited.

- If  $u \in S$  then all of  $S'$  will be explored before  $\text{DFS}(u)$  completes.
- If  $u \in S'$  then all of  $S'$  will be explored before any of  $S$ .



## $G^{\text{SCC}}$ and post-visit times

### Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

### Proof.

Let  $u$  be first vertex in  $S \cup S'$  that is visited.

- If  $u \in S$  then all of  $S'$  will be explored before  $\text{DFS}(u)$  completes.
- If  $u \in S'$  then all of  $S'$  will be explored before any of  $S$ .



## $G^{\text{SCC}}$ and post-visit times

### Proposition

*If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then  $\text{post}(S) > \text{post}(S')$ .*

### Proof.

Let  $u$  be first vertex in  $S \cup S'$  that is visited.

- If  $u \in S$  then all of  $S'$  will be explored before  $\text{DFS}(u)$  completes.
- If  $u \in S'$  then all of  $S'$  will be explored before any of  $S$ .



**A False Statement:** If  $S$  and  $S'$  are SCCs in  $G$  and  $(S, S')$  is an edge in  $G^{\text{SCC}}$  then for every  $u \in S$  and  $u' \in S'$ ,  $\text{post}(u) > \text{post}(u')$ .

# Topological ordering of $G^{\text{SCC}}$

## Corollary

*Ordering SCCs in decreasing order of  $\text{post}(S)$  gives a topological ordering of  $G^{\text{SCC}}$*

# Topological ordering of $G^{\text{SCC}}$

## Corollary

*Ordering SCCs in decreasing order of  $\text{post}(S)$  gives a topological ordering of  $G^{\text{SCC}}$*

**Recall:** for a DAG, ordering nodes in decreasing post-visit order gives a topological sort.

$\text{DFS}(G)$  gives some information on topological ordering of  $G^{\text{SCC}}$ !

# An Example




Figure: Graph  $G$




Figure: Graph with pre-post times for DFS(A); black edges in tree




Figure:  $G^{\text{SCC}}$  with post times

# Linear-time Algorithm for SCCs: Ideas

Exploit structure of meta-graph.

## Algorithm

- Let  $u$  be a vertex in a sink SCC of  $G^{\text{SCC}}$
- Do  $\text{DFS}(u)$  to compute  $\text{SCC}(u)$
- Remove  $\text{SCC}(u)$  and repeat

## Justification

- $\text{DFS}(u)$  only visits vertices (and edges) in  $\text{SCC}(u)$
- $\text{DFS}(u)$  takes time proportional to size of  $\text{SCC}(u)$
- Therefore, total time  $O(n + m)$ !



# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

Can we obtain an *implicit* topological sort of  $G^{\text{SCC}}$  without computing  $G^{\text{SCC}}$ ?

# Big Challenge(s)

How do we find a vertex in the sink SCC of  $G^{\text{SCC}}$ ?

Can we obtain an *implicit* topological sort of  $G^{\text{SCC}}$  without computing  $G^{\text{SCC}}$ ?

**Answer:** DFS( $G$ ) gives some information!

# Finding Sources

## Proposition

*The vertex  $u$  with the highest post visit time belongs to a source SCC in  $G^{\text{SCC}}$*

# Finding Sources

## Proposition

*The vertex  $u$  with the highest post visit time belongs to a source SCC in  $G^{\text{SCC}}$*

## Proof.

- $\text{post}(\text{SCC}(u)) = \text{post}(u)$
- Thus,  $\text{post}(\text{SCC}(u))$  is highest and will be output first in topological ordering of  $G^{\text{SCC}}$ .



# Finding Sinks

## Proposition

*The vertex  $u$  with highest post visit time in  $\text{DFS}(G^{\text{rev}})$  belongs to a sink SCC of  $G$ .*

# Finding Sinks

## Proposition

*The vertex  $u$  with highest post visit time in  $\text{DFS}(G^{\text{rev}})$  belongs to a sink SCC of  $G$ .*

## Proof.

- $u$  belongs to source SCC of  $G^{\text{rev}}$
- Since graph of SCCs of  $G^{\text{rev}}$  is the reverse of  $G^{\text{SCC}}$ ,  $\text{SCC}(u)$  is sink SCC of  $G$ . □

# Linear Time Algorithm

```
Do DFS( $G^{\text{rev}}$ ) and sort vertices in decreasing post order.  
Mark all nodes as unvisited  
for each  $u$  in the computed order do  
    if  $u$  is not visited then  
        DFS( $u$ )  
        Let  $S_u$  be the nodes reached by  $u$   
        Output  $S_u$  as a strong connected component  
        Remove  $S_u$  from  $G$ 
```

## Analysis

Running time is  $O(n + m)$ . (Exercise)



# Linear Time Algorithm: An Example




Figure: Graph  $G$

# Linear Time Algorithm: An Example




Figure: Graph  $G$




Figure:  $G^{\text{rev}}$

# Linear Time Algorithm: An Example




Figure: Graph G




Figure:  $G^{\text{rev}}$  with pre-post times.  
Red edges not traversed in DFS

# Linear Time Algorithm: An Example




Figure: Graph  $G$




Figure:  $G^{\text{rev}}$  with pre-post times.  
Red edges not traversed in DFS

Order of second DFS:  $\text{DFS}(G) = \{G\}$ ;

# Linear Time Algorithm: An Example




Figure: Graph  $G$




Figure:  $G^{\text{rev}}$  with pre-post times.  
Red edges not traversed in DFS

Order of second DFS:  $\text{DFS}(G) = \{G\}$ ;  $\text{DFS}(H) = \{H\}$ ;

# Linear Time Algorithm: An Example




Figure: Graph  $G$




Figure:  $G^{\text{rev}}$  with pre-post times.  
Red edges not traversed in DFS

Order of second DFS:  $\text{DFS}(G) = \{G\}$ ;  $\text{DFS}(H) = \{H\}$ ;  
 $\text{DFS}(B) = \{B, E, F\}$ ;

# Linear Time Algorithm: An Example




Figure: Graph  $G$




Figure:  $G^{\text{rev}}$  with pre-post times.  
Red edges not traversed in DFS

Order of second DFS:  $\text{DFS}(G) = \{G\}$ ;  $\text{DFS}(H) = \{H\}$ ;  
 $\text{DFS}(B) = \{B, E, F\}$ ;  $\text{DFS}(A) = \{A, C, D\}$ .

# Obtaining the meta-graph from strong connected components

**Exercise:** Given all the strong connected components of a directed graph  $G = (V, E)$  show that the meta-graph  $G^{\text{SCC}}$  can be obtained in  $O(m + n)$  time.



## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$

## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$
- Strong components of  $G^{rev}$  and  $G$  are same and meta-graph of  $G$  is reverse of meta-graph of  $G^{rev}$ .

## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$
- Strong components of  $G^{rev}$  and  $G$  are same and meta-graph of  $G$  is reverse of meta-graph of  $G^{rev}$ .
- consider  $DFG(G^{rev})$  and let  $u_1, u_2, \dots, u_k$  be such that  $post(u_i) = post(S_i) = \max_{v \in S_i} post(v)$ .

## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$
- Strong components of  $G^{rev}$  and  $G$  are same and meta-graph of  $G$  is reverse of meta-graph of  $G^{rev}$ .
- consider  $DFG(G^{rev})$  and let  $u_1, u_2, \dots, u_k$  be such that  $post(u_i) = post(S_i) = \max_{v \in S_i} post(v)$ .
- Assume without loss of generality that  $post(u_k) > post(u_{k-1}) \geq \dots \geq post(u_1)$  (renumber otherwise). Then  $S_k, S_{k-1}, \dots, S_1$  is a topological sort of meta-graph of  $G^{rev}$  and hence  $S_1, S_2, \dots, S_k$  is a topological sort of the meta-graph of  $G$ .

## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$
- Strong components of  $G^{rev}$  and  $G$  are same and meta-graph of  $G$  is reverse of meta-graph of  $G^{rev}$ .
- consider  $DFG(G^{rev})$  and let  $u_1, u_2, \dots, u_k$  be such that  $post(u_i) = post(S_i) = \max_{v \in S_i} post(v)$ .
- Assume without loss of generality that  $post(u_k) > post(u_{k-1}) \geq \dots \geq post(u_1)$  (renumber otherwise). Then  $S_k, S_{k-1}, \dots, S_1$  is a topological sort of meta-graph of  $G^{rev}$  and hence  $S_1, S_2, \dots, S_k$  is a topological sort of the meta-graph of  $G$ .
- $u_k$  has highest post number and  $DFS(u_k)$  will explore all of  $S_k$  which is a sink component in  $G$ .

## Correctness: more details

- let  $S_1, S_2, \dots, S_k$  be strong components in  $G$
- Strong components of  $G^{rev}$  and  $G$  are same and meta-graph of  $G$  is reverse of meta-graph of  $G^{rev}$ .
- consider  $DFG(G^{rev})$  and let  $u_1, u_2, \dots, u_k$  be such that  $post(u_i) = post(S_i) = \max_{v \in S_i} post(v)$ .
- Assume without loss of generality that  $post(u_k) > post(u_{k-1}) \geq \dots \geq post(u_1)$  (renumber otherwise). Then  $S_k, S_{k-1}, \dots, S_1$  is a topological sort of meta-graph of  $G^{rev}$  and hence  $S_1, S_2, \dots, S_k$  is a topological sort of the meta-graph of  $G$ .
- $u_k$  has highest post number and  $DFS(u_k)$  will explore all of  $S_k$  which is a sink component in  $G$ .
- After  $S_k$  is removed  $u_{k-1}$  has highest post number and  $DFS(u_{k-1})$  will explore all of  $S_{k-1}$  which is a sink component in remaining graph  $G - S_k$ . Formal proof by induction.

## Part III

An Application to make

# make Utility [Feldman]

- Unix utility for automatically building large software applications



# make Utility [Feldman]

- Unix utility for automatically building large software applications
- A makefile specifies

# make Utility [Feldman]

- Unix utility for automatically building large software applications
- A makefile specifies
  - Object files to be created,

# make Utility [Feldman]

- Unix utility for automatically building large software applications
- A makefile specifies
  - Object files to be created,
  - Source/object files to be used in creation, and

# make Utility [Feldman]


- Unix utility for automatically building large software applications
- A makefile specifies
  - Object files to be created,
  - Source/object files to be used in creation, and
  - How to create them

# An Example makefile

```
project:  main.o utils.o command.o
    cc -o project main.o utils.o command.o

main.o:  main.c defs.h
    cc -c main.c
utils.o:  utils.c defs.h command.h
    cc -c utils.c
command.o:  command.c defs.h command.h
    cc -c command.c
```

# makefile as a Digraph



# Computational Problems for make

- Is the `makefile` reasonable?

# Computational Problems for make

- Is the `makefile` reasonable?
- If it is reasonable, in what order should the object files be created?



# Computational Problems for `make`

- Is the `makefile` reasonable?
- If it is reasonable, in what order should the object files be created?
- If it is not reasonable, provide helpful debugging information.

# Computational Problems for make

- Is the `makefile` reasonable?
- If it is reasonable, in what order should the object files be created?
- If it is not reasonable, provide helpful debugging information.
- If some file is modified, find the fewest compilations needed to make application consistent.

# Algorithms for make

- Is the makefile reasonable? Is  $G$  a DAG?

# Algorithms for make

- Is the makefile reasonable? Is  $G$  a DAG?
- If it is reasonable, in what order should the object files be created? Find a topological sort of a DAG.

# Algorithms for make

- Is the makefile reasonable? Is  $G$  a DAG?
- If it is reasonable, in what order should the object files be created? Find a topological sort of a DAG.
- If it is not reasonable, provide helpful debugging information. Output a cycle. More generally, output all strong connected components.

# Algorithms for make

- Is the makefile reasonable? **Is  $G$  a DAG?**
- If it is reasonable, in what order should the object files be created? **Find a topological sort of a DAG.**
- If it is not reasonable, provide helpful debugging information. **Output a cycle. More generally, output all strong connected components.**
- If some file is modified, find the fewest compilations needed to make application consistent.

# Algorithms for make

- Is the makefile reasonable? Is  $G$  a DAG?
- If it is reasonable, in what order should the object files be created? Find a topological sort of a DAG.
- If it is not reasonable, provide helpful debugging information. Output a cycle. More generally, output all strong connected components.
- If some file is modified, find the fewest compilations needed to make application consistent.
  - Find all vertices reachable (using DFS/BFS) from modified files in directed graph, and recompile them in proper order. Verify that one can find the files to recompile and the ordering in linear time.

# Takeaway Points

- Given a directed graph  $G$ , its SCCs and the associated acyclic meta-graph  $G^{\text{SCC}}$  give a structural decomposition of  $G$  that should be kept in mind.
- There is a DFS based linear time algorithm to compute all the SCCs and the meta-graph. Properties of DFS crucial for the algorithm.
- DAGs arise in many application and topological sort is a key property in algorithm design. Linear time algorithms to compute a topological sort (there can be many possible orderings so not unique).