

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <string.h>

int main() {
    char command[100];
    char *args[20];
    char *token;
    int i = 0;
    pid_t pid;
    int status;

    printf("Enter a Linux command: ");
    fgets(command, sizeof(command), stdin);

    // Remove newline
    command[strcspn(command, "\n")] = '\0';

    // Split command into arguments
    token = strtok(command, " ");

    while (token != NULL && i < 19) {
        args[i++] = token;
        token = strtok(NULL, " ");
    }

    args[i] = NULL;

    // Create child process
    pid = fork();

    if (pid < 0) {
        perror("fork failed");
        return 1;
    }

    else if (pid == 0) {
        // Child process
        printf("\nChild Process:\n");
        printf("Child PID : %d\n", getpid());
        printf("Parent PID : %d\n", getppid());

        // Execute command
        execvp(args[0], args);
    }
}
```

```
Last login: Fri Aug 14 01:44:36 on console
venkat@Venkats-MacBook-Air ~ % nano week-1.c
venkat@Venkats-MacBook-Air ~ % gcc week-1.c
venkat@Venkats-MacBook-Air ~ % ./a.out
Enter a Linux command: ls

Parent Process:
Parent PID : 26738
Child PID  : 26741

Child Process:
Child PID  : 26741
Parent PID : 26738
a.out      arithmetic.c  Documents      execse.c        execworking.c.save  Movies          Pictures        TextHackCorpus.java
Applications Desktop      Downloads      execworking.c   Library           Music           Public          week-1.c

Child process has completed.
Parent process resumes execution.
venkat@Venkats-MacBook-Air ~ % █
```