



Chapter 8: Subnetting IP Networks

CCNA Routing and Switching

Introduction to Networks v6.0



Chapter 8 - Sections & Objectives

- 8.1 Subnetting an IPv4 Network
 - Implement an IPv4 addressing scheme to enable end-to-end connectivity in a small to medium-sized business network.
 - Explain how subnetting segments a network to enable better communication.
 - Explain how to calculate IPv4 subnets for a /24 prefix.
 - Explain how to calculate IPv4 subnets for a /16 and /8 prefix.
 - Given a set of requirements for subnetting, implement an IPv4 addressing scheme.
 - Explain how to create a flexible addressing scheme using variable length subnet masking (VLSM).
- 8.2 Addressing Schemes
 - Given a set of requirements, implement a VLSM addressing scheme to provide connectivity to end users in a small to medium-sized network.
 - Implement a VLSM addressing scheme.

Chapter 8 - Sections & Objectives (Cont.)

- 8.3 Address Schemes
 - Explain design considerations for implementing IPv6 in a business network.
 - Explain how to implement IPv6 address assignments in a business network.


8.1 Subnetting an IPv4 Network



Network Segmentation



Broadcast Domains

- Devices use broadcasts in an Ethernet LAN to locate:
 - **Other devices** - Address Resolution Protocol (ARP) which sends Layer 2 broadcasts to a known IPv4 address on the local network to discover the associated MAC address.
 - **Services** – Dynamic Host Configuration Protocol (DHCP) which sends broadcasts on the local network to locate a DHCP server.
- Switches propagate broadcasts out all interfaces except the interface on which it was received.



Problems with Large Broadcast Domains

- Hosts can generate excessive broadcasts and negatively affect the network.
 - Slow network operations due to the significant amount of traffic it can cause.
 - Slow device operations because a device must accept and process each broadcast packet.
- Solution: Reduce the size of the network to create smaller broadcast domains. These smaller network spaces are called *subnets*.





Network Segmentation

Reasons for Subnetting


- Reduces overall network traffic and improves network performance.
- Enables an administrator to implement security policies such as which subnets are allowed or not allowed to communicate together.

Subnetting by Location



Communicating between Networks

Subnetting by Device Type



Subnetting an IPv4 Network

Octet Boundaries

Networks are most easily subnetted at the octet boundary of /8, /16, and /24

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of hosts
/8	255.0.0.0	<code>nnnnnnnn . hhhhhhhh . hhhhhhhh . hhhhhhhh</code> <code>11111111 . 00000000 . 00000000 . 00000000</code>	16,777,214
/16	255.255.0.0	<code>nnnnnnnn . nnnnnnnn . hhhhhhhh . hhhhhhhh</code> <code>11111111 . 11111111 . 00000000 . 00000000</code>	65,534
/24	255.255.255.0	<code>nnnnnnnn . nnnnnnnn . nnnnnnnn . hhhhhhhh</code> <code>11111111 . 11111111 . 11111111 . 00000000</code>	254

- Prefix length and the subnet mask are different ways of identifying the network portion of an address.
- Subnets are created by borrowing host bits for network bits.
- More host bits borrowed, the more subnets that can be defined.

Subnetting on the Octet Boundary

Subnet Address (256 Possible Subnets)	Host Range (65,534 possible hosts per subnet)	Broadcast
<u>10.0.0.0/16</u>	<u>10.0.0.1</u> – <u>10.0.255.254</u>	<u>10.0.255.255</u>
<u>10.1.0.0/16</u>	<u>10.1.0.1</u> – <u>10.1.255.254</u>	<u>10.1.255.255</u>
<u>10.2.0.0/16</u>	<u>10.2.0.1</u> – <u>10.2.255.254</u>	<u>10.2.255.255</u>
<u>10.3.0.0/16</u>	<u>10.3.0.1</u> – <u>10.3.255.254</u>	<u>10.3.255.255</u>
<u>10.4.0.0/16</u>	<u>10.4.0.1</u> – <u>10.4.255.254</u>	<u>10.4.255.255</u>
<u>10.5.0.0/16</u>	<u>10.5.0.1</u> – <u>10.5.255.254</u>	<u>10.5.255.255</u>
<u>10.6.0.0/16</u>	<u>10.6.0.1</u> – <u>10.6.255.254</u>	<u>10.6.255.255</u>
<u>10.7.0.0/16</u>	<u>10.7.0.1</u> – <u>10.7.255.254</u>	<u>10.7.255.255</u>
...
<u>10.255.0.0/16</u>	<u>10.255.0.1</u> – <u>10.255.255.254</u>	<u>10.255.255.255</u>

- Subnetting Network 10.x.0.0/16
- Define up to 256 subnets with each subnet capable of connecting 65,534 hosts.
- First two octets identify the network portion while the last two octets are for host IP addresses.

Subnetting on the Octet Boundary (Cont.)

Subnet Address (65,536 Possible Subnets)	Host Range (254 possible hosts per subnet)	Broadcast
<u>10.0.0.0/24</u>	<u>10.0.0.1</u> - <u>10.0.0.254</u>	<u>10.0.0.255</u>
<u>10.0.1.0/24</u>	<u>10.0.1.1</u> - <u>10.0.1.254</u>	<u>10.0.1.255</u>
<u>10.0.2.0/24</u>	<u>10.0.2.1</u> - <u>10.0.2.254</u>	<u>10.0.1.255</u>
...
<u>10.0.255.0/24</u>	<u>10.0.255.1</u> - <u>10.0.255.254</u>	<u>10.0.255.255</u>
<u>10.1.0.0/24</u>	<u>10.1.0.1</u> - <u>10.1.0.254</u>	<u>10.1.0.255</u>
<u>10.1.1.0/24</u>	<u>10.1.1.1</u> - <u>10.1.1.254</u>	<u>1.1.1.0.255</u>
<u>10.1.2.0/24</u>	<u>10.1.2.1</u> - <u>10.1.2.254</u>	<u>10.1.2.0.255</u>
...
<u>10.100.0.0/24</u>	<u>10.100.0.1</u> - <u>10.100.0.254</u>	<u>10.100.0.255</u>
...
<u>10.255.255.0/24</u>	<u>10.255.255.1</u> - <u>10.255.255.254</u>	<u>10.255.255.255</u>

- Subnetting Network 10.x.x.0/24
- Define 65,536 subnets each capable of connecting 254 hosts.
- /24 boundary is very popular in subnetting because of number of hosts.

Subnetting an IPv4 Network

Classless Subnetting

Subnetting a /24 Network

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of subnets	# of hosts
/25	255.255.255.128	n n n n n n n n . n n n n n n n n . n n n n n n n n . n h h h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 0 0 0 0 0 0 0	2	126
/26	255.255.255.192	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n h h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 0 0 0 0 0 0	4	62
/27	255.255.255.224	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 0 0 0 0 0	8	30
/28	255.255.255.240	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n n h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 0 0 0 0	16	14
/29	255.255.255.248	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n n n h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 0 0 0	32	6
/30	255.255.255.252	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n n n n h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 0 0	64	2

Subnets can borrow bits from *any* host bit position to create other masks.

Video Demonstration – The Subnet Mask

Subnetting in Binary

- ANDING
 - Convert IP address and Subnet Mask to Binary (line up vertically like an addition problem)
 - Logically AND (1 and 1 = 1, all other combinations = 0)
 - Result is network address for original IP address
- Classful Subnetting
 - Class A /8 255.0.0.0
 - Class B /16 255.255.0.0
 - Class C /24 255.255.255.0



Subnetting an IPv4 Network

Video Demonstration – The Subnet Mask (Cont.)

Subnetting 192.168.1.0/24			
192	168	1	0
255	255	255	128
11000000	10101000	00000001	00000000
11111111	11111111	11111111	10000000
N	N	N	Sn H

Subnet bits = $2^1 = 2$
Host bits = $2^7 = 128 - 2 = 126$
Subnetworks = 2

Subnetting 192.168.1.0/24			
192	168	1	68
255	255	255	128
11000000	10101000	00000001	01000100
11111111	11111111	11111111	10000000
11000000	10101000	00000001	00000000
192	168	1	0

192.168.1.0 /25 -----> 192.168.1.127 /25
192.168.1.128 /25 -----> 192.168.1.255 /25

Video Demonstration – Subnetting with the Magic Number

- Magic number technique used to calculate subnets
- Magic number is simply the place value of the last one in the subnet mask
- /25 11111111.11111111.11111111.10000000 magic number = 128
- /26 11111111.11111111.11111111.11000000 magic number = 64
- /27 11111111.11111111.11111111.11100000 magic number = 32



Video Demonstration – Subnetting with the Magic Number (Cont.)

The Magic Number is the last 1 in Binary

192	168	1	0
255	255	255	224
11000000	10101000	00000001	00000000
11111111	11111111	11111111	11100000
			SN H

The Magic Number is? 32

- 192.168.1.0 /27
- 192.168.1.32 /27
- 192.168.1.64 /27
- 192.168.1.96 /27
- 192.168.1.128 /27
- 192.168.1.160 /27
- 192.168.1.192 /27
- 192.168.1.224 /27

Video Demonstration – Subnetting with the Magic Number (Cont.)

Subnetting 172.16.0.0/16 -->/23

172	16	0	0
255	255	254	0
10101010	00010000	00000000	00000000
11111111	11111111	1111 1110	00000000
		Sn	H

What is the magic number? 2



172.16.0.0 ---- 172.16.1.255 /23

172.16.2.0 /23

172.16.4.0 /23

Subnetting an IPv4 Network



Classless Subnetting Example



Subnetting an IPv4 Network

Creating 2 Subnets

■ /25 Subnetting Topology




Video Demonstration – Creating Two Equal-sized Subnets (/25)

Create 2 Equal-sized Subnets from 192.168.1.0 /24

- **Subnet Mask** - 11111111.11111111.11111111.10000000

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
128	64	32	16	8	4	2	1
1	0	0	0	0	0	0	0

- Magic Number = 128
- 192.168.1.0 /25 (start at 0)
- 192.168.1.128 /25 (Add 128)



Subnetting an IPv4 Network


Subnetting Formulas

Calculate Number of Subnets Formula

$$2^n$$

n = bits borrowed

Subnetting a /24 Network



Subnetting an IPv4 Network

Subnetting Formulas (Cont.)

Calculate Number of
Hosts Formula

$$2^n - 2$$

n = the number of bits remaining in the host
field

Calculating the Number of Hosts

192. 168. 1. 0 000 0000




7 bits remain in host field

$2^7 = 128$ IP addresses per subnet
 $2^7 - 2 = 126$ host IP addresses per subnet

Subnetting an IPv4 Network

Creating 4 Subnets

- /26 Subnetting Topology



Subnetting an IPv4 Network

Creating 4 Subnets (Cont.)


- /26 Subnetting Topology

Net 0	Network	192.	168.	1.	00	00	0000	192.168.1.0
	First	192.	168.	1.	00	00	0001	192.168.1.1
	Last	192.	168.	1.	00	11	1110	192.168.1.62
	Broadcast	192.	168.	1.	00	11	1111	192.168.1.63
Net 1	Network	192.	168.	1.	01	00	0000	192.168.1.64
	First	192.	168.	1.	01	00	0001	192.168.1.65
	Last	192.	168.	1.	01	11	1110	192.168.1.126
	Broadcast	192.	168.	1.	01	11	1111	192.168.1.127
Net 2	Network	192.	168.	1.	10	00	0000	192.168.1.128
	First	192.	168.	1.	10	00	0001	192.168.1.129
	Last	192.	168.	1.	10	11	1110	192.168.1.190
	Broadcast	192.	168.	1.	10	11	1111	192.168.1.191

Subnetting an IPv4 Network

Creating 4 Subnets (Cont.)

- /26 Subnetting Topology



Video Demonstration – Creating Four Equal-sized Subnets (/26)

Create 4 Equal-sized Subnets from 192.168.1.0 /24

- Subnet Mask in Binary – 11111111.11111111.11111111.**11**000000
- $2^2 = 4$ Subnets
- Magic Number = 64
- 192.168.1.0 /26
- 192.168.1.64 /26
- 192.168.1.128 /26
- 192.168.1.192 /26



Video Demonstration – Creating Eight Equal-sized Subnets (/27)

Create 8 Equal-sized Subnets from 192.168.1.0 /24

- Borrow 3 bits – 11111111.11111111.11111111.**111**00000
- Magic Number = 32
- 192.168.1.0 /27 (Start at 0)
- 192.168.1.32 /27 (Add 32 to previous network)
- 192.168.1.64 /27 (Add 32)
- 192.168.1.96 /27 (Add 32)
- 192.168.1.128 /27 (Add 32)
- 192.168.1.160 /27 (Add 32)
- 192.168.1.192 /27 (Add 32)
- 192.168.1.224 /27 (Add 32)





Subnetting a /16 and /8 Prefix

Creating Subnets with a /16 prefix

Subnetting a /16 Network				
Prefix Length	Subnet Mask	Network Address (n = network, h = host)	# of subnets	# of hosts
/17	255.255.128.0	nnnnnnnn.nnnnnnnn.nh h h h h h h h h h h h h h h h h 11111111.11111111.10000000.00000000	2	32766
/18	255.255.192.0	nnnnnnnn.nnnnnnnn.nn h h h h h h h h h h h h h h h h 11111111.11111111.11000000.00000000	4	16382
/19	255.255.224.0	nnnnnnnn.nnnnnnnn.nnn h h h h h h h h h h h h h h h h 11111111.11111111.11100000.00000000	8	8190
/20	255.255.240.0	nnnnnnnn.nnnnnnnn.nnnn h h h h h h h h h h h h h h h h 11111111.11111111.11110000.00000000	16	4094
/21	255.255.248.0	nnnnnnnn.nnnnnnnn.nnnnn h h h h h h h h h h h h h h h h 11111111.11111111.11111000.00000000	32	2046
/22	255.255.252.0	nnnnnnnn.nnnnnnnn.nnnnnn h h h h h h h h h h h h h h h h 11111111.11111111.11111100.00000000	64	1022

Subnetting a /16 and /8 Prefix

Creating 100 Subnets with a /16 prefix



Subnetting a /16 and /8 Prefix

Calculating the Hosts

Hosts = 2^n
(where n = host bits remaining)

172.	16.	00 00 00 0	0. 0000 0000
------	-----	------------	--------------

9 bits remain in host field

$2^9 = 512$ IP addresses per subnet
 $2^9 - 2 = 510$ host IP addresses per subnet

Address Range for 172.16.0.0/23 Subnet

Network Address

172.	16.	00 00 00 0	0. 0000 0000
------	-----	------------	--------------

 = 172.16.0.0/23

First Host Address

172.	16.	00 00 00 0	0. 0000 0001
------	-----	------------	--------------

 = 172.16.0.1/23

Last Host Address

172.	16.	00 00 00 0	1. 1111 1110
------	-----	------------	--------------

 = 172.16.1.254/23


Broadcast Address

172.	16.	00 00 00 0	1. 1111 1111
------	-----	------------	--------------


 = 172.16.1.255/23

Video Demonstration – Creating One Hundred Equal-sized Subnets

- An enterprise network requires 100 equal-sized subnets starting from 172.16.0.0/16
 - New Subnet Mask
 - 11111111.11111111.**11111111**0.00000000
 - $2^7 = 128$ Subnets
 - $2^9 = 512$ hosts per subnet
 - Magic Number = 2
 - 172.16.**0**.0 /23
 - 172.16.**2**.0 /23
 - 172.16.**4**.0 /23
 - 172.16.**6**.0 /23
 - ...
 - 172.16.**254**.0 /23





Creating 1000 Subnets with a /8 Network



Subnetting a /16 and /8 Prefix

Creating 1000 Subnets with a /8 Network (Cont.)



Video Demonstration – Subnetting Across Multiple Octets

The Magic Number is the last 1 in Binary

10	0	0	0
255	0	0	0
00001010	00000000	00000000	00000000
11111111	11100000	00000000	00000000
	SN H	H	H

The Magic Number is? 32

10.0.0.0 /11

10.32.0.0 /11

10.64.0.0 /11

10.96.0.0 /11

10.128.0.0 /11

10.160.0.0 /11

10.192.0.0 – 10.223.255.255 /11

10.224.0.0 /11




New Challenge Problem: Create over 300 Equal-sized Subnets of 20,000 Hosts each starting from 10.0.0.0/8

Subnetting Based on Host Requirements

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of subnets	# of hosts
/25	255.255.255.128	n n n n n n n n . n n n n n n n n . n n n n n n n n . n h h h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 0 0 0 0 0 0 0	2	126
/26	255.255.255.192	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n h h h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 0 0 0 0 0 0 0	4	62
/27	255.255.255.224	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n h h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 0 0 0 0 0 0	8	30
/28	255.255.255.240	n n n n n n n n . n n n n n n n n . n n n n n n n n . n n n n h h h h h 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 1 1 1 1 . 1 1 1 1 0 0 0 0 0	16	14



Subnetting Based On Network Requirements

Host devices used by employees in the Engineering department in one network and Management in a separate network.



Subnetting to Meet Requirements

Network Requirement Example




	Network Portion	Host Portion		Dotted Decimal
	10101100.00010000.000000	00.00	000000	172.16.0.0/22
0	10101100.00010000.000000	00.00	000000	172.16.0.0/26
1	10101100.00010000.000000	00.01	000000	172.16.0.64/26
2	10101100.00010000.000000	00.10	000000	172.16.0.128/26
3	10101100.00010000.000000	00.11	000000	172.16.0.192/26
4	10101100.00010000.000000	01.00	000000	172.16.1.0/26
5	10101100.00010000.000000	01.01	000000	172.16.1.64/26
6	10101100.00010000.000000	01.10	000000	172.16.1.128/26
Nets 7 - 13 not shown				
14	10101100.00010000.000000	11.10	000000	172.16.3.128/26
15	10101100.00010000.000000	11.11	000000	172.16.3.192/26

4 bits borrowed from host portion to create subnets

Subnetting to Meet Requirements

Network Requirement Example (Cont.)



Lab – Calculating IPv4 Subnets



Lab – Calculating IPv4 Subnets

Objectives

Part 1: Determine IPv4 Address Subnetting

Part 2: Calculate IPv4 Address Subnetting

Background / Scenario

The ability to work with IPv4 subnets and determine network and host information based on a given IP address and subnet mask is critical to understanding how IPv4 networks operate. The first part is designed to reinforce how to compute network IP address information from a given IP address and subnet mask. When given an IP address and subnet mask, you will be able to determine other information about the subnet.

Required Resources

- 1 PC (Windows 7 or 8 with Internet access)
- Optional: IPv4 address calculator

Part 1: Determine IPv4 Address Subnetting

In Part 1, you will determine the network and broadcast addresses, as well as the number of hosts, given an IPv4 address and subnet mask.

REVIEW: To determine the network address, perform binary ANDing on the IPv4 address using the subnet mask provided. The result will be the network address. Hint: If the subnet mask has decimal value 255 in an octet, the result will ALWAYS be the original value of that octet. If the subnet mask has decimal value 0 in an octet, the result will ALWAYS be 0 for that octet.

Example:

IP Address	192.168.10.10
Subnet Mask	255.255.255.0
	=====
Result (Network)	192.168.10.0

Subnetting to Meet Requirements

Packet Tracer – Subnetting Scenario




Cisco Networking Academy®

Mind Wide Open™

Packet Tracer - Subnetting Scenario

Topology



Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
R1	G0/0			
	G0/1			
	S0/0/0			


Subnetting to Meet Requirements

Lab – Designing and Implementing a Subnetted IPv4 Addressing Scheme



Lab - Designing and Implementing a Subnetted IPv4 Addressing Scheme

Topology






Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
R1	G0/0			N/A
	G0/1			N/A
	Lo0			N/A
	Lo1			N/A
S1	VLAN 1	N/A	N/A	N/A
PC-A	NIC			
PC-B	NIC			

Benefits of Variable Length Subnet Masking


Traditional Subnetting Wastes Addresses




Benefits of Variable Length Subnet Masking

Variable Length Subnet Masks (VLSM)

Traditional



Subnets of Varying Sizes



Benefits of Variable Length Subnet Masking

Basic VLSM

Basic Subnetting

	Network portion	Host portion	Dotted Decimal	
	11000000.10101000.00010100	.00000000	192.168.20.0/24	
0	11000000.10101000.00010100	.000	00000	192.168.20.0/27
1	11000000.10101000.00010100	.001	00000	192.168.20.32/27
2	11000000.10101000.00010100	.010	00000	192.168.20.64/27
3	11000000.10101000.00010100	.011	00000	192.168.20.96/27
4	11000000.10101000.00010100	.100	00000	192.168.20.128/27
5	11000000.10101000.00010100	.101	00000	192.168.20.160/27
6	11000000.10101000.00010100	.110	00000	192.168.20.192/27
7	11000000.10101000.00010100	.111	00000	192.168.20.224/27

LANs
A, B, C, D

Unused /
Available

Subnet 7 will be subnetted further.

	Network portion	Host portion	Dotted Decimal	
7	11000000.10101000.00010100	.111	00000	192.168.20.224/27
3 more bits borrowed from subnet 7				
7:0	11000000.10101000.00010100	.111000	00	192.168.20.224/30
7:1	11000000.10101000.00010100	.111001	00	192.168.20.228/30
7:2	11000000.10101000.00010100	.111010	00	192.168.20.232/30
7:3	11000000.10101000.00010100	.111011	00	192.168.20.236/30
7:4	11000000.10101000.00010100	.111100	00	192.168.20.240/30
7:5	11000000.10101000.00010100	.111101	00	192.168.20.244/30
7:6	11000000.10101000.00010100	.111110	00	192.168.20.248/30
7:7	11000000.10101000.00010100	.111111	00	192.168.20.252/30

Subnetting a subnet

WANs

Unused /
Available




Benefits of Variable Length Subnet Masking

Video Demonstration – VLSM Basics


▪ Basic VLSM

- Subnets do not have to be equal sizes, as long as their address ranges do not overlap.
- When creating subnets it is easier to work from larger to smaller.



Benefits of Variable Length Subnet Masking

VLSM in Practice



Benefits of Variable Length Subnet Masking

VLSM Chart

VLSM Subnetting of 192.168.20.0/24		
	/27 Network	Hosts
Bldg A	.0	.1 - .30
Bldg B	.32	.33 - .62
Bldg C	.64	.65 - .94
Bldg D	.96	.97 - .126
Unused	.128	.129 - .158
Unused	.160	.161 - .190
Unused	.192	.193 - .222
	.224	.225 - .254

	/30 Network	Hosts
WAN R1-R2	.224	.225 - .226
WAN R2-R3	.228	.229 - .230
WAN R3-R4	.232	.233 - .234
Unused	.236	.237 - .238
Unused	.240	.241 - .242
Unused	.244	.245 - .246
Unused	.248	.249 - .250
Unused	.252	.253 - .254

Video Demonstration – VLSM Example

- Given the network 172.16.0.0
/23 creates subnets:
 - 1 network for 200 hosts - 256
 - 1 network for 100 hosts - 128
 - 1 network for 50 hosts - 64
 - 1 network for 25 hosts - 32
 - 1 network for 10 hosts - 16
 - 4 point-to-point networks for 2 hosts each – $4 \times 4 = 16$

/23 = 2^9 hosts = 512

$256 + 128 + 64 + 32 + 16 + 16 = 512$ hosts needed

Address range 172.16.0.0 – 172.16.1.255

~~172.16.0.0 /23~~

172.16.0.0 /24 (256)

~~172.16.1.0 /24~~

172.16.1.0 /25 (128)

~~172.16.1.128 /25~~

172.16.1.128 /26 (64)

~~172.16.1.192 /26~~

172.16.1.192 /27 (32)

~~172.16.1.224 /27~~

172.16.1.224 /28 (16)

~~172.16.1.240 /28~~

172.16.1.240 /30 (4)

172.16.1.244 /30 (4)

172.16.1.248 /30 (4)

172.16.1.252 /30 (4)




8.2 Addressing Schemes




Structured Design

Network Address Planning


Planning IP Address Assignment



Student LAN



Faculty LAN



Admin LAN

Planning requires decisions on each subnet in terms of size, the number of hosts per subnet, and how host addresses will be assigned.

Planning to Address the Network



- Each host in an internetwork must have a unique address.
- Need proper planning & documentation.
- Must provide & control access to servers from internal hosts and external hosts.
- Layer 3 STATIC address assigned to a server can be used to control access to that server.
- Monitoring security and performance of hosts means network traffic is examined for source IP addresses that are generating or receiving excessive packets.


Assigning Addresses to Devices

- Devices that require addresses:
 - **End user clients**
 - Can be set for DHCP to save time and manual errors.
 - A change in the subnetting scheme requires reconfiguration of DHCP server. IPv6 clients use DHCPv6/SLAAC.
 - **Servers**
 - Configured with static addresses.
 - Private addresses translated to public addresses if accessible from the Internet.
 - **Intermediary devices**
 - Set with static addresses for remote management.
 - **Gateway**
 - Router interface used to exit the network.

Network: 192.168.1.0/24		
Use	First	Last
Host Devices	.1	.229
Servers	.230	.239
Printers	.240	.249
Intermediary Devices	.250	.253
Gateway (router LAN interface)	.254	

Structured Design

Packet Tracer – Designing and Implementing a VLSM Addressing Scheme



Cisco Networking Academy®

Mind Wide Open™

Packet Tracer - Designing and Implementing a VLSM Addressing Scheme

Topology

You will receive one of three possible topologies.

Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
	G0/0			N/A
	G0/1			N/A
	S0/0/0			N/A
	G0/0			N/A
	G0/1			N/A
	S0/0/0			N/A
	VLAN 1			
	VLAN 1			
	VLAN 1			
	VLAN 1			
	NIC			
	NIC			
	NIC			
	NIC			

Objectives

Part 1: Examine the Network Requirements

Part 2: Design the VLSM Addressing Scheme

Part 3: Assign IP Addresses to Devices and Verify Connectivity

Structured Design

Lab – Designing and Implementing a VLSM Addressing Scheme




Cisco Networking Academy®

Mind Wide Open™

Lab – Designing and Implementing a VLSM Addressing Scheme

Topology



Objectives

Part 1: Examine Network Requirements

Part 2: Design the VLSM Address Scheme

Part 3: Cable and Configure the IPv4 Network

Background / Scenario

Variable Length Subnet Mask (VLSM) was designed to avoid wasting IP addresses. With VLSM, a network is subnetted and then re-subnetted. This process can be repeated multiple times to create subnets of various sizes based on the number of hosts required in each subnet. Effective use of VLSM requires address planning.

In this lab, use the 172.16.128.0/17 network address to develop an address scheme for the network displayed in the topology diagram. VLSM is used to meet the IPv4 addressing requirements. After you have designed the VLSM address scheme, you will configure the interfaces on the routers with the appropriate IP address information.


8.3 Design Considerations for IPv6



The IPv6 Global Unicast Address

- IPv6 subnetting is not concerned with conserving address space.
- IPv6 subnetting is about building an addressing hierarchy based on the number of subnetworks needed.
- IPv6 link-local address is never subnetted.
- IPv6 global unicast address can be subnetted.
- IPv6 global unicast address normally consists of a /48 global routing prefix, a 16 bit subnet ID, and a 64 bit interface ID.


Structure



Global Routing Prefix


This is the prefix, or network, portion of the address that is assigned by the provider. Typically, Regional Internet Registries (RIRs) assign a /48 global routing prefix to ISPs and customers.

Subnetting Using the Subnet ID



Subnetting an IPv6 Network

IPv6 Subnet Allocation



Address Block: 2001:0DB8:ACAD::/48

5 subnets allocated
from 65,536
available subnets

```
2001:0DB8:ACAD:0000::/64
2001:0DB8:ACAD:0001::/64
2001:0DB8:ACAD:0002::/64
2001:0DB8:ACAD:0003::/64
2001:0DB8:ACAD:0004::/64
2001:0DB8:ACAD:0005::/64
2001:0DB8:ACAD:0006::/64
2001:0DB8:ACAD:0007::/64
2001:0DB8:ACAD:0008::/64
2001:0DB8:ACAD:FFFF::/64
```



```
R1(config)# interface gigabitethernet 0/0
R1(config-if)# ipv6 address 2001:db8:acad:1::1/64
R1(config-if)# exit
R1(config)# interface gigabitethernet 0/1
R1(config-if)# ipv6 address 2001:db8:acad:2::1/64
R1(config-if)# exit
R1(config)# interface serial 0/0/0
R1(config-if)# ipv6 address 2001:db8:acad:3::1/64
R1(config-if)# end
R1#
```


Subnetting an IPv6 Network

Packet Tracer – Implementing a Subnetted IPv6 Addressing Scheme



Packet Tracer - Implementing a Subnetted IPv6 Addressing Scheme

Topology




Addressing Table

Device	Interface	IPv6 Address	Link-Local
R1	G0/0		FE80::1
	G0/1		FE80::1
	S0/0/0		FE80::1
R2	G0/0		FE80::2
	G0/1		FE80::2
	S0/0/0		FE80::2
PC1	NIC	Auto Config	
PC2	NIC	Auto Config	

8.4 Chapter Summary



Packet Tracer - Skills Integration Challenge




Cisco Networking Academy[®]

Mind Wide Open[™]

Packet Tracer - Skills Integration Challenge

Topology



500 Hosts
PC-A1 LAN A1 Sw-A1
IPv4 Networks
250 Hosts
PC-A2 LAN A2 Sw-A2
Branch-A
172.20.16.0/23
172.20.31.252/30
DNS Server
central.pk
172.20.32.10
centralv6.pk
2001:DB8:FADE:1000::10
2001:DB8:FADE:00FF::/64
Branch-B
2001:DB8:FADE:00FF::/64
PC-B1 LAN B1 Sw-B1
IPv6 Networks
PC-B2 LAN B2 Sw-B2

Addressing Table

Device	Interface	IPv4 Address	Subnet Mask	Default Gateway
		IPv6 Address/Prefix		
Branch-A	G0/0			N/A
	G0/1			N/A
	G0/2	172.20.31.254	255.255.255.252	N/A
	G0/3			N/A

Chapter 8: Subnetting IP Networks

- Implement an IPv4 addressing scheme to enable end-to-end connectivity in a small to medium-sized business network.
- Given a set of requirements, implement a VLSM addressing scheme to provide connectivity to end users in a small to medium-sized network.
- Explain design considerations for implementing IPv6 in a business network.

New Terms and Commands

<ul style="list-style-type: none">• octet boundary• Variable Length Subnet Masking (VLSM)		
--	--	--

