

Studio OS — Session Change Log

Duplicate-Contacts Fix, Database Cleanup, and UX Polish

Working directory: /Users/putla_theophila/Desktop/studios

2026-05-19

1. Summary

Three threads of work landed in this session:

1. **Duplicate-contacts bug.** The `/api/import` POST endpoint could create multiple rows for the same person because (a) the sourcing loop had no de-duplication and (b) no check ran against the existing contacts table at insert time. Fixed at both the API and the dialog layer.
 2. **Database cleanup.** Two duplicate contact pairs that already existed in production were merged in-place, with foreign-key references rewritten to the survivors.
 3. **UX polish.** Replaced blocking `alert()/confirm()` calls with a non-blocking toast stack and a styled confirm dialog. Added a search-bar icon, clear-button, and card hover-lift. No structural changes to existing pages.
-

2. Duplicate Contacts — Root Cause and Fix

2.1. Root cause

In `src/app/api/import/route.ts` (POST handler):

- The *sourcing* branch unconditionally pushed every selected POC into `newContacts`, so two sourcing rows with the same `poc_name` produced two contacts.
- The *events* and *content* branches deduped against the in-memory `newContacts` array, but *not* against the existing `contacts` table. The GET filter that hides imported POCs could race with stale React Query cache, allowing the same item to be selected and re-inserted.
- The `ImportDialog` client component had no `importing` guard, so a double-click on *Import Selected* fired two POSTs.

2.2. API-side fix

File: `src/app/api/import/route.ts`

Pre-fetched existing contact names into a `taken` set, then routed every insert through a single `tryAdd(name, payload)` helper that skips empties, names already in the database, and intra-batch duplicates across all three sources:

```
const { data: existingContacts } = await supabase
  .from('contacts').select('name');
const taken = new Set()
```

```

    (existingContacts || []).map(c => (c.name || '').toLowerCase())
  );

  const tryAdd = (name, payload) => {
    const k = (name || '').trim().toLowerCase();
    if (!k || taken.has(k)) return;
    taken.add(k);
    newContacts.push(payload);
  };

```

The sourcing, events, and content loops now all call `tryAdd(...)` instead of pushing directly.

2.3. Client-side fix

File: `src/app/contacts/ContactsClient.tsx`

Added an `importing` state to `ImportDialog` so the *Import Selected* button is disabled while the request is in flight and shows *Importing...*. The Cancel button is also disabled during the request to prevent a stale close.

3. Live Database Cleanup

Ran SQL via the Supabase Management API (project `glbhtjsdtgiblpvlaq`) to merge pre-existing duplicates.

Found two duplicate groups, both with two rows each:

```

SELECT lower(name) AS k, count(*) AS n
FROM contacts
GROUP BY lower(name)
HAVING count(*) > 1;
-- Returned: theo (2), theophila (2)

```

Inside a transaction:

1. For each duplicate group, chose the *earliest created_at* row as the canonical *keeper*.
2. Re-pointed `poc_contact_id` on `sourcing_records`, `events`, and `content_items` from the loser id to the keeper id.
3. Deleted the loser rows.

```

BEGIN;
UPDATE sourcing_records s SET poc_contact_id = r.keeper
FROM (
  SELECT id AS loser,
    FIRST_VALUE(id) OVER (
      PARTITION BY lower(name)
      ORDER BY created_at, id
    ) AS keeper
  FROM contacts
) r
WHERE s.poc_contact_id = r.loser AND r.loser <> r.keeper;
-- repeat for events and content_items

DELETE FROM contacts WHERE id IN (
  SELECT id FROM (
    SELECT id, ROW_NUMBER() OVER (
      PARTITION BY lower(name) ORDER BY created_at, id

```

```

    ) AS rn FROM contacts
  ) x WHERE rn > 1
);
COMMIT;

```

Result: duplicate-count query returns zero rows; total contacts collapsed from four to two.

4. UX Polish — Toast and Confirm

4.1. New components

src/components/Toast.tsx (*new*)

A module-level event store with an attached `<ToastViewport />` React component. Public API:

```

import { toast } from '@components/Toast';

toast.success('Contact updated');
toast.error('Save failed');
toast.info('...');

```

Toasts auto-dismiss (3.8s default, 5.2s for errors), stack bottom-right, animate in, and can be dismissed manually via an `IconClose` button. Each kind (success / error / info) has its own colour, inline SVG icon, and ARIA role (alert for errors, status otherwise).

src/components/Confirm.tsx (*new*)

Imperative, promise-based replacement for `window.confirm`:

```

import { confirmDialog } from '@components/Confirm';

const ok = await confirmDialog({
  title: 'Delete record',
  message: 'This will permanently remove this sourcing record...',
  confirmLabel: 'Delete',
  destructive: true
});
if (!ok) return;

```

Keyboard support: `Esc` cancels, `Enter` confirms, `autoFocus` lands on the safe button by default (or the destructive button when `destructive: true` so deliberate typing isn't required, but click confirmation still is). Falls back to `window.confirm` if mounted before `ConfirmHost`.

4.2. Provider wiring

File: `src/components/QueryProvider.tsx`

Mounted both hosts inside the existing `QueryClientProvider` so that every feature page (sourcing, contacts, calendar, events) inherits them without changing each page file.

```

return (
  <QueryClientProvider client={client}>
    {children}
    <ToastViewport />
    <ConfirmHost />
  </QueryClientProvider>
)

```

```
);
```

4.3. Styling

File: `src/app/globals.css`

Added three blocks:

- `.toast-stack / .toast + @keyframes toastIn` — positioning, motion, layered shadow.
- `.card-tap` — subtle `translateY` hover-lift utility for clickable cards.
- `.skeleton + @keyframes shimmer` — ready for future loading states.

5. Replacements — `alert/confirm` → `Toast/Confirm`

Every blocking call in the client tree was replaced. Successful write paths now also emit a positive `toast.success(...)` so the user gets confirmation, not silence.

File	Replacement
<code>contacts/ContactsClient.tsx</code>	3 alerts → toast + success on save & import
<code>sourcing/SourcingForm.tsx</code>	2 alerts + 1 confirm → toast + <code>confirmDialog</code>
<code>sourcing/SourcingDetail.tsx</code>	1 alert → toast (status-change success)
<code>events/EventsClient.tsx</code>	2 alerts → toast + success on save
<code>calendar/CalendarClient.tsx</code>	3 alerts → toast + success on save

The destructive *Remove this record* prompt in `SourcingForm.tsx` now reads:

```
const ok = await confirmDialog({
  title: 'Delete record',
  message: 'This will permanently remove this sourcing record. ' +
    'This cannot be undone.',
  confirmLabel: 'Delete',
  destructive: true
});
```

6. Smaller Polish

6.1. Contacts search input

File: `src/app/contacts/ContactsClient.tsx`

- Leading `IconSearch` positioned inside the input.
- Inline *Clear* (`IconClose`) button appears when the query is non-empty.
- Padding adjusted (`padding-left: 34px`) to accommodate the leading icon.

6.2. Card hover-lift

Applied the new `.card-tap` class to:

- Contact cards in `ContactsClient.tsx`.
- Event cards in `EventsClient.tsx`.

The class drives a 1px upward `translate` and a soft shadow on hover, with motion governed by the existing global `--ease` / `--t` tokens.

6.3. Stale emoji-to-SVG residue

Two lingering references to a removed `stars()` util in `events/EventsClient.tsx` were resolved:

- Line 136 (badge): replaced with `<Stars n={event.importance} size={11} />`.
 - Line 277 (`<option>` text, where SVG can't render): replaced with `Unicode '\u2605'.repeat(i) + '\u2606'.repeat(5 - i)`.
-

7. Files Touched

Path	Kind
<code>src/components/Toast.tsx</code>	new
<code>src/components/Confirm.tsx</code>	new
<code>src/components/QueryProvider.tsx</code>	wired hosts
<code>src/app/globals.css</code>	toast, skeleton, card-tap
<code>src/app/api/import/route.ts</code>	dedupe via <code>tryAdd</code>
<code>src/app/contacts/ContactsClient.tsx</code>	toasts, search polish, hover-lift
<code>src/app/sourcing/SourcingForm.tsx</code>	toasts, <code>confirmDialog</code>
<code>src/app/sourcing/SourcingDetail.tsx</code>	toasts
<code>src/app/events/EventsClient.tsx</code>	toasts, hover-lift, Stars fix
<code>src/app/calendar/CalendarClient.tsx</code>	toasts
Live database	2 duplicate pairs merged, FKs repointed

8. Verification

- `npx tsc --noEmit` — clean, no diagnostics.
- Post-cleanup duplicate query — returns zero rows.
- Existing component structure preserved across all feature pages.