## 3D Vehicle Reconstruction via Monocular Camera with Deep Learning Models and Direct Linear Transformation

2024-2 Robot Vision (M3228.003000)

Thomas Putzer

Computer Science and Engineering Seoul National University Seoul, South Korea putzer\_thomas@snu.ac.kr Anggraini Ditha

Civil and Environmental Engineering
Seoul National University
Seoul, South Korea
email address or ORCID

Weihao Chao Mechanical Engineering Seoul National University Seoul, South Korea email address or ORCID

Abstract-Hello here goes the abstract

## I. INTRODUCTION

[1] (Leave this citation for now, otherwise it breaks (if we have 0 citations, and the command at the end))

Bla Bla Bla

## II. 3D POSE ESTIMATION

double column text here. . double column text here. . .lkasj fundingasdf
. double column text here. . lsakdfj laks ich icha heise
. double column text here. . laskdjf lasdffi cich ic ach .

lkasdjf lakjsd flkajsdl fkjasdl fjasldj flaskdjf laksjdfl kajsdflkajsdlfjasldkfjalsdkjflaskjdf laskdjf lasjkdfl aksjdflkasjd flaskjdf lkasdjf lkasjdf laksjdfl akjsdlfj asldkfj alsdjkf lasdjf laskdjf laskdjf laksdjfl aksdjfl askdjl askdjf l

moin meister laskdfj a double column text here. . . double column text here. . . double column text here. . . double

Matrix representation of the standard projection onto the z = 1 plane.

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} = \begin{bmatrix} x \\ y \\ z \\ z \end{bmatrix} \stackrel{\text{div } z}{=} \begin{bmatrix} \frac{x}{z} \\ \frac{y}{z} \\ 1 \end{bmatrix}$$
 (1)

The API projection Matrix

$$M_{API} = M_O M_P = \begin{bmatrix} \frac{2}{r-l} & 0 & 0 & \frac{-(r+l)}{r-l} \\ 0 & \frac{2}{t-b} & 0 & \frac{-(t+b)}{t-b} \\ 0 & 0 & \frac{2}{f-n} & \frac{-(f+n)}{f-n} \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} n & 0 & 0 & 0 \\ 0 & n & 0 & 0 \\ 0 & 0 & n+f & -nf \\ 0 & 0 & 1 & 0 \end{bmatrix} = \begin{bmatrix} c_1 & 0 & 0 & 0 \\ 0 & c_2 & 0 & 0 \\ 0 & 0 & c_3 & c_4 \\ 0 & 0 & 1 & 0 \end{bmatrix}$$
 (2)

To get the screen-space position of a vertex, we multiply it by its Modelview Matrix and API Projection Matrix before doing the projective division. We have all the parameters except the Model Matrix.  $p'=M_{API}M_{Modelview}p$ 

$$\begin{bmatrix} x' \\ y' \end{bmatrix} \stackrel{\text{div } z}{\equiv} \begin{bmatrix} c_1 & 0 & 0 & 0 \\ 0 & c_2 & 0 & 0 \\ 0 & 0 & c_3 & c_4 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} a & b & c & d \\ e & f & g & h \\ i & j & k & l \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

If we multiply that out, we get for x' and y'

$$x' = \frac{c_1 ax + c_1 by + c_1 cz + c_1 d}{ix + jy + kz + l}$$
$$y' = \frac{c_2 ex + c_2 fy + c_2 gz + c_2 h}{ix + jy + kz + l}$$

We can multiply by the denuminator and solve for 0. Since this holds for every pair of points  $(p_1, p'_1), (p_2, p'_2), ..., (p_n, p'_n)$  that we track we can create the following system of equation: 3

## REFERENCES

[1] J.-B. Michel, Y. K. Shen, A. P. Aiden, A. Veres, M. K. Gray, T. G. B. Team, J. P. Pickett, D. Hoiberg, D. Clancy, P. Norvig, J. Orwant, S. Pinker, M. A. Nowak, and E. L. Aiden, "Quantitative analysis of culture using millions of digitized books," *Science*, vol. 331, no. 6014, pp. 176–182, 2011. [Online]. Available: https://www.science.org/doi/abs/10.1126/science.1199644