

Rajalakshmi Engineering College

Name: Puvanesu R
Email: 241901085@rajalakshmi.edu.in
Roll no: 241901085
Phone: 6382355104
Branch: REC
Department: CSE (CS) - Section 1
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 9_PAH

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Arun is building a task manager to keep track of tasks using a LinkedList. The task manager supports the following operations:

"ADD <task>" Adds the given task to the end of the list. "REMOVE" Removes the first task from the list. "SHOW" Displays all tasks in the list in order. If the list is empty, print "EMPTY".

Help Arun implement this functionality using a LinkedList.

Input Format

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <task>"
- "REMOVE"
- "SHOW"

Output Format

For each "SHOW" command, the output prints the tasks in order, separated by spaces.

If no tasks exist, print "EMPTY".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

ADD homework

ADD project

SHOW

REMOVE

SHOW

Output: homework project

project

Answer

// You are using Java

import java.util.*;

```
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = Integer.parseInt(scanner.nextLine());
        LinkedList<String> tasks = new LinkedList<>();

        for (int i = 0; i < n; i++) {
            String command = scanner.nextLine();

            if (command.startsWith("ADD ")) {
                String task = command.substring(4);
                tasks.add(task);
            } else if (command.equals("REMOVE")) {
```

```

        if (!tasks.isEmpty()) {
            tasks.removeFirst();
        }
    } else if (command.equals("SHOW")) {
        if (tasks.isEmpty()) {
            System.out.println("EMPTY");
        } else {
            for (String task : tasks) {
                System.out.print(task + " ");
            }
            System.out.println();
        }
    }
}

```

2. Problem Statement

For each element:

4 5 (next greater element)5 102 1010 -1 (No greater element)8 -16 -1

Input Format

The first line contains an integer n, representing the number of elements.

The second line contains n space-separated integers arr[i], where arr[i] is the stock price on the i-th day.

Output Format

The output prints n space-separated integers representing the Next Greater Element for each element in the array.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6

4 5 2 10 8 6

Output: 5 10 10 -1 -1 -1

Answer

// You are using Java

import java.util.*;

```
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();
        int[] arr = new int[n];
        int[] nge = new int[n];
        Stack<Integer> stack = new Stack<>();

        for (int i = 0; i < n; i++) {
            arr[i] = scanner.nextInt();
        }

        for (int i = n - 1; i >= 0; i--) {
            while (!stack.isEmpty() && stack.peek() <= arr[i]) {
```

```

        stack.pop();
    }
    nge[i] = stack.isEmpty() ? -1 : stack.peek();
    stack.push(arr[i]);
}

for (int val : nge) {
    System.out.print(val + " ");
}
}
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Rekha is a teacher who wants to calculate the average of marks scored by her students in a test. She needs to store all the marks dynamically because the number of students may vary each time. Using an ArrayList allows her to easily add any number of marks without worrying about the initial size.

Help her implement the task.

Input Format

The first line of input is an integer n , representing the number of students..

The second line of input consists of n double values, representing the marks of each student, separated by a space.

Output Format

The output prints: "Average of the list: " followed by the average value formatted to two decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

1.0 2.0 3.0 4.0 5.0

Output: Average of the list: 3.00

Answer

```
import java.util.ArrayList;
```

```
import java.util.Scanner;
```

```
class StudentMarksAverage {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        int n = scanner.nextInt();  
        ArrayList<Double> marksList = new ArrayList<>();  
        for (int i = 0; i < n; i++) {  
            double mark = scanner.nextDouble();  
            marksList.add(mark);  
        }  
        double sum = 0.0;  
        for (double mark : marksList) {  
            sum += mark;  
        }  
        double average = sum / n;  
        if (average == (long) average) {  
            System.out.printf("Average of the list: %.2f\n", average);  
        } else {  
            System.out.printf("Average of the list: %.2f\n", average);  
        }  
        scanner.close();  
    }  
}
```

Status : Correct

Marks : 10/10