


COLLISIONREPAIR: First-Aid and Automated Patching for Storage Collision Vulnerabilities in Smart Contracts

Yu Pan^{1*}, Wanjing Han^{1*}, Yue Duan², Mu Zhang¹


¹University of Utah, Salt Lake City, United States

²Singapore Management University, Singapore

Storage Collision



Upgradable Smart Contracts



Motivating Example

```
1 contract Proxy {
2     uint64[3] fees;           // slot [0x0]
3     address[3] feeRecipients; // slot [0x1]-[0x3]
4     [...]
5     address public LOGIC;     // slot [ERC-1967]
6
7     enum FeeType {penalty, transaction, sales}
8
9     constructor() {
10         feeRecipients = [0x[..], 0x[..], 0x[..];
11         LOGIC = 0x[..];
12         LOGIC.initialize();
13     }
14     function updateFee(FeeType t, uint64 percent) {
15         fees[(uint) t] = percent;
16     }
17     fallback() external {
18         LOGIC.delegatecall(msg.data);
19     }
20 }
21
```

```
22 abstract contract Initializable {
23     bool internal initialized; // slot [0x0]
24     [...]
25 }
26
27 contract Logic is Initializable {
28     uint256[256] private __gap; // slot [0x1]-[0x100]
29     address admin;              // slot [0x101]
30     array artworkIDs;           // slot [0x102]
31     mapping artworkHolders;    // slot [0x103]
32
33     function initialize() external {
34         require(!initialized);
35         initialized = 1;
36         admin = msg.sender;
37     }
38     function withdraw() external {
39         require(msg.sender == admin);
40         payable(admin).transfer(this.balance);
41     }
42 }
```

Non-Fungible Token(NFT) Contract

Motivating Example

```
1 contract Proxy {
2     uint64[3] fees;           // slot [0x0]
3     address[3] feeRecipients; // slot [0x1]-[0x3]
4     [...]
5     address public LOGIC;     // slot [ERC-1967]
6
7     enum FeeType {penalty, transaction, sales}
8
9     constructor() {
10         feeRecipients = [0x[..], 0x[..], 0x[..]];
11         LOGIC = 0x[..];
12         LOGIC.initialize();
13     }
14     function updateFee(FeeType t, uint64 percent) {
15         fees[(uint) t] = percent;
16     }
17     fallback() external {
18         LOGIC.delegatecall(msg.data);
19     }
20 }
21
```



Stores fees and recipient info

```
22 abstract contract Initializable {
23     bool internal initialized; // slot [0x0]
24     [...]
25 }
26
27 contract Logic is Initializable {
28     uint256[256] private __gap; // slot [0x1]-[0x100]
29     address admin;              // slot [0x101]
30     array artworkIDs;           // slot [0x102]
31     mapping artworkHolders;     // slot [0x103]
32
33     function initialize() external {
34         require(!initialized);
35         initialized = 1;
36         admin = msg.sender;
37     }
38     function withdraw() external {
39         require(msg.sender == admin);
40         payable(admin).transfer(this.balance);
41     }
42 }
```

Motivating Example

```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [ERC-1967]
6
7   enum FeeType {penalty, transaction, sales}
8
9   constructor() {
10    feeRecipients = [0x[..], 0x[..], 0x[..]];
11    LOGIC = 0x[..];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15    fees[(uint) t] = percent;
16  }
17  fallback() external {
18    LOGIC.delegatecall(msg.data);
19  }
20 }
21
```

Stores fees and recipient info

```
22 abstract contract Initializable {
23   bool internal initialized; // slot [0x0]
24   [...]
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;     // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```

Processes withdrawals

State Lives in Proxy Storage

```
1 contract Proxy {  
2     uint64[3] fees;           // slot [0x0]  
3     address[3] feeRecipients; // slot [0x1]-[0x3]  
4     [..]
```

uint64[3] fees;

```
9     constructor() {  
10         feeRecipients = [0x[..], 0x[..], 0x[..]];  
11         LOGIC = 0x[..];  
12         LOGIC.initialize();  
13     }  
14     function updateFee(FeeType t, uint64 percent) {  
15         fees[(uint) t] = percent;  
16     }  
17     fallback() external {  
18         LOGIC.delegatecall(msg.data);  
19     }  
20 }  
21
```

State Lives in Proxy Storage

```
1 contract Proxy {  
2     uint64[3] fees;                // slot [0x0]  
3  
4     enum FeeType {penalty, transaction, sales}  
5  
6     constructor() {  
7         feeRecipients = [0x[..], 0x[..], 0x[..]];  
8         LOGIC = 0x[..];  
9         LOGIC.initialize();  
10    }  
11    function updateFee(FeeType t, uint64 percent) {  
12        fees[(uint) t] = percent;  
13    }  
14    fallback() external {  
15        LOGIC.delegatecall(msg.data);  
16    }  
17 }  
18  
19  
20  
21
```

`fees` is Stored in Slot 0

Reserved Storage Slots

```
22 abstract contract Initializable {
23     bool internal initialized;    // slot [0x0]
24     [..]
25 }
26
27 contract Logic is Initializable {
28     uint256[256] private __gap;
29     array artworkIDs;             // slot [0x100]
30     mapping artworkHolders;      // slot [0x103]
31
32     function initialize() external {
33         require(!initialized);
34         initialized = 1;
35         admin = msg.sender;
36     }
37     function withdraw() external {
38         require(msg.sender == admin);
39         payable(admin).transfer(this.balance);
40     }
41 }
42 }
```

Reserved Storage Slots

```
22 abstract contract Initializable {
23     bool internal initialized; // slot [0x0]
24     [..]
25 }
26
27 contract Logic is Initializable {
28     uint256[256] private __gap;
29     array artworkIDs; // slot [0x100]
30     mapping artworkHolders; // slot [0x103]
31
32     function initialize() external {
33         require(!initialized);
34         initialized = 1;
35         admin = msg.sender;
36     }
37     function withdraw() external {
38         require(msg.sender == admin);
39         payable(admin).transfer(this.balance);
40     }
41 }
42 }
```



Developers' Protection


Avoiding Storage Collision is Hard

```
contract Logic is Initializable
```

```
26
27 contract Logic is Initializable {
28     uint256[256] private __gap; // slot [0x1]-[0x100]
29
30     bool internal initialized;
31
32
33     function initialize() external {
34         require(!initialized);
35         initialized = 1;
36         admin = msg.sender;
37     }
38     function withdraw() external {
39         require(msg.sender == admin);
40         payable(admin).transfer(this.balance);
41     }
42 }
```

Avoiding Storage Collision is Hard

```
22 abstract contract Initializable {  
23     bool internal initialized; // slot [0x0]  
  
27 contract Logic is Initializable {  
28     uint256[256] private __gap; // slot [0x1]-[0x100]  
  
32  
33     function initialize() external {  
34         require(!initialized);  
35         initialized = 1;  
36         admin = msg.sender;  
37     }  
38     function withdraw() external {  
39         require(msg.sender == admin);  
40         payable(admin).transfer(this.balance);  
41     }  
42 }
```



Inherited Variable Also Occupies Slot 0!

Avoiding Storage Collision is Hard

```
22 abstract contract Initializable {
23     bool internal initialized; // slot [0x0]
24     [...]
25 }
26
27 contract Logic is Initializable {
28     uint256[256] private __gap; // slot [0x1]-[0x100]
29     address admin; // slot [0x101]
30     array artworkIDs; // slot [0x102]
```

```
    require(!initialized);
```

```
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37 }
38 function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41 }
42 }
```

Access Control Flag!

Avoiding Storage Collision is Hard


```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [ERC-1967]
6
7   enum FeeType {penalty, transaction, sales}
8
9   constructor() {
10    feeRecipients = [0x[..], 0x[..], 0x[..];
11    LOGIC = 0x[..];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15    // ...
16  }
17
18  LOGIC.delegatecall(msg.data);
19 }
20 }
21
```

`fees[(uint) t] = percent;`

```
22 abstract contract Initializable {
23   bool internal initialized; // slot [0x0]
24   [...]
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;     // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```

Avoiding Storage Collision is Hard

```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [0x4]
6
7   enum FeeType {penalty, transfer, sales}
8
9   constructor() {
10    feeRecipients = 0x[...], 0x[...], 0x[...];
11    LOGIC = 0x[...];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15    fees[t] = percent;
16  }
17  LOGIC.delegatecall(msg.data);
18  }
19 }
20 }
21 }
```


may collide 

`bool internal initialized;`

```
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;     // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```

Avoiding Storage Collision is Hard

```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [0x4]
6
7   enum FeeType {penalty, transfer, sales}
8
9   constructor() {
10    feeRecipients = 0x[...], 0x[...], 0x[...];
11    LOGIC = 0x[...];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15    fees[t] = percent;
16  }
17  LOGIC.delegatecall(msg.data);
18  }
19 }
20 }
21 }
```

may collide 

`bool internal initialized;`

```
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;     // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```

Fail to protect; Collision happens!

Static Detection Falls Short

```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [ERC-1967]
6
7   enum FeeType {penalty, transaction, sales}
8
9   constructor() {
10    feeRecipients = [0x[..], 0x[..], 0x[..];
11    LOGIC = 0x[..];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15
16    LOGIC.updateFee(t, msg.sender, percent);
17  }
18
19  }
20 }
21
```

fees[(uint) t] = percent;



Index Resolved at Runtime

```
22 abstract contract Initializable {
23   bool internal initialized; // slot [0x0]
24   [...]
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;    // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```

Static Detection Falls Short

```
1 contract Proxy {
2   uint64[3] fees;           // slot [0x0]
3   address[3] feeRecipients; // slot [0x1]-[0x3]
4   [...]
5   address public LOGIC;     // slot [ERC-1967]
6
7   enum FeeType {penalty, transaction, sales}
8
9   constructor() {
10    feeRecipients = [0x[..], 0x[..], 0x[..];
11    LOGIC = 0x[..];
12    LOGIC.initialize();
13  }
14  function updateFee(FeeType t, uint64 percent) {
15
16    LOGIC.updateFee(msg.sender,
17
18  }
19
20 }
21
```

fees[(uint) t] = percent;



Index Resolved at Runtime

```
22 abstract contract Initializable {
23   bool internal initialized; // slot [0x0]
24   [...]
25 }
26
27 contract Logic is Initializable {
28   uint256[256] private __gap; // slot [0x1]-[0x100]
29   address admin;              // slot [0x101]
30   array artworkIDs;           // slot [0x102]
31   mapping artworkHolders;    // slot [0x103]
32
33   function initialize() external {
34     require(!initialized);
35     initialized = 1;
36     admin = msg.sender;
37   }
38   function withdraw() external {
39     require(msg.sender == admin);
40     payable(admin).transfer(this.balance);
41   }
42 }
```



USCHUNT(USENIX Security '23)
CRUSH(NDSS '24)

Our Solution

COLLISIONREPAIR patches code to precisely mitigate storage collision attacks at runtime

Existing Patching Can't Solve this Problem!

Existing Patching Can't Solve this Problem!

- SmartShield(***SANER '20***)
- SGuard(***Oakland '21***)
- EVMPATCH(***USENIX Security '21***)
- ELYSIUM(***RAID '22***)
- SmartFix(***FSE '23***)

Existing Patching Can't Solve this Problem!

- SmartShield(***SANER '20***)
- SGuard(***Oakland '21***)
- EVMPATCH(***USENIX Security '21***)
- ELYSIUM(***RAID '22***)
- SmartFix(***FSE '23***)




**Single Point Detection
Cannot Maintain Storage
Access States Continuously**

Continuous and Precise Monitoring –


[illegible]

Continuous and Precise Monitoring – Solution: Ownership Changes Example



Who?


Continuous and Precise Monitoring – Solution: Ownership Changes Example



Who?

Where?

Continuous and Precise Monitoring – Solution: Ownership Changes Example



[illegible]

No collision

[illegible]

No collision

[illegible]


No collision

[illegible]


Collision!

Low-level Implementation


Insight: Mask & Shift Pattern




Load Data



Create and Apply Bitmask



Write New Data



Partial Patch Bytecode

```
... // Relocated instructions from top
1215: PUSH8 0xFFFFFFFFFFFFFFFF // Relocated instruction
1224: DUP1 // Duplicate the bitmask (0xF...F)
... // Locate the memory for 2nd arg
1231: MSTORE // Store the bitmask as 2nd arg
1232: DUP3 // Duplicate the 2^64
... // Locate the memory for 3rd arg
1239: MSTORE // Store 2^64 as 3rd arg
1240: PUSH4 0x56B10083 // Selector of ``check()`` function
... // Store the function selector
1252: AND // Relocated instruction
... // Relocated instructions
1255: SWAP1 // Relocated instruction
1256: DUP1 // Duplicate the slot number
... // Locate the memory for 1st arg
1263: MSTORE // Store slot number as 1st arg
... // Prepare for other arguments
1275: PUSH20 0xFE..1EE // The monitoring contract address
1296: GAS // The remaining gas
1297: CALL // Call the ``check()`` function
1298: SSTORE // Relocated instruction
1299: POP // Pop ``check()`` return value
... // Relocated instructions
1303: JUMP // Jump to next basic block
```


Partial Patch Bytecode

```

...                               // Relocated instructions from top
1215: PUSH8 0xFFFFFFFFFFFFFFFF // Relocated instruction
1224: DUP1                        // Duplicate the bitmask (0xF...F)
...                               // Locate the memory for 2nd arg
1231: MSTORE                      // Store the bitmask as 2nd arg
1232: DUP3                        // Duplicate the 2^64
...                               // Locate the memory for 3rd arg
1239: MSTORE                      // Store 2^64 as 3rd arg
1240: PUSH4 0x56B10083           // Selector of ``check()`` function
...                               // Store the function selector
1252: AND                        // Relocated instruction
...                               // Relocated instructions
1255: SWAP1                      // Relocated instruction
1256: DUP1                        // Duplicate the slot number
...                               // Locate the memory for 1st arg
1263: MSTORE                      // Store slot number as 1st arg
...                               // Prepare for other arguments
1275: PUSH20 0xFE..1EE           // The monitoring contract address
1296: GAS                        // The remaining gas
1297: CALL                      // Call the ``check()`` function
1298: SSTORE                     // Relocated instruction
1299: POP                       // Pop ``check()`` return value
...                               // Relocated instructions
1303: JUMP                      // Jump to next basic block

```

Prepare
arguments



Partial Patch Bytecode

```

...                               // Relocated instructions from top
1215: PUSH8 0xFFFFFFFFFFFFFFFF // Relocated instruction
1224: DUP1                        // Duplicate the bitmask (0xF...F)
...                               // Locate the memory for 2nd arg
1231: MSTORE                     // Store the bitmask as 2nd arg
1232: DUP3                       // Duplicate the 2^64
...                               // Locate the memory for 3rd arg
1239: MSTORE                     // Store 2^64 as 3rd arg
1240: PUSH4 0x56B10083          // Selector of ``check()`` function
...                               // Store the function selector
1252: AND                        // Relocated instruction
...                               // Relocated instructions
1255: SWAP1                     // Relocated instruction
1256: DUP1                      // Duplicate the slot number
...                               // Locate the memory for 1st arg
1263: MSTORE                     // Store slot number as 1st arg
...                               // Prepare for other arguments
1275: PUSH20 0xFE..1EE         // The monitoring contract address
1296: GAS                       // The remaining gas
1297: CALL                      // Call the ``check()`` function
1298: SSTORE                    // Relocated instruction
1299: POP                      // Pop ``check()`` return value
...                               // Relocated instructions
1303: JUMP                     // Jump to next basic block

```


Prepare
arguments

Send to check()



Evaluation Dataset

- Vulnerable: 12,526 vulnerable contracts from CRUSH(***NDSS '24***)
- Random: 6,018 upgradeable contracts randomly selected from Etherscan




Random Sample: Past Transactions Replayed







Vulnerable: Past Transactions Replayed




Vulnerable: Attack Transactions Replayed



Vulnerable: Safe Transactions Replayed



Runtime and Gas Overhead



Case Study

Contract	EIP	Correct Implementation	TxS		Collision Detected	Increased Code		Gas Overhead	Runtime Overhead
			Replayed	All		Proxy	Logic		
Audius Governance V1	EIP-1967	No	0	873	Y	7.2%	3.9%	-	-
Audius Governance V2	EIP-1967	Yes	340	340	N	7.2%	3.9%	22.52%	21.50%
Audius Token V1	EIP-1967	No	0	134,161	Y	7.2%	2.6%	-	-
Audius Token V2	EIP-1967	Yes	137,271	137,271	N	7.2%	3.9%	21.32%	20.10%
xToken V1	EIP-1967	No	0	142	Y	3.3%	3.4%	-	-
xToken V2	EIP-1967	Yes	16	16	N	3.3%	2.6%	18.70%	16.56%
Compound III	EIP-1967	Yes	70,312	70,312	N	4.8%	2.5%	25.60%	22.30%
DerivaDEX	EIP-2535	Yes	6,913	6,913	N	7.3%	3.0%	27.53%	24.42%

Case Study

Contract	EIP	Correct Implementation	Tx		Collision Detected	Increased Code		Gas Overhead	Runtime Overhead
			Replayed	All		Proxy	Logic		
Audius Governance V1	EIP-1967	No	0	873	Y	7.2%	3.9%	-	-
Audius Governance V2	EIP-1967	Yes	340	340	N	7.2%	3.9%	22.52%	21.50%
Audius Token V1	EIP-1967	No	0	134,161	Y	7.2%	2.6%	-	-
Audius Token V2	EIP-1967	Yes	137,271	137,271	N	7.2%	3.9%	21.32%	20.10%
xToken V1	EIP-1967	No	0	142	Y	3.3%	3.4%	-	-
xToken V2	EIP-1967	Yes	16	16	N	3.3%	2.6%	18.70%	16.56%
Compound III	EIP-1967	Yes	70,312	70,312	N	4.8%	2.5%	25.60%	22.30%
DerivaDEX	EIP-2535	Yes	6,913	6,913	N	7.3%	3.0%	27.53%	24.42%

Case Study

Contract	EIP	Correct Implementation	Tx		Collision Detected	Increased Code		Gas Overhead	Runtime Overhead
			Replayed	All		Proxy	Logic		
Audius Governance V1	EIP-1967	No	0	873	Y	7.2%	3.9%	-	-
Audius Governance V2	EIP-1967	Yes	340	340	N	7.2%	3.9%	22.52%	21.50%
Audius Token V1	EIP-1967	No	0	134,161	Y	7.2%	2.6%	-	-
Audius Token V2	EIP-1967	Yes	137,271	137,271	N	7.2%	3.9%	21.32%	20.10%
xToken V1	EIP-1967	No	0	142	Y	3.3%	3.4%	-	-
xToken V2	EIP-1967	Yes	16	16	N	3.3%	2.6%	18.70%	16.56%
Compound III	EIP-1967	Yes	70,312	70,312	N	4.8%	2.5%	25.60%	22.30%
DerivaDEX	EIP-2535	Yes	6,913	6,913	N	7.3%	3.0%	27.53%	24.42%

Conclusion

- We present **COLLISIONREPAIR**, an automated patching system for mitigating storage collision vulnerabilities.
- **COLLISIONREPAIR** defines ownership model to track storage usage.
- Evaluated on 12,526 real-world contracts, **COLLISIONREPAIR** effectively prevents storage collisions while preserving normal functionality.

Thank You!

