

International study centre

AN INTRODUCTION TO OBJECT-ORIENTATION AND THE
JAVA PROGRAMMING LANGUAGE

JAVA GUI DEVELOPMENT

❑ Name : John Alamina

❑ Email : john.alamina@hud.ac.uk

Outline

- ❖ Introduction to GUI development
- ❖ Setting up an application window
- ❖ Component Hierarchy
- ❖ JButton
- ❖ Labels and TextFields
- ❖ Basic Layouts in Java
- ❖ Event Handling
- ❖ Exception handling
- ❖ Exercises

Introduction to GUI Development

- ❖ GUI is the acronym for Graphical User Interface
- ❖ The Graphical User Interface employs a WYSIWIG approach.
- ❖ WYSIWIG-what you see is what you get
- ❖ User interact with the computer using mini graphical screens called application windows occupying regions of the computer screen
- ❖ Interactions include pointing, clicking buttons, scrolling, typing into text fields/areas etc.
- ❖ There are different GUI toolkits in Java including SWT, JavaFX and Swing.


Setting up an application window

- ❖ The java swing library is the basic java GUI library.
- ❖ Swing has a number of packages.
- ❖ We will use the following packages.
 - ❖ javax.swing;
 - ❖ java.awt;
 - ❖ java.awt.event;

```
import javax.swing.JFrame;

public class CreateWindow{

    public CreateWindow(){
        JFrame frame = new JFrame("Using JFrame");
        frame.setSize(400,300);
        frame.setResizable(true);
        frame.setVisible(true);
    }
    public static void main(String args[]){
        new CreateWindow();
    }
}
```




Any Questions?




Component Hierarchy

LAYING OUT COMPONENTS



COMPONENT INHERITANCE



Button

```
public class BasicButton{  
    public BasicButton(){  
        JFrame frame = new JFrame("Using JFrame2");  
        frame.setSize(400,300);  
        frame.setResizable(true);  
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);  
  
        //creating a button  
        JButton b=new JButton("Just a button");  
  
        //add button to frame  
        frame.getContentPane().add(b);  
  
        frame.setVisible(true);  
    }  
    public static void main(String ar[]){  
        new BasicButton();  
    }  
}
```

Any Questions?



Label and TextField

- ❖ A label and textfield can be created using the same process of creating a button
- ❖ TextField is an editable text component for entering text
- ❖ A label contains a non-editable text component.
- ❖ You can see how to work with different components in the java swing library here:
<https://docs.oracle.com/javase/tutorial/uiswing/components/componentlist.html>

Behaviours inherited from the `javax.swing.Component`

- `comp.getWidth()` and `comp.getHeight()` are functions that give the current size of the component, in pixels
- `comp.setEnabled(true)` and `comp.setEnabled(false)` can be used to enable and disable the component.
- There is a boolean-valued function, `comp.isEnabled()` that you can call to discover whether the component is enabled.
- `comp.setVisible(true)` and `comp.setVisible(false)` can be called to hide or show the component.
- `comp.setFont(font)` sets the font that is used for text displayed on the component.
- `comp.setBackground(color)` and `comp.setForeground(color)` set the background and foreground colors for the component.
- `comp.setOpaque(true)` tells the component that the area occupied by the component should be filled with the component's background color before the content of the component is painted.
- `comp.setToolTipText(string)` sets the specified string as a "tool tip" for the component
- `comp.setPreferredSize(size)` sets the size at which the component should be displayed, if possible.

Any Questions?



Basic Layouts

- ❖ There are various ways to layout components within a top-level window.
- ❖ The simplest way is by absolute positioning. The alternative is using a layout manager
- ❖ These include
 - ❖ Flow Layout
 - ❖ Border Layout
 - ❖ Grid layout
- ❖ The basic layouts can be combined together to form complex layouts.
- ❖ We can use a wireframe diagram to determine how to layout our components and what layouts can be used to achieve a specific design.

Flow and Grid Layout

- ❖ This is the default layout manager for the JPanel class
- ❖ The JPanel class is used to group components together
- ❖ The Flow layout lays out components from left to right and then top to bottom.
- ❖ The grid layout lays out components in predefined rows and columns of a grid


Border Layout

- ❖ Border Layout is the Default layout for the JFrame class
- ❖ Border layout has 5 positions
 - ❖ Top (header) NORTH position
 - ❖ Bottom (footer) SOUTH position
 - ❖ flush right EAST position
 - ❖ flush left WEST position
 - ❖ CENTER
- ❖ The default position for the border layout is CENTER

Any Questions?



Simple Calculator wireframe



Simple calculator layout

```
import javax.swing.JFrame;
import javax.swing.JPanel;
import javax.swing.JButton;
import javax.swing.JTextField;
import java.awt.BorderLayout;

public class SimpleCalc extends JFrame{

    public SimpleCalc(){

        //initialise frame
        this.initFrame();

        //create button grid
        JPanel buttons=this.createButtonGrid();

        //creating a button
        JTextField display=new JTextField("0",1

0);

        //add contents and show frame
        getContentPane().add(buttons,BorderLayo
ut.CENTER);
        getContentPane().add(display,BorderLayo
ut.NORTH);
        pack();
        setVisible(true);
    }
}
```

```
private JPanel createButtonGrid(){
    JPanel buttons=new JPanel();
    buttons.setLayout(new GridLayout(5,4));
    buttons.add(new JButton("A/C"));
    buttons.add(new JButton("C"));
    buttons.add(new JButton("M+"));
    buttons.add(new JButton("+/-"));
    buttons.add(new JButton("7"));
    buttons.add(new JButton("8"));
    buttons.add(new JButton("9"));
    buttons.add(new JButton("x"));
    buttons.add(new JButton("4"));
    buttons.add(new JButton("5"));
    buttons.add(new JButton("6"));
    buttons.add(new JButton("/"));
    buttons.add(new JButton("1"));
    buttons.add(new JButton("2"));
    buttons.add(new JButton("3"));
    buttons.add(new JButton("-"));
    buttons.add(new JButton("."));
    buttons.add(new JButton("0"));
    buttons.add(new JButton("="));
    buttons.add(new JButton("+"));
    return buttons;
}
```

Any Questions?



Exception Handling

- ❖ A mechanism of recovering or gracefully exiting from anticipated runtime errors.
- ❖ We can anticipate that in a division may include a denominator of 0, resulting in a Divide-By-Zero Exception.
- ❖ We can also anticipate that a file requested by our program to read from may not exist in the operating system file path given, resulting in a File-Not-Found exception.
- ❖ There are many of such predefined Exception defined by the Java library and we can also define our own exceptions, or use the default Exception class.
- ❖ Two ways of handling exceptions including either the throws keyword on an encapsulating method or using the try-catch-finally block.
- ❖ We can also generate predefined or user-defined exceptions using by throwing an exception using the “throw” keyword.

Divide-by-zero Exception handling example


```
private void div(double x){  
    try{  
        setVal(getVal()/x);  
    } catch(Exception e){  
        System.out.println(e.getMessage());  
    };  
}
```

Any Questions?



Event handling



- ❖ An GUI event is a user activity that the program responds to.
- ❖ These events are activated by interactions from the user on our components such as clicking a button
- ❖ An event source is a GUI component capable of generating events.
- ❖ An event listener is attached to an event source and is able to perform action based on events
- ❖ In Java swing, the Listener interface is implemented by the listener to respond to and acquire information about subscribed events




Simple Calculator events

```
void actionPerformed(ActionEvent evt){  
    String op=evt.getActionCommand();  
    display.setText(calc.calculate(op));  
}
```

Simple Calculator Design



Calculate() operation - Calculator Class



Any Questions?



A solid orange horizontal bar at the bottom of the slide.

Exercises



1. Create an exception handler for the appropriate portion of the Loan Calculator program developed in Lesson 3.
2. Create a simple Calculator application using javax.swing GUI library.
3. Create a wireframe diagram for the address book program.
4. Create a GUI for the address book program.
5. (advanced) Complete your address book program by adding the appropriate event handler methods.

Java Bootcamp challenge

- ❖ Create a GUI application for the POS system given by the following class and sequence diagram (click on image to open in browser)



Supplementary material



- ❖ [The Java Tutorial](#)
- ❖ [Java API documentation](#)
- ❖ [Link to today's Session screencast](#)
- ❖ [Link to John's Group Padlet](#)
- ❖ [Link to Kelly's Group Padlet](#)