

# Lab8- DNS, Postfix & Simple Spoofing Detection

**Instructor:** Dr. Maryam R. Aliabadi

**Lab Duration:** 1.5 hours

**Date:** Oct 31<sup>st</sup>, 2025

---

## Lab Overview

In this lab you will configure a simple local DNS (BIND9) and Postfix email server on Ubuntu, then practice identifying a spoofed email. The steps use easy commands and are suitable for introductory students.

---

## Learning Outcomes

By completing this lab, students will be able to:

1. Understand the role of email protocols and headers in cybersecurity.
  2. Configure basic email services (Postfix) on Ubuntu and test mail delivery.
  3. Examine and interpret key email headers: From:, Received:, and Authentication-Results:.
  4. Identify signs of email spoofing using SPF, DKIM, DMARC, and sender/received IP analysis.
  5. Apply simple automation to detect suspicious or potentially spoofed emails using rules derived from manual analysis.
  6. Develop basic text-processing or scripting skills in Bash or Python to parse and analyze email headers.
- 

## What You Need

- Ubuntu VM with a student account (use sudo for admin tasks)
  - Internet access for package install
  - Packages used: bind9, bind9utils, postfix, mailutils, telnet
-

## Part 1 — Configure a Local DNS Server (BIND9)

A local DNS cache helps your system resolve names faster. Follow these steps:

**Open Terminal and Install DNS packages:**

```
sudo apt update
sudo apt install -y bind9 bind9utils
```

**Edit config file:**

```
sudo nano /etc/bind/named.conf.options
```

Inside the options { } block set:

```
options {
    directory "/var/cache/bind";
    listen-on { any; };
    allow-query { any; };
    recursion yes;
};
```

**Check syntax:** `sudo named-checkconf`

**Restart service:** `sudo systemctl restart bind9`  
`sudo systemctl enable bind9`

**Allow DNS in firewall:** `sudo ufw allow 53/udp`  
`sudo ufw reload`

**Test DNS:** `dig @localhost example.com +trace`

---

## Part 2 — Configure a Local Email Server (Postfix)

Create a simple local mail system to send and receive messages on your Ubuntu VM.

**Install Postfix and mail tools:** `sudo apt install -y postfix mailutils`  
(When asked: choose 'Local only'; set system mail name to 'testserv')

**Edit Postfix settings:** `sudo postconf -e "inet_interfaces = all"`  
`sudo postconf -e "myhostname = testserv"`

**Create mail alias:** `sudo nano /etc/aliases`

Add: `root: student`

Then: `sudo newaliases`

**Start and enable Postfix:** `sudo systemctl start postfix`  
`sudo systemctl enable postfix`

**Send a test email:** `echo "This is a test message" | mail -s "Postfix Test" student@localhost`

**Check mailbox:** `mail` # press Enter to view messages, 'q' to quit

---

## Part 3 — Detecting a Spoofed Email

You will send one normal email and one spoofed email, then check headers and logs to spot differences. Follow each step exactly.

### Step 1 — Send a normal message:

```
echo "This is a legitimate message" | mail -s "Normal Email"
student@localhost
```

#### Check mail logs:

```
sudo tail -n 20 /var/log/mail.log
```

Look for lines showing postfix/smtpd and from=<student@localhost> — this is the normal message.

### Step 2 — Send a spoofed message (using telnet): `telnet localhost 25`

Then type the following (press Enter after each line):

```
EHLO spoof
MAIL FROM:<fake@unknown.com>
RCPT TO:<student@localhost>
DATA
From: "Admin" <admin@trusted.com>
To: student@localhost
Subject: Spoof Test
```

This is a fake (spoofed) message.

```
.
QUIT
```

### Step 3 — View message headers: `sudo head -n 40 /var/mail/student`

Check the 'From:' header (claims admin@trusted.com) and compare to 'Received:' lines (shows localhost). Mismatch indicates spoofing.

**Step 4 — Check for authentication in logs:** `sudo grep "connect from"`  
`/var/log/mail.log | tail -n 10`  
`sudo grep sasl /var/log/mail.log`

If 'sasl' entries exist, the message was authenticated. Spoofed messages typically lack 'sasl' entries.

---

## Part 4 — Manual and Automated Email Analysis

You are given **10 real-looking email header snippets** provided in headers.txt. You need to identify how many of the emails are legit and how many of them are spoofed.

### Task 1 – Manual Analysis

For each header:

1. Identify **sender IP** from Received fields
  2. Check SPF, DKIM, DMARC results
  3. Compare “From” domain with the actual sending server’s domain
  4. Decide if spoofing occurred and document why
- 

### Task 2 – Automate Analysis

build a small program (Bash or Python) that reads headers.txt and flags messages as SUSPICIOUS or OK using the same simple rules you used in manual analysis.

### Simple rules (use these — they match the manual exercise)

- If **SPF** ≠ pass → suspicious.
- If **DKIM** ≠ pass → suspicious.
- If **DMARC** ≠ pass → suspicious.
- If the From: domain does not match the envelope sender (smtp.mailfrom) → suspicious (when smtp.mailfrom is present).
- If the earliest (bottom-most) Received: line shows a **local/private IP** (127.0.0.1, 10.x.x.x, 192.168.x.x, 172.16-31.x.x) while the From: domain appears external → suspicious.
- Otherwise mark OK.

*Note: these are simple, classroom rules for spotting spoofed emails. Real-world detection uses more advanced checks and deeper analysis.*

---

## Deliverable

1- **Lab Report (PDF or Word)** containing:

- Screenshots or terminal outputs showing the Postfix server configuration and test emails.
- A table demonstrating the result of Manual analysis of each email snippet (10 messages), including:
  - Sender IP from Received: headers
  - SPF/DKIM/DMARC results
  - Comparison of From: domain and actual sending server domain
  - Determination of whether spoofing occurred and rationale
  - Legit or Forged

## 2-Automation Script

- A student-written Bash or Python script that reads the headers.txt file, applies the simple spoof detection rules, and outputs a summary for each message.
- The result of running the script clearly flagging suspicious messages.

Submit your report in a zipped folder with the following name format through the Learning Hub.

***Filename: Lab8-FirstName-LastName-StdNo.PDF***

---

**Good luck!**

## Quick Commands Reference

```
sudo tail -n 200 /var/log/mail.log  
sudo grep 'connect from' /var/log/mail.log -n  
sudo head -n 200 /var/mail/student  
sudo postconf -n | egrep 'inet_interfaces|myhostname'  
dig @localhost example.com +trace
```