Databricks ML Associate

Questions 901–1000 (Tenth 100)

Practice Exam Deck

How to Use This Deck

100 new questions (Q901–Q1000), none repeated from Q1–Q900.

Each question slide has four options (A–D).

The next slide gives the correct answer and explains why the right option is right and why each wrong option is wrong.

This set emphasizes the Feature Store client migration, serving containers, UC registry migration, SQL alerting/dashboards, AutoML cloning, tuning strategies, DLT APPLY CHANGES, job task values, and notebook-scoped tracking.

Question 901

Which client replaced `FeatureStoreClient` for Unity Catalog Feature Store tables?

A. `FeatureEngineeringClient`

B. `FeatureStoreClientV2`

C. `UnityCatalogClient`

D. `FeatureClient`

Answer 901

Correct: A — `FeatureEngineeringClient` is the UC client.

Wrong:

B, C, D are not real clients.

Question 902

Which import statement is used to create a Feature Engineering client?

A. `from databricks.feature_engineering import FeatureEngineeringClient`

B. `from databricks.feature_store import FeatureStoreClient`

C. `from databricks.ml import FeatureClient`

D. `from databricks.uc import FeatureEngineeringClient`

Answer 902

Correct: A — the UC client comes from `feature_engineering`.

Wrong:

B is the legacy client.

C, D are not real imports.

Question 903

Which import statement is used for the legacy workspace Feature Store client?

A. `from databricks.feature_store import FeatureStoreClient`

B. `from databricks.feature_engineering import FeatureEngineeringClient`

C. `from databricks.ml import FeatureStoreClient`

D. `from databricks.uc import FeatureStoreClient`

Answer 903

Correct: A — the legacy client comes from `feature_store`.

Wrong:

B is the UC client.

C, D are not real imports.

Question 904

Which client should you use for account-level feature tables in Unity Catalog?

A. `FeatureEngineeringClient`

B. `FeatureStoreClient`

C. `MLflowClient`

D. `UnityCatalogClient`

Answer 904

Correct: A — UC feature tables use `FeatureEngineeringClient`.

Wrong:

B is legacy.

C is MLflow.

D is not a feature client.

Question 905

Which client method creates a feature table in Unity Catalog?

A. `fe.create_table()`

B. `fe.create()`

C. `fe.new_table()`

D. `fe.register_table()`

Answer 905

Correct: A — `create_table()` creates UC feature tables.

Wrong:

B, C, D are not the API.

Question 906

Which method computes a training set with `FeatureEngineeringClient`?

A. `fe.create_training_set()`

B. `fe.build_training_set()`

C. `fe.make_training_set()`

D. `fe.get_training_set()`

Answer 906

Correct: A — `create_training_set()` computes training sets.

Wrong:

B, C, D are not the API.

Question 907

Which method logs a feature-aware model with `FeatureEngineeringClient`?

A. `fe.log_model()`

B. `fe.save_model()`

C. `fe.register_model()`

D. `fe.store_model()`

Answer 907

Correct: A — `log_model()` logs feature-aware models.

Wrong:

B, C, D are not the API.

Question 908

Which method scores a batch DataFrame with a feature-aware model?

A. `fe.score_batch()`

B. `fe.predict_batch()`

C. `fe.run_batch()`

D. `fe.infer_batch()`

Answer 908

Correct: A — `score_batch()` performs batch scoring.

Wrong:

B, C, D are not the API.

Question 909

What does a Feature Engineering client's `get_table()` return?

A. A feature table object

B. A model

C. A cluster

D. A notebook

Answer 909

Correct: A — `get_table()` returns the table object.

Wrong:

B, C, D are unrelated.

Question 910

What does a feature table object's `description` attribute contain?

A. The table's metadata description

B. The model weights

C. The training data

D. The cluster settings

Answer 910

Correct: A — `description` holds metadata.

Wrong:

B, C, D are unrelated.

Question 911

What is an MLflow model serving container image?

A. A container image that serves a logged MLflow model
B. A model artifact
C. A feature table
D. A cluster

Answer 911

Correct: A — serving images serve MLflow models.

Wrong:

B, C, D are unrelated.

Question 912

Which tool builds an MLflow model serving image?

A. `mlflow models build-docker`

B. `mlflow build`

C. `mlflow image`

D. `mlflow docker`

Answer 912

Correct: A — `build-docker` builds serving images.

Wrong:

B, C, D are not the CLI command.

Question 913

What does an MLflow model serving container expose?

A. An HTTP endpoint for predictions

B. A model registry

C. A feature store

D. A notebook

Answer 913

Correct: A — serving images expose HTTP prediction endpoints.

Wrong:

B, C, D are unrelated.

Question 914

What is the purpose of `mlflow models serve`?

A. It serves a model locally for testing

B. It trains a model

C. It registers a model

D. It deletes a model

Answer 914

Correct: A — `serve` runs a local endpoint.

Wrong:

B, C, D are unrelated.

Question 915

Which endpoint does the MLflow model server expose by default?

A. `/invocations`

B. `/predict`

C. `/score`

D. `/infer`

Answer 915

Correct: A — `/invocations` is the default endpoint.

Wrong:

B, C, D are not the default.

Question 916

Why migrate from the workspace model registry to Unity Catalog?

A. To gain governance, lineage, and cross-workspace access

B. To train faster

C. To serve faster

D. To store more features

Answer 916

Correct: A — UC adds governance and lineage.

Wrong:

B, C, D are false.

Question 917

Which tool migrates registered models to Unity Catalog?

A. The Databricks model registry migration notebook
B. A notebook widget
C. A SQL warehouse
D. A cluster

Answer 917

Correct: A — the migration notebook handles it.

Wrong:

B, C, D are unrelated.

Question 918

What is a Databricks SQL alert?

A. A condition-triggered notification on query results

B. A model metric

C. A feature table

D. A cluster

Answer 918

Correct: A — alerts notify on query results.

Wrong:

B, C, D are unrelated.

Question 919

What is a Databricks SQL dashboard?

A. A collection of query visualizations

B. A model artifact

C. A cluster

D. A feature table

Answer 919

Correct: A — dashboards visualize query results.

Wrong:

B, C, D are unrelated.

Question 920

What is a SQL query parameter in Databricks SQL?

A. A placeholder for runtime values

B. A model metric

C. A cluster

D. A feature table

Answer 920

Correct: A — SQL parameters pass runtime values.

Wrong:

B, C, D are unrelated.

Question 921

What does a SQL warehouse's auto-stop setting do?

A. Stops the warehouse after an idle period

B. Stops a running model

C. Stops a feature table

D. Stops a cluster policy

Answer 921

Correct: A — auto-stop idles warehouses down.

Wrong:

B, C, D are unrelated.

Question 922

What is AutoML experiment cloning?

A. Copying an AutoML experiment to reproduce or modify it
B. Training a new model
C. Serving a model
D. Registering a model

Answer 922

Correct: A — cloning reproduces experiments.

Wrong:

B, C, D are unrelated.

Question 923

What is the main advantage of `TrainValidationSplit` over `CrossValidator`?

A. Fewer models trained, saving compute

B. Higher accuracy

C. More folds

D. Fewer hyperparameters

Answer 923

Correct: A — a single split trains fewer models.

Wrong:

B, C, D are false.

Question 924

What does `TrainValidationSplit.setTrainRatio(0.8)` mean?

A. 80% training, 20% validation

B. 80% validation, 20% training

C. 80% test, 20% training

D. 80% train, 20% dropped

Answer 924

Correct: A — 80% training, 20% validation.

Wrong:

B, C, D misread the ratio.

Question 925

What is a DLT `APPLY CHANGES` target used for?

A. Applying CDC changes into a target table

B. Training a model

C. Serving a model

D. Registering a model

Answer 925

Correct: A — `APPLY CHANGES` handles CDC.

Wrong:

B, C, D are unrelated.

Question 926

What does `APPLY CHANGES INTO` handle in DLT?

A. Upserts and deletes from a change feed

B. Training

C. Serving

D. Registration

Answer 926

Correct: A — it applies upserts/deletes.

Wrong:

B, C, D are unrelated.

Question 927

What is a job task value in Databricks?

A. A value returned from a task for downstream tasks

B. A model metric

C. A feature table

D. A cluster

Answer 927

Correct: A — task values pass data between tasks.

Wrong:

B, C, D are unrelated.

Question 928

Which API reads a task value from a downstream task?

A. `dbutils.jobs.taskValues.get()`

B. `dbutils.widgets.get()`

C. `dbutils.jobs.get()`

D. `dbutils.values.get()`

Answer 928

Correct: A — task values are read via `taskValues`.

Wrong:

B reads widgets.

C, D are not APIs.

Question 929

Which API sets a task value from a task?

A. `dbutils.jobs.taskValues.set()`

B. `dbutils.widgets.set()`

C. `dbutils.values.set()`

D. `dbutils.jobs.set()`

Answer 929

Correct: A — `taskValues.set()` sets task values.

Wrong:

B sets widgets.

C, D are not APIs.

Question 930

What is notebook-scoped MLflow tracking?

A. Tracking runs from within a notebook session
B. Tracking a cluster
C. Tracking a feature table
D. Tracking a notebook widget

Answer 930

Correct: A — notebook-scoped tracking logs from a session.

Wrong:

B, C, D are unrelated.

Question 931

Which MLflow function starts a run in a notebook?

A. `mlflow.start_run()`

B. `mlflow.begin()`

C. `mlflow.open()`

D. `mlflow.init()`

Answer 931

Correct: A — `start_run()` opens a run.

Wrong:

B, C, D are not the API.

Question 932

Which MLflow function ends a run?

A. `mlflow.end_run()`

B. `mlflow.close()`

C. `mlflow.stop()`

D. `mlflow.finish()`

Answer 932

Correct: A — `end_run()` closes a run.

Wrong:

B, C, D are not the API.

Question 933

What does the MLflow tracking UI show for a run?

A. Params, metrics, artifacts, and source
B. Only metrics
C. Only params
D. Only artifacts

Answer 933

Correct: A — the UI shows all run metadata.

Wrong:

B, C, D are incomplete.

Question 934

Which MLflow API returns a run's details?

A. `mlflow.get_run()`

B. `mlflow.run_info()`

C. `mlflow.details()`

D. `mlflow.info()`

Answer 934

Correct: A — `get_run()` returns run details.

Wrong:

B, C, D are not the API.

Question 935

Which MLflow API returns an experiment's details?

A. `mlflow.get_experiment()`

B. `mlflow.experiment_info()`

C. `mlflow.exp()`

D. `mlflow.info_exp()`

Answer 935

Correct: A — `get_experiment()` returns details.

Wrong:

B, C, D are not the API.

Question 936

Which MLflow API lists experiments?

A. `mlflow.search_experiments()`

B. `mlflow.list_experiments()`

C. `mlflow.experiments()`

D. `mlflow.all_experiments()`

Answer 936

Correct: A — `search_experiments()` lists experiments.

Wrong:

B, C, D are not the API.

Question 937

What is a model's input example stored for?

A. Documenting expected serving inputs
B. Training a model
C. Registering a model
D. Deleting a model

Answer 937

Correct: A — input examples document serving inputs.

Wrong:

B, C, D are unrelated.

Question 938

Which API logs a model with an input example?

A. `mlflow.log_model(..., input_example=...)`

B. `mlflow.log_param()`

C. `mlflow.log_metric()`

D. `mlflow.set_tag()`

Answer 938

Correct: A — `input_example` is a `log_model` argument.

Wrong:

B, C, D log other things.

Question 939

What is a model's signature inferred from?

A. Sample input and output data

B. Model weights

C. Cluster size

D. Feature table

Answer 939

Correct: A — signatures infer from samples.

Wrong:

B, C, D are unrelated.

Question 940

What is a model's alias used for in serving?

A. Pointing an endpoint to a version
B. Training a model
C. Registering a model
D. Deleting a model

Answer 940

Correct: A — aliases point endpoints to versions.

Wrong:

B, C, D are unrelated.

Question 941

What is a model's version number?

A. An integer identifying a specific version

B. A metric

C. A cluster setting

D. A feature table

Answer 941

Correct: A — versions are numbered sequentially.

Wrong:

B, C, D are unrelated.

Question 942

What is a model version's status in Unity Catalog?

A. A readiness state such as pending registration or ready

B. A metric

C. A cluster setting

D. A feature table

Answer 942

Correct: A — status reflects registration state.

Wrong:

B, C, D are unrelated.

Question 943

Which status means a version is not yet ready to serve?

A. `PENDING_REGISTRATION`

B. `READY`

C. `ONLINE`

D. `ACTIVE`

Answer 943

Correct: A — pending registration is not ready.

Wrong:

B is ready.

C, D are not statuses.

Question 944

What does a model version's `READY` status mean?

A. The version can be used for serving

B. The version is being trained

C. The version is deleted

D. The version is a draft

Answer 944

Correct: A — READY means the version is usable.

Wrong:

B, C, D are false.

Question 945

What is an MLflow experiment's default artifact location?

A. A workspace-configured storage path
B. A local disk
C. A model registry
D. A feature table

Answer 945

Correct: A — artifact locations are configured by the workspace.

Wrong:

B, C, D are not the default.

Question 946

What is a Databricks SQL warehouse's serverless behavior?

A. Quick startup without cluster management

B. Manual cluster setup

C. Only local storage

D. No SQL support

Answer 946

Correct: A — serverless SQL starts quickly.

Wrong:

B, C, D are false.

Question 947

What is a SQL dashboard's schedule?

A. How often the dashboard refreshes

B. How often the model retrains

C. How often clusters restart

D. How often features update

Answer 947

Correct: A — schedules control dashboard refresh.

Wrong:

B, C, D are unrelated.

Question 948

What is a SQL alert's destination?

A. Where notifications are sent

B. The model registry

C. The feature store

D. The cluster

Answer 948

Correct: A — destinations receive alerts.

Wrong:

B, C, D are unrelated.

Question 949

What is a SQL query's run-as user?

A. The user whose permissions run the query
B. The model owner
C. The cluster owner
D. The feature owner

Answer 949

Correct: A — run-as determines query permissions.

Wrong:

B, C, D are unrelated.

Question 950

What is a DLT pipeline's cluster configuration?

A. The compute settings for running the pipeline
B. The model type
C. The feature table
D. The notebook

Answer 950

Correct: A — cluster settings control compute.

Wrong:

B, C, D are unrelated.

Question 951

What is a DLT pipeline's development mode?

A. A faster iteration mode with reduced resources
B. A production mode
C. A training mode
D. A serving mode

Answer 951

Correct: A — development mode speeds iteration.

Wrong:

B, C, D are false.

Question 952

What is a DLT pipeline's trigger interval?

A. How often a triggered pipeline runs
B. How often the model trains
C. How often the cluster restarts
D. How often features update

Answer 952

Correct: A — trigger intervals control pipeline runs.

Wrong:

B, C, D are unrelated.

Question 953

What is a DLT pipeline's target schema?

A. Where tables are created

B. Where models are registered

C. Where features are stored

D. Where clusters run

Answer 953

Correct: A — target schemas hold DLT tables.

Wrong:

B, C, D are unrelated.

Question 954

What is a DLT expectation's name used for?

A. Reporting data quality metrics

B. Training a model

C. Serving a model

D. Registering a model

Answer 954

Correct: A — names label quality metrics.

Wrong:

B, C, D are unrelated.

Question 955

What is a DLT pipeline's event log used for?

A. Debugging and monitoring pipeline runs
B. Training a model
C. Serving a model
D. Registering a model

Answer 955

Correct: A — event logs support debugging.

Wrong:

B, C, D are unrelated.

Question 956

What is a SQL dashboard's parameter?

A. A runtime value used in dashboard queries

B. A model metric

C. A cluster setting

D. A feature table

Answer 956

Correct: A — dashboard parameters pass values.

Wrong:

B, C, D are unrelated.

Question 957

What is a SQL dashboard's schedule owner?

A. The user responsible for the schedule

B. The model owner

C. The cluster owner

D. The feature owner

Answer 957

Correct: A — schedule owners manage refresh.

Wrong:

B, C, D are unrelated.

Question 958

What is a SQL query's cache?

A. Reuse of results for repeated queries

B. A model artifact

C. A cluster

D. A feature table

Answer 958

Correct: A — caches reuse query results.

Wrong:

B, C, D are unrelated.

Question 959

What is a SQL query's schedule in Databricks SQL?

A. Periodic refresh of a query or dashboard

B. Model retraining

C. Cluster restart

D. Feature updates

Answer 959

Correct: A — schedules refresh queries/dashboards.

Wrong:

B, C, D are unrelated.

Question 960

What is a SQL alert's condition?

A. A predicate that triggers the alert

B. A model metric

C. A feature table

D. A cluster

Answer 960

Correct: A — conditions define alert triggers.

Wrong:

B, C, D are unrelated.

Question 961

What is a SQL dashboard's embed token?

A. A token that allows embedding the dashboard externally

B. A model metric

C. A feature table

D. A cluster

Answer 961

Correct: A — embed tokens enable external embedding.

Wrong:

B, C, D are unrelated.

Question 962

What is a SQL query's parameter marker syntax?

A. `:param_name`

B. {`param_name`}

C. `$param_name`

D. `@param_name`

Answer 962

Correct: A — markers use `:name` syntax.

Wrong:

B, C, D are not the Databricks SQL syntax.

Question 963

What is a SQL query's warehouse?

A. The compute used to run the query

B. A model artifact

C. A feature table

D. A cluster policy

Answer 963

Correct: A — warehouses run SQL queries.

Wrong:

B, C, D are unrelated.

Question 964

What is the main benefit of a Databricks SQL warehouse over an all-purpose cluster for BI?

A. Optimized for SQL and BI workloads

B. Supports Spark ML

C. Supports Python

D. Supports streaming

Answer 964

Correct: A — SQL warehouses are BI-optimized.

Wrong:

B, C, D are not supported in SQL warehouses.

Question 965

What is a SQL warehouse's size?

A. Its compute capacity

B. Its storage capacity

C. Its model size

D. Its feature count

Answer 965

Correct: A — size controls SQL compute.

Wrong:

B, C, D are unrelated.

Question 966

What is a SQL warehouse's multi-cluster setting?

A. Whether the warehouse scales to multiple clusters
B. Whether it supports ML
C. Whether it supports streaming
D. Whether it supports notebooks

Answer 966

Correct: A — multi-cluster enables scaling.

Wrong:

B, C, D are false.

Question 967

What is a model alias change logged as?

A. A registry activity event

B. A training metric

C. A feature table

D. A notebook

Answer 967

Correct: A — alias changes are registry activity.

Wrong:

B, C, D are unrelated.

Question 968

What is a model version's owner used for?

A. Accountability for the version

B. Training a model

C. Serving a model

D. Registering a model

Answer 968

Correct: A — owners are accountable.

Wrong:

B, C, D are unrelated.

Question 969

What is a model version's run link used for?

A. Traceability to the originating run

B. Training a model

C. Serving a model

D. Registering a model

Answer 969

Correct: A — run links provide traceability.

Wrong:

B, C, D are unrelated.

Question 970

What is a model version's signature used for?

A. Validating input/output schemas

B. Training a model

C. Serving a model

D. Registering a model

Answer 970

Correct: A — signatures validate schemas.

Wrong:

B, C, D are unrelated.

Question 971

What is a model version's input example used for?

A. Documenting expected input format
B. Training a model
C. Serving a model
D. Registering a model

Answer 971

Correct: A — input examples document input format.

Wrong:

B, C, D are unrelated.

Question 972

What is a model version's description used for?

A. Recording human-readable notes

B. Training a model

C. Serving a model

D. Registering a model

Answer 972

Correct: A — descriptions hold notes.

Wrong:

B, C, D are unrelated.

Question 973

What is a model version's tag used for?

A. Key-value metadata
B. Training a model
C. Serving a model
D. Registering a model

Answer 973

Correct: A — tags attach metadata.

Wrong:

B, C, D are unrelated.

Question 974

What is a model version's alias used for?

A. Referencing a version by name

B. Training a model

C. Serving a model

D. Registering a model

Answer 974

Correct: A — aliases reference versions.

Wrong:

B, C, D are unrelated.

Question 975

What is a model version's stage used for in the workspace registry?

A. Indicating lifecycle state

B. Training a model

C. Serving a model

D. Registering a model

Answer 975

Correct: A — stages indicate lifecycle.

Wrong:

B, C, D are unrelated.

Question 976

Which API sets a model version's stage in the workspace registry?

A. `mlflow.transition_model_version_stage()`

B. `mlflow.set_stage()`

C. `mlflow.move_version()`

D. `mlflow.change_stage()`

Answer 976

Correct: A — that API transitions stages.

Wrong:

B, C, D are not the API.

Question 977

Which API sets a model version's alias in Unity Catalog?

A. `mlflow.set_registered_model_alias()`

B. `mlflow.set_alias()`

C. `mlflow.add_alias()`

D. `mlflow.create_alias()`

Answer 977

Correct: A — that API sets aliases.

Wrong:

B, C, D are not the API.

Question 978

Which API deletes a model version's alias?

A. `mlflow.delete_registered_model_alias()`

B. `mlflow.remove_alias()`

C. `mlflow.drop_alias()`

D. `mlflow.remove_alias_model()`

Answer 978

Correct: A — that API deletes aliases.

Wrong:

B, C, D are not the API.

Question 979

Which API lists a model's aliases?

A. `mlflow.get_model_version_aliases()`

B. `mlflow.list_aliases()`

C. `mlflow.aliases()`

D. `mlflow.model_aliases()`

Answer 979

Correct: A — that API lists aliases.

Wrong:

B, C, D are not the API.

Question 980

Which API searches model versions?

A. `mlflow.search_model_versions()`

B. `mlflow.list_versions()`

C. `mlflow.find_versions()`

D. `mlflow.query_versions()`

Answer 980

Correct: A — that API searches versions.

Wrong:

B, C, D are not the API.

Question 981

What is the purpose of an MLflow run's source?

A. Identifying the notebook or file that started the run
B. Training a model
C. Serving a model
D. Registering a model

Answer 981

Correct: A — source identifies the run origin.

Wrong:

B, C, D are unrelated.

Question 982

What is the purpose of an MLflow run's user?

A. Identifying who started the run
B. Training a model
C. Serving a model
D. Registering a model

Answer 982

Correct: A — user identifies the initiator.

Wrong:

B, C, D are unrelated.

Question 983

What is the purpose of an MLflow run's start time?

A. Recording when the run began
B. Training a model
C. Serving a model
D. Registering a model

Answer 983

Correct: A — start time records run start.

Wrong:

B, C, D are unrelated.

Question 984

What is the purpose of an MLflow run's end time?

A. Recording when the run ended

B. Training a model

C. Serving a model

D. Registering a model

Answer 984

Correct: A — end time records run end.

Wrong:

B, C, D are unrelated.

Question 985

What is a run's lifecycle stage in MLflow?

A. Active or deleted

B. Training or serving

C. Online or offline

D. Public or private

Answer 985

Correct: A — lifecycle stages are active/deleted.

Wrong:

B, C, D are not lifecycle stages.

Question 986

What is an experiment's lifecycle stage in MLflow?

A. Active or deleted

B. Training or serving

C. Online or offline

D. Public or private

Answer 986

Correct: A — lifecycle stages are active/deleted.

Wrong:

B, C, D are not lifecycle stages.

Question 987

What is the purpose of a model's signature in MLflow?

A. Defining input/output schema
B. Training a model
C. Serving a model
D. Registering a model

Answer 987

Correct: A — signatures define schemas.

Wrong:

B, C, D are unrelated.

Question 988

What is the purpose of an MLflow model's `MLmodel` file?

A. Defining the model's flavor and dependencies

B. Training a model

C. Serving a model

D. Registering a model

Answer 988

Correct: A — `MLmodel` defines flavor/deps.

Wrong:

B, C, D are unrelated.

Question 989

What is the purpose of an MLflow model's `conda.yaml`?

A. Defining the model's dependencies

B. Training a model

C. Serving a model

D. Registering a model

Answer 989

Correct: A — `conda.yaml` lists dependencies.

Wrong:

B, C, D are unrelated.

Question 990

What is the purpose of an MLflow model's `requirements.txt`?

A. Listing Python package requirements

B. Training a model

C. Serving a model

D. Registering a model

Answer 990

Correct: A — it lists Python dependencies.

Wrong:

B, C, D are unrelated.

Question 991

What is an MLflow model's `input_example` stored as?

A. An artifact used at serving for validation

B. A metric

C. A cluster setting

D. A feature table

Answer 991

Correct: A — input examples are artifacts.

Wrong:

B, C, D are unrelated.

Question 992

What does `mlflow.models.get_model_dependencies()` return?

A. A model's dependencies

B. A model's weights

C. A model's metrics

D. A model's tags

Answer 992

Correct: A — it returns dependencies.

Wrong:

B, C, D are not returned.

Question 993

What is the purpose of an MLflow run's parent run ID?

A. Identifying the parent of a nested run
B. Training a model
C. Serving a model
D. Registering a model

Answer 993

Correct: A — parent run IDs link nested runs.

Wrong:

B, C, D are unrelated.

Question 994

What is the purpose of an MLflow run's experiment ID?

A. Identifying the experiment the run belongs to
B. Training a model
C. Serving a model
D. Registering a model

Answer 994

Correct: A — experiment IDs link runs to experiments.

Wrong:

B, C, D are unrelated.

Question 995

What is the purpose of an MLflow run's artifact URI?

A. Locating the run's artifacts
B. Training a model
C. Serving a model
D. Registering a model

Answer 995

Correct: A — artifact URIs locate files.

Wrong:

B, C, D are unrelated.

Question 996

What is the purpose of an MLflow run's status?

A. Indicating whether it succeeded or failed
B. Training a model
C. Serving a model
D. Registering a model

Answer 996

Correct: A — status indicates success/failure.

Wrong:

B, C, D are unrelated.

Question 997

What is the purpose of an MLflow run's params?

A. Recording run inputs

B. Recording run metrics

C. Recording run artifacts

D. Recording run tags

Answer 997

Correct: A — params are run inputs.

Wrong:

B, C, D are other data.

Question 998

What is the purpose of an MLflow run's metrics?

A. Recording run outputs

B. Recording run inputs

C. Recording run artifacts

D. Recording run tags

Answer 998

Correct: A — metrics are run outputs.

Wrong:

B, C, D are other data.

Question 999

What is the purpose of an MLflow run's tags?

A. Recording metadata about the run

B. Recording run inputs

C. Recording run outputs

D. Recording run artifacts

Answer 999

Correct: A — tags store metadata.

Wrong:

B, C, D are other data.

Question 1000

What is the best practice for organizing MLflow runs?

A. Use experiments per project and tags for run metadata
B. Use one experiment for everything
C. Use no experiments
D. Use one run for everything

Answer 1000

Correct: A — organize by experiment and tag.

Wrong:

B, C, D are poor practices.