Databricks ML Associate

Questions 201–300 (Third 100)

Practice Exam Deck

How to Use This Deck

100 new questions (Q201–Q300), none repeated from the first two sets.

Each question slide has four options (A–D).

The next slide gives the correct answer and explains why the right option is right and why each wrong option is wrong.

Question 201

Which method updates the description of an existing Feature Store table?

A. `fe.update_table()`

B. `fe.set_description()`

C. `fe.write_table()`

D. `fe.create_table()`

Answer 201

Correct: A — `update_table()` updates table metadata.

Wrong:

B is not the API.

C writes features.

D creates a table.

Question 202

Which method deletes a feature table?

A. `fe.drop_table()`

B. `fe.delete_table()`

C. `fe.remove_table()`

D. `fe.write_table()`

Answer 202

Correct: A — `drop_table()` deletes a feature table.

Wrong:

B, C are not the API.

D writes features.

Question 203

What happens if two feature table rows share the same primary key without a timestamp key?

A. The table cannot be used for point-in-time lookups

B. It trains faster

C. It improves accuracy

D. It creates a new feature table

Answer 203

Correct: A — point-in-time lookups require a timestamp key.

Wrong:

B, C are false.

D does not happen.

Question 204

Which is a valid reason to use a Feature Store over raw Delta tables?

A. Automated point-in-time joins and feature lineage

B. Faster cluster startup

C. Automatic model deployment

D. Free storage

Answer 204

Correct: A — Feature Store provides point-in-time joins and lineage.

Wrong:

B is compute.

C is deployment.

D is billing.

Question 205

What does `fs.get_table()` return?

A. A FeatureStoreTable object

B. A Spark DataFrame

C. A pandas DataFrame

D. A model

Answer 205

Correct: A — it returns a FeatureStoreTable object.

Wrong:

B you call `.load_df()` for a DataFrame.

C is pandas.

D is a model.

Question 206

Which MLflow component stores model files?

A. The artifact store
B. The backend store
C. The tracking server
D. The model registry

Answer 206

Correct: A — model files are artifacts.

Wrong:

B stores metadata.

C coordinates tracking.

D manages versions.

Question 207

What does `mlflow.log_dict()` do?

A. Logs a dictionary as a JSON artifact

B. Logs a parameter

C. Logs a metric

D. Logs a tag

Answer 207

Correct: A — `log_dict()` stores a JSON artifact.

Wrong:

B is `log_param`.

C is `log_metric`.

D is `set_tag`.

Question 208

What is an MLflow run?

A. A single execution of training code

B. A cluster

C. A feature table

D. An experiment

Answer 208

Correct: A — a run is one execution.

Wrong:

B is compute.

C is data.

D groups runs.

Question 209

What is an MLflow experiment?

A. A collection of related runs

B. A single run

C. A model

D. A cluster

Answer 209

Correct: A — experiments group related runs.

Wrong:

B is a run.

C is a model.

D is compute.

Question 210

How can you compare runs visually in MLflow?

A. Use the experiment UI to compare metrics and parameters

B. Open a notebook

C. Use a SQL warehouse

D. Use a cluster log

Answer 210

Correct: A — the experiment UI compares runs.

Wrong:

B, C, D do not compare runs.

Question 211

Which MLflow API loads a model from a registry URI?

A. `mlflow.pyfunc.load_model()`

B. `mlflow.load_model()`

C. `mlflow.get_model()`

D. `mlflow.fetch_model()`

Answer 211

Correct: A — `pyfunc.load_model()` loads a registry model.

Wrong:

B, C, D are not the loading API.

Question 212

What is MLflow autologging?

A. Automatic logging of params, metrics, and models
B. Automatic model deployment
C. Automatic data cleaning
D. Automatic cluster creation

Answer 212

Correct: A — autologging logs run data automatically.

Wrong:

B is deployment.

C is data prep.

D is compute.

Question 213

Which MLflow function enables autologging for scikit-learn?

A. `mlflow.sklearn.autolog()`

B. `mlflow.autolog_sklearn()`

C. `mlflow.enable_sklearn()`

D. `mlflow.sklearn.log()`

Answer 213

Correct: A — `sklearn.autolog()` enables autologging.

Wrong:

B, C, D are not the API.

Question 214

Which MLflow API creates a new experiment?

A. `mlflow.create_experiment()`

B. `mlflow.new_experiment()`

C. `mlflow.start_experiment()`

D. `mlflow.set_experiment()`

Answer 214

Correct: A — `create_experiment()` creates one.

Wrong:

B, C are not the API.

D sets the active experiment.

Question 215

Which MLflow API sets the active experiment?

A. `mlflow.set_experiment()`

B. `mlflow.create_experiment()`

C. `mlflow.start_experiment()`

D. `mlflow.use_experiment()`

Answer 215

Correct: A — `set_experiment()` sets the active one.

Wrong:

B creates.

C, D are not the API.

Question 216

What does AutoML generate in addition to the leaderboard?

A. A data exploration notebook

B. A cluster

C. A SQL warehouse

D. A Git repo

Answer 216

Correct: A — AutoML generates an EDA notebook.

Wrong:

B, C, D are not produced by AutoML.

Question 217

What input does AutoML require?

A. A table or DataFrame with a target column
B. A trained model
C. A cluster
D. A SQL warehouse

Answer 217

Correct: A — AutoML needs data with a target.

Wrong:

B is the output.

C is compute.

D is SQL compute.

Question 218

Which is a supported AutoML problem type?

A. Classification

B. Clustering

C. Dimensionality reduction

D. Recommendation

Answer 218

Correct: A — AutoML supports classification (and regression/forecasting).

Wrong:

B, C, D are not AutoML problem types.

Question 219

What does AutoML do with generated notebooks?

A. It lets you edit and reproduce the trials
B. It deletes them
C. It hides them
D. It converts them to SQL

Answer 219

Correct: A — generated notebooks are editable.

Wrong:

B, C, D are false.

Question 220

Which API registers an AutoML best model into the registry?

A. One-click registration in the UI or `mlflow.register_model()`

B. `automl.deploy()`

C. `automl.register()`

D. `mlflow.save()`

Answer 220

Correct: A — registration is one-click or via `register_model`.

Wrong:

B, C are not APIs.

D is not registration.

Question 221

What does `df.withColumnRenamed()` do?

A. Renames an existing column

B. Adds a column

C. Drops a column

D. Selects columns

Answer 221

Correct: A — it renames a column.

Wrong:

B is `withColumn`.

C is `drop`.

D is `select`.

Question 222

What does `df.drop()` do?

A. Drops columns

B. Drops rows

C. Drops nulls

D. Drops the DataFrame

Answer 222

Correct: A — `drop()` removes columns.

Wrong:

B is `filter`.

C is `na.drop`.

D is not a Spark operation.

Question 223

Which Spark function returns the number of rows?

A. `count()`

B. `size()`

C. `length()`

D. `numRows()`

Answer 223

Correct: A — `count()` returns row count.

Wrong:

B, C are for arrays/strings.

D is not an API.

Question 224

Which operation sorts a Spark DataFrame?

A. `orderBy()`

B. `sortBy()`

C. `arrange()`

D. `rank()`

Answer 224

Correct: A — `orderBy()` sorts rows.

Wrong:

B is Scala collections.

C is pandas.

D is a window function.

Question 225

What does `df.limit(10)` return?

A. A new DataFrame with at most 10 rows

B. The 10th row

C. A scalar

D. A column

Answer 225

Correct: A — it returns up to 10 rows.

Wrong:

B, C, D are not what it returns.

Question 226

Why is `collect()` dangerous on large DataFrames?

A. It pulls all data to the driver, risking memory overflow
B. It deletes data
C. It changes the schema
D. It drops nulls

Answer 226

Correct: A — `collect()` moves data to the driver.

Wrong:

B, C, D are false.

Question 227

Which action triggers computation on a Spark DataFrame?

A. `show()`

B. `select()`

C. `filter()`

D. `withColumn()`

Answer 227

Correct: A — `show()` is an action.

Wrong:

B, C, D are lazy transformations.

Question 228

What is lazy evaluation in Spark?

A. Transformations are not executed until an action is called
B. Data is never loaded
C. Results are cached automatically
D. Queries run immediately

Answer 228

Correct: A — Spark delays execution until an action.

Wrong:

B, C, D are false.

Question 229

What is a broadcast join?

A. A join where a small table is sent to all workers

B. A join on all columns

C. A join that drops rows

D. A join without a key

Answer 229

Correct: A — broadcast joins replicate a small table.

Wrong:

B, C, D are false.

Question 230

What is a shuffle in Spark?

A. Redistribution of data across partitions

B. A random sample

C. A cache operation

D. A schema change

Answer 230

Correct: A — shuffles redistribute data.

Wrong:

B, C, D are false.

Question 231

What is a UDF in Spark?

A. A user-defined function applied to columns

B. A built-in function

C. A DataFrame

D. A cluster

Answer 231

Correct: A — a UDF is a user-defined function.

Wrong:

B is built-in.

C is a DataFrame.

D is compute.

Question 232

Why can Python UDFs be slower than native Spark functions?

A. They require serialization between JVM and Python
B. They are always parallel
C. They use no memory
D. They are written in Scala

Answer 232

Correct: A — Python UDFs pay serialization overhead.

Wrong:

B, C, D are false.

Question 233

What is a pandas UDF?

A. A vectorized UDF that operates on pandas Series/DataFrames

B. A built-in function

C. A clustering method

D. A storage format

Answer 233

Correct: A — pandas UDFs are vectorized.

Wrong:

B, C, D are false.

Question 234

What does `applyInPandas` require?

A. A schema for the output DataFrame

B. A cluster

C. A model

D. A feature table

Answer 234

Correct: A — it requires an output schema.

Wrong:

B, C, D are not required.

Question 235

Which Spark ML evaluator is used for regression?

A. `RegressionEvaluator`
B. `BinaryClassificationEvaluator`
C. `MulticlassClassificationEvaluator`
D. `ClusteringEvaluator`

Answer 235

Correct: A — it evaluates regression.

Wrong:

B, C are classification.

D is clustering.

Question 236

Which metric can `RegressionEvaluator` compute?

A. RMSE

B. AUC

C. F1

D. Silhouette

Answer 236

Correct: A — it computes RMSE and related regression metrics.

Wrong:

B is AUC.

C is F1.

D is clustering.

Question 237

What does `setMetricName()` do on an evaluator?

A. Sets the metric to compute

B. Sets the label column

C. Sets the prediction column

D. Sets the model

Answer 237

Correct: A — it sets the metric name.

Wrong:

B is `setLabelCol`.

C is `setPredictionCol`.

D is unrelated.

Question 238

What does `setLabelCol()` do on an evaluator?

A. Sets the target column

B. Sets the metric

C. Sets the prediction column

D. Sets the model

Answer 238

Correct: A — it sets the label column.

Wrong:

B is `setMetricName`.

C is `setPredictionCol`.

D is unrelated.

Question 239

What does `setPredictionCol()` do on an evaluator?

A. Sets the column containing predictions
B. Sets the target column
C. Sets the metric
D. Sets the model

Answer 239

Correct: A — it sets the prediction column.

Wrong:

B is `setLabelCol`.

C is `setMetricName`.

D is unrelated.

Question 240

What does `CrossValidator.fit()` return?

A. A `CrossValidatorModel` with the best model
B. A DataFrame
C. A metric
D. A cluster

Answer 240

Correct: A — it returns a `CrossValidatorModel`.

Wrong:

B, C, D are not returned.

Question 241

How do you access the best model from a `CrossValidatorModel`?

A. `.bestModel`

B. `.model`

C. `.best`

D. `.getModel()`

Answer 241

Correct: A — `bestModel` holds the best model.

Wrong:

B, C, D are not the attribute.

Question 242

What does `avgMetrics` on a `CrossValidatorModel` contain?

A. The average metric for each hyperparameter combination

B. The metric for one fold

C. The best model

D. The feature importance

Answer 242

Correct: A — `avgMetrics` has per-combination scores.

Wrong:

B is one fold.

C is `bestModel`.

D is importance.

Question 243

Why is `cache()` useful before cross-validation?

A. It avoids recomputing data across folds

B. It tunes hyperparameters

C. It registers models

D. It deploys models

Answer 243

Correct: A — caching avoids recomputation across folds.

Wrong:

B, C, D are false.

Question 244

What does `ParamGridBuilder.addGrid()` do?

A. Adds a hyperparameter and its values to the grid

B. Adds a model

C. Adds a feature

D. Adds a metric

Answer 244

Correct: A — it adds a parameter grid.

Wrong:

B, C, D are false.

Question 245

What does `TrainValidationSplit.setTrainRatio(0.8)` mean?

A. 80% of data is used for training

B. 80% is used for validation

C. 80% is test

D. 80% is dropped

Answer 245

Correct: A — 80% trains, 20% validates.

Wrong:

B, C, D misread the ratio.

Question 246

What does `cvModel.bestModel` refer to when using `TrainValidationSplit`?

A. The best model from the split

B. The metric

C. The validation data

D. The training data

Answer 246

Correct: A — `bestModel` is the best model.

Wrong:

B, C, D are not models.

Question 247

Which Spark ML classifier predicts probabilities?

A. `LogisticRegression`

B. `LinearRegression`

C. `KMeans`

D. `ALS`

Answer 247

Correct: A — logistic regression predicts probabilities.

Wrong:

B is regression.

C is clustering.

D is recommendation.

Question 248

What does the sigmoid function do in logistic regression?

A. Maps a linear score to a probability
B. Scales features
C. Encodes categories
D. Imputes values

Answer 248

Correct: A — sigmoid maps scores to probabilities.

Wrong:

B, C, D are other steps.

Question 249

What is the decision threshold in binary classification?

A. The probability cutoff for predicting the positive class
B. The number of trees
C. The learning rate
D. The feature count

Answer 249

Correct: A — the threshold converts probabilities to labels.

Wrong:

B, C, D are unrelated.

Question 250

Why might you lower the decision threshold?

A. To increase recall

B. To increase precision

C. To reduce variance

D. To reduce training time

Answer 250

Correct: A — lowering the threshold usually raises recall.

Wrong:

B is the opposite tradeoff.

C, D are unrelated.

Question 251

What does a model's feature importance show?

A. Which features contribute most to predictions
B. The training time
C. The cluster size
D. The data size

Answer 251

Correct: A — importance shows feature contribution.

Wrong:

B, C, D are unrelated.

Question 252

Which model type supports feature importance in Spark ML?

A. Tree-based models

B. KMeans

C. ALS

D. PCA

Answer 252

Correct: A — tree models expose feature importance.

Wrong:

B, C, D do not expose importance.

Question 253

What is a partial dependence plot?

A. A plot showing the effect of one feature on predictions
B. A plot of feature importance
C. A plot of training error
D. A plot of validation error

Answer 253

Correct: A — partial dependence shows feature effects.

Wrong:

B, C, D are other plots.

Question 254

What is SHAP used for?

A. Explaining model predictions with feature attributions
B. Training models
C. Deploying models
D. Storing models

Answer 254

Correct: A — SHAP explains predictions.

Wrong:

B, C, D are not its purpose.

Question 255

What is LIME used for?

A. Local explanations of individual predictions

B. Global training

C. Model deployment

D. Data storage

Answer 255

Correct: A — LIME gives local explanations.

Wrong:

B, C, D are not its purpose.

Question 256

What is a confusion matrix used for?

A. Evaluating classification outcomes
B. Evaluating regression outcomes
C. Clustering
D. Dimensionality reduction

Answer 256

Correct: A — confusion matrices evaluate classifiers.

Wrong:

B, C, D use other methods.

Question 257

What does the `numTrees` parameter control in a random forest?

A. The number of trees in the forest

B. The tree depth

C. The learning rate

D. The number of features

Answer 257

Correct: A — `numTrees` sets tree count.

Wrong:

B is `maxDepth`.

C is `stepSize`.

D is `featureSubsetStrategy`.

Question 258

What does `maxBins` control in Spark ML trees?

A. The number of bins for continuous feature splits

B. The number of trees

C. The learning rate

D. The number of features

Answer 258

Correct: A — `maxBins` controls binning.

Wrong:

B is `numTrees`.

C is `stepSize`.

D is feature strategy.

Question 259

What does `stepSize` control in gradient boosted trees?

A. The learning rate
B. The number of trees
C. The tree depth
D. The number of features

Answer 259

Correct: A — `stepSize` is the learning rate.

Wrong:

B is `maxIter`.

C is `maxDepth`.

D is feature strategy.

Question 260

What does `subsamplingRate` control in gradient boosted trees?

A. The fraction of data used for each tree

B. The number of trees

C. The tree depth

D. The number of features

Answer 260

Correct: A — it controls per-tree data sampling.

Wrong:

B, C, D are other parameters.

Question 261

What does `featureSubsetStrategy` control in random forests?

A. How many features are considered per split

B. The number of trees

C. The tree depth

D. The learning rate

Answer 261

Correct: A — it controls features per split.

Wrong:

B, C, D are other parameters.

Question 262

What does `minInstancesPerNode` control?

A. The minimum number of rows required to split a node

B. The number of trees

C. The learning rate

D. The number of features

Answer 262

Correct: A — it sets the minimum rows per node.

Wrong:

B, C, D are other parameters.

Question 263

What is regularization in linear models?

A. A penalty on coefficient size to reduce overfitting

B. A way to add features

C. A way to remove rows

D. A clustering method

Answer 263

Correct: A — regularization penalizes coefficients.

Wrong:

B, C, D are false.

Question 264

What is the difference between L1 and L2 regularization?

A. L1 can zero out coefficients; L2 shrinks them

B. L2 zeros coefficients; L1 shrinks them

C. They are identical

D. Neither affects coefficients

Answer 264

Correct: A — L1 is sparse; L2 shrinks.

Wrong:

B is reversed.

C, D are false.

Question 265

What does `regParam` control in Spark ML linear models?

A. The regularization strength

B. The learning rate

C. The number of iterations

D. The number of features

Answer 265

Correct: A — `regParam` sets regularization.

Wrong:

B is `stepSize`.

C is `maxIter`.

D is feature count.

Question 266

What does `elasticNetParam` control?

A. The mix of L1 and L2 regularization

B. The number of trees

C. The number of iterations

D. The feature count

Answer 266

Correct: A — it controls the L1/L2 mix.

Wrong:

B, C, D are other parameters.

Question 267

What is a sparse vector in Spark ML?

A. A vector with mostly zero values

B. A vector with all nonzero values

C. A vector of strings

D. A vector of labels

Answer 267

Correct: A — sparse vectors are mostly zeros.

Wrong:

B is dense.

C, D are other data types.

Question 268

Why does one-hot encoding produce sparse vectors?

A. Most categories are zero for any given row

B. All values are nonzero

C. It encodes numeric data

D. It scales features

Answer 268

Correct: A — one-hot vectors are mostly zeros.

Wrong:

B, C, D are false.

Question 269

What does `VectorSlicer` do?

A. Selects a subset of features from a vector

B. Scales a vector

C. Encodes a vector

D. Imputes a vector

Answer 269

Correct: A — VectorSlicer selects features.

Wrong:

B, C, D are other transformers.

Question 270

What is the purpose of a `SQLTransformer`?

A. It applies a SQL query as a transformation

B. It trains a model

C. It registers a model

D. It deploys a model

Answer 270

Correct: A — SQLTransformer applies SQL.

Wrong:

B, C, D are false.

Question 271

What is a Delta table?

A. A table stored in Delta Lake with ACID transactions

B. A temporary view

C. A Python list

D. A model

Answer 271

Correct: A — Delta tables provide ACID storage.

Wrong:

B, C, D are not Delta tables.

Question 272

What is time travel in Delta Lake?

A. Querying previous versions of a table
B. Time-based clustering
C. A scheduling feature
D. A model type

Answer 272

Correct: A — time travel queries old versions.

Wrong:

B, C, D are false.

Question 273

What does `OPTIMIZE` do on a Delta table?

A. Compacts small files

B. Deletes the table

C. Adds a column

D. Changes the schema

Answer 273

Correct: A — OPTIMIZE compacts files.

Wrong:

B, C, D are false.

Question 274

What is `VACUUM` used for on a Delta table?

A. Removing old files not needed for time travel
B. Adding files
C. Compacting files
D. Changing the schema

Answer 274

Correct: A — VACUUM removes stale files.

Wrong:

B, C, D are false.

Question 275

Which Unity Catalog object contains schemas?

A. Catalog

B. Table

C. View

D. Volume

Answer 275

Correct: A — catalogs contain schemas.

Wrong:

B, C, D are lower-level objects.

Question 276

Which Unity Catalog object contains tables?

A. Schema

B. Catalog

C. Volume

D. Workspace

Answer 276

Correct: A — schemas contain tables.

Wrong:

B contains schemas.

C is for files.

D is not a UC object.

Question 277

What is a Unity Catalog volume used for?

A. Storing files under governance
B. Storing tables
C. Storing models
D. Storing functions

Answer 277

Correct: A — volumes store files.

Wrong:

B is tables.

C is models.

D is functions.

Question 278

Which privilege allows reading a table in Unity Catalog?

A. `SELECT`

B. `READ`

C. `VIEW`

D. `GET`

Answer 278

Correct: A — `SELECT` grants read access.

Wrong:

B, C, D are not the privilege names.

Question 279

Which privilege allows writing to a table in Unity Catalog?

A. `MODIFY`

B. `WRITE`

C. `INSERT`

D. `UPDATE`

Answer 279

Correct: A — `MODIFY` grants write access.

Wrong:

B, C, D are not the privilege names.

Question 280

What is a Databricks Job?

A. A scheduled or triggered workflow of tasks

B. A cluster

C. A notebook

D. A model

Answer 280

Correct: A — Jobs run tasks on a schedule or trigger.

Wrong:

B, C, D are not jobs.

Question 281

What is the difference between all-purpose and job clusters?

A. All-purpose clusters are interactive; job clusters are for automated jobs
B. They are identical
C. Job clusters are interactive
D. All-purpose clusters are only for SQL

Answer 281

Correct: A — interactive vs. job compute.

Wrong:

B, C, D are false.

Question 282

What does a Databricks Repo integrate with?

A. A Git provider

B. A SQL warehouse

C. A model registry

D. A feature store

Answer 282

Correct: A — Repos integrate with Git.

Wrong:

B, C, D are other services.

Question 283

Why use a Git branch for feature development in Databricks Repos?

A. To isolate changes from production code

B. To train faster

C. To save storage

D. To improve accuracy

Answer 283

Correct: A — branches isolate development.

Wrong:

B, C, D are false.

Question 284

What is the matrix view in a Databricks Job run used for?

A. Visualizing task statuses and failures
B. Training models
C. Registering models
D. Writing SQL

Answer 284

Correct: A — the matrix view shows task status.

Wrong:

B, C, D are unrelated.

Question 285

What is a notebook widget in Databricks?

A. A parameter input for a notebook

B. A model

C. A cluster

D. A table

Answer 285

Correct: A — widgets are notebook parameters.

Wrong:

B, C, D are not widgets.

Question 286

What does `dbutils.widgets.text()` do?

A. Creates a text input widget

B. Creates a cluster

C. Creates a table

D. Creates a model

Answer 286

Correct: A — it creates a text widget.

Wrong:

B, C, D are false.

Question 287

What does `dbutils.secrets.get()` do?

A. Retrieves a secret value securely

B. Creates a secret scope

C. Deletes a secret

D. Lists secrets

Answer 287

Correct: A — it retrieves a secret.

Wrong:

B, C, D are other secret operations.

Question 288

Why should secrets not be hard-coded in notebooks?

A. They can be exposed in version control and logs
B. They slow training
C. They reduce accuracy
D. They increase storage

Answer 288

Correct: A — hard-coded secrets leak.

Wrong:

B, C, D are false.

Question 289

Which serving endpoint type supports low-latency REST inference?

A. Real-time serving

B. Batch serving

C. Streaming serving

D. Notebook serving

Answer 289

Correct: A — real-time serving is low-latency REST.

Wrong:

B, C are other modes.

D is not a serving mode.

Question 290

What does a serving endpoint require to route to multiple model versions?

A. Traffic splitting configuration
B. A new cluster
C. A new table
D. A new notebook

Answer 290

Correct: A — traffic splitting enables multi-version routing.

Wrong:

B, C, D are unrelated.

Question 291

What is the purpose of authentication on a serving endpoint?

A. To control who can call the endpoint
B. To train the model
C. To store the model
D. To register the model

Answer 291

Correct: A — auth controls access.

Wrong:

B, C, D are unrelated.

Question 292

What is a batch inference job typically scheduled with?

A. A Databricks Job

B. A SQL warehouse

C. A notebook widget

D. A Repo

Answer 292

Correct: A — Jobs schedule batch inference.

Wrong:

B is SQL compute.

C is UI.

D is Git.

Question 293

What is the main risk of training on stale features?

A. The model learns patterns that do not hold in production

B. Training becomes faster

C. Accuracy always improves

D. Storage increases

Answer 293

Correct: A — stale features cause misalignment.

Wrong:

B, C, D are false.

Question 294

Why is feature lineage important?

A. It shows where features come from and how they were computed

B. It speeds training

C. It reduces storage

D. It improves accuracy

Answer 294

Correct: A — lineage tracks feature origin.

Wrong:

B, C, D are false.

Question 295

What is a model signature used for in serving?

A. Validating input and output schemas
B. Training the model
C. Registering the model
D. Deleting the model

Answer 295

Correct: A — signatures validate schemas.

Wrong:

B, C, D are unrelated.

Question 296

What is the purpose of a data quality check before training?

A. To catch missing, invalid, or drifted values
B. To speed training
C. To register models
D. To deploy models

Answer 296

Correct: A — quality checks catch bad data.

Wrong:

B, C, D are unrelated.

Question 297

Why is reproducibility important in ML?

A. It lets others verify and reproduce results
B. It speeds training
C. It reduces storage
D. It improves accuracy

Answer 297

Correct: A — reproducibility supports verification.

Wrong:

B, C, D are not the main reason.

Question 298

What is a model card?

A. A document describing a model's use, data, performance, and limitations

B. A model file

C. A cluster

D. A notebook

Answer 298

Correct: A — model cards document models.

Wrong:

B, C, D are not model cards.

Question 299

What is the purpose of monitoring feature drift in production?

A. To detect when input distributions change
B. To train the model
C. To register the model
D. To delete the model

Answer 299

Correct: A — drift monitoring detects input changes.

Wrong:

B, C, D are unrelated.

Question 300

What is the best practice for logging secrets in MLflow?

A. Never log secrets; use secret scopes

B. Log them as params

C. Log them as metrics

D. Log them as artifacts

Answer 300

Correct: A — secrets must not be logged.

Wrong:

B, C, D expose secrets.